

MySQL 5.7 Error Message Reference

Abstract

This is the MySQL 5.7 Error Message Reference. It lists all error messages produced by server and client programs in MySQL 5.7. This document accompanies [Error Messages and Common Problems](#), in [MySQL 5.7 Reference Manual](#).

For help with using MySQL, please visit the [MySQL Forums](#), where you can discuss your issues with other MySQL users.

Document generated on: 2025-07-02 (revision: 82696)

Table of Contents

Preface and Legal Notices	v
1 MySQL Error Reference	1
2 Server Error Message Reference	3
3 Client Error Message Reference	95
4 Global Error Message Reference	101
Index	105

Preface and Legal Notices

This is the MySQL 5.7 Error Message Reference. It lists all error messages produced by server and client programs in MySQL 5.7.

Legal Notices

Copyright © 1997, 2025, Oracle and/or its affiliates.

License Restrictions

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

Warranty Disclaimer

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

Restricted Rights Notice

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

Hazardous Applications Notice

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Trademark Notice

Oracle, Java, MySQL, and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC

International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

Third-Party Content, Products, and Services Disclaimer

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Use of This Documentation

This documentation is NOT distributed under a GPL license. Use of this documentation is subject to the following terms:

You may create a printed copy of this documentation solely for your own personal use. Conversion to other formats is allowed as long as the actual content is not altered or edited in any way. You shall not publish or distribute this documentation in any form or on any media, except if you distribute the documentation in a manner similar to how Oracle disseminates it (that is, electronically for download on a Web site with the software) or on a CD-ROM or similar medium, provided however that the documentation is disseminated together with the software on the same medium. Any other use, such as any dissemination of printed copies or use of this documentation, in whole or in part, in another publication, requires the prior written consent from an authorized representative of Oracle. Oracle and/or its affiliates reserve any and all rights to this documentation not expressly granted above.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at

<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support for Accessibility

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit

<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Chapter 1 MySQL Error Reference

This document provides a reference for the various types of error messages in MySQL:

- Error messages produced only by the server: [Chapter 2, Server Error Message Reference](#)

On the server side, error messages may occur during the startup and shutdown processes, as a result of issues that occur during SQL statement execution, and so forth.

- The MySQL server writes some error messages to its error log. These indicate issues of interest to database administrators or that require DBA action.
- The server sends other error messages to client programs. These indicate issues pertaining only to a particular client. The MySQL client library takes errors received from the server and makes them available to the host client program.
- Error messages that originate only from within the MySQL client library: [Chapter 3, Client Error Message Reference](#)

Client-side error messages are generated from within the MySQL client library, usually involving problems communicating with the server.

- Error messages that are shared between the server and the client library: [Chapter 4, Global Error Message Reference](#)

Some “global” error messages are shared in the sense that they can be produced by the MySQL server or by MySQL client programs.

For a description of the types of error information MySQL provides and how to obtain information about them, see [Error Messages and Common Problems](#), in [MySQL 5.7 Reference Manual](#).

Chapter 2 Server Error Message Reference

The MySQL server writes some error messages to its error log, and sends others to client programs.

Example server-side error messages written to the error log:

```
2018-09-26T14:46:06.326016Z 0 [Note] Skipping generation of SSL  
certificates as options related to SSL are specified.  
  
2018-10-02T03:20:39.410387Z 0 [ERROR] Plugin 'InnoDB'  
registration as a STORAGE ENGINE failed.
```

Example server-side error message sent to client programs, as displayed by the `mysql` client:

```
mysql> SELECT * FROM no_such_table;  
ERROR 1146 (42S02): Table 'test.no_such_table' doesn't exist
```

Each server error message includes an error code, SQLSTATE value, and message string, as described in [Error Message Sources and Elements](#). These elements are available as described in [Error Information Interfaces](#).

In addition to the errors in the following list, the server can also produce error messages that have error codes in the range from 1 to 999. See [Chapter 4, Global Error Message Reference](#)

- Error number: [1000](#); Symbol: [ER_HASHCHK](#); SQLSTATE: [HY000](#)

Message: hashchk

Unused.

- Error number: [1001](#); Symbol: [ER_NISAMCHK](#); SQLSTATE: [HY000](#)

Message: isamchk

Unused.

- Error number: [1002](#); Symbol: [ER_NO](#); SQLSTATE: [HY000](#)

Message: NO

Used in the construction of other messages.

- Error number: [1003](#); Symbol: [ER_YES](#); SQLSTATE: [HY000](#)

Message: YES

Used in the construction of other messages.

Extended `EXPLAIN` format generates Note messages. [ER_YES](#) is used in the `Code` column for these messages in subsequent `SHOW WARNINGS` output.

- Error number: [1004](#); Symbol: [ER_CANT_CREATE_FILE](#); SQLSTATE: [HY000](#)

Message: Can't create file '%s' (errno: %d - %s)

Occurs for failure to create or copy a file needed for some operation.

Possible causes: Permissions problem for source file; destination file already exists but is not writeable.

- Error number: [1005](#); Symbol: [ER_CANT_CREATE_TABLE](#); SQLSTATE: [HY000](#)

Message: Can't create table '%s' (errno: %d)

[InnoDB](#) reports this error when a table cannot be created. If the error message refers to error 150, table creation failed because a [foreign key constraint](#) was not correctly formed. If the error message refers to error -1, table creation probably failed because the table includes a column name that matched the name of an internal [InnoDB](#) table.

- Error number: [1006](#); Symbol: [ER_CANT_CREATE_DB](#); SQLSTATE: [HY000](#)

Message: Can't create database '%s' (errno: %d)
- Error number: [1007](#); Symbol: [ER_DB_CREATE_EXISTS](#); SQLSTATE: [HY000](#)

Message: Can't create database '%s'; database exists

An attempt to create a database failed because the database already exists.

Drop the database first if you really want to replace an existing database, or add an [IF NOT EXISTS](#) clause to the [CREATE DATABASE](#) statement if to retain an existing database without having the statement produce an error.
- Error number: [1008](#); Symbol: [ER_DB_DROP_EXISTS](#); SQLSTATE: [HY000](#)

Message: Can't drop database '%s'; database doesn't exist
- Error number: [1009](#); Symbol: [ER_DB_DROP_DELETE](#); SQLSTATE: [HY000](#)

Message: Error dropping database (can't delete '%s', errno: %d)
- Error number: [1010](#); Symbol: [ER_DB_DROP_RMDIR](#); SQLSTATE: [HY000](#)

Message: Error dropping database (can't rmdir '%s', errno: %d)
- Error number: [1011](#); Symbol: [ER_CANT_DELETE_FILE](#); SQLSTATE: [HY000](#)

Message: Error on delete of '%s' (errno: %d - %s)
- Error number: [1012](#); Symbol: [ER_CANT_FIND_SYSTEM_REC](#); SQLSTATE: [HY000](#)

Message: Can't read record in system table

Returned by [InnoDB](#) for attempts to access [InnoDB INFORMATION_SCHEMA](#) tables when [InnoDB](#) is unavailable.
- Error number: [1013](#); Symbol: [ER_CANT_GET_STAT](#); SQLSTATE: [HY000](#)

Message: Can't get status of '%s' (errno: %d - %s)
- Error number: [1014](#); Symbol: [ER_CANT_GET_WD](#); SQLSTATE: [HY000](#)

Message: Can't get working directory (errno: %d - %s)
- Error number: [1015](#); Symbol: [ER_CANT_LOCK](#); SQLSTATE: [HY000](#)

Message: Can't lock file (errno: %d - %s)
- Error number: [1016](#); Symbol: [ER_CANT_OPEN_FILE](#); SQLSTATE: [HY000](#)

Message: Can't open file: '%s' (errno: %d - %s)

[InnoDB](#) reports this error when the table from the [InnoDB data files](#) cannot be found, even though the [.frm](#) file for the table exists. See [Troubleshooting InnoDB Data Dictionary Operations](#).
- Error number: [1017](#); Symbol: [ER_FILE_NOT_FOUND](#); SQLSTATE: [HY000](#)

-
- Message: Can't find file: '%s' (errno: %d - %s)
 - Error number: [1018](#); Symbol: [ER_CANT_READ_DIR](#); SQLSTATE: [HY000](#)
Message: Can't read dir of '%s' (errno: %d - %s)
 - Error number: [1019](#); Symbol: [ER_CANT_SET_WD](#); SQLSTATE: [HY000](#)
Message: Can't change dir to '%s' (errno: %d - %s)
 - Error number: [1020](#); Symbol: [ER_CHECKREAD](#); SQLSTATE: [HY000](#)
Message: Record has changed since last read in table '%s'
 - Error number: [1021](#); Symbol: [ER_DISK_FULL](#); SQLSTATE: [HY000](#)
Message: Disk full (%s); waiting for someone to free some space... (errno: %d - %s)
 - Error number: [1022](#); Symbol: [ER_DUP_KEY](#); SQLSTATE: [23000](#)
Message: Can't write; duplicate key in table '%s'
 - Error number: [1023](#); Symbol: [ER_ERROR_ON_CLOSE](#); SQLSTATE: [HY000](#)
Message: Error on close of '%s' (errno: %d - %s)
 - Error number: [1024](#); Symbol: [ER_ERROR_ON_READ](#); SQLSTATE: [HY000](#)
Message: Error reading file '%s' (errno: %d - %s)
 - Error number: [1025](#); Symbol: [ER_ERROR_ON_RENAME](#); SQLSTATE: [HY000](#)
Message: Error on rename of '%s' to '%s' (errno: %d - %s)
 - Error number: [1026](#); Symbol: [ER_ERROR_ON_WRITE](#); SQLSTATE: [HY000](#)
Message: Error writing file '%s' (errno: %d - %s)
 - Error number: [1027](#); Symbol: [ER_FILE_USED](#); SQLSTATE: [HY000](#)
Message: '%s' is locked against change
 - Error number: [1028](#); Symbol: [ER_FILSORT_ABORT](#); SQLSTATE: [HY000](#)
Message: Sort aborted
 - Error number: [1029](#); Symbol: [ER_FORM_NOT_FOUND](#); SQLSTATE: [HY000](#)
Message: View '%s' doesn't exist for '%s'
 - Error number: [1030](#); Symbol: [ER_GET_ERRNO](#); SQLSTATE: [HY000](#)
Message: Got error %d from storage engine
Check the `%d` value to see what the OS error means. For example, 28 indicates that you have run out of disk space.
 - Error number: [1031](#); Symbol: [ER_ILLEGAL_HA](#); SQLSTATE: [HY000](#)
Message: Table storage engine for '%s' doesn't have this option
 - Error number: [1032](#); Symbol: [ER_KEY_NOT_FOUND](#); SQLSTATE: [HY000](#)
Message: Can't find record in '%s'

-
- Error number: [1033](#); Symbol: [ER_NOT_FORM_FILE](#); SQLSTATE: [HY000](#)
Message: Incorrect information in file: '%s'
 - Error number: [1034](#); Symbol: [ER_NOT_KEYFILE](#); SQLSTATE: [HY000](#)
Message: Incorrect key file for table '%s'; try to repair it
 - Error number: [1035](#); Symbol: [ER_OLD_KEYFILE](#); SQLSTATE: [HY000](#)
Message: Old key file for table '%s'; repair it!
 - Error number: [1036](#); Symbol: [ER_OPEN_AS_READONLY](#); SQLSTATE: [HY000](#)
Message: Table '%s' is read only
 - Error number: [1037](#); Symbol: [ER_OUTOFMEMORY](#); SQLSTATE: [HY001](#)
Message: Out of memory; restart server and try again (needed %d bytes)
 - Error number: [1038](#); Symbol: [ER_OUT_OF_SORTMEMORY](#); SQLSTATE: [HY001](#)
Message: Out of sort memory, consider increasing server sort buffer size
 - Error number: [1039](#); Symbol: [ER_UNEXPECTED_EOF](#); SQLSTATE: [HY000](#)
Message: Unexpected EOF found when reading file '%s' (errno: %d - %s)
 - Error number: [1040](#); Symbol: [ER_CON_COUNT_ERROR](#); SQLSTATE: [08004](#)
Message: Too many connections
 - Error number: [1041](#); Symbol: [ER_OUT_OF_RESOURCES](#); SQLSTATE: [HY000](#)
Message: Out of memory; check if mysqld or some other process uses all available memory; if not, you may have to use 'ulimit' to allow mysqld to use more memory or you can add more swap space
 - Error number: [1042](#); Symbol: [ER_BAD_HOST_ERROR](#); SQLSTATE: [08S01](#)
Message: Can't get hostname for your address
 - Error number: [1043](#); Symbol: [ER_HANDSHAKE_ERROR](#); SQLSTATE: [08S01](#)
Message: Bad handshake
 - Error number: [1044](#); Symbol: [ER_DBACCESS_DENIED_ERROR](#); SQLSTATE: [42000](#)
Message: Access denied for user '%s'@'%s' to database '%s'
 - Error number: [1045](#); Symbol: [ER_ACCESS_DENIED_ERROR](#); SQLSTATE: [28000](#)
Message: Access denied for user '%s'@'%s' (using password: %s)
 - Error number: [1046](#); Symbol: [ER_NO_DB_ERROR](#); SQLSTATE: [3D000](#)
Message: No database selected
 - Error number: [1047](#); Symbol: [ER_UNKNOWN_COM_ERROR](#); SQLSTATE: [08S01](#)
Message: Unknown command
 - Error number: [1048](#); Symbol: [ER_BAD_NULL_ERROR](#); SQLSTATE: [23000](#)
Message: Column '%s' cannot be null

- Error number: 1049; Symbol: ER_BAD_DB_ERROR; SQLSTATE: 42000
Message: Unknown database '%s'
- Error number: 1050; Symbol: ER_TABLE_EXISTS_ERROR; SQLSTATE: 42S01
Message: Table '%s' already exists
- Error number: 1051; Symbol: ER_BAD_TABLE_ERROR; SQLSTATE: 42S02
Message: Unknown table '%s'
- Error number: 1052; Symbol: ER_NON_UNIQ_ERROR; SQLSTATE: 23000
Message: Column '%s' in %s is ambiguous

```
%s = column name  
%s = location of column (for example, "field list")
```

Likely cause: A column appears in a query without appropriate qualification, such as in a select list or ON clause.

Examples:

```
mysql> SELECT i FROM t INNER JOIN t AS t2;  
ERROR 1052 (23000): Column 'i' in field list is ambiguous  
  
mysql> SELECT * FROM t LEFT JOIN t AS t2 ON i = i;  
ERROR 1052 (23000): Column 'i' in on clause is ambiguous
```

Resolution:

- Qualify the column with the appropriate table name:

```
mysql> SELECT t2.i FROM t INNER JOIN t AS t2;
```

- Modify the query to avoid the need for qualification:

```
mysql> SELECT * FROM t LEFT JOIN t AS t2 USING (i);
```

- Error number: 1053; Symbol: ER_SERVER_SHUTDOWN; SQLSTATE: 08S01

Message: Server shutdown in progress

- Error number: 1054; Symbol: ER_BAD_FIELD_ERROR; SQLSTATE: 42S22

Message: Unknown column '%s' in '%s'

- Error number: 1055; Symbol: ER_WRONG_FIELD_WITH_GROUP; SQLSTATE: 42000

Message: '%s' isn't in GROUP BY

- Error number: 1056; Symbol: ER_WRONG_GROUP_FIELD; SQLSTATE: 42000

Message: Can't group on '%s'

- Error number: 1057; Symbol: ER_WRONG_SUM_SELECT; SQLSTATE: 42000

Message: Statement has sum functions and columns in same statement

- Error number: 1058; Symbol: ER_WRONG_VALUE_COUNT; SQLSTATE: 21S01

Message: Column count doesn't match value count

- Error number: 1059; Symbol: ER_TOO_LONG_IDENT; SQLSTATE: 42000

Message: Identifier name '%s' is too long

- Error number: [1060](#); Symbol: [ER_DUP_FIELDNAME](#); SQLSTATE: [42S21](#)

Message: Duplicate column name '%s'

- Error number: [1061](#); Symbol: [ER_DUP_KEYNAME](#); SQLSTATE: [42000](#)

Message: Duplicate key name '%s'

- Error number: [1062](#); Symbol: [ER_DUP_ENTRY](#); SQLSTATE: [23000](#)

Message: Duplicate entry '%s' for key %d

The message returned with this error uses the format string for [ER_DUP_ENTRY_WITH_KEY_NAME](#).

- Error number: [1063](#); Symbol: [ER_WRONG_FIELD_SPEC](#); SQLSTATE: [42000](#)

Message: Incorrect column specifier for column '%s'

- Error number: [1064](#); Symbol: [ER_PARSE_ERROR](#); SQLSTATE: [42000](#)

Message: %s near '%s' at line %d

- Error number: [1065](#); Symbol: [ER_EMPTY_QUERY](#); SQLSTATE: [42000](#)

Message: Query was empty

- Error number: [1066](#); Symbol: [ER_NONUNIQ_TABLE](#); SQLSTATE: [42000](#)

Message: Not unique table/alias: '%s'

- Error number: [1067](#); Symbol: [ER_INVALID_DEFAULT](#); SQLSTATE: [42000](#)

Message: Invalid default value for '%s'

- Error number: [1068](#); Symbol: [ER_MULTIPLE_PRI_KEY](#); SQLSTATE: [42000](#)

Message: Multiple primary key defined

- Error number: [1069](#); Symbol: [ER_TOO_MANY_KEYS](#); SQLSTATE: [42000](#)

Message: Too many keys specified; max %d keys allowed

- Error number: [1070](#); Symbol: [ER_TOO_MANY_KEY_PARTS](#); SQLSTATE: [42000](#)

Message: Too many key parts specified; max %d parts allowed

- Error number: [1071](#); Symbol: [ER_TOO_LONG_KEY](#); SQLSTATE: [42000](#)

Message: Specified key was too long; max key length is %d bytes

- Error number: [1072](#); Symbol: [ER_KEY_COLUMN_DOES_NOT_EXISTS](#); SQLSTATE: [42000](#)

Message: Key column '%s' doesn't exist in table

- Error number: [1073](#); Symbol: [ER_BLOB_USED_AS_KEY](#); SQLSTATE: [42000](#)

Message: BLOB column '%s' can't be used in key specification with the used table type

- Error number: [1074](#); Symbol: [ER_TOO_BIG_FIELDLENGTH](#); SQLSTATE: [42000](#)

Message: Column length too big for column '%s' (max = %lu); use BLOB or TEXT instead

-
- Error number: [1075](#); Symbol: [ER_WRONG_AUTO_KEY](#); SQLSTATE: [42000](#)

Message: Incorrect table definition; there can be only one auto column and it must be defined as a key
 - Error number: [1076](#); Symbol: [ER_READY](#); SQLSTATE: [HY000](#)

Message: %s: ready for connections. Version: '%s' socket: '%s' port: %d
 - Error number: [1077](#); Symbol: [ER_NORMAL_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: %s: Normal shutdown
 - Error number: [1078](#); Symbol: [ER_GOT_SIGNAL](#); SQLSTATE: [HY000](#)

Message: %s: Got signal %d. Aborting!
 - Error number: [1079](#); Symbol: [ER_SHUTDOWN_COMPLETE](#); SQLSTATE: [HY000](#)

Message: %s: Shutdown complete
 - Error number: [1080](#); Symbol: [ER_FORCING_CLOSE](#); SQLSTATE: [08S01](#)

Message: %s: Forcing close of thread %ld user: '%s'
 - Error number: [1081](#); Symbol: [ER_IPSOCK_ERROR](#); SQLSTATE: [08S01](#)

Message: Can't create IP socket
 - Error number: [1082](#); Symbol: [ER_NO_SUCH_INDEX](#); SQLSTATE: [42S12](#)

Message: Table '%s' has no index like the one used in CREATE INDEX; recreate the table
 - Error number: [1083](#); Symbol: [ER_WRONG_FIELD_TERMINATORS](#); SQLSTATE: [42000](#)

Message: Field separator argument is not what is expected; check the manual
 - Error number: [1084](#); Symbol: [ER_BLOBS_AND_NO_TERMINATED](#); SQLSTATE: [42000](#)

Message: You can't use fixed rowlength with BLOBs; please use 'fields terminated by'
 - Error number: [1085](#); Symbol: [ER_TEXTFILE_NOT_READABLE](#); SQLSTATE: [HY000](#)

Message: The file '%s' must be in the database directory or be readable by all
 - Error number: [1086](#); Symbol: [ER_FILE_EXISTS_ERROR](#); SQLSTATE: [HY000](#)

Message: File '%s' already exists
 - Error number: [1087](#); Symbol: [ER_LOAD_INFO](#); SQLSTATE: [HY000](#)

Message: Records: %ld Deleted: %ld Skipped: %ld Warnings: %ld
 - Error number: [1088](#); Symbol: [ER_ALTER_INFO](#); SQLSTATE: [HY000](#)

Message: Records: %ld Duplicates: %ld
 - Error number: [1089](#); Symbol: [ER_WRONG_SUB_KEY](#); SQLSTATE: [HY000](#)

Message: Incorrect prefix key; the used key part isn't a string, the used length is longer than the key part, or the storage engine doesn't support unique prefix keys
 - Error number: [1090](#); Symbol: [ER_CANT_REMOVE_ALL_FIELDS](#); SQLSTATE: [42000](#)

Message: You can't delete all columns with ALTER TABLE; use DROP TABLE instead

- Error number: [1091](#); Symbol: [ER_CANT_DROP_FIELD_OR_KEY](#); SQLSTATE: [42000](#)

Message: Can't DROP '%s'; check that column/key exists
- Error number: [1092](#); Symbol: [ER_INSERT_INFO](#); SQLSTATE: [HY000](#)

Message: Records: %ld Duplicates: %ld Warnings: %ld
- Error number: [1093](#); Symbol: [ER_UPDATE_TABLE_USED](#); SQLSTATE: [HY000](#)

Message: You can't specify target table '%s' for update in FROM clause

This error occurs for attempts to select from and modify the same table within a single statement. If the select attempt occurs within a derived table, you can avoid this error by setting the [derived_merge](#) flag of the [optimizer_switch](#) system variable to force the subquery to be materialized into a temporary table, which effectively causes it to be a different table from the one modified. See [Optimizing Derived Tables and View References with Merging or Materialization](#).
- Error number: [1094](#); Symbol: [ER_NO SUCH THREAD](#); SQLSTATE: [HY000](#)

Message: Unknown thread id: %lu
- Error number: [1095](#); Symbol: [ER_KILL_DENIED_ERROR](#); SQLSTATE: [HY000](#)

Message: You are not owner of thread %lu
- Error number: [1096](#); Symbol: [ER_NO_TABLES_USED](#); SQLSTATE: [HY000](#)

Message: No tables used
- Error number: [1097](#); Symbol: [ER_TOO_BIG_SET](#); SQLSTATE: [HY000](#)

Message: Too many strings for column %s and SET
- Error number: [1098](#); Symbol: [ER_NO_UNIQUE_LOGFILE](#); SQLSTATE: [HY000](#)

Message: Can't generate a unique log-filename %s.(1-999)
- Error number: [1099](#); Symbol: [ER_TABLE_NOT_LOCKED_FOR_WRITE](#); SQLSTATE: [HY000](#)

Message: Table '%s' was locked with a READ lock and can't be updated
- Error number: [1100](#); Symbol: [ER_TABLE_NOT_LOCKED](#); SQLSTATE: [HY000](#)

Message: Table '%s' was not locked with LOCK TABLES
- Error number: [1101](#); Symbol: [ER_BLOB_CANT_HAVE_DEFAULT](#); SQLSTATE: [42000](#)

Message: BLOB, TEXT, GEOMETRY or JSON column '%s' can't have a default value
- Error number: [1102](#); Symbol: [ER_WRONG_DB_NAME](#); SQLSTATE: [42000](#)

Message: Incorrect database name '%s'
- Error number: [1103](#); Symbol: [ER_WRONG_TABLE_NAME](#); SQLSTATE: [42000](#)

Message: Incorrect table name '%s'
- Error number: [1104](#); Symbol: [ER_TOO_BIG_SELECT](#); SQLSTATE: [42000](#)

Message: The SELECT would examine more than MAX_JOIN_SIZE rows; check your WHERE and use SET SQL_BIG_SELECTS=1 or SET MAX_JOIN_SIZE=# if the SELECT is okay
- Error number: [1105](#); Symbol: [ER_UNKNOWN_ERROR](#); SQLSTATE: [HY000](#)

Message: Unknown error

- Error number: [1106](#); Symbol: [ER_UNKNOWN_PROCEDURE](#); SQLSTATE: [42000](#)

Message: Unknown procedure '%s'

- Error number: [1107](#); Symbol: [ER_WRONG_PARAMCOUNT_TO_PROCEDURE](#); SQLSTATE: [42000](#)

Message: Incorrect parameter count to procedure '%s'

- Error number: [1108](#); Symbol: [ER_WRONG_PARAMETERS_TO_PROCEDURE](#); SQLSTATE: [HY000](#)

Message: Incorrect parameters to procedure '%s'

- Error number: [1109](#); Symbol: [ER_UNKNOWN_TABLE](#); SQLSTATE: [42S02](#)

Message: Unknown table '%s' in %s

- Error number: [1110](#); Symbol: [ER_FIELD_SPECIFIED_TWICE](#); SQLSTATE: [42000](#)

Message: Column '%s' specified twice

- Error number: [1111](#); Symbol: [ER_INVALID_GROUP_FUNC_USE](#); SQLSTATE: [HY000](#)

Message: Invalid use of group function

- Error number: [1112](#); Symbol: [ER_UNSUPPORTED_EXTENSION](#); SQLSTATE: [42000](#)

Message: Table '%s' uses an extension that doesn't exist in this MySQL version

- Error number: [1113](#); Symbol: [ER_TABLE_MUST_HAVE_COLUMNS](#); SQLSTATE: [42000](#)

Message: A table must have at least 1 column

- Error number: [1114](#); Symbol: [ER_RECORD_FILE_FULL](#); SQLSTATE: [HY000](#)

Message: The table '%s' is full

[InnoDB](#) reports this error when the system tablespace runs out of free space. Reconfigure the system tablespace to add a new data file.

- Error number: [1115](#); Symbol: [ER_UNKNOWN_CHARACTER_SET](#); SQLSTATE: [42000](#)

Message: Unknown character set: '%s'

- Error number: [1116](#); Symbol: [ER_TOO_MANY_TABLES](#); SQLSTATE: [HY000](#)

Message: Too many tables; MySQL can only use %d tables in a join

- Error number: [1117](#); Symbol: [ER_TOO_MANY_FIELDS](#); SQLSTATE: [HY000](#)

Message: Too many columns

- Error number: [1118](#); Symbol: [ER_TOO_BIG_ROWSIZE](#); SQLSTATE: [42000](#)

Message: Row size too large. The maximum row size for the used table type, not counting BLOBs, is %ld. This includes storage overhead, check the manual. You have to change some columns to TEXT or BLOBs

- Error number: [1119](#); Symbol: [ER_STACK_OVERRUN](#); SQLSTATE: [HY000](#)

Message: Thread stack overrun: Used: %ld of a %ld stack. Use 'mysqld --thread_stack=#' to specify a bigger stack if needed

- Error number: [1120](#); Symbol: [ER_WRONG_OUTER_JOIN](#); SQLSTATE: [42000](#)

Message: Cross dependency found in OUTER JOIN; examine your ON conditions
- Error number: [1121](#); Symbol: [ER_NULL_COLUMN_IN_INDEX](#); SQLSTATE: [42000](#)

Message: Table handler doesn't support NULL in given index. Please change column '%s' to be NOT NULL or use another handler
- Error number: [1122](#); Symbol: [ER_CANT_FIND_UDF](#); SQLSTATE: [HY000](#)

Message: Can't load function '%s'
- Error number: [1123](#); Symbol: [ER_CANT_INITIALIZE_UDF](#); SQLSTATE: [HY000](#)

Message: Can't initialize function '%s'; %s
- Error number: [1124](#); Symbol: [ER_UDF_NO_PATHS](#); SQLSTATE: [HY000](#)

Message: No paths allowed for shared library
- Error number: [1125](#); Symbol: [ER_UDF_EXISTS](#); SQLSTATE: [HY000](#)

Message: Function '%s' already exists
- Error number: [1126](#); Symbol: [ER_CANT_OPEN_LIBRARY](#); SQLSTATE: [HY000](#)

Message: Can't open shared library '%s' (errno: %d %s)
- Error number: [1127](#); Symbol: [ER_CANT_FIND_DL_ENTRY](#); SQLSTATE: [HY000](#)

Message: Can't find symbol '%s' in library
- Error number: [1128](#); Symbol: [ER_FUNCTION_NOT_DEFINED](#); SQLSTATE: [HY000](#)

Message: Function '%s' is not defined
- Error number: [1129](#); Symbol: [ER_HOST_IS_BLOCKED](#); SQLSTATE: [HY000](#)

Message: Host '%s' is blocked because of many connection errors; unblock with 'mysqladmin flush-hosts'
- Error number: [1130](#); Symbol: [ER_HOST_NOT_PRIVILEGED](#); SQLSTATE: [HY000](#)

Message: Host '%s' is not allowed to connect to this MySQL server
- Error number: [1131](#); Symbol: [ER_PASSWORD_ANONYMOUS_USER](#); SQLSTATE: [42000](#)

Message: You are using MySQL as an anonymous user and anonymous users are not allowed to change passwords
- Error number: [1132](#); Symbol: [ER_PASSWORD_NOT_ALLOWED](#); SQLSTATE: [42000](#)

Message: You must have privileges to update tables in the mysql database to be able to change passwords for others
- Error number: [1133](#); Symbol: [ER_PASSWORD_NO_MATCH](#); SQLSTATE: [42000](#)

Message: Can't find any matching row in the user table
- Error number: [1134](#); Symbol: [ER_UPDATE_INFO](#); SQLSTATE: [HY000](#)

Message: Rows matched: %ld Changed: %ld Warnings: %ld

-
- Error number: [1135](#); Symbol: [ER_CANT_CREATE_THREAD](#); SQLSTATE: [HY000](#)
Message: Can't create a new thread (errno %d); if you are not out of available memory, you can consult the manual for a possible OS-dependent bug
 - Error number: [1136](#); Symbol: [ER_WRONG_VALUE_COUNT_ON_ROW](#); SQLSTATE: [21S01](#)
Message: Column count doesn't match value count at row %d
 - Error number: [1137](#); Symbol: [ER_CANT_REOPEN_TABLE](#); SQLSTATE: [HY000](#)
Message: Can't reopen table: '%s'
 - Error number: [1138](#); Symbol: [ER_INVALID_USE_OF_NULL](#); SQLSTATE: [22004](#)
Message: Invalid use of NULL value
 - Error number: [1139](#); Symbol: [ER_REGEXP_ERROR](#); SQLSTATE: [42000](#)
Message: Got error '%s' from regexp
 - Error number: [1140](#); Symbol: [ER_MIX_OF_GROUP_FUNC_AND_FIELDS](#); SQLSTATE: [42000](#)
Message: Mixing of GROUP columns (MIN(),MAX(),COUNT(),...) with no GROUP columns is illegal if there is no GROUP BY clause
 - Error number: [1141](#); Symbol: [ER_NONEXISTING_GRANT](#); SQLSTATE: [42000](#)
Message: There is no such grant defined for user '%s' on host '%s'
 - Error number: [1142](#); Symbol: [ER_TABLEACCESS_DENIED_ERROR](#); SQLSTATE: [42000](#)
Message: %s command denied to user '%s'@'%s' for table '%s'
 - Error number: [1143](#); Symbol: [ER_COLUMNACCESS_DENIED_ERROR](#); SQLSTATE: [42000](#)
Message: %s command denied to user '%s'@'%s' for column '%s' in table '%s'
 - Error number: [1144](#); Symbol: [ER_ILLEGAL_GRANT_FOR_TABLE](#); SQLSTATE: [42000](#)
Message: Illegal GRANT/REVOKE command; please consult the manual to see which privileges can be used
 - Error number: [1145](#); Symbol: [ER_GRANT_WRONG_HOST_OR_USER](#); SQLSTATE: [42000](#)
Message: The host or user argument to GRANT is too long
 - Error number: [1146](#); Symbol: [ER_NO_SUCH_TABLE](#); SQLSTATE: [42S02](#)
Message: Table '%s.%s' doesn't exist
 - Error number: [1147](#); Symbol: [ER_NONEXISTING_TABLE_GRANT](#); SQLSTATE: [42000](#)
Message: There is no such grant defined for user '%s' on host '%s' on table '%s'
 - Error number: [1148](#); Symbol: [ER_NOT_ALLOWED_COMMAND](#); SQLSTATE: [42000](#)
Message: The used command is not allowed with this MySQL version
 - Error number: [1149](#); Symbol: [ER_SYNTAX_ERROR](#); SQLSTATE: [42000](#)
Message: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use
 - Error number: [1150](#); Symbol: [ER_UNUSED1](#); SQLSTATE: [HY000](#)

Message: Delayed insert thread couldn't get requested lock for table %s

- Error number: 1151; Symbol: ER_UNUSED2; SQLSTATE: HY000

Message: Too many delayed threads in use

- Error number: 1152; Symbol: ER_ABORTING_CONNECTION; SQLSTATE: 08S01

Message: Aborted connection %d to db: '%s' user: '%s' (%s)

- Error number: 1153; Symbol: ER_NET_PACKET_TOO_LARGE; SQLSTATE: 08S01

Message: Got a packet bigger than 'max_allowed_packet' bytes

- Error number: 1154; Symbol: ER_NET_READ_ERROR_FROM_PIPE; SQLSTATE: 08S01

Message: Got a read error from the connection pipe

- Error number: 1155; Symbol: ER_NET_FCNTL_ERROR; SQLSTATE: 08S01

Message: Got an error from fcntl()

- Error number: 1156; Symbol: ER_NET_PACKETS_OUT_OF_ORDER; SQLSTATE: 08S01

Message: Got packets out of order

- Error number: 1157; Symbol: ER_NET_UNCOMPRESS_ERROR; SQLSTATE: 08S01

Message: Couldn't uncompress communication packet

- Error number: 1158; Symbol: ER_NET_READ_ERROR; SQLSTATE: 08S01

Message: Got an error reading communication packets

- Error number: 1159; Symbol: ER_NET_READ_INTERRUPTED; SQLSTATE: 08S01

Message: Got timeout reading communication packets

- Error number: 1160; Symbol: ER_NET_ERROR_ON_WRITE; SQLSTATE: 08S01

Message: Got an error writing communication packets

- Error number: 1161; Symbol: ER_NET_WRITE_INTERRUPTED; SQLSTATE: 08S01

Message: Got timeout writing communication packets

- Error number: 1162; Symbol: ER_TOO_LONG_STRING; SQLSTATE: 42000

Message: Result string is longer than 'max_allowed_packet' bytes

- Error number: 1163; Symbol: ER_TABLE_CANT_HANDLE_BLOB; SQLSTATE: 42000

Message: The used table type doesn't support BLOB/TEXT columns

- Error number: 1164; Symbol: ER_TABLE_CANT_HANDLE_AUTO_INCREMENT; SQLSTATE: 42000

Message: The used table type doesn't support AUTO_INCREMENT columns

- Error number: 1165; Symbol: ER_UNUSED3; SQLSTATE: HY000

Message: INSERT DELAYED can't be used with table '%s' because it is locked with LOCK TABLES

- Error number: 1166; Symbol: ER_WRONG_COLUMN_NAME; SQLSTATE: 42000

Message: Incorrect column name '%s'

-
- Error number: [1167](#); Symbol: [ER_WRONG_KEY_COLUMN](#); SQLSTATE: [42000](#)
Message: The used storage engine can't index column '%s'
 - Error number: [1168](#); Symbol: [ER_WRONG_MRG_TABLE](#); SQLSTATE: [HY000](#)
Message: Unable to open underlying table which is differently defined or of non-MyISAM type or doesn't exist
 - Error number: [1169](#); Symbol: [ER_DUP_UNIQUE](#); SQLSTATE: [23000](#)
Message: Can't write, because of unique constraint, to table '%s'
 - Error number: [1170](#); Symbol: [ER_BLOB_KEY_WITHOUT_LENGTH](#); SQLSTATE: [42000](#)
Message: BLOB/TEXT column '%s' used in key specification without a key length
 - Error number: [1171](#); Symbol: [ER_PRIMARY_CANT_HAVE_NULL](#); SQLSTATE: [42000](#)
Message: All parts of a PRIMARY KEY must be NOT NULL; if you need NULL in a key, use UNIQUE instead
 - Error number: [1172](#); Symbol: [ER_TOO_MANY_ROWS](#); SQLSTATE: [42000](#)
Message: Result consisted of more than one row
 - Error number: [1173](#); Symbol: [ER_REQUIRES_PRIMARY_KEY](#); SQLSTATE: [42000](#)
Message: This table type requires a primary key
 - Error number: [1174](#); Symbol: [ER_NO_RAID_COMPILED](#); SQLSTATE: [HY000](#)
Message: This version of MySQL is not compiled with RAID support
 - Error number: [1175](#); Symbol: [ER_UPDATE_WITHOUT_KEY_IN_SAFE_MODE](#); SQLSTATE: [HY000](#)
Message: You are using safe update mode and you tried to update a table without a WHERE that uses a KEY column. %s
 - Error number: [1176](#); Symbol: [ER_KEY_DOES_NOT_EXISTS](#); SQLSTATE: [42000](#)
Message: Key '%s' doesn't exist in table '%s'
 - Error number: [1177](#); Symbol: [ER_CHECK_NO SUCH_TABLE](#); SQLSTATE: [42000](#)
Message: Can't open table
 - Error number: [1178](#); Symbol: [ER_CHECK_NOT_IMPLEMENTED](#); SQLSTATE: [42000](#)
Message: The storage engine for the table doesn't support %s
 - Error number: [1179](#); Symbol: [ER_CANT_DO_THIS_DURING_AN_TRANSACTION](#); SQLSTATE: [25000](#)
Message: You are not allowed to execute this command in a transaction
 - Error number: [1180](#); Symbol: [ER_ERROR_DURING_COMMIT](#); SQLSTATE: [HY000](#)
Message: Got error %d during COMMIT
 - Error number: [1181](#); Symbol: [ER_ERROR_DURING_ROLLBACK](#); SQLSTATE: [HY000](#)
Message: Got error %d during ROLLBACK

- Error number: 1182; Symbol: [ER_ERROR_DURING_FLUSH_LOGS](#); SQLSTATE: HY000
Message: Got error %d during FLUSH_LOGS
- Error number: 1183; Symbol: [ER_ERROR_DURING_CHECKPOINT](#); SQLSTATE: HY000
Message: Got error %d during CHECKPOINT
- Error number: 1184; Symbol: [ER_NEW_ABORTING_CONNECTION](#); SQLSTATE: 08S01
Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s)
- Error number: 1185; Symbol: [ER_DUMP_NOT_IMPLEMENTED](#); SQLSTATE: HY000
Message: The storage engine for the table does not support binary table dump
- Error number: 1186; Symbol: [ER_FLUSH_MASTER_BINLOG_CLOSED](#); SQLSTATE: HY000
Message: Binlog closed, cannot RESET MASTER
- Error number: 1187; Symbol: [ER_INDEX_REBUILD](#); SQLSTATE: HY000
Message: Failed rebuilding the index of dumped table '%s'
- Error number: 1188; Symbol: [ER_MASTER](#); SQLSTATE: HY000
Message: Error from master: '%s'
- Error number: 1189; Symbol: [ER_MASTER_NET_READ](#); SQLSTATE: 08S01
Message: Net error reading from master
- Error number: 1190; Symbol: [ER_MASTER_NET_WRITE](#); SQLSTATE: 08S01
Message: Net error writing to master
- Error number: 1191; Symbol: [ER_FT_MATCHING_KEY_NOT_FOUND](#); SQLSTATE: HY000
Message: Can't find FULLTEXT index matching the column list
- Error number: 1192; Symbol: [ER_LOCK_OR_ACTIVE_TRANSACTION](#); SQLSTATE: HY000
Message: Can't execute the given command because you have active locked tables or an active transaction
- Error number: 1193; Symbol: [ER_UNKNOWN_SYSTEM_VARIABLE](#); SQLSTATE: HY000
Message: Unknown system variable '%s'
- Error number: 1194; Symbol: [ER_CRASHED_ON_USAGE](#); SQLSTATE: HY000
Message: Table '%s' is marked as crashed and should be repaired
- Error number: 1195; Symbol: [ER_CRASHED_ON_REPAIR](#); SQLSTATE: HY000
Message: Table '%s' is marked as crashed and last (automatic?) repair failed
- Error number: 1196; Symbol: [ER_WARNING_NOT_COMPLETE_ROLLBACK](#); SQLSTATE: HY000
Message: Some non-transactional changed tables couldn't be rolled back
- Error number: 1197; Symbol: [ER_TRANS_CACHE_FULL](#); SQLSTATE: HY000
Message: Multi-statement transaction required more than 'max_binlog_cache_size' bytes of storage; increase this mysqld variable and try again

- Error number: [1198](#); Symbol: [ER_SLAVE_MUST_STOP](#); SQLSTATE: [HY000](#)

Message: This operation cannot be performed with a running slave; run STOP SLAVE first
- Error number: [1199](#); Symbol: [ER_SLAVE_NOT_RUNNING](#); SQLSTATE: [HY000](#)

Message: This operation requires a running slave; configure slave and do START SLAVE
- Error number: [1200](#); Symbol: [ER_BAD_SLAVE](#); SQLSTATE: [HY000](#)

Message: The server is not configured as slave; fix in config file or with CHANGE MASTER TO
- Error number: [1201](#); Symbol: [ER_MASTER_INFO](#); SQLSTATE: [HY000](#)

Message: Could not initialize master info structure; more error messages can be found in the MySQL error log
- Error number: [1202](#); Symbol: [ER_SLAVE_THREAD](#); SQLSTATE: [HY000](#)

Message: Could not create slave thread; check system resources
- Error number: [1203](#); Symbol: [ER_TOO_MANY_USER_CONNECTIONS](#); SQLSTATE: [42000](#)

Message: User %s already has more than 'max_user_connections' active connections
- Error number: [1204](#); Symbol: [ER_SET_CONSTANTS_ONLY](#); SQLSTATE: [HY000](#)

Message: You may only use constant expressions with SET
- Error number: [1205](#); Symbol: [ER_LOCK_WAIT_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: Lock wait timeout exceeded; try restarting transaction

[InnoDB](#) reports this error when lock wait timeout expires. The statement that waited too long was [rolled back](#) (not the entire [transaction](#)). You can increase the value of the [innodb_lock_wait_timeout](#) configuration option if SQL statements should wait longer for other transactions to complete, or decrease it if too many long-running transactions are causing [locking](#) problems and reducing [concurrency](#) on a busy system.
- Error number: [1206](#); Symbol: [ER_LOCK_TABLE_FULL](#); SQLSTATE: [HY000](#)

Message: The total number of locks exceeds the lock table size

[InnoDB](#) reports this error when the total number of locks exceeds the amount of memory devoted to managing locks. To avoid this error, increase the value of [innodb_buffer_pool_size](#). Within an individual application, a workaround may be to break a large operation into smaller pieces. For example, if the error occurs for a large [INSERT](#), perform several smaller [INSERT](#) operations.
- Error number: [1207](#); Symbol: [ER_READ_ONLY_TRANSACTION](#); SQLSTATE: [25000](#)

Message: Update locks cannot be acquired during a READ UNCOMMITTED transaction
- Error number: [1208](#); Symbol: [ER_DROP_DB_WITH_READ_LOCK](#); SQLSTATE: [HY000](#)

Message: DROP DATABASE not allowed while thread is holding global read lock
- Error number: [1209](#); Symbol: [ER_CREATE_DB_WITH_READ_LOCK](#); SQLSTATE: [HY000](#)

Message: CREATE DATABASE not allowed while thread is holding global read lock
- Error number: [1210](#); Symbol: [ER_WRONG_ARGUMENTS](#); SQLSTATE: [HY000](#)

Message: Incorrect arguments to %s

- Error number: [1211](#); Symbol: [ER_NO_PERMISSION_TO_CREATE_USER](#); SQLSTATE: [42000](#)

Message: '%s'@'%s' is not allowed to create new users
- Error number: [1212](#); Symbol: [ER_UNION_TABLES_IN_DIFFERENT_DIR](#); SQLSTATE: [HY000](#)

Message: Incorrect table definition; all MERGE tables must be in the same database
- Error number: [1213](#); Symbol: [ER_LOCK_DEADLOCK](#); SQLSTATE: [40001](#)

Message: Deadlock found when trying to get lock; try restarting transaction

[InnoDB](#) reports this error when a [transaction](#) encounters a [deadlock](#) and is automatically [rolled back](#) so that your application can take corrective action. To recover from this error, run all the operations in this transaction again. A deadlock occurs when requests for locks arrive in inconsistent order between transactions. The transaction that was rolled back released all its locks, and the other transaction can now get all the locks it requested. Thus, when you re-run the transaction that was rolled back, it might have to wait for other transactions to complete, but typically the deadlock does not recur. If you encounter frequent deadlocks, make the sequence of locking operations ([LOCK TABLES, SELECT ... FOR UPDATE](#), and so on) consistent between the different transactions or applications that experience the issue. See [Deadlocks in InnoDB](#) for details.
- Error number: [1214](#); Symbol: [ER_TABLE_CANT_HANDLE_FT](#); SQLSTATE: [HY000](#)

Message: The used table type doesn't support FULLTEXT indexes
- Error number: [1215](#); Symbol: [ER_CANNOT_ADD_FOREIGN](#); SQLSTATE: [HY000](#)

Message: Cannot add foreign key constraint
- Error number: [1216](#); Symbol: [ER_NO_REFERENCED_ROW](#); SQLSTATE: [23000](#)

Message: Cannot add or update a child row: a foreign key constraint fails

[InnoDB](#) reports this error when you try to add a row but there is no parent row, and a [foreign key constraint](#) fails. Add the parent row first.
- Error number: [1217](#); Symbol: [ER_ROW_IS_REFERENCED](#); SQLSTATE: [23000](#)

Message: Cannot delete or update a parent row: a foreign key constraint fails

[InnoDB](#) reports this error when you try to delete a parent row that has children, and a [foreign key constraint](#) fails. Delete the children first.
- Error number: [1218](#); Symbol: [ER_CONNECT_TO_MASTER](#); SQLSTATE: [08S01](#)

Message: Error connecting to master: %s
- Error number: [1219](#); Symbol: [ER_QUERY_ON_MASTER](#); SQLSTATE: [HY000](#)

Message: Error running query on master: %s
- Error number: [1220](#); Symbol: [ER_ERROR_WHEN_EXECUTING_COMMAND](#); SQLSTATE: [HY000](#)

Message: Error when executing command %s: %s
- Error number: [1221](#); Symbol: [ER_WRONG_USAGE](#); SQLSTATE: [HY000](#)

Message: Incorrect usage of %s and %s
- Error number: [1222](#); Symbol: [ER_WRONG_NUMBER_OF_COLUMNS_IN_SELECT](#); SQLSTATE: [21000](#)

Message: The used SELECT statements have a different number of columns

-
- Error number: [1223](#); Symbol: [ER_CANT_UPDATE_WITH_READLOCK](#); SQLSTATE: [HY000](#)
Message: Can't execute the query because you have a conflicting read lock
 - Error number: [1224](#); Symbol: [ER_MIXING_NOT_ALLOWED](#); SQLSTATE: [HY000](#)
Message: Mixing of transactional and non-transactional tables is disabled
 - Error number: [1225](#); Symbol: [ER_DUP_ARGUMENT](#); SQLSTATE: [HY000](#)
Message: Option '%s' used twice in statement
 - Error number: [1226](#); Symbol: [ER_USER_LIMIT_REACHED](#); SQLSTATE: [42000](#)
Message: User '%s' has exceeded the '%s' resource (current value: %ld)
 - Error number: [1227](#); Symbol: [ER_SPECIFIC_ACCESS_DENIED_ERROR](#); SQLSTATE: [42000](#)
Message: Access denied; you need (at least one of) the %s privilege(s) for this operation
 - Error number: [1228](#); Symbol: [ER_LOCAL_VARIABLE](#); SQLSTATE: [HY000](#)
Message: Variable '%s' is a SESSION variable and can't be used with SET GLOBAL
 - Error number: [1229](#); Symbol: [ER_GLOBAL_VARIABLE](#); SQLSTATE: [HY000](#)
Message: Variable '%s' is a GLOBAL variable and should be set with SET GLOBAL
 - Error number: [1230](#); Symbol: [ER_NO_DEFAULT](#); SQLSTATE: [42000](#)
Message: Variable '%s' doesn't have a default value
 - Error number: [1231](#); Symbol: [ER_WRONG_VALUE_FOR_VAR](#); SQLSTATE: [42000](#)
Message: Variable '%s' can't be set to the value of '%s'
 - Error number: [1232](#); Symbol: [ER_WRONG_TYPE_FOR_VAR](#); SQLSTATE: [42000](#)
Message: Incorrect argument type to variable '%s'
 - Error number: [1233](#); Symbol: [ER_VAR_CANT_BE_READ](#); SQLSTATE: [HY000](#)
Message: Variable '%s' can only be set, not read
 - Error number: [1234](#); Symbol: [ER_CANT_USE_OPTION_HERE](#); SQLSTATE: [42000](#)
Message: Incorrect usage/placement of '%s'
 - Error number: [1235](#); Symbol: [ER_NOT_SUPPORTED_YET](#); SQLSTATE: [42000](#)
Message: This version of MySQL doesn't yet support '%s'
 - Error number: [1236](#); Symbol: [ER_MASTER_FATAL_ERROR_READING_BINLOG](#); SQLSTATE: [HY000](#)
Message: Got fatal error %d from master when reading data from binary log: '%s'
 - Error number: [1237](#); Symbol: [ER_SLAVE_IGNORED_TABLE](#); SQLSTATE: [HY000](#)
Message: Slave SQL thread ignored the query because of replicate-*-table rules
 - Error number: [1238](#); Symbol: [ER_INCORRECT_GLOBAL_LOCAL_VAR](#); SQLSTATE: [HY000](#)
Message: Variable '%s' is a %s variable
 - Error number: [1239](#); Symbol: [ER_WRONG_FK_DEF](#); SQLSTATE: [42000](#)

Message: Incorrect foreign key definition for '%s': %s

- Error number: 1240; Symbol: [ER_KEY_REF_DO_NOT_MATCH_TABLE_REF](#); SQLSTATE: HY000

Message: Key reference and table reference don't match

- Error number: 1241; Symbol: [ER_OPERAND_COLUMNS](#); SQLSTATE: 21000

Message: Operand should contain %d column(s)

- Error number: 1242; Symbol: [ER_SUBQUERY_NO_1_ROW](#); SQLSTATE: 21000

Message: Subquery returns more than 1 row

- Error number: 1243; Symbol: [ER_UNKNOWN_STMT_HANDLER](#); SQLSTATE: HY000

Message: Unknown prepared statement handler (%.*s) given to %s

- Error number: 1244; Symbol: [ER_CORRUPT_HELP_DB](#); SQLSTATE: HY000

Message: Help database is corrupt or does not exist

- Error number: 1245; Symbol: [ER_CYCLIC_REFERENCE](#); SQLSTATE: HY000

Message: Cyclic reference on subqueries

- Error number: 1246; Symbol: [ER_AUTO_CONVERT](#); SQLSTATE: HY000

Message: Converting column '%s' from %s to %s

- Error number: 1247; Symbol: [ER_ILLEGAL_REFERENCE](#); SQLSTATE: 42S22

Message: Reference '%s' not supported (%s)

- Error number: 1248; Symbol: [ER_DERIVED_MUST_HAVE_ALIAS](#); SQLSTATE: 42000

Message: Every derived table must have its own alias

- Error number: 1249; Symbol: [ER_SELECT_REDUCED](#); SQLSTATE: 01000

Message: Select %u was reduced during optimization

- Error number: 1250; Symbol: [ER_TABLENAME_NOT_ALLOWED_HERE](#); SQLSTATE: 42000

Message: Table '%s' from one of the SELECTs cannot be used in %s

- Error number: 1251; Symbol: [ER_NOT_SUPPORTED_AUTH_MODE](#); SQLSTATE: 08004

Message: Client does not support authentication protocol requested by server; consider upgrading MySQL client

- Error number: 1252; Symbol: [ER_SPATIAL_CANT_HAVE_NULL](#); SQLSTATE: 42000

Message: All parts of a SPATIAL index must be NOT NULL

- Error number: 1253; Symbol: [ER_COLLATION_CHARSET_MISMATCH](#); SQLSTATE: 42000

Message: COLLATION '%s' is not valid for CHARACTER SET '%s'

- Error number: 1254; Symbol: [ER_SLAVE_WAS_RUNNING](#); SQLSTATE: HY000

Message: Slave is already running

- Error number: 1255; Symbol: [ER_SLAVE_WAS_NOT_RUNNING](#); SQLSTATE: HY000

Message: Slave already has been stopped

- Error number: [1256](#); Symbol: [ER_TOO_BIG_FOR_UNCOMPRESS](#); SQLSTATE: [HY000](#)

Message: Uncompressed data size too large; the maximum size is %d (probably, length of uncompressed data was corrupted)

- Error number: [1257](#); Symbol: [ER_ZLIB_Z_MEM_ERROR](#); SQLSTATE: [HY000](#)

Message: ZLIB: Not enough memory

- Error number: [1258](#); Symbol: [ER_ZLIB_Z_BUF_ERROR](#); SQLSTATE: [HY000](#)

Message: ZLIB: Not enough room in the output buffer (probably, length of uncompressed data was corrupted)

- Error number: [1259](#); Symbol: [ER_ZLIB_Z_DATA_ERROR](#); SQLSTATE: [HY000](#)

Message: ZLIB: Input data corrupted

- Error number: [1260](#); Symbol: [ER_CUT_VALUE_GROUP_CONCAT](#); SQLSTATE: [HY000](#)

Message: Row %u was cut by GROUP_CONCAT()

- Error number: [1261](#); Symbol: [ER_WARN_TOO_FEW_RECORDS](#); SQLSTATE: [01000](#)

Message: Row %ld doesn't contain data for all columns

- Error number: [1262](#); Symbol: [ER_WARN_TOO_MANY_RECORDS](#); SQLSTATE: [01000](#)

Message: Row %ld was truncated; it contained more data than there were input columns

- Error number: [1263](#); Symbol: [ER_WARN_NULL_TO_NOTNULL](#); SQLSTATE: [22004](#)

Message: Column set to default value; NULL supplied to NOT NULL column '%s' at row %ld

- Error number: [1264](#); Symbol: [ER_WARN_DATA_OUT_OF_RANGE](#); SQLSTATE: [22003](#)

Message: Out of range value for column '%s' at row %ld

- Error number: [1265](#); Symbol: [WARN_DATA_TRUNCATED](#); SQLSTATE: [01000](#)

Message: Data truncated for column '%s' at row %ld

- Error number: [1266](#); Symbol: [ER_WARN_USING_OTHER_HANDLER](#); SQLSTATE: [HY000](#)

Message: Using storage engine %s for table '%s'

- Error number: [1267](#); Symbol: [ER_CANT_AGGREGATE_2COLLATIONS](#); SQLSTATE: [HY000](#)

Message: Illegal mix of collations (%s,%s) and (%s,%s) for operation '%s'

- Error number: [1268](#); Symbol: [ER_DROP_USER](#); SQLSTATE: [HY000](#)

Message: Cannot drop one or more of the requested users

- Error number: [1269](#); Symbol: [ER_REVOKED_GRANTS](#); SQLSTATE: [HY000](#)

Message: Can't revoke all privileges for one or more of the requested users

- Error number: [1270](#); Symbol: [ER_CANT_AGGREGATE_3COLLATIONS](#); SQLSTATE: [HY000](#)

Message: Illegal mix of collations (%s,%s), (%s,%s), (%s,%s) for operation '%s'

- Error number: [1271](#); Symbol: [ER_CANT_AGGREGATE_NCOLLATIONS](#); SQLSTATE: [HY000](#)
Message: Illegal mix of collations for operation '%s'
- Error number: [1272](#); Symbol: [ER_VARIABLE_IS_NOT_STRUCT](#); SQLSTATE: [HY000](#)
Message: Variable '%s' is not a variable component (can't be used as XXXX.variable_name)
- Error number: [1273](#); Symbol: [ER_UNKNOWN_COLLATION](#); SQLSTATE: [HY000](#)
Message: Unknown collation: '%s'
- Error number: [1274](#); Symbol: [ER_SLAVE_IGNORED_SSL_PARAMS](#); SQLSTATE: [HY000](#)
Message: SSL parameters in CHANGE MASTER are ignored because this MySQL slave was compiled without SSL support; they can be used later if MySQL slave with SSL is started
- Error number: [1275](#); Symbol: [ER_SERVER_IS_IN_SECURE_AUTH_MODE](#); SQLSTATE: [HY000](#)
Message: Server is running in --secure-auth mode, but '%s'@'%s' has a password in the old format; please change the password to the new format
- Error number: [1276](#); Symbol: [ER_WARN_FIELD_RESOLVED](#); SQLSTATE: [HY000](#)
Message: Field or reference '%s%s%s%s%s' of SELECT #%%d was resolved in SELECT #%%d
- Error number: [1277](#); Symbol: [ER_BAD_SLAVE_UNTIL_COND](#); SQLSTATE: [HY000](#)
Message: Incorrect parameter or combination of parameters for START SLAVE UNTIL
- Error number: [1278](#); Symbol: [ER_MISSING_SKIP_SLAVE](#); SQLSTATE: [HY000](#)
Message: It is recommended to use --skip-slave-start when doing step-by-step replication with START SLAVE UNTIL; otherwise, you will get problems if you get an unexpected slave's mysqld restart
- Error number: [1279](#); Symbol: [ER_UNTIL_COND_IGNORED](#); SQLSTATE: [HY000](#)
Message: SQL thread is not to be started so UNTIL options are ignored
- Error number: [1280](#); Symbol: [ER_WRONG_NAME_FOR_INDEX](#); SQLSTATE: [42000](#)
Message: Incorrect index name '%s'
- Error number: [1281](#); Symbol: [ER_WRONG_NAME_FOR_CATALOG](#); SQLSTATE: [42000](#)
Message: Incorrect catalog name '%s'
- Error number: [1282](#); Symbol: [ER_WARN_QC_RESIZE](#); SQLSTATE: [HY000](#)
Message: Query cache failed to set size %lu; new query cache size is %lu
- Error number: [1283](#); Symbol: [ER_BAD_FT_COLUMN](#); SQLSTATE: [HY000](#)
Message: Column '%s' cannot be part of FULLTEXT index
- Error number: [1284](#); Symbol: [ER_UNKNOWN_KEY_CACHE](#); SQLSTATE: [HY000](#)
Message: Unknown key cache '%s'
- Error number: [1285](#); Symbol: [ER_WARN_HOSTNAME_WONT_WORK](#); SQLSTATE: [HY000](#)
Message: MySQL is started in --skip-name-resolve mode; you must restart it without this switch for this grant to work

-
- Error number: [1286](#); Symbol: [ER_UNKNOWN_STORAGE_ENGINE](#); SQLSTATE: [42000](#)
Message: Unknown storage engine '%s'
 - Error number: [1287](#); Symbol: [ER_WARN_DEPRECATED_SYNTAX](#); SQLSTATE: [HY000](#)
Message: '%s' is deprecated and will be removed in a future release. Please use %s instead
 - Error number: [1288](#); Symbol: [ER_NON_UPDATABLE_TABLE](#); SQLSTATE: [HY000](#)
Message: The target table %s of the %s is not updatable
 - Error number: [1289](#); Symbol: [ER_FEATURE_DISABLED](#); SQLSTATE: [HY000](#)
Message: The '%s' feature is disabled; you need MySQL built with '%s' to have it working
 - Error number: [1290](#); Symbol: [ER_OPTION_PREVENTS_STATEMENT](#); SQLSTATE: [HY000](#)
Message: The MySQL server is running with the %s option so it cannot execute this statement
 - Error number: [1291](#); Symbol: [ER_DUPLICATED_VALUE_IN_TYPE](#); SQLSTATE: [HY000](#)
Message: Column '%s' has duplicated value '%s' in %s
 - Error number: [1292](#); Symbol: [ER_TRUNCATED_WRONG_VALUE](#); SQLSTATE: [22007](#)
Message: Truncated incorrect %s value: '%s'
 - Error number: [1293](#); Symbol: [ER_TOO MUCH_AUTO_TIMESTAMP_COLS](#); SQLSTATE: [HY000](#)
Message: Incorrect table definition; there can be only one TIMESTAMP column with CURRENT_TIMESTAMP in DEFAULT or ON UPDATE clause
 - Error number: [1294](#); Symbol: [ER_INVALID_ON_UPDATE](#); SQLSTATE: [HY000](#)
Message: Invalid ON UPDATE clause for '%s' column
 - Error number: [1295](#); Symbol: [ER_UNSUPPORTED_PS](#); SQLSTATE: [HY000](#)
Message: This command is not supported in the prepared statement protocol yet
 - Error number: [1296](#); Symbol: [ER_GET_ERRMSG](#); SQLSTATE: [HY000](#)
Message: Got error %d '%s' from %s
 - Error number: [1297](#); Symbol: [ER_GET_TEMPORARY_ERRMSG](#); SQLSTATE: [HY000](#)
Message: Got temporary error %d '%s' from %s
 - Error number: [1298](#); Symbol: [ER_UNKNOWN_TIME_ZONE](#); SQLSTATE: [HY000](#)
Message: Unknown or incorrect time zone: '%s'
 - Error number: [1299](#); Symbol: [ER_WARN_INVALID_TIMESTAMP](#); SQLSTATE: [HY000](#)
Message: Invalid TIMESTAMP value in column '%s' at row %ld
 - Error number: [1300](#); Symbol: [ER_INVALID_CHARACTER_STRING](#); SQLSTATE: [HY000](#)
Message: Invalid %s character string: '%s'
 - Error number: [1301](#); Symbol: [ER_WARN_ALLOWED_PACKET_OVERFLOWED](#); SQLSTATE: [HY000](#)
Message: Result of %s() was larger than max_allowed_packet (%ld) - truncated

- Error number: 1302; Symbol: ER_CONFLICTING_DECLARATIONS; SQLSTATE: HY000
Message: Conflicting declarations: '%s%s' and '%s%s'
- Error number: 1303; Symbol: ER_SP_NO_RECURSIVE_CREATE; SQLSTATE: 2F003
Message: Can't create a %s from within another stored routine
- Error number: 1304; Symbol: ER_SP_ALREADY_EXISTS; SQLSTATE: 42000
Message: %s %s already exists
- Error number: 1305; Symbol: ER_SP_DOES_NOT_EXIST; SQLSTATE: 42000
Message: %s %s does not exist
- Error number: 1306; Symbol: ER_SP_DROP_FAILED; SQLSTATE: HY000
Message: Failed to DROP %s %s
- Error number: 1307; Symbol: ER_SP_STORE_FAILED; SQLSTATE: HY000
Message: Failed to CREATE %s %s
- Error number: 1308; Symbol: ER_SP_LILABEL_MISMATCH; SQLSTATE: 42000
Message: %s with no matching label: %s
- Error number: 1309; Symbol: ER_SP_LABEL_REDEFINE; SQLSTATE: 42000
Message: Redefining label %s
- Error number: 1310; Symbol: ER_SP_LABEL_MISMATCH; SQLSTATE: 42000
Message: End-label %s without match
- Error number: 1311; Symbol: ER_SP_UNINIT_VAR; SQLSTATE: 01000
Message: Referring to uninitialized variable %s
- Error number: 1312; Symbol: ER_SP_BADSELECT; SQLSTATE: 0A000
Message: PROCEDURE %s can't return a result set in the given context
- Error number: 1313; Symbol: ER_SP_BADRETURN; SQLSTATE: 42000
Message: RETURN is only allowed in a FUNCTION
- Error number: 1314; Symbol: ER_SP_BADSTATEMENT; SQLSTATE: 0A000
Message: %s is not allowed in stored procedures
- Error number: 1315; Symbol: ER_UPDATE_LOG_DEPRECATED_IGNORED; SQLSTATE: 42000
Message: The update log is deprecated and replaced by the binary log; SET SQL_LOG_UPDATE has been ignored.
- Error number: 1316; Symbol: ER_UPDATE_LOG_DEPRECATED_TRANSLATED; SQLSTATE: 42000
Message: The update log is deprecated and replaced by the binary log; SET SQL_LOG_UPDATE has been translated to SET SQL_LOG_BIN.
- Error number: 1317; Symbol: ER_QUERY_INTERRUPTED; SQLSTATE: 70100
Message: Query execution was interrupted

-
- Error number: [1318](#); Symbol: [ER_SP_WRONG_NO_OF_ARGS](#); SQLSTATE: [42000](#)
Message: Incorrect number of arguments for %s %s; expected %u, got %u
 - Error number: [1319](#); Symbol: [ER_SP_COND_MISMATCH](#); SQLSTATE: [42000](#)
Message: Undefined CONDITION: %s
 - Error number: [1320](#); Symbol: [ER_SP_NORETURN](#); SQLSTATE: [42000](#)
Message: No RETURN found in FUNCTION %s
 - Error number: [1321](#); Symbol: [ER_SP_NORETURNEND](#); SQLSTATE: [2F005](#)
Message: FUNCTION %s ended without RETURN
 - Error number: [1322](#); Symbol: [ER_SP_BAD_CURSOR_QUERY](#); SQLSTATE: [42000](#)
Message: Cursor statement must be a SELECT
 - Error number: [1323](#); Symbol: [ER_SP_BAD_CURSOR_SELECT](#); SQLSTATE: [42000](#)
Message: Cursor SELECT must not have INTO
 - Error number: [1324](#); Symbol: [ER_SP_CURSOR_MISMATCH](#); SQLSTATE: [42000](#)
Message: Undefined CURSOR: %s
 - Error number: [1325](#); Symbol: [ER_SP_CURSOR_ALREADY_OPEN](#); SQLSTATE: [24000](#)
Message: Cursor is already open
 - Error number: [1326](#); Symbol: [ER_SP_CURSOR_NOT_OPEN](#); SQLSTATE: [24000](#)
Message: Cursor is not open
 - Error number: [1327](#); Symbol: [ER_SP_UNDECLARED_VAR](#); SQLSTATE: [42000](#)
Message: Undeclared variable: %s
 - Error number: [1328](#); Symbol: [ER_SP_WRONG_NO_OF_FETCH_ARGS](#); SQLSTATE: [HY000](#)
Message: Incorrect number of FETCH variables
 - Error number: [1329](#); Symbol: [ER_SP_FETCH_NO_DATA](#); SQLSTATE: [02000](#)
Message: No data - zero rows fetched, selected, or processed
 - Error number: [1330](#); Symbol: [ER_SP_DUP_PARAM](#); SQLSTATE: [42000](#)
Message: Duplicate parameter: %s
 - Error number: [1331](#); Symbol: [ER_SP_DUP_VAR](#); SQLSTATE: [42000](#)
Message: Duplicate variable: %s
 - Error number: [1332](#); Symbol: [ER_SP_DUP_COND](#); SQLSTATE: [42000](#)
Message: Duplicate condition: %s
 - Error number: [1333](#); Symbol: [ER_SP_DUP_CURS](#); SQLSTATE: [42000](#)
Message: Duplicate cursor: %s
 - Error number: [1334](#); Symbol: [ER_SP_CANT.Alter](#); SQLSTATE: [HY000](#)

Message: Failed to ALTER %s %s

- Error number: 1335; Symbol: ER_SP_SUBSELECT_NYI; SQLSTATE: 0A000

Message: Subquery value not supported

- Error number: 1336; Symbol: ER_STMT_NOT_ALLOWED_IN_SF_OR_TRG; SQLSTATE: 0A000

Message: %s is not allowed in stored function or trigger

- Error number: 1337; Symbol: ER_SP_VARCOND_AFTER_CURSHNDLR; SQLSTATE: 42000

Message: Variable or condition declaration after cursor or handler declaration

- Error number: 1338; Symbol: ER_SP_CURSOR_AFTER_HANDLER; SQLSTATE: 42000

Message: Cursor declaration after handler declaration

- Error number: 1339; Symbol: ER_SP_CASE_NOT_FOUND; SQLSTATE: 20000

Message: Case not found for CASE statement

- Error number: 1340; Symbol: ER_FPARSER_TOO_BIG_FILE; SQLSTATE: HY000

Message: Configuration file '%s' is too big

- Error number: 1341; Symbol: ER_FPARSER_BAD_HEADER; SQLSTATE: HY000

Message: Malformed file type header in file '%s'

- Error number: 1342; Symbol: ER_FPARSER_EOF_IN_COMMENT; SQLSTATE: HY000

Message: Unexpected end of file while parsing comment '%s'

- Error number: 1343; Symbol: ER_FPARSER_ERROR_IN_PARAMETER; SQLSTATE: HY000

Message: Error while parsing parameter '%s' (line: '%s')

- Error number: 1344; Symbol: ER_FPARSER_EOF_IN_UNKNOWN_PARAMETER; SQLSTATE: HY000

Message: Unexpected end of file while skipping unknown parameter '%s'

- Error number: 1345; Symbol: ER_VIEW_NO_EXPLAIN; SQLSTATE: HY000

Message: EXPLAIN/SHOW can not be issued; lacking privileges for underlying table

- Error number: 1346; Symbol: ER_FRM_UNKNOWN_TYPE; SQLSTATE: HY000

Message: File '%s' has unknown type '%s' in its header

- Error number: 1347; Symbol: ER_WRONG_OBJECT; SQLSTATE: HY000

Message: '%s.%s' is not %s

The named object is incorrect for the type of operation attempted on it. It must be an object of the named type.

- Error number: 1348; Symbol: ER_NONUPDATEABLE_COLUMN; SQLSTATE: HY000

Message: Column '%s' is not updatable

- Error number: 1349; Symbol: ER_VIEW_SELECT_DERIVED; SQLSTATE: HY000

Message: View's SELECT contains a subquery in the FROM clause

`ER_VIEW_SELECT_DERIVED` was removed after 5.7.6.

- Error number: `1349`; Symbol: `ER_VIEW_SELECT_DERIVED_UNUSED`; SQLSTATE: `HY000`

Message: View's SELECT contains a subquery in the FROM clause

`ER_VIEW_SELECT_DERIVED_UNUSED` was added in 5.7.7.

- Error number: `1350`; Symbol: `ER_VIEW_SELECT_CLAUSE`; SQLSTATE: `HY000`

Message: View's SELECT contains a '%s' clause

- Error number: `1351`; Symbol: `ER_VIEW_SELECT_VARIABLE`; SQLSTATE: `HY000`

Message: View's SELECT contains a variable or parameter

- Error number: `1352`; Symbol: `ER_VIEW_SELECT_TMPTABLE`; SQLSTATE: `HY000`

Message: View's SELECT refers to a temporary table '%s'

- Error number: `1353`; Symbol: `ER_VIEW_WRONG_LIST`; SQLSTATE: `HY000`

Message: View's SELECT and view's field list have different column counts

- Error number: `1354`; Symbol: `ER_WARN_VIEW_MERGE`; SQLSTATE: `HY000`

Message: View merge algorithm can't be used here for now (assumed undefined algorithm)

- Error number: `1355`; Symbol: `ER_WARN_VIEW_WITHOUT_KEY`; SQLSTATE: `HY000`

Message: View being updated does not have complete key of underlying table in it

- Error number: `1356`; Symbol: `ER_VIEW_INVALID`; SQLSTATE: `HY000`

Message: View '%s.%s' references invalid table(s) or column(s) or function(s) or definer/invoker of view lack rights to use them

- Error number: `1357`; Symbol: `ER_SP_NO_DROP_SP`; SQLSTATE: `HY000`

Message: Can't drop or alter a %s from within another stored routine

- Error number: `1358`; Symbol: `ER_SP_GOTO_IN_HNDLR`; SQLSTATE: `HY000`

Message: GOTO is not allowed in a stored procedure handler

- Error number: `1359`; Symbol: `ER_TRG_ALREADY_EXISTS`; SQLSTATE: `HY000`

Message: Trigger already exists

- Error number: `1360`; Symbol: `ER_TRG_DOES_NOT_EXIST`; SQLSTATE: `HY000`

Message: Trigger does not exist

- Error number: `1361`; Symbol: `ER_TRG_ON_VIEW_OR_TEMP_TABLE`; SQLSTATE: `HY000`

Message: Trigger's '%s' is view or temporary table

- Error number: `1362`; Symbol: `ER_TRG_CANT_CHANGE_ROW`; SQLSTATE: `HY000`

Message: Updating of %s row is not allowed in %trigger

- Error number: `1363`; Symbol: `ER_TRG_NO SUCH_ROW_IN_TRG`; SQLSTATE: `HY000`

Message: There is no %s row in %s trigger

- Error number: [1364](#); Symbol: [ER_NO_DEFAULT_FOR_FIELD](#); SQLSTATE: [HY000](#)
Message: Field '%s' doesn't have a default value
- Error number: [1365](#); Symbol: [ER_DIVISION_BY_ZERO](#); SQLSTATE: [22012](#)
Message: Division by 0
- Error number: [1366](#); Symbol: [ER_TRUNCATED_WRONG_VALUE_FOR_FIELD](#); SQLSTATE: [HY000](#)
Message: Incorrect %s value: '%s' for column '%s' at row %ld
- Error number: [1367](#); Symbol: [ER_ILLEGAL_VALUE_FOR_TYPE](#); SQLSTATE: [22007](#)
Message: Illegal %s '%s' value found during parsing
- Error number: [1368](#); Symbol: [ER_VIEW_NONUPD_CHECK](#); SQLSTATE: [HY000](#)
Message: CHECK OPTION on non-updatable view '%s.%s'
- Error number: [1369](#); Symbol: [ER_VIEW_CHECK_FAILED](#); SQLSTATE: [HY000](#)
Message: CHECK OPTION failed '%s.%s'
- Error number: [1370](#); Symbol: [ER_PROCACCESS_DENIED_ERROR](#); SQLSTATE: [42000](#)
Message: %s command denied to user '%s'@'%s' for routine '%s'
- Error number: [1371](#); Symbol: [ER_RELAY_LOG_FAIL](#); SQLSTATE: [HY000](#)
Message: Failed purging old relay logs: %s
- Error number: [1372](#); Symbol: [ER_PASSWD_LENGTH](#); SQLSTATE: [HY000](#)
Message: Password hash should be a %d-digit hexadecimal number
- Error number: [1373](#); Symbol: [ER_UNKNOWN_TARGET_BINLOG](#); SQLSTATE: [HY000](#)
Message: Target log not found in binlog index
- Error number: [1374](#); Symbol: [ER_IO_ERR_LOG_INDEX_READ](#); SQLSTATE: [HY000](#)
Message: I/O error reading log index file
- Error number: [1375](#); Symbol: [ER_BINLOG_PURGE_PROHIBITED](#); SQLSTATE: [HY000](#)
Message: Server configuration does not permit binlog purge
- Error number: [1376](#); Symbol: [ER_FSEEK_FAIL](#); SQLSTATE: [HY000](#)
Message: Failed on fseek()
- Error number: [1377](#); Symbol: [ER_BINLOG_PURGE_FATAL_ERR](#); SQLSTATE: [HY000](#)
Message: Fatal error during log purge
- Error number: [1378](#); Symbol: [ER_LOG_IN_USE](#); SQLSTATE: [HY000](#)
Message: A purgeable log is in use, will not purge
- Error number: [1379](#); Symbol: [ER_LOG_PURGE_UNKNOWN_ERR](#); SQLSTATE: [HY000](#)
Message: Unknown error during log purge
- Error number: [1380](#); Symbol: [ER_RELAY_LOG_INIT](#); SQLSTATE: [HY000](#)

Message: Failed initializing relay log position: %s

- Error number: 1381; Symbol: ER_NO_BINARY_LOGGING; SQLSTATE: HY000

Message: You are not using binary logging

- Error number: 1382; Symbol: ER_RESERVED_SYNTAX; SQLSTATE: HY000

Message: The '%s' syntax is reserved for purposes internal to the MySQL server

- Error number: 1383; Symbol: ER_WSAS_FAILED; SQLSTATE: HY000

Message: WSAStartup Failed

- Error number: 1384; Symbol: ER_DIFF_GROUPS_PROC; SQLSTATE: HY000

Message: Can't handle procedures with different groups yet

- Error number: 1385; Symbol: ER_NO_GROUP_FOR_PROC; SQLSTATE: HY000

Message: Select must have a group with this procedure

- Error number: 1386; Symbol: ER_ORDER_WITH_PROC; SQLSTATE: HY000

Message: Can't use ORDER clause with this procedure

- Error number: 1387; Symbol: ER_LOGGING_PROHIBIT_CHANGING_OF; SQLSTATE: HY000

Message: Binary logging and replication forbid changing the global server %s

- Error number: 1388; Symbol: ER_NO_FILE_MAPPING; SQLSTATE: HY000

Message: Can't map file: %s, errno: %d

- Error number: 1389; Symbol: ER_WRONG_MAGIC; SQLSTATE: HY000

Message: Wrong magic in %s

- Error number: 1390; Symbol: ER_PS_MANY_PARAM; SQLSTATE: HY000

Message: Prepared statement contains too many placeholders

- Error number: 1391; Symbol: ER_KEY_PART_0; SQLSTATE: HY000

Message: Key part '%s' length cannot be 0

- Error number: 1392; Symbol: ER_VIEW_CHECKSUM; SQLSTATE: HY000

Message: View text checksum failed

- Error number: 1393; Symbol: ER_VIEW_MULTIUPDATE; SQLSTATE: HY000

Message: Can not modify more than one base table through a join view '%s.%s'

- Error number: 1394; Symbol: ER_VIEW_NO_INSERT_FIELD_LIST; SQLSTATE: HY000

Message: Can not insert into join view '%s.%s' without fields list

- Error number: 1395; Symbol: ER_VIEW_DELETE_MERGE_VIEW; SQLSTATE: HY000

Message: Can not delete from join view '%s.%s'

- Error number: 1396; Symbol: ER_CANNOT_USER; SQLSTATE: HY000

Message: Operation %s failed for %s

- Error number: [1397](#); Symbol: [ER_XAER_NOTA](#); SQLSTATE: [XAE04](#)
Message: XAER_NOTA: Unknown XID
- Error number: [1398](#); Symbol: [ER_XAER_INVAL](#); SQLSTATE: [XAE05](#)
Message: XAER_INVAL: Invalid arguments (or unsupported command)
- Error number: [1399](#); Symbol: [ER_XAER_RMFAIL](#); SQLSTATE: [XAE07](#)
Message: XAER_RMFAIL: The command cannot be executed when global transaction is in the %s state
- Error number: [1400](#); Symbol: [ER_XAER_OUTSIDE](#); SQLSTATE: [XAE09](#)
Message: XAER_OUTSIDE: Some work is done outside global transaction
- Error number: [1401](#); Symbol: [ER_XAER_RMERR](#); SQLSTATE: [XAE03](#)
Message: XAER_RMERR: Fatal error occurred in the transaction branch - check your data for consistency
- Error number: [1402](#); Symbol: [ER_XA_RBROLLBACK](#); SQLSTATE: [XA100](#)
Message: XA_RBROLLBACK: Transaction branch was rolled back
- Error number: [1403](#); Symbol: [ER_NONEXISTING_PROC_GRANT](#); SQLSTATE: [42000](#)
Message: There is no such grant defined for user '%s' on host '%s' on routine '%s'
- Error number: [1404](#); Symbol: [ER_PROC_AUTO_GRANT_FAIL](#); SQLSTATE: [HY000](#)
Message: Failed to grant EXECUTE and ALTER ROUTINE privileges
- Error number: [1405](#); Symbol: [ER_PROC_AUTO_REVOKED_FAIL](#); SQLSTATE: [HY000](#)
Message: Failed to revoke all privileges to dropped routine
- Error number: [1406](#); Symbol: [ER_DATA_TOO_LONG](#); SQLSTATE: [22001](#)
Message: Data too long for column '%s' at row %ld
- Error number: [1407](#); Symbol: [ER_SP_BAD_SQLSTATE](#); SQLSTATE: [42000](#)
Message: Bad SQLSTATE: '%s'
- Error number: [1408](#); Symbol: [ER_STARTUP](#); SQLSTATE: [HY000](#)
Message: %s: ready for connections. Version: '%s' socket: '%s' port: %d %s
- Error number: [1409](#); Symbol: [ER_LOAD_FROM_FIXED_SIZE_ROWS_TO_VAR](#); SQLSTATE: [HY000](#)
Message: Can't load value from file with fixed size rows to variable
- Error number: [1410](#); Symbol: [ER_CANT_CREATE_USER_WITH_GRANT](#); SQLSTATE: [42000](#)
Message: You are not allowed to create a user with GRANT
- Error number: [1411](#); Symbol: [ER_WRONG_VALUE_FOR_TYPE](#); SQLSTATE: [HY000](#)
Message: Incorrect %s value: '%s' for function %s
- Error number: [1412](#); Symbol: [ER_TABLE_DEF_CHANGED](#); SQLSTATE: [HY000](#)
Message: Table definition has changed, please retry transaction

-
- Error number: [1413](#); Symbol: [ER_SP_DUP_HANDLER](#); SQLSTATE: [42000](#)
Message: Duplicate handler declared in the same block
 - Error number: [1414](#); Symbol: [ER_SP_NOT_VAR_ARG](#); SQLSTATE: [42000](#)
Message: OUT or INOUT argument %d for routine %s is not a variable or NEW pseudo-variable in BEFORE trigger
 - Error number: [1415](#); Symbol: [ER_SP_NO_RETSET](#); SQLSTATE: [0A000](#)
Message: Not allowed to return a result set from a %s
 - Error number: [1416](#); Symbol: [ER_CANT_CREATE_GEOMETRY_OBJECT](#); SQLSTATE: [22003](#)
Message: Cannot get geometry object from data you send to the GEOMETRY field
 - Error number: [1417](#); Symbol: [ER_FAILED_ROUTINE_BREAK_BINLOG](#); SQLSTATE: [HY000](#)
Message: A routine failed and has neither NO SQL nor READS SQL DATA in its declaration and binary logging is enabled; if non-transactional tables were updated, the binary log will miss their changes
 - Error number: [1418](#); Symbol: [ER_BINLOG_UNSAFE_ROUTINE](#); SQLSTATE: [HY000](#)
Message: This function has none of DETERMINISTIC, NO SQL, or READS SQL DATA in its declaration and binary logging is enabled (you *might* want to use the less safe log_bin_trust_function_creators variable)
 - Error number: [1419](#); Symbol: [ER_BINLOG_CREATE_ROUTINE_NEED_SUPER](#); SQLSTATE: [HY000](#)
Message: You do not have the SUPER privilege and binary logging is enabled (you *might* want to use the less safe log_bin_trust_function_creators variable)
 - Error number: [1420](#); Symbol: [ER_EXEC_STMT_WITH_OPEN_CURSOR](#); SQLSTATE: [HY000](#)
Message: You can't execute a prepared statement which has an open cursor associated with it. Reset the statement to re-execute it.
 - Error number: [1421](#); Symbol: [ER_STMT_HAS_NO_OPEN_CURSOR](#); SQLSTATE: [HY000](#)
Message: The statement (%lu) has no open cursor.
 - Error number: [1422](#); Symbol: [ER_COMMIT_NOT_ALLOWED_IN_SF_OR_TRG](#); SQLSTATE: [HY000](#)
Message: Explicit or implicit commit is not allowed in stored function or trigger.
 - Error number: [1423](#); Symbol: [ER_NO_DEFAULT_FOR_VIEW_FIELD](#); SQLSTATE: [HY000](#)
Message: Field of view '%s.%s' underlying table doesn't have a default value
 - Error number: [1424](#); Symbol: [ER_SP_NO_RECURSION](#); SQLSTATE: [HY000](#)
Message: Recursive stored functions and triggers are not allowed.
 - Error number: [1425](#); Symbol: [ER_TOO_BIG_SCALE](#); SQLSTATE: [42000](#)
Message: Too big scale %d specified for column '%s'. Maximum is %lu.
 - Error number: [1426](#); Symbol: [ER_TOO_BIG_PRECISION](#); SQLSTATE: [42000](#)
Message: Too-big precision %d specified for '%s'. Maximum is %lu.
 - Error number: [1427](#); Symbol: [ER_M_BIGGER_THAN_D](#); SQLSTATE: [42000](#)

Message: For float(M,D), double(M,D) or decimal(M,D), M must be >= D (column '%s').

- Error number: 1428; Symbol: [ER_WRONG_LOCK_OF_SYSTEM_TABLE](#); SQLSTATE: HY000

Message: You can't combine write-locking of system tables with other tables or lock types

- Error number: 1429; Symbol: [ER_CONNECT_TO_FOREIGN_DATA_SOURCE](#); SQLSTATE: HY000

Message: Unable to connect to foreign data source: %s

- Error number: 1430; Symbol: [ER_QUERY_ON_FOREIGN_DATA_SOURCE](#); SQLSTATE: HY000

Message: There was a problem processing the query on the foreign data source. Data source error: %s

- Error number: 1431; Symbol: [ER_FOREIGN_DATA_SOURCE_DOESNT_EXIST](#); SQLSTATE: HY000

Message: The foreign data source you are trying to reference does not exist. Data source error: %s

- Error number: 1432; Symbol: [ER_FOREIGN_DATA_STRING_INVALID_CANT_CREATE](#); SQLSTATE: HY000

Message: Can't create federated table. The data source connection string '%s' is not in the correct format

- Error number: 1433; Symbol: [ER_FOREIGN_DATA_STRING_INVALID](#); SQLSTATE: HY000

Message: The data source connection string '%s' is not in the correct format

- Error number: 1434; Symbol: [ER_CANT_CREATE_FEDERATED_TABLE](#); SQLSTATE: HY000

Message: Can't create federated table. Foreign data src error: %s

- Error number: 1435; Symbol: [ER_TRG_IN_WRONG_SCHEMA](#); SQLSTATE: HY000

Message: Trigger in wrong schema

- Error number: 1436; Symbol: [ER_STACK_OVERRUN_NEED_MORE](#); SQLSTATE: HY000

Message: Thread stack overrun: %ld bytes used of a %ld byte stack, and %ld bytes needed. Use 'mysqld --thread_stack=#' to specify a bigger stack.

- Error number: 1437; Symbol: [ER_TOO_LONG_BODY](#); SQLSTATE: 42000

Message: Routine body for '%s' is too long

- Error number: 1438; Symbol: [ER_WARN_CANT_DROP_DEFAULT_KEYCACHE](#); SQLSTATE: HY000

Message: Cannot drop default keycache

- Error number: 1439; Symbol: [ER_TOO_BIG_DISPLAYWIDTH](#); SQLSTATE: 42000

Message: Display width out of range for column '%s' (max = %lu)

- Error number: 1440; Symbol: [ER_XAER_DUP_ID](#); SQLSTATE: XAE08

Message: XAER_DUPID: The XID already exists

- Error number: 1441; Symbol: [ER_DATETIME_FUNCTION_OVERFLOW](#); SQLSTATE: 22008

Message: Datetime function: %s field overflow

- Error number: 1442; Symbol: [ER_CANT_UPDATE_USED_TABLE_IN_SF_OR_TRG](#); SQLSTATE: HY000

Message: Can't update table '%s' in stored function/trigger because it is already used by statement which invoked this stored function/trigger.

- Error number: [1443](#); Symbol: [ER_VIEW_PREVENT_UPDATE](#); SQLSTATE: [HY000](#)

Message: The definition of table '%s' prevents operation %s on table "%s".

- Error number: [1444](#); Symbol: [ER_PS_NO_RECURSION](#); SQLSTATE: [HY000](#)

Message: The prepared statement contains a stored routine call that refers to that same statement. It's not allowed to execute a prepared statement in such a recursive manner

- Error number: [1445](#); Symbol: [ER_SP_CANT_SET_AUTOCOMMIT](#); SQLSTATE: [HY000](#)

Message: Not allowed to set autocommit from a stored function or trigger

- Error number: [1446](#); Symbol: [ER_MALFORMED_DEFINER](#); SQLSTATE: [HY000](#)

Message: Definer is not fully qualified

- Error number: [1447](#); Symbol: [ER_VIEW_FRM_NO_USER](#); SQLSTATE: [HY000](#)

Message: View '%s'.'%s' has no definer information (old table format). Current user is used as definer. Please recreate the view!

- Error number: [1448](#); Symbol: [ER_VIEW_OTHER_USER](#); SQLSTATE: [HY000](#)

Message: You need the SUPER privilege for creation view with '%s'@'%s' definer

- Error number: [1449](#); Symbol: [ER_NO_SUCH_USER](#); SQLSTATE: [HY000](#)

Message: The user specified as a definer ('%s'@'%s') does not exist

- Error number: [1450](#); Symbol: [ER_FORBID_SCHEMA_CHANGE](#); SQLSTATE: [HY000](#)

Message: Changing schema from '%s' to '%s' is not allowed.

- Error number: [1451](#); Symbol: [ER_ROW_IS_REFERENCED_2](#); SQLSTATE: [23000](#)

Message: Cannot delete or update a parent row: a foreign key constraint fails (%s)

[InnoDB](#) reports this error when you try to delete a parent row that has children, and a [foreign key constraint](#) fails. Delete the children first.

- Error number: [1452](#); Symbol: [ER_NO_REFERENCED_ROW_2](#); SQLSTATE: [23000](#)

Message: Cannot add or update a child row: a foreign key constraint fails (%s)

[InnoDB](#) reports this error when you try to add a row but there is no parent row, and a [foreign key constraint](#) fails. Add the parent row first.

- Error number: [1453](#); Symbol: [ER_SP_BAD_VAR_SHADOW](#); SQLSTATE: [42000](#)

Message: Variable '%s' must be quoted with `...`, or renamed

- Error number: [1454](#); Symbol: [ER_TRG_NO_DEFINER](#); SQLSTATE: [HY000](#)

Message: No definer attribute for trigger '%s'.'%s'. The trigger will be activated under the authorization of the invoker, which may have insufficient privileges. Please recreate the trigger.

- Error number: [1455](#); Symbol: [ER_OLD_FILE_FORMAT](#); SQLSTATE: [HY000](#)

Message: '%s' has an old format, you should re-create the '%s' object(s)

- Error number: [1456](#); Symbol: [ER_SP_RECUSION_LIMIT](#); SQLSTATE: [HY000](#)

Message: Recursive limit %d (as set by the max_sp_recursion_depth variable) was exceeded for routine %s
- Error number: [1457](#); Symbol: [ER_SP_PROC_TABLE_CORRUPT](#); SQLSTATE: [HY000](#)

Message: Failed to load routine %s. The table mysql.proc is missing, corrupt, or contains bad data (internal code %d)
- Error number: [1458](#); Symbol: [ER_SP_WRONG_NAME](#); SQLSTATE: [42000](#)

Message: Incorrect routine name '%s'
- Error number: [1459](#); Symbol: [ER_TABLE_NEEDS_UPGRADE](#); SQLSTATE: [HY000](#)

Message: Table upgrade required. Please do "REPAIR TABLE `%%`" or dump/reload to fix it!
- Error number: [1460](#); Symbol: [ER_SP_NO_AGGREGATE](#); SQLSTATE: [42000](#)

Message: AGGREGATE is not supported for stored functions
- Error number: [1461](#); Symbol: [ER_MAX_PREPARED_STMT_COUNT_REACHED](#); SQLSTATE: [42000](#)

Message: Can't create more than max_prepared_stmt_count statements (current value: %lu)
- Error number: [1462](#); Symbol: [ER_VIEW_RECUSIVE](#); SQLSTATE: [HY000](#)

Message: `%%`.%s` contains view recursion
- Error number: [1463](#); Symbol: [ER_NON_GROUPING_FIELD_USED](#); SQLSTATE: [42000](#)

Message: Non-grouping field '%s' is used in %s clause
- Error number: [1464](#); Symbol: [ER_TABLE_CANT_HANDLE_SPKEYS](#); SQLSTATE: [HY000](#)

Message: The used table type doesn't support SPATIAL indexes
- Error number: [1465](#); Symbol: [ER_NO_TRIGGER_ON_SYSTEM_SCHEMA](#); SQLSTATE: [HY000](#)

Message: Triggers can not be created on system tables
- Error number: [1466](#); Symbol: [ER_REMOVED_SPACES](#); SQLSTATE: [HY000](#)

Message: Leading spaces are removed from name '%s'
- Error number: [1467](#); Symbol: [ER_AUTOINC_READ_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to read auto-increment value from storage engine
- Error number: [1468](#); Symbol: [ER_USERNAME](#); SQLSTATE: [HY000](#)

Message: user name
- Error number: [1469](#); Symbol: [ER_HOSTNAME](#); SQLSTATE: [HY000](#)

Message: host name
- Error number: [1470](#); Symbol: [ER_WRONG_STRING_LENGTH](#); SQLSTATE: [HY000](#)

Message: String '%s' is too long for %s (should be no longer than %d)
- Error number: [1471](#); Symbol: [ER_NON_INSERTABLE_TABLE](#); SQLSTATE: [HY000](#)

Message: The target table %s of the %s is not insertable-into

- Error number: 1472; Symbol: `ER_ADMIN_WRONG_MRG_TABLE`; SQLSTATE: `HY000`

Message: Table '%s' is differently defined or of non-MyISAM type or doesn't exist
- Error number: 1473; Symbol: `ER_TOO_HIGH_LEVEL_OF_NESTING_FOR_SELECT`; SQLSTATE: `HY000`

Message: Too high level of nesting for select
- Error number: 1474; Symbol: `ER_NAME_BECOMES_EMPTY`; SQLSTATE: `HY000`

Message: Name '%s' has become "
- Error number: 1475; Symbol: `ER_AMBIGUOUS_FIELD_TERM`; SQLSTATE: `HY000`

Message: First character of the FIELDS TERMINATED string is ambiguous; please use non-optional and non-empty FIELDS ENCLOSED BY
- Error number: 1476; Symbol: `ER_FOREIGN_SERVER_EXISTS`; SQLSTATE: `HY000`

Message: The foreign server, %s, you are trying to create already exists.
- Error number: 1477; Symbol: `ER_FOREIGN_SERVER_DOESNT_EXIST`; SQLSTATE: `HY000`

Message: The foreign server name you are trying to reference does not exist. Data source error: %s
- Error number: 1478; Symbol: `ER_ILLEGAL_HA_CREATE_OPTION`; SQLSTATE: `HY000`

Message: Table storage engine '%s' does not support the create option '%s'
- Error number: 1479; Symbol: `ER_PARTITIONQUIRES_VALUES_ERROR`; SQLSTATE: `HY000`

Message: Syntax error: %s PARTITIONING requires definition of VALUES %s for each partition
- Error number: 1480; Symbol: `ER_PARTITION_WRONG_VALUES_ERROR`; SQLSTATE: `HY000`

Message: Only %s PARTITIONING can use VALUES %s in partition definition
- Error number: 1481; Symbol: `ER_PARTITION_MAXVALUE_ERROR`; SQLSTATE: `HY000`

Message: MAXVALUE can only be used in last partition definition
- Error number: 1482; Symbol: `ER_PARTITION_SUBPARTITION_ERROR`; SQLSTATE: `HY000`

Message: Subpartitions can only be hash partitions and by key
- Error number: 1483; Symbol: `ER_PARTITION_SUBPART_MIX_ERROR`; SQLSTATE: `HY000`

Message: Must define subpartitions on all partitions if on one partition
- Error number: 1484; Symbol: `ER_PARTITION_WRONG_NO_PART_ERROR`; SQLSTATE: `HY000`

Message: Wrong number of partitions defined, mismatch with previous setting
- Error number: 1485; Symbol: `ER_PARTITION_WRONG_NO_SUBPART_ERROR`; SQLSTATE: `HY000`

Message: Wrong number of subpartitions defined, mismatch with previous setting
- Error number: 1486; Symbol: `ER_WRONG_EXPR_IN_PARTITION_FUNC_ERROR`; SQLSTATE: `HY000`

Message: Constant, random or timezone-dependent expressions in (sub)partitioning function are not allowed

- Error number: [1487](#); Symbol: [ER_NO_CONST_EXPR_IN_RANGE_OR_LIST_ERROR](#); SQLSTATE: [HY000](#)

Message: Expression in RANGE/LIST VALUES must be constant
- Error number: [1488](#); Symbol: [ER_FIELD_NOT_FOUND_PART_ERROR](#); SQLSTATE: [HY000](#)

Message: Field in list of fields for partition function not found in table
- Error number: [1489](#); Symbol: [ER_LIST_OF_FIELDS_ONLY_IN_HASH_ERROR](#); SQLSTATE: [HY000](#)

Message: List of fields is only allowed in KEY partitions
- Error number: [1490](#); Symbol: [ER_INCONSISTENT_PARTITION_INFO_ERROR](#); SQLSTATE: [HY000](#)

Message: The partition info in the frm file is not consistent with what can be written into the frm file
- Error number: [1491](#); Symbol: [ER_PARTITION_FUNC_NOT_ALLOWED_ERROR](#); SQLSTATE: [HY000](#)

Message: The %s function returns the wrong type
- Error number: [1492](#); Symbol: [ER_PARTITIONS_MUST_BE_DEFINED_ERROR](#); SQLSTATE: [HY000](#)

Message: For %s partitions each partition must be defined
- Error number: [1493](#); Symbol: [ER_RANGE_NOT_INCREASING_ERROR](#); SQLSTATE: [HY000](#)

Message: VALUES LESS THAN value must be strictly increasing for each partition
- Error number: [1494](#); Symbol: [ER_INCONSISTENT_TYPE_OF_FUNCTIONS_ERROR](#); SQLSTATE: [HY000](#)

Message: VALUES value must be of same type as partition function
- Error number: [1495](#); Symbol: [ER_MULTIPLE_DEF_CONST_IN_LIST_PART_ERROR](#); SQLSTATE: [HY000](#)

Message: Multiple definition of same constant in list partitioning
- Error number: [1496](#); Symbol: [ER_PARTITION_ENTRY_ERROR](#); SQLSTATE: [HY000](#)

Message: Partitioning can not be used stand-alone in query
- Error number: [1497](#); Symbol: [ER_MIX_HANDLER_ERROR](#); SQLSTATE: [HY000](#)

Message: The mix of handlers in the partitions is not allowed in this version of MySQL
- Error number: [1498](#); Symbol: [ER_PARTITION_NOT_DEFINED_ERROR](#); SQLSTATE: [HY000](#)

Message: For the partitioned engine it is necessary to define all %s
- Error number: [1499](#); Symbol: [ER_TOO_MANY_PARTITIONS_ERROR](#); SQLSTATE: [HY000](#)

Message: Too many partitions (including subpartitions) were defined
- Error number: [1500](#); Symbol: [ER_SUBPARTITION_ERROR](#); SQLSTATE: [HY000](#)

Message: It is only possible to mix RANGE/LIST partitioning with HASH/KEY partitioning for subpartitioning
- Error number: [1501](#); Symbol: [ER_CANT_CREATE_HANDLER_FILE](#); SQLSTATE: [HY000](#)

Message: Failed to create specific handler file

-
- Error number: 1502; Symbol: `ER_BLOB_FIELD_IN_PART_FUNC_ERROR`; SQLSTATE: HY000
Message: A BLOB field is not allowed in partition function
 - Error number: 1503; Symbol: `ER_UNIQUE_KEY_NEED_ALL_FIELDS_IN_PF`; SQLSTATE: HY000
Message: A %s must include all columns in the table's partitioning function
 - Error number: 1504; Symbol: `ER_NO_PARTS_ERROR`; SQLSTATE: HY000
Message: Number of %s = 0 is not an allowed value
 - Error number: 1505; Symbol: `ER_PARTITION_MGMT_ON_NONPARTITIONED`; SQLSTATE: HY000
Message: Partition management on a not partitioned table is not possible
 - Error number: 1506; Symbol: `ER_FOREIGN_KEY_ON_PARTITIONED`; SQLSTATE: HY000
Message: Foreign keys are not yet supported in conjunction with partitioning
 - Error number: 1507; Symbol: `ER_DROP_PARTITION_NON_EXISTENT`; SQLSTATE: HY000
Message: Error in list of partitions to %s
 - Error number: 1508; Symbol: `ER_DROP_LAST_PARTITION`; SQLSTATE: HY000
Message: Cannot remove all partitions, use DROP TABLE instead
 - Error number: 1509; Symbol: `ER_COALESCE_ONLY_ON_HASH_PARTITION`; SQLSTATE: HY000
Message: COALESCE PARTITION can only be used on HASH/KEY partitions
 - Error number: 1510; Symbol: `ER_REORG_HASH_ONLY_ON_SAME_NO`; SQLSTATE: HY000
Message: REORGANIZE PARTITION can only be used to reorganize partitions not to change their numbers
 - Error number: 1511; Symbol: `ER_REORG_NO_PARAM_ERROR`; SQLSTATE: HY000
Message: REORGANIZE PARTITION without parameters can only be used on auto-partitioned tables using HASH PARTITIONS
 - Error number: 1512; Symbol: `ER_ONLY_ON_RANGE_LIST_PARTITION`; SQLSTATE: HY000
Message: %s PARTITION can only be used on RANGE/LIST partitions
 - Error number: 1513; Symbol: `ER_ADD_PARTITION_SUBPART_ERROR`; SQLSTATE: HY000
Message: Trying to Add partition(s) with wrong number of subpartitions
 - Error number: 1514; Symbol: `ER_ADD_PARTITION_NO_NEW_PARTITION`; SQLSTATE: HY000
Message: At least one partition must be added
 - Error number: 1515; Symbol: `ER_COALESCE_PARTITION_NO_PARTITION`; SQLSTATE: HY000
Message: At least one partition must be coalesced
 - Error number: 1516; Symbol: `ER_REORG_PARTITION_NOT_EXIST`; SQLSTATE: HY000
Message: More partitions to reorganize than there are partitions
 - Error number: 1517; Symbol: `ER_SAME_NAME_PARTITION`; SQLSTATE: HY000
Message: Duplicate partition name %s

- Error number: 1518; Symbol: `ER_NO_BINLOG_ERROR`; SQLSTATE: `HY000`

Message: It is not allowed to shut off binlog on this command
- Error number: 1519; Symbol: `ER_CONSECUTIVE_REORG_PARTITIONS`; SQLSTATE: `HY000`

Message: When reorganizing a set of partitions they must be in consecutive order
- Error number: 1520; Symbol: `ER_REORG_OUTSIDE_RANGE`; SQLSTATE: `HY000`

Message: Reorganize of range partitions cannot change total ranges except for last partition where it can extend the range
- Error number: 1521; Symbol: `ER_PARTITION_FUNCTION_FAILURE`; SQLSTATE: `HY000`

Message: Partition function not supported in this version for this handler
- Error number: 1522; Symbol: `ER_PART_STATE_ERROR`; SQLSTATE: `HY000`

Message: Partition state cannot be defined from CREATE/ALTER TABLE
- Error number: 1523; Symbol: `ER_LIMITED_PART_RANGE`; SQLSTATE: `HY000`

Message: The %s handler only supports 32 bit integers in VALUES
- Error number: 1524; Symbol: `ER_PLUGIN_IS_NOT_LOADED`; SQLSTATE: `HY000`

Message: Plugin '%s' is not loaded
- Error number: 1525; Symbol: `ER_WRONG_VALUE`; SQLSTATE: `HY000`

Message: Incorrect %s value: '%s'
- Error number: 1526; Symbol: `ER_NO_PARTITION_FOR_GIVEN_VALUE`; SQLSTATE: `HY000`

Message: Table has no partition for value %s
- Error number: 1527; Symbol: `ER_FILEGROUP_OPTION_ONLY_ONCE`; SQLSTATE: `HY000`

Message: It is not allowed to specify %s more than once
- Error number: 1528; Symbol: `ER_CREATE_FILEGROUP_FAILED`; SQLSTATE: `HY000`

Message: Failed to create %s
- Error number: 1529; Symbol: `ER_DROP_FILEGROUP_FAILED`; SQLSTATE: `HY000`

Message: Failed to drop %s
- Error number: 1530; Symbol: `ER_TABLESPACE_AUTO_EXTEND_ERROR`; SQLSTATE: `HY000`

Message: The handler doesn't support autoextend of tablespaces
- Error number: 1531; Symbol: `ER_WRONG_SIZE_NUMBER`; SQLSTATE: `HY000`

Message: A size parameter was incorrectly specified, either number or on the form 10M
- Error number: 1532; Symbol: `ER_SIZE_OVERFLOW_ERROR`; SQLSTATE: `HY000`

Message: The size number was correct but we don't allow the digit part to be more than 2 billion
- Error number: 1533; Symbol: `ER_ALTER_FILEGROUP_FAILED`; SQLSTATE: `HY000`

Message: Failed to alter: %s

- Error number: 1534; Symbol: `ER_BINLOG_ROW_LOGGING_FAILED`; SQLSTATE: HY000
Message: Writing one row to the row-based binary log failed
- Error number: 1535; Symbol: `ER_BINLOG_ROW_WRONG_TABLE_DEF`; SQLSTATE: HY000
Message: Table definition on master and slave does not match: %s
- Error number: 1536; Symbol: `ER_BINLOG_ROW_RBR_TO_SBR`; SQLSTATE: HY000
Message: Slave running with --log-slave-updates must use row-based binary logging to be able to replicate row-based binary log events
- Error number: 1537; Symbol: `ER_EVENT_ALREADY_EXISTS`; SQLSTATE: HY000
Message: Event '%s' already exists
- Error number: 1538; Symbol: `ER_EVENT_STORE_FAILED`; SQLSTATE: HY000
Message: Failed to store event %s. Error code %d from storage engine.
- Error number: 1539; Symbol: `ER_EVENT_DOES_NOT_EXIST`; SQLSTATE: HY000
Message: Unknown event '%s'
- Error number: 1540; Symbol: `ER_EVENT_CANT.Alter`; SQLSTATE: HY000
Message: Failed to alter event '%s'
- Error number: 1541; Symbol: `ER_EVENT_DROP_FAILED`; SQLSTATE: HY000
Message: Failed to drop %s
- Error number: 1542; Symbol: `ER_EVENT_INTERVAL_NOT_POSITIVE_OR_TOO_BIG`; SQLSTATE: HY000
Message: INTERVAL is either not positive or too big
- Error number: 1543; Symbol: `ER_EVENT_ENDS_BEFORE_STARTS`; SQLSTATE: HY000
Message: ENDS is either invalid or before STARTS
- Error number: 1544; Symbol: `ER_EVENT_EXEC_TIME_IN_THE_PAST`; SQLSTATE: HY000
Message: Event execution time is in the past. Event has been disabled
- Error number: 1545; Symbol: `ER_EVENT_OPEN_TABLE_FAILED`; SQLSTATE: HY000
Message: Failed to open mysql.event
- Error number: 1546; Symbol: `ER_EVENT_NEITHER_M_EXPR_NOR_M_AT`; SQLSTATE: HY000
Message: No datetime expression provided
- Error number: 1547; Symbol: `ER_OBSOLETE_COL_COUNT_DOESNT_MATCH_CORRUPTED`; SQLSTATE: HY000
Message: Column count of mysql.%s is wrong. Expected %d, found %d. The table is probably corrupted
- Error number: 1548; Symbol: `ER_OBSOLETE_CANNOT_LOAD_FROM_TABLE`; SQLSTATE: HY000
Message: Cannot load from mysql.%s. The table is probably corrupted
- Error number: 1549; Symbol: `ER_EVENT_CANNOT_DELETE`; SQLSTATE: HY000

Message: Failed to delete the event from mysql.event

- Error number: 1550; Symbol: ER_EVENT_COMPILE_ERROR; SQLSTATE: HY000

Message: Error during compilation of event's body

- Error number: 1551; Symbol: ER_EVENT_SAME_NAME; SQLSTATE: HY000

Message: Same old and new event name

- Error number: 1552; Symbol: ER_EVENT_DATA_TOO_LONG; SQLSTATE: HY000

Message: Data for column '%s' too long

- Error number: 1553; Symbol: ER_DROP_INDEX_FK; SQLSTATE: HY000

Message: Cannot drop index '%s': needed in a foreign key constraint

InnoDB reports this error when you attempt to drop the last index that can enforce a particular referential constraint.

For optimal performance with DML statements, InnoDB requires an index to exist on [foreign key](#) columns, so that [UPDATE](#) and [DELETE](#) operations on a [parent table](#) can easily check whether corresponding rows exist in the [child table](#). MySQL creates or drops such indexes automatically when needed, as a side-effect of [CREATE TABLE](#), [CREATE INDEX](#), and [ALTER TABLE](#) statements.

When you drop an index, InnoDB checks if the index is used for checking a foreign key constraint. It is still OK to drop the index if there is another index that can be used to enforce the same constraint. InnoDB prevents you from dropping the last index that can enforce a particular referential constraint.

- Error number: 1554; Symbol: ER_WARN_DEPRECATED_SYNTAX_WITH_VER; SQLSTATE: HY000

Message: The syntax '%s' is deprecated and will be removed in MySQL %s. Please use %s instead

- Error number: 1555; Symbol: ER_CANT_WRITE_LOCK_LOG_TABLE; SQLSTATE: HY000

Message: You can't write-lock a log table. Only read access is possible

- Error number: 1556; Symbol: ER_CANT_LOCK_LOG_TABLE; SQLSTATE: HY000

Message: You can't use locks with log tables.

- Error number: 1557; Symbol: ER_FOREIGN_DUPLICATE_KEY_OLD_UNUSED; SQLSTATE: 23000

Message: Upholding foreign key constraints for table '%s', entry '%s', key %d would lead to a duplicate entry

- Error number: 1558; Symbol: ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE; SQLSTATE: HY000

Message: Column count of mysql.%s is wrong. Expected %d, found %d. Created with MySQL %d, now running %d. Please use mysql_upgrade to fix this error.

- Error number: 1559; Symbol: ER_TEMP_TABLE_PREVENTS_SWITCH_OUT_OF_RBR; SQLSTATE: HY000

Message: Cannot switch out of the row-based binary log format when the session has open temporary tables

- Error number: 1560; Symbol: ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_FORMAT; SQLSTATE: HY000

Message: Cannot change the binary logging format inside a stored function or trigger

-
- Error number: [1561](#); Symbol: [ER_NDB_CANT_SWITCH_BINLOG_FORMAT](#); SQLSTATE: [HY000](#)
Message: The NDB cluster engine does not support changing the binlog format on the fly yet
 - Error number: [1562](#); Symbol: [ER_PARTITION_NO_TEMPORARY](#); SQLSTATE: [HY000](#)
Message: Cannot create temporary table with partitions
 - Error number: [1563](#); Symbol: [ER_PARTITION_CONST_DOMAIN_ERROR](#); SQLSTATE: [HY000](#)
Message: Partition constant is out of partition function domain
 - Error number: [1564](#); Symbol: [ER_PARTITION_FUNCTION_IS_NOT_ALLOWED](#); SQLSTATE: [HY000](#)
Message: This partition function is not allowed
 - Error number: [1565](#); Symbol: [ER_DDL_LOG_ERROR](#); SQLSTATE: [HY000](#)
Message: Error in DDL log
 - Error number: [1566](#); Symbol: [ER_NULL_IN_VALUES_LESS_THAN](#); SQLSTATE: [HY000](#)
Message: Not allowed to use NULL value in VALUES LESS THAN
 - Error number: [1567](#); Symbol: [ER_WRONG_PARTITION_NAME](#); SQLSTATE: [HY000](#)
Message: Incorrect partition name
 - Error number: [1568](#); Symbol: [ER_CANT_CHANGE_TX_CHARACTERISTICS](#); SQLSTATE: [25001](#)
Message: Transaction characteristics can't be changed while a transaction is in progress
 - Error number: [1569](#); Symbol: [ER_DUP_ENTRY_AUTOINCREMENT_CASE](#); SQLSTATE: [HY000](#)
Message: ALTER TABLE causes auto_increment resequencing, resulting in duplicate entry '%s' for key '%s'
 - Error number: [1570](#); Symbol: [ER_EVENT MODIFY_QUEUE_ERROR](#); SQLSTATE: [HY000](#)
Message: Internal scheduler error %d
 - Error number: [1571](#); Symbol: [ER_EVENT_SET_VAR_ERROR](#); SQLSTATE: [HY000](#)
Message: Error during starting/stopping of the scheduler. Error code %u
 - Error number: [1572](#); Symbol: [ER_PARTITION_MERGE_ERROR](#); SQLSTATE: [HY000](#)
Message: Engine cannot be used in partitioned tables
 - Error number: [1573](#); Symbol: [ER_CANT_ACTIVATE_LOG](#); SQLSTATE: [HY000](#)
Message: Cannot activate '%s' log
 - Error number: [1574](#); Symbol: [ER_RBR_NOT_AVAILABLE](#); SQLSTATE: [HY000](#)
Message: The server was not built with row-based replication
 - Error number: [1575](#); Symbol: [ER_BASE64_DECODE_ERROR](#); SQLSTATE: [HY000](#)
Message: Decoding of base64 string failed
 - Error number: [1576](#); Symbol: [ER_EVENT_RECUSION_FORBIDDEN](#); SQLSTATE: [HY000](#)
Message: Recursion of EVENT DDL statements is forbidden when body is present

- Error number: 1577; Symbol: [ER_EVENTS_DB_ERROR](#); SQLSTATE: HY000

Message: Cannot proceed because system tables used by Event Scheduler were found damaged at server start

To address this issue, try running `mysql_upgrade`.
- Error number: 1578; Symbol: [ER_ONLY_INTEGERS_ALLOWED](#); SQLSTATE: HY000

Message: Only integers allowed as number here
- Error number: 1579; Symbol: [ER_UNSUPORTED_LOG_ENGINE](#); SQLSTATE: HY000

Message: This storage engine cannot be used for log tables"
- Error number: 1580; Symbol: [ER_BAD_LOG_STATEMENT](#); SQLSTATE: HY000

Message: You cannot '%s' a log table if logging is enabled
- Error number: 1581; Symbol: [ER_CANT_RENAME_LOG_TABLE](#); SQLSTATE: HY000

Message: Cannot rename '%s'. When logging enabled, rename to/from log table must rename two tables: the log table to an archive table and another table back to '%s'
- Error number: 1582; Symbol: [ER_WRONG_PARAMCOUNT_TO_NATIVE_FCT](#); SQLSTATE: 42000

Message: Incorrect parameter count in the call to native function '%s'
- Error number: 1583; Symbol: [ER_WRONG_PARAMETERS_TO_NATIVE_FCT](#); SQLSTATE: 42000

Message: Incorrect parameters in the call to native function '%s'
- Error number: 1584; Symbol: [ER_WRONG_PARAMETERS_TO_STORED_FCT](#); SQLSTATE: 42000

Message: Incorrect parameters in the call to stored function %s
- Error number: 1585; Symbol: [ER_NATIVE_FCT_NAME_COLLISION](#); SQLSTATE: HY000

Message: This function '%s' has the same name as a native function
- Error number: 1586; Symbol: [ER_DUP_ENTRY_WITH_KEY_NAME](#); SQLSTATE: 23000

Message: Duplicate entry '%s' for key '%s'

The format string for this error is also used with [ER_DUP_ENTRY](#).
- Error number: 1587; Symbol: [ER_BINLOG_PURGE_EMFILE](#); SQLSTATE: HY000

Message: Too many files opened, please execute the command again
- Error number: 1588; Symbol: [ER_EVENT_CANNOT_CREATE_IN_THE_PAST](#); SQLSTATE: HY000

Message: Event execution time is in the past and ON COMPLETION NOT PRESERVE is set. The event was dropped immediately after creation.
- Error number: 1589; Symbol: [ER_EVENT_CANNOT_ALTER_IN_THE_PAST](#); SQLSTATE: HY000

Message: Event execution time is in the past and ON COMPLETION NOT PRESERVE is set. The event was not changed. Specify a time in the future.
- Error number: 1590; Symbol: [ER_SLAVE INCIDENT](#); SQLSTATE: HY000

Message: The incident %s occurred on the master. Message: %s

-
- Error number: [1591](#); Symbol: [ER_NO_PARTITION_FOR_GIVEN_VALUE_SILENT](#); SQLSTATE: [HY000](#)

Message: Table has no partition for some existing values
 - Error number: [1592](#); Symbol: [ER_BINLOG_UNSAFE_STATEMENT](#); SQLSTATE: [HY000](#)

Message: Unsafe statement written to the binary log using statement format since BINLOG_FORMAT = STATEMENT. %s
 - Error number: [1593](#); Symbol: [ER_SLAVE_FATAL_ERROR](#); SQLSTATE: [HY000](#)

Message: Fatal error: %s
 - Error number: [1594](#); Symbol: [ER_SLAVE_RELAY_LOG_READ_FAILURE](#); SQLSTATE: [HY000](#)

Message: Relay log read failure: %s
 - Error number: [1595](#); Symbol: [ER_SLAVE_RELAY_LOG_WRITE_FAILURE](#); SQLSTATE: [HY000](#)

Message: Relay log write failure: %s
 - Error number: [1596](#); Symbol: [ER_SLAVE_CREATE_EVENT_FAILURE](#); SQLSTATE: [HY000](#)

Message: Failed to create %s
 - Error number: [1597](#); Symbol: [ER_SLAVE_MASTER_COM_FAILURE](#); SQLSTATE: [HY000](#)

Message: Master command %s failed: %s
 - Error number: [1598](#); Symbol: [ER_BINLOG_LOGGING_IMPOSSIBLE](#); SQLSTATE: [HY000](#)

Message: Binary logging not possible. Message: %s
 - Error number: [1599](#); Symbol: [ER_VIEW_NO_CREATION_CTX](#); SQLSTATE: [HY000](#)

Message: View `'%s`.`%s` has no creation context
 - Error number: [1600](#); Symbol: [ER_VIEW_INVALID_CREATION_CTX](#); SQLSTATE: [HY000](#)

Message: Creation context of view `'%s`.`%s' is invalid
 - Error number: [1601](#); Symbol: [ER_SR_INVALID_CREATION_CTX](#); SQLSTATE: [HY000](#)

Message: Creation context of stored routine `'%s`.`%s` is invalid
 - Error number: [1602](#); Symbol: [ER_TRG_CORRUPTED_FILE](#); SQLSTATE: [HY000](#)

Message: Corrupted TRG file for table `'%s`.`%s`
 - Error number: [1603](#); Symbol: [ER_TRG_NO_CREATION_CTX](#); SQLSTATE: [HY000](#)

Message: Triggers for table `'%s`.`%s` have no creation context
 - Error number: [1604](#); Symbol: [ER_TRG_INVALID_CREATION_CTX](#); SQLSTATE: [HY000](#)

Message: Trigger creation context of table `'%s`.`%s` is invalid
 - Error number: [1605](#); Symbol: [ER_EVENT_INVALID_CREATION_CTX](#); SQLSTATE: [HY000](#)

Message: Creation context of event `'%s`.`%s` is invalid
 - Error number: [1606](#); Symbol: [ER_TRG_CANT_OPEN_TABLE](#); SQLSTATE: [HY000](#)

Message: Cannot open table for trigger `'%s`.`%s`

- Error number: [1607](#); Symbol: [ER_CANT_CREATE_ROUTINE](#); SQLSTATE: [HY000](#)
Message: Cannot create stored routine `'%s`. Check warnings
- Error number: [1608](#); Symbol: [ER_NEVER_USED](#); SQLSTATE: [HY000](#)
Message: Ambiguous slave modes combination. %s
- Error number: [1609](#); Symbol:
[ER_NO_FORMAT_DESCRIPTION_EVENT_BEFORE_BINLOG_STATEMENT](#); SQLSTATE: [HY000](#)
Message: The BINLOG statement of type `'%s` was not preceded by a format description BINLOG statement.
- Error number: [1610](#); Symbol: [ER_SLAVE_CORRUPT_EVENT](#); SQLSTATE: [HY000](#)
Message: Corrupted replication event was detected
- Error number: [1611](#); Symbol: [ER_LOAD_DATA_INVALID_COLUMN](#); SQLSTATE: [HY000](#)
Message: Invalid column reference (%s) in LOAD DATA
[ER_LOAD_DATA_INVALID_COLUMN](#) was removed after 5.7.7.
- Error number: [1611](#); Symbol: [ER_LOAD_DATA_INVALID_COLUMN_UNUSED](#); SQLSTATE: [HY000](#)
Message: Invalid column reference (%s) in LOAD DATA
[ER_LOAD_DATA_INVALID_COLUMN_UNUSED](#) was added in 5.7.8.
- Error number: [1612](#); Symbol: [ER_LOG_PURGE_NO_FILE](#); SQLSTATE: [HY000](#)
Message: Being purged log %s was not found
- Error number: [1613](#); Symbol: [ER_XA_RBTIMEOUT](#); SQLSTATE: [XA106](#)
Message: XA_RBTIMEOUT: Transaction branch was rolled back: took too long
- Error number: [1614](#); Symbol: [ER_XA_RBDEADLOCK](#); SQLSTATE: [XA102](#)
Message: XA_RBDEADLOCK: Transaction branch was rolled back: deadlock was detected
- Error number: [1615](#); Symbol: [ER_NEED_REPREPARE](#); SQLSTATE: [HY000](#)
Message: Prepared statement needs to be re-prepared
- Error number: [1616](#); Symbol: [ER_DELAYED_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)
Message: DELAYED option not supported for table '%s'
- Error number: [1617](#); Symbol: [WARN_NO_MASTER_INFO](#); SQLSTATE: [HY000](#)
Message: The master info structure does not exist
- Error number: [1618](#); Symbol: [WARN_OPTION_IGNORED](#); SQLSTATE: [HY000](#)
Message: <%s> option ignored
- Error number: [1619](#); Symbol: [WARN_PLUGIN_DELETE_BUILTIN](#); SQLSTATE: [HY000](#)
Message: Built-in plugins cannot be deleted
[WARN_PLUGIN_DELETE_BUILTIN](#) was removed after 5.7.4.
- Error number: [1619](#); Symbol: [ER_PLUGIN_DELETE_BUILTIN](#); SQLSTATE: [HY000](#)

Message: Built-in plugins cannot be deleted

`ER_PLUGIN_DELETE_BUILTIN` was added in 5.7.5.

- Error number: `1620`; Symbol: `WARN_PLUGIN_BUSY`; SQLSTATE: `HY000`

Message: Plugin is busy and will be uninstalled on shutdown

- Error number: `1621`; Symbol: `ER_VARIABLE_IS_READONLY`; SQLSTATE: `HY000`

Message: %s variable '%s' is read-only. Use SET %s to assign the value

- Error number: `1622`; Symbol: `ER_WARN_ENGINE_TRANSACTION_ROLLBACK`; SQLSTATE: `HY000`

Message: Storage engine %s does not support rollback for this statement. Transaction rolled back and must be restarted

- Error number: `1623`; Symbol: `ER_SLAVE_HEARTBEAT_FAILURE`; SQLSTATE: `HY000`

Message: Unexpected master's heartbeat data: %s

- Error number: `1624`; Symbol: `ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE`; SQLSTATE: `HY000`

Message: The requested value for the heartbeat period is either negative or exceeds the maximum allowed (%s seconds).

- Error number: `1625`; Symbol: `ER_NDB_REPLICATION_SCHEMA_ERROR`; SQLSTATE: `HY000`

Message: Bad schema for mysql.ndb_replication table. Message: %s

- Error number: `1626`; Symbol: `ER_CONFLICT_FN_PARSE_ERROR`; SQLSTATE: `HY000`

Message: Error in parsing conflict function. Message: %s

- Error number: `1627`; Symbol: `ER_EXCEPTIONS_WRITE_ERROR`; SQLSTATE: `HY000`

Message: Write to exceptions table failed. Message: %s"

- Error number: `1628`; Symbol: `ER_TOO_LONG_TABLE_COMMENT`; SQLSTATE: `HY000`

Message: Comment for table '%s' is too long (max = %lu)

- Error number: `1629`; Symbol: `ER_TOO_LONG_FIELD_COMMENT`; SQLSTATE: `HY000`

Message: Comment for field '%s' is too long (max = %lu)

- Error number: `1630`; Symbol: `ER_FUNC_INEXISTENT_NAME_COLLISION`; SQLSTATE: `42000`

Message: FUNCTION %s does not exist. Check the 'Function Name Parsing and Resolution' section in the Reference Manual

- Error number: `1631`; Symbol: `ER_DATABASE_NAME`; SQLSTATE: `HY000`

Message: Database

- Error number: `1632`; Symbol: `ER_TABLE_NAME`; SQLSTATE: `HY000`

Message: Table

- Error number: `1633`; Symbol: `ER_PARTITION_NAME`; SQLSTATE: `HY000`

Message: Partition

- Error number: [1634](#); Symbol: [ER_SUBPARTITION_NAME](#); SQLSTATE: [HY000](#)
Message: Subpartition
- Error number: [1635](#); Symbol: [ER_TEMPORARY_NAME](#); SQLSTATE: [HY000](#)
Message: Temporary
- Error number: [1636](#); Symbol: [ER_RENAMED_NAME](#); SQLSTATE: [HY000](#)
Message: Renamed
- Error number: [1637](#); Symbol: [ER_TOO_MANY_CONCURRENT_TRXS](#); SQLSTATE: [HY000](#)
Message: Too many active concurrent transactions
- Error number: [1638](#); Symbol: [WARN_NON_ASCII_SEPARATOR_NOT_IMPLEMENTED](#); SQLSTATE: [HY000](#)
Message: Non-ASCII separator arguments are not fully supported
- Error number: [1639](#); Symbol: [ER_DEBUG_SYNC_TIMEOUT](#); SQLSTATE: [HY000](#)
Message: debug sync point wait timed out
- Error number: [1640](#); Symbol: [ER_DEBUG_SYNC_HIT_LIMIT](#); SQLSTATE: [HY000](#)
Message: debug sync point hit limit reached
- Error number: [1641](#); Symbol: [ER_DUP_SIGNAL_SET](#); SQLSTATE: [42000](#)
Message: Duplicate condition information item '%s'
- Error number: [1642](#); Symbol: [ER_SIGNAL_WARN](#); SQLSTATE: [01000](#)
Message: Unhandled user-defined warning condition
- Error number: [1643](#); Symbol: [ER_SIGNAL_NOT_FOUND](#); SQLSTATE: [02000](#)
Message: Unhandled user-defined not found condition
- Error number: [1644](#); Symbol: [ER_SIGNAL_EXCEPTION](#); SQLSTATE: [HY000](#)
Message: Unhandled user-defined exception condition
- Error number: [1645](#); Symbol: [ER_RESIGNAL_WITHOUT_ACTIVE_HANDLER](#); SQLSTATE: [0K000](#)
Message: RESIGNAL when handler not active
- Error number: [1646](#); Symbol: [ER_SIGNAL_BAD_CONDITION_TYPE](#); SQLSTATE: [HY000](#)
Message: SIGNAL/RESIGNAL can only use a CONDITION defined with SQLSTATE
- Error number: [1647](#); Symbol: [WARN_COND_ITEM_TRUNCATED](#); SQLSTATE: [HY000](#)
Message: Data truncated for condition item '%s'
- Error number: [1648](#); Symbol: [ER_COND_ITEM_TOO_LONG](#); SQLSTATE: [HY000](#)
Message: Data too long for condition item '%s'
- Error number: [1649](#); Symbol: [ER_UNKNOWN_LOCALE](#); SQLSTATE: [HY000](#)
Message: Unknown locale: '%s'

- Error number: [1650](#); Symbol: [ER_SLAVE_IGNORE_SERVER_IDS](#); SQLSTATE: [HY000](#)

Message: The requested server id %d clashes with the slave startup option --replicate-same-server-id
- Error number: [1651](#); Symbol: [ER_QUERY_CACHE_DISABLED](#); SQLSTATE: [HY000](#)

Message: Query cache is disabled; restart the server with query_cache_type=1 to enable it
- Error number: [1652](#); Symbol: [ER_SAME_NAME_PARTITION_FIELD](#); SQLSTATE: [HY000](#)

Message: Duplicate partition field name '%s'
- Error number: [1653](#); Symbol: [ER_PARTITION_COLUMN_LIST_ERROR](#); SQLSTATE: [HY000](#)

Message: Inconsistency in usage of column lists for partitioning
- Error number: [1654](#); Symbol: [ER_WRONG_TYPE_COLUMN_VALUE_ERROR](#); SQLSTATE: [HY000](#)

Message: Partition column values of incorrect type
- Error number: [1655](#); Symbol: [ER_TOO_MANY_PARTITION_FUNC_FIELDS_ERROR](#); SQLSTATE: [HY000](#)

Message: Too many fields in '%s'
- Error number: [1656](#); Symbol: [ER_MAXVALUE_IN_VALUES_IN](#); SQLSTATE: [HY000](#)

Message: Cannot use MAXVALUE as value in VALUES IN
- Error number: [1657](#); Symbol: [ER_TOO_MANY_VALUES_ERROR](#); SQLSTATE: [HY000](#)

Message: Cannot have more than one value for this type of %s partitioning
- Error number: [1658](#); Symbol: [ER_ROW_SINGLE_PARTITION_FIELD_ERROR](#); SQLSTATE: [HY000](#)

Message: Row expressions in VALUES IN only allowed for multi-field column partitioning
- Error number: [1659](#); Symbol: [ER_FIELD_TYPE_NOT_ALLOWED_AS_PARTITION_FIELD](#); SQLSTATE: [HY000](#)

Message: Field '%s' is of a not allowed type for this type of partitioning
- Error number: [1660](#); Symbol: [ER_PARTITION_FIELDS_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: The total length of the partitioning fields is too large
- Error number: [1661](#); Symbol: [ER_BINLOG_ROW_ENGINE_AND_STMT_ENGINE](#); SQLSTATE: [HY000](#)

Message: Cannot execute statement: impossible to write to binary log since both row-incapable engines and statement-incapable engines are involved.
- Error number: [1662](#); Symbol: [ER_BINLOG_ROW_MODE_AND_STMT_ENGINE](#); SQLSTATE: [HY000](#)

Message: Cannot execute statement: impossible to write to binary log since BINLOG_FORMAT = ROW and at least one table uses a storage engine limited to statement-based logging.
- Error number: [1663](#); Symbol: [ER_BINLOG_UNSAFE_AND_STMT_ENGINE](#); SQLSTATE: [HY000](#)

Message: Cannot execute statement: impossible to write to binary log since statement is unsafe, storage engine is limited to statement-based logging, and BINLOG_FORMAT = MIXED. %s
- Error number: [1664](#); Symbol: [ER_BINLOG_ROW_INJECTION_AND_STMT_ENGINE](#); SQLSTATE: [HY000](#)

Message: Cannot execute statement: impossible to write to binary log since statement is unsafe, storage engine is limited to statement-based logging, and BINLOG_FORMAT = MIXED. %s

Message: Cannot execute statement: impossible to write to binary log since statement is in row format and at least one table uses a storage engine limited to statement-based logging.

- Error number: [1665](#); Symbol: [ER_BINLOG_STMT_MODE_AND_ROW_ENGINE](#); SQLSTATE: [HY000](#)

Message: Cannot execute statement: impossible to write to binary log since BINLOG_FORMAT = STATEMENT and at least one table uses a storage engine limited to row-based logging.%s

- Error number: [1666](#); Symbol: [ER_BINLOG_ROW_INJECTION_AND_STMT_MODE](#); SQLSTATE: [HY000](#)

Message: Cannot execute statement: impossible to write to binary log since statement is in row format and BINLOG_FORMAT = STATEMENT.

- Error number: [1667](#); Symbol: [ER_BINLOG_MULTIPLE_ENGINES_AND_SELF_LOGGING_ENGINE](#); SQLSTATE: [HY000](#)

Message: Cannot execute statement: impossible to write to binary log since more than one engine is involved and at least one engine is self-logging.

- Error number: [1668](#); Symbol: [ER_BINLOG_UNSAFE_LIMIT](#); SQLSTATE: [HY000](#)

Message: The statement is unsafe because it uses a LIMIT clause. This is unsafe because the set of rows included cannot be predicted.

- Error number: [1669](#); Symbol: [ER_UNUSED4](#); SQLSTATE: [HY000](#)

Message: The statement is unsafe because it uses INSERT DELAYED. This is unsafe because the times when rows are inserted cannot be predicted.

- Error number: [1670](#); Symbol: [ER_BINLOG_UNSAFE_SYSTEM_TABLE](#); SQLSTATE: [HY000](#)

Message: The statement is unsafe because it uses the general log, slow query log, or performance_schema table(s). This is unsafe because system tables may differ on slaves.

- Error number: [1671](#); Symbol: [ER_BINLOG_UNSAFE_AUTOINC_COLUMNS](#); SQLSTATE: [HY000](#)

Message: Statement is unsafe because it invokes a trigger or a stored function that inserts into an AUTO_INCREMENT column. Inserted values cannot be logged correctly.

- Error number: [1672](#); Symbol: [ER_BINLOG_UNSAFE_UDF](#); SQLSTATE: [HY000](#)

Message: Statement is unsafe because it uses a UDF which may not return the same value on the slave.

- Error number: [1673](#); Symbol: [ER_BINLOG_UNSAFE_SYSTEM_VARIABLE](#); SQLSTATE: [HY000](#)

Message: Statement is unsafe because it uses a system variable that may have a different value on the slave.

- Error number: [1674](#); Symbol: [ER_BINLOG_UNSAFE_SYSTEM_FUNCTION](#); SQLSTATE: [HY000](#)

Message: Statement is unsafe because it uses a system function that may return a different value on the slave.

- Error number: [1675](#); Symbol: [ER_BINLOG_UNSAFE_NONTRANS_AFTER_TRANS](#); SQLSTATE: [HY000](#)

Message: Statement is unsafe because it accesses a non-transactional table after accessing a transactional table within the same transaction.

- Error number: [1676](#); Symbol: [ER_MESSAGE_AND_STATEMENT](#); SQLSTATE: [HY000](#)

Message: %s Statement: %s

- Error number: [1677](#); Symbol: [ER_SLAVE_CONVERSION_FAILED](#); SQLSTATE: [HY000](#)

Message: Column %d of table '%s.%s' cannot be converted from type '%s' to type '%s'

- Error number: [1678](#); Symbol: [ER_SLAVE_CANT_CREATE_CONVERSION](#); SQLSTATE: [HY000](#)

Message: Can't create conversion table for table '%s.%s'

- Error number: [1679](#); Symbol: [ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG_FORMAT](#); SQLSTATE: [HY000](#)

Message: Cannot modify @@session.binlog_format inside a transaction

- Error number: [1680](#); Symbol: [ER_PATH_LENGTH](#); SQLSTATE: [HY000](#)

Message: The path specified for %s is too long.

- Error number: [1681](#); Symbol: [ER_WARN_DEPRECATED_SYNTAX_NO_REPLACEMENT](#); SQLSTATE: [HY000](#)

Message: '%s' is deprecated and will be removed in a future release.

- Error number: [1682](#); Symbol: [ER_WRONG_NATIVE_TABLE_STRUCTURE](#); SQLSTATE: [HY000](#)

Message: Native table '%s'.'%s' has the wrong structure

- Error number: [1683](#); Symbol: [ER_WRONG_PERFSCHEMA_USAGE](#); SQLSTATE: [HY000](#)

Message: Invalid performance_schema usage.

- Error number: [1684](#); Symbol: [ER_WARN_I_S_SKIPPED_TABLE](#); SQLSTATE: [HY000](#)

Message: Table '%s'.'%s' was skipped since its definition is being modified by concurrent DDL statement

- Error number: [1685](#); Symbol: [ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG_DIRECT](#); SQLSTATE: [HY000](#)

Message: Cannot modify @@session.binlog_direct_non_transactional_updates inside a transaction

- Error number: [1686](#); Symbol: [ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_DIRECT](#); SQLSTATE: [HY000](#)

Message: Cannot change the binlog direct flag inside a stored function or trigger

- Error number: [1687](#); Symbol: [ER_SPATIAL_MUST_HAVE_GEOM_COL](#); SQLSTATE: [42000](#)

Message: A SPATIAL index may only contain a geometrical type column

- Error number: [1688](#); Symbol: [ER_TOO_LONG_INDEX_COMMENT](#); SQLSTATE: [HY000](#)

Message: Comment for index '%s' is too long (max = %lu)

- Error number: [1689](#); Symbol: [ER_LOCK_ABORTED](#); SQLSTATE: [HY000](#)

Message: Wait on a lock was aborted due to a pending exclusive lock

- Error number: [1690](#); Symbol: [ER_DATA_OUT_OF_RANGE](#); SQLSTATE: [22003](#)

Message: %s value is out of range in '%s'

- Error number: [1691](#); Symbol: [ER_WRONG_SPVAR_TYPE_IN_LIMIT](#); SQLSTATE: [HY000](#)

Message: A variable of a non-integer based type in LIMIT clause

- Error number: 1692; Symbol: `ER_BINLOG_UNSAFE_MULTIPLE_ENGINES_AND_SELF_LOGGING_ENGINE`; SQLSTATE: HY000

Message: Mixing self-logging and non-self-logging engines in a statement is unsafe.

- Error number: 1693; Symbol: `ER_BINLOG_UNSAFE_MIXED_STATEMENT`; SQLSTATE: HY000

Message: Statement accesses nontransactional table as well as transactional or temporary table, and writes to any of them.

- Error number: 1694; Symbol: `ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_SQL_LOG_BIN`; SQLSTATE: HY000

Message: Cannot modify @@session.sql_log_bin inside a transaction

- Error number: 1695; Symbol: `ER_STORED_FUNCTION_PREVENTS_SWITCH_SQL_LOG_BIN`; SQLSTATE: HY000

Message: Cannot change the sql_log_bin inside a stored function or trigger

- Error number: 1696; Symbol: `ER_FAILED_READ_FROM_PAR_FILE`; SQLSTATE: HY000

Message: Failed to read from the .par file

- Error number: 1697; Symbol: `ER_VALUES_IS_NOT_INT_TYPE_ERROR`; SQLSTATE: HY000

Message: VALUES value for partition '%s' must have type INT

- Error number: 1698; Symbol: `ER_ACCESS_DENIED_NO_PASSWORD_ERROR`; SQLSTATE: 28000

Message: Access denied for user '%s'@'%s'

- Error number: 1699; Symbol: `ER_SET_PASSWORD_AUTH_PLUGIN`; SQLSTATE: HY000

Message: SET PASSWORD has no significance for users authenticating via plugins

- Error number: 1700; Symbol: `ER_GRANT_PLUGIN_USER_EXISTS`; SQLSTATE: HY000

Message: GRANT with IDENTIFIED WITH is illegal because the user %-.*s already exists

- Error number: 1701; Symbol: `ER_TRUNCATE_ILLEGAL_FK`; SQLSTATE: 42000

Message: Cannot truncate a table referenced in a foreign key constraint (%s)

- Error number: 1702; Symbol: `ER_PLUGIN_IS_PERMANENT`; SQLSTATE: HY000

Message: Plugin '%s' is force_plus_permanent and can not be unloaded

- Error number: 1703; Symbol: `ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE_MIN`; SQLSTATE: HY000

Message: The requested value for the heartbeat period is less than 1 millisecond. The value is reset to 0, meaning that heartbeating will effectively be disabled.

- Error number: 1704; Symbol: `ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE_MAX`; SQLSTATE: HY000

Message: The requested value for the heartbeat period exceeds the value of `slave_net_timeout` seconds. A sensible value for the period should be less than the timeout.

- Error number: 1705; Symbol: `ER_STMT_CACHE_FULL`; SQLSTATE: HY000

Message: Multi-row statements required more than 'max_binlog_stmt_cache_size' bytes of storage; increase this mysqld variable and try again

- Error number: [1706](#); Symbol: [ER_MULTI_UPDATE_KEY_CONFLICT](#); SQLSTATE: [HY000](#)

Message: Primary key/partition key update is not allowed since the table is updated both as '%s' and '%s'.

- Error number: [1707](#); Symbol: [ER_TABLE_NEEDS_REBUILD](#); SQLSTATE: [HY000](#)

Message: Table rebuild required. Please do "ALTER TABLE `'%s` FORCE" or dump/reload to fix it!

- Error number: [1708](#); Symbol: [WARN_OPTION_BELOW_LIMIT](#); SQLSTATE: [HY000](#)

Message: The value of '%s' should be no less than the value of '%s'

- Error number: [1709](#); Symbol: [ER_INDEX_COLUMN_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: Index column size too large. The maximum column size is %lu bytes.

- Error number: [1710](#); Symbol: [ER_ERROR_IN_TRIGGER_BODY](#); SQLSTATE: [HY000](#)

Message: Trigger '%s' has an error in its body: '%s'

- Error number: [1711](#); Symbol: [ER_ERROR_IN_UNKNOWN_TRIGGER_BODY](#); SQLSTATE: [HY000](#)

Message: Unknown trigger has an error in its body: '%s'

- Error number: [1712](#); Symbol: [ER_INDEX_CORRUPT](#); SQLSTATE: [HY000](#)

Message: Index %s is corrupted

- Error number: [1713](#); Symbol: [ER_UNDO_RECORD_TOO_BIG](#); SQLSTATE: [HY000](#)

Message: Undo log record is too big.

- Error number: [1714](#); Symbol: [ER_BINLOG_UNSAFE_INSERT_IGNORE_SELECT](#); SQLSTATE: [HY000](#)

Message: INSERT IGNORE... SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are ignored. This order cannot be predicted and may differ on master and the slave.

- Error number: [1715](#); Symbol: [ER_BINLOG_UNSAFE_INSERT_SELECT_UPDATE](#); SQLSTATE: [HY000](#)

Message: INSERT... SELECT... ON DUPLICATE KEY UPDATE is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are updated. This order cannot be predicted and may differ on master and the slave.

- Error number: [1716](#); Symbol: [ER_BINLOG_UNSAFE_REPLACE_SELECT](#); SQLSTATE: [HY000](#)

Message: REPLACE... SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are replaced. This order cannot be predicted and may differ on master and the slave.

- Error number: [1717](#); Symbol: [ER_BINLOG_UNSAFE_CREATE_IGNORE_SELECT](#); SQLSTATE: [HY000](#)

Message: CREATE... IGNORE SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are ignored. This order cannot be predicted and may differ on master and the slave.

-
- Error number: [1718](#); Symbol: [ER_BINLOG_UNSAFE_CREATE_REPLACE_SELECT](#); SQLSTATE: [HY000](#)

Message: CREATE... REPLACE SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are replaced. This order cannot be predicted and may differ on master and the slave.

- Error number: [1719](#); Symbol: [ER_BINLOG_UNSAFE_UPDATE_IGNORE](#); SQLSTATE: [HY000](#)

Message: UPDATE IGNORE is unsafe because the order in which rows are updated determines which (if any) rows are ignored. This order cannot be predicted and may differ on master and the slave.

- Error number: [1720](#); Symbol: [ER_PLUGIN_NO_UNINSTALL](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' is marked as not dynamically uninstallable. You have to stop the server to uninstall it.

- Error number: [1721](#); Symbol: [ER_PLUGIN_NO_INSTALL](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' is marked as not dynamically installable. You have to stop the server to install it.

- Error number: [1722](#); Symbol: [ER_BINLOG_UNSAFE_WRITE_AUTOINC_SELECT](#); SQLSTATE: [HY000](#)

Message: Statements writing to a table with an auto-increment column after selecting from another table are unsafe because the order in which rows are retrieved determines what (if any) rows will be written. This order cannot be predicted and may differ on master and the slave.

- Error number: [1723](#); Symbol: [ER_BINLOG_UNSAFE_CREATE_SELECT_AUTOINC](#); SQLSTATE: [HY000](#)

Message: CREATE TABLE... SELECT... on a table with an auto-increment column is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are inserted. This order cannot be predicted and may differ on master and the slave.

- Error number: [1724](#); Symbol: [ER_BINLOG_UNSAFE_INSERT_TWO_KEYS](#); SQLSTATE: [HY000](#)

Message: INSERT... ON DUPLICATE KEY UPDATE on a table with more than one UNIQUE KEY is unsafe

- Error number: [1725](#); Symbol: [ER_TABLE_IN_FK_CHECK](#); SQLSTATE: [HY000](#)

Message: Table is being used in foreign key check.

- Error number: [1726](#); Symbol: [ER_UNSUPPORTED_ENGINE](#); SQLSTATE: [HY000](#)

Message: Storage engine '%s' does not support system tables. [%s.%s]

- Error number: [1727](#); Symbol: [ER_BINLOG_UNSAFE_AUTOINC_NOT_FIRST](#); SQLSTATE: [HY000](#)

Message: INSERT into autoincrement field which is not the first part in the composed primary key is unsafe.

- Error number: [1728](#); Symbol: [ER_CANNOT_LOAD_FROM_TABLE_V2](#); SQLSTATE: [HY000](#)

Message: Cannot load from %s.%s. The table is probably corrupted

- Error number: [1729](#); Symbol: [ER_MASTER_DELAY_VALUE_OUT_OF_RANGE](#); SQLSTATE: [HY000](#)

Message: The requested value %s for the master delay exceeds the maximum %u

-
- Error number: [1730](#); Symbol: [ER_ONLY_FD_AND_RBR_EVENTS_ALLOWED_IN_BINLOG_STATEMENT](#); SQLSTATE: [HY000](#)

Message: Only Format_description_log_event and row events are allowed in BINLOG statements (but %s was provided)
 - Error number: [1731](#); Symbol: [ER_PARTITION_EXCHANGE_DIFFERENT_OPTION](#); SQLSTATE: [HY000](#)

Message: Non matching attribute '%s' between partition and table
 - Error number: [1732](#); Symbol: [ER_PARTITION_EXCHANGE_PART_TABLE](#); SQLSTATE: [HY000](#)

Message: Table to exchange with partition is partitioned: '%s'
 - Error number: [1733](#); Symbol: [ER_PARTITION_EXCHANGE_TEMP_TABLE](#); SQLSTATE: [HY000](#)

Message: Table to exchange with partition is temporary: '%s'
 - Error number: [1734](#); Symbol: [ER_PARTITION_INSTEAD_OF_SUBPARTITION](#); SQLSTATE: [HY000](#)

Message: Subpartitioned table, use subpartition instead of partition
 - Error number: [1735](#); Symbol: [ER_UNKNOWN_PARTITION](#); SQLSTATE: [HY000](#)

Message: Unknown partition '%s' in table '%s'
 - Error number: [1736](#); Symbol: [ER_TABLES_DIFFERENT_METADATA](#); SQLSTATE: [HY000](#)

Message: Tables have different definitions
 - Error number: [1737](#); Symbol: [ER_ROW_DOES_NOT_MATCH_PARTITION](#); SQLSTATE: [HY000](#)

Message: Found a row that does not match the partition
 - Error number: [1738](#); Symbol: [ER_BINLOG_CACHE_SIZE_GREATER_THAN_MAX](#); SQLSTATE: [HY000](#)

Message: Option binlog_cache_size (%lu) is greater than max_binlog_cache_size (%lu); setting binlog_cache_size equal to max_binlog_cache_size.
 - Error number: [1739](#); Symbol: [ER_WARN_INDEX_NOT_APPLICABLE](#); SQLSTATE: [HY000](#)

Message: Cannot use %s access on index '%s' due to type or collation conversion on field '%s'
 - Error number: [1740](#); Symbol: [ER_PARTITION_EXCHANGE_FOREIGN_KEY](#); SQLSTATE: [HY000](#)

Message: Table to exchange with partition has foreign key references: '%s'
 - Error number: [1741](#); Symbol: [ER_NO SUCH KEY VALUE](#); SQLSTATE: [HY000](#)

Message: Key value '%s' was not found in table '%s.%s'
 - Error number: [1742](#); Symbol: [ER_RPL_INFO_DATA_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: Data for column '%s' too long
 - Error number: [1743](#); Symbol: [ER_NETWORK_READ_EVENT_CHECKSUM_FAILURE](#); SQLSTATE: [HY000](#)

Message: Replication event checksum verification failed while reading from network.
 - Error number: [1744](#); Symbol: [ER_BINLOG_READ_EVENT_CHECKSUM_FAILURE](#); SQLSTATE: [HY000](#)

Message: Replication event checksum verification failed while reading from a log file.

- Error number: 1745; Symbol: `ER_BINLOG_STMT_CACHE_SIZE_GREATER_THAN_MAX`; SQLSTATE: `HY000`

Message: Option binlog_stmt_cache_size (%lu) is greater than max_binlog_stmt_cache_size (%lu); setting binlog_stmt_cache_size equal to max_binlog_stmt_cache_size.

- Error number: 1746; Symbol: `ER_CANT_UPDATE_TABLE_IN_CREATE_TABLE_SELECT`; SQLSTATE: `HY000`

Message: Can't update table '%s' while '%s' is being created.

- Error number: 1747; Symbol: `ER_PARTITION_CLAUSE_ON_NONPARTITIONED`; SQLSTATE: `HY000`

Message: PARTITION () clause on non partitioned table

- Error number: 1748; Symbol: `ER_ROW_DOES_NOT_MATCH_GIVEN_PARTITION_SET`; SQLSTATE: `HY000`

Message: Found a row not matching the given partition set

- Error number: 1749; Symbol: `ER_NO_SUCH_PARTITION__UNUSED`; SQLSTATE: `HY000`

Message: partition '%s' doesn't exist

- Error number: 1750; Symbol: `ER_CHANGE_RPL_INFO_REPOSITORY_FAILURE`; SQLSTATE: `HY000`

Message: Failure while changing the type of replication repository: %s.

- Error number: 1751; Symbol: `ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_CREATED_TEMP_TABLE`; SQLSTATE: `HY000`

Message: The creation of some temporary tables could not be rolled back.

- Error number: 1752; Symbol: `ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_DROPPED_TEMP_TABLE`; SQLSTATE: `HY000`

Message: Some temporary tables were dropped, but these operations could not be rolled back.

- Error number: 1753; Symbol: `ER_MTS_FEATURE_IS_NOT_SUPPORTED`; SQLSTATE: `HY000`

Message: %s is not supported in multi-threaded slave mode. %s

- Error number: 1754; Symbol: `ER_MTS_UPDATED_DBs_GREATER_MAX`; SQLSTATE: `HY000`

Message: The number of modified databases exceeds the maximum %d; the database names will not be included in the replication event metadata.

- Error number: 1755; Symbol: `ER_MTS_CANT_PARALLEL`; SQLSTATE: `HY000`

Message: Cannot execute the current event group in the parallel mode. Encountered event %s, relay-log name %s, position %s which prevents execution of this event group in parallel mode. Reason: %s.

- Error number: 1756; Symbol: `ER_MTS_INCONSISTENT_DATA`; SQLSTATE: `HY000`

Message: %s

- Error number: 1757; Symbol: `ER_FULLTEXT_NOT_SUPPORTED_WITH_PARTITIONING`; SQLSTATE: `HY000`

Message: FULLTEXT index is not supported for partitioned tables.

- Error number: 1758; Symbol: [ER_DA_INVALID_CONDITION_NUMBER](#); SQLSTATE: [35000](#)

Message: Invalid condition number

- Error number: 1759; Symbol: [ER_INSECURE_PLAIN_TEXT](#); SQLSTATE: [HY000](#)

Message: Sending passwords in plain text without SSL/TLS is extremely insecure.

- Error number: 1760; Symbol: [ER_INSECURE_CHANGE_MASTER](#); SQLSTATE: [HY000](#)

Message: Storing MySQL user name or password information in the master info repository is not secure and is therefore not recommended. Please consider using the USER and PASSWORD connection options for START SLAVE; see the 'START SLAVE Syntax' in the MySQL Manual for more information.

- Error number: 1761; Symbol: [ER_FOREIGN_DUPLICATE_KEY_WITH_CHILD_INFO](#); SQLSTATE: [23000](#)

Message: Foreign key constraint for table '%s', record '%s' would lead to a duplicate entry in table '%s', key '%s'

- Error number: 1762; Symbol: [ER_FOREIGN_DUPLICATE_KEY_WITHOUT_CHILD_INFO](#); SQLSTATE: [23000](#)

Message: Foreign key constraint for table '%s', record '%s' would lead to a duplicate entry in a child table

- Error number: 1763; Symbol: [ER_SQLTHREAD_WITH_SECURE_SLAVE](#); SQLSTATE: [HY000](#)

Message: Setting authentication options is not possible when only the Slave SQL Thread is being started.

- Error number: 1764; Symbol: [ER_TABLE_HAS_NO_FT](#); SQLSTATE: [HY000](#)

Message: The table does not have FULLTEXT index to support this query

- Error number: 1765; Symbol: [ER_VARIABLE_NOT_SETTABLE_IN_SF_OR_TRIGGER](#); SQLSTATE: [HY000](#)

Message: The system variable %s cannot be set in stored functions or triggers.

- Error number: 1766; Symbol: [ER_VARIABLE_NOT_SETTABLE_IN_TRANSACTION](#); SQLSTATE: [HY000](#)

Message: The system variable %s cannot be set when there is an ongoing transaction.

- Error number: 1767; Symbol: [ER_GTID_NEXT_IS_NOT_IN_GTID_NEXT_LIST](#); SQLSTATE: [HY000](#)

Message: The system variable @@SESSION.GTID_NEXT has the value %s, which is not listed in @@SESSION.GTID_NEXT_LIST.

- Error number: 1768; Symbol: [ER_CANT_CHANGE_GTID_NEXT_IN_TRANSACTION_WHEN_GTID_NEXT_LIST_IS_NULL](#); SQLSTATE: [HY000](#)

Message: The system variable @@SESSION.GTID_NEXT cannot change inside a transaction.

[ER_CANT_CHANGE_GTID_NEXT_IN_TRANSACTION_WHEN_GTID_NEXT_LIST_IS_NULL](#) was removed after 5.7.5.

- Error number: [1768](#); Symbol: [ER_CANT_CHANGE_GTID_NEXT_IN_TRANSACTION](#); SQLSTATE: [HY000](#)

Message: The system variable @@SESSION.GTID_NEXT cannot change inside a transaction.

[ER_CANT_CHANGE_GTID_NEXT_IN_TRANSACTION](#) was added in 5.7.6.

- Error number: [1769](#); Symbol: [ER_SET_STATEMENT_CANNOT_INVOKE_FUNCTION](#); SQLSTATE: [HY000](#)

Message: The statement 'SET %s' cannot invoke a stored function.

- Error number: [1770](#); Symbol: [ER_GTID_NEXT_CANT_BE_AUTOMATIC_IF_GTID_NEXT_LIST_IS_NON_NULL](#); SQLSTATE: [HY000](#)

Message: The system variable @@SESSION.GTID_NEXT cannot be 'AUTOMATIC' when @@SESSION.GTID_NEXT_LIST is non-NULL.

- Error number: [1771](#); Symbol: [ER_SKIPPING_LOGGED_TRANSACTION](#); SQLSTATE: [HY000](#)

Message: Skipping transaction %s because it has already been executed and logged.

- Error number: [1772](#); Symbol: [ER_MALFORMED_GTID_SET_SPECIFICATION](#); SQLSTATE: [HY000](#)

Message: Malformed GTID set specification '%s'.

- Error number: [1773](#); Symbol: [ER_MALFORMED_GTID_SET_ENCODING](#); SQLSTATE: [HY000](#)

Message: Malformed GTID set encoding.

- Error number: [1774](#); Symbol: [ER_MALFORMED_GTID_SPECIFICATION](#); SQLSTATE: [HY000](#)

Message: Malformed GTID specification '%s'.

- Error number: [1775](#); Symbol: [ER_GNO_EXHAUSTED](#); SQLSTATE: [HY000](#)

Message: Impossible to generate GTID: the integer component reached the maximum value. Restart the server with a new server_uuid.

- Error number: [1776](#); Symbol: [ER_BAD_SLAVE_AUTO_POSITION](#); SQLSTATE: [HY000](#)

Message: Parameters MASTER_LOG_FILE, MASTER_LOG_POS, RELAY_LOG_FILE and RELAY_LOG_POS cannot be set when MASTER_AUTO_POSITION is active.

- Error number: [1777](#); Symbol: [ER_AUTO_POSITION_REQUIRES_GTID_MODE_ON](#); SQLSTATE: [HY000](#)

Message: CHANGE MASTER TO MASTER_AUTO_POSITION = 1 can only be executed when @@GLOBAL.GTID_MODE = ON.

[ER_AUTO_POSITION_REQUIRES_GTID_MODE_ON](#) was removed after 5.7.5.

- Error number: [1777](#); Symbol: [ER_AUTO_POSITION_REQUIRES_GTID_MODE_NOT_OFF](#); SQLSTATE: [HY000](#)

Message: CHANGE MASTER TO MASTER_AUTO_POSITION = 1 cannot be executed because @@GLOBAL.GTID_MODE = OFF.

[ER_AUTO_POSITION_REQUIRES_GTID_MODE_NOT_OFF](#) was added in 5.7.6.

- Error number: [1778](#); Symbol: [ER_CANT_DO_IMPLICIT_COMMIT_IN_TRX_WHEN_GTID_NEXT_IS_SET](#); SQLSTATE: [HY000](#)

Message: Cannot execute statements with implicit commit inside a transaction when
@@SESSION.GTID_NEXT == 'UUID:NUMBER'.

- Error number: [1779](#); Symbol:
`ER_GTID_MODE_2_OR_3_REQUIRES_ENFORCE_GTID_CONSISTENCY_ON`; SQLSTATE: [HY000](#)

Message: @@GLOBAL.GTID_MODE = ON or UPGRADE_STEP_2 requires
@@GLOBAL.ENFORCE_GTID_CONSISTENCY = 1.

`ER_GTID_MODE_2_OR_3_REQUIRES_ENFORCE_GTID_CONSISTENCY_ON` was removed after
5.7.5.

- Error number: [1779](#); Symbol:
`ER_GTID_MODE_ON_REQUIRES_ENFORCE_GTID_CONSISTENCY_ON`; SQLSTATE: [HY000](#)

Message: GTID_MODE = ON requires ENFORCE_GTID_CONSISTENCY = ON.

`ER_GTID_MODE_ON_REQUIRES_ENFORCE_GTID_CONSISTENCY_ON` was added in 5.7.6.

- Error number: [1780](#); Symbol: `ER_GTID_MODE_REQUIRES_BINLOG`; SQLSTATE: [HY000](#)

Message: @@GLOBAL.GTID_MODE = ON or ON_PERMISSIVE or OFF_PERMISSIVE requires --
log-bin and --log-slave-updates.

- Error number: [1781](#); Symbol: `ER_CANT_SET_GTID_NEXT_TO_GTID_WHEN_GTID_MODE_IS_OFF`;
SQLSTATE: [HY000](#)

Message: @@SESSION.GTID_NEXT cannot be set to UUID:NUMBER when
@@GLOBAL.GTID_MODE = OFF.

- Error number: [1782](#); Symbol:
`ER_CANT_SET_GTID_NEXT_TO_ANONYMOUS_WHEN_GTID_MODE_IS_ON`; SQLSTATE: [HY000](#)

Message: @@SESSION.GTID_NEXT cannot be set to ANONYMOUS when
@@GLOBAL.GTID_MODE = ON.

- Error number: [1783](#); Symbol:
`ER_CANT_SET_GTID_NEXT_LIST_TO_NON_NULL_WHEN_GTID_MODE_IS_OFF`; SQLSTATE:
[HY000](#)

Message: @@SESSION.GTID_NEXT_LIST cannot be set to a non-NULL value when
@@GLOBAL.GTID_MODE = OFF.

- Error number: [1784](#); Symbol: `ER_FOUND_GTID_EVENT_WHEN_GTID_MODE_IS_OFF`; SQLSTATE:
[HY000](#)

Message: Found a Gtid_log_event or Previous_gtids_log_event when @@GLOBAL.GTID_MODE =
OFF.

`ER_FOUND_GTID_EVENT_WHEN_GTID_MODE_IS_OFF` was removed after 5.7.5.

- Error number: [1784](#); Symbol: `ER_FOUND_GTID_EVENT_WHEN_GTID_MODE_IS_OFF_UNUSED`;
SQLSTATE: [HY000](#)

Message: Found a Gtid_log_event when @@GLOBAL.GTID_MODE = OFF.

`ER_FOUND_GTID_EVENT_WHEN_GTID_MODE_IS_OFF_UNUSED` was added in 5.7.6.

- Error number: [1785](#); Symbol: [ER_GTID_UNSAFE_NON_TRANSACTIONAL_TABLE](#); SQLSTATE: [HY000](#)

Message: Statement violates GTID consistency: Updates to non-transactional tables can only be done in either autocommitted statements or single-statement transactions, and never in the same statement as updates to transactional tables.

- Error number: [1786](#); Symbol: [ER_GTID_UNSAFE_CREATE_SELECT](#); SQLSTATE: [HY000](#)

Message: Statement violates GTID consistency: CREATE TABLE ... SELECT.

- Error number: [1787](#); Symbol: [ER_GTID_UNSAFE_CREATE_DROP_TEMPORARY_TABLE_IN TRANSACTION](#); SQLSTATE: [HY000](#)

Message: Statement violates GTID consistency: CREATE TEMPORARY TABLE and DROP TEMPORARY TABLE can only be executed outside transactional context. These statements are also not allowed in a function or trigger because functions and triggers are also considered to be multi-statement transactions.

- Error number: [1788](#); Symbol: [ER_GTID_MODE_CAN_ONLY_CHANGE_ONE_STEP_AT_A_TIME](#); SQLSTATE: [HY000](#)

Message: The value of @@GLOBAL.GTID_MODE can only be changed one step at a time: OFF <-> OFF_PERMISSIVE <-> ON_PERMISSIVE <-> ON. Also note that this value must be stepped up or down simultaneously on all servers. See the Manual for instructions.

- Error number: [1789](#); Symbol: [ER_MASTER_HAS_PURGED_REQUIRED_GTIDS](#); SQLSTATE: [HY000](#)

Message: The slave is connecting using CHANGE MASTER TO MASTER_AUTO_POSITION = 1, but the master has purged binary logs containing GTIDs that the slave requires. Replicate the missing transactions from elsewhere, or provision a new slave from backup. Consider increasing the master's binary log expiration period. %s.

- Error number: [1790](#); Symbol: [ER_CANT_SET_GTID_NEXT_WHEN_OWNING_GTID](#); SQLSTATE: [HY000](#)

Message: @@SESSION.GTID_NEXT cannot be changed by a client that owns a GTID. The client owns %s. Ownership is released on COMMIT or ROLLBACK.

- Error number: [1791](#); Symbol: [ER_UNKNOWN_EXPLAIN_FORMAT](#); SQLSTATE: [HY000](#)

Message: Unknown EXPLAIN format name: '%s'

- Error number: [1792](#); Symbol: [ER_CANT_EXECUTE_IN_READ_ONLY_TRANSACTION](#); SQLSTATE: [25006](#)

Message: Cannot execute statement in a READ ONLY transaction.

- Error number: [1793](#); Symbol: [ER_TOO_LONG_TABLE_PARTITION_COMMENT](#); SQLSTATE: [HY000](#)

Message: Comment for table partition '%s' is too long (max = %lu)

- Error number: [1794](#); Symbol: [ER_SLAVE_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: Slave is not configured or failed to initialize properly. You must at least set --server-id to enable either a master or a slave. Additional error messages can be found in the MySQL error log.

- Error number: [1795](#); Symbol: [ER_INNODB_FT_LIMIT](#); SQLSTATE: [HY000](#)

Message: InnoDB presently supports one FULLTEXT index creation at a time

- Error number: [1796](#); Symbol: [ER_INNODB_NO_FT_TEMP_TABLE](#); SQLSTATE: [HY000](#)

Message: Cannot create FULLTEXT index on temporary InnoDB table

- Error number: 1797; Symbol: `ER_INNODB_FT_WRONG_DOCID_COLUMN`; SQLSTATE: HY000

Message: Column '%s' is of wrong type for an InnoDB FULLTEXT index

- Error number: 1798; Symbol: `ER_INNODB_FT_WRONG_DOCID_INDEX`; SQLSTATE: HY000

Message: Index '%s' is of wrong type for an InnoDB FULLTEXT index

- Error number: 1799; Symbol: `ER_INNODB_ONLINE_LOG_TOO_BIG`; SQLSTATE: HY000

Message: Creating index '%s' required more than 'innodb_online_alter_log_max_size' bytes of modification log. Please try again.

- Error number: 1800; Symbol: `ER_UNKNOWN_ALTER_ALGORITHM`; SQLSTATE: HY000

Message: Unknown ALGORITHM '%s'

- Error number: 1801; Symbol: `ER_UNKNOWN_ALTER_LOCK`; SQLSTATE: HY000

Message: Unknown LOCK type '%s'

- Error number: 1802; Symbol: `ER_MTS_CHANGE_MASTER_CANT_RUN_WITH_GAPS`; SQLSTATE: HY000

Message: CHANGE MASTER cannot be executed when the slave was stopped with an error or killed in MTS mode. Consider using RESET SLAVE or START SLAVE UNTIL.

- Error number: 1803; Symbol: `ER_MTS_RECOVERY_FAILURE`; SQLSTATE: HY000

Message: Cannot recover after SLAVE errored out in parallel execution mode. Additional error messages can be found in the MySQL error log.

- Error number: 1804; Symbol: `ER_MTS_RESET_WORKERS`; SQLSTATE: HY000

Message: Cannot clean up worker info tables. Additional error messages can be found in the MySQL error log.

- Error number: 1805; Symbol: `ER_COL_COUNT_DOESNT_MATCH_CORRUPTED_V2`; SQLSTATE: HY000

Message: Column count of %s.%s is wrong. Expected %d, found %d. The table is probably corrupted

- Error number: 1806; Symbol: `ER_SLAVE_SILENT_RETRY_TRANSACTION`; SQLSTATE: HY000

Message: Slave must silently retry current transaction

- Error number: 1807; Symbol: `ER_DISCARD_FK_CHECKS_RUNNING`; SQLSTATE: HY000

Message: There is a foreign key check running on table '%s'. Cannot discard the table.

- Error number: 1808; Symbol: `ER_TABLE_SCHEMA_MISMATCH`; SQLSTATE: HY000

Message: Schema mismatch (%s)

- Error number: 1809; Symbol: `ER_TABLE_IN_SYSTEM_TABLESPACE`; SQLSTATE: HY000

Message: Table '%s' in system tablespace

- Error number: 1810; Symbol: `ER_IO_READ_ERROR`; SQLSTATE: HY000

Message: IO Read error: (%lu, %s) %s

- Error number: [1811](#); Symbol: [ER_IO_WRITE_ERROR](#); SQLSTATE: [HY000](#)
Message: IO Write error: (%lu, %s) %s
- Error number: [1812](#); Symbol: [ER_TABLESPACE_MISSING](#); SQLSTATE: [HY000](#)
Message: Tablespace is missing for table %s.
- Error number: [1813](#); Symbol: [ER_TABLESPACE_EXISTS](#); SQLSTATE: [HY000](#)
Message: Tablespace '%s' exists.
- Error number: [1814](#); Symbol: [ER_TABLESPACE_DISCARDED](#); SQLSTATE: [HY000](#)
Message: Tablespace has been discarded for table '%s'
- Error number: [1815](#); Symbol: [ER_INTERNAL_ERROR](#); SQLSTATE: [HY000](#)
Message: Internal error: %s
- Error number: [1816](#); Symbol: [ER_INNODB_IMPORT_ERROR](#); SQLSTATE: [HY000](#)
Message: ALTER TABLE %s IMPORT TABLESPACE failed with error %lu : '%s'
- Error number: [1817](#); Symbol: [ER_INNODB_INDEX_CORRUPT](#); SQLSTATE: [HY000](#)
Message: Index corrupt: %s
- Error number: [1818](#); Symbol: [ER_INVALID_YEAR_COLUMN_LENGTH](#); SQLSTATE: [HY000](#)
Message: Supports only YEAR or YEAR(4) column.
- Error number: [1819](#); Symbol: [ER_NOT_VALID_PASSWORD](#); SQLSTATE: [HY000](#)
Message: Your password does not satisfy the current policy requirements
- Error number: [1820](#); Symbol: [ER_MUST_CHANGE_PASSWORD](#); SQLSTATE: [HY000](#)
Message: You must reset your password using ALTER USER statement before executing this statement.
- Error number: [1821](#); Symbol: [ER_FK_NO_INDEX_CHILD](#); SQLSTATE: [HY000](#)
Message: Failed to add the foreign key constraint. Missing index for constraint '%s' in the foreign table '%s'
- Error number: [1822](#); Symbol: [ER_FK_NO_INDEX_PARENT](#); SQLSTATE: [HY000](#)
Message: Failed to add the foreign key constraint. Missing index for constraint '%s' in the referenced table '%s'
- Error number: [1823](#); Symbol: [ER_FK_FAIL_ADD_SYSTEM](#); SQLSTATE: [HY000](#)
Message: Failed to add the foreign key constraint '%s' to system tables
- Error number: [1824](#); Symbol: [ER_FK_CANNOT_OPEN_PARENT](#); SQLSTATE: [HY000](#)
Message: Failed to open the referenced table '%s'
- Error number: [1825](#); Symbol: [ER_FK_INCORRECT_OPTION](#); SQLSTATE: [HY000](#)
Message: Failed to add the foreign key constraint on table '%s'. Incorrect options in FOREIGN KEY constraint '%s'

-
- Error number: [1826](#); Symbol: [ER_FK_DUP_NAME](#); SQLSTATE: [HY000](#)
Message: Duplicate foreign key constraint name '%s'
 - Error number: [1827](#); Symbol: [ER_PASSWORD_FORMAT](#); SQLSTATE: [HY000](#)
Message: The password hash doesn't have the expected format. Check if the correct password algorithm is being used with the PASSWORD() function.
 - Error number: [1828](#); Symbol: [ER_FK_COLUMN_CANNOT_DROP](#); SQLSTATE: [HY000](#)
Message: Cannot drop column '%s': needed in a foreign key constraint '%s'
 - Error number: [1829](#); Symbol: [ER_FK_COLUMN_CANNOT_DROP_CHILD](#); SQLSTATE: [HY000](#)
Message: Cannot drop column '%s': needed in a foreign key constraint '%s' of table '%s'
 - Error number: [1830](#); Symbol: [ER_FK_COLUMN_NOT_NULL](#); SQLSTATE: [HY000](#)
Message: Column '%s' cannot be NOT NULL: needed in a foreign key constraint '%s' SET NULL
 - Error number: [1831](#); Symbol: [ER_DUP_INDEX](#); SQLSTATE: [HY000](#)
Message: Duplicate index '%s' defined on the table '%s.%s'. This is deprecated and will be disallowed in a future release.
 - Error number: [1832](#); Symbol: [ER_FK_COLUMN_CANNOT_CHANGE](#); SQLSTATE: [HY000](#)
Message: Cannot change column '%s': used in a foreign key constraint '%s'
 - Error number: [1833](#); Symbol: [ER_FK_COLUMN_CANNOT_CHANGE_CHILD](#); SQLSTATE: [HY000](#)
Message: Cannot change column '%s': used in a foreign key constraint '%s' of table '%s'
 - Error number: [1834](#); Symbol: [ER_FK_CANNOT_DELETE_PARENT](#); SQLSTATE: [HY000](#)
Message: Cannot delete rows from table which is parent in a foreign key constraint '%s' of table '%s'
[ER_FK_CANNOT_DELETE_PARENT](#) was removed after 5.7.3.
 - Error number: [1834](#); Symbol: [ER_UNUSED5](#); SQLSTATE: [HY000](#)
Message: Cannot delete rows from table which is parent in a foreign key constraint '%s' of table '%s'
[ER_UNUSED5](#) was added in 5.7.4.
 - Error number: [1835](#); Symbol: [ER_MALFORMED_PACKET](#); SQLSTATE: [HY000](#)
Message: Malformed communication packet.
 - Error number: [1836](#); Symbol: [ER_READ_ONLY_MODE](#); SQLSTATE: [HY000](#)
Message: Running in read-only mode
 - Error number: [1837](#); Symbol: [ER_GTID_NEXT_TYPE_UNDEFINED_GROUP](#); SQLSTATE: [HY000](#)
Message: When @@SESSION.GTID_NEXT is set to a GTID, you must explicitly set it to a different value after a COMMIT or ROLLBACK. Please check GTID_NEXT variable manual page for detailed explanation. Current @@SESSION.GTID_NEXT is '%s'.
 - Error number: [1838](#); Symbol: [ER_VARIABLE_NOT_SETTABLE_IN_SP](#); SQLSTATE: [HY000](#)
Message: The system variable %s cannot be set in stored procedures.

- Error number: [1839](#); Symbol: [ER_CANT_SET_GTID_PURGED_WHEN_GTID_MODE_IS_OFF](#); SQLSTATE: [HY000](#)

Message: @@GLOBAL.GTID_PURGED can only be set when @@GLOBAL.GTID_MODE = ON.
- Error number: [1840](#); Symbol: [ER_CANT_SET_GTID_PURGED_WHEN_GTID_EXECUTED_IS_NOT_EMPTY](#); SQLSTATE: [HY000](#)

Message: @@GLOBAL.GTID_PURGED can only be set when @@GLOBAL.GTID_EXECUTED is empty.
- Error number: [1841](#); Symbol: [ER_CANT_SET_GTID_PURGED_WHEN_OWNED_GTIDS_IS_NOT_EMPTY](#); SQLSTATE: [HY000](#)

Message: @@GLOBAL.GTID_PURGED can only be set when there are no ongoing transactions (not even in other clients).
- Error number: [1842](#); Symbol: [ER_GTID_PURGED_WAS_CHANGED](#); SQLSTATE: [HY000](#)

Message: @@GLOBAL.GTID_PURGED was changed from '%s' to '%s'.
- Error number: [1843](#); Symbol: [ER_GTID_EXECUTED_WAS_CHANGED](#); SQLSTATE: [HY000](#)

Message: @@GLOBAL.GTID_EXECUTED was changed from '%s' to '%s'.
- Error number: [1844](#); Symbol: [ER_BINLOG_STMT_MODE_AND_NO_REPL_TABLES](#); SQLSTATE: [HY000](#)

Message: Cannot execute statement: impossible to write to binary log since BINLOG_FORMAT = STATEMENT, and both replicated and non replicated tables are written to.
- Error number: [1845](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED](#); SQLSTATE: [0A000](#)

Message: %s is not supported for this operation. Try %s.
[ER_ALTER_OPERATION_NOT_SUPPORTED](#) was added in 5.7.1.
- Error number: [1846](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON](#); SQLSTATE: [0A000](#)

Message: %s is not supported. Reason: %s. Try %s.
[ER_ALTER_OPERATION_NOT_SUPPORTED_REASON](#) was added in 5.7.1.
- Error number: [1847](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_COPY](#); SQLSTATE: [HY000](#)

Message: COPY algorithm requires a lock
[ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_COPY](#) was added in 5.7.1.
- Error number: [1848](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_PARTITION](#); SQLSTATE: [HY000](#)

Message: Partition specific operations do not yet support LOCK/ALGORITHM
[ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_PARTITION](#) was added in 5.7.1.
- Error number: [1849](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_FK_RENAME](#); SQLSTATE: [HY000](#)

Message: Columns participating in a foreign key are renamed
[ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_FK_RENAME](#) was added in 5.7.1.

-
- Error number: 1850; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_COLUMN_TYPE`; SQLSTATE: `HY000`

Message: Cannot change column type INPLACE

`ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_COLUMN_TYPE` was added in 5.7.1.

- Error number: 1851; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_FK_CHECK`; SQLSTATE: `HY000`

Message: Adding foreign keys needs `foreign_key_checks=OFF`

`ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_FK_CHECK` was added in 5.7.1.

- Error number: 1852; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_IGNORE`; SQLSTATE: `HY000`

Message: Creating unique indexes with IGNORE requires COPY algorithm to remove duplicate rows

`ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_IGNORE` was added in 5.7.1, removed after 5.7.3.

- Error number: 1852; Symbol: `ER_UNUSED6`; SQLSTATE: `HY000`

Message: Creating unique indexes with IGNORE requires COPY algorithm to remove duplicate rows

`ER_UNUSED6` was added in 5.7.4.

- Error number: 1853; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_NOPK`; SQLSTATE: `HY000`

Message: Dropping a primary key is not allowed without also adding a new primary key

`ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_NOPK` was added in 5.7.1.

- Error number: 1854; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_AUTOINC`; SQLSTATE: `HY000`

Message: Adding an auto-increment column requires a lock

`ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_AUTOINC` was added in 5.7.1.

- Error number: 1855; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_HIDDEN_FTS`; SQLSTATE: `HY000`

Message: Cannot replace hidden FTS_DOC_ID with a user-visible one

`ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_HIDDEN_FTS` was added in 5.7.1.

- Error number: 1856; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_CHANGE_FTS`; SQLSTATE: `HY000`

Message: Cannot drop or rename FTS_DOC_ID

`ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_CHANGE_FTS` was added in 5.7.1.

- Error number: 1857; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_FTS`; SQLSTATE: `HY000`

Message: Fulltext index creation requires a lock

`ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_FTS` was added in 5.7.1.

- Error number: 1858; Symbol: `ER_SQL_SLAVE_SKIP_COUNTER_NOT_SETTABLE_IN_GTID_MODE`; SQLSTATE: `HY000`

Message: sql_slave_skip_counter can not be set when the server is running with `@@GLOBAL.GTID_MODE = ON`. Instead, for each transaction that you want to skip, generate an empty transaction with the same GTID as the transaction

`ER_SQL_SLAVE_SKIP_COUNTER_NOT_SETTABLE_IN_GTID_MODE` was added in 5.7.1.

- Error number: 1859; Symbol: `ER_DUP_UNKNOWN_IN_INDEX`; SQLSTATE: `23000`

Message: Duplicate entry for key '%s'

`ER_DUP_UNKNOWN_IN_INDEX` was added in 5.7.1.

- Error number: 1860; Symbol: `ER_IDENT_CAUSES_TOO_LONG_PATH`; SQLSTATE: `HY000`

Message: Long database name and identifier for object resulted in path length exceeding %d characters. Path: '%s'.

`ER_IDENT_CAUSES_TOO_LONG_PATH` was added in 5.7.1.

- Error number: 1861; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_NOT_NULL`; SQLSTATE: `HY000`

Message: cannot silently convert NULL values, as required in this SQL_MODE

`ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_NOT_NULL` was added in 5.7.1.

- Error number: 1862; Symbol: `ER_MUST_CHANGE_PASSWORD_LOGIN`; SQLSTATE: `HY000`

Message: Your password has expired. To log in you must change it using a client that supports expired passwords.

`ER_MUST_CHANGE_PASSWORD_LOGIN` was added in 5.7.1.

- Error number: 1863; Symbol: `ER_ROW_IN_WRONG_PARTITION`; SQLSTATE: `HY000`

Message: Found a row in wrong partition %s

`ER_ROW_IN_WRONG_PARTITION` was added in 5.7.1.

- Error number: 1864; Symbol: `ER_MTS_EVENT_BIGGER_PENDING_JOBS_SIZE_MAX`; SQLSTATE: `HY000`

Message: Cannot schedule event %s, relay-log name %s, position %s to Worker thread because its size %lu exceeds %lu of slave_pending_jobs_size_max.

`ER_MTS_EVENT_BIGGER_PENDING_JOBS_SIZE_MAX` was added in 5.7.2.

- Error number: 1865; Symbol: `ER_INNODB_NO_FTUSES_PARSER`; SQLSTATE: `HY000`

Message: Cannot CREATE FULLTEXT INDEX WITH PARSER on InnoDB table

`ER_INNODB_NO_FTUSES_PARSER` was added in 5.7.2.

- Error number: 1866; Symbol: `ER_BINLOG_LOGICAL_CORRUPTION`; SQLSTATE: `HY000`

Message: The binary log file '%s' is logically corrupted: %s

`ER_BINLOG_LOGICAL_CORRUPTION` was added in 5.7.2.

- Error number: 1867; Symbol: `ER_WARN_PURGE_LOG_IN_USE`; SQLSTATE: `HY000`

Message: file %s was not purged because it was being read by %d thread(s), purged only %d out of %d files.

`ER_WARN_PURGE_LOG_IN_USE` was added in 5.7.2.

- Error number: 1868; Symbol: `ER_WARN_PURGE_LOG_IS_ACTIVE`; SQLSTATE: `HY000`

Message: file %s was not purged because it is the active log file.

`ER_WARN_PURGE_LOG_IS_ACTIVE` was added in 5.7.2.

- Error number: 1869; Symbol: `ER_AUTO_INCREMENT_CONFLICT`; SQLSTATE: `HY000`

Message: Auto-increment value in UPDATE conflicts with internally generated values

`ER_AUTO_INCREMENT_CONFLICT` was added in 5.7.2.

- Error number: 1870; Symbol: `WARN_ON_BLOCKHOLE_IN_RBR`; SQLSTATE: `HY000`

Message: Row events are not logged for %s statements that modify BLACKHOLE tables in row format. Table(s): '%s'

`WARN_ON_BLOCKHOLE_IN_RBR` was added in 5.7.2.

- Error number: 1871; Symbol: `ER_SLAVE_MI_INIT_REPOSITORY`; SQLSTATE: `HY000`

Message: Slave failed to initialize master info structure from the repository

`ER_SLAVE_MI_INIT_REPOSITORY` was added in 5.7.2.

- Error number: 1872; Symbol: `ER_SLAVE_RLI_INIT_REPOSITORY`; SQLSTATE: `HY000`

Message: Slave failed to initialize relay log info structure from the repository

`ER_SLAVE_RLI_INIT_REPOSITORY` was added in 5.7.2.

- Error number: 1873; Symbol: `ER_ACCESS_DENIED_CHANGE_USER_ERROR`; SQLSTATE: `28000`

Message: Access denied trying to change to user '%s'@'%s' (using password: %s). Disconnecting.

`ER_ACCESS_DENIED_CHANGE_USER_ERROR` was added in 5.7.2.

- Error number: 1874; Symbol: `ER_INNODB_READ_ONLY`; SQLSTATE: `HY000`

Message: InnoDB is in read only mode.

`ER_INNODB_READ_ONLY` was added in 5.7.2.

- Error number: 1875; Symbol: `ER_STOP_SLAVE_SQL_THREAD_TIMEOUT`; SQLSTATE: `HY000`

Message: STOP SLAVE command execution is incomplete: Slave SQL thread got the stop signal, thread is busy, SQL thread will stop once the current task is complete.

`ER_STOP_SLAVE_SQL_THREAD_TIMEOUT` was added in 5.7.2.

- Error number: 1876; Symbol: `ER_STOP_SLAVE_IO_THREAD_TIMEOUT`; SQLSTATE: `HY000`

Message: STOP SLAVE command execution is incomplete: Slave IO thread got the stop signal, thread is busy, IO thread will stop once the current task is complete.

`ER_STOP_SLAVE_IO_THREAD_TIMEOUT` was added in 5.7.2.

- Error number: 1877; Symbol: `ER_TABLE_CORRUPT`; SQLSTATE: `HY000`

Message: Operation cannot be performed. The table '%s.%s' is missing, corrupt or contains bad data.

`ER_TABLE_CORRUPT` was added in 5.7.2.

- Error number: 1878; Symbol: `ER_TEMP_FILE_WRITE_FAILURE`; SQLSTATE: `HY000`

Message: Temporary file write failure.

`ER_TEMP_FILE_WRITE_FAILURE` was added in 5.7.3.

- Error number: 1879; Symbol: `ER_INNODB_FT_AUX_NOT_HEX_ID`; SQLSTATE: `HY000`

Message: Upgrade index name failed, please use create index(alter table) algorithm copy to rebuild index.

`ER_INNODB_FT_AUX_NOT_HEX_ID` was added in 5.7.4.

- Error number: 1880; Symbol: `ER_OLD_TEMPORALS_UPGRADED`; SQLSTATE: `HY000`

Message: TIME/TIMESTAMP/DATETIME columns of old format have been upgraded to the new format.

`ER_OLD_TEMPORALS_UPGRADED` was added in 5.7.4.

- Error number: 1881; Symbol: `ER_INNODB_FORCED_RECOVERY`; SQLSTATE: `HY000`

Message: Operation not allowed when innodb_forced_recovery > 0.

`ER_INNODB_FORCED_RECOVERY` was added in 5.7.4.

- Error number: 1882; Symbol: `ER_AES_INVALID_IV`; SQLSTATE: `HY000`

Message: The initialization vector supplied to %s is too short. Must be at least %d bytes long

`ER_AES_INVALID_IV` was added in 5.7.4.

- Error number: 1883; Symbol: `ER_PLUGIN_CANNOT_BE_UNINSTALLED`; SQLSTATE: `HY000`

Message: Plugin '%s' cannot be uninstalled now. %s

`ER_PLUGIN_CANNOT_BE_UNINSTALLED` was added in 5.7.5.

- Error number: 1884; Symbol:

`ER_GTIID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AND_GTID_GROUP`; SQLSTATE: `HY000`

Message: Cannot execute statement because it needs to be written to the binary log as multiple statements, and this is not allowed when @@SESSION.GTID_NEXT == 'UUID:NUMBER'.

`ER_GTIID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AND_GTID_GROUP` was added in 5.7.5.

- Error number: 1885; Symbol: `ER_SLAVE_HAS_MORE_GTIDS_THAN_MASTER`; SQLSTATE: `HY000`

Message: Slave has more GTIDs than the master has, using the master's SERVER_UUID. This may indicate that the end of the binary log was truncated or that the last binary log file was lost, e.g., after a power or disk failure when sync_binlog != 1. The master may or may not have rolled back transactions that were already replicated to the slave. Suggest to replicate any transactions that master has rolled back from slave to master, and/or commit empty transactions on master to account for transactions that have been committed on master but are not included in GTID_EXECUTED.

`ER_SLAVE_HAS_MORE_GTIDS_THAN_MASTER` was added in 5.7.6.

- Error number: 1886; Symbol: `ER_MISSING_KEY`; SQLSTATE: `HY000`

Message: The table '%s.%s' does not have the necessary key(s) defined on it. Please check the table definition and create index(s) accordingly.

[ER_MISSING_KEY](#) was added in 5.7.22.

- Error number: [1887](#); Symbol: [WARN_NAMED_PIPE_ACCESS_EVERYONE](#); SQLSTATE: [HY000](#)

Message: Setting named_pipe_full_access_group='%s' is insecure. Consider using a Windows group with fewer members.

[WARN_NAMED_PIPE_ACCESS_EVERYONE](#) was added in 5.7.27.

- Error number: [1888](#); Symbol: [ER_FOUND_MISSING_GTIDS](#); SQLSTATE: [HY000](#)

Message: Cannot replicate to server with server_uuid='%s' because the present server has purged required binary logs. The connecting server needs to replicate the missing transactions from elsewhere, or be replaced by a new server created from a more recent backup. To prevent this error in the future, consider increasing the binary log expiration period on the present server. %s.

[ER_FOUND_MISSING_GTIDS](#) was added in 5.7.29.

- Error number: [1906](#); Symbol: [ER_SLAVE_IO_THREAD_MUST_STOP](#); SQLSTATE: [HY000](#)

Message: This operation cannot be performed with a running slave io thread; run STOP SLAVE IO_THREAD first.

[ER_SLAVE_IO_THREAD_MUST_STOP](#) was added in 5.7.4, removed after 5.7.5.

- Error number: [3000](#); Symbol: [ER_FILE_CORRUPT](#); SQLSTATE: [HY000](#)

Message: File %s is corrupted

- Error number: [3001](#); Symbol: [ER_ERROR_ON_MASTER](#); SQLSTATE: [HY000](#)

Message: Query partially completed on the master (error on master: %d) and was aborted. There is a chance that your master is inconsistent at this point. If you are sure that your master is ok, run this query manually on the slave and then restart the slave with SET GLOBAL SQL_SLAVE_SKIP_COUNTER=1; START SLAVE;. Query:'%s'

- Error number: [3002](#); Symbol: [ER_INCONSISTENT_ERROR](#); SQLSTATE: [HY000](#)

Message: Query caused different errors on master and slave. Error on master: message (format)='%s' error code=%d; Error on slave:actual message='%s', error code=%d. Default database:'%s'. Query:'%s'

- Error number: [3003](#); Symbol: [ER_STORAGE_ENGINE_NOT_LOADED](#); SQLSTATE: [HY000](#)

Message: Storage engine for table '%s'.'%s' is not loaded.

- Error number: [3004](#); Symbol: [ER_GET_STACKED_DA_WITHOUT_ACTIVE_HANDLER](#); SQLSTATE: [0Z002](#)

Message: GET STACKED DIAGNOSTICS when handler not active

- Error number: [3005](#); Symbol: [ER_WARN_LEGACY_SYNTAX_CONVERTED](#); SQLSTATE: [HY000](#)

Message: %s is no longer supported. The statement was converted to %s.

- Error number: [3006](#); Symbol: [ER_BINLOG_UNSAFE_FULLTEXT_PLUGIN](#); SQLSTATE: [HY000](#)

Message: Statement is unsafe because it uses a fulltext parser plugin which may not return the same value on the slave.

`ER_BINLOG_UNSAFE_FULLTEXT_PLUGIN` was added in 5.7.1.

- Error number: 3007; Symbol: `ER_CANNOT_DISCARD_TEMPORARY_TABLE`; SQLSTATE: `HY000`

Message: Cannot DISCARD/IMPORT tablespace associated with temporary table

`ER_CANNOT_DISCARD_TEMPORARY_TABLE` was added in 5.7.1.

- Error number: 3008; Symbol: `ER_FK_DEPTH_EXCEEDED`; SQLSTATE: `HY000`

Message: Foreign key cascade delete/update exceeds max depth of %d.

`ER_FK_DEPTH_EXCEEDED` was added in 5.7.2.

- Error number: 3009; Symbol: `ER_COL_COUNT_DOESNT_MATCH PLEASE_UPDATE_V2`; SQLSTATE: `HY000`

Message: Column count of %s.%s is wrong. Expected %d, found %d. Created with MySQL %d, now running %d. Please use mysql_upgrade to fix this error.

`ER_COL_COUNT_DOESNT_MATCH PLEASE_UPDATE_V2` was added in 5.7.2.

- Error number: 3010; Symbol: `ER_WARN_TRIGGER_DOESNT_HAVE_CREATED`; SQLSTATE: `HY000`

Message: Trigger %s.%s.%s does not have CREATED attribute.

`ER_WARN_TRIGGER_DOESNT_HAVE_CREATED` was added in 5.7.2.

- Error number: 3011; Symbol: `ER_REFERENCED_TRG_DOES_NOT_EXIST`; SQLSTATE: `HY000`

Message: Referenced trigger '%s' for the given action time and event type does not exist.

`ER_REFERENCED_TRG_DOES_NOT_EXIST` was added in 5.7.2.

- Error number: 3012; Symbol: `ER_EXPLAIN_NOT_SUPPORTED`; SQLSTATE: `HY000`

Message: EXPLAIN FOR CONNECTION command is supported only for SELECT/UPDATE/INSERT/DELETE/REPLACE

`ER_EXPLAIN_NOT_SUPPORTED` was added in 5.7.2.

- Error number: 3013; Symbol: `ER_INVALID_FIELD_SIZE`; SQLSTATE: `HY000`

Message: Invalid size for column '%s'.

`ER_INVALID_FIELD_SIZE` was added in 5.7.2.

- Error number: 3014; Symbol: `ER_MISSING_HA_CREATE_OPTION`; SQLSTATE: `HY000`

Message: Table storage engine '%s' found required create option missing

`ER_MISSING_HA_CREATE_OPTION` was added in 5.7.2.

- Error number: 3015; Symbol: `ER_ENGINE_OUT_OF_MEMORY`; SQLSTATE: `HY000`

Message: Out of memory in storage engine '%s'.

`ER_ENGINE_OUT_OF_MEMORY` was added in 5.7.3.

-
- Error number: 3016; Symbol: `ER_PASSWORD_EXPIRE_ANONYMOUS_USER`; SQLSTATE: `HY000`

Message: The password for anonymous user cannot be expired.
`ER_PASSWORD_EXPIRE_ANONYMOUS_USER` was added in 5.7.3.
 - Error number: 3017; Symbol: `ER_SLAVE_SQL_THREAD_MUST_STOP`; SQLSTATE: `HY000`

Message: This operation cannot be performed with a running slave sql thread; run STOP SLAVE SQL_THREAD first
`ER_SLAVE_SQL_THREAD_MUST_STOP` was added in 5.7.3.
 - Error number: 3018; Symbol: `ER_NO_FT_MATERIALIZED_SUBQUERY`; SQLSTATE: `HY000`

Message: Cannot create FULLTEXT index on materialized subquery
`ER_NO_FT_MATERIALIZED_SUBQUERY` was added in 5.7.4.
 - Error number: 3019; Symbol: `ER_INNODB_UNDO_LOG_FULL`; SQLSTATE: `HY000`

Message: Undo Log error: %s
`ER_INNODB_UNDO_LOG_FULL` was added in 5.7.4.
 - Error number: 3020; Symbol: `ER_INVALID_ARGUMENT_FOR_LOGARITHM`; SQLSTATE: `2201E`

Message: Invalid argument for logarithm
`ER_INVALID_ARGUMENT_FOR_LOGARITHM` was added in 5.7.4.
 - Error number: 3021; Symbol: `ER_SLAVE_CHANNEL_IO_THREAD_MUST_STOP`; SQLSTATE: `HY000`

Message: This operation cannot be performed with a running slave io thread; run STOP SLAVE IO_THREAD FOR CHANNEL '%s' first.
`ER_SLAVE_CHANNEL_IO_THREAD_MUST_STOP` was added in 5.7.6.
 - Error number: 3022; Symbol: `ER_WARN_OPEN_TEMP_TABLES_MUST_BE_ZERO`; SQLSTATE: `HY000`

Message: This operation may not be safe when the slave has temporary tables. The tables will be kept open until the server restarts or until the tables are deleted by any replicated DROP statement. Suggest to wait until slave_open_temp_tables = 0.
`ER_WARN_OPEN_TEMP_TABLES_MUST_BE_ZERO` was added in 5.7.4.
 - Error number: 3023; Symbol: `ER_WARN_ONLY_MASTER_LOG_FILE_NO_POS`; SQLSTATE: `HY000`

Message: CHANGE MASTER TO with a MASTER_LOG_FILE clause but no MASTER_LOG_POS clause may not be safe. The old position value may not be valid for the new binary log file.
`ER_WARN_ONLY_MASTER_LOG_FILE_NO_POS` was added in 5.7.4.
 - Error number: 3024; Symbol: `ER_QUERY_TIMEOUT`; SQLSTATE: `HY000`

Message: Query execution was interrupted, maximum statement execution time exceeded
`ER_QUERY_TIMEOUT` was added in 5.7.4.
 - Error number: 3025; Symbol: `ER_NON_RO_SELECT_DISABLE_TIMER`; SQLSTATE: `HY000`

Message: Select is not a read only statement, disabling timer

`ER_NON_RO_SELECT_DISABLE_TIMER` was added in 5.7.4.

- Error number: 3026; Symbol: `ER_DUP_LIST_ENTRY`; SQLSTATE: `HY000`

Message: Duplicate entry '%s'.

`ER_DUP_LIST_ENTRY` was added in 5.7.4.

- Error number: 3027; Symbol: `ER_SQL_MODE_NO_EFFECT`; SQLSTATE: `HY000`

Message: '%s' mode no longer has any effect. Use STRICT_ALL_TABLES or STRICT_TRANS_TABLES instead.

`ER_SQL_MODE_NO_EFFECT` was added in 5.7.4.

- Error number: 3028; Symbol: `ER_AGGREGATE_ORDER_FOR_UNION`; SQLSTATE: `HY000`

Message: Expression #%u of ORDER BY contains aggregate function and applies to a UNION

`ER_AGGREGATE_ORDER_FOR_UNION` was added in 5.7.5.

- Error number: 3029; Symbol: `ER_AGGREGATE_ORDER_NON_AGG_QUERY`; SQLSTATE: `HY000`

Message: Expression #%u of ORDER BY contains aggregate function and applies to the result of a non-aggregated query

`ER_AGGREGATE_ORDER_NON_AGG_QUERY` was added in 5.7.5.

- Error number: 3030; Symbol: `ER_SLAVE_WORKER_STOPPED_PREVIOUS_THD_ERROR`; SQLSTATE: `HY000`

Message: Slave worker has stopped after at least one previous worker encountered an error when slave-preserve-commit-order was enabled. To preserve commit order, the last transaction executed by this thread has not been committed. When restarting the slave after fixing any failed threads, you should fix this worker as well.

`ER_SLAVE_WORKER_STOPPED_PREVIOUS_THD_ERROR` was added in 5.7.5.

- Error number: 3031; Symbol: `ER_DONT_SUPPORT_SLAVE_PRESERVE_COMMIT_ORDER`; SQLSTATE: `HY000`

Message: slave_preserve_commit_order is not supported %s.

`ER_DONT_SUPPORT_SLAVE_PRESERVE_COMMIT_ORDER` was added in 5.7.5.

- Error number: 3032; Symbol: `ER_SERVER_OFFLINE_MODE`; SQLSTATE: `HY000`

Message: The server is currently in offline mode

`ER_SERVER_OFFLINE_MODE` was added in 5.7.5.

- Error number: 3033; Symbol: `ER_GIS_DIFFERENT_SRIDS`; SQLSTATE: `HY000`

Message: Binary geometry function %s given two geometries of different srids: %u and %u, which should have been identical.

Geometry values passed as arguments to spatial functions must have the same SRID value.

`ER_GIS_DIFFERENT_SRIDS` was added in 5.7.5.

- Error number: 3034; Symbol: `ER_GIS_UNSUPPORTED_ARGUMENT`; SQLSTATE: `HY000`

Message: Calling geometry function %s with unsupported types of arguments.

A spatial function was called with a combination of argument types that the function does not support.

`ER_GIS_UNSUPPORTED_ARGUMENT` was added in 5.7.5.

- Error number: `3035`; Symbol: `ER_GIS_UNKNOWN_ERROR`; SQLSTATE: `HY000`

Message: Unknown GIS error occurred in function %s.

`ER_GIS_UNKNOWN_ERROR` was added in 5.7.5.

- Error number: `3036`; Symbol: `ER_GIS_UNKNOWN_EXCEPTION`; SQLSTATE: `HY000`

Message: Unknown exception caught in GIS function %s.

`ER_GIS_UNKNOWN_EXCEPTION` was added in 5.7.5.

- Error number: `3037`; Symbol: `ER_GIS_INVALID_DATA`; SQLSTATE: `22023`

Message: Invalid GIS data provided to function %s.

A spatial function was called with an argument not recognized as a valid geometry value.

`ER_GIS_INVALID_DATA` was added in 5.7.5.

- Error number: `3038`; Symbol: `ER_BOOST_GEOMETRY_EMPTY_INPUT_EXCEPTION`; SQLSTATE: `HY000`

Message: The geometry has no data in function %s.

`ER_BOOST_GEOMETRY_EMPTY_INPUT_EXCEPTION` was added in 5.7.5.

- Error number: `3039`; Symbol: `ER_BOOST_GEOMETRY_CENTROID_EXCEPTION`; SQLSTATE: `HY000`

Message: Unable to calculate centroid because geometry is empty in function %s.

`ER_BOOST_GEOMETRY_CENTROID_EXCEPTION` was added in 5.7.5.

- Error number: `3040`; Symbol: `ER_BOOST_GEOMETRY_OVERLAY_INVALID_INPUT_EXCEPTION`; SQLSTATE: `HY000`

Message: Geometry overlay calculation error: geometry data is invalid in function %s.

`ER_BOOST_GEOMETRY_OVERLAY_INVALID_INPUT_EXCEPTION` was added in 5.7.5.

- Error number: `3041`; Symbol: `ER_BOOST_GEOMETRY_TURN_INFO_EXCEPTION`; SQLSTATE: `HY000`

Message: Geometry turn info calculation error: geometry data is invalid in function %s.

`ER_BOOST_GEOMETRY_TURN_INFO_EXCEPTION` was added in 5.7.5.

- Error number: `3042`; Symbol: `ER_BOOST_GEOMETRY_SELF_INTERSECTION_POINT_EXCEPTION`; SQLSTATE: `HY000`

Message: Analysis procedures of intersection points interrupted unexpectedly in function %s.

`ER_BOOST_GEOMETRY_SELF_INTERSECTION_POINT_EXCEPTION` was added in 5.7.5.

- Error number: `3043`; Symbol: `ER_BOOST_GEOMETRY_UNKNOWN_EXCEPTION`; SQLSTATE: `HY000`

Message: Unknown exception thrown in function %s.

`ER_BOOST_GEOMETRY_UNKNOWN_EXCEPTION` was added in 5.7.5.

- Error number: `3044`; Symbol: `ER_STD_BAD_ALLOC_ERROR`; SQLSTATE: `HY000`

Message: Memory allocation error: %s in function %s.

`ER_STD_BAD_ALLOC_ERROR` was added in 5.7.5.

- Error number: `3045`; Symbol: `ER_STD_DOMAIN_ERROR`; SQLSTATE: `HY000`

Message: Domain error: %s in function %s.

`ER_STD_DOMAIN_ERROR` was added in 5.7.5.

- Error number: `3046`; Symbol: `ER_STD_LENGTH_ERROR`; SQLSTATE: `HY000`

Message: Length error: %s in function %s.

`ER_STD_LENGTH_ERROR` was added in 5.7.5.

- Error number: `3047`; Symbol: `ER_STD_INVALID_ARGUMENT`; SQLSTATE: `HY000`

Message: Invalid argument error: %s in function %s.

`ER_STD_INVALID_ARGUMENT` was added in 5.7.5.

- Error number: `3048`; Symbol: `ER_STD_OUT_OF_RANGE_ERROR`; SQLSTATE: `HY000`

Message: Out of range error: %s in function %s.

`ER_STD_OUT_OF_RANGE_ERROR` was added in 5.7.5.

- Error number: `3049`; Symbol: `ER_STD_OVERFLOW_ERROR`; SQLSTATE: `HY000`

Message: Overflow error error: %s in function %s.

`ER_STD_OVERFLOW_ERROR` was added in 5.7.5.

- Error number: `3050`; Symbol: `ER_STD_RANGE_ERROR`; SQLSTATE: `HY000`

Message: Range error: %s in function %s.

`ER_STD_RANGE_ERROR` was added in 5.7.5.

- Error number: `3051`; Symbol: `ER_STD_UNDERFLOW_ERROR`; SQLSTATE: `HY000`

Message: Underflow error: %s in function %s.

`ER_STD_UNDERFLOW_ERROR` was added in 5.7.5.

- Error number: `3052`; Symbol: `ER_STD_LOGIC_ERROR`; SQLSTATE: `HY000`

Message: Logic error: %s in function %s.

`ER_STD_LOGIC_ERROR` was added in 5.7.5.

- Error number: `3053`; Symbol: `ER_STD_RUNTIME_ERROR`; SQLSTATE: `HY000`

Message: Runtime error: %s in function %s.

`ER_STD_RUNTIME_ERROR` was added in 5.7.5.

- Error number: `3054`; Symbol: `ER_STD_UNKNOWN_EXCEPTION`; SQLSTATE: `HY000`

Message: Unknown exception: %s in function %s.

`ER_STD_UNKNOWN_EXCEPTION` was added in 5.7.5.

- Error number: `3055`; Symbol: `ER_GIS_DATA_WRONG_ENDIANESS`; SQLSTATE: `HY000`

Message: Geometry byte string must be little endian.

`ER_GIS_DATA_WRONG_ENDIANESS` was added in 5.7.5.

- Error number: `3056`; Symbol: `ER_CHANGE_MASTER_PASSWORD_LENGTH`; SQLSTATE: `HY000`

Message: The password provided for the replication user exceeds the maximum length of 32 characters

`ER_CHANGE_MASTER_PASSWORD_LENGTH` was added in 5.7.5.

- Error number: `3057`; Symbol: `ER_USER_LOCK_WRONG_NAME`; SQLSTATE: `42000`

Message: Incorrect user-level lock name '%s'.

`ER_USER_LOCK_WRONG_NAME` was added in 5.7.5.

- Error number: `3058`; Symbol: `ER_USER_LOCK_DEADLOCK`; SQLSTATE: `HY000`

Message: Deadlock found when trying to get user-level lock; try rolling back transaction/releasing locks and restarting lock acquisition.

This error is returned when the metadata locking subsystem detects a deadlock for an attempt to acquire a named lock with `GET_LOCK`.

`ER_USER_LOCK_DEADLOCK` was added in 5.7.5.

- Error number: `3059`; Symbol: `ER_REPLACE_INACCESSIBLE_ROWS`; SQLSTATE: `HY000`

Message: REPLACE cannot be executed as it requires deleting rows that are not in the view

`ER_REPLACE_INACCESSIBLE_ROWS` was added in 5.7.5.

- Error number: `3060`; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_GIS`; SQLSTATE: `HY000`

Message: Do not support online operation on table with GIS index

`ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_GIS` was added in 5.7.5.

- Error number: `3061`; Symbol: `ER_ILLEGAL_USER_VAR`; SQLSTATE: `42000`

Message: User variable name '%s' is illegal

`ER_ILLEGAL_USER_VAR` was added in 5.7.5.

- Error number: `3062`; Symbol: `ER_GTID_MODE_OFF`; SQLSTATE: `HY000`

Message: Cannot %s when GTID_MODE = OFF.

`ER_GTID_MODE_OFF` was added in 5.7.5.

- Error number: `3063`; Symbol: `ER_UNSUPPORTED_BY_REPLICATION_THREAD`; SQLSTATE: `HY000`

Message: Cannot %s from a replication slave thread.

`ER_UNSUPPORTED_BY_REPLICATION_THREAD` was added in 5.7.5.

- Error number: 3064; Symbol: `ER_WRONG_TYPE`; SQLSTATE: HY000
Message: Incorrect type for argument %s in function %s.
`ER_WRONG_TYPE` was added in 5.7.5.
- Error number: 3065; Symbol: `ER_FIELD_IN_ORDER_NOT_SELECT`; SQLSTATE: HY000
Message: Expression #%u of ORDER BY clause is not in SELECT list, references column '%s' which is not in SELECT list; this is incompatible with %s
`ER_FIELD_IN_ORDER_NOT_SELECT` was added in 5.7.5.
- Error number: 3066; Symbol: `ER_AGGREGATE_IN_ORDER_NOT_SELECT`; SQLSTATE: HY000
Message: Expression #%u of ORDER BY clause is not in SELECT list, contains aggregate function; this is incompatible with %s
`ER_AGGREGATE_IN_ORDER_NOT_SELECT` was added in 5.7.5.
- Error number: 3067; Symbol: `ER_INVALID_RPL_WILD_TABLE_FILTER_PATTERN`; SQLSTATE: HY000
Message: Supplied filter list contains a value which is not in the required format 'db_pattern.table_pattern'
`ER_INVALID_RPL_WILD_TABLE_FILTER_PATTERN` was added in 5.7.5.
- Error number: 3068; Symbol: `ER_NET_OK_PACKET_TOO_LARGE`; SQLSTATE: 08S01
Message: OK packet too large
`ER_NET_OK_PACKET_TOO_LARGE` was added in 5.7.5.
- Error number: 3069; Symbol: `ER_INVALID_JSON_DATA`; SQLSTATE: HY000
Message: Invalid JSON data provided to function %s: %s
`ER_INVALID_JSON_DATA` was added in 5.7.5.
- Error number: 3070; Symbol: `ER_INVALID_GEOJSON_MISSING_MEMBER`; SQLSTATE: HY000
Message: Invalid GeoJSON data provided to function %s: Missing required member '%s'
`ER_INVALID_GEOJSON_MISSING_MEMBER` was added in 5.7.5.
- Error number: 3071; Symbol: `ER_INVALID_GEOJSON_WRONG_TYPE`; SQLSTATE: HY000
Message: Invalid GeoJSON data provided to function %s: Member '%s' must be of type '%s'
`ER_INVALID_GEOJSON_WRONG_TYPE` was added in 5.7.5.
- Error number: 3072; Symbol: `ER_INVALID_GEOJSON_UNSPECIFIED`; SQLSTATE: HY000
Message: Invalid GeoJSON data provided to function %s
`ER_INVALID_GEOJSON_UNSPECIFIED` was added in 5.7.5.
- Error number: 3073; Symbol: `ER_DIMENSION_UNSUPPORTED`; SQLSTATE: HY000
Message: Unsupported number of coordinate dimensions in function %s: Found %u, expected %u
`ER_DIMENSION_UNSUPPORTED` was added in 5.7.5.

- Error number: 3074; Symbol: `ER_SLAVE_CHANNEL_DOES_NOT_EXIST`; SQLSTATE: `HY000`

Message: Slave channel '%s' does not exist.
`ER_SLAVE_CHANNEL_DOES_NOT_EXIST` was added in 5.7.6.
- Error number: 3075; Symbol: `ER_SLAVE_MULTIPLE_CHANNELS_HOST_PORT`; SQLSTATE: `HY000`

Message: A slave channel '%s' already exists for the given host and port combination.
`ER_SLAVE_MULTIPLE_CHANNELS_HOST_PORT` was added in 5.7.6.
- Error number: 3076; Symbol: `ER_SLAVE_CHANNEL_NAME_INVALID_OR_TOO_LONG`; SQLSTATE: `HY000`

Message: Couldn't create channel: Channel name is either invalid or too long.
`ER_SLAVE_CHANNEL_NAME_INVALID_OR_TOO_LONG` was added in 5.7.6.
- Error number: 3077; Symbol: `ER_SLAVE_NEW_CHANNEL_WRONG_REPOSITORY`; SQLSTATE: `HY000`

Message: To have multiple channels, repository cannot be of type FILE; Please check the repository configuration and convert them to TABLE.
`ER_SLAVE_NEW_CHANNEL_WRONG_REPOSITORY` was added in 5.7.6.
- Error number: 3078; Symbol: `ER_SLAVE_CHANNEL_DELETE`; SQLSTATE: `HY000`

Message: Cannot delete slave info objects for channel '%s'.
`ER_SLAVE_CHANNEL_DELETE` was added in 5.7.6.
- Error number: 3079; Symbol: `ER_SLAVE_MULTIPLE_CHANNELS_CMD`; SQLSTATE: `HY000`

Message: Multiple channels exist on the slave. Please provide channel name as an argument.
`ER_SLAVE_MULTIPLE_CHANNELS_CMD` was added in 5.7.6.
- Error number: 3080; Symbol: `ER_SLAVE_MAX_CHANNELS_EXCEEDED`; SQLSTATE: `HY000`

Message: Maximum number of replication channels allowed exceeded.
`ER_SLAVE_MAX_CHANNELS_EXCEEDED` was added in 5.7.6.
- Error number: 3081; Symbol: `ER_SLAVE_CHANNEL_MUST_STOP`; SQLSTATE: `HY000`

Message: This operation cannot be performed with running replication threads; run STOP SLAVE FOR CHANNEL '%s' first
`ER_SLAVE_CHANNEL_MUST_STOP` was added in 5.7.6.
- Error number: 3082; Symbol: `ER_SLAVE_CHANNEL_NOT_RUNNING`; SQLSTATE: `HY000`

Message: This operation requires running replication threads; configure slave and run START SLAVE FOR CHANNEL '%s'
`ER_SLAVE_CHANNEL_NOT_RUNNING` was added in 5.7.6.
- Error number: 3083; Symbol: `ER_SLAVE_CHANNEL_WAS_RUNNING`; SQLSTATE: `HY000`

Message: Replication thread(s) for channel '%s' are already running.
`ER_SLAVE_CHANNEL_WAS_RUNNING` was added in 5.7.6.

- Error number: 3084; Symbol: `ER_SLAVE_CHANNEL_WAS_NOT_RUNNING`; SQLSTATE: `HY000`

Message: Replication thread(s) for channel '%s' are already stopped.

`ER_SLAVE_CHANNEL_WAS_NOT_RUNNING` was added in 5.7.6.

- Error number: 3085; Symbol: `ER_SLAVE_CHANNEL_SQL_THREAD_MUST_STOP`; SQLSTATE: `HY000`

Message: This operation cannot be performed with a running slave sql thread; run STOP SLAVE SQL_THREAD FOR CHANNEL '%s' first.

`ER_SLAVE_CHANNEL_SQL_THREAD_MUST_STOP` was added in 5.7.6.

- Error number: 3086; Symbol: `ER_SLAVE_CHANNEL_SQL_SKIP_COUNTER`; SQLSTATE: `HY000`

Message: When `sql_slave_skip_counter > 0`, it is not allowed to start more than one SQL thread by using 'START SLAVE [SQL_THREAD]'. Value of `sql_slave_skip_counter` can only be used by one SQL thread at a time. Please use 'START SLAVE [SQL_THREAD] FOR CHANNEL' to start the SQL thread which will use the value of `sql_slave_skip_counter`.

`ER_SLAVE_CHANNEL_SQL_SKIP_COUNTER` was added in 5.7.6.

- Error number: 3087; Symbol: `ER_WRONG_FIELD_WITH_GROUP_V2`; SQLSTATE: `HY000`

Message: Expression #`%u` of %s is not in GROUP BY clause and contains nonaggregated column '%s' which is not functionally dependent on columns in GROUP BY clause; this is incompatible with `sql_mode=only_full_group_by`

`ER_WRONG_FIELD_WITH_GROUP_V2` was added in 5.7.6.

- Error number: 3088; Symbol: `ER_MIX_OF_GROUP_FUNC_AND_FIELDS_V2`; SQLSTATE: `HY000`

Message: In aggregated query without GROUP BY, expression #`%u` of %s contains nonaggregated column '%s'; this is incompatible with `sql_mode=only_full_group_by`

`ER_MIX_OF_GROUP_FUNC_AND_FIELDS_V2` was added in 5.7.6.

- Error number: 3089; Symbol: `ER_WARN_DEPRECATED_SYSVAR_UPDATE`; SQLSTATE: `HY000`

Message: Updating '%s' is deprecated. It will be made read-only in a future release.

`ER_WARN_DEPRECATED_SYSVAR_UPDATE` was added in 5.7.6.

- Error number: 3090; Symbol: `ER_WARN_DEPRECATED_SQLMODE`; SQLSTATE: `HY000`

Message: Changing sql mode '%s' is deprecated. It will be removed in a future release.

`ER_WARN_DEPRECATED_SQLMODE` was added in 5.7.6.

- Error number: 3091; Symbol: `ER_CANNOT_LOG_PARTIAL_DROP_DATABASE_WITH_GTID`; SQLSTATE: `HY000`

Message: DROP DATABASE failed; some tables may have been dropped but the database directory remains. The GTID has not been added to `GTID_EXECUTED` and the statement was not written to the binary log. Fix this as follows: (1) remove all files from the database directory %s; (2) SET `GTID_NEXT=%s`; (3) DROP DATABASE `'%s`'.

`ER_CANNOT_LOG_PARTIAL_DROP_DATABASE_WITH_GTID` was added in 5.7.6.

-
- Error number: 3092; Symbol: `ER_GROUP_REPLICATION_CONFIGURATION`; SQLSTATE: `HY000`

Message: The server is not configured properly to be an active member of the group. Please see more details on error log.

`ER_GROUP_REPLICATION_CONFIGURATION` was added in 5.7.6.

- Error number: 3093; Symbol: `ER_GROUP_REPLICATION_RUNNING`; SQLSTATE: `HY000`

Message: The START GROUP_REPLICATION command failed since the group is already running.

`ER_GROUP_REPLICATION_RUNNING` was added in 5.7.6.

- Error number: 3094; Symbol: `ER_GROUP_REPLICATION_APPLIER_INIT_ERROR`; SQLSTATE: `HY000`

Message: The START GROUP_REPLICATION command failed as the applier module failed to start.

`ER_GROUP_REPLICATION_APPLIER_INIT_ERROR` was added in 5.7.6.

- Error number: 3095; Symbol: `ER_GROUP_REPLICATION_STOP_APPLIER_THREAD_TIMEOUT`; SQLSTATE: `HY000`

Message: The STOP GROUP_REPLICATION command execution is incomplete: The applier thread got the stop signal while it was busy. The applier thread will stop once the current task is complete.

`ER_GROUP_REPLICATION_STOP_APPLIER_THREAD_TIMEOUT` was added in 5.7.6.

- Error number: 3096; Symbol:

`ER_GROUP_REPLICATION_COMMUNICATION_LAYER_SESSION_ERROR`; SQLSTATE: `HY000`

Message: The START GROUP_REPLICATION command failed as there was an error when initializing the group communication layer.

`ER_GROUP_REPLICATION_COMMUNICATION_LAYER_SESSION_ERROR` was added in 5.7.6.

- Error number: 3097; Symbol: `ER_GROUP_REPLICATION_COMMUNICATION_LAYER_JOIN_ERROR`; SQLSTATE: `HY000`

Message: The START GROUP_REPLICATION command failed as there was an error when joining the communication group.

`ER_GROUP_REPLICATION_COMMUNICATION_LAYER_JOIN_ERROR` was added in 5.7.6.

- Error number: 3098; Symbol: `ER_BEFORE_DML_VALIDATION_ERROR`; SQLSTATE: `HY000`

Message: The table does not comply with the requirements by an external plugin.

`ER_BEFORE_DML_VALIDATION_ERROR` was added in 5.7.6.

- Error number: 3099; Symbol: `ER_PREVENTS_VARIABLE_WITHOUT_RBR`; SQLSTATE: `HY000`

Message: Cannot change the value of variable %s without binary log format as ROW.

From 5.7.6: `transaction_write_set_extraction` option value is set and `binlog_format` is not ROW.

`ER_PREVENTS_VARIABLE_WITHOUT_RBR` was added in 5.7.6.

-
- Error number: [3100](#); Symbol: [ER_RUN_HOOK_ERROR](#); SQLSTATE: [HY000](#)

Message: Error on observer while running replication hook '%s'.

[ER_RUN_HOOK_ERROR](#) was added in 5.7.6.

- Error number: [3101](#); Symbol: [ER_TRANSACTION_ROLLBACK_DURING_COMMIT](#); SQLSTATE: [HY000](#)

Message: Plugin instructed the server to rollback the current transaction.

When using Group Replication, this means that a transaction failed the group certification process, due to one or more members detecting a potential conflict, and was thus rolled back. See [Group Replication](#).

[ER_TRANSACTION_ROLLBACK_DURING_COMMIT](#) was added in 5.7.6.

- Error number: [3102](#); Symbol: [ER_GENERATED_COLUMN_FUNCTION_IS_NOT_ALLOWED](#); SQLSTATE: [HY000](#)

Message: Expression of generated column '%s' contains a disallowed function.

[ER_GENERATED_COLUMN_FUNCTION_IS_NOT_ALLOWED](#) was added in 5.7.6.

- Error number: [3103](#); Symbol: [ER_KEY_BASED_ON_GENERATED_COLUMN](#); SQLSTATE: [HY000](#)

Message: Key/Index cannot be defined on a virtual generated column.

[ER_KEY_BASED_ON_GENERATED_COLUMN](#) was added in 5.7.6, removed after 5.7.7.

- Error number: [3103](#); Symbol: [ER_UNSUPPORTED_ALTER_INPLACE_ON_VIRTUAL_COLUMN](#); SQLSTATE: [HY000](#)

Message: INPLACE ADD or DROP of virtual columns cannot be combined with other ALTER TABLE actions

[ER_UNSUPPORTED_ALTER_INPLACE_ON_VIRTUAL_COLUMN](#) was added in 5.7.8.

- Error number: [3104](#); Symbol: [ER_WRONG_FK_OPTION_FOR_GENERATED_COLUMN](#); SQLSTATE: [HY000](#)

Message: Cannot define foreign key with %s clause on a generated column.

[ER_WRONG_FK_OPTION_FOR_GENERATED_COLUMN](#) was added in 5.7.6.

- Error number: [3105](#); Symbol: [ER_NON_DEFAULT_VALUE_FOR_GENERATED_COLUMN](#); SQLSTATE: [HY000](#)

Message: The value specified for generated column '%s' in table '%s' is not allowed.

[ER_NON_DEFAULT_VALUE_FOR_GENERATED_COLUMN](#) was added in 5.7.6.

- Error number: [3106](#); Symbol: [ER_UNSUPPORTED_ACTION_ON_GENERATED_COLUMN](#); SQLSTATE: [HY000](#)

Message: '%s' is not supported for generated columns.

[ER_UNSUPPORTED_ACTION_ON_GENERATED_COLUMN](#) was added in 5.7.6.

-
- Error number: [3107](#); Symbol: [ER_GENERATED_COLUMN_NON_PRIOR](#); SQLSTATE: [HY000](#)

Message: Generated column can refer only to generated columns defined prior to it.

To address this issue, change the table definition to define each generated column later than any generated columns to which it refers.

[ER_GENERATED_COLUMN_NON_PRIOR](#) was added in 5.7.6.
 - Error number: [3108](#); Symbol: [ER_DEPENDENT_BY_GENERATED_COLUMN](#); SQLSTATE: [HY000](#)

Message: Column '%s' has a generated column dependency.

You cannot drop or rename a generated column if another column refers to it. You must either drop those columns as well, or redefine them not to refer to the generated column.

[ER_DEPENDENT_BY_GENERATED_COLUMN](#) was added in 5.7.6.
 - Error number: [3109](#); Symbol: [ER_GENERATED_COLUMN_REF_AUTO_INC](#); SQLSTATE: [HY000](#)

Message: Generated column '%s' cannot refer to auto-increment column.

[ER_GENERATED_COLUMN_REF_AUTO_INC](#) was added in 5.7.6.
 - Error number: [3110](#); Symbol: [ER_FEATURE_NOT_AVAILABLE](#); SQLSTATE: [HY000](#)

Message: The '%s' feature is not available; you need to remove '%s' or use MySQL built with '%s'

[ER_FEATURE_NOT_AVAILABLE](#) was added in 5.7.6.
 - Error number: [3111](#); Symbol: [ER_CANT_SET_GTID_MODE](#); SQLSTATE: [HY000](#)

Message: SET @@GLOBAL.GTID_MODE = %s is not allowed because %s.

[ER_CANT_SET_GTID_MODE](#) was added in 5.7.6.
 - Error number: [3112](#); Symbol: [ER_CANT_USE_AUTO_POSITION_WITH_GTID_MODE_OFF](#); SQLSTATE: [HY000](#)

Message: The replication receiver thread%s cannot start in AUTO_POSITION mode: this server uses @@GLOBAL.GTID_MODE = OFF.

[ER_CANT_USE_AUTO_POSITION_WITH_GTID_MODE_OFF](#) was added in 5.7.6.
 - Error number: [3113](#); Symbol: [ER_CANT_REPLICATE_ANONYMOUS_WITH_AUTO_POSITION](#); SQLSTATE: [HY000](#)

Message: Cannot replicate anonymous transaction when AUTO_POSITION = 1, at file %s, position %lld.

[ER_CANT_REPLICATE_ANONYMOUS_WITH_AUTO_POSITION](#) was added in 5.7.6.
 - Error number: [3114](#); Symbol: [ER_CANT_REPLICATE_ANONYMOUS_WITH_GTID_MODE_ON](#); SQLSTATE: [HY000](#)

Message: Cannot replicate anonymous transaction when @@GLOBAL.GTID_MODE = ON, at file %s, position %lld.

[ER_CANT_REPLICATE_ANONYMOUS_WITH_GTID_MODE_ON](#) was added in 5.7.6.

-
- Error number: 3115; Symbol: `ER_CANT_REPLICATE_GTID_WITH_GTID_MODE_OFF`; SQLSTATE: `HY000`

Message: Cannot replicate GTID-transaction when @@GLOBAL.GTID_MODE = OFF, at file %s, position %lld.

`ER_CANT_REPLICATE_GTID_WITH_GTID_MODE_OFF` was added in 5.7.6.

- Error number: 3116; Symbol:
`ER_CANT_SET_ENFORCE_GTID_CONSISTENCY_ON_WITH_ONGOING_GTID_VIOLATING_TRANSACTIONS`; SQLSTATE: `HY000`

Message: Cannot set ENFORCE_GTID_CONSISTENCY = ON because there are ongoing transactions that violate GTID consistency.

`ER_CANT_SET_ENFORCE_GTID_CONSISTENCY_ON_WITH_ONGOING_GTID_VIOLATING_TRANSACTIONS` is renamed to `ER_CANT_ENFORCE_GTID_CONSISTENCY_WITH_ONGOING_GTID_VIOLATING_TX` in MySQL 8.0.

`ER_CANT_SET_ENFORCE_GTID_CONSISTENCY_ON_WITH_ONGOING_GTID_VIOLATING_TRANSACTIONS` was added in 5.7.6.

- Error number: 3117; Symbol:
`ER_SET_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONGOING_GTID_VIOLATING_TRANSACTIONS`; SQLSTATE: `HY000`

Message: There are ongoing transactions that violate GTID consistency.

`ER_SET_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONGOING_GTID_VIOLATING_TRANSACTIONS` is renamed to `ER_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONGOING_GTID_VIOLATING_TX` in MySQL 8.0.

`ER_SET_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONGOING_GTID_VIOLATING_TRANSACTIONS` was added in 5.7.6.

- Error number: 3118; Symbol: `ER_ACCOUNT_HAS_BEEN_LOCKED`; SQLSTATE: `HY000`

Message: Access denied for user '%s'@'%s'. Account is locked.

The account was locked with `CREATE USER ... ACCOUNT LOCK` or `ALTER USER ... ACCOUNT LOCK`. An administrator can unlock it with `ALTER USER ... ACCOUNT UNLOCK`.

`ER_ACCOUNT_HAS_BEEN_LOCKED` was added in 5.7.6.

- Error number: 3119; Symbol: `ER_WRONG_TABLESPACE_NAME`; SQLSTATE: `42000`

Message: Incorrect tablespace name `'%s'

`ER_WRONG_TABLESPACE_NAME` was added in 5.7.6.

- Error number: 3120; Symbol: `ER_TABLESPACE_IS_NOT_EMPTY`; SQLSTATE: `HY000`

Message: Tablespace `'%s` is not empty.

`ER_TABLESPACE_IS_NOT_EMPTY` was added in 5.7.6.

- Error number: 3121; Symbol: `ER_WRONG_FILE_NAME`; SQLSTATE: `HY000`

Message: Incorrect File Name `'%s'`.

`ER_WRONG_FILE_NAME` was added in 5.7.6.

-
- Error number: [3122](#); Symbol: [ER_BOOST_GEOMETRY_INCONSISTENT_TURNS_EXCEPTION](#); SQLSTATE: [HY000](#)

Message: Inconsistent intersection points.
[ER_BOOST_GEOMETRY_INCONSISTENT_TURNS_EXCEPTION](#) was added in 5.7.7.
 - Error number: [3123](#); Symbol: [ER_WARN_OPTIMIZER_HINT_SYNTAX_ERROR](#); SQLSTATE: [HY000](#)

Message: Optimizer hint syntax error
[ER_WARN_OPTIMIZER_HINT_SYNTAX_ERROR](#) was added in 5.7.7.
 - Error number: [3124](#); Symbol: [ER_WARN_BAD_MAX_EXECUTION_TIME](#); SQLSTATE: [HY000](#)

Message: Unsupported MAX_EXECUTION_TIME
[ER_WARN_BAD_MAX_EXECUTION_TIME](#) was added in 5.7.7.
 - Error number: [3125](#); Symbol: [ER_WARN_UNSUPPORTED_MAX_EXECUTION_TIME](#); SQLSTATE: [HY000](#)

Message: MAX_EXECUTION_TIME hint is supported by top-level standalone SELECT statements only
The [MAX_EXECUTION_TIME](#) optimizer hint is supported only for [SELECT](#) statements.
[ER_WARN_UNSUPPORTED_MAX_EXECUTION_TIME](#) was added in 5.7.7.
 - Error number: [3126](#); Symbol: [ER_WARN_CONFLICTING_HINT](#); SQLSTATE: [HY000](#)

Message: Hint %s is ignored as conflicting/duplicated
[ER_WARN_CONFLICTING_HINT](#) was added in 5.7.7.
 - Error number: [3127](#); Symbol: [ER_WARN_UNKNOWN_QB_NAME](#); SQLSTATE: [HY000](#)

Message: Query block name %s is not found for %s hint
[ER_WARN_UNKNOWN_QB_NAME](#) was added in 5.7.7.
 - Error number: [3128](#); Symbol: [ER_UNRESOLVED_HINT_NAME](#); SQLSTATE: [HY000](#)

Message: Unresolved name %s for %s hint
[ER_UNRESOLVED_HINT_NAME](#) was added in 5.7.7.
 - Error number: [3129](#); Symbol: [ER_WARN_DEPRECATED_SQLMODE_UNSET](#); SQLSTATE: [HY000](#)

Message: Unsetting sql mode '%s' is deprecated. It will be made read-only in a future release.
[ER_WARN_DEPRECATED_SQLMODE_UNSET](#) was added in 5.7.7, removed after 5.7.7.
 - Error number: [3129](#); Symbol: [ER_WARN_ON MODIFYING_GTID_EXECUTED_TABLE](#); SQLSTATE: [HY000](#)

Message: Please do not modify the %s table. This is a mysql internal system table to store GTIDs for committed transactions. Modifying it can lead to an inconsistent GTID state.
[ER_WARN_ON MODIFYING_GTID_EXECUTED_TABLE](#) was added in 5.7.8.
 - Error number: [3130](#); Symbol: [ER_PLUGGABLE_PROTOCOL_COMMAND_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)

Message: Command not supported by pluggable protocols

`ER_PLUGGABLE_PROTOCOL_COMMAND_NOT_SUPPORTED` was added in 5.7.8.

- Error number: 3131; Symbol: `ER_LOCKING_SERVICE_WRONG_NAME`; SQLSTATE: `42000`

Message: Incorrect locking service lock name '%s'.

A locking service name was specified as `NULL`, the empty string, or a string longer than 64 characters. Namespace and lock names must be non-`NULL`, nonempty, and no more than 64 characters long.

`ER_LOCKING_SERVICE_WRONG_NAME` was added in 5.7.8.

- Error number: 3132; Symbol: `ER_LOCKING_SERVICE_DEADLOCK`; SQLSTATE: `HY000`

Message: Deadlock found when trying to get locking service lock; try releasing locks and restarting lock acquisition.

`ER_LOCKING_SERVICE_DEADLOCK` was added in 5.7.8.

- Error number: 3133; Symbol: `ER_LOCKING_SERVICE_TIMEOUT`; SQLSTATE: `HY000`

Message: Service lock wait timeout exceeded.

`ER_LOCKING_SERVICE_TIMEOUT` was added in 5.7.8.

- Error number: 3134; Symbol: `ER_GIS_MAX_POINTS_IN_GEOMETRY_OVERFLOWED`; SQLSTATE: `HY000`

Message: Parameter %s exceeds the maximum number of points in a geometry (%lu) in function %s.

`ER_GIS_MAX_POINTS_IN_GEOMETRY_OVERFLOWED` was added in 5.7.8.

- Error number: 3135; Symbol: `ER_SQL_MODE_MERGED`; SQLSTATE: `HY000`

Message: 'NO_ZERO_DATE', 'NO_ZERO_IN_DATE' and 'ERROR_FOR_DIVISION_BY_ZERO' sql modes should be used with strict mode. They will be merged with strict mode in a future release.

`ER_SQL_MODE_MERGED` was added in 5.7.8.

- Error number: 3136; Symbol: `ER_VTOKEN_PLUGIN_TOKEN_MISMATCH`; SQLSTATE: `HY000`

Message: Version token mismatch for %.*.s. Correct value %.*.s

The client has set its `version_tokens_session` system variable to the list of tokens it requires the server to match, but the server token list has at least one matching token name that has a value different from what the client requires. See [Version Tokens](#).

`ER_VTOKEN_PLUGIN_TOKEN_MISMATCH` was added in 5.7.8.

- Error number: 3137; Symbol: `ER_VTOKEN_PLUGIN_TOKEN_NOT_FOUND`; SQLSTATE: `HY000`

Message: Version token %.*.s not found.

The client has set its `version_tokens_session` system variable to the list of tokens it requires the server to match, but the server token list is missing at least one of those tokens. See [Version Tokens](#).

`ER_VTOKEN_PLUGIN_TOKEN_NOT_FOUND` was added in 5.7.8.

-
- Error number: [3138](#); Symbol: [ER_CANT_SET_VARIABLE_WHEN_OWNING_GTID](#); SQLSTATE: [HY000](#)

Message: Variable %s cannot be changed by a client that owns a GTID. The client owns %s. Ownership is released on COMMIT or ROLLBACK.

[ER_CANT_SET_VARIABLE_WHEN_OWNING_GTID](#) was added in 5.7.8.
 - Error number: [3139](#); Symbol: [ER_SLAVE_CHANNEL_OPERATION_NOT_ALLOWED](#); SQLSTATE: [HY000](#)

Message: %s cannot be performed on channel '%s'.

[ER_SLAVE_CHANNEL_OPERATION_NOT_ALLOWED](#) was added in 5.7.8.
 - Error number: [3140](#); Symbol: [ER_INVALID_JSON_TEXT](#); SQLSTATE: [22032](#)

Message: Invalid JSON text: "%s" at position %u in value for column '%s'.

[ER_INVALID_JSON_TEXT](#) was added in 5.7.8.
 - Error number: [3141](#); Symbol: [ER_INVALID_JSON_TEXT_IN_PARAM](#); SQLSTATE: [22032](#)

Message: Invalid JSON text in argument %u to function %s: "%s" at position %u.%s

[ER_INVALID_JSON_TEXT_IN_PARAM](#) was added in 5.7.8.
 - Error number: [3142](#); Symbol: [ER_INVALID_JSON_BINARY_DATA](#); SQLSTATE: [HY000](#)

Message: The JSON binary value contains invalid data.

[ER_INVALID_JSON_BINARY_DATA](#) was added in 5.7.8.
 - Error number: [3143](#); Symbol: [ER_INVALID_JSON_PATH](#); SQLSTATE: [42000](#)

Message: Invalid JSON path expression. The error is around character position %u.%s

[ER_INVALID_JSON_PATH](#) was added in 5.7.8.
 - Error number: [3144](#); Symbol: [ER_INVALID_JSON_CHARSET](#); SQLSTATE: [22032](#)

Message: Cannot create a JSON value from a string with CHARACTER SET '%s'.

[ER_INVALID_JSON_CHARSET](#) was added in 5.7.8.
 - Error number: [3145](#); Symbol: [ER_INVALID_JSON_CHARSET_IN_FUNCTION](#); SQLSTATE: [22032](#)

Message: Invalid JSON character data provided to function %s: '%s'; utf8 is required.

[ER_INVALID_JSON_CHARSET_IN_FUNCTION](#) was added in 5.7.8.
 - Error number: [3146](#); Symbol: [ER_INVALID_TYPE_FOR_JSON](#); SQLSTATE: [22032](#)

Message: Invalid data type for JSON data in argument %u to function %s; a JSON string or JSON type is required.

[ER_INVALID_TYPE_FOR_JSON](#) was added in 5.7.8.
 - Error number: [3147](#); Symbol: [ER_INVALID_CAST_TO_JSON](#); SQLSTATE: [22032](#)

Message: Cannot CAST value to JSON.

[ER_INVALID_CAST_TO_JSON](#) was added in 5.7.8.

- Error number: 3148; Symbol: [ER_INVALID_JSON_PATH_CHARSET](#); SQLSTATE: 42000

Message: A path expression must be encoded in the utf8 character set. The path expression '%s' is encoded in character set '%s'.
[ER_INVALID_JSON_PATH_CHARSET](#) was added in 5.7.8.
- Error number: 3149; Symbol: [ER_INVALID_JSON_PATH_WILDCARD](#); SQLSTATE: 42000

Message: In this situation, path expressions may not contain the * and ** tokens.
[ER_INVALID_JSON_PATH_WILDCARD](#) was added in 5.7.8.
- Error number: 3150; Symbol: [ER_JSON_VALUE_TOO_BIG](#); SQLSTATE: 22032

Message: The JSON value is too big to be stored in a JSON column.
[ER_JSON_VALUE_TOO_BIG](#) was added in 5.7.8.
- Error number: 3151; Symbol: [ER_JSON_KEY_TOO_BIG](#); SQLSTATE: 22032

Message: The JSON object contains a key name that is too long.
[ER_JSON_KEY_TOO_BIG](#) was added in 5.7.8.
- Error number: 3152; Symbol: [ER_JSON_USED_AS_KEY](#); SQLSTATE: 42000

Message: JSON column '%s' cannot be used in key specification.
[ER_JSON_USED_AS_KEY](#) was added in 5.7.8.
- Error number: 3153; Symbol: [ER_JSON_VACUOUS_PATH](#); SQLSTATE: 42000

Message: The path expression '\$' is not allowed in this context.
[ER_JSON_VACUOUS_PATH](#) was added in 5.7.8.
- Error number: 3154; Symbol: [ER_JSON_BAD_ONE_OR_ALL_ARG](#); SQLSTATE: 42000

Message: The oneOrAll argument to %s may take these values: 'one' or 'all'.
[ER_JSON_BAD_ONE_OR_ALL_ARG](#) was added in 5.7.8.
- Error number: 3155; Symbol: [ER_NUMERIC_JSON_VALUE_OUT_OF_RANGE](#); SQLSTATE: 22003

Message: Out of range JSON value for CAST to %s%s from column %s at row %ld
[ER_NUMERIC_JSON_VALUE_OUT_OF_RANGE](#) was added in 5.7.8.
- Error number: 3156; Symbol: [ER_INVALID_JSON_VALUE_FOR_CAST](#); SQLSTATE: 22018

Message: Invalid JSON value for CAST to %s%s from column %s at row %ld
[ER_INVALID_JSON_VALUE_FOR_CAST](#) was added in 5.7.8.
- Error number: 3157; Symbol: [ER_JSON_DOCUMENT_TOO_DEEP](#); SQLSTATE: 22032

Message: The JSON document exceeds the maximum depth.
[ER_JSON_DOCUMENT_TOO_DEEP](#) was added in 5.7.8.
- Error number: 3158; Symbol: [ER_JSON_DOCUMENT_NULL_KEY](#); SQLSTATE: 22032

Message: JSON documents may not contain NULL member names.

`ER_JSON_DOCUMENT_NULL_KEY` was added in 5.7.8.

- Error number: 3159; Symbol: `ER_SECURE_TRANSPORT_REQUIRED`; SQLSTATE: HY000

Message: Connections using insecure transport are prohibited while --require_secure_transport=ON.

With the `require_secure_transport` system variable, clients can connect only using secure transports. Qualifying connections are those using SSL, a Unix socket file, or shared memory.

`ER_SECURE_TRANSPORT_REQUIRED` was added in 5.7.8.

- Error number: 3160; Symbol: `ER_NO_SECURE_TRANSPORTS_CONFIGURED`; SQLSTATE: HY000

Message: No secure transports (SSL or Shared Memory) are configured, unable to set --require_secure_transport=ON.

The `require_secure_transport` system variable cannot be enabled if the server does not support at least one secure transport. Configure the server with the required SSL keys/certificates to enable SSL connections, or enable the `shared_memory` system variable to enable shared-memory connections.

`ER_NO_SECURE_TRANSPORTS_CONFIGURED` was added in 5.7.8.

- Error number: 3161; Symbol: `ER_DISABLED_STORAGE_ENGINE`; SQLSTATE: HY000

Message: Storage engine %s is disabled (Table creation is disallowed).

An attempt was made to create a table or tablespace using a storage engine listed in the value of the `disabled_storage_engines` system variable, or to change an existing table or tablespace to such an engine. Choose a different storage engine.

`ER_DISABLED_STORAGE_ENGINE` was added in 5.7.8.

- Error number: 3162; Symbol: `ER_USER_DOES_NOT_EXIST`; SQLSTATE: HY000

Message: User %s does not exist.

`ER_USER_DOES_NOT_EXIST` was added in 5.7.8.

- Error number: 3163; Symbol: `ER_USER_ALREADY_EXISTS`; SQLSTATE: HY000

Message: User %s already exists.

`ER_USER_ALREADY_EXISTS` was added in 5.7.8.

- Error number: 3164; Symbol: `ER_AUDIT_API_ABORT`; SQLSTATE: HY000

Message: Aborted by Audit API ('%s';%d).

This error indicates that an audit plugin terminated execution of an event. The message typically indicates the event subclass name and a numeric status value.

`ER_AUDIT_API_ABORT` was added in 5.7.8.

- Error number: 3165; Symbol: `ER_INVALID_JSON_PATH_ARRAY_CELL`; SQLSTATE: 42000

Message: A path expression is not a path to a cell in an array.

`ER_INVALID_JSON_PATH_ARRAY_CELL` was added in 5.7.8.

- Error number: 3166; Symbol: `ER_BUFPOLL_RESIZE_INPROGRESS`; SQLSTATE: HY000

Message: Another buffer pool resize is already in progress.

`ER_BUFPOOL_RESIZE_INPROGRESS` was added in 5.7.9.

- Error number: 3167; Symbol: `ER_FEATURE_DISABLED_SEE_DOC`; SQLSTATE: `HY000`

Message: The '%s' feature is disabled; see the documentation for '%s'

`ER_FEATURE_DISABLED_SEE_DOC` was added in 5.7.9.

- Error number: 3168; Symbol: `ER_SERVER_ISNT_AVAILABLE`; SQLSTATE: `HY000`

Message: Server isn't available

`ER_SERVER_ISNT_AVAILABLE` was added in 5.7.9.

- Error number: 3169; Symbol: `ER_SESSION_WAS_KILLED`; SQLSTATE: `HY000`

Message: Session was killed

`ER_SESSION_WAS_KILLED` was added in 5.7.9.

- Error number: 3170; Symbol: `ER_CAPACITY_EXCEEDED`; SQLSTATE: `HY000`

Message: Memory capacity of %llu bytes for '%s' exceeded. %s

`ER_CAPACITY_EXCEEDED` was added in 5.7.9.

- Error number: 3171; Symbol: `ER_CAPACITY_EXCEEDED_IN_RANGE_OPTIMIZER`; SQLSTATE: `HY000`

Message: Range optimization was not done for this query.

`ER_CAPACITY_EXCEEDED_IN_RANGE_OPTIMIZER` was added in 5.7.9.

- Error number: 3172; Symbol: `ER_TABLE_NEEDS_UPG_PART`; SQLSTATE: `HY000`

Message: Partitioning upgrade required. Please dump/reload to fix it or do: ALTER TABLE `'%s`.`%s`' UPGRADE PARTITIONING

`ER_TABLE_NEEDS_UPG_PART` was added in 5.7.9.

- Error number: 3173; Symbol: `ER_CANT_WAIT_FOR_EXECUTED_GTID_SET_WHILE_OWNING_A_GTID`; SQLSTATE: `HY000`

Message: The client holds ownership of the GTID %s. Therefore, WAIT_FOR_EXECUTED_GTID_SET cannot wait for this GTID.

`ER_CANT_WAIT_FOR_EXECUTED_GTID_SET_WHILE_OWNING_A_GTID` was added in 5.7.9.

- Error number: 3174; Symbol: `ER_CANNOT_ADD_FOREIGN_BASE_COL_VIRTUAL`; SQLSTATE: `HY000`

Message: Cannot add foreign key on the base column of indexed virtual column.

`ER_CANNOT_ADD_FOREIGN_BASE_COL_VIRTUAL` was added in 5.7.10.

- Error number: 3175; Symbol: `ER_CANNOT_CREATE_VIRTUAL_INDEX_CONSTRAINT`; SQLSTATE: `HY000`

Message: Cannot create index on virtual column whose base column has foreign constraint.

`ER_CANNOT_CREATE_VIRTUAL_INDEX_CONSTRAINT` was added in 5.7.10.

-
- Error number: [3176](#); Symbol: [ER_ERROR_ON MODIFYING_GTID_EXECUTED_TABLE](#); SQLSTATE: [HY000](#)

Message: Please do not modify the %s table with an XA transaction. This is an internal system table used to store GTIDs for committed transactions. Although modifying it can lead to an inconsistent GTID state, if necessary you can modify it with a non-XA transaction.

[ER_ERROR_ON MODIFYING_GTID_EXECUTED_TABLE](#) was added in 5.7.11.

- Error number: [3177](#); Symbol: [ER_LOCK_REFUSED_BY_ENGINE](#); SQLSTATE: [HY000](#)

Message: Lock acquisition refused by storage engine.

[ER_LOCK_REFUSED_BY_ENGINE](#) was added in 5.7.11.

- Error number: [3178](#); Symbol: [ER_UNSUPPORTED_ALTER_ONLINE_ON_VIRTUAL_COLUMN](#); SQLSTATE: [HY000](#)

Message: ADD COLUMN col...VIRTUAL, ADD INDEX(col)

[ER_UNSUPPORTED_ALTER_ONLINE_ON_VIRTUAL_COLUMN](#) was added in 5.7.11.

- Error number: [3179](#); Symbol: [ER_MASTER_KEY_ROTATION_NOT_SUPPORTED_BY_SE](#); SQLSTATE: [HY000](#)

Message: Master key rotation is not supported by storage engine.

[ER_MASTER_KEY_ROTATION_NOT_SUPPORTED_BY_SE](#) was added in 5.7.11.

- Error number: [3180](#); Symbol: [ER_MASTER_KEY_ROTATION_ERROR_BY_SE](#); SQLSTATE: [HY000](#)

Message: Encryption key rotation error reported by SE: %s

[ER_MASTER_KEY_ROTATION_ERROR_BY_SE](#) was added in 5.7.11.

- Error number: [3181](#); Symbol: [ER_MASTER_KEY_ROTATION_BINLOG_FAILED](#); SQLSTATE: [HY000](#)

Message: Write to binlog failed. However, master key rotation has been completed successfully.

[ER_MASTER_KEY_ROTATION_BINLOG_FAILED](#) was added in 5.7.11.

- Error number: [3182](#); Symbol: [ER_MASTER_KEY_ROTATION_SE_UNAVAILABLE](#); SQLSTATE: [HY000](#)

Message: Storage engine is not available.

[ER_MASTER_KEY_ROTATION_SE_UNAVAILABLE](#) was added in 5.7.11.

- Error number: [3183](#); Symbol: [ER_TABLESPACE_CANNOT_ENCRYPT](#); SQLSTATE: [HY000](#)

Message: This tablespace can't be encrypted.

[ER_TABLESPACE_CANNOT_ENCRYPT](#) was added in 5.7.11.

- Error number: [3184](#); Symbol: [ER_INVALID_ENCRYPTION_OPTION](#); SQLSTATE: [HY000](#)

Message: Invalid encryption option.

[ER_INVALID_ENCRYPTION_OPTION](#) was added in 5.7.11.

- Error number: [3185](#); Symbol: [ER_CANNOT_FIND_KEY_IN_KEYRING](#); SQLSTATE: [HY000](#)

Message: Can't find master key from keyring, please check in the server log if a keyring plugin is loaded and initialized successfully.

`ER_CANNOT_FIND_KEY_IN_KEYRING` was added in 5.7.11.

- Error number: 3186; Symbol: `ER_CAPACITY_EXCEEDED_IN_PARSER`; SQLSTATE: `HY000`

Message: Parser bailed out for this query.

`ER_CAPACITY_EXCEEDED_IN_PARSER` was added in 5.7.12.

- Error number: 3187; Symbol: `ER_UNSUPPORTED_ALTER_ENCRYPTION_INPLACE`; SQLSTATE: `HY000`

Message: Cannot alter encryption attribute by inplace algorithm.

`ER_UNSUPPORTED_ALTER_ENCRYPTION_INPLACE` was added in 5.7.13.

- Error number: 3188; Symbol: `ER_KEYRING_UDF_KEYRING_SERVICE_ERROR`; SQLSTATE: `HY000`

Message: Function '%s' failed because underlying keyring service returned an error. Please check if a keyring plugin is installed and that provided arguments are valid for the keyring you are using.

`ER_KEYRING_UDF_KEYRING_SERVICE_ERROR` was added in 5.7.13.

- Error number: 3189; Symbol: `ER_USER_COLUMN_OLD_LENGTH`; SQLSTATE: `HY000`

Message: It seems that your db schema is old. The %s column is 77 characters long and should be 93 characters long. Please run mysql_upgrade.

`ER_USER_COLUMN_OLD_LENGTH` was added in 5.7.13.

- Error number: 3190; Symbol: `ER_CANT_RESET_MASTER`; SQLSTATE: `HY000`

Message: RESET MASTER is not allowed because %s.

`ER_CANT_RESET_MASTER` was added in 5.7.14.

- Error number: 3191; Symbol: `ER_GROUP_REPLICATION_MAX_GROUP_SIZE`; SQLSTATE: `HY000`

Message: The START GROUP_REPLICATION command failed since the group already has 9 members.

`ER_GROUP_REPLICATION_MAX_GROUP_SIZE` was added in 5.7.14.

- Error number: 3192; Symbol: `ER_CANNOT_ADD_FOREIGN_BASE_COL_STORED`; SQLSTATE: `HY000`

Message: Cannot add foreign key on the base column of stored column.

`ER_CANNOT_ADD_FOREIGN_BASE_COL_STORED` was added in 5.7.14.

- Error number: 3193; Symbol: `ER_TABLE_REFERENCED`; SQLSTATE: `HY000`

Message: Cannot complete the operation because table is referenced by another connection.

`ER_TABLE_REFERENCED` was added in 5.7.14.

- Error number: 3194; Symbol: `ER_PARTITION_ENGINE_DEPRECATED_FOR_TABLE`; SQLSTATE: `HY000`

Message: The partition engine, used by table '%s.%s', is deprecated and will be removed in a future release. Please use native partitioning instead.

`ER_PARTITION_ENGINE_DEPRECATED_FOR_TABLE` was added in 5.7.17.

-
- Error number: [3195](#); Symbol: [ER_WARN_USING_GEOMFROMWKB_TO_SET_SRID_ZERO](#); SQLSTATE: [01000](#)

Message: %s(geometry) is deprecated and will be replaced by st_srid(geometry, 0) in a future version. Use %s(st_aswkb(geometry), 0) instead.

[ER_WARN_USING_GEOMFROMWKB_TO_SET_SRID_ZERO](#) was added in 5.7.19.

- Error number: [3196](#); Symbol: [ER_WARN_USING_GEOMFROMWKB_TO_SET_SRID](#); SQLSTATE: [01000](#)

Message: %s(geometry, srid) is deprecated and will be replaced by st_srid(geometry, srid) in a future version. Use %s(st_aswkb(geometry), srid) instead.

[ER_WARN_USING_GEOMFROMWKB_TO_SET_SRID](#) was added in 5.7.19.

- Error number: [3197](#); Symbol: [ER_XA_RETRY](#); SQLSTATE: [HY000](#)

Message: The resource manager is not able to commit the transaction branch at this time. Please retry later.

[ER_XA_RETRY](#) was added in 5.7.19.

- Error number: [3198](#); Symbol: [ER_KEYRING_AWS_UDF_AWS_KMS_ERROR](#); SQLSTATE: [HY000](#)

Message: Function %s failed due to: %s.

[ER_KEYRING_AWS_UDF_AWS_KMS_ERROR](#) was added in 5.7.19.

- Error number: [3199](#); Symbol: [ER_BINLOG_UNSAFE_XA](#); SQLSTATE: [HY000](#)

Message: Statement is unsafe because it is being used inside a XA transaction. Concurrent XA transactions may deadlock on slaves when replicated using statements.

[ER_BINLOG_UNSAFE_XA](#) was added in 5.7.20.

- Error number: [3200](#); Symbol: [ER_UDF_ERROR](#); SQLSTATE: [HY000](#)

Message: %s UDF failed; %s

[ER_UDF_ERROR](#) was added in 5.7.21.

- Error number: [3201](#); Symbol: [ER_KEYRING_MIGRATION_FAILURE](#); SQLSTATE: [HY000](#)

Message: Can not perform keyring migration : %s

[ER_KEYRING_MIGRATION_FAILURE](#) was added in 5.7.21.

- Error number: [3202](#); Symbol: [ER_KEYRING_ACCESS_DENIED_ERROR](#); SQLSTATE: [42000](#)

Message: Access denied; you need %s privileges for this operation

[ER_KEYRING_ACCESS_DENIED_ERROR](#) was added in 5.7.21.

- Error number: [3203](#); Symbol: [ER_KEYRING_MIGRATION_STATUS](#); SQLSTATE: [HY000](#)

Message: Keyring migration %s.

[ER_KEYRING_MIGRATION_STATUS](#) was added in 5.7.21.

- Error number: [3204](#); Symbol: [ER_PLUGIN_FAILED_TO_OPEN_TABLES](#); SQLSTATE: [HY000](#)

Message: Failed to open the %s filter tables.

`ER_PLUGIN_FAILED_TO_OPEN_TABLES` was added in 5.7.22.

- Error number: 3205; Symbol: `ER_PLUGIN_FAILED_TO_OPEN_TABLE`; SQLSTATE: `HY000`

Message: Failed to open '%s.%s' %s table.

`ER_PLUGIN_FAILED_TO_OPEN_TABLE` was added in 5.7.22.

- Error number: 3206; Symbol: `ER_AUDIT_LOG_NO_KEYRING_PLUGIN_INSTALLED`; SQLSTATE: `HY000`

Message: No keyring plugin installed.

`ER_AUDIT_LOG_NO_KEYRING_PLUGIN_INSTALLED` was added in 5.7.22.

- Error number: 3207; Symbol: `ER_AUDIT_LOG_ENCRYPTION_PASSWORD_HAS_NOT_BEEN_SET`; SQLSTATE: `HY000`

Message: Audit log encryption password has not been set; it will be generated automatically. Use `audit_log_encryption_password_get` to obtain the password or `audit_log_encryption_password_set` to set a new one.

`ER_AUDIT_LOG_ENCRYPTION_PASSWORD_HAS_NOT_BEEN_SET` was added in 5.7.22.

- Error number: 3208; Symbol: `ER_AUDIT_LOG_COULD_NOT_CREATE_AES_KEY`; SQLSTATE: `HY000`

Message: Could not create AES key. OpenSSL's EVP_BytesToKey function failed.

`ER_AUDIT_LOG_COULD_NOT_CREATE_AES_KEY` was added in 5.7.22.

- Error number: 3209; Symbol: `ER_AUDIT_LOG_ENCRYPTION_PASSWORD_CANNOT_BE_FETCHED`; SQLSTATE: `HY000`

Message: Audit log encryption password cannot be fetched from the keyring. Password used so far is used for encryption.

`ER_AUDIT_LOG_ENCRYPTION_PASSWORD_CANNOT_BE_FETCHED` was added in 5.7.22.

- Error number: 3210; Symbol: `ER_AUDIT_LOG_JSON_FILTERING_NOT_ENABLED`; SQLSTATE: `HY000`

Message: Audit Log filtering has not been installed.

`ER_AUDIT_LOG_JSON_FILTERING_NOT_ENABLED` was added in 5.7.22.

- Error number: 3211; Symbol: `ER_AUDIT_LOG_UDF_INSUFFICIENT_PRIVILEGE`; SQLSTATE: `HY000`

Message: Request ignored for '%s'@'%s'. SUPER_ACL needed to perform operation

`ER_AUDIT_LOG_UDF_INSUFFICIENT_PRIVILEGE` was added in 5.7.22.

- Error number: 3212; Symbol: `ER_AUDIT_LOG_SUPER_PRIVILEGE_REQUIRED`; SQLSTATE: `HY000`

Message: SUPER privilege required for '%s'@'%s' user.

`ER_AUDIT_LOG_SUPER_PRIVILEGE_REQUIRED` was added in 5.7.22.

- Error number: 3213; Symbol: `ER_COULD_NOT_REINITIALIZE_AUDIT_LOG_FILTERS`; SQLSTATE: `HY000`

Message: Could not reinitialize audit log filters.

`ER_COULD_NOT_REINITIALIZE_AUDIT_LOG_FILTERS` was added in 5.7.22.

- Error number: `3214`; Symbol: `ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_TYPE`; SQLSTATE: `HY000`

Message: Invalid argument type

`ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_TYPE` was added in 5.7.22.

- Error number: `3215`; Symbol: `ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_COUNT`; SQLSTATE: `HY000`

Message: Invalid argument count

`ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_COUNT` was added in 5.7.22.

- Error number: `3216`; Symbol: `ER_AUDIT_LOG_HAS_NOT_BEEN_INSTALLED`; SQLSTATE: `HY000`

Message: audit_log plugin has not been installed using INSTALL PLUGIN syntax.

`ER_AUDIT_LOG_HAS_NOT_BEEN_INSTALLED` was added in 5.7.22.

- Error number: `3217`; Symbol:

`ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH_ARG_TYPE`; SQLSTATE: `HY000`

Message: Invalid "max_array_length" argument type.

`ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH_ARG_TYPE` was added in 5.7.22.

- Error number: `3218`; Symbol:

`ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH_ARG_VALUE`; SQLSTATE: `HY000`

Message: Invalid "max_array_length" argument value.

`ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH_ARG_VALUE` was added in 5.7.22.

- Error number: `3219`; Symbol: `ER_AUDIT_LOG_JSON_FILTER_PARSING_ERROR`; SQLSTATE: `HY000`

Message: %s

`ER_AUDIT_LOG_JSON_FILTER_PARSING_ERROR` was added in 5.7.22.

- Error number: `3220`; Symbol: `ER_AUDIT_LOG_JSON_FILTER_NAME_CANNOT_BE_EMPTY`; SQLSTATE: `HY000`

Message: Filter name cannot be empty.

`ER_AUDIT_LOG_JSON_FILTER_NAME_CANNOT_BE_EMPTY` was added in 5.7.22.

- Error number: `3221`; Symbol: `ER_AUDIT_LOG_JSON_USER_NAME_CANNOT_BE_EMPTY`; SQLSTATE: `HY000`

Message: User cannot be empty.

`ER_AUDIT_LOG_JSON_USER_NAME_CANNOT_BE_EMPTY` was added in 5.7.22.

- Error number: `3222`; Symbol: `ER_AUDIT_LOG_JSON_FILTER_DOES_NOT_EXISTS`; SQLSTATE: `HY000`

Message: Specified filter has not been found.

`ER_AUDIT_LOG_JSON_FILTER_DOES_NOT_EXISTS` was added in 5.7.22.

- Error number: 3223; Symbol:

`ER_AUDIT_LOG_USER_FIRST_CHARACTER_MUST_BE_ALPHANUMERIC`; SQLSTATE: `HY000`

Message: First character of the user name must be alphanumeric.

`ER_AUDIT_LOG_USER_FIRST_CHARACTER_MUST_BE_ALPHANUMERIC` was added in 5.7.22.

- Error number: 3224; Symbol: `ER_AUDIT_LOG_USER_NAME_INVALID_CHARACTER`; SQLSTATE: `HY000`

Message: Invalid character in the user name.

`ER_AUDIT_LOG_USER_NAME_INVALID_CHARACTER` was added in 5.7.22.

- Error number: 3225; Symbol: `ER_AUDIT_LOG_HOST_NAME_INVALID_CHARACTER`; SQLSTATE: `HY000`

Message: Invalid character in the host name.

`ER_AUDIT_LOG_HOST_NAME_INVALID_CHARACTER` was added in 5.7.22.

- Error number: 3226; Symbol: `WARN_DEPRECATED_MAXDB_SQL_MODE_FOR_TIMESTAMP`; SQLSTATE: `HY000`

Message: With the MAXDB SQL mode enabled, TIMESTAMP is identical with DATETIME. The MAXDB SQL mode is deprecated and will be removed in a future release. Please disable the MAXDB SQL mode and use DATETIME instead.

`WARN_DEPRECATED_MAXDB_SQL_MODE_FOR_TIMESTAMP` was added in 5.7.22.

- Error number: 3227; Symbol: `ER_XA_REPLICATION_FILTERS`; SQLSTATE: `HY000`

Message: The use of replication filters with XA transactions is not supported, and can lead to an undefined state in the replication slave.

`ER_XA_REPLICATION_FILTERS` was added in 5.7.23.

- Error number: 3228; Symbol: `ER_CANT_OPEN_ERROR_LOG`; SQLSTATE: `HY000`

Message: Could not open file '%s' for error logging%~~%s~~

`ER_CANT_OPEN_ERROR_LOG` was added in 5.7.24.

- Error number: 3229; Symbol: `ER_GROUPING_ON_TIMESTAMP_IN_DST`; SQLSTATE: `HY000`

Message: Grouping on temporal is non-deterministic for timezones having DST. Please consider switching to UTC for this query.

`ER_GROUPING_ON_TIMESTAMP_IN_DST` was added in 5.7.27.

- Error number: 3230; Symbol: `ER_CANT_START_SERVER_NAMED_PIPE`; SQLSTATE: `HY000`

Message: Can't start server : Named Pipe "%s" already in use.

`ER_CANT_START_SERVER_NAMED_PIPE` was added in 5.7.27.

- Error number: 3231; Symbol: `ER_WRITE_SET_EXCEEDS_LIMIT`; SQLSTATE: `HY000`

Message: The size of writeset data for the current transaction exceeds a limit imposed by an external component. If using Group Replication check 'group_replication_transaction_size_limit'.

`ER_WRITE_SET_EXCEEDS_LIMIT` was added in 5.7.33.

- Error number: `3232`; Symbol: `ER_DEPRECATED_TLS_VERSION_SESSION`; SQLSTATE: `HY000`

Message: Accepted a connection with deprecated protocol '%s' for account `'%s`@`%s` from host `'%s`. Client supplied username `'%s`

`ER_DEPRECATED_TLS_VERSION_SESSION` was added in 5.7.35.

- Error number: `3233`; Symbol: `ER_WARN_DEPRECATED_TLS_VERSION`; SQLSTATE: `HY000`

Message: A deprecated TLS version %s is enabled. Please use TLSv1.2 or higher.

`ER_WARN_DEPRECATED_TLS_VERSION` was added in 5.7.35.

- Error number: `3234`; Symbol: `ER_WARN_WRONG_NATIVE_TABLE_STRUCTURE`; SQLSTATE: `HY000`

Message: Optional native table '%s'.'%s' has the wrong structure or is missing.

`ER_WARN_WRONG_NATIVE_TABLE_STRUCTURE` was added in 5.7.39.

- Error number: `3235`; Symbol: `ER_AES_INVALID_KDF_NAME`; SQLSTATE: `HY000`

Message: KDF method name is not valid. Please use hkdf or pbkdf2_hmac method name

`ER_AES_INVALID_KDF_NAME` was added in 5.7.40.

- Error number: `3236`; Symbol: `ER_AES_INVALID_KDF_ITERATIONS`; SQLSTATE: `HY000`

Message: For KDF method pbkdf2_hmac iterations value less than 1000 or more than 65535 is not allowed due to security reasons. Please provide iterations ≥ 1000 and iterations < 65535

`ER_AES_INVALID_KDF_ITERATIONS` was added in 5.7.40.

- Error number: `3237`; Symbol: `WARN_AES_KEY_SIZE`; SQLSTATE: `HY000`

Message: AES key size should be %d bytes length or secure KDF methods hkdf or pbkdf2_hmac should be used, please provide exact AES key size or use KDF methods for better security.

`WARN_AES_KEY_SIZE` was added in 5.7.40.

- Error number: `3238`; Symbol: `ER_AES_INVALID_KDF_OPTION_SIZE`; SQLSTATE: `HY000`

Message: KDF option size is invalid, please provide valid size $< %d$ bytes and not NULL

`ER_AES_INVALID_KDF_OPTION_SIZE` was added in 5.7.40.

Chapter 3 Client Error Message Reference

Client error messages originate from within the MySQL client library. Here is an example client error message, as displayed by the `mysql` client:

```
$> mysql -h no-such-host
ERROR 2005 (HY000): Unknown MySQL server host 'no-such-host' (0)
```

Each client error message includes an error code, SQLSTATE value, and message string, as described in [Error Message Sources and Elements](#). These elements are available as described in [Error Information Interfaces](#). For client errors, the SQLSTATE value is always '`HY000`' (general error), so it is not meaningful for distinguishing one client error from another.

The client library also makes available to host client programs any errors that originate on the server side and are received by the client from the server. For a list of server-side errors, see [Chapter 2, Server Error Message Reference](#).

In addition to the errors in the following list, the client library can also produce error messages that have error codes in the range from 1 to 999. See [Chapter 4, Global Error Message Reference](#)

- Error number: `2000`; Symbol: `CR_UNKNOWN_ERROR`;
Message: Unknown MySQL error
- Error number: `2001`; Symbol: `CR_SOCKET_CREATE_ERROR`;
Message: Can't create UNIX socket (%d)
- Error number: `2002`; Symbol: `CR_CONNECTION_ERROR`;
Message: Can't connect to local MySQL server through socket '%s' (%d)
- Error number: `2003`; Symbol: `CR_CONN_HOST_ERROR`;
Message: Can't connect to MySQL server on '%s' (%d)
- Error number: `2004`; Symbol: `CR_IPSOCK_ERROR`;
Message: Can't create TCP/IP socket (%d)
- Error number: `2005`; Symbol: `CR_UNKNOWN_HOST`;
Message: Unknown MySQL server host '%s' (%d)
- Error number: `2006`; Symbol: `CR_SERVER_GONE_ERROR`;
Message: MySQL server has gone away
- Error number: `2007`; Symbol: `CR_VERSION_ERROR`;
Message: Protocol mismatch; server version = %d, client version = %d
- Error number: `2008`; Symbol: `CR_OUT_OF_MEMORY`;
Message: MySQL client ran out of memory
- Error number: `2009`; Symbol: `CR_WRONG_HOST_INFO`;
Message: Wrong host info
- Error number: `2010`; Symbol: `CR_LOCALHOST_CONNECTION`;
Message: Localhost via UNIX socket

- Error number: 2011; Symbol: `CR_TCP_CONNECTION`;
Message: %s via TCP/IP
- Error number: 2012; Symbol: `CR_SERVER_HANDSHAKE_ERR`;
Message: Error in server handshake
- Error number: 2013; Symbol: `CR_SERVER_LOST`;
Message: Lost connection to MySQL server during query
- Error number: 2014; Symbol: `CR_COMMANDS_OUT_OF_SYNC`;
Message: Commands out of sync; you can't run this command now

Commands were executed in an improper order. This error occurs when a function is called that is not appropriate for the current state of the connection. For example, if `mysql_stmt_fetch()` is not called enough times to read an entire result set (that is, enough times to return `MYSQL_NO_DATA`), this error may occur for the following C API call.
- Error number: 2015; Symbol: `CR_NAMEDPIPE_CONNECTION`;
Message: Named pipe: %s
- Error number: 2016; Symbol: `CR_NAMEDPIPEWAIT_ERROR`;
Message: Can't wait for named pipe to host: %s pipe: %s (%lu)
- Error number: 2017; Symbol: `CR_NAMEDPIPEOPEN_ERROR`;
Message: Can't open named pipe to host: %s pipe: %s (%lu)
- Error number: 2018; Symbol: `CR_NAMEDPIPESETSTATE_ERROR`;
Message: Can't set state of named pipe to host: %s pipe: %s (%lu)
- Error number: 2019; Symbol: `CR_CANT_READ_CHARSET`;
Message: Can't initialize character set %s (path: %s)
- Error number: 2020; Symbol: `CR_NET_PACKET_TOO_LARGE`;
Message: Got packet bigger than 'max_allowed_packet' bytes
- Error number: 2021; Symbol: `CR_EMBEDDED_CONNECTION`;
Message: Embedded server
- Error number: 2022; Symbol: `CR_PROBE_SLAVE_STATUS`;
Message: Error on SHOW SLAVE STATUS:
- Error number: 2023; Symbol: `CR_PROBE_SLAVE_HOSTS`;
Message: Error on SHOW SLAVE HOSTS:
- Error number: 2024; Symbol: `CR_PROBE_SLAVE_CONNECT`;
Message: Error connecting to slave:
- Error number: 2025; Symbol: `CR_PROBE_MASTER_CONNECT`;
Message: Error connecting to master:

-
- Error number: 2026; Symbol: `CR_SSL_CONNECTION_ERROR`;
Message: SSL connection error: %s
 - Error number: 2027; Symbol: `CR_MALFORMED_PACKET`;
Message: Malformed packet
 - Error number: 2028; Symbol: `CR_WRONG_LICENSE`;
Message: This client library is licensed only for use with MySQL servers having '%s' license
 - Error number: 2029; Symbol: `CR_NULL_POINTER`;
Message: Invalid use of null pointer
 - Error number: 2030; Symbol: `CR_NO_PREPARE_STMT`;
Message: Statement not prepared
 - Error number: 2031; Symbol: `CR_PARAMS_NOT_BOUND`;
Message: No data supplied for parameters in prepared statement
 - Error number: 2032; Symbol: `CR_DATA_TRUNCATED`;
Message: Data truncated
 - Error number: 2033; Symbol: `CR_NO_PARAMETERS_EXISTS`;
Message: No parameters exist in the statement
 - Error number: 2034; Symbol: `CR_INVALID_PARAMETER_NO`;
Message: Invalid parameter number

The column number for `mysql_stmt_fetch_column()` was invalid.

The parameter number for `mysql_stmt_send_long_data()` was invalid.

A key name was empty or the amount of connection attribute data for `mysql_options4()` exceeds the 64KB limit.
 - Error number: 2035; Symbol: `CR_INVALID_BUFFER_USE`;
Message: Can't send long data for non-string/non-binary data types (parameter: %d)
 - Error number: 2036; Symbol: `CR_UNSUPPORTED_PARAM_TYPE`;
Message: Using unsupported buffer type: %d (parameter: %d)
 - Error number: 2037; Symbol: `CR_SHARED_MEMORY_CONNECTION`;
Message: Shared memory: %s
 - Error number: 2038; Symbol: `CR_SHARED_MEMORY_CONNECT_REQUEST_ERROR`;
Message: Can't open shared memory; client could not create request event (%lu)
 - Error number: 2039; Symbol: `CR_SHARED_MEMORY_CONNECT_ANSWER_ERROR`;
Message: Can't open shared memory; no answer event received from server (%lu)
 - Error number: 2040; Symbol: `CR_SHARED_MEMORY_CONNECT_FILE_MAP_ERROR`;

Message: Can't open shared memory; server could not allocate file mapping (%lu)

- Error number: 2041; Symbol: `CR_SHARED_MEMORY_CONNECT_MAP_ERROR`;

Message: Can't open shared memory; server could not get pointer to file mapping (%lu)

- Error number: 2042; Symbol: `CR_SHARED_MEMORY_FILE_MAP_ERROR`;

Message: Can't open shared memory; client could not allocate file mapping (%lu)

- Error number: 2043; Symbol: `CR_SHARED_MEMORY_MAP_ERROR`;

Message: Can't open shared memory; client could not get pointer to file mapping (%lu)

- Error number: 2044; Symbol: `CR_SHARED_MEMORY_EVENT_ERROR`;

Message: Can't open shared memory; client could not create %s event (%lu)

- Error number: 2045; Symbol: `CR_SHARED_MEMORY_CONNECT_ABANDONED_ERROR`;

Message: Can't open shared memory; no answer from server (%lu)

- Error number: 2046; Symbol: `CR_SHARED_MEMORY_CONNECT_SET_ERROR`;

Message: Can't open shared memory; cannot send request event to server (%lu)

- Error number: 2047; Symbol: `CR_CONN_UNKNOW_PROTOCOL`;

Message: Wrong or unknown protocol

- Error number: 2048; Symbol: `CR_INVALID_CONN_HANDLE`;

Message: Invalid connection handle

- Error number: 2049; Symbol: `CR_SECURE_AUTH`;

Message: Connection using old (pre-4.1.1) authentication protocol refused (client option 'secure_auth' enabled)

`CR_SECURE_AUTH` was removed after 5.7.4.

- Error number: 2049; Symbol: `CR_UNUSED_1`;

Message: Connection using old (pre-4.1.1) authentication protocol refused (client option 'secure_auth' enabled)

`CR_UNUSED_1` was added in 5.7.5.

- Error number: 2050; Symbol: `CR_FETCH_CANCELED`;

Message: Row retrieval was canceled by `mysql_stmt_close()` call

- Error number: 2051; Symbol: `CR_NO_DATA`;

Message: Attempt to read column without prior row fetch

- Error number: 2052; Symbol: `CR_NO_STMT_METADATA`;

Message: Prepared statement contains no metadata

- Error number: 2053; Symbol: `CR_NO_RESULT_SET`;

Message: Attempt to read a row while there is no result set associated with the statement

-
- Error number: [2054](#); Symbol: [CR_NOT_IMPLEMENTED](#);
Message: This feature is not implemented yet
 - Error number: [2055](#); Symbol: [CR_SERVER_LOST_EXTENDED](#);
Message: Lost connection to MySQL server at '%s', system error: %d
 - Error number: [2056](#); Symbol: [CR_STMT_CLOSED](#);
Message: Statement closed indirectly because of a preceding %s() call
 - Error number: [2057](#); Symbol: [CR_NEW_STMT_METADATA](#);
Message: The number of columns in the result set differs from the number of bound buffers. You must reset the statement, rebind the result set columns, and execute the statement again
 - Error number: [2058](#); Symbol: [CR_ALREADY_CONNECTED](#);
Message: This handle is already connected. Use a separate handle for each connection.
 - Error number: [2059](#); Symbol: [CR_AUTH_PLUGIN_CANNOT_LOAD](#);
Message: Authentication plugin '%s' cannot be loaded: %s
 - Error number: [2060](#); Symbol: [CR_DUPLICATE_CONNECTION_ATTR](#);
Message: There is an attribute with the same name already
A duplicate connection attribute name was specified for `mysql_options4()`.
 - Error number: [2061](#); Symbol: [CR_AUTH_PLUGIN_ERR](#);
Message: Authentication plugin '%s' reported error: %s
[CR_AUTH_PLUGIN_ERR](#) was added in 5.7.1.
 - Error number: [2062](#); Symbol: [CR_INSECURE_API_ERR](#);
Message: Insecure API function call: '%s' Use instead: '%s'
An insecure function call was detected. Modify the application to use the suggested alternative function instead.
[CR_INSECURE_API_ERR](#) was added in 5.7.6.
 - Error number: [2063](#); Symbol: [CR_INVALID_CLIENT_CHARSET](#);
Message: '%s' character set is having more than 1 byte minimum character length, which cannot be used as a client character set. Please use any of the single byte minimum ones, e.g. utf8mb4, latin1 etc.
[CR_INVALID_CLIENT_CHARSET](#) was added in 5.7.42.

Chapter 4 Global Error Message Reference

This document lists “global” error messages that are shared in the sense that they can be produced by the MySQL server or by MySQL client programs. These errors have error codes in the range from 1 to 999.

Each global error message includes an error code, SQLSTATE value, and message string, as described in [Error Message Sources and Elements](#). These elements are available as described in [Error Information Interfaces](#). For global errors, the SQLSTATE value is always '`HY000`' (general error), so it is not meaningful for distinguishing one client error from another.

- Error number: `1`; Symbol: `EE_CANTCREATEFILE`;

Message: Can't create/write to file '%s' (Errcode: %d - %s)

- Error number: `2`; Symbol: `EE_READ`;

Message: Error reading file '%s' (Errcode: %d - %s)

- Error number: `3`; Symbol: `EE_WRITE`;

Message: Error writing file '%s' (Errcode: %d - %s)

- Error number: `4`; Symbol: `EE_BADCLOSE`;

Message: Error on close of '%s' (Errcode: %d - %s)

- Error number: `5`; Symbol: `EE_OUTOFMEMORY`;

Message: Out of memory (Needed %u bytes)

- Error number: `6`; Symbol: `EE_DELETE`;

Message: Error on delete of '%s' (Errcode: %d - %s)

- Error number: `7`; Symbol: `EE_LINK`;

Message: Error on rename of '%s' to '%s' (Errcode: %d - %s)

- Error number: `9`; Symbol: `EE_EOFERR`;

Message: Unexpected EOF found when reading file '%s' (Errcode: %d - %s)

- Error number: `10`; Symbol: `EE_CANTLOCK`;

Message: Can't lock file (Errcode: %d - %s)

- Error number: `11`; Symbol: `EE_CANTUNLOCK`;

Message: Can't unlock file (Errcode: %d - %s)

- Error number: `12`; Symbol: `EE_DIR`;

Message: Can't read dir of '%s' (Errcode: %d - %s)

- Error number: `13`; Symbol: `EE_STAT`;

Message: Can't get stat of '%s' (Errcode: %d - %s)

- Error number: `14`; Symbol: `EE_CANT_CHSIZE`;

Message: Can't change size of file (Errcode: %d - %s)

- Error number: 15; Symbol: [EE_CANT_OPEN_STREAM](#);
Message: Can't open stream from handle (Errcode: %d - %s)
- Error number: 16; Symbol: [EE_GETWD](#);
Message: Can't get working directory (Errcode: %d - %s)
- Error number: 17; Symbol: [EE_SETWD](#);
Message: Can't change dir to '%s' (Errcode: %d - %s)
- Error number: 18; Symbol: [EE_LINK_WARNING](#);
Message: Warning: '%s' had %d links
- Error number: 19; Symbol: [EE_OPEN_WARNING](#);
Message: Warning: %d files and %d streams is left open
- Error number: 20; Symbol: [EE_DISK_FULL](#);
Message: Disk is full writing '%s' (Errcode: %d - %s). Waiting for someone to free space...
- Error number: 21; Symbol: [EE_CANT_MKDIR](#);
Message: Can't create directory '%s' (Errcode: %d - %s)
- Error number: 22; Symbol: [EE_UNKNOWN_CHARSET](#);
Message: Character set '%s' is not a compiled character set and is not specified in the '%s' file
- Error number: 23; Symbol: [EE_OUT_OF_FILERESOURCES](#);
Message: Out of resources when opening file '%s' (Errcode: %d - %s)
- Error number: 24; Symbol: [EE_CANT_READLINK](#);
Message: Can't read value for symlink '%s' (Error %d - %s)
- Error number: 25; Symbol: [EE_CANT_SYMLINK](#);
Message: Can't create symlink '%s' pointing at '%s' (Error %d - %s)
- Error number: 26; Symbol: [EE_REALPATH](#);
Message: Error on realpath() on '%s' (Error %d - %s)
- Error number: 27; Symbol: [EE_SYNC](#);
Message: Can't sync file '%s' to disk (Errcode: %d - %s)
- Error number: 28; Symbol: [EE_UNKNOWN_COLLATION](#);
Message: Collation '%s' is not a compiled collation and is not specified in the '%s' file
- Error number: 29; Symbol: [EE_FILENOFOUND](#);
Message: File '%s' not found (Errcode: %d - %s)
- Error number: 30; Symbol: [EE_FILE_NOT_CLOSED](#);
Message: File '%s' (fileno: %d) was not closed
- Error number: 31; Symbol: [EE_CHANGE_OWNERSHIP](#);

Message: Can't change ownership of the file '%s' (Errcode: %d - %s)

- Error number: 32; Symbol: `EE_CHANGE_PERMISSIONS`;

Message: Can't change permissions of the file '%s' (Errcode: %d - %s)

- Error number: 33; Symbol: `EE_CANT_SEEK`;

Message: Can't seek in file '%s' (Errcode: %d - %s)

- Error number: 34; Symbol: `EE_CAPACITY_EXCEEDED`;

Message: Memory capacity exceeded (capacity %llu bytes)

`EE_CAPACITY_EXCEEDED` was added in 5.7.9.

Index

C

CR_ALREADY_CONNECTED error code, 99
CR_AUTH_PLUGIN_CANNOT_LOAD error code, 99
CR_AUTH_PLUGIN_ERR error code, 99
CR_CANT_READ_CHARSET error code, 96
CR_COMMANDS_OUT_OF_SYNC error code, 96
CR_CONNECTION_ERROR error code, 95
CR_CONN_HOST_ERROR error code, 95
CR_CONN_UNKNOW_PROTOCOL error code, 98
CR_DATA_TRUNCATED error code, 97
CR_DUPLICATE_CONNECTION_ATTR error code, 99
CR_EMBEDDED_CONNECTION error code, 96
CR_FETCH_CANCELED error code, 98
CR_INSECURE_API_ERR error code, 99
CR_INVALID_BUFFER_USE error code, 97
CR_INVALID_CLIENT_CHARSET error code, 99
CR_INVALID_CONN_HANDLE error code, 98
CR_INVALID_PARAMETER_NO error code, 97
CR_IPSOCK_ERROR error code, 95
CR_LOCALHOST_CONNECTION error code, 95
CR_MALFORMED_PACKET error code, 97
CR_NAMEDPIPEOPEN_ERROR error code, 96
CR_NAMEDPIPESETSTATE_ERROR error code, 96
CR_NAMEDPIPEWAIT_ERROR error code, 96
CR_NAMEDPIPE_CONNECTION error code, 96
CR_NET_PACKET_TOO_LARGE error code, 96
CR_NEW_STMT_METADATA error code, 99
CR_NOT_IMPLEMENTED error code, 99
CR_NO_DATA error code, 98
CR_NO_PARAMETERS_EXISTS error code, 97
CR_NO_PREPARE_STMT error code, 97
CR_NO_RESULT_SET error code, 98
CR_NO_STMT_METADATA error code, 98
CR_NULL_POINTER error code, 97
CR_OUT_OF_MEMORY error code, 95
CR_PARAMS_NOT_BOUND error code, 97
CR_PROBE_MASTER_CONNECT error code, 96
CR_PROBE_SLAVE_CONNECT error code, 96
CR_PROBE_SLAVE_HOSTS error code, 96
CR_PROBE_SLAVE_STATUS error code, 96
CR_SECURE_AUTH error code, 98
CR_SERVER_GONE_ERROR error code, 95
CR_SERVER_HANDSHAKE_ERR error code, 96
CR_SERVER_LOST error code, 96
CR_SERVER_LOST_EXTENDED error code, 99
CR_SHARED_MEMORY_CONNECTION error code, 97
CR_SHARED_MEMORY_CONNECT_ABANDONED_ERROR error code, 98
CR_SHARED_MEMORY_CONNECT_ANSWER_ERROR error code, 97
CR_SHARED_MEMORY_CONNECT_FILE_MAP_ERROR error code, 98
CR_SHARED_MEMORY_CONNECT_MAP_ERROR error code, 98

CR_SHARED_MEMORY_CONNECT_REQUEST_ERROR error code, 97
CR_SHARED_MEMORY_CONNECT_SET_ERROR error code, 98
CR_SHARED_MEMORY_EVENT_ERROR error code, 98
CR_SHARED_MEMORY_FILE_MAP_ERROR error code, 98
CR_SHARED_MEMORY_MAP_ERROR error code, 98
CR_SOCKET_CREATE_ERROR error code, 95
CR_SSL_CONNECTION_ERROR error code, 97
CR_STMT_CLOSED error code, 99
CR_TCP_CONNECTION error code, 96
CR_UNKNOWN_ERROR error code, 95
CR_UNKNOWN_HOST error code, 95
CR_UNSUPPORTED_PARAM_TYPE error code, 97
CR_UNUSED_1 error code, 98
CR_VERSION_ERROR error code, 95
CR_WRONG_HOST_INFO error code, 95
CR_WRONG_LICENSE error code, 97

E

EE_BADCLOSE error code, 101
EE_CANTCREATEFILE error code, 101
EE_CANTLOCK error code, 101
EE_CANTUNLOCK error code, 101
EE_CANT_CHSIZE error code, 101
EE_CANT_MKDIR error code, 102
EE_CANT_OPEN_STREAM error code, 102
EE_CANT_READLINK error code, 102
EE_CANT_SEEK error code, 103
EE_CANT_SYMLINK error code, 102
EE_CAPACITY_EXCEEDED error code, 103
EE_CHANGE_OWNERSHIP error code, 103
EE_CHANGE_PERMISSIONS error code, 103
EE_DELETE error code, 101
EE_DIR error code, 101
EE_DISK_FULL error code, 102
EE_EOFERR error code, 101
EE_FILENOFOUND error code, 102
EE_FILE_NOT_CLOSED error code, 102
EE_GETWD error code, 102
EE_LINK error code, 101
EE_LINK_WARNING error code, 102
EE_OPEN_WARNING error code, 102
EE_OUTOFMEMORY error code, 101
EE_OUT_OF_FILERESOURCES error code, 102
EE_READ error code, 101
EE_REALPATH error code, 102
EE_SETWD error code, 102
EE_STAT error code, 101
EE_SYNC error code, 102
EE_UNKOWN_CHARSET error code, 102
EE_UNKOWN_COLLATION error code, 102
EE_WRITE error code, 101
error code
 CR_ALREADY_CONNECTED, 99
 CR_AUTH_PLUGIN_CANNOT_LOAD, 99

CR_AUTH_PLUGIN_ERR, 99
CR_CANT_READ_CHARSET, 96
CR_COMMANDS_OUT_OF_SYNC, 96
CR_CONNECTION_ERROR, 95
CR_CONN_HOST_ERROR, 95
CR_CONN_UNKNOW_PROTOCOL, 98
CR_DATA_TRUNCATED, 97
CR_DUPLICATE_CONNECTION_ATTR, 99
CR_EMBEDDED_CONNECTION, 96
CR_FETCH_CANCELED, 98
CR_INSECURE_API_ERR, 99
CR_INVALID_BUFFER_USE, 97
CR_INVALID_CLIENT_CHARSET, 99
CR_INVALID_CONN_HANDLE, 98
CR_INVALID_PARAMETER_NO, 97
CR_IPSOCK_ERROR, 95
CR_LOCALHOST_CONNECTION, 95
CR_MALFORMED_PACKET, 97
CR_NAMEDPIPEOPEN_ERROR, 96
CR_NAMEDPIPESETSTATE_ERROR, 96
CR_NAMEDPIPEWAIT_ERROR, 96
CR_NAMEDPIPE_CONNECTION, 96
CR_NET_PACKET_TOO_LARGE, 96
CR_NEW_STMT_METADATA, 99
CR_NOT_IMPLEMENTED, 99
CR_NO_DATA, 98
CR_NO_PARAMETERS_EXISTS, 97
CR_NO_PREPARE_STMT, 97
CR_NO_RESULT_SET, 98
CR_NO_STMT_METADATA, 98
CR_NULL_POINTER, 97
CR_OUT_OF_MEMORY, 95
CR_PARAMS_NOT_BOUND, 97
CR_PROBE_MASTER_CONNECT, 96
CR_PROBE_SLAVE_CONNECT, 96
CR_PROBE_SLAVE_HOSTS, 96
CR_PROBE_SLAVE_STATUS, 96
CR_SECURE_AUTH, 98
CR_SERVER_GONE_ERROR, 95
CR_SERVER_HANDSHAKE_ERR, 96
CR_SERVER_LOST, 96
CR_SERVER_LOST_EXTENDED, 99
CR_SHARED_MEMORY_CONNECTION, 97
CR_SHARED_MEMORY_CONNECT_ABANDONED_ERROR, 98
CR_SHARED_MEMORY_CONNECT_ABANDONED_ERROR, 98
CR_SHARED_MEMORY_CONNECT_ANSWER_ERROR, 97
CR_SHARED_MEMORY_CONNECT_FILE_MAP_ERROR, 98
CR_SHARED_MEMORY_CONNECT_MAP_ERROR, 98
CR_SHARED_MEMORY_CONNECT_REQUEST_ERROR, 97
CR_SHARED_MEMORY_CONNECT_SET_ERROR, 98
CR_SHARED_MEMORY_EVENT_ERROR, 98
CR_SHARED_MEMORY_FILE_MAP_ERROR, 98
CR_SHARED_MEMORY_MAP_ERROR, 98
CR_SOCKET_CREATE_ERROR, 95
CR_SSL_CONNECTION_ERROR, 97
CR_STMT_CLOSED, 99
CR_TCP_CONNECTION, 96
CR_UNKNOWN_ERROR, 95
CR_UNKNOWN_HOST, 95
CR_UNSUPPORTED_PARAM_TYPE, 97
CR_UNUSED_1, 98
CR_VERSION_ERROR, 95
CR_WRONG_HOST_INFO, 95
CR_WRONG_LICENSE, 97
EE_BADCLOSE, 101
EE_CANTCREATEFILE, 101
EE_CANTLOCK, 101
EE_CANTUNLOCK, 101
EE_CANT_CHSIZE, 101
EE_CANT_MKDIR, 102
EE_CANT_OPEN_STREAM, 102
EE_CANT_READLINK, 102
EE_CANT_SEEK, 103
EE_CANT_SYMLINK, 102
EE_CAPACITY_EXCEEDED, 103
EE_CHANGE_OWNERSHIP, 103
EE_CHANGE_PERMISSIONS, 103
EE_DELETE, 101
EE_DIR, 101
EE_DISK_FULL, 102
EE_EOFERR, 101
EE_FILENOFOUND, 102
EE_FILE_NOT_CLOSED, 102
EE_GETWD, 102
EE_LINK, 101
EE_LINK_WARNING, 102
EE_OPEN_WARNING, 102
EE_OUTOFMEMORY, 101
EE_OUT_OF_FILERESOURCES, 102
EE_READ, 101
EE_REALPATH, 102
EE_SETWD, 102
EE_STAT, 101
EE_SYNC, 102
EE_UNKNOWN_CHARSET, 102
EE_UNKNOWN_COLLATION, 102
ER_ACCESS_DENIED_ERROR, 6
ER_ACCESS_DENIED_NO_PASSWORD_ERROR, 50
ER_ACCOUNT_HAS_BEEN_LOCKED, 80
ER_ADD_PARTITION_NO_NEW_PARTITION, 37
ER_ADD_PARTITION_SUBPART_ERROR, 37
ER_ADMIN_WRONG_MRGR_TABLE, 35
ER_AES_INVALID_IV, 66
ER_AES_INVALID_KDF_ITERATIONS, 93
ER_AES_INVALID_KDF_NAME, 93
ER_AES_INVALID_KDF_OPTION_SIZE, 93

ER_AGGREGATE_IN_ORDER_NOT_SELECT, 74	ER_AUDIT_LOG_NO_KEYRING_PLUGIN_INSTALLED, 90
ER_AGGREGATE_ORDER_FOR_UNION, 70	ER_AUDIT_LOG_SUPER_PRIVILEGE_REQUIRED, 90
ER_AGGREGATE_ORDER_NON_0AGG_QUERY, 70	ER_AUDIT_LOG_UDF_INSUFFICIENT_PRIVILEGE, 90
ER_ALTER_FILEGROUP_FAILED, 38	ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_COUNT, 91
ER_ALTER_INFO, 9	ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_TYPE, 91
ER_ALTER_OPERATION_NOT_SUPPORTED, 62	ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH, 91
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON91	ER_CHANGE_FTS, 91
62	ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH, 91
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON91AUTOINC,	ER_COLUMN_TYPE, 91
63	ER_AUDIT_LOG_USER_FIRST_CHARACTER_MUST_BE_, 91
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON91CHANGE_FTS,	ER_AUDIT_LOG_USER_NAME_INVALID_CHARACTER, 91
63	ER_AUTOINC_READ_FAILED, 34
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON91CREATE_CONVERT, 20	ER_INCREMENT_CONFLICT, 65
62	ER_AUTO_INCREMENT_POSITIONQUIRES_GTID_MODE_NOT_ON, 56
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON91CREATE_POSITIONQUIRES_GTID_MODE_ON, 56	ER_BAD_FIELD_ERROR, 7
63	ER_BAD_FT_COLUMN, 22
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON91CREATE_HOST_ERROR, 6	ER_BAD_LOG_STATEMENT, 42
63	ER_BAD_NULL_ERROR, 6
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON91CREATE_SLAVE, 17	ER_BAD_SLAVE_AUTO_POSITION, 56
64	ER_BAD_SLAVE_UNTIL_COND, 22
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON91CREATE_TABLE_ERROR, 7	ER_BAD_TABLE_ERROR, 7
62	ER_BASE64_DECODE_ERROR, 41
ER_AMBIGUOUS_FIELD_TERM, 35	ER_BEFORE_DML_VALIDATION_ERROR, 77
ER_AUDIT_API_ABORT, 85	ER_BINLOG_CACHE_SIZE_GREATER_THAN_MAX, 53
ER_AUDIT_LOG_COULD_NOT_CREATE_AES_KEY, 90	ER_BINLOG_CREATE_ROUTINE_NEED_SUPER, 31
ER_AUDIT_LOG_ENCRYPTION_PASSWORD_CANNOT_BE_BENLOGGED, 90	ER_BINLOG_LOGGING_IMPOSSIBLE, 43
ER_AUDIT_LOG_ENCRYPTION_PASSWORD_HAS_NOTE_BINLOGGED, 90	ER_BINLOG_LOGICAL_CORRUPTION, 64
ER_AUDIT_LOG_HAS_NOT BEEN_INSTALLED, 91	ER_BINLOG_MULTIPLE_ENGINES_AND_SELF_LOGGING, 48
ER_AUDIT_LOG_HOST_NAME_INVALID_CHARACTER, 92	ER_BINLOG_PURGE_EMFILE, 42
ER_AUDIT_LOG_JSON_FILTERING_NOT_ENABLED, 90	ER_BINLOG_PURGE_FATAL_ERR, 28
ER_AUDIT_LOG_JSON_FILTER_DOES_NOT_EXISTS, 92	ER_BINLOG_PURGE_PROHIBITED, 28
ER_AUDIT_LOG_JSON_FILTER_NAME_CANNOT_BE_EMPTY, 91	ER_BINLOG_READ_EVENT_CHECKSUM_FAILURE, 54
ER_AUDIT_LOG_JSON_FILTER_PARSING_ERROR, 91	ER_BINLOG_ROW_ENGINE_AND_STMT_ENGINE, 48
ER_AUDIT_LOG_JSON_USER_NAME_CANNOT_BE_EMPTY, 91	ER_BINLOG_ROW_INJECTION_AND_STMT_MODE, 48
	ER_BINLOG_ROW_LOGGING_FAILED, 39

ER_BINLOG_ROW_MODE_AND_STMT_ENGINE, 47
ER_BINLOG_ROW_RBR_TO_SBR, 39
ER_BINLOG_ROW_WRONG_TABLE_DEF, 39
ER_BINLOG_STMT_CACHE_SIZE_GREATER_THAN_MAX_BUFPOOL_RESIZE_INPROGRESS, 85
54
ER_BINLOG_STMT_MODE_AND_NO_REPL_TABLES, 62
ER_BINLOG_STMT_MODE_AND_ROW_ENGINE, 48
ER_BINLOG_UNSAFE_AND_STMT_ENGINE, 47
ER_BINLOG_UNSAFE_AUTOINC_COLUMNS, 48
ER_BINLOG_UNSAFE_AUTOINC_NOT_FIRST, 52
ER_BINLOG_UNSAFE_CREATE_IGNORE_SELECT, 51
ER_BINLOG_UNSAFE_CREATE_REPLACE_SELECT, 52
ER_BINLOG_UNSAFE_CREATE_SELECT_AUTOINC, 52
ER_BINLOG_UNSAFE_FULLTEXT_PLUGIN, 67
ER_BINLOG_UNSAFE_INSERT_IGNORE_SELECT, 51
ER_BINLOG_UNSAFE_INSERT_SELECT_UPDATE, 51
ER_BINLOG_UNSAFE_INSERT_TWO_KEYS, 52
ER_BINLOG_UNSAFE_LIMIT, 48
ER_BINLOG_UNSAFE_MIXED_STATEMENT, 50
ER_BINLOG_UNSAFE_MULTIPLE_ENGINES_AND_SELECTING_CHARACTERISTICS, 41
50
ER_BINLOG_UNSAFE_NONTRANS_AFTER_TRANS, 48
ER_BINLOG_UNSAFE_REPLACE_SELECT, 51
ER_BINLOG_UNSAFE_ROUTINE, 31
ER_BINLOG_UNSAFE_STATEMENT, 43
ER_BINLOG_UNSAFE_SYSTEM_FUNCTION, 48
ER_BINLOG_UNSAFE_SYSTEM_TABLE, 48
ER_BINLOG_UNSAFE_SYSTEM_VARIABLE, 48
ER_BINLOG_UNSAFE_UDF, 48
ER_BINLOG_UNSAFE_UPDATE_IGNORE, 52
ER_BINLOG_UNSAFE_WRITE_AUTOINC_SELECT, 52
ER_BINLOG_UNSAFE_XA, 89
ER_BLOBS_AND_NO_TERMINATED, 9
ER_BLOB_CANT_HAVE_DEFAULT, 10
ER_BLOB_FIELD_IN_PART_FUNC_ERROR, 37
ER_BLOB_KEY_WITHOUT_LENGTH, 15
ER_BLOB_USED_AS_KEY, 8
ER_BOOST_GEOMETRY_CENTROID_EXCEPTION, 71
ER_BOOST_GEOMETRY_EMPTY_INPUT_EXCEPTION, 71
ER_BOOST_GEOMETRY_INCONSISTENT_TURNS_EXCEPTION, 81
ER_BOOST_GEOMETRY_OVERLAY_INVALID_INPUT_EXCEPTION, 71
ER_BOOST_GEOMETRY_SELF_INTERSECTION_POINTER_EXCEPTION, 71
ER_BOOST_GEOMETRY_TURN_INFO_EXCEPTION, 71
ER_BOOST_GEOMETRY_UNKNOWN_EXCEPTION, 72
ER_CANNOT_ADD_FOREIGN, 18
ER_CANNOT_ADD_FOREIGN_BASE_COL_STORED, 88
ER_CANNOT_ADD_FOREIGN_BASE_COL_VIRTUAL, 86
ER_CANNOT_CREATE_VIRTUAL_INDEX_CONSTRAINT, 86
ER_CANNOT_DISCARD_TEMPORARY_TABLE, 68
ER_CANNOT_FIND_KEY_IN_KEYRING, 88
ER_CANNOT_LOAD_FROM_TABLE_V2, 52
ER_CANNOT_LOG_PARTIAL_DROP_DATABASE_WITH_GTID, 76
ER_CANNOT_USER, 29
ER_CANT_ACTIVATE_LOG, 41
ER_CANTAggregate_2COLLATIONS, 21
ER_CANTAggregate_3COLLATIONS, 21
ER_CANTAggregate_NCOLLATIONS, 22
ER_CANT_CHANGE_GTID_NEXT_IN_TRANSACTION, 56
ER_CANT_CHANGE_GTID_NEXT_IN_TRANSACTION_WHEN, 55
ER_CANTCASTINGCHARACTERISTICS, 41
ER_CANT_CREATE_DB, 4
ER_CANT_CREATE_FEDERATED_TABLE, 32
ER_CANT_CREATE_FILE, 3
ER_CANT_CREATE_GEOMETRY_OBJECT, 31
ER_CANT_CREATE_HANDLER_FILE, 36
ER_CANT_CREATE_SRoutine, 44
ER_CANT_CREATE_TABLE, 4
ER_CANT_CREATE_THREAD, 13
ER_CANT_CREATE_USER_WITH_GRANT, 30
ER_CANT_DELETE_FILE, 4
ER_CANT_DO_IMPLICIT_COMMIT_IN_TRX_WHEN_GTID_NE, 57
ER_CANT_DO_THIS_DURING_AN_TRANSACTION, 15
ER_CANT_DROP_FIELD_OR_KEY, 10
ER_CANT_EXECUTE_IN_READ_ONLY_TRANSACTION, 58
ER_CANT_FIND_DL_ENTRY, 12
ER_CANT_FIND_SYSTEM_REC, 4
ER_CANT_FIND_UDF, 12
ER_CANT_GET_STAT, 4
ER_CANT_INITIALIZE_UDF, 12
ER_CANT_LOCK_TABLE, 40
ER_CANT_OPEN_ERROR_LOG, 92
ER_CANT_OPEN_FILE, 4
ER_CANTOPEN_LIBRARY, 12
ER_CANT_READ_DIR, 5
ER_CANT_REMOVE_ALL_FIELDS, 9

ER_CANT_RENAME_LOG_TABLE, 42	ER_COL_COUNT_DOESNT_MATCH_CORRUPTED_V2, 59
ER_CANT_REOPEN_TABLE, 13	ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE, 40
ER_CANT_REPLICATE_ANONYMOUS_WITH_AUTO_POSITION, 79	ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE_V2, 68
ER_CANT_REPLICATE_ANONYMOUS_WITH_GTID_MODE, 79	ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE_V2, 31
ER_CANT_REPLICATE_GTID_WITH_GTID_MODE_OFFER_COMMIT_NOT_ALLOWED_IN_SF_OR_TRG, 80	ER_COND_ITEM_TOO_LONG, 46
ER_CANT_RESET_MASTER, 88	ER_CONFLICT_FN_PARSE_ERROR, 45
ER_CANT_SET_ENFORCE_GTID_CONSISTENCY_ON_PARTITIONING_CONFIG_VIOLATIONS, 80	ER_CONNECT_TO_FOREIGN_DATA_SOURCE, 24
ER_CANT_SET_GTID_MODE, 79	ER_CONNECT_TO_MASTER, 18
ER_CANT_SET_GTID_NEXT_LIST_TO_NON_NULL_WHEN_GTID_MODE_IS_OFF, 57	ER_CONNECT_TO_SLAVE, 18
ER_CANT_SET_GTID_NEXT_TO_ANONYMOUS_WHEN_BTREE_SHRINKS_INNREORG_PARTITIONS, 57	ER_CON_COUNT_ERROR, 6
ER_CANT_SET_GTID_NEXT_TO_GTID_WHEN_GTID_MODE_IS_BROKEN, 57	ER_COULD_NOT_HELP_DB, 20
ER_CANT_SET_GTID_NEXT_WHEN_OWNING_GTID, 91	ER_COULD_NOT_REINITIALIZE_AUDIT_LOG_FILTERS, 16
ER_CANT_SET_GTID_PURGED_WHEN_GTID_EXECUTED, 62	ER_CRASHED_ON_REPAIR, 16
ER_CANT_SET_GTID_PURGED_WHEN_GTID_MODE_IS_CREATE_FILEGROUP_FAILED, 62	ER_CREATE_DB_WITH_READ_LOCK, 17
ER_CANT_SET_GTID_PURGED_WHEN_OWNED_GTID_IS_RISK_OF_INCOMPATIBILITY, 62	ER_CREATE_FILEGROUP_FAILED, 38
ER_CANT_SET_VARIABLE_WHEN_OWNING_GTID, 83	ER_CUT_VALUE_GROUP_CONCAT, 21
ER_CANT_SET_WD, 5	ER_DATABASE_NAME, 45
ER_CANT_START_SERVER_NAMED_PIPE, 92	ER_DATA_OUT_OF_RANGE, 49
ER_CANT_UPDATE_TABLE_IN_CREATE_TABLE_SELECT, 54	ER_DA_INVALID_CONDITION_NUMBER, 55
ER_CANT_UPDATE_USED_TABLE_IN_SF_OR_TRG, 33	ER_DBACCESS_DENIED_ERROR, 6
ER_CANT_UPDATE_WITH_READLOCK, 19	ER_DB_CREATE_EXISTS, 4
ER_CANT_USE_AUTO_POSITION_WITH_GTID_MODE, 79	ER_DB_DROP_DELETE, 4
ER_CANT_WAIT_FOR_EXECUTED_GTID_SET WHILE_BTREE_SHRINKS NOT_SUPPORTED, 86	ER_DB_DROP_EXISTS, 4
ER_CANT_WRITE_LOCK_LOG_TABLE, 40	ER_DB_DROP_RMDIR, 4
ER_CAPACITY_EXCEEDED, 86	ER_DEBUG_SYNC_HIT_LIMIT, 46
ER_CAPACITY_EXCEEDED_IN_PARSER, 88	ER_DEBUG_SYNC_TIMEOUT, 46
ER_CAPACITY_EXCEEDED_IN_RANGE_OPTIMIZER, 86	ER_DDL_LOG_ERROR, 41
ER_CHANGE_MASTER_PASSWORD_LENGTH, 73	ER_DEPENDENT_BY_GENERATED_COLUMN, 79
ER_CHANGE_RPL_INFO_REPOSITORY_FAILURE, 54	ER_DEPRECATED_TLS_VERSION_SESSION, 93
ER_CHECKREAD, 5	ER_DERIVED_MUST_HAVE_ALIAS, 20
ER_CHECK_NOT_IMPLEMENTED, 15	ER_DIFF_GROUPS_PROC, 29
ER_CHECK_NO SUCH_TABLE, 15	ER_DIMENSION_UNSUPPORTED, 74
ER_COALESCE_ONLY_ON_HASH_PARTITION, 37	ER_DISABLED_STORAGE_ENGINE, 85
ER_COALESCE_PARTITION_NO_PARTITION, 37	ER_DISCARD_FK_CHECKS_RUNNING, 59
ER_COLLATION_CHARSET_MISMATCH, 20	ER_DISK_FULL, 5
ER_COLUMNACCESS_DENIED_ERROR, 13	ER_DIVISION_BY_ZERO, 28
	ER_DONT_SUPPORT_SLAVE_PRESERVE_COMMIT_ORDER, 70
	ER_DROP_DB_WITH_READ_LOCK, 17
	ER_DROP_FILEGROUP_FAILED, 38
	ER_DROP_INDEX_FK, 40
	ER_DROP_LAST_PARTITION, 37
	ER_DROP_PARTITION_NON_EXISTENT, 37
	ER_DROP_USER, 21
	ER_DUMP_NOT_IMPLEMENTED, 16
	ER_DUPLICATED_VALUE_IN_TYPE, 23

ER_DUP_ARGUMENT, 19
ER_DUP_ENTRY, 8
ER_DUP_ENTRY_AUTOINCREMENT_CASE, 41
ER_DUP_ENTRY_WITH_KEY_NAME, 42
ER_DUP_FIELDNAME, 8
ER_DUP_INDEX, 61
ER_DUP_KEY, 5
ER_DUP_KEYNAME, 8
ER_DUP_LIST_ENTRY, 70
ER_DUP_SIGNAL_SET, 46
ER_DUP_UNIQUE, 15
ER_DUP_UNKNOWN_IN_INDEX, 64
ER_EMPTY_QUERY, 8
ER_ENGINE_OUT_OF_MEMORY, 68
ER_ERROR_DURING_CHECKPOINT, 16
ER_ERROR_DURING_COMMIT, 15
ER_ERROR_DURING_FLUSH_LOGS, 16
ER_ERROR_DURING_ROLLBACK, 15
ER_ERROR_IN_TRIGGER_BODY, 51
ER_ERROR_IN_UNKNOWN_TRIGGER_BODY, 51
ER_ERROR_ON_CLOSE, 5
ER_ERROR_ON_MASTER, 67
ER_ERROR_ON MODIFYING_GTID_EXECUTED_TABLE_R_FK_INCORRECT_OPTION, 60
87
ER_ERROR_ON_READ, 5
ER_ERROR_ON_RENAME, 5
ER_ERROR_ON_WRITE, 5
ER_ERROR_WHEN_EXECUTING_COMMAND, 18
ER_EVENTS_DB_ERROR, 42
ER_EVENT_ALREADY_EXISTS, 39
ER_EVENT_CANNOT_ALTER_IN_THE_PAST, 42
ER_EVENT_CANNOT_CREATE_IN_THE_PAST, 42
ER_EVENT_CANNOT_DELETE, 40
ER_EVENT_CANT ALTER, 39
ER_EVENT_COMPILE_ERROR, 40
ER_EVENT_DATA_TOO_LONG, 40
ER_EVENT_DOES_NOT_EXIST, 39
ER_EVENT_DROP_FAILED, 39
ER_EVENT_ENDS_BEFORE_STARTS, 39
ER_EVENT_EXEC_TIME_IN_THE_PAST, 39
ER_EVENT_INTERVAL_NOT_POSITIVE_OR_TOO_BIG, 39
ER_EVENT_INVALID_CREATION_CTX, 43
ER_EVENT_MODIFY_QUEUE_ERROR, 41
ER_EVENT_NEITHER_M_EXPR_NOR_M_AT, 39
ER_EVENT_OPEN_TABLE_FAILED, 39
ER_EVENT_RECURSION_FORBIDDEN, 41
ER_EVENT_SAME_NAME, 40
ER_EVENT_SET_VAR_ERROR, 41
ER_EVENT_STORE_FAILED, 39
ER_EXCEPTIONS_WRITE_ERROR, 45
ER_EXEC_STMT_WITH_OPEN_CURSOR, 31
ER_EXPLAIN_NOT_SUPPORTED, 68
ER_FAILED_READ_FROM_PAR_FILE, 50
ER_FAILED_ROUTINE_BREAK_BINLOG, 31
ER_FEATURE_DISABLED, 23
ER_FEATURE_DISABLED_SEE_DOC, 86
ER_FEATURE_NOT_AVAILABLE, 79
ER_FIELD_IN_ORDER_NOT_SELECT, 74
ER_FIELD_NOT_FOUND_PART_ERROR, 36
ER_FIELD_SPECIFIED_TWICE, 11
ER_FIELD_TYPE_NOT_ALLOWED_AS_PARTITION_FIELD, 47
ER_FILEGROUP_OPTION_ONLY_ONCE, 38
ER_FILE_CORRUPT, 67
ER_FILE_EXISTS_ERROR, 9
ER_FILE_NOT_FOUND, 5
ER_FILE_USED, 5
ER_FILSORT_ABORT, 5
ER_FK_CANNOT_DELETE_PARENT, 61
ER_FK_CANNOT_OPEN_PARENT, 60
ER_FK_COLUMN_CANNOT_CHANGE, 61
ER_FK_COLUMN_CANNOT_CHANGE_CHILD, 61
ER_FK_COLUMN_CANNOT_DROP, 61
ER_FK_COLUMN_CANNOT_DROP_CHILD, 61
ER_FK_COLUMN_NOT_NULL, 61
ER_FK_DEPTH_EXCEEDED, 68
ER_FK_DUP_NAME, 61
ER_FK_FAIL_ADD_SYSTEM, 60
ER_FK_NO_INDEX_CHILD, 60
ER_FK_NO_INDEX_PARENT, 60
ER_FLUSH_MASTER_BINLOG_CLOSED, 16
ER_FORBID_SCHEMA_CHANGE, 33
ER_FORCING_CLOSE, 9
ER_FOREIGN_DATA_SOURCE_DOESNT_EXIST, 32
ER_FOREIGN_DATA_STRING_INVALID, 32
ER_FOREIGN_DATA_STRING_INVALID_CANT_CREATE, 32
ER_FOREIGN_DUPLICATE_KEY_OLD_UNUSED, 40
ER_FOREIGN_DUPLICATE_KEY_WITHOUT_CHILD_INFO, 55
ER_FOREIGN_DUPLICATE_KEY_WITH_CHILD_INFO, 55
ER_FOREIGN_KEY_ON_PARTITIONED, 37
ER_FOREIGN_SERVER_DOESNT_EXIST, 35
ER_FOREIGN_SERVER_EXISTS, 35
ER_FORM_NOT_FOUND, 5
ER_FOUND_GTID_EVENT_WHEN_GTID_MODE_IS_OFF, 57
ER_FOUND_GTID_EVENT_WHEN_GTID_MODE_IS_OFF_UN 57
ER_FOUND_MISSING_GTIDS, 67
ER_FPARSER_BAD_HEADER, 26
ER_FPARSER_EOF_IN_COMMENT, 26
ER_FPARSER_EOF_IN_UNKNOWN_PARAMETER, 26
ER_FPARSER_ERROR_IN_PARAMETER, 26
ER_FPARSER_TOO_BIG_FILE, 26
ER_FRM_UNKNOWN_TYPE, 26
ER_FSEEK_FAIL, 28
ER_FT_MATCHING_KEY_NOT_FOUND, 16

ER_FULLTEXT_NOT_SUPPORTED_WITH_PARTITIONING	58	ER_GTID_UNSAFE_CREATE_SELECT, 58
55		ER_GTID_UNSAFE_NON_TRANSACTIONAL_TABLE, 58
ER_FUNCTION_NOT_DEFINED, 12		ER_HANDSHAKE_ERROR, 6
ER_FUNC_INEXISTENT_NAME_COLLISION, 45		ER_HASHCHK, 3
ER_GENERATED_COLUMN_FUNCTION_IS_NOT_ALLO		ER_HOSTNAME, 34
78		ER_HOST_IS_BLOCKED, 12
ER_GENERATED_COLUMN_NON_PRIOR, 79		ER_HOST_NOT_PRIVILEGED, 12
ER_GENERATED_COLUMN_REF_AUTO_INC, 79		ER_IDENT_CAUSES_TOO_LONG_PATH, 64
ER_GET_ERRMSG, 23		ER_ILLEGAL_GRANT_FOR_TABLE, 13
ER_GET_ERRNO, 5		ER_ILLEGAL_HA, 5
ER_GET_STACKED_DA_WITHOUT_ACTIVE_HANDLER		ER_ILLEGAL_HA_CREATE_OPTION, 35
67		ER_ILLEGAL_REFERENCE, 20
ER_GET_TEMPORARY_ERRMSG, 23		ER_ILLEGAL_USER_VAR, 73
ER_GIS_DATA_WRONG_ENDIANESS, 73		ER_ILLEGAL_VALUE_FOR_TYPE, 28
ER_GIS_DIFFERENT_SRIDS, 70		ER_INCONSISTENT_ERROR, 67
ER_GIS_INVALID_DATA, 71		ER_INCONSISTENT_PARTITION_INFO_ERROR, 36
ER_GIS_MAX_POINTS_IN_GEOMETRY_OVERFLOWED		ER_INCONSISTENT_TYPE_OF_FUNCTIONS_ERROR, 36
82		ER_INCORRECT_GLOBAL_LOCAL_VAR, 19
ER_GIS_UNKNOWN_ERROR, 71		ER_INCORRECT_TYPE, 74
ER_GIS_UNKNOWN_EXCEPTION, 71		ER_INDEX_COLUMN_TOO_LONG, 51
ER_GIS_UNSUPPORTED_ARGUMENT, 71		ER_INDEX_CORRUPT, 51
ER_GLOBAL_VARIABLE, 19		ER_INDEX_REBUILD, 16
ER_GNO_EXHAUSTED, 56		ER_INNODB_FORCED_RECOVERY, 66
ER_GOT_SIGNAL, 9		ER_INNODB_FT_AUX_NOT_HEX_ID, 66
ER_GRANT_PLUGIN_USER_EXISTS, 50		ER_INNODB_FT_LIMIT, 58
ER_GRANT_WRONG_HOST_OR_USER, 13		ER_INNODB_FT_WRONG_DOCID_COLUMN, 59
ER_GROUPING_ON_TIMESTAMP_IN_DST, 92		ER_INNODB_IMPORT_WRONG_DOCID_INDEX, 59
ER_GROUP_REPLICATION_APPLIER_INIT_ERROR,		ER_INNODB_IMPORT_ERROR, 60
77		ER_INNODB_SESSION_FT_CONFIG_CORRUPT, 60
ER_GROUP_REPLICATION_COMMUNICATION_LAYERE		ER_INNODB_NO_FT_TEMP_TABLE, 59
77		ER_INNODB_NO_FTUSES_PARSER, 64
ER_GROUP_REPLICATION_COMMUNICATION_LAYERE		ER_INNODB_ONLINE_LOG_TOO_BIG, 59
77		ER_INNODB_READ_ONLY, 65
ER_GROUP_REPLICATION_CONFIGURATION, 77		ER_INNODB_UNDO_LOG_FULL, 69
ER_GROUP_REPLICATION_MAX_GROUP_SIZE,		ER_INSECURE_CHANGE_MASTER, 55
88		ER_INSECURE_PLAIN_TEXT, 55
ER_GROUP_REPLICATION_RUNNING, 77		ER_INSERT_INFO, 10
ER_GROUP_REPLICATION_STOP_APPLIER_THREAD		ER_INSECURE_TRANSACTION, 49
77		ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLO
ER_GTID_EXECUTED_WAS_CHANGED, 62		57
ER_GTID_MODE_2_OR_3QUIRES_ENFORCE_GTID_C		49
57		ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_SQL_L
ER_GTID_MODE_CAN_ONLY_CHANGE_ONE_STEP_A		49
58		ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_SQL_L
ER_GTID_MODE_OFF, 73		ER_INVALID_ARGUMENT_FOR_LOGARITHM, 69
ER_GTID_MODE_ON_REQUIRESENFORCE_GTID_C		ER_INTERNAL_ERROR, 60
57		ER_INVALID_CHARACTER_STRING, 23
ER_GTID_MODE_REQUIRESBINLOG, 57		ER_INVALID_DEFAULT, 8
ER_GTID_NEXT_CANT_BE_AUTOMATIC_IF_GTID_N		ER_INVALID_ENCRYPTION_OPTION, 87
56		ER_INVALID_FIELD_SIZE, 68
ER_GTID_NEXT_IS_NOT_IN_GTID_NEXT_LIST,		ER_INVALID_GEOJSON_MISSING_MEMBER, 74
55		ER_INVALID_GEOJSON_WRONG_TYPE, 74
ER_GTID_NEXT_TYPE_UNDEFINED_GROUP, 61		ER_INVALID_JSON_BINARY_DATA, 83
ER_GTID_PURGED_WAS_CHANGED, 62		
ER_GTID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT		
66		
ER_GTID_UNSAFE_CREATE_DROP_TEMPORARY_TA		
58		

ER_INVALID_JSON_CHARSET, 83
ER_INVALID_JSON_CHARSET_IN_FUNCTION, 83
ER_INVALID_JSON_DATA, 74
ER_INVALID_JSON_PATH, 83
ER_INVALID_JSON_PATH_ARRAY_CELL, 85
ER_INVALID_JSON_PATH_CHARSET, 84
ER_INVALID_JSON_PATH_WILDCARD, 84
ER_INVALID_JSON_TEXT, 83
ER_INVALID_JSON_TEXT_IN_PARAM, 83
ER_INVALID_JSON_VALUE_FOR_CAST, 84
ER_INVALID_ON_UPDATE, 23
ER_INVALID_RPL_WILD_TABLE_FILTER_PATTERN, 74
ER_INVALID_TYPE_FOR_JSON, 83
ER_INVALID_USE_OF_NULL, 13
ER_INVALID_YEAR_COLUMN_LENGTH, 60
ER_IO_ERR_LOG_INDEX_READ, 28
ER_IO_READ_ERROR, 59
ER_IO_WRITE_ERROR, 60
ER_IPSOCK_ERROR, 9
ER_JSON_BAD_ONE_OR_ALL_ARG, 84
ER_JSON_DOCUMENT_NULL_KEY, 85
ER_JSON_DOCUMENT_TOO_DEEP, 84
ER_JSON_KEY_TOO_BIG, 84
ER_JSON_USED_AS_KEY, 84
ER_JSON_VACUOUS_PATH, 84
ER_JSON_VALUE_TOO_BIG, 84
ER_KEYRING_ACCESS_DENIED_ERROR, 89
ER_KEYRING_AWS_UDF_AWS_KMS_ERROR, 89
ER_KEYRING_MIGRATION_FAILURE, 89
ER_KEYRING_MIGRATION_STATUS, 89
ER_KEYRING_UDF_KEYRING_SERVICE_ERROR, 88
ER_KEY_BASED_ON_GENERATED_COLUMN, 78
ER_KEY_COLUMN_DOES_NOT_EXITS, 8
ER_KEY_DOES_NOT_EXITS, 15
ER_KEY_NOT_FOUND, 5
ER_KEY_PART_0, 29
ER_KEY_REF_DO_NOT_MATCH_TABLE_REF, 20
ER_KILL_DENIED_ERROR, 10
ER_LIMITED_PART_RANGE, 38
ER_LIST_OF_FIELDS_ONLY_IN_HASH_ERROR, 36
ER_LOAD_DATA_INVALID_COLUMN, 44
ER_LOAD_DATA_INVALID_COLUMN_UNUSED, 44
ER_LOAD_FROM_FIXED_SIZE_ROWS_TO_VAR, 30
ER_LOAD_INFO, 9
ER_LOCAL_VARIABLE, 19
ER_LOCKING_SERVICE_DEADLOCK, 82
ER_LOCKING_SERVICE_TIMEOUT, 82
ER_LOCKING_SERVICE_WRONG_NAME, 82
ER_LOCK_ABORTED, 49
ER_LOCK_DEADLOCK, 18
ER_LOCK_OR_ACTIVE_TRANSACTION, 16
ER_LOCK_REFUSED_BY_ENGINE, 87
ER_LOCK_TABLE_FULL, 17
ER_LOCK_WAIT_TIMEOUT, 17
ER_LOGGING_PROHIBIT_CHANGING_OF, 29
ER_LOG_IN_USE, 28
ER_LOG_PURGE_NO_FILE, 44
ER_LOG_PURGE_UNKNOWN_ERR, 28
ER_MALFORMED_DEFINER, 33
ER_MALFORMED_GTID_SET_ENCODING, 56
ER_MALFORMED_GTID_SET_SPECIFICATION, 56
ER_MALFORMED_GTID_SPECIFICATION, 56
ER_MALFORMED_PACKET, 61
ER_MASTER, 16
ER_MASTER_DELAY_VALUE_OUT_OF_RANGE, 52
ER_MASTER_FATAL_ERROR_READING_BINLOG, 19
ER_MASTER_HAS_PURGED_REQUIRED_GTIDS, 58
ER_MASTER_INFO, 17
ER_MASTER_KEY_ROTATION_BINLOG_FAILED, 87
ER_MASTER_KEY_ROTATION_ERROR_BY_SE, 87
ER_MASTER_KEY_ROTATION_NOT_SUPPORTED_BY_SE, 87
ER_MASTER_KEY_ROTATION_SE_UNAVAILABLE, 87
ER_MASTER_NET_READ, 16
ER_MASTER_NET_WRITE, 16
ER_MAXVALUE_IN_VALUES_IN, 47
ER_MAX_PREPARED_STMT_COUNT_REACHED, 34
ER_MESSAGE_AND_STATEMENT, 49
ER_MISSING_HA_CREATE_OPTION, 68
ER_MISSING_KEY, 67
ER_MISSING_SKIP_SLAVE, 22
ER_MIXING_NOT_ALLOWED, 19
ER_MIX_HANDLER_ERROR, 36
ER_MIX_OF_GROUP_FUNC_AND_FIELDS, 13
ER_MIX_OF_GROUP_FUNC_AND_FIELDS_V2, 76
ER_MTS_CANT_PARALLEL, 54
ER_MTS_CHANGE_MASTER_CANT_RUN_WITH_GAPS, 59
ER_MTS_EVENT_BIGGER_PENDING_JOBS_SIZE_MAX, 64
ER_MTS_FEATURE_IS_NOT_SUPPORTED, 54
ER_MTS_INCONSISTENT_DATA, 54
ER_MTS_RECOVERY_FAILURE, 59
ER_MTS_RESET_WORKERS, 59
ER_MTS_UPDATED_DBs_GREATER_MAX, 54
ER_MULTIPLE_DEF_CONST_IN_LIST_PART_ERROR, 36
ER_MULTIPLE_PRI_KEY, 8
ER_MULTI_UPDATE_KEY_CONFLICT, 51
ER_MUST_CHANGE_PASSWORD, 60
ER_MUST_CHANGE_PASSWORD_LOGIN, 64
ER_M_BIGGER_THAN_D, 32
ER_NAME_BECOMES_EMPTY, 35

ER_NATIVE_FCT_NAME_COLLISION, 42	ER_NO_REFERENCED_ROW, 18
ER_NDB_CANT_SWITCH_BINLOG_FORMAT, 41	ER_NO_REFERENCED_ROW_2, 33
ER_NDB_REPLICATION_SCHEMA_ERROR, 45	ER_NO_SECURE_TRANSPORTS_CONFIGURED, 85
ER_NEED_REPREPARE, 44	ER_NO SUCH INDEX, 9
ER_NETWORK_READ_EVENT_CHECKSUM_FAILURE, 53	ER_NO SUCH KEY VALUE, 53
ER_NET_ERROR_ON_WRITE, 14	ER_NO SUCH PARTITION UNUSED, 54
ER_NET_FCNTL_ERROR, 14	ER_NO SUCH TABLE, 13
ER_NET_OK_PACKET_TOO_LARGE, 74	ER_NO SUCH THREAD, 10
ER_NET_PACKETS_OUT_OF_ORDER, 14	ER_NO SUCH USER, 33
ER_NET_PACKET_TOO_LARGE, 14	ER_NO_TABLES_USED, 10
ER_NET_READ_ERROR, 14	ER_NO_TRIGGERES_ON_SYSTEM_SCHEMA, 34
ER_NET_READ_ERROR_FROM_PIPE, 14	ER_NO_UNIQUE_LOGFILE, 10
ER_NET_READ_INTERRUPTED, 14	ER_NULL_COLUMN_IN_INDEX, 12
ER_NET_UNCOMPRESS_ERROR, 14	ER_NULL_IN_VALUES_LESS_THAN, 41
ER_NET_WRITE_INTERRUPTED, 14	ER_NUMERIC_JSON_VALUE_OUT_OF_RANGE, 84
ER_NEVER_USED, 44	ER_OBSOLETE_CANNOT_LOAD_FROM_TABLE, 39
ER_NEW_ABORTING_CONNECTION, 16	ER_OBSOLETE_COL_COUNT_DOESNT_MATCH_CORRU
ER_NISAMCHK, 3	39
ER_NO, 3	ER_OLD_FILE_FORMAT, 33
ER_NONEXISTING_GRANT, 13	ER_OLD_KEYFILE, 6
ER_NONEXISTING_PROC_GRANT, 30	ER_OLD_TEMPORALS_UPGRADED, 66
ER_NONEXISTING_TABLE_GRANT, 13	ER_ONLY_FD_AND_RBR_EVENTS_ALLOWED_IN_BINLO
ER_NONUNIQ_TABLE, 8	78
ER_NONUPDATEABLE_COLUMN, 26	ER_ONLY_INTEGERS_ALLOWED, 42
ER_NON_DEFAULT_VALUE_FOR_GENERATED_COLUMN, 28	ER_ONLY_ON_RANGE_LIST_PARTITION, 37
ER_NON_GROUPING_FIELD_USED, 34	ER_OPEN_AS_READONLY, 6
ER_NON_INSERTABLE_TABLE, 34	ER_OPERAND_COLUMNS, 20
ER_NON_RO_SELECT_DISABLE_TIMER, 70	ER_OPTION_PREVENTS_STATEMENT, 23
ER_NON_UNIQ_ERROR, 7	ER_ORDER_WITH_PROC, 29
ER_NON_UPDATABLE_TABLE, 23	ER_OUTOFMEMORY, 6
ER_NORMAL_SHUTDOWN, 9	ER_OUT_OF_RESOURCES, 6
ER_NOT_ALLOWED_COMMAND, 13	ER_OUT_OF_SORTMEMORY, 6
ER_NOT_FORM_FILE, 6	ER_PARSE_ERROR, 8
ER_NOT_KEYFILE, 6	ER_PARTITIONS_MUST_BE_DEFINED_ERROR, 36
ER_NOT_SUPPORTED_AUTH_MODE, 20	ER_PARTITION_CLAUSE_ON_NONPARTITIONED, 54
ER_NOT_SUPPORTED_YET, 19	ER_PARTITION_COLUMN_LIST_ERROR, 47
ER_NOT_VALID_PASSWORD, 60	ER_PARTITION_CONST_DOMAIN_ERROR, 41
ER_NO_BINARY_LOGGING, 29	ER_PARTITION_ENGINE_DEPRECATED_FOR_TABLE, 88
ER_NO_BINLOG_ERROR, 38	ER_PARTITION_ENTRY_ERROR, 36
ER_NO_CONST_EXPR_IN_RANGE_OR_LIST_ERROR, 36	ER_PARTITION_EXCHANGE_DIFFERENT_OPTION, 53
ER_NO_DB_ERROR, 6	ER_PARTITION_EXCHANGE_FOREIGN_KEY, 53
ER_NO_DEFAULT, 19	ER_PARTITION_EXCHANGE_TEMP_TABLE, 53
ER_NO_DEFAULT_FOR_FIELD, 28	ER_PARTITION_FIELDS_TOO_LONG, 47
ER_NO_DEFAULT_FOR_VIEW_FIELD, 31	ER_PARTITION_FUNCTION_FAILURE, 38
ER_NO_FILE_MAPPING, 29	ER_PARTITION_FUNCTION_IS_NOT_ALLOWED, 41
ER_NO_FORMAT_DESCRIPTION_EVENT_BEFORE_BINLOG, 44	ER_PARTITION_FUNC_NOT_ALLOWED_ERROR, 36
ER_NO_FT_MATERIALIZED_SUBQUERY, 69	ER_PARTITION_INSTEAD_OF_SUBPARTITION, 53
ER_NO_GROUP_FOR_PROC, 29	
ER_NO_PARTITION_FOR_GIVEN_VALUE, 38	
ER_NO_PARTITION_FOR_GIVEN_VALUE_SILENT, 43	
ER_NO_PARTS_ERROR, 37	
ER_NO_PERMISSION_TO_CREATE_USER, 18	
ER_NO_RAID_COMPILED, 15	

ER_PARTITION_MAXVALUE_ERROR, 35
ER_PARTITION_MERGE_ERROR, 41
ER_PARTITION_MGMT_ON_NONPARTITIONED, 37
ER_PARTITION_NAME, 45
ER_PARTITION_NOT_DEFINED_ERROR, 36
ER_PARTITION_NO_TEMPORARY, 41
ER_PARTITIONQUIRES_VALUES_ERROR, 35
ER_PARTITION_SUBPARTITION_ERROR, 35
ER_PARTITION_SUBPART_MIX_ERROR, 35
ER_PARTITION_WRONG_NO_PART_ERROR, 35
ER_PARTITION_WRONG_NO_SUBPART_ERROR, 35
ER_PARTITION_WRONG_VALUES_ERROR, 35
ER_PART_STATE_ERROR, 38
ER_PASSWD_LENGTH, 28
ER_PASSWORD_ANONYMOUS_USER, 12
ER_PASSWORD_EXPIRE_ANONYMOUS_USER, 69
ER_PASSWORD_FORMAT, 61
ER_PASSWORD_NOT_ALLOWED, 12
ER_PASSWORD_NO_MATCH, 12
ER_PATH_LENGTH, 49
ER_PLUGGABLE_PROTOCOL_COMMAND_NOT_SUPPORTED, 82
ER_PLUGIN_CANNOT_BE_UNINSTALLED, 66
ER_PLUGIN_DELETE_BUILTIN, 45
ER_PLUGIN_FAILED_TO_OPEN_TABLE, 90
ER_PLUGIN_FAILED_TO_OPEN_TABLES, 90
ER_PLUGIN_IS_NOT_LOADED, 38
ER_PLUGIN_IS_PERMANENT, 50
ER_PLUGIN_NO_INSTALL, 52
ER_PLUGIN_NO_UNINSTALL, 52
ER_PREVENTS_VARIABLE_WITHOUT_RBR, 77
ER_PRIMARY_CANT_HAVE_NULL, 15
ER_PROCACCESS_DENIED_ERROR, 28
ER_PROC_AUTO_GRANT_FAIL, 30
ER_PROC_AUTO_REVOKE_FAIL, 30
ER_PS_MANY_PARAM, 29
ER_PS_NO_RECURSION, 33
ER_QUERY_CACHE_DISABLED, 47
ER_QUERY_INTERRUPTED, 24
ER_QUERY_ON_FOREIGN_DATA_SOURCE, 32
ER_QUERY_ON_MASTER, 18
ER_QUERY_TIMEOUT, 69
ER_RANGE_NOT_INCREASING_ERROR, 36
ER_RBR_NOT_AVAILABLE, 41
ER_READY, 9
ER_READ_ONLY_MODE, 61
ER_READ_ONLY_TRANSACTION, 17
ER_RECORD_FILE_FULL, 11
ER_REFERENCED_TRG_DOES_NOT_EXIST, 68
ER_REGEXP_ERROR, 13
ER_RELAY_LOG_FAIL, 28
ER_RELAY_LOG_INIT, 29
ER_REMOVED_SPACES, 34
ER_RENAMED_NAME, 46
ER_REORG_HASH_ONLY_ON_SAME_NO, 37
ER_REORG_NO_PARAM_ERROR, 37
ER_REORG_OUTSIDE_RANGE, 38
ER_REORG_PARTITION_NOT_EXIST, 37
ER_REPLACE_INACCESSIBLE_ROWS, 73
ER_REQUIRES_PRIMARY_KEY, 15
ER_RESERVED_SYNTAX, 29
ER_RESIGNAL_WITHOUT_ACTIVE_HANDLER, 46
ER_REVOKER_GRANTS, 21
ER_ROW_DOES_NOT_MATCH_GIVEN_PARTITION_SET, 54
ER_ROW_DOES_NOT_MATCH_PARTITION, 53
ER_ROW_IN_WRONG_PARTITION, 64
ER_ROW_IS_REFERENCED, 18
ER_ROW_IS_REFERENCED_2, 33
ER_ROW_SINGLE_PARTITION_FIELD_ERROR, 47
ER_RPL_INFO_DATA_TOO_LONG, 53
ER_RUN_HOOK_ERROR, 78
ER_SAME_NAME_PARTITION, 37
ER_SAME_NAME_PARTITION_FIELD, 47
ER_SECURE_TRANSPORT_REQUIRED, 85
ER_SELECT_REDUCED, 20
ER_SERVER_ISNT_AVAILABLE, 86
ER_SERVER_IS_IN_SECURE_AUTH_MODE, 22
ER_SERVER_OFFLINE_MODE, 70
ER_SERVER_SHUTDOWN, 7
ER_SESSION_WAS_KILLED, 86
ER_SET_CONSTANTS_ONLY, 17
ER_SET_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ON, 80
ER_SET_PASSWORD_AUTH_PLUGIN, 50
ER_SET_STATEMENT_CANNOT_INVOKE_FUNCTION, 56
ER_SHUTDOWN_COMPLETE, 9
ER_SIGNAL_BAD_CONDITION_TYPE, 46
ER_SIGNAL_EXCEPTION, 46
ER_SIGNAL_NOT_FOUND, 46
ER_SIGNAL_WARN, 46
ER_SIZE_OVERFLOW_ERROR, 38
ER_SKIPPING_LOGGED_TRANSACTION, 56
ER_SLAVE_CANT_CREATE_CONVERSION, 49
ER_SLAVE_CHANNEL_DELETE, 75
ER_SLAVE_CHANNEL_DOES_NOT_EXIST, 75
ER_SLAVE_CHANNEL_IO_THREAD_MUST_STOP, 69
ER_SLAVE_CHANNEL_MUST_STOP, 75
ER_SLAVE_CHANNEL_NAME_INVALID_OR_TOO_LONG, 75
ER_SLAVE_CHANNEL_NOT_RUNNING, 75
ER_SLAVE_CHANNEL_OPERATION_NOT_ALLOWED, 83
ER_SLAVE_CHANNEL_SQL_SKIP_COUNTER, 76
ER_SLAVE_CHANNEL_SQL_THREAD_MUST_STOP, 76
ER_SLAVE_CHANNEL_WAS_NOT_RUNNING, 76
ER_SLAVE_CHANNEL_WAS_RUNNING, 75
ER_SLAVE_CONFIGURATION, 58
ER_SLAVE_CONVERSION_FAILED, 49

ER_SLAVE_CORRUPT_EVENT, 44	ER_SP_DUP_COND, 25
ER_SLAVE_CREATE_EVENT_FAILURE, 43	ER_SP_DUP_CURS, 25
ER_SLAVE_FATAL_ERROR, 43	ER_SP_DUP_HANDLER, 31
ER_SLAVE_HAS_MORE_GTIDS_THAN_MASTER, 66	ER_SP_DUP_PARAM, 25
ER_SLAVE_HEARTBEAT_FAILURE, 45	ER_SP_DUP_VAR, 25
ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE, 45	ER_SP_FETCH_NO_DATA, 25
ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE_MASTER, 50	ER_SP_GOTO_IN_HNDLR, 27
ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE_MASTER, 50	ER_SP_LABEL_MISMATCH, 24
ER_SLAVE_IGNORED_SSL_PARAMS, 22	ER_SP_LABEL_REDEFINE, 24
ER_SLAVE_IGNORED_TABLE, 19	ER_SP_LILABEL_MISMATCH, 24
ER_SLAVE_IGNORE_SERVER_IDS, 47	ER_SP_NORETURN, 25
ER_SLAVE INCIDENT, 42	ER_SP_NORETURNEND, 25
ER_SLAVE_IO_THREAD_MUST_STOP, 67	ER_SP_NOT_VAR_ARG, 31
ER_SLAVE_MASTER_COM_FAILURE, 43	ER_SP_NO_AGGREGATE, 34
ER_SLAVE_MAX_CHANNELS_EXCEEDED, 75	ER_SP_NO_DROP_SP, 27
ER_SLAVE_MI_INIT_REPOSITORY, 65	ER_SP_NO_RECursion, 31
ER_SLAVE_MULTIPLE_CHANNELS_CMD, 75	ER_SP_NO_RECURSIVE_CREATE, 24
ER_SLAVE_MULTIPLE_CHANNELS_HOST_PORT, 75	ER_SP_NO_RETSET, 31
ER_SLAVE_MUST_STOP, 17	ER_SP_PROC_TABLE_CORRUPT, 34
ER_SLAVE_NEW_CHANNEL_WRONG_REPOSITORY, 75	ER_SP_RECursion_LIMIT, 34
ER_SLAVE_NOT_RUNNING, 17	ER_SP_STORE_FAILED, 24
ER_SLAVE_RELAY_LOG_READ_FAILURE, 43	ER_SP_SUBSELECT_NYI, 26
ER_SLAVE_RELAY_LOG_WRITE_FAILURE, 43	ER_SP_UNDECLARED_VAR, 25
ER_SLAVE_RLI_INIT_REPOSITORY, 65	ER_SP_UNINIT_VAR, 24
ER_SLAVE_SILENT_RETRY_TRANSACTION, 59	ER_SP_VARCOND_AFTER_CURSHNDLR, 26
ER_SLAVE_SQL_THREAD_MUST_STOP, 69	ER_SP_WRONG_NAME, 34
ER_SLAVE_THREAD, 17	ER_SP_WRONG_NO_OF_ARGS, 25
ER_SLAVE_WAS_NOT_RUNNING, 21	ER_SQLTHREAD_WITH_SECURE_SLAVE, 55
ER_SLAVE_WAS_RUNNING, 20	ER_SQL_MODE_MERGED, 82
ER_SLAVE_WORKER_STOPPED_PREVIOUS_THD_ER	ER_SQL_MODE_NO_EFFECT, 70
70	ER_SQL_SLAVE_SKIP_COUNTER_NOT_SETTABLE_IN_G
ER_SPATIAL_CANT_HAVE_NULL, 20	64
ER_SPATIAL_MUST_HAVE_GEOM_COL, 49	ER_SR_INVALID_CREATION_CTX, 43
ER_SPECIFIC_ACCESS_DENIED_ERROR, 19	ER_STACK_OVERRUN, 11
ER_SP_ALREADY_EXISTS, 24	ER_STACK_OVERRUN_NEED_MORE, 32
ER_SP_BADRETURN, 24	ER_STARTUP, 30
ER_SP_BADSELECT, 24	ER_STD_BAD_ALLOC_ERROR, 72
ER_SP_BADSTATEMENT, 24	ER_STD_DOMAIN_ERROR, 72
ER_SP_BAD_CURSOR_QUERY, 25	ER_STD_INVALID_ARGUMENT, 72
ER_SP_BAD_CURSOR_SELECT, 25	ER_STD_LENGTH_ERROR, 72
ER_SP_BAD_SQLSTATE, 30	ER_STD_LOGIC_ERROR, 72
ER_SP_BAD_VAR_SHADOW, 33	ER_STD_OUT_OF_RANGE_ERROR, 72
ER_SP_CANT.Alter, 26	ER_STD_OVERFLOW_ERROR, 72
ER_SP_CANT_SET_AUTOCOMMIT, 33	ER_STD_RANGE_ERROR, 72
ER_SP_CASE_NOT_FOUND, 26	ER_STD_RUNTIME_ERROR, 72
ER_SP_COND_MISMATCH, 25	ER_STD_UNDERFLOW_ERROR, 72
ER_SP_CURSOR_AFTER_HANDLER, 26	ER_STD_UNKNOWN_EXCEPTION, 73
ER_SP_CURSOR_ALREADY_OPEN, 25	ER_STMT_CACHE_FULL, 51
ER_SP_CURSOR_MISMATCH, 25	ER_STMT_HAS_NO_OPEN_CURSOR, 31
ER_SP_CURSOR_NOT_OPEN, 25	ER_STMT_NOT_ALLOWED_IN_SF_OR_TRG, 26
ER_SP_DOES_NOT_EXIST, 24	ER_STOP_SLAVE_IO_THREAD_TIMEOUT, 65
ER_SP_DROP_FAILED, 24	ER_STOP_SLAVE_SQL_THREAD_TIMEOUT, 65
	ER_STORAGE_ENGINE_NOT_LOADED, 67
	ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_
	49
	ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_
	40

ER_STORED_FUNCTION_PREVENTS_SWITCH_SQL_ER_TOO_LONG_TABLE_PARTITION_COMMENT,
50
ER_SUBPARTITION_ERROR, 36
ER_SUBPARTITION_NAME, 46
ER_SUBQUERY_NO_1_ROW, 20
ER_SYNTAX_ERROR, 13
ER_TABLEACCESS_DENIED_ERROR, 13
ER_TABLENAME_NOT_ALLOWED_HERE, 20
ER_TABLESPACE_AUTO_EXTEND_ERROR, 38
ER_TABLESPACE_CANNOT_ENCRYPT, 87
ER_TABLESPACE_DISCARDED, 60
ER_TABLESPACE_EXISTS, 60
ER_TABLESPACE_IS_NOT_EMPTY, 80
ER_TABLESPACE_MISSING, 60
ER_TABLES_DIFFERENT_METADATA, 53
ER_TABLE_CANT_HANDLE_AUTO_INCREMENT,
14
ER_TABLE_CANT_HANDLE_BLOB, 14
ER_TABLE_CANT_HANDLE_FT, 18
ER_TABLE_CANT_HANDLE_SPKEYS, 34
ER_TABLE_CORRUPT, 66
ER_TABLE_DEF_CHANGED, 30
ER_TABLE_EXISTS_ERROR, 7
ER_TABLE_HAS_NO_FT, 55
ER_TABLE_IN_FK_CHECK, 52
ER_TABLE_IN_SYSTEM_TABLESPACE, 59
ER_TABLE_MUST_HAVE_COLUMNS, 11
ER_TABLE_NAME, 45
ER_TABLE_NEEDS_REBUILD, 51
ER_TABLE_NEEDS_UPGRADE, 34
ER_TABLE_NEEDS_UPG_PART, 86
ER_TABLE_NOT_LOCKED, 10
ER_TABLE_NOT_LOCKED_FOR_WRITE, 10
ER_TABLE_REFERENCED, 88
ER_TABLE_SCHEMA_MISMATCH, 59
ER_TEMPORARY_NAME, 46
ER_TEMP_FILE_WRITE_FAILURE, 66
ER_TEMP_TABLE_PREVENTS_SWITCH_OUT_OF_RBR_ER_UNION_TABLES_IN_DIFFERENT_DIR, 18
40
ER_TEXTFILE_NOT_READABLE, 9
ER_TOO_BIG_DISPLAYWIDTH, 32
ER_TOO_BIG_FIELDLENGTH, 8
ER_TOO_BIG_FOR_UNCOMPRESS, 21
ER_TOO_BIG_PRECISION, 31
ER_TOO_BIG_ROWSIZE, 11
ER_TOO_BIG_SCALE, 31
ER_TOO_BIG_SELECT, 10
ER_TOO_BIG_SET, 10
ER_TOO_HIGH_LEVEL_OF_NESTING_FOR_SELECT,
35
ER_TOO_LONG_BODY, 32
ER_TOO_LONG_FIELD_COMMENT, 45
ER_TOO_LONG_IDENT, 8
ER_TOO_LONG_INDEX_COMMENT, 49
ER_TOO_LONG_KEY, 8
ER_TOO_LONG_STRING, 14
ER_TOO_LONG_TABLE_COMMENT, 45
58
ER_TOO_MANY_CONCURRENT_TRXS, 46
ER_TOO_MANY_FIELDS, 11
ER_TOO_MANY_KEYS, 8
ER_TOO_MANY_KEY_PARTS, 8
ER_TOO_MANY_PARTITIONS_ERROR, 36
ER_TOO_MANY_PARTITION_FUNC_FIELDS_ERROR,
47
ER_TOO_MANY_ROWS, 15
ER_TOO_MANY_TABLES, 11
ER_TOO_MANY_USER_CONNECTIONS, 17
ER_TOO_MANY_VALUES_ERROR, 47
ER_TOO MUCH_AUTO_TIMESTAMP_COLS, 23
ER_TRANSACTION_ROLLBACK_DURING_COMMIT,
78
ER_TRANS_CACHE_FULL, 16
ER_TRG_ALREADY_EXISTS, 27
ER_TRG_CANT_CHANGE_ROW, 27
ER_TRG_CANT_OPEN_TABLE, 43
ER_TRG_CORRUPTED_FILE, 43
ER_TRG_DOES_NOT_EXIST, 27
ER_TRG_INVALID_CREATION_CTX, 43
ER_TRG_IN_WRONG_SCHEMA, 32
ER_TRG_NO_CREATION_CTX, 43
ER_TRG_NO_DEFINER, 33
ER_TRG_NO_SUCH_ROW_IN_TRG, 27
ER_TRG_ON_VIEW_OR_TEMP_TABLE, 27
ER_TRUNCATED_WRONG_VALUE, 23
ER_TRUNCATED_WRONG_VALUE_FOR_FIELD,
28
ER_TRUNCATE_ILLEGAL_FK, 50
ER_UDF_ERROR, 89
ER_UDF_EXISTS, 12
ER_UDF_NO_PATHS, 12
ER_UNDO_RECORD_TOO_BIG, 51
ER_UNEXPECTED_EOF, 6
ER_UNIQUE_KEY_NEED_ALL_FIELDS_IN_PF, 37
ER_UNKNOWN_ALTER_ALGORITHM, 59
ER_UNKNOWN_ALTER_LOCK, 59
ER_UNKNOWN_CHARACTER_SET, 11
ER_UNKNOWN_COLLATION, 22
ER_UNKNOWN_COM_ERROR, 6
ER_UNKNOWN_ERROR, 11
ER_UNKNOWN_EXPLAIN_FORMAT, 58
ER_UNKNOWN_KEY_CACHE, 22
ER_UNKNOWN_LOCALE, 46
ER_UNKNOWN_PARTITION, 53
ER_UNKNOWN_PROCEDURE, 11
ER_UNKNOWN_STMT_HANDLER, 20
ER_UNKNOWN_STORAGE_ENGINE, 23
ER_UNKNOWN_SYSTEM_VARIABLE, 16
ER_UNKNOWN_TABLE, 11
ER_UNKNOWN_TARGET_BINLOG, 28
ER_UNKNOWN_TIME_ZONE, 23
ER_UNRESOLVED_HINT_NAME, 81
ER_UNSUPORTED_LOG_ENGINE, 42

ER_UNSUPPORTED_ACTION_ON_GENERATED_COLUMNVIEW_SELECT_DERIVED, 27
78
ER_UNSUPPORTED_ALTER_ENCRYPTION_INPLACE, ER_VIEW_SELECT_DERIVED_UNUSED, 27
88
ER_UNSUPPORTED_ALTER_INPLACE_ON_VIRTUAL_COLUMNVIEW_WRONG_LIST, 27
78
ER_UNSUPPORTED_ALTER_ONLINE_ON_VIRTUAL_CURRENTPROXY_PLUGIN_TOKEN_NOT_FOUND, 82
87
ER_UNSUPPORTED_BY_REPLICATION_THREAD, ER_WARNING_NOT_COMPLETE_ROLLBACK, 16
73
ER_UNSUPPORTED_ENGINE, 52
ER_UNSUPPORTED_EXTENSION, 11
ER_UNSUPPORTED_PS, 23
ER_UNTIL_COND_IGNORED, 22
ER_UNUSED1, 14
ER_UNUSED2, 14
ER_UNUSED3, 14
ER_UNUSED4, 48
ER_UNUSED5, 61
ER_UNUSED6, 63
ER_UPDATE_INFO, 12
ER_UPDATE_LOG_DEPRECATED_IGNORED, 24
ER_UPDATE_LOG_DEPRECATED_TRANSLATED, 24
ER_UPDATE_TABLE_USED, 10
ER_UPDATE_WITHOUT_KEY_IN_SAFE_MODE, 15
ER_USERNAME, 34
ER_USER_ALREADY_EXISTS, 85
ER_USER_COLUMN_OLD_LENGTH, 88
ER_USER_DOES_NOT_EXIST, 85
ER_USER_LIMIT_REACHED, 19
ER_USER_LOCK_DEADLOCK, 73
ER_USER_LOCK_WRONG_NAME, 73
ER_VALUES_IS_NOT_INT_TYPE_ERROR, 50
ER_VARIABLE_IS_NOT_STRUCT, 22
ER_VARIABLE_IS_READONLY, 45
ER_VARIABLE_NOT_SETTABLE_IN_SF_OR_TRIGGER, ER_WARN_NULL_TO_NOTNULL, 21
55
ER_VARIABLE_NOT_SETTABLE_IN_SP, 61
ER_VARIABLE_NOT_SETTABLE_IN_TRANSACTION, ER_WARN_ONLY_MASTER_LOG_FILE_NO_POS, 69
55
ER_VAR_CANT_BE_READ, 19
ER_VIEW_CHECKSUM, 29
ER_VIEW_CHECK_FAILED, 28
ER_VIEW_DELETE_MERGE_VIEW, 29
ER_VIEW_FRM_NO_USER, 33
ER_VIEW_INVALID, 27
ER_VIEW_INVALID_CREATION_CTX, 43
ER_VIEW_MULTIUPDATE, 29
ER_VIEW_NONUPD_CHECK, 28
ER_VIEW_NO_CREATION_CTX, 43
ER_VIEW_NO_EXPLAIN, 26
ER_VIEW_NO_INSERT_FIELD_LIST, 29
ER_VIEW_OTHER_USER, 33
ER_VIEW_PREVENT_UPDATE, 33
ER_VIEW_RECURSIVE, 34
ER_VIEW_SELECT_CLAUSE, 27
ER_VIEW_SELECT_DERIVED, 27
ER_VIEW_SELECT_TMPTABLE, 27
ER_VIEW_SELECT_VARIABLE, 27
ER_VTOKEN_PLUGIN_TOKEN_MISMATCH, 82
ER_VTOKEN_PLUGIN_TOKEN_NOT_FOUND, 82
ER_WARNING_NOT_COMPLETE_ROLLBACK, 16
ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_CREATE, 54
ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_DRCON, 54
ER_WARN_ALLOWED_PACKET_OVERFLOWED, 23
ER_WARN_BAD_MAX_EXECUTION_TIME, 81
ER_WARN_CANT_DROP_DEFAULT_KEYCACHE, 32
ER_WARN_CONFLICTING_HINT, 81
ER_WARN_DATA_OUT_OF_RANGE, 21
ER_WARN_DEPRECATED_SQLMODE, 76
ER_WARN_DEPRECATED_SQLMODE_UNSET, 81
ER_WARN_DEPRECATED_SYNTAX, 23
ER_WARN_DEPRECATED_SYNTAX_NO_REPLACEMENT, 49
ER_WARN_DEPRECATED_SYNTAX_WITH_VER, 40
ER_WARN_DEPRECATED_SYSVAR_UPDATE, 76
ER_WARN_DEPRECATED_TLS_VERSION, 93
ER_WARN_ENGINE_TRANSACTION_ROLLBACK, 45
ER_WARN_FIELD_RESOLVED, 22
ER_WARN_HOSTNAME_WONT_WORK, 22
ER_WARN_INDEX_NOT_APPLICABLE, 53
ER_WARN_INVALID_TIMESTAMP, 23
ER_WARN_I_S_SKIPPED_TABLE, 49
ER_WARN_LEGACY_SYNTAX_CONVERTED, 67
ER_WARN_NULL_TO_NOTNULL, 21
ER_WARN_ONLY_MASTER_LOG_FILE_NO_POS, 69
ER_WARN_ON MODIFYING_GTIID_EXECUTED_TABLE, 81
81
ER_WARN_OPEN_TEMP_TABLES_MUST_BE_ZERO, 69
ER_WARN_OPTIMIZER_HINT_SYNTAX_ERROR, 81
81
ER_WARN_PURGE_LOG_IN_USE, 65
ER_WARN_PURGE_LOG_IS_ACTIVE, 65
ER_WARN_QC_RESIZE, 22
ER_WARN_TOO_FEW_RECORDS, 21
ER_WARN_TOO_MANY_RECORDS, 21
ER_WARN_TRIGGER_DOESNT_HAVE_CREATED, 68
ER_WARN_UNKNOWN_QB_NAME, 81
ER_WARN_UNSUPPORTED_MAX_EXECUTION_TIME, 81
81
ER_WARN_USING_GEOMFROMWKB_TO_SET_SRID, 89

ER_WARN_USING_GEOMFROMWKB_TO_SET_SRID_ZERO_WRONG_VALUE_COUNT, 7
89
ER_WARN_USING_OTHER_HANDLER, 21
ER_WARN_VIEW_MERGE, 27
ER_WARN_VIEW_WITHOUT_KEY, 27
ER_WARN_WRONG_NATIVE_TABLE_STRUCTURE, 93
ER_WRITE_SET_EXCEEDS_LIMIT, 93
ER_WRONG_ARGUMENTS, 17
ER_WRONG_AUTO_KEY, 9
ER_WRONG_COLUMN_NAME, 14
ER_WRONG_DB_NAME, 10
ER_WRONG_EXPR_IN_PARTITION_FUNC_ERROR, 35
ER_WRONG_FIELD_SPEC, 8
ER_WRONG_FIELD_TERMINATORS, 9
ER_WRONG_FIELD_WITH_GROUP, 7
ER_WRONG_FIELD_WITH_GROUP_V2, 76
ER_WRONG_FILE_NAME, 80
ER_WRONG_FK_DEF, 20
ER_WRONG_FK_OPTION_FOR_GENERATED_COLUMN, 78
ER_WRONG_GROUP_FIELD, 7
ER_WRONG_KEY_COLUMN, 15
ER_WRONG_LOCK_OF_SYSTEM_TABLE, 32
ER_WRONG_MAGIC, 29
ER_WRONG_MRGR_TABLE, 15
ER_WRONG_NAME_FOR_CATALOG, 22
ER_WRONG_NAME_FOR_INDEX, 22
ER_WRONG_NATIVE_TABLE_STRUCTURE, 49
ER_WRONG_NUMBER_OF_COLUMNS_IN_SELECT, 18
ER_WRONG_OBJECT, 26
ER_WRONG_OUTER_JOIN, 12
ER_WRONG_PARAMCOUNT_TO_NATIVE_FCT, 42
ER_WRONG_PARAMCOUNT_TO_PROCEDURE, 11
ER_WRONG_PARAMETERS_TO_NATIVE_FCT, 42
ER_WRONG_PARAMETERS_TO_PROCEDURE, 11
ER_WRONG_PARAMETERS_TO_STORED_FCT, 42
ER_WRONG_PARTITION_NAME, 41
ER_WRONG_PERFSHEMA_USAGE, 49
ER_WRONG_SIZE_NUMBER, 38
ER_WRONG_SPVAR_TYPE_IN_LIMIT, 50
ER_WRONG_STRING_LENGTH, 34
ER_WRONG_SUB_KEY, 9
ER_WRONG_SUM_SELECT, 7
ER_WRONG_TABLESPACE_NAME, 80
ER_WRONG_TABLE_NAME, 10
ER_WRONG_TYPE_COLUMN_VALUE_ERROR, 47
ER_WRONG_TYPE_FOR_VAR, 19
ER_WRONG_USAGE, 18
ER_WRONG_VALUE, 38
ER_WRONG_VALUE_COUNT_ON_ROW, 13
ER_WRONG_VALUE_FOR_TYPE, 30
ER_WRONG_VALUE_FOR_VAR, 19
ER_WSAS_FAILED, 29
ER_XAER_DUPID, 32
ER_XAER_INVAL, 30
ER_XAER_NOTA, 30
ER_XAER_OUTSIDE, 30
ER_XAER_RMERR, 30
ER_XAER_RMFFAIL, 30
ER_XA_RBDEADLOCK, 44
ER_XA_RBROLLBACK, 30
ER_XA_RBTIMEOUT, 44
ER_XA_REPLICATION_FILTERS, 92
ER_XA_RETRY, 89
ER_YES, 3
ER_ZLIB_Z_BUF_ERROR, 21
ER_ZLIB_Z_DATA_ERROR, 21
ER_ZLIB_Z_MEM_ERROR, 21
WARN_COND_ITEM_TRUNCATED, 46
WARN_DATA_TRUNCATED, 21
WARN_DEPRECATED_MAXDB_SQL_MODE_FOR_TIMESTAMP, 92
WARN_NAMED_PIPE_ACCESS_EVERYONE, 67
WARN_NON_ASCII_SEPARATOR_NOT_IMPLEMENTED, 46
WARN_NO_MASTER_INFO, 44
WARN_ON_BLOCKHOLE_IN_RBR, 65
WARN_OPTION_BELOW_LIMIT, 51
WARN_OPTION_IGNORED, 44
WARN_PLUGIN_BUSY, 45
WARN_PLUGIN_DELETE_BUILTIN, 44
ER_ABORTING_CONNECTION error code, 14
ER_ACCESS_DENIED_CHANGE_USER_ERROR error code, 65
ER_ACCESS_DENIED_ERROR error code, 6
ER_ACCESS_DENIED_NO_PASSWORD_ERROR error code, 50
ER_ACCOUNT_HAS BEEN LOCKED error code, 80
ER_ADD_PARTITION_NO_NEW_PARTITION error code, 37
ER_ADD_PARTITION_SUBPART_ERROR error code, 37
ER_ADMIN_WRONG_MRGR_TABLE error code, 35
ER_AES_INVALID_IV error code, 66
ER_AES_INVALID_KDF_ITERATIONS error code, 93
ER_AES_INVALID_KDF_NAME error code, 93
ER_AES_INVALID_KDF_OPTION_SIZE error code, 93
ER_AGGREGATE_IN_ORDER_NOT_SELECT error code, 74
ER_AGGREGATE_ORDER_FOR_UNION error code, 70
ER_AGGREGATE_ORDER_NON_AGG_QUERY error code, 70
ER_ALTER_FILEGROUP_FAILED error code, 38
ER_ALTER_INFO error code, 9

ER.Alter.Operation.NotSupported error code, 62	ER.Audit.Log.UDF.Invalid.Argument.Count error code, 91
ER.Alter.Operation.NotSupported.Reasoner.Audit.Log.UDF.Invalid.Argument.Type error code, 62	error code, 91
ER.Alter.Operation.NotSupported.Reasoner.ChangeLog.UDF.Read.Invalid.Max.Array.Length error code, 63	error code, 91
ER.Alter.Operation.NotSupported.Reasoner.ChangeLog.UDF.Read.Invalid.Max.Array.Length error code, 63	error code, 91
ER.Alter.Operation.NotSupported.Reasoner.Compat.User.First.Character.MustBeAllError code, 63	error code, 92
ER.Alter.Operation.NotSupported.Reasoner.Compat.User.Name.Invalid.Character error code, 62	error code, 92
ER.Alter.Operation.NotSupported.Reasoner.Kachi.UDF.Read.Failed error code, 34	error code, 34
ER.Alter.Operation.NotSupported.Reasoner.Kachi.Convert error code, 20	ER.Auto.Convert error code, 20
ER.Alter.Operation.NotSupported.Reasoner.Karena.Increment.Conflict error code, 65	ER.Auto.Position.Requires.Gtid.Mode.NotOff error code, 65
ER.Alter.Operation.NotSupported.Reasoner.Karena.Increment.Conflict error code, 62	ER.Auto.Position.Requires.Gtid.Mode.On error code, 62
ER.Alter.Operation.NotSupported.Reasoner.Ft6 code, 56	ER.Bad.Db.Error error code, 7
ER.Alter.Operation.NotSupported.Reasoner.Ft6 code, 56	ER.Bad.Ft.Column error code, 22
ER.Alter.Operation.NotSupported.Reasoner.Ft6 code, 56	ER.Bad.Host.Error error code, 6
ER.Alter.Operation.NotSupported.Reasoner.Ft6 code, 56	ER.Bad.Log.Statement error code, 42
ER.Alter.Operation.NotSupported.Reasoner.Ft6 code, 56	ER.Bad.Null.Error error code, 6
ER.Alter.Operation.NotSupported.Reasoner.Ft6 code, 56	ER.Bad.Slave error code, 17
ER.Alter.Operation.NotSupported.Reasoner.Ft6 code, 56	ER.Bad.Slave.Auto.Position error code, 56
ER.Alter.Operation.NotSupported.Reasoner.Ft6 code, 64	ER.Bad.Slave.Until.Cond error code, 22
ER.Alter.Operation.NotSupported.Reasoner.Ft6 code, 62	ER.Bad4.Decode.Error error code, 41
ER.Ambiguous.Field.Term error code, 35	ER.Before.Dml.Validation.Error error code, 77
ER.Audit.Api.Abort error code, 85	ER.Binlog.Cache.Size.Greater.Than.Max error code, 53
ER.Audit.Log.Could.Not.Create.Aes.Key error code, 90	ER.Binlog.Create.Routine.Need.Super error code, 31
ER.Audit.Log.Encryption.Password.CannotBeBrought.Create.Routine.Need.Super error code, 90	ER.Binlog.Logging.Impossible error code, 43
ER.Audit.Log.Encryption.Password.Has.NotBeenCalled error code, 90	ER.Binlog.Logical.Corruption error code, 64
ER.Audit.Log.Has.Not.Been.Installed error code, 91	ER.Binlog.MultipleEngines.And.Self.Logging.E error code, 48
ER.Audit.Log.Host.Name.Invalid.Character error code, 92	ER.Binlog.Purge.Emfile error code, 42
ER.Audit.Log.Json.Filtering.Not.Enabled error code, 90	ER.Binlog.Purge.Fatal.Err error code, 28
ER.Audit.Log.Json.Filter.Does.Not.Exists error code, 92	ER.Binlog.Purge.Prohibited error code, 28
ER.Audit.Log.Json.Filter.Name.Cannot.BeEmpty error code, 91	ER.Binlog.Read.Event.Checksum.Failure error code, 54
ER.Audit.Log.Json.Filter.Parsing.Error error code, 91	ER.Binlog.Row.Engine.And.Stmt.Engine error code, 47
ER.Audit.Log.Json.User.Name.Cannot.BeEmpty error code, 91	ER.Binlog.Row.Injection.And.Stmt.Engine error code, 48
ER.Audit.Log.No.Keyring.Plugin.Installed error code, 90	ER.Binlog.Row.Mode.And.Stmt.Engine error code, 47
ER.Audit.Log.Super.Privilege.Required error code, 90	ER.Binlog.Row.Rbr.To.Sbr error code, 39
ER.Audit.Log.UDF.Insufficient.Privilege error code, 90	ER.Binlog.Row.Wrong.Table.Def error code, 39

ER_BINLOG_STMT_CACHE_SIZE_GREATER_THAN_MAX_BOOST_GEOMETRY_EMPTY_INPUT_EXCEPTION
error code, 54

ER_BINLOG_STMT_MODE_AND_NO_REPL_TABLES
error code, 62

ER_BINLOG_STMT_MODE_AND_ROW_ENGINE
error code, 48

ER_BINLOG_UNSAFE_AND_STMT_ENGINE error code, 47

ER_BINLOG_UNSAFE_AUTOINC_COLUMNS error code, 48

ER_BINLOG_UNSAFE_AUTOINC_NOT_FIRST error code, 52

ER_BINLOG_UNSAFE_CREATE_IGNORE_SELECT
error code, 51

ER_BINLOG_UNSAFE_CREATE_REPLACE_SELECT
error code, 52

ER_BINLOG_UNSAFE_CREATE_SELECT_AUTOINC
error code, 52

ER_BINLOG_UNSAFE_FULLTEXT_PLUGIN error code, 67

ER_BINLOG_UNSAFE_INSERT_IGNORE_SELECT
error code, 51

ER_BINLOG_UNSAFE_INSERT_SELECT_UPDATE
error code, 51

ER_BINLOG_UNSAFE_INSERT_TWO_KEYS error code, 52

ER_BINLOG_UNSAFE_LIMIT error code, 48

ER_BINLOG_UNSAFE_MIXED_STATEMENT error code, 50

ER_BINLOG_UNSAFE_MULTIPLE_ENGINES_AND_SELEROCASTING_IN_ONE_LOG error code, 41

ER_BINLOG_UNSAFE_NONTRANS_AFTER_TRANS
error code, 48

ER_BINLOG_UNSAFE_REPLACE_SELECT error code, 51

ER_BINLOG_UNSAFE_ROUTINE error code, 31

ER_BINLOG_UNSAFE_STATEMENT error code, 43

ER_BINLOG_UNSAFE_SYSTEM_FUNCTION error code, 48

ER_BINLOG_UNSAFE_SYSTEM_TABLE error code, 48

ER_BINLOG_UNSAFE_SYSTEM_VARIABLE error code, 48

ER_BINLOG_UNSAFE_UDF error code, 48

ER_BINLOG_UNSAFE_UPDATE_IGNORE error code, 52

ER_BINLOG_UNSAFE_WRITE_AUTOINC_SELECT
error code, 52

ER_BINLOG_UNSAFE_XA error code, 89

ER_BLOBS_AND_NO_TERMINATED error code, 9

ER_BLOB_CANT_HAVE_DEFAULT error code, 10

ER_BLOB_FIELD_IN_PART_FUNC_ERROR error code, 37

ER_BLOB_KEY_WITHOUT_LENGTH error code, 15

ER_BLOB_USED_AS_KEY error code, 8

ER_BOOST_GEOMETRY_CENTROID_EXCEPTION
error code, 71

ER_BOOST_GEOMETRY_EMPTY_INPUT_EXCEPTION
error code, 71

ER_BOOST_GEOMETRY_INCONSISTENT_TURNS_EXCEPTION
error code, 81

ER_BOOST_GEOMETRY_OVERLAY_INVALID_INPUT_EXCEPTION
error code, 71

ER_BOOST_GEOMETRY_SELF_INTERSECTION_POINT_EXCEPTION
error code, 71

ER_BOOST_GEOMETRY_TURN_INFO_EXCEPTION
error code, 71

ER_BOOST_GEOMETRY_UNKNOWN_EXCEPTION
error code, 72

ER_BUFPOLL_RESIZE_INPROGRESS error code, 85

ER_CANNOT_ADD_FOREIGN error code, 18

ER_CANNOT_ADD_FOREIGN_BASE_COL_STORED
error code, 88

ER_CANNOT_ADD_FOREIGN_BASE_COL_VIRTUAL
error code, 86

ER_CANNOT_CREATE_VIRTUAL_INDEX_CONSTRAINT
error code, 86

ER_CANNOT_DISCARD_TEMPORARY_TABLE error code, 68

ER_CANNOT_FIND_KEY_IN_KEYRING error code, 88

ER_CANNOT_LOAD_FROM_TABLE_V2 error code, 52

ER_CANNOT_LOG_PARTIAL_DROP_DATABASE_WITH_GTID
error code, 76

ER_CANNOT_USER error code, 29

ER_CANT_CHANGE_GTI
error code, 21

ER_CANT_CHANGE_GTI_IN_TRANSACTION
error code, 56

ER_CANT_CHANGE_GTI_IN_TRANSACTION_WHEN_GTID_Next
error code, 55

ER_CANT_CHANGE_TX_CHARACTERISTICS error code, 41

ER_CANT_CREATE_DB error code, 4

ER_CANT_CREATE_FEDERATED_TABLE error code, 32

ER_CANT_CREATE_FILE error code, 3

ER_CANT_CREATE_GEOMETRY_OBJECT error code, 31

ER_CANT_CREATE_HANDLER_FILE error code, 36

ER_CANT_CREATE_ROUTINE error code, 44

ER_CANT_CREATE_TABLE error code, 4

ER_CANT_CREATE_THREAD error code, 13

ER_CANT_CREATE_USER_WITH_GRANT error code, 30

ER_CANT_DELETE_FILE error code, 4

ER_CANT_DO_IMPLICIT_COMMIT_IN_TRX_WHEN_GTID_NEXT
error code, 57

ER_CANT_DO_THIS_DURING_AN_TRANSACTION	ER_CANT_WAIT_FOR_EXECUTED_GTID_SET_WHILE_OWNING_TABLE error code, 86
error code, 15	
ER_CANT_DROP_FIELD_OR_KEY error code, 10	ER_CANT_WRITE_LOCK_LOG_TABLE error code, 40
ER_CANT_EXECUTE_IN_READ_ONLY_TRANSACTION	ER_CAPACITY_EXCEEDED error code, 86
error code, 58	ER_CAPACITY_EXCEEDED_IN_PARSER error code, 88
ER_CANT_FIND_DL_ENTRY error code, 12	ER_CAPACITY_EXCEEDED_IN_RANGE_OPTIMIZER error code, 86
ER_CANT_FIND_SYSTEM_REC error code, 4	ER_CHANGE_MASTER_PASSWORD_LENGTH error code, 73
ER_CANT_FIND_UDF error code, 12	ER_CHANGE_RPL_INFO_REPOSITORY_FAILURE error code, 54
ER_CANT_GET_STAT error code, 4	ER_CHECKREAD error code, 5
ER_CANT_GET_WD error code, 4	ER_CHECK_NOT_IMPLEMENTED error code, 15
ER_CANT_INITIALIZE_UDF error code, 12	ER_CHECK_NO SUCH_TABLE error code, 15
ER_CANT_LOCK error code, 4	ER_COALESCE_ONLY_ON_HASH_PARTITION error code, 37
ER_CANT_LOCK_LOG_TABLE error code, 40	ER_COALESCE_PARTITION_NO_PARTITION error code, 37
ER_CANT_OPEN_ERROR_LOG error code, 92	ER_COLLATION_CHARSET_MISMATCH error code, 29
ER_CANT_OPEN_FILE error code, 4	ER_COLUMNACCESS_DENIED_ERROR error code, 10
ER_CANT_OPEN_LIBRARY error code, 12	ER_COL_COUNT_DOESNT_MATCH_CORRUPTED_V2 error code, 59
ER_CANT_READ_DIR error code, 5	ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE error code, 40
ER_CANT_REMOVE_ALL_FIELDS error code, 9	ER_COMMIT_NOT_ALLOWED_IN_SF_OR_TRG error code, 46
ER_CANT_RENAME_LOG_TABLE error code, 42	ER_COND_ITEM_TOO_LONG error code, 24
ER_CANT_REOPEN_TABLE error code, 13	ER_CONFLICT_FN_PARSE_ERROR error code, 45
ER_CANT_REPLICATE_ANONYMOUS_WITH_AUTO_POSITION	ER_CONNECT_TO_MASTER error code, 18
error code, 79	ER_CONSECUTIVE_REORG_PARTITIONS error code, 38
ER_CANT_REPLICATE_ANONYMOUS_WITH_GTID_MODE	ER_CON_COUNT_ERROR error code, 6
ON	ER_CRASHED_ON_REPAIR error code, 16
error code, 79	ER_CRASHED_ON_USAGE error code, 16
ER_CANT_REPLICATE_GTID_WITH_GTID_MODE_OFF	ER_CREATE_DB_WITH_READ_LOCK error code, 17
error code, 80	ER_CREATE_FILEGROUP_FAILED error code, 38
ER_CANT_RESET_MASTER error code, 88	ER_CUT_VALUE_GROUP_CONCAT error code, 21
ER_CANT_SET_ENFORCE_GTID_CONSISTENCY_ON	ER_CYCLIC_REFERENCE error code, 20
ER_CANT_SET_GTID_MODE error code, 79	ER_DATABASE_NAME error code, 45
ER_CANT_SET_GTID_NEXT_LIST_TO_NON_NULL_WHEN_GTID_MODE_IS_OFF	ER_DATA_OUT_OF_RANGE error code, 49
error code, 57	ER_DATA_TOO_LONG error code, 30
ER_CANT_SET_GTID_NEXT_TO_ANONYMOUS_WHEN_GTID_MODE_IS_NOT_DECLARED	ER_DATETIME_FUNCTION_OVERFLOW error code, 32
error code, 57	ER_DA_INVALID_CONDITION_NUMBER error code, 50
ER_CANT_SET_GTID_NEXT_TO_GTID_WHEN_GTID_MODE_IS_NOT_SET_TO_FOREIGN_DATA_SOURCE	ER_DBACCESS_DENIED_ERROR error code, 6
error code, 57	ER_DB_CREATE_EXISTS error code, 4
ER_CANT_SET_GTID_NEXT_WHEN_OWNING_GTID_MODE_IS_NOT_EMPTY	
error code, 58	
ER_CANT_SET_GTID_PURGED_WHEN_GTID_EXECUTION_MODE_IS_NOT_HELP_DB	
error code, 62	
ER_CANT_SET_GTID_PURGED_WHEN_GTID_MODE_IS_BROKEN	
error code, 62	
ER_CANT_SET_GTID_PURGED_WHEN_OWNED_GTID_IS_NOT_EMPTY	
error code, 62	
ER_CANT_SET_VARIABLE_WHEN_OWNING_GTID	
error code, 83	
ER_CANT_SET_WD error code, 5	
ER_CANT_START_SERVER_NAMED_PIPE error code, 92	
ER_CANT_UPDATE_TABLE_IN_CREATE_TABLE_SELECT	
error code, 54	
ER_CANT_UPDATE_USED_TABLE_IN_SF_OR_TRG	
error code, 33	
ER_CANT_UPDATE_WITH_READLOCK error code, 19	
ER_CANT_USE_AUTO_POSITION_WITH_GTID_MODE_OFF	
error code, 79	
ER_CANT_USE_OPTION_HERE error code, 19	

ER_DB_DROP_DELETE error code, 4
ER_DB_DROP_EXISTS error code, 4
ER_DB_DROP_RMDIR error code, 4
ER_DDL_LOG_ERROR error code, 41
ER_DEBUG_SYNC_HIT_LIMIT error code, 46
ER_DEBUG_SYNC_TIMEOUT error code, 46
ER_DELAYED_NOT_SUPPORTED error code, 44
ER_DEPENDENT_BY_GENERATED_COLUMN error code, 79
ER_DEPRECATED_TLS_VERSION_SESSION error code, 93
ER_DERIVED_MUST_HAVE_ALIAS error code, 20
ER_DIFF_GROUPS_PROC error code, 29
ER_DIMENSION_UNSUPPORTED error code, 74
ER_DISABLED_STORAGE_ENGINE error code, 85
ER_DISCARD_FK_CHECKS_RUNNING error code, 59
ER_DISK_FULL error code, 5
ER_DIVISION_BY_ZERO error code, 28
ER_DONT_SUPPORT_SLAVE_PRESERVE_COMMIT_ORDER error code, 70
ER_DROP_DB_WITH_READ_LOCK error code, 17
ER_DROP_FILEGROUP_FAILED error code, 38
ER_DROP_INDEX_FK error code, 40
ER_DROP_LAST_PARTITION error code, 37
ER_DROP_PARTITION_NON_EXISTENT error code, 37
ER_DROP_USER error code, 21
ER_DUMP_NOT_IMPLEMENTED error code, 16
ER_DUPLICATED_VALUE_IN_TYPE error code, 23
ER_DUP_ARGUMENT error code, 19
ER_DUP_ENTRY error code, 8
ER_DUP_ENTRY_AUTOINCREMENT_CASE error code, 41
ER_DUP_ENTRY_WITH_KEY_NAME error code, 42
ER_DUP_FIELDNAME error code, 8
ER_DUP_INDEX error code, 61
ER_DUP_KEY error code, 5
ER_DUP_KEYNAME error code, 8
ER_DUP_LIST_ENTRY error code, 70
ER_DUP_SIGNAL_SET error code, 46
ER_DUP_UNIQUE error code, 15
ER_DUP_UNKNOWN_IN_INDEX error code, 64
ER_EMPTY_QUERY error code, 8
ER_ENGINE_OUT_OF_MEMORY error code, 68
ER_ERROR_DURING_CHECKPOINT error code, 16
ER_ERROR_DURING_COMMIT error code, 15
ER_ERROR_DURING_FLUSH_LOGS error code, 16
ER_ERROR_DURING_ROLLBACK error code, 15
ER_ERROR_IN_TRIGGER_BODY error code, 51
ER_ERROR_IN_UNKNOWN_TRIGGER_BODY error code, 51
ER_ERROR_ON_CLOSE error code, 5
ER_ERROR_ON_MASTER error code, 67
ER_ERROR_ON MODIFYING_GTID_EXECUTED_TABLE error code, 87
ER_ERROR_ON_READ error code, 5
ER_ERROR_ON_RENAME error code, 5
ER_ERROR_ON_WRITE error code, 5
ER_ERROR_WHEN_EXECUTING_COMMAND error code, 18
ER_EVENTS_DB_ERROR error code, 42
ER_EVENT_ALREADY_EXISTS error code, 39
ER_EVENT_CANNOT_ALTER_IN_THE_PAST error code, 42
ER_EVENT_CANNOT_CREATE_IN_THE_PAST error code, 42
ER_EVENT_CANNOT_DELETE error code, 40
ER_EVENT_CANT_ALTER error code, 39
ER_EVENT_COMPILE_ERROR error code, 40
ER_EVENT_DATA_TOO_LONG error code, 40
ER_EVENT_DOES_NOT_EXIST error code, 39
ER_EVENT_DROP_FAILED error code, 39
ER_EVENT_ENDS_BEFORE_STARTS error code, 39
ER_EVENT_EXEC_TIME_IN_THE_PAST error code, 39
ER_EVENT_INTERVAL_NOT_POSITIVE_OR_TOO_BIG error code, 39
ER_EVENT_INVALID_CREATION_CTX error code, 43
ER_EVENT_MODIFY_QUEUE_ERROR error code, 41
ER_EVENT_NEITHER_M_EXPR_NOR_M_AT error code, 39
ER_EVENT_OPEN_TABLE_FAILED error code, 39
ER_EVENT_RECURSION_FORBIDDEN error code, 41
ER_EVENT_SAME_NAME error code, 40
ER_EVENT_SET_VAR_ERROR error code, 41
ER_EVENT_STORE_FAILED error code, 39
ER_EXCEPTIONS_WRITE_ERROR error code, 45
ER_EXEC_STMT_WITH_OPEN_CURSOR error code, 31
ER_EXPLAIN_NOT_SUPPORTED error code, 68
ER_FAILED_READ_FROM_PAR_FILE error code, 50
ER_FAILED_ROUTINE_BREAK_BINLOG error code, 31
ER_FEATURE_DISABLED error code, 23
ER_FEATURE_DISABLED_SEE_DOC error code, 86
ER_FEATURE_NOT_AVAILABLE error code, 79
ER_FIELD_IN_ORDER_NOT_SELECT error code, 74
ER_FIELD_NOT_FOUND_PART_ERROR error code, 36
ER_FIELD_SPECIFIED_TWICE error code, 11
ER_FIELD_TYPE_NOT_ALLOWED_AS_PARTITION_FIELD error code, 47
ER_FILEGROUP_OPTION_ONLY_ONCE error code, 38
ER_FILE_CORRUPT error code, 67
ER_FILE_EXISTS_ERROR error code, 9
ER_FILE_NOT_FOUND error code, 5
ER_FILE_USED error code, 5
ER_FILSORT_ABORT error code, 5
ER_FK_CANNOT_DELETE_PARENT error code, 61
ER_FK_FK_CANNOT_OPEN_PARENT error code, 60
ER_FK_COLUMN_CANNOT_CHANGE error code, 61
ER_FK_COLUMN_CANNOT_CHANGE_CHILD error code, 61

ER_FK_COLUMN_CANNOT_DROP error code, 61
ER_FK_COLUMN_CANNOT_DROP_CHILD error code, 61
ER_FK_COLUMN_NOT_NULL error code, 61
ER_FK_DEPTH_EXCEEDED error code, 68
ER_FK_DUP_NAME error code, 61
ER_FK_FAIL_ADD_SYSTEM error code, 60
ER_FK_INCORRECT_OPTION error code, 60
ER_FK_NO_INDEX_CHILD error code, 60
ER_FK_NO_INDEX_PARENT error code, 60
ER_FLUSH_MASTER_BINLOG_CLOSED error code, 16
ER_FORBID_SCHEMA_CHANGE error code, 33
ER_FORCING_CLOSE error code, 9
ER_FOREIGN_DATA_SOURCE_DOESNT_EXIST error code, 32
ER_FOREIGN_DATA_STRING_INVALID error code, 32
ER_FOREIGN_DATA_STRING_INVALID_CANT_CREATIER error code, 32
ER_FOREIGN_DUPLICATE_KEY_OLD_UNUSED error code, 40
ER_FOREIGN_DUPLICATE_KEY_WITHOUT_CHILD_INFO error code, 55
ER_FOREIGN_DUPLICATE_KEY_WITH_CHILD_INFO error code, 55
ER_FOREIGN_KEY_ON_PARTITIONED error code, 37
ER_FOREIGN_SERVER_DOESNT_EXIST error code, 35
ER_FOREIGN_SERVER_EXISTS error code, 35
ER_FORM_NOT_FOUND error code, 5
ER_FOUND_GTIID_EVENT_WHEN_GTIID_MODE_IS_OFER error code, 57
ER_FOUND_GTIID_EVENT_WHEN_GTIID_MODE_IS_OFER _CROSSED error code, 57
ER_FOUND_MISSING_GTIDS error code, 67
ER_FPARSER_BAD_HEADER error code, 26
ER_FPARSER_EOF_IN_COMMENT error code, 26
ER_FPARSER_EOF_IN_UNKNOWN_PARAMETER error code, 26
ER_FPARSER_ERROR_IN_PARAMETER error code, 26
ER_FPARSER_TOO_BIG_FILE error code, 26
ER_FRM_UNKNOWN_TYPE error code, 26
ER_FSEEK_FAIL error code, 28
ER_FT_MATCHING_KEY_NOT_FOUND error code, 16
ER_FULLTEXT_NOT_SUPPORTED_WITH_PARTITIONING error code, 55
ER_FUNCTION_NOT_DEFINED error code, 12
ER_FUNC_INEXISTENT_NAME_COLLISION error code, 45
ER_GENERATED_COLUMN_FUNCTION_IS_NOT_ALLOO error code, 78
ER_GENERATED_COLUMN_NON_PRIOR error code, 79
ER_GENERATED_COLUMN_REF_AUTO_INC error code, 79
ER_GET_ERRMSG error code, 23
ER_GET_ERRNO error code, 5
ER_GET_STACKED_DA_WITHOUT_ACTIVE_HANDLER error code, 67
ER_GET_TEMPORARY_ERRMSG error code, 23
ER_GIS_DATA_WRONG_ENDIANESS error code, 73
ER_GIS_DIFFERENT_SRIDS error code, 70
ER_GIS_INVALID_DATA error code, 71
ER_GIS_MAX_POINTS_IN_GEOMETRY_OVERFLOWED error code, 82
ER_GIS_UNKNOWN_ERROR error code, 71
ER_GIS_UNKNOWN_EXCEPTION error code, 71
ER_GIS_UNSUPPORTED_ARGUMENT error code, 71
ER_GLOBAL_VARIABLE error code, 19
ER_GNO_EXHAUSTED error code, 56
ER_GOT_SIGNAL error code, 9
ER_GRANT_PLUGIN_USER_EXISTS error code, 50
ER_GRANT_WRONG_HOST_OR_USER error code, 13
ER_GROUP_GROUPING_ON_TIMESTAMP_IN_DST error code, 92
ER_GROUP_REPLICATION_APPLIER_INIT_ERROR error code, 77
ER_GROUP_REPLICATION_COMMUNICATION_LAYER_JOIN error code, 77
ER_GROUP_REPLICATION_COMMUNICATION_LAYER_SES error code, 77
ER_GROUP_REPLICATION_CONFIGURATION error code, 77
ER_GROUP_REPLICATION_MAX_GROUP_SIZE error code, 88
ER_GROUP_RUNNING error code, 77
ER_GROUP_STOP_APPLIER_THREAD_TIME error code, 77
ER_GTIID_EXECUTED_WAS_CHANGED error code, 62
ER_GTIID_MODE_2_OR_3QUIRES_ENFORCE_GTIID_CO error code, 57
ER_GTIID_MODE_CAN_ONLY_CHANGE_ONE_STEP_AT_A_ error code, 58
ER_GTIID_MODE_OFF error code, 73
ER_GTIID_MODE_ONQUIRES_ENFORCE_GTIID_CONSI error code, 57
ER_GTIID_MODEQUIRES_BINLOG error code, 57
ER_GTIID_NEXT_CANT_BE_AUTOMATIC_IF_GTIID_NEXT_LI error code, 56
ER_GTIID_NEXT_IS_NOT_IN_GTIID_NEXT_LIST error code, 55
ER_GTIID_UNDEFINED_GROUP error code, 61
ER_GTIID_PURGED_WAS_CHANGED error code, 62
ER_GTIID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AN error code, 66
ER_GTIID_UNSAFE_CREATE_DROP_TEMPORARY_TABLE_ error code, 58

ER_GTID_UNSAFE_CREATE_SELECT error code, 58
ER_GTID_UNSAFE_NON_TRANSACTIONAL_TABLE error code, 58
ER_HANDSHAKE_ERROR error code, 6
ER_HASHCHK error code, 3
ER_HOSTNAME error code, 34
ER_HOST_IS_BLOCKED error code, 12
ER_HOST_NOT_PRIVILEGED error code, 12
ER_IDENT_CAUSES_TOO_LONG_PATH error code, 64
ER_ILLEGAL_GRANT_FOR_TABLE error code, 13
ER_ILLEGAL_HA error code, 5
ER_ILLEGAL_HA_CREATE_OPTION error code, 35
ER_ILLEGAL_REFERENCE error code, 20
ER_ILLEGAL_USER_VAR error code, 73
ER_ILLEGAL_VALUE_FOR_TYPE error code, 28
ER_INCONSISTENT_ERROR error code, 67
ER_INCONSISTENT_PARTITION_INFO_ERROR error code, 36
ER_INCONSISTENT_TYPE_OF_FUNCTIONS_ERROR error code, 36
ER_INCORRECT_GLOBAL_LOCAL_VAR error code, 19
ER_INCORRECT_TYPE error code, 74
ER_INDEX_COLUMN_TOO_LONG error code, 51
ER_INDEX_CORRUPT error code, 51
ER_INDEX_REBUILD error code, 16
ER_INNODB_FORCED_RECOVERY error code, 66
ER_INNODB_FT_AUX_NOT_HEX_ID error code, 66
ER_INNODB_FT_LIMIT error code, 58
ER_INNODB_FT_WRONG_DOCID_COLUMN error code, 59
ER_INNODB_FT_WRONG_DOCID_INDEX error code, 59
ER_INNODB_IMPORT_ERROR error code, 60
ER_INNODB_INDEX_CORRUPT error code, 60
ER_INNODB_NO_FT_TEMP_TABLE error code, 59
ER_INNODB_NO_FTUSES_PARSER error code, 64
ER_INNODB_ONLINE_LOG_TOO_BIG error code, 59
ER_INNODB_READ_ONLY error code, 65
ER_INNODB_UNDO_LOG_FULL error code, 69
ER_INSECURE_CHANGE_MASTER error code, 55
ER_INSECURE_PLAIN_TEXT error code, 55
ER_INSERT_INFO error code, 10
ER_INSIDE TRANSACTION_PREVENTS_SWITCH_BINLOG_KEYRING error code, 49
ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG_KEYRING error code, 49
ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_SQL_ROLLBACKBASED_ON_GENERATED_COLUMN error code, 50
ER_INTERNAL_ERROR error code, 60
ER_INVALID_ARGUMENT_FOR_LOGARITHM error code, 69
ER_INVALID_CAST_TO_JSON error code, 83
ER_INVALID_CHARACTER_STRING error code, 23
ER_INVALID_DEFAULT error code, 8
ER_INVALID_ENCRYPTION_OPTION error code, 87
ER_INVALID_FIELD_SIZE error code, 68
ER_INVALID_GEOJSON_MISSING_MEMBER error code, 74
ER_INVALID_GEOJSON_UNSPECIFIED error code, 74
ER_INVALID_GEOJSON_WRONG_TYPE error code, 74
ER_INVALID_GROUP_FUNC_USE error code, 11
ER_INVALID_JSON_BINARY_DATA error code, 83
ER_INVALID_JSON_CHARSET error code, 83
ER_INVALID_JSON_CHARSET_IN_FUNCTION error code, 83
ER_INVALID_JSON_DATA error code, 74
ER_INVALID_JSON_PATH error code, 83
ER_INVALID_JSON_PATH_ARRAY_CELL error code, 85
ER_INVALID_JSON_PATH_CHARSET error code, 84
ER_INVALID_JSON_PATH_WILDCARD error code, 84
ER_INVALID_JSON_TEXT error code, 83
ER_INVALID_JSON_TEXT_IN_PARAM error code, 83
ER_INVALID_JSON_VALUE_FOR_CAST error code, 84
ER_INVALID_ON_UPDATE error code, 23
ER_INVALID_RPL_WILD_TABLE_FILTER_PATTERN error code, 74
ER_INVALID_TYPE_FOR_JSON error code, 83
ER_INVALID_USE_OF_NULL error code, 13
ER_INVALID_YEAR_COLUMN_LENGTH error code, 60
ER_IO_ERR_LOG_INDEX_READ error code, 28
ER_IO_READ_ERROR error code, 59
ER_IO_WRITE_ERROR error code, 60
ER_IPSOCK_ERROR error code, 9
ER_JSON_BAD_ONE_OR_ALL_ARG error code, 84
ER_JSON_DOCUMENT_NULL_KEY error code, 85
ER_JSON_DOCUMENT_TOO_DEEP error code, 84
ER_JSON_KEY_TOO_BIG error code, 84
ER_JSON_USED_AS_KEY error code, 84
ER_JSON_VACUOUS_PATH error code, 84
ER_JSON_VALUE_TOO_BIG error code, 84
ER_KEYRING_ACCESS_DENIED_ERROR error code, 89
ER_KEYRING_AWS_UDF_AWS_KMS_ERROR error code, 89
ER_KEYRING_MIGRATION_FAILURE error code, 89
ER_KEYRING_MIGRATION_STATUS error code, 89
ER_KEYRING_UDF_KEYRING_SERVICE_ERROR error code, 88
ER_ROLLBACKBASED_ON_GENERATED_COLUMN error code, 78
ER_KEY_COLUMN_DOES_NOT_EXISTS error code, 8
ER_KEY_DOES_NOT_EXISTS error code, 15
ER_KEY_NOT_FOUND error code, 5
ER_KEY_PART_0 error code, 29
ER_KEY_REF_DO_NOT_MATCH_TABLE_REF error code, 20
ER_KILL_DENIED_ERROR error code, 10
ER_LIMITED_PART_RANGE error code, 38

ER_LIST_OF_FIELDS_ONLY_IN_HASH_ERROR error code, 36
ER_LOAD_DATA_INVALID_COLUMN error code, 44
ER_LOAD_DATA_INVALID_COLUMN_UNUSED error code, 44
ER_LOAD_FROM_FIXED_SIZE_ROWS_TO_VAR error code, 30
ER_LOAD_INFO error code, 9
ER_LOCAL_VARIABLE error code, 19
ER_LOCKING_SERVICE_DEADLOCK error code, 82
ER_LOCKING_SERVICE_TIMEOUT error code, 82
ER_LOCKING_SERVICE_WRONG_NAME error code, 82
ER_LOCK_ABORTED error code, 49
ER_LOCK_DEADLOCK error code, 18
ER_LOCK_OR_ACTIVE_TRANSACTION error code, 16
ER_LOCK_REFUSED_BY_ENGINE error code, 87
ER_LOCK_TABLE_FULL error code, 17
ER_LOCK_WAIT_TIMEOUT error code, 17
ER_LOGGING_PROHIBIT_CHANGING_OF error code, 29
ER_LOG_IN_USE error code, 28
ER_LOG_PURGE_NO_FILE error code, 44
ER_LOG_PURGE_UNKNOWN_ERR error code, 28
ER_MALFORMED_DEFINER error code, 33
ER_MALFORMED_GTID_SET_ENCODING error code, 56
ER_MALFORMED_GTID_SET_SPECIFICATION error code, 56
ER_MALFORMED_GTID_SPECIFICATION error code, 56
ER_MALFORMED_PACKET error code, 61
ER_MASTER error code, 16
ER_MASTER_DELAY_VALUE_OUT_OF_RANGE error code, 52
ER_MASTER_FATAL_ERROR_READING_BINLOG error code, 19
ER_MASTER_HAS_PURGED_REQUIRED_GTIDS error code, 58
ER_MASTER_INFO error code, 17
ER_MASTER_KEY_ROTATION_BINLOG_FAILED error code, 87
ER_MASTER_KEY_ROTATION_ERROR_BY_SE error code, 87
ER_MASTER_KEY_ROTATION_NOT_SUPPORTED_BY_SE error code, 87
ER_MASTER_KEY_ROTATION_SE_UNAVAILABLE error code, 87
ER_MASTER_NET_READ error code, 16
ER_MASTER_NET_WRITE error code, 16
ER_MAXVALUE_IN_VALUES_IN error code, 47
ER_MAX_PREPARED_STMT_COUNT_REACHED error code, 34
ER_MESSAGE_AND_STATEMENT error code, 49
ER_MISSING_HA_CREATE_OPTION error code, 68
ER_MISSING_KEY error code, 67
ER_MISSING_SKIP_SLAVE error code, 22
ER_MIXING_NOT_ALLOWED error code, 19
ER_MIX_HANDLER_ERROR error code, 36
ER_MIX_OF_GROUP_FUNC_AND_FIELDS error code, 13
ER_MIX_OF_GROUP_FUNC_AND_FIELDS_V2 error code, 76
ER_MTS_CANT_PARALLEL error code, 54
ER_MTS_CHANGE_MASTER_CANT_RUN_WITH_GAPS error code, 59
ER_MTS_EVENT_BIGGER_PENDING_JOBS_SIZE_MAX error code, 64
ER_MTS_FEATURE_IS_NOT_SUPPORTED error code, 54
ER_MTS_INCONSISTENT_DATA error code, 54
ER_MTS_RECOVERY_FAILURE error code, 59
ER_MTS_RESET_WORKERS error code, 59
ER_MTS_UPDATED_DBs_GREATER_MAX error code, 54
ER_MULTIPLE_DEF_CONST_IN_LIST_PART_ERROR error code, 36
ER_MULTIPLE_PRI_KEY error code, 8
ER_MULTI_UPDATE_KEY_CONFLICT error code, 51
ER_MUST_CHANGE_PASSWORD error code, 60
ER_MUST_CHANGE_PASSWORD_LOGIN error code, 64
ER_M_BIGGER_THAN_D error code, 32
ER_NAME_BECOMES_EMPTY error code, 35
ER_NATIVE_FCT_NAME_COLLISION error code, 42
ER_NDB_CANT_SWITCH_BINLOG_FORMAT error code, 41
ER_NDB_REPLICATION_SCHEMA_ERROR error code, 45
ER_NEED_REPREPARE error code, 44
ER_NETWORK_READ_EVENT_CHECKSUM_FAILURE error code, 53
ER_NET_ERROR_ON_WRITE error code, 14
ER_NET_FCNTL_ERROR error code, 14
ER_NET_OK_PACKET_TOO_LARGE error code, 74
ER_NET_PACKETS_OUT_OF_ORDER error code, 14
ER_NET_PACKET_TOO_LARGE error code, 14
ER_NET_READ_ERROR error code, 14
ER_NET_READ_ERROR_FROM_PIPE error code, 14
ER_NET_READ_INTERRUPTED error code, 14
ER_NET_UNCOMPRESS_ERROR error code, 14
ER_NET_WRITE_INTERRUPTED error code, 14
ER_NEVER_USED error code, 44
ER_NEW_ABORTING_CONNECTION error code, 16
ER_NISAMCHK error code, 3
ER_NO error code, 3
ER_NONEXISTING_GRANT error code, 13
ER_NONEXISTING_PROC_GRANT error code, 30
ER_NONEXISTING_TABLE_GRANT error code, 13
ER_NONUNIQ_TABLE error code, 8
ER_NONUPDATEABLE_COLUMN error code, 26
ER_NON_DEFAULT_VALUE_FOR_GENERATED_COLUMN error code, 78
ER_NON_GROUPING_FIELD_USED error code, 34
ER_NON_INSERTABLE_TABLE error code, 34

ER_NON_RO_SELECT_DISABLE_TIMER error code, 70
ER_NON_UNIQ_ERROR error code, 7
ER_NON_UPDATABLE_TABLE error code, 23
ER_NORMAL_SHUTDOWN error code, 9
ER_NOT_ALLOWED_COMMAND error code, 13
ER_NOT_FORM_FILE error code, 6
ER_NOT_KEYFILE error code, 6
ER_NOT_SUPPORTED_AUTH_MODE error code, 20
ER_NOT_SUPPORTED_YET error code, 19
ER_NOT_VALID_PASSWORD error code, 60
ER_NO_BINARY_LOGGING error code, 29
ER_NO_BINLOG_ERROR error code, 38
ER_NO_CONST_EXPR_IN_RANGE_OR_LIST_ERROR error code, 36
ER_NO_DB_ERROR error code, 6
ER_NO_DEFAULT error code, 19
ER_NO_DEFAULT_FOR_FIELD error code, 28
ER_NO_DEFAULT_FOR_VIEW_FIELD error code, 31
ER_NO_FILE_MAPPING error code, 29
ER_NO_FORMAT_DESCRIPTION_EVENT_BEFORE_BINLOG_ERROR error code, 44
ER_NO_FT_MATERIALIZED_SUBQUERY error code, 69
ER_NO_GROUP_FOR_PROC error code, 29
ER_NO_PARTITION_FOR_GIVEN_VALUE error code, 38
ER_NO_PARTITION_FOR_GIVEN_VALUE_SILENT error code, 43
ER_NO_PARTS_ERROR error code, 37
ER_NO_PERMISSION_TO_CREATE_USER error code, 18
ER_NO_RAID_COMPILED error code, 15
ER_NO_REFERENCED_ROW error code, 18
ER_NO_REFERENCED_ROW_2 error code, 33
ER_NO_SECURE_TRANSPORTS_CONFIGURED error code, 85
ER_NO SUCH INDEX error code, 9
ER_NO SUCH KEY_VALUE error code, 53
ER_NO SUCH PARTITION_UNUSED error code, 54
ER_NO SUCH TABLE error code, 13
ER_NO SUCH THREAD error code, 10
ER_NO SUCH USER error code, 33
ER_NO_TABLES_USED error code, 10
ER_NO_TRIGGER_ON_SYSTEM_SCHEMA error code, 34
ER_NO_UNIQUE_LOGFILE error code, 10
ER_NULL_COLUMN_IN_INDEX error code, 12
ER_NULL_IN_VALUES_LESS_THAN error code, 41
ER_NUMERIC_JSON_VALUE_OUT_OF_RANGE error code, 84
ER_OBSOLETE_CANNOT_LOAD_FROM_TABLE error code, 39
ER_OBSOLETE_COL_COUNT_DOESNT_MATCH_CORRESPONDING_PARTITION error code, 39
ER_OLD_FILE_FORMAT error code, 33
ER_OLD_KEYFILE error code, 6
ER_OLD_TEMPORALS_UPGRADED error code, 66
ER_ONLY_FD_AND_RBR_EVENTS_ALLOWED_IN_BINLOG_STANDBY error code, 53
ER_ONLY_INTEGERS_ALLOWED error code, 42
ER_ONLY_ON_RANGE_LIST_PARTITION error code, 37
ER_OPEN_AS_READONLY error code, 6
ER_OPERAND_COLUMNS error code, 20
ER_OPTION_PREVENTS_STATEMENT error code, 23
ER_ORDER_WITH_PROC error code, 29
ER_OUTOFMEMORY error code, 6
ER_OUT_OF_RESOURCES error code, 6
ER_OUT_OF_SORTMEMORY error code, 6
ER_PARSE_ERROR error code, 8
ER_PARTITIONS_MUST_BE_DEFINED_ERROR error code, 36
ER_PARTITION_CLAUSE_ON_NONPARTITIONED error code, 54
ER_PARTITION_COLUMN_LIST_ERROR error code, 47
ER_PARTITION_CONST_DOMAIN_ERROR error code, 41
ER_PARTITION_ENGINE_DEPRECATED_FOR_TABLE error code, 88
ER_PARTITION_ENTRY_ERROR error code, 36
ER_PARTITION_EXCHANGE_DIFFERENT_OPTION error code, 53
ER_PARTITION_EXCHANGE_FOREIGN_KEY error code, 53
ER_PARTITION_EXCHANGE_PART_TABLE error code, 53
ER_PARTITION_EXCHANGE_TEMP_TABLE error code, 53
ER_PARTITION_FIELDS_TOO_LONG error code, 47
ER_PARTITION_FUNCTION_FAILURE error code, 38
ER_PARTITION_FUNCTION_IS_NOT_ALLOWED error code, 41
ER_PARTITION_FUNC_NOT_ALLOWED_ERROR error code, 36
ER_PARTITION_INSTEAD_OF_SUBPARTITION error code, 53
ER_PARTITION_MAXVALUE_ERROR error code, 35
ER_PARTITION_MERGE_ERROR error code, 41
ER_PARTITION_MGMT_ON_NONPARTITIONED error code, 37
ER_PARTITION_NAME error code, 45
ER_PARTITION_NOT_DEFINED_ERROR error code, 36
ER_PARTITION_NO_TEMPORARY error code, 41
ER_PARTITIONQUIRES_VALUES_ERROR error code, 35
ER_PARTITION_SUBPARTITION_ERROR error code, 35
ER_PARTITION_SUBPART_MIX_ERROR error code, 35
ER_PARTITION_WRONG_NO_PART_ERROR error code, 35

ER_PARTITION_WRONG_NO_SUBPART_ERROR error code, 35
ER_PARTITION_WRONG_VALUES_ERROR error code, 35
ER_PART_STATE_ERROR error code, 38
ER_PASSWD_LENGTH error code, 28
ER_PASSWORD_ANONYMOUS_USER error code, 12
ER_PASSWORD_EXPIRE_ANONYMOUS_USER error code, 69
ER_PASSWORD_FORMAT error code, 61
ER_PASSWORD_NOT_ALLOWED error code, 12
ER_PASSWORD_NO_MATCH error code, 12
ER_PATH_LENGTH error code, 49
ER_PLUGGABLE_PROTOCOL_COMMAND_NOT_SUPPORTED error code, 82
ER_PLUGIN_CANNOT_BE_UNINSTALLED error code, 66
ER_PLUGIN_DELETE_BUILTIN error code, 45
ER_PLUGIN_FAILED_TO_OPEN_TABLE error code, 90
ER_PLUGIN_FAILED_TO_OPEN_TABLES error code, 90
ER_PLUGIN_IS_NOT_LOADED error code, 38
ER_PLUGIN_IS_PERMANENT error code, 50
ER_PLUGIN_NO_INSTALL error code, 52
ER_PLUGIN_NO_UNINSTALL error code, 52
ER_PREVENTS_VARIABLE_WITHOUT_RBR error code, 77
ER_PRIMARY_CANT_HAVE_NULL error code, 15
ER_PROCACCESS_DENIED_ERROR error code, 28
ER_PROC_AUTO_GRANT_FAIL error code, 30
ER_PROC_AUTO_REVOKED_FAIL error code, 30
ER_PS_MANY_PARAM error code, 29
ER_PS_NO_RECURSION error code, 33
ER_QUERY_CACHE_DISABLED error code, 47
ER_QUERY_INTERRUPTED error code, 24
ER_QUERY_ON_FOREIGN_DATA_SOURCE error code, 32
ER_QUERY_ON_MASTER error code, 18
ER_QUERY_TIMEOUT error code, 69
ER_RANGE_NOT_INCREASING_ERROR error code, 36
ER_RBR_NOT_AVAILABLE error code, 41
ER_READY error code, 9
ER_READ_ONLY_MODE error code, 61
ER_READ_ONLY_TRANSACTION error code, 17
ER_RECORD_FILE_FULL error code, 11
ER_REFERENCED_TRG_DOES_NOT_EXIST error code, 68
ER_REGEX_ERROR error code, 13
ER_RELAY_LOG_FAIL error code, 28
ER_RELAY_LOG_INIT error code, 29
ER_REMOVED_SPACES error code, 34
ER_RENAMED_NAME error code, 46
ER_REORG_HASH_ONLY_ON_SAME_NO error code, 37
ER_REORG_NO_PARAM_ERROR error code, 37
ER_REORG_OUTSIDE_RANGE error code, 38
ER_REORG_PARTITION_NOT_EXIST error code, 37
ER_REPLACE_INACCESSIBLE_ROWS error code, 73
ER_REQUIRES_PRIMARY_KEY error code, 15
ER_RESERVED_SYNTAX error code, 29
ER_RESIGNAL_WITHOUT_ACTIVE_HANDLER error code, 46
ER_REVOKE_GRANTS error code, 21
ER_ROW_DOES_NOT_MATCH_GIVEN_PARTITION_SET error code, 54
ER_ROW_DOES_NOT_MATCH_PARTITION error code, 53
ER_ROW_IN_WRONG_PARTITION error code, 64
ER_ROW_IS_REFERENCED error code, 18
ER_ROW_IS_REFERENCED_2 error code, 33
ER_ROW_SINGLE_PARTITION_FIELD_ERROR error code, 47
ER_RPL_INFO_DATA_TOO_LONG error code, 53
ER_RUN_HOOK_ERROR error code, 78
ER SAME_NAME_PARTITION error code, 37
ER SAME_NAME_PARTITION_FIELD error code, 47
ER_SECURE_TRANSPORT_REQUIRED error code, 85
ER_SELECT_REDUCED error code, 20
ER_SERVER_ISNT_AVAILABLE error code, 86
ER_SERVER_IS_IN_SECURE_AUTH_MODE error code, 22
ER_SERVER_OFFLINE_MODE error code, 70
ER_SERVER_SHUTDOWN error code, 7
ER_SESSION_WAS_KILLED error code, 86
ER_SET_CONSTANTS_ONLY error code, 17
ER_SET_ENFORCE_GTID_CONSISTENCY_WARN_WITH_O error code, 80
ER_SET_PASSWORD_AUTH_PLUGIN error code, 50
ER_SET_STATEMENT_CANNOT_INVOKE_FUNCTION error code, 56
ER_SHUTDOWN_COMPLETE error code, 9
ER_SIGNAL_BAD_CONDITION_TYPE error code, 46
ER_SIGNAL_EXCEPTION error code, 46
ER_SIGNAL_NOT_FOUND error code, 46
ER_SIGNAL_WARN error code, 46
ER_SIZE_OVERFLOW_ERROR error code, 38
ER_SKIPPING_LOGGED_TRANSACTION error code, 56
ER_SLAVE_CANT_CREATE_CONVERSION error code, 49
ER_SLAVE_CHANNEL_DELETE error code, 75
ER_SLAVE_CHANNEL_DOES_NOT_EXIST error code, 75
ER_SLAVE_CHANNEL_IO_THREAD_MUST_STOP error code, 69
ER_SLAVE_CHANNEL_MUST_STOP error code, 75
ER_SLAVE_CHANNEL_NAME_INVALID_OR_TOO_LONG error code, 75
ER_SLAVE_CHANNEL_NOT_RUNNING error code, 75
ER_SLAVE_CHANNEL_OPERATION_NOT_ALLOWED error code, 83

ER_SLAVE_CHANNEL_SQL_SKIP_COUNTER error code, 76
ER_SLAVE_CHANNEL_SQL_THREAD_MUST_STOP error code, 76
ER_SLAVE_CHANNEL_WAS_NOT_RUNNING error code, 76
ER_SLAVE_CHANNEL_WAS_RUNNING error code, 75
ER_SLAVE_CONFIGURATION error code, 58
ER_SLAVE_CONVERSION_FAILED error code, 49
ER_SLAVE_CORRUPT_EVENT error code, 44
ER_SLAVE_CREATE_EVENT_FAILURE error code, 43
ER_SLAVE_FATAL_ERROR error code, 43
ER_SLAVE_HAS_MORE_GTIDS_THAN_MASTER error code, 66
ER_SLAVE_HEARTBEAT_FAILURE error code, 45
ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE error code, 45
ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE_MASTER error code, 50
ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE_SLAVE error code, 50
ER_SLAVE_IGNORED_SSL_PARAMS error code, 22
ER_SLAVE_IGNORED_TABLE error code, 19
ER_SLAVE_IGNORE_SERVER_IDS error code, 47
ER_SLAVE INCIDENT error code, 42
ER_SLAVE_IO_THREAD_MUST_STOP error code, 67
ER_SLAVE_MASTER_COM_FAILURE error code, 43
ER_SLAVE_MAX_CHANNELS_EXCEEDED error code, 75
ER_SLAVE_MI_INIT_REPOSITORY error code, 65
ER_SLAVE_MULTIPLE_CHANNELS_CMD error code, 75
ER_SLAVE_MULTIPLE_CHANNELS_HOST_PORT error code, 75
ER_SLAVE_MUST_STOP error code, 17
ER_SLAVE_NEW_CHANNEL_WRONG_REPOSITORY error code, 75
ER_SLAVE_NOT_RUNNING error code, 17
ER_SLAVE_RELAY_LOG_READ_FAILURE error code, 43
ER_SLAVE_RELAY_LOG_WRITE_FAILURE error code, 43
ER_SLAVE_RLI_INIT_REPOSITORY error code, 65
ER_SLAVE_SILENT_RETRY_TRANSACTION error code, 59
ER_SLAVE_SQL_THREAD_MUST_STOP error code, 69
ER_SLAVE_THREAD error code, 17
ER_SLAVE_WAS_NOT_RUNNING error code, 21
ER_SLAVE_WAS_RUNNING error code, 20
ER_SLAVE_WORKER_STOPPED_PREVIOUS_THD_ERRORSQL_MODE_MERGED error code, 82
ER_SQL_MODE_NO_EFFECT error code, 70
ER_SQL_SLAVE_SKIP_COUNTER_NOT_SETTABLE_IN_GTID_M error code, 64
ER_SR_INVALID_CREATION_CTX error code, 43
ER_STACK_OVERRUN error code, 11

ER_STACK_OVERRUN_NEED_MORE error code, 32
ER_STARTUP error code, 30
ER_STD_BAD_ALLOC_ERROR error code, 72
ER_STD_DOMAIN_ERROR error code, 72
ER_STD_INVALID_ARGUMENT error code, 72
ER_STD_LENGTH_ERROR error code, 72
ER_STD_LOGIC_ERROR error code, 72
ER_STD_OUT_OF_RANGE_ERROR error code, 72
ER_STD_OVERFLOW_ERROR error code, 72
ER_STD_RANGE_ERROR error code, 72
ER_STD_RUNTIME_ERROR error code, 72
ER_STD_UNDERFLOW_ERROR error code, 72
ER_STD_UNKNOWN_EXCEPTION error code, 73
ER_STMT_CACHE_FULL error code, 51
ER_STMT_HAS_NO_OPEN_CURSOR error code, 31
ER_STMT_NOT_ALLOWED_IN_SF_OR_TRG error code, 26
ER_STOP_SLAVE_IO_THREAD_TIMEOUT error code, 65
ER_STOP_SLAVE_SQL_THREAD_TIMEOUT error code, 65
ER_STORAGE_ENGINE_NOT_LOADED error code, 67
ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG error code, 49
ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG error code, 40
ER_STORED_FUNCTION_PREVENTS_SWITCH_SQL_LOG error code, 50
ER_SUBPARTITION_ERROR error code, 36
ER_SUBPARTITION_NAME error code, 46
ER_SUBQUERY_NO_1_ROW error code, 20
ER_SYNTAX_ERROR error code, 13
ER_TABLEACCESS_DENIED_ERROR error code, 13
ER_TABLENAME_NOT_ALLOWED_HERE error code, 20
ER_TABLESPACE_AUTO_EXTEND_ERROR error code, 38
ER_TABLESPACE_CANNOT_ENCRYPT error code, 87
ER_TABLESPACE_DISCARDED error code, 60
ER_TABLESPACE_EXISTS error code, 60
ER_TABLESPACE_IS_NOT_EMPTY error code, 80
ER_TABLESPACE_MISSING error code, 60
ER_TABLES_DIFFERENT_METADATA error code, 53
ER_TABLE_CANT_HANDLE_AUTO_INCREMENT error code, 14
ER_TABLE_CANT_HANDLE_BLOB error code, 14
ER_TABLE_CANT_HANDLE_FT error code, 18
ER_TABLE_CANT_HANDLE_SPKEYS error code, 34
ER_TABLE_CORRUPT error code, 66
ER_TABLE_DEF_CHANGED error code, 30
ER_TABLE_EXISTS_ERROR error code, 7
ER_TABLE_HAS_NO_FT error code, 55
ER_TABLE_IN_FK_CHECK error code, 52
ER_TABLE_IN_SYSTEM_TABLESPACE error code, 59
ER_TABLE_MUST_HAVE_COLUMNS error code, 11
ER_TABLE_NAME error code, 45
ER_TABLE_NEEDS_REBUILD error code, 51
ER_TABLE_NEEDS_UPGRADE error code, 34
ER_TABLE_NEEDS_UPG_PART error code, 86
ER_TABLE_NOT_LOCKED error code, 10
ER_TABLE_NOT_LOCKED_FOR_WRITE error code, 10
ER_TABLE_REFERENCED error code, 88
ER_TABLE_SCHEMA_MISMATCH error code, 59
ER_TEMPORARY_NAME error code, 46
ER_TEMP_FILE_WRITE_FAILURE error code, 66
ER_TEMP_TABLE_PREVENTS_SWITCH_OUT_OF_RBR error code, 40
ER_TEXTFILE_NOT_READABLE error code, 9
ER_TOO_BIG_DISPLAYWIDTH error code, 32
ER_TOO_BIG_FIELDLENGTH error code, 8
ER_TOO_BIG_FOR_UNCOMPRESS error code, 21
ER_TOO_BIG_PRECISION error code, 31
ER_TOO_BIG_ROWSIZE error code, 11
ER_TOO_BIG_SCALE error code, 31
ER_TOO_BIG_SELECT error code, 10
ER_TOO_BIG_SET error code, 10
ER_TOO_HIGH_LEVEL_OF_NESTING_FOR_SELECT error code, 35
ER_TOO_LONG_BODY error code, 32
ER_TOO_LONG_FIELD_COMMENT error code, 45
ER_TOO_LONG_IDENT error code, 8
ER_TOO_LONG_INDEX_COMMENT error code, 49
ER_TOO_LONG_KEY error code, 8
ER_TOO_LONG_STRING error code, 14
ER_TOO_LONG_TABLE_COMMENT error code, 45
ER_TOO_LONG_TABLE_PARTITION_COMMENT error code, 58
ER_TOO_MANY_CONCURRENT_TRXS error code, 46
ER_TOO_MANY_FIELDS error code, 11
ER_TOO_MANY_KEYS error code, 8
ER_TOO_MANY_KEY_PARTS error code, 8
ER_TOO_MANY_PARTITIONS_ERROR error code, 36
ER_TOO_MANY_PARTITION_FUNC_FIELDS_ERROR error code, 47
ER_TOO_MANY_ROWS error code, 15
ER_TOO_MANY_TABLES error code, 11
ER_TOO_MANY_USER_CONNECTIONS error code, 17
ER_TOO_MANY_VALUES_ERROR error code, 47
ER_TOO MUCH_AUTO_TIMESTAMP_COLS error code, 23
ER_TRANSACTION_ROLLBACK_DURING_COMMIT error code, 78
ER_TRANS_CACHE_FULL error code, 16
ER_TRG_ALREADY_EXISTS error code, 27
ER_TRG_CANT_CHANGE_ROW error code, 27
ER_TRG_CANT_OPEN_TABLE error code, 43
ER_TRG_CORRUPTED_FILE error code, 43
ER_TRG_DOES_NOT_EXIST error code, 27
ER_TRG_INVALID_CREATION_CTX error code, 43

ER_TRG_IN_WRONG_SCHEMA error code, 32
ER_TRG_NO_CREATION_CTX error code, 43
ER_TRG_NO_DEFINER error code, 33
ER_TRG_NO SUCH_ROW_IN_TRG error code, 27
ER_TRG_ON_VIEW_OR_TEMP_TABLE error code, 27
ER_TRUNCATED_WRONG_VALUE error code, 23
ER_TRUNCATED_WRONG_VALUE_FOR_FIELD error code, 28
ER_TRUNCATE_ILLEGAL_FK error code, 50
ER_UDF_ERROR error code, 89
ER_UDF_EXISTS error code, 12
ER_UDF_NO_PATHS error code, 12
ER_UNDO_RECORD_TOO_BIG error code, 51
ER_UNEXPECTED_EOF error code, 6
ER_UNION_TABLES_IN_DIFFERENT_DIR error code, 18
ER_UNIQUE_KEY_NEED_ALL_FIELDS_IN_PF error code, 37
ER_UNKNOWN_ALTER_ALGORITHM error code, 59
ER_UNKNOWN_ALTER_LOCK error code, 59
ER_UNKNOWN_CHARACTER_SET error code, 11
ER_UNKNOWN_COLLATION error code, 22
ER_UNKNOWN_COM_ERROR error code, 6
ER_UNKNOWN_ERROR error code, 11
ER_UNKNOWN_EXPLAIN_FORMAT error code, 58
ER_UNKNOWN_KEY_CACHE error code, 22
ER_UNKNOWN_LOCALE error code, 46
ER_UNKNOWN_PARTITION error code, 53
ER_UNKNOWN PROCEDURE error code, 11
ER_UNKNOWN_STMT_HANDLER error code, 20
ER_UNKNOWN_STORAGE_ENGINE error code, 23
ER_UNKNOWN_SYSTEM_VARIABLE error code, 16
ER_UNKNOWN_TABLE error code, 11
ER_UNKNOWN_TARGET_BINLOG error code, 28
ER_UNKNOWN_TIME_ZONE error code, 23
ER_UNRESOLVED_HINT_NAME error code, 81
ER_UNSUPPORTED_LOG_ENGINE error code, 42
ER_UNSUPPORTED_ACTION_ON_GENERATED_COLUMN error code, 78
ER_UNSUPPORTED_ALTER_ENCRYPTION_INPLACE error code, 88
ER_UNSUPPORTED_ALTER_INPLACE_ON_VIRTUAL_COLUMN error code, 78
ER_UNSUPPORTED_ALTER_ONLINE_ON_VIRTUAL_COLUMN error code, 87
ER_UNSUPPORTED_BY_REPLICATION_THREAD error code, 73
ER_UNSUPPORTED_ENGINE error code, 52
ER_UNSUPPORTED_EXTENSION error code, 11
ER_UNSUPPORTED_PS error code, 23
ER_UNTIL_COND_IGNORED error code, 22
ER_UNUSED1 error code, 14
ER_UNUSED2 error code, 14
ER_UNUSED3 error code, 14
ER_UNUSED4 error code, 48
ER_UNUSED5 error code, 61
ER_UNUSED6 error code, 63

ER_UPDATE_INFO error code, 12
ER_UPDATE_LOG_DEPRECATED_IGNORED error code, 24
ER_UPDATE_LOG_DEPRECATED_TRANSLATED error code, 24
ER_UPDATE_TABLE_USED error code, 10
ER_UPDATE_WITHOUT_KEY_IN_SAFE_MODE error code, 15
ER_USERNAME error code, 34
ER_USER_ALREADY_EXISTS error code, 85
ER_USER_COLUMN_OLD_LENGTH error code, 88
ER_USER_DOES_NOT_EXIST error code, 85
ER_USER_LIMIT_REACHED error code, 19
ER_USER_LOCK_DEADLOCK error code, 73
ER_USER_LOCK_WRONG_NAME error code, 73
ER_VALUES_IS_NOT_INT_TYPE_ERROR error code, 50
ER_VARIABLE_IS_NOT_STRUCT error code, 22
ER_VARIABLE_IS_READONLY error code, 45
ER_VARIABLE_NOT_SETTABLE_IN_SF_OR_TRIGGER error code, 55
ER_VARIABLE_NOT_SETTABLE_IN_SP error code, 61
ER_VARIABLE_NOT_SETTABLE_IN_TRANSACTION error code, 55
ER_VAR_CANT_BE_READ error code, 19
ER_VIEW_CHECKSUM error code, 29
ER_VIEW_CHECK_FAILED error code, 28
ER_VIEW_DELETE_MERGE_VIEW error code, 29
ER_VIEW_FRM_NO_USER error code, 33
ER_VIEW_INVALID error code, 27
ER_VIEW_INVALID_CREATION_CTX error code, 43
ER_VIEW_MULTIUPDATE error code, 29
ER_VIEW_NONUPD_CHECK error code, 28
ER_VIEW_NO_CREATION_CTX error code, 43
ER_VIEW_NO_EXPLAIN error code, 26
ER_VIEW_NO_INSERT_FIELD_LIST error code, 29
ER_VIEW_OTHER_USER error code, 33
ER_VIEW_PREVENT_UPDATE error code, 33
ER_VIEW_RECURSIVE error code, 34
ER_VIEW_SELECT_CLAUSE error code, 27
ER_VIEW_SELECT_DERIVED error code, 27
ER_VIEW_SELECT_DERIVED_UNUSED error code, 27
ER_VIEW_SELECT_TMPTABLE error code, 27
ER_VIEW_SELECT_VARIABLE error code, 27
ER_VIEW_WRONG_LIST error code, 27
ER_VTOKEN_PLUGIN_TOKEN_MISMATCH error code, 82
ER_VTOKEN_PLUGIN_TOKEN_NOT_FOUND error code, 82
ER_WARNING_NOT_COMPLETE_ROLLBACK error code, 16
ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_CREATED error code, 54
ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_DROPPED error code, 54

ER_WARN_ALLOWED_PACKET_OVERFLOWED error code, 23
ER_WARN_BAD_MAX_EXECUTION_TIME error code, 81
ER_WARN_CANT_DROP_DEFAULT_KEYCACHE error code, 32
ER_WARN_CONFLICTING_HINT error code, 81
ER_WARN_DATA_OUT_OF_RANGE error code, 21
ER_WARN_DEPRECATED_SQLMODE error code, 76
ER_WARN_DEPRECATED_SQLMODE_UNSET error code, 81
ER_WARN_DEPRECATED_SYNTAX error code, 23
ER_WARN_DEPRECATED_SYNTAX_NO_REPLACEMENT error code, 49
ER_WARN_DEPRECATED_SYNTAX_WITH_VER error code, 40
ER_WARN_DEPRECATED_SYSVAR_UPDATE error code, 76
ER_WARN_DEPRECATED_TLS_VERSION error code, 93
ER_WARN_ENGINE_TRANSACTION_ROLLBACK error code, 45
ER_WARN_FIELD_RESOLVED error code, 22
ER_WARN_HOSTNAME_WONT_WORK error code, 22
ER_WARN_INDEX_NOT_APPLICABLE error code, 53
ER_WARN_INVALID_TIMESTAMP error code, 23
ER_WARN_I_S_SKIPPED_TABLE error code, 49
ER_WARN_LEGACY_SYNTAX_CONVERTED error code, 67
ER_WARN_NULL_TO_NOTNULL error code, 21
ER_WARN_ONLY_MASTER_LOG_FILE_NO_POS error code, 69
ER_WARN_ON MODIFYING_GTID_EXECUTED_TABLE error code, 81
ER_WARN_OPEN_TEMP_TABLES_MUST_BE_ZERO error code, 69
ER_WARN_OPTIMIZER_HINT_SYNTAX_ERROR error code, 81
ER_WARN_PURGE_LOG_IN_USE error code, 65
ER_WARN_PURGE_LOG_IS_ACTIVE error code, 65
ER_WARN_QC_RESIZE error code, 22
ER_WARN_TOO_FEW_RECORDS error code, 21
ER_WARN_TOO_MANY_RECORDS error code, 21
ER_WARN_TRIGGER_DOESNT_HAVE_CREATED error code, 68
ER_WARN_UNKNOWN_QB_NAME error code, 81
ER_WARN_UNSUPPORTED_MAX_EXECUTION_TIME error code, 81
ER_WARN_USING_GEOMFROMWKB_TO_SET_SRID error code, 89
ER_WARN_USING_GEOMFROMWKB_TO_SET_SRID error code, 89
ER_WARN_USING_OTHER_HANDLER error code, 21
ER_WARN_VIEW_MERGE error code, 27
ER_WARN_VIEW_WITHOUT_KEY error code, 27
ER_WARN_WRONG_NATIVE_TABLE_STRUCTURE error code, 93
ER_WRITE_SET_EXCEEDS_LIMIT error code, 93
ER_WRONG_ARGUMENTS error code, 17
ER_WRONG_AUTO_KEY error code, 9
ER_WRONG_COLUMN_NAME error code, 14
ER_WRONG_DB_NAME error code, 10
ER_WRONG_EXPR_IN_PARTITION_FUNC_ERROR error code, 35
ER_WRONG_FIELD_SPEC error code, 8
ER_WRONG_FIELD_TERMINATORS error code, 9
ER_WRONG_FIELD_WITH_GROUP error code, 7
ER_WRONG_FIELD_WITH_GROUP_V2 error code, 76
ER_WRONG_FILE_NAME error code, 80
ER_WRONG_FK_DEF error code, 20
ER_WRONG_FK_OPTION_FOR_GENERATED_COLUMN error code, 78
ER_WRONG_GROUP_FIELD error code, 7
ER_WRONG_KEY_COLUMN error code, 15
ER_WRONG_LOCK_OF_SYSTEM_TABLE error code, 32
ER_WRONG_MAGIC error code, 29
ER_WRONG_MRGR_TABLE error code, 15
ER_WRONG_NAME_FOR_CATALOG error code, 22
ER_WRONG_NAME_FOR_INDEX error code, 22
ER_WRONG_NATIVE_TABLE_STRUCTURE error code, 49
ER_WRONG_NUMBER_OF_COLUMNS_IN_SELECT error code, 18
ER_WRONG_OBJECT error code, 26
ER_WRONG_OUTER_JOIN error code, 12
ER_WRONG_PARAMCOUNT_TO_NATIVE_FCT error code, 42
ER_WRONG_PARAMCOUNT_TO_PROCEDURE error code, 11
ER_WRONG_PARAMETERS_TO_NATIVE_FCT error code, 42
ER_WRONG_PARAMETERS_TO_PROCEDURE error code, 11
ER_WRONG_PARAMETERS_TO_STORED_FCT error code, 42
ER_WRONG_PARTITION_NAME error code, 41
ER_WRONG_PERFSHEMA_USAGE error code, 49
ER_WRONG_SIZE_NUMBER error code, 38
ER_WRONG_SPVAR_TYPE_IN_LIMIT error code, 50
ER_WRONG_STRING_LENGTH error code, 34
ER_WRONG_SUB_KEY error code, 9
ER_WRONG_SUM_SELECT error code, 7
ER_WRONG_TABLESPACE_NAME error code, 80
ER_WRONG_TABLE_NAME error code, 10
ER_WRONG_TYPE_COLUMN_VALUE_ERROR error code, 47
ER_WRONG_TYPE_FOR_VAR error code, 19
ER_WRONG_USAGE error code, 18
ER_WRONG_VALUE error code, 38
ER_WRONG_VALUE_COUNT error code, 7
ER_WRONG_VALUE_COUNT_ON_ROW error code, 13
ER_WRONG_VALUE_FOR_TYPE error code, 30

ER_WRONG_VALUE_FOR_VAR error code, 19
ER_WSAS_FAILED error code, 29
ER_XAER_DUPID error code, 32
ER_XAER_INVAL error code, 30
ER_XAER_NOTA error code, 30
ER_XAER_OUTSIDE error code, 30
ER_XAER_RMERR error code, 30
ER_XAER_RMFAIL error code, 30
ER_XA_RBDEADLOCK error code, 44
ER_XA_RBROLLBACK error code, 30
ER_XA_RBTIMEOUT error code, 44
ER_XA_REPLICATION_FILTERS error code, 92
ER_XA_RETRY error code, 89
ER_YES error code, 3
ER_ZLIB_Z_BUF_ERROR error code, 21
ER_ZLIB_Z_DATA_ERROR error code, 21
ER_ZLIB_Z_MEM_ERROR error code, 21

W

WARN_AES_KEY_SIZE error code, 93
WARN_COND_ITEM_TRUNCATED error code, 46
WARN_DATA_TRUNCATED error code, 21
WARN_DEPRECATED_MAXDB_SQL_MODE_FOR_TIMESTAMP
error code, 92
WARN_NAMED_PIPE_ACCESS_EVERYONE error
code, 67
WARN_NON_ASCII_SEPARATOR_NOT_IMPLEMENTED
error code, 46
WARN_NO_MASTER_INFO error code, 44
WARN_ON_BLOCKHOLE_IN_RBR error code, 65
WARN_OPTION_BELOW_LIMIT error code, 51
WARN_OPTION_IGNORED error code, 44
WARN_PLUGIN_BUSY error code, 45
WARN_PLUGIN_DELETE_BUILTIN error code, 44