

# **MySQL 8.3 Error Message Reference**

---

## Abstract

This is the MySQL 8.3 Error Message Reference. It lists all error messages produced by server and client programs in MySQL 8.3. This document accompanies [Error Messages and Common Problems](#), in [MySQL 8.3 Reference Manual](#).

For help with using MySQL, please visit the [MySQL Forums](#), where you can discuss your issues with other MySQL users.

Document generated on: 2024-03-25 (revision: 78168)

---

---

## Table of Contents

Preface and Legal Notices .....	v
1 MySQL Error Reference .....	1
2 Server Error Message Reference .....	3
3 Client Error Message Reference .....	405
4 Global Error Message Reference .....	411
Index .....	419



---

# Preface and Legal Notices

This is the MySQL 8.3 Error Message Reference. It lists all error messages produced by server and client programs in MySQL 8.3.

## Legal Notices

Copyright © 1997, 2024, Oracle and/or its affiliates.

### License Restrictions

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

### Warranty Disclaimer

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

### Restricted Rights Notice

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

### Hazardous Applications Notice

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

### Trademark Notice

Oracle, Java, MySQL, and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC

International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

### **Third-Party Content, Products, and Services Disclaimer**

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

### **Use of This Documentation**

This documentation is NOT distributed under a GPL license. Use of this documentation is subject to the following terms:

You may create a printed copy of this documentation solely for your own personal use. Conversion to other formats is allowed as long as the actual content is not altered or edited in any way. You shall not publish or distribute this documentation in any form or on any media, except if you distribute the documentation in a manner similar to how Oracle disseminates it (that is, electronically for download on a Web site with the software) or on a CD-ROM or similar medium, provided however that the documentation is disseminated together with the software on the same medium. Any other use, such as any dissemination of printed copies or use of this documentation, in whole or in part, in another publication, requires the prior written consent from an authorized representative of Oracle. Oracle and/or its affiliates reserve any and all rights to this documentation not expressly granted above.

## **Documentation Accessibility**

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at

<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

## **Access to Oracle Support for Accessibility**

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit

<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

---

# Chapter 1 MySQL Error Reference

This document provides a reference for the various types of error messages in MySQL:

- Error messages produced only by the server: [Chapter 2, \*Server Error Message Reference\*](#)

On the server side, error messages may occur during the startup and shutdown processes, as a result of issues that occur during SQL statement execution, and so forth.

- The MySQL server writes some error messages to its error log. These indicate issues of interest to database administrators or that require DBA action.
- The server sends other error messages to client programs. These indicate issues pertaining only to a particular client. The MySQL client library takes errors received from the server and makes them available to the host client program.
- Error messages that originate only from within the MySQL client library: [Chapter 3, \*Client Error Message Reference\*](#)

Client-side error messages are generated from within the MySQL client library, usually involving problems communicating with the server.

- Error messages that are shared between the server and the client library: [Chapter 4, \*Global Error Message Reference\*](#)

Some “global” error messages are shared in the sense that they can be produced by the MySQL server or by MySQL client programs.

For a description of the types of error information MySQL provides and how to obtain information about them, see [Error Messages and Common Problems](#), in [MySQL 8.3 Reference Manual](#).





---

## Chapter 2 Server Error Message Reference

The MySQL server writes some error messages to its error log, and sends others to client programs.

Example server-side error messages written to the error log:

```
2018-10-28T13:01:32.735983Z 0 [Note] [MY-010303] [Server] Skipping
generation of SSL certificates as options related to SSL are specified.

2018-10-02T03:20:39.410387Z 768 [ERROR] [MY-010045] [Server] Event Scheduler:
[evtuser@localhost][myschema.e_daily] Unknown database 'mydb'
```

Example server-side error message sent to client programs, as displayed by the `mysql` client:

```
mysql> SELECT * FROM no_such_table;
ERROR 1146 (42S02): Table 'test.no_such_table' doesn't exist
```

Each server error message includes an error code, SQLSTATE value, and message string, as described in [Error Message Sources and Elements](#). These elements are available as described in [Error Information Interfaces](#).

In addition to the errors in the following list, the server can also produce error messages that have error codes in the range from 1 to 999. See [Chapter 4, Global Error Message Reference](#)

- Error number: [1002](#); Symbol: [ER\\_NO](#); SQLSTATE: [HY000](#)

Message: NO

Used in the construction of other messages.

- Error number: [1003](#); Symbol: [ER\\_YES](#); SQLSTATE: [HY000](#)

Message: YES

Used in the construction of other messages.

Extended [EXPLAIN](#) format generates Note messages. [ER\\_YES](#) is used in the [Code](#) column for these messages in subsequent [SHOW WARNINGS](#) output.

- Error number: [1004](#); Symbol: [ER\\_CANT\\_CREATE\\_FILE](#); SQLSTATE: [HY000](#)

Message: Can't create file '%s' (errno: %d - %s)

Occurs for failure to create or copy a file needed for some operation.

Possible causes: Permissions problem for source file; destination file already exists but is not writeable.

- Error number: [1005](#); Symbol: [ER\\_CANT\\_CREATE\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Can't create table '%s' (errno: %d - %s)

[InnoDB](#) reports this error when a table cannot be created. If the error message refers to error 150, table creation failed because a [foreign key constraint](#) was not correctly formed. If the error message refers to error -1, table creation probably failed because the table includes a column name that matched the name of an internal [InnoDB](#) table.

- Error number: [1006](#); Symbol: [ER\\_CANT\\_CREATE\\_DB](#); SQLSTATE: [HY000](#)

Message: Can't create database '%s' (errno: %d - %s)

- Error number: [1007](#); Symbol: [ER\\_DB\\_CREATE\\_EXISTS](#); SQLSTATE: [HY000](#)

Message: Can't create database '%s'; database exists

---

An attempt to create a database failed because the database already exists.

Drop the database first if you really want to replace an existing database, or add an `IF NOT EXISTS` clause to the `CREATE DATABASE` statement if to retain an existing database without having the statement produce an error.

- Error number: `1008`; Symbol: `ER_DB_DROP_EXISTS`; SQLSTATE: `HY000`

Message: Can't drop database '%s'; database doesn't exist

- Error number: `1010`; Symbol: `ER_DB_DROP_RMDIR`; SQLSTATE: `HY000`

Message: Error dropping database (can't rmdir '%s', errno: %d - %s)

- Error number: `1012`; Symbol: `ER_CANT_FIND_SYSTEM_REC`; SQLSTATE: `HY000`

Message: Can't read record in system table

Returned by `InnoDB` for attempts to access `InnoDB INFORMATION_SCHEMA` tables when `InnoDB` is unavailable.

- Error number: `1013`; Symbol: `ER_CANT_GET_STAT`; SQLSTATE: `HY000`

Message: Can't get status of '%s' (errno: %d - %s)

- Error number: `1015`; Symbol: `ER_CANT_LOCK`; SQLSTATE: `HY000`

Message: Can't lock file (errno: %d - %s)

- Error number: `1016`; Symbol: `ER_CANT_OPEN_FILE`; SQLSTATE: `HY000`

Message: Can't open file: '%s' (errno: %d - %s)

`InnoDB` reports this error when the table from the `InnoDB data files` cannot be found.

- Error number: `1017`; Symbol: `ER_FILE_NOT_FOUND`; SQLSTATE: `HY000`

Message: Can't find file: '%s' (errno: %d - %s)

- Error number: `1018`; Symbol: `ER_CANT_READ_DIR`; SQLSTATE: `HY000`

Message: Can't read dir of '%s' (errno: %d - %s)

- Error number: `1020`; Symbol: `ER_CHECKREAD`; SQLSTATE: `HY000`

Message: Record has changed since last read in table '%s'

- Error number: `1022`; Symbol: `ER_DUP_KEY`; SQLSTATE: `23000`

Message: Can't write; duplicate key in table '%s'

- Error number: `1024`; Symbol: `ER_ERROR_ON_READ`; SQLSTATE: `HY000`

Message: Error reading file '%s' (errno: %d - %s)

- Error number: `1025`; Symbol: `ER_ERROR_ON_RENAME`; SQLSTATE: `HY000`

Message: Error on rename of '%s' to '%s' (errno: %d - %s)

- Error number: `1026`; Symbol: `ER_ERROR_ON_WRITE`; SQLSTATE: `HY000`

Message: Error writing file '%s' (errno: %d - %s)

- Error number: `1027`; Symbol: `ER_FILE_USED`; SQLSTATE: `HY000`

---

Message: '%s' is locked against change

- Error number: 1030; Symbol: [ER\\_GET\\_ERRNO](#); SQLSTATE: HY000

Message: Got error %d - '%s' from storage engine

Check the %d value to see what the OS error means. For example, 28 indicates that you have run out of disk space.

- Error number: 1031; Symbol: [ER\\_ILLEGAL HA](#); SQLSTATE: HY000

Message: Table storage engine for '%s' doesn't have this option

- Error number: 1032; Symbol: [ER\\_KEY\\_NOT\\_FOUND](#); SQLSTATE: HY000

Message: Can't find record in '%s'

- Error number: 1033; Symbol: [ER\\_NOT\\_FORM\\_FILE](#); SQLSTATE: HY000

Message: Incorrect information in file: '%s'

- Error number: 1034; Symbol: [ER\\_NOT\\_KEYFILE](#); SQLSTATE: HY000

Message: Incorrect key file for table '%s'; try to repair it

- Error number: 1035; Symbol: [ER\\_OLD\\_KEYFILE](#); SQLSTATE: HY000

Message: Old key file for table '%s'; repair it!

- Error number: 1036; Symbol: [ER\\_OPEN\\_AS\\_READONLY](#); SQLSTATE: HY000

Message: Table '%s' is read only

- Error number: 1037; Symbol: [ER\\_OUTOFMEMORY](#); SQLSTATE: HY001

Message: Out of memory; restart server and try again (needed %d bytes)

- Error number: 1038; Symbol: [ER\\_OUT\\_OF\\_SORTMEMORY](#); SQLSTATE: HY001

Message: Out of sort memory, consider increasing server sort buffer size

- Error number: 1040; Symbol: [ER\\_CON\\_COUNT\\_ERROR](#); SQLSTATE: 08004

Message: Too many connections

- Error number: 1041; Symbol: [ER\\_OUT\\_OF\\_RESOURCES](#); SQLSTATE: HY000

Message: Out of memory; check if mysqld or some other process uses all available memory; if not, you may have to use 'ulimit' to allow mysqld to use more memory or you can add more swap space

- Error number: 1042; Symbol: [ER\\_BAD\\_HOST\\_ERROR](#); SQLSTATE: 08S01

Message: Can't get hostname for your address

- Error number: 1043; Symbol: [ER\\_HANDSHAKE\\_ERROR](#); SQLSTATE: 08S01

Message: Bad handshake

- Error number: 1044; Symbol: [ER\\_DBACCESS\\_DENIED\\_ERROR](#); SQLSTATE: 42000

Message: Access denied for user '%s'@'%s' to database '%s'

- Error number: 1045; Symbol: [ER\\_ACCESS\\_DENIED\\_ERROR](#); SQLSTATE: 28000

---

Message: Access denied for user '%s'@'%s' (using password: %s)

- Error number: 1046; Symbol: [ER\\_NO\\_DB\\_ERROR](#); SQLSTATE: 3D000

Message: No database selected

- Error number: 1047; Symbol: [ER\\_UNKNOWN\\_COM\\_ERROR](#); SQLSTATE: 08S01

Message: Unknown command

- Error number: 1048; Symbol: [ER\\_BAD\\_NULL\\_ERROR](#); SQLSTATE: 23000

Message: Column '%s' cannot be null

- Error number: 1049; Symbol: [ER\\_BAD\\_DB\\_ERROR](#); SQLSTATE: 42000

Message: Unknown database '%s'

- Error number: 1050; Symbol: [ER\\_TABLE\\_EXISTS\\_ERROR](#); SQLSTATE: 42S01

Message: Table '%s' already exists

- Error number: 1051; Symbol: [ER\\_BAD\\_TABLE\\_ERROR](#); SQLSTATE: 42S02

Message: Unknown table '%s'

- Error number: 1052; Symbol: [ER\\_NON\\_UNIQ\\_ERROR](#); SQLSTATE: 23000

Message: Column '%s' in %s is ambiguous

```
%s = column name
%s = location of column (for example, "field list")
```

Likely cause: A column appears in a query without appropriate qualification, such as in a select list or ON clause.

Examples:

```
mysql> SELECT i FROM t INNER JOIN t AS t2;
ERROR 1052 (23000): Column 'i' in field list is ambiguous

mysql> SELECT * FROM t LEFT JOIN t AS t2 ON i = i;
ERROR 1052 (23000): Column 'i' in on clause is ambiguous
```

Resolution:

- Qualify the column with the appropriate table name:

```
mysql> SELECT t2.i FROM t INNER JOIN t AS t2;
```

- Modify the query to avoid the need for qualification:

```
mysql> SELECT * FROM t LEFT JOIN t AS t2 USING (i);
```

- Error number: 1053; Symbol: [ER\\_SERVER\\_SHUTDOWN](#); SQLSTATE: 08S01

Message: Server shutdown in progress

- Error number: 1054; Symbol: [ER\\_BAD\\_FIELD\\_ERROR](#); SQLSTATE: 42S22

Message: Unknown column '%s' in '%s'

- Error number: 1055; Symbol: [ER\\_WRONG\\_FIELD\\_WITH\\_GROUP](#); SQLSTATE: 42000

Message: '%s' isn't in GROUP BY

- 
- Error number: [1056](#); Symbol: [ER\\_WRONG\\_GROUP\\_FIELD](#); SQLSTATE: [42000](#)  
Message: Can't group on '%s'
  - Error number: [1057](#); Symbol: [ER\\_WRONG\\_SUM\\_SELECT](#); SQLSTATE: [42000](#)  
Message: Statement has sum functions and columns in same statement
  - Error number: [1058](#); Symbol: [ER\\_WRONG\\_VALUE\\_COUNT](#); SQLSTATE: [21S01](#)  
Message: Column count doesn't match value count
  - Error number: [1059](#); Symbol: [ER\\_TOO\\_LONG\\_IDENT](#); SQLSTATE: [42000](#)  
Message: Identifier name '%s' is too long
  - Error number: [1060](#); Symbol: [ER\\_DUP\\_FIELDNAME](#); SQLSTATE: [42S21](#)  
Message: Duplicate column name '%s'
  - Error number: [1061](#); Symbol: [ER\\_DUP\\_KEYNAME](#); SQLSTATE: [42000](#)  
Message: Duplicate key name '%s'
  - Error number: [1062](#); Symbol: [ER\\_DUP\\_ENTRY](#); SQLSTATE: [23000](#)  
Message: Duplicate entry '%s' for key %d  
The message returned with this error uses the format string for [ER\\_DUP\\_ENTRY\\_WITH\\_KEY\\_NAME](#).
  - Error number: [1063](#); Symbol: [ER\\_WRONG\\_FIELD\\_SPEC](#); SQLSTATE: [42000](#)  
Message: Incorrect column specifier for column '%s'
  - Error number: [1064](#); Symbol: [ER\\_PARSE\\_ERROR](#); SQLSTATE: [42000](#)  
Message: %s near '%s' at line %d
  - Error number: [1065](#); Symbol: [ER\\_EMPTY\\_QUERY](#); SQLSTATE: [42000](#)  
Message: Query was empty
  - Error number: [1066](#); Symbol: [ER\\_NONUNIQ\\_TABLE](#); SQLSTATE: [42000](#)  
Message: Not unique table/alias: '%s'
  - Error number: [1067](#); Symbol: [ER\\_INVALID\\_DEFAULT](#); SQLSTATE: [42000](#)  
Message: Invalid default value for '%s'
  - Error number: [1068](#); Symbol: [ER\\_MULTIPLE\\_PRI\\_KEY](#); SQLSTATE: [42000](#)  
Message: Multiple primary key defined
  - Error number: [1069](#); Symbol: [ER\\_TOO\\_MANY\\_KEYS](#); SQLSTATE: [42000](#)  
Message: Too many keys specified; max %d keys allowed
  - Error number: [1070](#); Symbol: [ER\\_TOO\\_MANY\\_KEY\\_PARTS](#); SQLSTATE: [42000](#)  
Message: Too many key parts specified; max %d parts allowed
  - Error number: [1071](#); Symbol: [ER\\_TOO\\_LONG\\_KEY](#); SQLSTATE: [42000](#)  
Message: Specified key was too long; max key length is %d bytes

- 
- Error number: 1072; Symbol: [ER\\_KEY\\_COLUMN\\_DOES\\_NOT\\_EXISTS](#); SQLSTATE: 42000  
Message: Key column '%s' doesn't exist in table
  - Error number: 1073; Symbol: [ER\\_BLOB\\_USED\\_AS\\_KEY](#); SQLSTATE: 42000  
Message: BLOB column '%s' can't be used in key specification with the used table type
  - Error number: 1074; Symbol: [ER\\_TOO\\_BIG\\_FIELDLENGTH](#); SQLSTATE: 42000  
Message: Column length too big for column '%s' (max = %lu); use BLOB or TEXT instead
  - Error number: 1075; Symbol: [ER\\_WRONG\\_AUTO\\_KEY](#); SQLSTATE: 42000  
Message: Incorrect table definition; there can be only one auto column and it must be defined as a key
  - Error number: 1076; Symbol: [ER\\_READY](#); SQLSTATE: HY000  
Message: %s: ready for connections. Version: '%s' socket: '%s' port: %d
  - Error number: 1079; Symbol: [ER\\_SHUTDOWN\\_COMPLETE](#); SQLSTATE: HY000  
Message: %s: Shutdown complete
  - Error number: 1080; Symbol: [ER\\_FORCING\\_CLOSE](#); SQLSTATE: 08S01  
Message: %s: Forcing close of thread %ld user: '%s'
  - Error number: 1081; Symbol: [ER\\_IPSOCK\\_ERROR](#); SQLSTATE: 08S01  
Message: Can't create IP socket
  - Error number: 1082; Symbol: [ER\\_NO\\_SUCH\\_INDEX](#); SQLSTATE: 42S12  
Message: Table '%s' has no index like the one used in CREATE INDEX; recreate the table
  - Error number: 1083; Symbol: [ER\\_WRONG\\_FIELD\\_TERMINATORS](#); SQLSTATE: 42000  
Message: Field separator argument is not what is expected; check the manual
  - Error number: 1084; Symbol: [ER\\_BLOBS\\_AND\\_NO\\_TERMINATED](#); SQLSTATE: 42000  
Message: You can't use fixed rowlength with BLOBs; please use 'fields terminated by'
  - Error number: 1085; Symbol: [ER\\_TEXTFILE\\_NOT\\_READABLE](#); SQLSTATE: HY000  
Message: The file '%s' must be in the database directory or be readable by all
  - Error number: 1086; Symbol: [ER\\_FILE\\_EXISTS\\_ERROR](#); SQLSTATE: HY000  
Message: File '%s' already exists
  - Error number: 1087; Symbol: [ER\\_LOAD\\_INFO](#); SQLSTATE: HY000  
Message: Records: %ld Deleted: %ld Skipped: %ld Warnings: %ld
  - Error number: 1088; Symbol: [ER\\_ALTER\\_INFO](#); SQLSTATE: HY000  
Message: Records: %ld Duplicates: %ld
  - Error number: 1089; Symbol: [ER\\_WRONG\\_SUB\\_KEY](#); SQLSTATE: HY000  
Message: Incorrect prefix key; the used key part isn't a string, the used length is longer than the key part, or the storage engine doesn't support unique prefix keys

- 
- Error number: 1090; Symbol: [ER\\_CANT\\_REMOVE\\_ALL\\_FIELDS](#); SQLSTATE: 42000  
Message: You can't delete all columns with ALTER TABLE; use DROP TABLE instead
  - Error number: 1091; Symbol: [ER\\_CANT\\_DROP\\_FIELD\\_OR\\_KEY](#); SQLSTATE: 42000  
Message: Can't DROP '%s'; check that column/key exists
  - Error number: 1092; Symbol: [ER\\_INSERT\\_INFO](#); SQLSTATE: HY000  
Message: Records: %ld Duplicates: %ld Warnings: %ld
  - Error number: 1093; Symbol: [ER\\_UPDATE\\_TABLE\\_USED](#); SQLSTATE: HY000  
Message: You can't specify target table '%s' for update in FROM clause  
  
This error occurs for attempts to select from and modify the same table within a single statement. If the select attempt occurs within a derived table, you can avoid this error by setting the [derived\\_merge](#) flag of the [optimizer\\_switch](#) system variable to force the subquery to be materialized into a temporary table, which effectively causes it to be a different table from the one modified. See [Optimizing Derived Tables, View References, and Common Table Expressions with Merging or Materialization](#).
  - Error number: 1094; Symbol: [ER\\_NO\\_SUCH\\_THREAD](#); SQLSTATE: HY000  
Message: Unknown thread id: %lu
  - Error number: 1095; Symbol: [ER\\_KILL\\_DENIED\\_ERROR](#); SQLSTATE: HY000  
Message: You are not owner of thread %lu
  - Error number: 1096; Symbol: [ER\\_NO\\_TABLES\\_USED](#); SQLSTATE: HY000  
Message: No tables used
  - Error number: 1097; Symbol: [ER\\_TOO\\_BIG\\_SET](#); SQLSTATE: HY000  
Message: Too many strings for column %s and SET
  - Error number: 1098; Symbol: [ER\\_NO\\_UNIQUE\\_LOGFILE](#); SQLSTATE: HY000  
Message: Can't generate a unique log-filename %s.(1-999)
  - Error number: 1099; Symbol: [ER\\_TABLE\\_NOT\\_LOCKED\\_FOR\\_WRITE](#); SQLSTATE: HY000  
Message: Table '%s' was locked with a READ lock and can't be updated
  - Error number: 1100; Symbol: [ER\\_TABLE\\_NOT\\_LOCKED](#); SQLSTATE: HY000  
Message: Table '%s' was not locked with LOCK TABLES
  - Error number: 1101; Symbol: [ER\\_BLOB\\_CANT\\_HAVE\\_DEFAULT](#); SQLSTATE: 42000  
Message: BLOB, TEXT, GEOMETRY or JSON column '%s' can't have a default value
  - Error number: 1102; Symbol: [ER\\_WRONG\\_DB\\_NAME](#); SQLSTATE: 42000  
Message: Incorrect database name '%s'
  - Error number: 1103; Symbol: [ER\\_WRONG\\_TABLE\\_NAME](#); SQLSTATE: 42000  
Message: Incorrect table name '%s'
  - Error number: 1104; Symbol: [ER\\_TOO\\_BIG\\_SELECT](#); SQLSTATE: 42000

---

Message: The SELECT would examine more than MAX\_JOIN\_SIZE rows; check your WHERE and use SET SQL\_BIG\_SELECTS=1 or SET MAX\_JOIN\_SIZE=# if the SELECT is okay

- Error number: 1105; Symbol: ER\_UNKNOWN\_ERROR; SQLSTATE: HY000

Message: Unknown error

- Error number: 1106; Symbol: ER\_UNKNOWN\_PROCEDURE; SQLSTATE: 42000

Message: Unknown procedure '%s'

- Error number: 1107; Symbol: ER\_WRONG\_PARAMCOUNT\_TO\_PROCEDURE; SQLSTATE: 42000

Message: Incorrect parameter count to procedure '%s'

- Error number: 1108; Symbol: ER\_WRONG\_PARAMETERS\_TO\_PROCEDURE; SQLSTATE: HY000

Message: Incorrect parameters to procedure '%s'

- Error number: 1109; Symbol: ER\_UNKNOWN\_TABLE; SQLSTATE: 42S02

Message: Unknown table '%s' in %s

- Error number: 1110; Symbol: ER\_FIELD\_SPECIFIED\_TWICE; SQLSTATE: 42000

Message: Column '%s' specified twice

- Error number: 1111; Symbol: ER\_INVALID\_GROUP\_FUNC\_USE; SQLSTATE: HY000

Message: Invalid use of group function

- Error number: 1112; Symbol: ER\_UNSUPPORTED\_EXTENSION; SQLSTATE: 42000

Message: Table '%s' uses an extension that doesn't exist in this MySQL version

- Error number: 1113; Symbol: ER\_TABLE\_MUST\_HAVE\_COLUMNS; SQLSTATE: 42000

Message: A table must have at least 1 column

- Error number: 1114; Symbol: ER\_RECORD\_FILE\_FULL; SQLSTATE: HY000

Message: The table '%s' is full

InnoDB reports this error when the system tablespace runs out of free space. Reconfigure the system tablespace to add a new data file.

- Error number: 1115; Symbol: ER\_UNKNOWN\_CHARACTER\_SET; SQLSTATE: 42000

Message: Unknown character set: '%s'

- Error number: 1116; Symbol: ER\_TOO\_MANY\_TABLES; SQLSTATE: HY000

Message: Too many tables; MySQL can only use %d tables in a join

- Error number: 1117; Symbol: ER\_TOO\_MANY\_FIELDS; SQLSTATE: HY000

Message: Too many columns

- Error number: 1118; Symbol: ER\_TOO\_BIG\_ROWSIZE; SQLSTATE: 42000

Message: Row size too large. The maximum row size for the used table type, not counting BLOBs, is %ld. This includes storage overhead, check the manual. You have to change some columns to TEXT or BLOBs



- 
- Error number: [1119](#); Symbol: [ER\\_STACK\\_OVERRUN](#); SQLSTATE: [HY000](#)  
Message: Thread stack overrun: Used: %ld of a %ld stack. Use 'mysqld --thread\_stack=#' to specify a bigger stack if needed
  - Error number: [1120](#); Symbol: [ER\\_WRONG\\_OUTER\\_JOIN\\_UNUSED](#); SQLSTATE: [42000](#)  
Message: Cross dependency found in OUTER JOIN; examine your ON conditions
  - Error number: [1121](#); Symbol: [ER\\_NULL\\_COLUMN\\_IN\\_INDEX](#); SQLSTATE: [42000](#)  
Message: Table handler doesn't support NULL in given index. Please change column '%s' to be NOT NULL or use another handler
  - Error number: [1122](#); Symbol: [ER\\_CANT\\_FIND\\_UDF](#); SQLSTATE: [HY000](#)  
Message: Can't load function '%s'
  - Error number: [1123](#); Symbol: [ER\\_CANT\\_INITIALIZE\\_UDF](#); SQLSTATE: [HY000](#)  
Message: Can't initialize function '%s'; %s
  - Error number: [1124](#); Symbol: [ER\\_UDF\\_NO\\_PATHS](#); SQLSTATE: [HY000](#)  
Message: No paths allowed for shared library
  - Error number: [1125](#); Symbol: [ER\\_UDF\\_EXISTS](#); SQLSTATE: [HY000](#)  
Message: Function '%s' already exists
  - Error number: [1126](#); Symbol: [ER\\_CANT\\_OPEN\\_LIBRARY](#); SQLSTATE: [HY000](#)  
Message: Can't open shared library '%s' (errno: %d %s)
  - Error number: [1127](#); Symbol: [ER\\_CANT\\_FIND\\_DL\\_ENTRY](#); SQLSTATE: [HY000](#)  
Message: Can't find symbol '%s' in library
  - Error number: [1128](#); Symbol: [ER\\_FUNCTION\\_NOT\\_DEFINED](#); SQLSTATE: [HY000](#)  
Message: Function '%s' is not defined
  - Error number: [1129](#); Symbol: [ER\\_HOST\\_IS\\_BLOCKED](#); SQLSTATE: [HY000](#)  
Message: Host '%s' is blocked because of many connection errors; unblock with 'mysqladmin flush-hosts'
  - Error number: [1130](#); Symbol: [ER\\_HOST\\_NOT\\_PRIVILEGED](#); SQLSTATE: [HY000](#)  
Message: Host '%s' is not allowed to connect to this MySQL server
  - Error number: [1131](#); Symbol: [ER\\_PASSWORD\\_ANONYMOUS\\_USER](#); SQLSTATE: [42000](#)  
Message: You are using MySQL as an anonymous user and anonymous users are not allowed to change passwords
  - Error number: [1132](#); Symbol: [ER\\_PASSWORD\\_NOT\\_ALLOWED](#); SQLSTATE: [42000](#)  
Message: You must have privileges to update tables in the mysql database to be able to change passwords for others
  - Error number: [1133](#); Symbol: [ER\\_PASSWORD\\_NO\\_MATCH](#); SQLSTATE: [42000](#)  
Message: Can't find any matching row in the user table

- 
- Error number: [1134](#); Symbol: [ER\\_UPDATE\\_INFO](#); SQLSTATE: [HY000](#)  
Message: Rows matched: %ld Changed: %ld Warnings: %ld
  - Error number: [1135](#); Symbol: [ER\\_CANT\\_CREATE\\_THREAD](#); SQLSTATE: [HY000](#)  
Message: Can't create a new thread (errno %d); if you are not out of available memory, you can consult the manual for a possible OS-dependent bug
  - Error number: [1136](#); Symbol: [ER\\_WRONG\\_VALUE\\_COUNT\\_ON\\_ROW](#); SQLSTATE: [21S01](#)  
Message: Column count doesn't match value count at row %ld
  - Error number: [1137](#); Symbol: [ER\\_CANT\\_REOPEN\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Can't reopen table: '%s'
  - Error number: [1138](#); Symbol: [ER\\_INVALID\\_USE\\_OF\\_NULL](#); SQLSTATE: [22004](#)  
Message: Invalid use of NULL value
  - Error number: [1139](#); Symbol: [ER\\_REGEXP\\_ERROR](#); SQLSTATE: [42000](#)  
Message: Got error '%s' from regexp
  - Error number: [1140](#); Symbol: [ER\\_MIX\\_OF\\_GROUP\\_FUNC\\_AND\\_FIELDS](#); SQLSTATE: [42000](#)  
Message: Mixing of GROUP columns (MIN(),MAX(),COUNT(),...) with no GROUP columns is illegal if there is no GROUP BY clause
  - Error number: [1141](#); Symbol: [ER\\_NONEXISTING\\_GRANT](#); SQLSTATE: [42000](#)  
Message: There is no such grant defined for user '%s' on host '%s'
  - Error number: [1142](#); Symbol: [ER\\_TABLEACCESS\\_DENIED\\_ERROR](#); SQLSTATE: [42000](#)  
Message: %s command denied to user '%s'@'%s' for table '%s'
  - Error number: [1143](#); Symbol: [ER\\_COLUMNACCESS\\_DENIED\\_ERROR](#); SQLSTATE: [42000](#)  
Message: %s command denied to user '%s'@'%s' for column '%s' in table '%s'
  - Error number: [1144](#); Symbol: [ER\\_ILLEGAL\\_GRANT\\_FOR\\_TABLE](#); SQLSTATE: [42000](#)  
Message: Illegal GRANT/REVOKE command; please consult the manual to see which privileges can be used
  - Error number: [1145](#); Symbol: [ER\\_GRANT\\_WRONG\\_HOST\\_OR\\_USER](#); SQLSTATE: [42000](#)  
Message: The host or user argument to GRANT is too long
  - Error number: [1146](#); Symbol: [ER\\_NO\\_SUCH\\_TABLE](#); SQLSTATE: [42S02](#)  
Message: Table '%s.%s' doesn't exist
  - Error number: [1147](#); Symbol: [ER\\_NONEXISTING\\_TABLE\\_GRANT](#); SQLSTATE: [42000](#)  
Message: There is no such grant defined for user '%s' on host '%s' on table '%s'
  - Error number: [1148](#); Symbol: [ER\\_NOT\\_ALLOWED\\_COMMAND](#); SQLSTATE: [42000](#)  
Message: The used command is not allowed with this MySQL version
  - Error number: [1149](#); Symbol: [ER\\_SYNTAX\\_ERROR](#); SQLSTATE: [42000](#)

---

Message: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use

- Error number: 1152; Symbol: [ER\\_ABORTING\\_CONNECTION](#); SQLSTATE: 08S01  
Message: Aborted connection %ld to db: '%s' user: '%s' (%s)
- Error number: 1153; Symbol: [ER\\_NET\\_PACKET\\_TOO\\_LARGE](#); SQLSTATE: 08S01  
Message: Got a packet bigger than 'max\_allowed\_packet' bytes
- Error number: 1154; Symbol: [ER\\_NET\\_READ\\_ERROR\\_FROM\\_PIPE](#); SQLSTATE: 08S01  
Message: Got a read error from the connection pipe
- Error number: 1155; Symbol: [ER\\_NET\\_FCNTL\\_ERROR](#); SQLSTATE: 08S01  
Message: Got an error from fcntl()
- Error number: 1156; Symbol: [ER\\_NET\\_PACKETS\\_OUT\\_OF\\_ORDER](#); SQLSTATE: 08S01  
Message: Got packets out of order
- Error number: 1157; Symbol: [ER\\_NET\\_UNCOMPRESS\\_ERROR](#); SQLSTATE: 08S01  
Message: Couldn't uncompress communication packet
- Error number: 1158; Symbol: [ER\\_NET\\_READ\\_ERROR](#); SQLSTATE: 08S01  
Message: Got an error reading communication packets
- Error number: 1159; Symbol: [ER\\_NET\\_READ\\_INTERRUPTED](#); SQLSTATE: 08S01  
Message: Got timeout reading communication packets
- Error number: 1160; Symbol: [ER\\_NET\\_ERROR\\_ON\\_WRITE](#); SQLSTATE: 08S01  
Message: Got an error writing communication packets
- Error number: 1161; Symbol: [ER\\_NET\\_WRITE\\_INTERRUPTED](#); SQLSTATE: 08S01  
Message: Got timeout writing communication packets
- Error number: 1162; Symbol: [ER\\_TOO\\_LONG\\_STRING](#); SQLSTATE: 42000  
Message: Result string is longer than 'max\_allowed\_packet' bytes
- Error number: 1163; Symbol: [ER\\_TABLE\\_CANT\\_HANDLE\\_BLOB](#); SQLSTATE: 42000  
Message: The used table type doesn't support BLOB/TEXT columns
- Error number: 1164; Symbol: [ER\\_TABLE\\_CANT\\_HANDLE\\_AUTO\\_INCREMENT](#); SQLSTATE: 42000  
Message: The used table type doesn't support AUTO\_INCREMENT columns
- Error number: 1166; Symbol: [ER\\_WRONG\\_COLUMN\\_NAME](#); SQLSTATE: 42000  
Message: Incorrect column name '%s'
- Error number: 1167; Symbol: [ER\\_WRONG\\_KEY\\_COLUMN](#); SQLSTATE: 42000  
Message: The used storage engine can't index column '%s'
- Error number: 1168; Symbol: [ER\\_WRONG\\_MRG\\_TABLE](#); SQLSTATE: HY000

---

Message: Unable to open underlying table which is differently defined or of non-MyISAM type or doesn't exist

- Error number: [1169](#); Symbol: [ER\\_DUP\\_UNIQUE](#); SQLSTATE: [23000](#)

Message: Can't write, because of unique constraint, to table '%s'

- Error number: [1170](#); Symbol: [ER\\_BLOB\\_KEY\\_WITHOUT\\_LENGTH](#); SQLSTATE: [42000](#)

Message: BLOB/TEXT column '%s' used in key specification without a key length

- Error number: [1171](#); Symbol: [ER\\_PRIMARY\\_CANT\\_HAVE\\_NULL](#); SQLSTATE: [42000](#)

Message: All parts of a PRIMARY KEY must be NOT NULL; if you need NULL in a key, use UNIQUE instead

- Error number: [1172](#); Symbol: [ER\\_TOO\\_MANY\\_ROWS](#); SQLSTATE: [42000](#)

Message: Result consisted of more than one row

- Error number: [1173](#); Symbol: [ER\\_REQUIRES\\_PRIMARY\\_KEY](#); SQLSTATE: [42000](#)

Message: This table type requires a primary key

- Error number: [1175](#); Symbol: [ER\\_UPDATE\\_WITHOUT\\_KEY\\_IN\\_SAFE\\_MODE](#); SQLSTATE: [HY000](#)

Message: You are using safe update mode and you tried to update a table without a WHERE that uses a KEY column. %s

- Error number: [1176](#); Symbol: [ER\\_KEY\\_DOES\\_NOT\\_EXIST](#); SQLSTATE: [42000](#)

Message: Key '%s' doesn't exist in table '%s'

- Error number: [1177](#); Symbol: [ER\\_CHECK\\_NO\\_SUCH\\_TABLE](#); SQLSTATE: [42000](#)

Message: Can't open table

- Error number: [1178](#); Symbol: [ER\\_CHECK\\_NOT\\_IMPLEMENTED](#); SQLSTATE: [42000](#)

Message: The storage engine for the table doesn't support %s

- Error number: [1179](#); Symbol: [ER\\_CANT\\_DO\\_THIS\\_DURING\\_AN\\_TRANSACTION](#); SQLSTATE: [25000](#)

Message: You are not allowed to execute this command in a transaction

- Error number: [1180](#); Symbol: [ER\\_ERROR\\_DURING\\_COMMIT](#); SQLSTATE: [HY000](#)

Message: Got error %d - '%s' during COMMIT

- Error number: [1181](#); Symbol: [ER\\_ERROR\\_DURING\\_ROLLBACK](#); SQLSTATE: [HY000](#)

Message: Got error %d - '%s' during ROLLBACK

- Error number: [1182](#); Symbol: [ER\\_ERROR\\_DURING\\_FLUSH\\_LOGS](#); SQLSTATE: [HY000](#)

Message: Got error %d during FLUSH\_LOGS

- Error number: [1184](#); Symbol: [ER\\_NEW\\_ABORTING\\_CONNECTION](#); SQLSTATE: [08S01](#)

Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s)

- Error number: [1188](#); Symbol: [ER\\_SOURCE](#); SQLSTATE: [HY000](#)

---

Message: Error from source: '%s'

- Error number: 1189; Symbol: [ER\\_SOURCE\\_NET\\_READ](#); SQLSTATE: 08S01

Message: Net error reading from source

- Error number: 1190; Symbol: [ER\\_SOURCE\\_NET\\_WRITE](#); SQLSTATE: 08S01

Message: Net error writing to source

- Error number: 1191; Symbol: [ER\\_FT\\_MATCHING\\_KEY\\_NOT\\_FOUND](#); SQLSTATE: HY000

Message: Can't find FULLTEXT index matching the column list

- Error number: 1192; Symbol: [ER\\_LOCK\\_OR\\_ACTIVE\\_TRANSACTION](#); SQLSTATE: HY000

Message: Can't execute the given command because you have active locked tables or an active transaction

- Error number: 1193; Symbol: [ER\\_UNKNOWN\\_SYSTEM\\_VARIABLE](#); SQLSTATE: HY000

Message: Unknown system variable '%s'

- Error number: 1194; Symbol: [ER\\_CRASHED\\_ON\\_USAGE](#); SQLSTATE: HY000

Message: Table '%s' is marked as crashed and should be repaired

- Error number: 1195; Symbol: [ER\\_CRASHED\\_ON\\_REPAIR](#); SQLSTATE: HY000

Message: Table '%s' is marked as crashed and last (automatic?) repair failed

- Error number: 1196; Symbol: [ER\\_WARNING\\_NOT\\_COMPLETE\\_ROLLBACK](#); SQLSTATE: HY000

Message: Some non-transactional changed tables couldn't be rolled back

- Error number: 1197; Symbol: [ER\\_TRANS\\_CACHE\\_FULL](#); SQLSTATE: HY000

Message: Multi-statement transaction required more than 'max\_binlog\_cache\_size' bytes of storage; increase this mysqld variable and try again

- Error number: 1199; Symbol: [ER\\_REPLICA\\_NOT\\_RUNNING](#); SQLSTATE: HY000

Message: This operation requires a running replica; configure replica and do START REPLICA

- Error number: 1200; Symbol: [ER\\_BAD\\_REPLICA](#); SQLSTATE: HY000

Message: The server is not configured as replica; fix in config file or with CHANGE REPLICATION SOURCE TO

- Error number: 1201; Symbol: [ER\\_CONNECTION\\_METADATA](#); SQLSTATE: HY000

Message: Could not initialize connection metadata structure; more error messages can be found in the MySQL error log

- Error number: 1202; Symbol: [ER\\_REPLICA\\_THREAD](#); SQLSTATE: HY000

Message: Could not create replica thread; check system resources

- Error number: 1203; Symbol: [ER\\_TOO\\_MANY\\_USER\\_CONNECTIONS](#); SQLSTATE: 42000

Message: User %s already has more than 'max\_user\_connections' active connections

- Error number: 1204; Symbol: [ER\\_SET\\_CONSTANTS\\_ONLY](#); SQLSTATE: HY000

---

Message: You may only use constant expressions with SET

- Error number: 1205; Symbol: `ER_LOCK_WAIT_TIMEOUT`; SQLSTATE: `HY000`

Message: Lock wait timeout exceeded; try restarting transaction

`InnoDB` reports this error when lock wait timeout expires. The statement that waited too long was **rolled back** (not the entire **transaction**). You can increase the value of the `innodb_lock_wait_timeout` configuration option if SQL statements should wait longer for other transactions to complete, or decrease it if too many long-running transactions are causing **locking** problems and reducing **concurrency** on a busy system.

- Error number: 1206; Symbol: `ER_LOCK_TABLE_FULL`; SQLSTATE: `HY000`

Message: The total number of locks exceeds the lock table size

`InnoDB` reports this error when the total number of locks exceeds the amount of memory devoted to managing locks. To avoid this error, increase the value of `innodb_buffer_pool_size`. Within an individual application, a workaround may be to break a large operation into smaller pieces. For example, if the error occurs for a large `INSERT`, perform several smaller `INSERT` operations.

- Error number: 1207; Symbol: `ER_READ_ONLY_TRANSACTION`; SQLSTATE: `25000`

Message: Update locks cannot be acquired during a READ UNCOMMITTED transaction

- Error number: 1210; Symbol: `ER_WRONG_ARGUMENTS`; SQLSTATE: `HY000`

Message: Incorrect arguments to %s

- Error number: 1211; Symbol: `ER_NO_PERMISSION_TO_CREATE_USER`; SQLSTATE: `42000`

Message: '%s'@'%s' is not allowed to create new users

- Error number: 1213; Symbol: `ER_LOCK_DEADLOCK`; SQLSTATE: `40001`

Message: Deadlock found when trying to get lock; try restarting transaction

`InnoDB` reports this error when a **transaction** encounters a **deadlock** and is automatically **rolled back** so that your application can take corrective action. To recover from this error, run all the operations in this transaction again. A deadlock occurs when requests for locks arrive in inconsistent order between transactions. The transaction that was rolled back released all its locks, and the other transaction can now get all the locks it requested. Thus, when you re-run the transaction that was rolled back, it might have to wait for other transactions to complete, but typically the deadlock does not recur. If you encounter frequent deadlocks, make the sequence of locking operations (`LOCK TABLES`, `SELECT . . . FOR UPDATE`, and so on) consistent between the different transactions or applications that experience the issue. See [Deadlocks in InnoDB](#) for details.

- Error number: 1214; Symbol: `ER_TABLE_CANT_HANDLE_FT`; SQLSTATE: `HY000`

Message: The used table type doesn't support FULLTEXT indexes

- Error number: 1215; Symbol: `ER_CANNOT_ADD_FOREIGN`; SQLSTATE: `HY000`

Message: Cannot add foreign key constraint

- Error number: 1216; Symbol: `ER_NO_REFERENCED_ROW`; SQLSTATE: `23000`

Message: Cannot add or update a child row: a foreign key constraint fails

`InnoDB` reports this error when you try to add a row but there is no parent row, and a **foreign key constraint** fails. Add the parent row first.

- 
- Error number: 1217; Symbol: [ER\\_ROW\\_IS\\_REFERENCED](#); SQLSTATE: 23000  
Message: Cannot delete or update a parent row: a foreign key constraint fails  
[InnoDB](#) reports this error when you try to delete a parent row that has children, and a [foreign key constraint](#) fails. Delete the children first.
  - Error number: 1218; Symbol: [ER\\_CONNECT\\_TO\\_SOURCE](#); SQLSTATE: 08S01  
Message: Error connecting to source: %s
  - Error number: 1220; Symbol: [ER\\_ERROR\\_WHEN\\_EXECUTING\\_COMMAND](#); SQLSTATE: HY000  
Message: Error when executing command %s: %s
  - Error number: 1221; Symbol: [ER\\_WRONG\\_USAGE](#); SQLSTATE: HY000  
Message: Incorrect usage of %s and %s
  - Error number: 1222; Symbol: [ER\\_WRONG\\_NUMBER\\_OF\\_COLUMNS\\_IN\\_SELECT](#); SQLSTATE: 21000  
Message: The used SELECT statements have a different number of columns
  - Error number: 1223; Symbol: [ER\\_CANT\\_UPDATE\\_WITH\\_READLOCK](#); SQLSTATE: HY000  
Message: Can't execute the query because you have a conflicting read lock
  - Error number: 1224; Symbol: [ER\\_MIXING\\_NOT\\_ALLOWED](#); SQLSTATE: HY000  
Message: Mixing of transactional and non-transactional tables is disabled
  - Error number: 1225; Symbol: [ER\\_DUP\\_ARGUMENT](#); SQLSTATE: HY000  
Message: Option '%s' used twice in statement
  - Error number: 1226; Symbol: [ER\\_USER\\_LIMIT\\_REACHED](#); SQLSTATE: 42000  
Message: User '%s' has exceeded the '%s' resource (current value: %ld)
  - Error number: 1227; Symbol: [ER\\_SPECIFIC\\_ACCESS\\_DENIED\\_ERROR](#); SQLSTATE: 42000  
Message: Access denied; you need (at least one of) the %s privilege(s) for this operation
  - Error number: 1228; Symbol: [ER\\_LOCAL\\_VARIABLE](#); SQLSTATE: HY000  
Message: Variable '%s' is a SESSION variable and can't be used with SET GLOBAL
  - Error number: 1229; Symbol: [ER\\_GLOBAL\\_VARIABLE](#); SQLSTATE: HY000  
Message: Variable '%s' is a GLOBAL variable and should be set with SET GLOBAL
  - Error number: 1230; Symbol: [ER\\_NO\\_DEFAULT](#); SQLSTATE: 42000  
Message: Variable '%s' doesn't have a default value
  - Error number: 1231; Symbol: [ER\\_WRONG\\_VALUE\\_FOR\\_VAR](#); SQLSTATE: 42000  
Message: Variable '%s' can't be set to the value of '%s'
  - Error number: 1232; Symbol: [ER\\_WRONG\\_TYPE\\_FOR\\_VAR](#); SQLSTATE: 42000  
Message: Incorrect argument type to variable '%s'
  - Error number: 1233; Symbol: [ER\\_VAR\\_CANT\\_BE\\_READ](#); SQLSTATE: HY000

---

Message: Variable '%s' can only be set, not read

- Error number: 1234; Symbol: [ER\\_CANT\\_USE\\_OPTION\\_HERE](#); SQLSTATE: 42000

Message: Incorrect usage/placement of '%s'

- Error number: 1235; Symbol: [ER\\_NOT\\_SUPPORTED\\_YET](#); SQLSTATE: 42000

Message: This version of MySQL doesn't yet support '%s'

- Error number: 1236; Symbol: [ER\\_SOURCE\\_FATAL\\_ERROR\\_READING\\_BINLOG](#); SQLSTATE: HY000

Message: Got fatal error %d from source when reading data from binary log: '%s'

- Error number: 1237; Symbol: [ER\\_REPLICA\\_IGNORED\\_TABLE](#); SQLSTATE: HY000

Message: Replica SQL thread ignored the query because of replicate-\*table rules

- Error number: 1238; Symbol: [ER\\_INCORRECT\\_GLOBAL\\_LOCAL\\_VAR](#); SQLSTATE: HY000

Message: Variable '%s' is a %s variable

- Error number: 1239; Symbol: [ER\\_WRONG\\_FK\\_DEF](#); SQLSTATE: 42000

Message: Incorrect foreign key definition for '%s': %s

- Error number: 1240; Symbol: [ER\\_KEY\\_REF\\_DO\\_NOT\\_MATCH\\_TABLE\\_REF](#); SQLSTATE: HY000

Message: Key reference and table reference don't match

- Error number: 1241; Symbol: [ER\\_OPERAND\\_COLUMNS](#); SQLSTATE: 21000

Message: Operand should contain %d column(s)

- Error number: 1242; Symbol: [ER\\_SUBQUERY\\_NO\\_1\\_ROW](#); SQLSTATE: 21000

Message: Subquery returns more than 1 row

- Error number: 1243; Symbol: [ER\\_UNKNOWN\\_STMT\\_HANDLER](#); SQLSTATE: HY000

Message: Unknown prepared statement handler (%.\*s) given to %s

- Error number: 1244; Symbol: [ER\\_CORRUPT\\_HELP\\_DB](#); SQLSTATE: HY000

Message: Help database is corrupt or does not exist

- Error number: 1246; Symbol: [ER\\_AUTO\\_CONVERT](#); SQLSTATE: HY000

Message: Converting column '%s' from %s to %s

- Error number: 1247; Symbol: [ER\\_ILLEGAL\\_REFERENCE](#); SQLSTATE: 42S22

Message: Reference '%s' not supported (%s)

- Error number: 1248; Symbol: [ER\\_DERIVED\\_MUST\\_HAVE\\_ALIAS](#); SQLSTATE: 42000

Message: Every derived table must have its own alias

- Error number: 1249; Symbol: [ER\\_SELECT\\_REDUCED](#); SQLSTATE: 01000

Message: Select %u was reduced during optimization

- Error number: 1250; Symbol: [ER\\_TABLENAME\\_NOT\\_ALLOWED\\_HERE](#); SQLSTATE: 42000

Message: Table '%s' from one of the SELECTs cannot be used in %s



- 
- Error number: [1251](#); Symbol: [ER\\_NOT\\_SUPPORTEDED\\_AUTH\\_MODE](#); SQLSTATE: [08004](#)  
Message: Client does not support authentication protocol requested by server; consider upgrading MySQL client
  - Error number: [1252](#); Symbol: [ER\\_SPATIAL\\_CANT\\_HAVE\\_NULL](#); SQLSTATE: [42000](#)  
Message: All parts of a SPATIAL index must be NOT NULL
  - Error number: [1253](#); Symbol: [ER\\_COLLATION\\_CHARSET\\_MISMATCH](#); SQLSTATE: [42000](#)  
Message: COLLATION '%s' is not valid for CHARACTER SET '%s'
  - Error number: [1256](#); Symbol: [ER\\_TOO\\_BIG\\_FOR\\_UNCOMPRESS](#); SQLSTATE: [HY000](#)  
Message: Uncompressed data size too large; the maximum size is %d (probably, length of uncompressed data was corrupted)
  - Error number: [1257](#); Symbol: [ER\\_ZLIB\\_Z\\_MEM\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: ZLIB: Not enough memory
  - Error number: [1258](#); Symbol: [ER\\_ZLIB\\_Z\\_BUF\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: ZLIB: Not enough room in the output buffer (probably, length of uncompressed data was corrupted)
  - Error number: [1259](#); Symbol: [ER\\_ZLIB\\_Z\\_DATA\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: ZLIB: Input data corrupted
  - Error number: [1260](#); Symbol: [ER\\_CUT\\_VALUE\\_GROUP\\_CONCAT](#); SQLSTATE: [HY000](#)  
Message: Row %u was cut by GROUP\_CONCAT()
  - Error number: [1261](#); Symbol: [ER\\_WARN\\_TOO\\_FEW\\_RECORDS](#); SQLSTATE: [01000](#)  
Message: Row %ld doesn't contain data for all columns
  - Error number: [1262](#); Symbol: [ER\\_WARN\\_TOO\\_MANY\\_RECORDS](#); SQLSTATE: [01000](#)  
Message: Row %ld was truncated; it contained more data than there were input columns
  - Error number: [1263](#); Symbol: [ER\\_WARN\\_NULL\\_TO\\_NOTNULL](#); SQLSTATE: [22004](#)  
Message: Column set to default value; NULL supplied to NOT NULL column '%s' at row %ld
  - Error number: [1264](#); Symbol: [ER\\_WARN\\_DATA\\_OUT\\_OF\\_RANGE](#); SQLSTATE: [22003](#)  
Message: Out of range value for column '%s' at row %ld
  - Error number: [1265](#); Symbol: [WARN\\_DATA\\_TRUNCATED](#); SQLSTATE: [01000](#)  
Message: Data truncated for column '%s' at row %ld
  - Error number: [1266](#); Symbol: [ER\\_WARN\\_USING\\_OTHER\\_HANDLER](#); SQLSTATE: [HY000](#)  
Message: Using storage engine %s for table '%s'
  - Error number: [1267](#); Symbol: [ER\\_CANT\\_AGGREGATE\\_2COLLATIONS](#); SQLSTATE: [HY000](#)  
Message: Illegal mix of collations (%s,%s) and (%s,%s) for operation '%s'
  - Error number: [1269](#); Symbol: [ER\\_REVOKE\\_GRANTS](#); SQLSTATE: [HY000](#)

---

Message: Can't revoke all privileges for one or more of the requested users

- Error number: [1270](#); Symbol: [ER\\_CANT\\_AGGREGATE\\_3COLLATIONS](#); SQLSTATE: [HY000](#)

Message: Illegal mix of collations (%s,%s), (%s,%s), (%s,%s) for operation '%s'

- Error number: [1271](#); Symbol: [ER\\_CANT\\_AGGREGATE\\_NCOLLATIONS](#); SQLSTATE: [HY000](#)

Message: Illegal mix of collations for operation '%s'

- Error number: [1272](#); Symbol: [ER\\_VARIABLE\\_IS\\_NOT\\_STRUCT](#); SQLSTATE: [HY000](#)

Message: Variable '%s' is not a variable component (can't be used as XXXX.variable\_name)

- Error number: [1273](#); Symbol: [ER\\_UNKNOWN\\_COLLATION](#); SQLSTATE: [HY000](#)

Message: Unknown collation: '%s'

- Error number: [1274](#); Symbol: [ER\\_REPLICA\\_IGNORED\\_SSL\\_PARAMS](#); SQLSTATE: [HY000](#)

Message: SSL parameters in CHANGE REPLICATION SOURCE are ignored because this MySQL replica was compiled without SSL support; they can be used later if MySQL replica with SSL is started

- Error number: [1276](#); Symbol: [ER\\_WARN\\_FIELD\\_RESOLVED](#); SQLSTATE: [HY000](#)

Message: Field or reference '%s%s%s%s%s' of SELECT #%d was resolved in SELECT #%d

- Error number: [1277](#); Symbol: [ER\\_BAD\\_REPLICA\\_UNTIL\\_COND](#); SQLSTATE: [HY000](#)

Message: Incorrect parameter or combination of parameters for START REPLICA UNTIL

- Error number: [1278](#); Symbol: [ER\\_MISSING\\_SKIP\\_REPLICA](#); SQLSTATE: [HY000](#)

Message: It is recommended to use --skip-replica-start when doing step-by-step replication with START REPLICA UNTIL; otherwise, you will get problems if you get an unexpected replica's mysqld restart

- Error number: [1279](#); Symbol: [ER\\_UNTIL\\_COND\\_IGNORED](#); SQLSTATE: [HY000](#)

Message: SQL thread is not to be started so UNTIL options are ignored

- Error number: [1280](#); Symbol: [ER\\_WRONG\\_NAME\\_FOR\\_INDEX](#); SQLSTATE: [42000](#)

Message: Incorrect index name '%s'

- Error number: [1281](#); Symbol: [ER\\_WRONG\\_NAME\\_FOR\\_CATALOG](#); SQLSTATE: [42000](#)

Message: Incorrect catalog name '%s'

- Error number: [1283](#); Symbol: [ER\\_BAD\\_FT\\_COLUMN](#); SQLSTATE: [HY000](#)

Message: Column '%s' cannot be part of FULLTEXT index

- Error number: [1284](#); Symbol: [ER\\_UNKNOWN\\_KEY\\_CACHE](#); SQLSTATE: [HY000](#)

Message: Unknown key cache '%s'

- Error number: [1285](#); Symbol: [ER\\_WARN\\_HOSTNAME\\_WONT\\_WORK](#); SQLSTATE: [HY000](#)

Message: MySQL is started in --skip-name-resolve mode; you must restart it without this switch for this grant to work

- Error number: [1286](#); Symbol: [ER\\_UNKNOWN\\_STORAGE\\_ENGINE](#); SQLSTATE: [42000](#)

---

Message: Unknown storage engine '%s'

- Error number: 1287; Symbol: [ER\\_WARN\\_DEPRECATED\\_SYNTAX](#); SQLSTATE: HY000

Message: '%s' is deprecated and will be removed in a future release. Please use %s instead

- Error number: 1288; Symbol: [ER\\_NON\\_UPDATABLE\\_TABLE](#); SQLSTATE: HY000

Message: The target table %s of the %s is not updatable

- Error number: 1289; Symbol: [ER\\_FEATURE\\_DISABLED](#); SQLSTATE: HY000

Message: The '%s' feature is disabled; you need MySQL built with '%s' to have it working

- Error number: 1290; Symbol: [ER\\_OPTION\\_PREVENTS\\_STATEMENT](#); SQLSTATE: HY000

Message: The MySQL server is running with the %s option so it cannot execute this statement

- Error number: 1291; Symbol: [ER\\_DUPLICATED\\_VALUE\\_IN\\_TYPE](#); SQLSTATE: HY000

Message: Column '%s' has duplicated value '%s' in %s

- Error number: 1292; Symbol: [ER\\_TRUNCATED\\_WRONG\\_VALUE](#); SQLSTATE: 22007

Message: Truncated incorrect %s value: '%s'

- Error number: 1294; Symbol: [ER\\_INVALID\\_ON\\_UPDATE](#); SQLSTATE: HY000

Message: Invalid ON UPDATE clause for '%s' column

- Error number: 1295; Symbol: [ER\\_UNSUPPORTED\\_PS](#); SQLSTATE: HY000

Message: This command is not supported in the prepared statement protocol yet

- Error number: 1296; Symbol: [ER\\_GET\\_ERRMSG](#); SQLSTATE: HY000

Message: Got error %d '%s' from %s

- Error number: 1297; Symbol: [ER\\_GET\\_TEMPORARY\\_ERRMSG](#); SQLSTATE: HY000

Message: Got temporary error %d '%s' from %s

- Error number: 1298; Symbol: [ER\\_UNKNOWN\\_TIME\\_ZONE](#); SQLSTATE: HY000

Message: Unknown or incorrect time zone: '%s'

- Error number: 1299; Symbol: [ER\\_WARN\\_INVALID\\_TIMESTAMP](#); SQLSTATE: HY000

Message: Invalid TIMESTAMP value in column '%s' at row %ld

- Error number: 1300; Symbol: [ER\\_INVALID\\_CHARACTER\\_STRING](#); SQLSTATE: HY000

Message: Invalid %s character string: '%s'

- Error number: 1301; Symbol: [ER\\_WARN\\_ALLOWED\\_PACKET\\_OVERFLOWED](#); SQLSTATE: HY000

Message: Result of %s() was larger than max\_allowed\_packet (%ld) - truncated

- Error number: 1302; Symbol: [ER\\_CONFLICTING\\_DECLARATIONS](#); SQLSTATE: HY000

Message: Conflicting declarations: '%s%s' and '%s%s'

- Error number: 1303; Symbol: [ER\\_SP\\_NO\\_RECURSIVE\\_CREATE](#); SQLSTATE: 2F003

Message: Can't create a %s from within another stored routine

- 
- Error number: 1304; Symbol: ER\_SP\_ALREADY\_EXISTS; SQLSTATE: 42000  
Message: %s %s already exists
  - Error number: 1305; Symbol: ER\_SP\_DOES\_NOT\_EXIST; SQLSTATE: 42000  
Message: %s %s does not exist
  - Error number: 1306; Symbol: ER\_SP\_DROP\_FAILED; SQLSTATE: HY000  
Message: Failed to DROP %s %s
  - Error number: 1307; Symbol: ER\_SP\_STORE\_FAILED; SQLSTATE: HY000  
Message: Failed to CREATE %s %s
  - Error number: 1308; Symbol: ER\_SP\_LILABEL\_MISMATCH; SQLSTATE: 42000  
Message: %s with no matching label: %s
  - Error number: 1309; Symbol: ER\_SP\_LABEL\_REDEFINE; SQLSTATE: 42000  
Message: Redefining label %s
  - Error number: 1310; Symbol: ER\_SP\_LABEL\_MISMATCH; SQLSTATE: 42000  
Message: End-label %s without match
  - Error number: 1311; Symbol: ER\_SP\_UNINIT\_VAR; SQLSTATE: 01000  
Message: Referring to uninitialized variable %s
  - Error number: 1312; Symbol: ER\_SP\_BADSELECT; SQLSTATE: 0A000  
Message: PROCEDURE %s can't return a result set in the given context
  - Error number: 1313; Symbol: ER\_SP\_BADRETURN; SQLSTATE: 42000  
Message: RETURN is only allowed in a FUNCTION
  - Error number: 1314; Symbol: ER\_SP\_BADSTATEMENT; SQLSTATE: 0A000  
Message: %s is not allowed in stored procedures
  - Error number: 1315; Symbol: ER\_UPDATE\_LOG\_DEPRECATED\_IGNORED; SQLSTATE: 42000  
Message: The update log is deprecated and replaced by the binary log; SET SQL\_LOG\_UPDATE has been ignored.
  - Error number: 1316; Symbol: ER\_UPDATE\_LOG\_DEPRECATED\_TRANSLATED; SQLSTATE: 42000  
Message: The update log is deprecated and replaced by the binary log; SET SQL\_LOG\_UPDATE has been translated to SET SQL\_LOG\_BIN.
  - Error number: 1317; Symbol: ER\_QUERY\_INTERRUPTED; SQLSTATE: 70100  
Message: Query execution was interrupted
  - Error number: 1318; Symbol: ER\_SP\_WRONG\_NO\_OF\_ARGS; SQLSTATE: 42000  
Message: Incorrect number of arguments for %s %s; expected %u, got %u
  - Error number: 1319; Symbol: ER\_SP\_COND\_MISMATCH; SQLSTATE: 42000  
Message: Undefined CONDITION: %s

- 
- Error number: 1320; Symbol: ER\_SP\_NORETURN; SQLSTATE: 42000  
Message: No RETURN found in FUNCTION %s
  - Error number: 1321; Symbol: ER\_SP\_NORETURNEND; SQLSTATE: 2F005  
Message: FUNCTION %s ended without RETURN
  - Error number: 1322; Symbol: ER\_SP\_BAD\_CURSOR\_QUERY; SQLSTATE: 42000  
Message: Cursor statement must be a SELECT
  - Error number: 1323; Symbol: ER\_SP\_BAD\_CURSOR\_SELECT; SQLSTATE: 42000  
Message: Cursor SELECT must not have INTO
  - Error number: 1324; Symbol: ER\_SP\_CURSOR\_MISMATCH; SQLSTATE: 42000  
Message: Undefined CURSOR: %s
  - Error number: 1325; Symbol: ER\_SP\_CURSOR\_ALREADY\_OPEN; SQLSTATE: 24000  
Message: Cursor is already open
  - Error number: 1326; Symbol: ER\_SP\_CURSOR\_NOT\_OPEN; SQLSTATE: 24000  
Message: Cursor is not open
  - Error number: 1327; Symbol: ER\_SP\_UNDECLARED\_VAR; SQLSTATE: 42000  
Message: Undeclared variable: %s
  - Error number: 1328; Symbol: ER\_SP\_WRONG\_NO\_OF\_FETCH\_ARGS; SQLSTATE: HY000  
Message: Incorrect number of FETCH variables
  - Error number: 1329; Symbol: ER\_SP\_FETCH\_NO\_DATA; SQLSTATE: 02000  
Message: No data - zero rows fetched, selected, or processed
  - Error number: 1330; Symbol: ER\_SP\_DUP\_PARAM; SQLSTATE: 42000  
Message: Duplicate parameter: %s
  - Error number: 1331; Symbol: ER\_SP\_DUP\_VAR; SQLSTATE: 42000  
Message: Duplicate variable: %s
  - Error number: 1332; Symbol: ER\_SP\_DUP\_COND; SQLSTATE: 42000  
Message: Duplicate condition: %s
  - Error number: 1333; Symbol: ER\_SP\_DUP\_CURS; SQLSTATE: 42000  
Message: Duplicate cursor: %s
  - Error number: 1334; Symbol: ER\_SP\_CANT ALTER; SQLSTATE: HY000  
Message: Failed to ALTER %s %s
  - Error number: 1335; Symbol: ER\_SP\_SUBSELECT\_NYI; SQLSTATE: 0A000  
Message: Subquery value not supported
  - Error number: 1336; Symbol: ER\_STMT\_NOT\_ALLOWED\_IN\_SF\_OR\_TRG; SQLSTATE: 0A000

---

Message: %s is not allowed in stored function or trigger

- Error number: 1337; Symbol: [ER\\_SP\\_VARCOND\\_AFTER\\_CURSHNDLR](#); SQLSTATE: 42000

Message: Variable or condition declaration after cursor or handler declaration

- Error number: 1338; Symbol: [ER\\_SP\\_CURSOR\\_AFTER\\_HANDLER](#); SQLSTATE: 42000

Message: Cursor declaration after handler declaration

- Error number: 1339; Symbol: [ER\\_SP\\_CASE\\_NOT\\_FOUND](#); SQLSTATE: 20000

Message: Case not found for CASE statement

- Error number: 1340; Symbol: [ER\\_FPARSER\\_TOO\\_BIG\\_FILE](#); SQLSTATE: HY000

Message: Configuration file '%s' is too big

- Error number: 1341; Symbol: [ER\\_FPARSER\\_BAD\\_HEADER](#); SQLSTATE: HY000

Message: Malformed file type header in file '%s'

- Error number: 1342; Symbol: [ER\\_FPARSER\\_EOF\\_IN\\_COMMENT](#); SQLSTATE: HY000

Message: Unexpected end of file while parsing comment '%s'

- Error number: 1343; Symbol: [ER\\_FPARSER\\_ERROR\\_IN\\_PARAMETER](#); SQLSTATE: HY000

Message: Error while parsing parameter '%s' (line: '%s')

- Error number: 1344; Symbol: [ER\\_FPARSER\\_EOF\\_IN\\_UNKNOWN\\_PARAMETER](#); SQLSTATE: HY000

Message: Unexpected end of file while skipping unknown parameter '%s'

- Error number: 1345; Symbol: [ER\\_VIEW\\_NO\\_EXPLAIN](#); SQLSTATE: HY000

Message: EXPLAIN/SHOW can not be issued; lacking privileges for underlying table

- Error number: 1347; Symbol: [ER\\_WRONG\\_OBJECT](#); SQLSTATE: HY000

Message: '%s.%s' is not %s

The named object is incorrect for the type of operation attempted on it. It must be an object of the named type. Example: [HANDLER OPEN](#) requires a base table, not a view. It fails if attempted on an [INFORMATION\\_SCHEMA](#) table that is implemented as a view on data dictionary tables.

- Error number: 1348; Symbol: [ER\\_NONUPDATEABLE\\_COLUMN](#); SQLSTATE: HY000

Message: Column '%s' is not updatable

- Error number: 1350; Symbol: [ER\\_VIEW\\_SELECT\\_CLAUSE](#); SQLSTATE: HY000

Message: View's SELECT contains a '%s' clause

- Error number: 1351; Symbol: [ER\\_VIEW\\_SELECT\\_VARIABLE](#); SQLSTATE: HY000

Message: View's SELECT contains a variable or parameter

- Error number: 1352; Symbol: [ER\\_VIEW\\_SELECT\\_TMPTABLE](#); SQLSTATE: HY000

Message: View's SELECT refers to a temporary table '%s'

- Error number: 1353; Symbol: [ER\\_VIEW\\_WRONG\\_LIST](#); SQLSTATE: HY000

---

Message: In definition of view, derived table or common table expression, SELECT list and column names list have different column counts

- Error number: 1354; Symbol: [ER\\_WARN\\_VIEW\\_MERGE](#); SQLSTATE: HY000

Message: View merge algorithm can't be used here for now (assumed undefined algorithm)

- Error number: 1355; Symbol: [ER\\_WARN\\_VIEW\\_WITHOUT\\_KEY](#); SQLSTATE: HY000

Message: View being updated does not have complete key of underlying table in it

- Error number: 1356; Symbol: [ER\\_VIEW\\_INVALID](#); SQLSTATE: HY000

Message: View '%s.%s' references invalid table(s) or column(s) or function(s) or definer/invoker of view lack rights to use them

- Error number: 1357; Symbol: [ER\\_SP\\_NO\\_DROP\\_SP](#); SQLSTATE: HY000

Message: Can't drop or alter a %s from within another stored routine

- Error number: 1359; Symbol: [ER\\_TRG\\_ALREADY\\_EXISTS](#); SQLSTATE: HY000

Message: Trigger already exists

- Error number: 1360; Symbol: [ER\\_TRG\\_DOES\\_NOT\\_EXIST](#); SQLSTATE: HY000

Message: Trigger does not exist

- Error number: 1361; Symbol: [ER\\_TRG\\_ON\\_VIEW\\_OR\\_TEMP\\_TABLE](#); SQLSTATE: HY000

Message: Trigger's '%s' is view or temporary table

- Error number: 1362; Symbol: [ER\\_TRG\\_CANT\\_CHANGE\\_ROW](#); SQLSTATE: HY000

Message: Updating of %s row is not allowed in %strigger

- Error number: 1363; Symbol: [ER\\_TRG\\_NO\\_SUCH\\_ROW\\_IN\\_TRG](#); SQLSTATE: HY000

Message: There is no %s row in %s trigger

- Error number: 1364; Symbol: [ER\\_NO\\_DEFAULT\\_FOR\\_FIELD](#); SQLSTATE: HY000

Message: Field '%s' doesn't have a default value

- Error number: 1365; Symbol: [ER\\_DIVISION\\_BY\\_ZERO](#); SQLSTATE: 22012

Message: Division by 0

- Error number: 1366; Symbol: [ER\\_TRUNCATED\\_WRONG\\_VALUE\\_FOR\\_FIELD](#); SQLSTATE: HY000

Message: Incorrect %s value: '%s' for column '%s' at row %ld

- Error number: 1367; Symbol: [ER\\_ILLEGAL\\_VALUE\\_FOR\\_TYPE](#); SQLSTATE: 22007

Message: Illegal %s '%s' value found during parsing

- Error number: 1368; Symbol: [ER\\_VIEW\\_NONUPD\\_CHECK](#); SQLSTATE: HY000

Message: CHECK OPTION on non-updatable view '%s.%s'

- Error number: 1369; Symbol: [ER\\_VIEW\\_CHECK\\_FAILED](#); SQLSTATE: HY000

Message: CHECK OPTION failed '%s.%s'

- Error number: 1370; Symbol: [ER\\_PROCACCESS\\_DENIED\\_ERROR](#); SQLSTATE: 42000

- 
- Message: %s command denied to user '%s'@'%s' for routine '%s'
- Error number: 1371; Symbol: [ER\\_RELAY\\_LOG\\_FAIL](#); SQLSTATE: HY000  
Message: Failed purging old relay logs: %s
  - Error number: 1373; Symbol: [ER\\_UNKNOWN\\_TARGET\\_BINLOG](#); SQLSTATE: HY000  
Message: Target log not found in binlog index
  - Error number: 1374; Symbol: [ER\\_IO\\_ERR\\_LOG\\_INDEX\\_READ](#); SQLSTATE: HY000  
Message: I/O error reading log index file
  - Error number: 1375; Symbol: [ER\\_BINLOG\\_PURGE\\_PROHIBITED](#); SQLSTATE: HY000  
Message: Server configuration does not permit binlog purge
  - Error number: 1376; Symbol: [ER\\_FSEEK\\_FAIL](#); SQLSTATE: HY000  
Message: Failed on fseek()
  - Error number: 1377; Symbol: [ER\\_BINLOG\\_PURGE\\_FATAL\\_ERR](#); SQLSTATE: HY000  
Message: Fatal error during log purge
  - Error number: 1378; Symbol: [ER\\_LOG\\_IN\\_USE](#); SQLSTATE: HY000  
Message: A purgeable log is in use, will not purge
  - Error number: 1379; Symbol: [ER\\_LOG\\_PURGE\\_UNKNOWN\\_ERR](#); SQLSTATE: HY000  
Message: Unknown error during log purge
  - Error number: 1380; Symbol: [ER\\_RELAY\\_LOG\\_INIT](#); SQLSTATE: HY000  
Message: Failed initializing relay log position: %s
  - Error number: 1381; Symbol: [ER\\_NO\\_BINARY\\_LOGGING](#); SQLSTATE: HY000  
Message: You are not using binary logging
  - Error number: 1382; Symbol: [ER\\_RESERVED\\_SYNTAX](#); SQLSTATE: HY000  
Message: The '%s' syntax is reserved for purposes internal to the MySQL server
  - Error number: 1390; Symbol: [ER\\_PS\\_MANY\\_PARAM](#); SQLSTATE: HY000  
Message: Prepared statement contains too many placeholders
  - Error number: 1391; Symbol: [ER\\_KEY\\_PART\\_0](#); SQLSTATE: HY000  
Message: Key part '%s' length cannot be 0
  - Error number: 1392; Symbol: [ER\\_VIEW\\_CHECKSUM](#); SQLSTATE: HY000  
Message: View text checksum failed
  - Error number: 1393; Symbol: [ER\\_VIEW\\_MULTIUPDATE](#); SQLSTATE: HY000  
Message: Can not modify more than one base table through a join view '%s.%s'
  - Error number: 1394; Symbol: [ER\\_VIEW\\_NO\\_INSERT\\_FIELD\\_LIST](#); SQLSTATE: HY000  
Message: Can not insert into join view '%s.%s' without fields list



- 
- Error number: 1395; Symbol: [ER\\_VIEW\\_DELETE\\_MERGE\\_VIEW](#); SQLSTATE: HY000  
Message: Can not delete from join view '%s.%s'
  - Error number: 1396; Symbol: [ER\\_CANNOT\\_USER](#); SQLSTATE: HY000  
Message: Operation %s failed for %s
  - Error number: 1397; Symbol: [ER\\_XAER\\_NOTA](#); SQLSTATE: XAE04  
Message: XAER\_NOTA: Unknown XID
  - Error number: 1398; Symbol: [ER\\_XAER\\_INVALID](#); SQLSTATE: XAE05  
Message: XAER\_INVALID: Invalid arguments (or unsupported command)
  - Error number: 1399; Symbol: [ER\\_XAER\\_RMFAIL](#); SQLSTATE: XAE07  
Message: XAER\_RMFAIL: The command cannot be executed when global transaction is in the %s state
  - Error number: 1400; Symbol: [ER\\_XAER\\_OUTSIDE](#); SQLSTATE: XAE09  
Message: XAER\_OUTSIDE: Some work is done outside global transaction
  - Error number: 1401; Symbol: [ER\\_XAER\\_RMERR](#); SQLSTATE: XAE03  
Message: XAER\_RMERR: Fatal error occurred in the transaction branch - check your data for consistency
  - Error number: 1402; Symbol: [ER\\_XA\\_RBROLLBACK](#); SQLSTATE: XA100  
Message: XA\_RBROLLBACK: Transaction branch was rolled back
  - Error number: 1403; Symbol: [ER\\_NONEXISTING\\_PROC\\_GRANT](#); SQLSTATE: 42000  
Message: There is no such grant defined for user '%s' on host '%s' on routine '%s'
  - Error number: 1404; Symbol: [ER\\_PROC\\_AUTO\\_GRANT\\_FAIL](#); SQLSTATE: HY000  
Message: Failed to grant EXECUTE and ALTER ROUTINE privileges
  - Error number: 1405; Symbol: [ER\\_PROC\\_AUTO\\_REVOKE\\_FAIL](#); SQLSTATE: HY000  
Message: Failed to revoke all privileges to dropped routine
  - Error number: 1406; Symbol: [ER\\_DATA\\_TOO\\_LONG](#); SQLSTATE: 22001  
Message: Data too long for column '%s' at row %ld
  - Error number: 1407; Symbol: [ER\\_SP\\_BAD\\_SQLSTATE](#); SQLSTATE: 42000  
Message: Bad SQLSTATE: '%s'
  - Error number: 1408; Symbol: [ER\\_STARTUP](#); SQLSTATE: HY000  
Message: %s: ready for connections. Version: '%s' socket: '%s' port: %d %s
  - Error number: 1409; Symbol: [ER\\_LOAD\\_FROM\\_FIXED\\_SIZE\\_ROWS\\_TO\\_VAR](#); SQLSTATE: HY000  
Message: Can't load value from file with fixed size rows to variable
  - Error number: 1410; Symbol: [ER\\_CANT\\_CREATE\\_USER\\_WITH\\_GRANT](#); SQLSTATE: 42000  
Message: You are not allowed to create a user with GRANT

- 
- Error number: 1411; Symbol: [ER\\_WRONG\\_VALUE\\_FOR\\_TYPE](#); SQLSTATE: HY000  
Message: Incorrect %s value: '%s' for function %s
  - Error number: 1412; Symbol: [ER\\_TABLE\\_DEF\\_CHANGED](#); SQLSTATE: HY000  
Message: Table definition has changed, please retry transaction
  - Error number: 1413; Symbol: [ER\\_SP\\_DUP\\_HANDLER](#); SQLSTATE: 42000  
Message: Duplicate handler declared in the same block
  - Error number: 1414; Symbol: [ER\\_SP\\_NOT\\_VAR\\_ARG](#); SQLSTATE: 42000  
Message: OUT or INOUT argument %d for routine %s is not a variable or NEW pseudo-variable in BEFORE trigger
  - Error number: 1415; Symbol: [ER\\_SP\\_NO\\_RESET](#); SQLSTATE: 0A000  
Message: Not allowed to return a result set from a %s
  - Error number: 1416; Symbol: [ER\\_CANT\\_CREATE\\_GEOMETRY\\_OBJECT](#); SQLSTATE: 22003  
Message: Cannot get geometry object from data you send to the GEOMETRY field
  - Error number: 1418; Symbol: [ER\\_BINLOG\\_UNSAFE\\_ROUTINE](#); SQLSTATE: HY000  
Message: This function has none of DETERMINISTIC, NO SQL, or READS SQL DATA in its declaration and binary logging is enabled (you \*might\* want to use the less safe log\_bin\_trust\_function\_creators variable)
  - Error number: 1419; Symbol: [ER\\_BINLOG\\_CREATE\\_ROUTINE\\_NEED\\_SUPER](#); SQLSTATE: HY000  
Message: You do not have the SUPER privilege and binary logging is enabled (you \*might\* want to use the less safe log\_bin\_trust\_function\_creators variable)
  - Error number: 1421; Symbol: [ER\\_STMT\\_HAS\\_NO\\_OPEN\\_CURSOR](#); SQLSTATE: HY000  
Message: The statement (%lu) has no open cursor.
  - Error number: 1422; Symbol: [ER\\_COMMIT\\_NOT\\_ALLOWED\\_IN\\_SF\\_OR\\_TRG](#); SQLSTATE: HY000  
Message: Explicit or implicit commit is not allowed in stored function or trigger.
  - Error number: 1423; Symbol: [ER\\_NO\\_DEFAULT\\_FOR\\_VIEW\\_FIELD](#); SQLSTATE: HY000  
Message: Field of view '%s.%s' underlying table doesn't have a default value
  - Error number: 1424; Symbol: [ER\\_SP\\_NO\\_RECURSION](#); SQLSTATE: HY000  
Message: Recursive stored functions and triggers are not allowed.
  - Error number: 1425; Symbol: [ER\\_TOO\\_BIG\\_SCALE](#); SQLSTATE: 42000  
Message: Too big scale %d specified for column '%s'. Maximum is %lu.
  - Error number: 1426; Symbol: [ER\\_TOO\\_BIG\\_PRECISION](#); SQLSTATE: 42000  
Message: Too-big precision %d specified for '%s'. Maximum is %lu.
  - Error number: 1427; Symbol: [ER\\_M\\_BIGGER\\_THAN\\_D](#); SQLSTATE: 42000  
Message: For float(M,D), double(M,D) or decimal(M,D), M must be >= D (column '%s').
  - Error number: 1428; Symbol: [ER\\_WRONG\\_LOCK\\_OF\\_SYSTEM\\_TABLE](#); SQLSTATE: HY000

---

Message: You can't combine write-locking of system tables with other tables or lock types

- Error number: 1429; Symbol: [ER\\_CONNECT\\_TO\\_FOREIGN\\_DATA\\_SOURCE](#); SQLSTATE: HY000

Message: Unable to connect to foreign data source: %s

- Error number: 1430; Symbol: [ER\\_QUERY\\_ON\\_FOREIGN\\_DATA\\_SOURCE](#); SQLSTATE: HY000

Message: There was a problem processing the query on the foreign data source. Data source error: %s

- Error number: 1431; Symbol: [ER\\_FOREIGN\\_DATA\\_SOURCE\\_DOESNT\\_EXIST](#); SQLSTATE: HY000

Message: The foreign data source you are trying to reference does not exist. Data source error: %s

- Error number: 1432; Symbol: [ER\\_FOREIGN\\_DATA\\_STRING\\_INVALID\\_CANT\\_CREATE](#); SQLSTATE: HY000

Message: Can't create federated table. The data source connection string '%s' is not in the correct format

- Error number: 1433; Symbol: [ER\\_FOREIGN\\_DATA\\_STRING\\_INVALID](#); SQLSTATE: HY000

Message: The data source connection string '%s' is not in the correct format

- Error number: 1435; Symbol: [ER\\_TRG\\_IN\\_WRONG\\_SCHEMA](#); SQLSTATE: HY000

Message: Trigger in wrong schema

- Error number: 1436; Symbol: [ER\\_STACK\\_OVERRUN\\_NEED\\_MORE](#); SQLSTATE: HY000

Message: Thread stack overrun: %ld bytes used of a %ld byte stack, and %ld bytes needed. Use 'mysqld --thread\_stack=#' to specify a bigger stack.

- Error number: 1437; Symbol: [ER\\_TOO\\_LONG\\_BODY](#); SQLSTATE: 42000

Message: Routine body for '%s' is too long

- Error number: 1438; Symbol: [ER\\_WARN\\_CANT\\_DROP\\_DEFAULT\\_KEYCACHE](#); SQLSTATE: HY000

Message: Cannot drop default keycache

- Error number: 1439; Symbol: [ER\\_TOO\\_BIG\\_DISPLAYWIDTH](#); SQLSTATE: 42000

Message: Display width out of range for column '%s' (max = %lu)

- Error number: 1440; Symbol: [ER\\_XAER\\_DUPID](#); SQLSTATE: XAE08

Message: XAER\_DUPID: The XID already exists

- Error number: 1441; Symbol: [ER\\_DATETIME\\_FUNCTION\\_OVERFLOW](#); SQLSTATE: 22008

Message: Datetime function: %s field overflow

- Error number: 1442; Symbol: [ER\\_CANT\\_UPDATE\\_USED\\_TABLE\\_IN\\_SF\\_OR\\_TRG](#); SQLSTATE: HY000

Message: Can't update table '%s' in stored function/trigger because it is already used by statement which invoked this stored function/trigger.

- Error number: 1443; Symbol: [ER\\_VIEW\\_PREVENT\\_UPDATE](#); SQLSTATE: HY000

Message: The definition of table '%s' prevents operation %s on table '%s'.

- 
- Error number: 1444; Symbol: [ER\\_PS\\_NO\\_RECURSION](#); SQLSTATE: HY000  
Message: The prepared statement contains a stored routine call that refers to that same statement. It's not allowed to execute a prepared statement in such a recursive manner
  - Error number: 1445; Symbol: [ER\\_SP\\_CANT\\_SET\\_AUTOCOMMIT](#); SQLSTATE: HY000  
Message: Not allowed to set autocommit from a stored function or trigger
  - Error number: 1447; Symbol: [ER\\_VIEW\\_FRM\\_NO\\_USER](#); SQLSTATE: HY000  
Message: View '%s'.'%s' has no definer information (old table format). Current user is used as definer. Please recreate the view!
  - Error number: 1448; Symbol: [ER\\_VIEW\\_OTHER\\_USER](#); SQLSTATE: HY000  
Message: You need the SUPER privilege for creation view with '%s'@'%s' definer
  - Error number: 1449; Symbol: [ER\\_NO\\_SUCH\\_USER](#); SQLSTATE: HY000  
Message: The user specified as a definer ('%s'@'%s') does not exist
  - Error number: 1450; Symbol: [ER\\_FORBID\\_SCHEMA\\_CHANGE](#); SQLSTATE: HY000  
Message: Changing schema from '%s' to '%s' is not allowed.
  - Error number: 1451; Symbol: [ER\\_ROW\\_IS\\_REFERENCED\\_2](#); SQLSTATE: 23000  
Message: Cannot delete or update a parent row: a foreign key constraint fails (%s)  
[InnoDB](#) reports this error when you try to delete a parent row that has children, and a [foreign key constraint](#) fails. Delete the children first.
  - Error number: 1452; Symbol: [ER\\_NO\\_REFERENCED\\_ROW\\_2](#); SQLSTATE: 23000  
Message: Cannot add or update a child row: a foreign key constraint fails (%s)  
[InnoDB](#) reports this error when you try to add a row but there is no parent row, and a [foreign key constraint](#) fails. Add the parent row first.
  - Error number: 1453; Symbol: [ER\\_SP\\_BAD\\_VAR\\_SHADOW](#); SQLSTATE: 42000  
Message: Variable '%s' must be quoted with `...`, or renamed
  - Error number: 1454; Symbol: [ER\\_TRG\\_NO\\_DEFINER](#); SQLSTATE: HY000  
Message: No definer attribute for trigger '%s'.'%s'. It's disallowed to create trigger without definer.
  - Error number: 1455; Symbol: [ER\\_OLD\\_FILE\\_FORMAT](#); SQLSTATE: HY000  
Message: '%s' has an old format, you should re-create the '%s' object(s)
  - Error number: 1456; Symbol: [ER\\_SP\\_RECURSION\\_LIMIT](#); SQLSTATE: HY000  
Message: Recursive limit %d (as set by the max\_sp\_recursion\_depth variable) was exceeded for routine %s
  - Error number: 1458; Symbol: [ER\\_SP\\_WRONG\\_NAME](#); SQLSTATE: 42000  
Message: Incorrect routine name '%s'
  - Error number: 1459; Symbol: [ER\\_TABLE\\_NEEDS\\_UPGRADE](#); SQLSTATE: HY000  
Message: Table upgrade required. Please do "REPAIR TABLE `'%s`" or dump/reload to fix it!

- 
- Error number: 1460; Symbol: [ER\\_SP\\_NO\\_AGGREGATE](#); SQLSTATE: 42000  
Message: AGGREGATE is not supported for stored functions
  - Error number: 1461; Symbol: [ER\\_MAX\\_PREPARED\\_STMT\\_COUNT\\_REACHED](#); SQLSTATE: 42000  
Message: Can't create more than max\_prepared\_stmt\_count statements (current value: %lu)
  - Error number: 1462; Symbol: [ER\\_VIEW\\_RECURSIVE](#); SQLSTATE: HY000  
Message: `%s`.`%s` contains view recursion
  - Error number: 1463; Symbol: [ER\\_NON\\_GROUPING\\_FIELD\\_USED](#); SQLSTATE: 42000  
Message: Non-grouping field '%s' is used in %s clause
  - Error number: 1464; Symbol: [ER\\_TABLE\\_CANT\\_HANDLE\\_SPKEYS](#); SQLSTATE: HY000  
Message: The used table type doesn't support SPATIAL indexes
  - Error number: 1465; Symbol: [ER\\_NO\\_TRIGGERS\\_ON\\_SYSTEM\\_SCHEMA](#); SQLSTATE: HY000  
Message: Triggers can not be created on system tables
  - Error number: 1466; Symbol: [ER\\_REMOVED\\_SPACES](#); SQLSTATE: HY000  
Message: Leading spaces are removed from name '%s'
  - Error number: 1467; Symbol: [ER\\_AUTOINC\\_READ\\_FAILED](#); SQLSTATE: HY000  
Message: Failed to read auto-increment value from storage engine
  - Error number: 1468; Symbol: [ER\\_USERNAME](#); SQLSTATE: HY000  
Message: user name
  - Error number: 1469; Symbol: [ER\\_HOSTNAME](#); SQLSTATE: HY000  
Message: host name
  - Error number: 1470; Symbol: [ER\\_WRONG\\_STRING\\_LENGTH](#); SQLSTATE: HY000  
Message: String '%s' is too long for %s (should be no longer than %d)
  - Error number: 1471; Symbol: [ER\\_NON\\_INSERTABLE\\_TABLE](#); SQLSTATE: HY000  
Message: The target table %s of the %s is not insertable-into
  - Error number: 1472; Symbol: [ER\\_ADMIN\\_WRONG\\_MRG\\_TABLE](#); SQLSTATE: HY000  
Message: Table '%s' is differently defined or of non-MyISAM type or doesn't exist
  - Error number: 1473; Symbol: [ER\\_TOO\\_HIGH\\_LEVEL\\_OF\\_NESTING\\_FOR\\_SELECT](#); SQLSTATE: HY000  
Message: Too high level of nesting for select
  - Error number: 1474; Symbol: [ER\\_NAME\\_BECOMES\\_EMPTY](#); SQLSTATE: HY000  
Message: Name '%s' has become "
  - Error number: 1475; Symbol: [ER\\_AMBIGUOUS\\_FIELD\\_TERM](#); SQLSTATE: HY000  
Message: First character of the FIELDS TERMINATED string is ambiguous; please use non-optional and non-empty FIELDS ENCLOSED BY

- 
- Error number: 1476; Symbol: [ER\\_FOREIGN\\_SERVER\\_EXISTS](#); SQLSTATE: HY000  
Message: The foreign server, %s, you are trying to create already exists.
  - Error number: 1477; Symbol: [ER\\_FOREIGN\\_SERVER\\_DOESNT\\_EXIST](#); SQLSTATE: HY000  
Message: The foreign server name you are trying to reference does not exist. Data source error: %s
  - Error number: 1478; Symbol: [ER\\_ILLEGAL\\_HA\\_CREATE\\_OPTION](#); SQLSTATE: HY000  
Message: Table storage engine '%s' does not support the create option '%s'
  - Error number: 1479; Symbol: [ER\\_PARTITION\\_REQUIRES\\_VALUES\\_ERROR](#); SQLSTATE: HY000  
Message: Syntax error: %s PARTITIONING requires definition of VALUES %s for each partition
  - Error number: 1480; Symbol: [ER\\_PARTITION\\_WRONG\\_VALUES\\_ERROR](#); SQLSTATE: HY000  
Message: Only %s PARTITIONING can use VALUES %s in partition definition
  - Error number: 1481; Symbol: [ER\\_PARTITION\\_MAXVALUE\\_ERROR](#); SQLSTATE: HY000  
Message: MAXVALUE can only be used in last partition definition
  - Error number: 1484; Symbol: [ER\\_PARTITION\\_WRONG\\_NO\\_PART\\_ERROR](#); SQLSTATE: HY000  
Message: Wrong number of partitions defined, mismatch with previous setting
  - Error number: 1485; Symbol: [ER\\_PARTITION\\_WRONG\\_NO\\_SUBPART\\_ERROR](#); SQLSTATE: HY000  
Message: Wrong number of subpartitions defined, mismatch with previous setting
  - Error number: 1486; Symbol: [ER\\_WRONG\\_EXPR\\_IN\\_PARTITION\\_FUNC\\_ERROR](#); SQLSTATE: HY000  
Message: Constant, random or timezone-dependent expressions in (sub)partitioning function are not allowed
  - Error number: 1488; Symbol: [ER\\_FIELD\\_NOT\\_FOUND\\_PART\\_ERROR](#); SQLSTATE: HY000  
Message: Field in list of fields for partition function not found in table
  - Error number: 1490; Symbol: [ER\\_INCONSISTENT\\_PARTITION\\_INFO\\_ERROR](#); SQLSTATE: HY000  
Message: The partition info in the frm file is not consistent with what can be written into the frm file
  - Error number: 1491; Symbol: [ER\\_PARTITION\\_FUNC\\_NOT\\_ALLOWED\\_ERROR](#); SQLSTATE: HY000  
Message: The %s function returns the wrong type
  - Error number: 1492; Symbol: [ER\\_PARTITIONS\\_MUST\\_BE\\_DEFINED\\_ERROR](#); SQLSTATE: HY000  
Message: For %s partitions each partition must be defined
  - Error number: 1493; Symbol: [ER\\_RANGE\\_NOT\\_INCREASING\\_ERROR](#); SQLSTATE: HY000  
Message: VALUES LESS THAN value must be strictly increasing for each partition
  - Error number: 1494; Symbol: [ER\\_INCONSISTENT\\_TYPE\\_OF\\_FUNCTIONS\\_ERROR](#); SQLSTATE: HY000  
Message: VALUES value must be of same type as partition function
  - Error number: 1495; Symbol: [ER\\_MULTIPLE\\_DEF\\_CONST\\_IN\\_LIST\\_PART\\_ERROR](#); SQLSTATE: HY000

---

Message: Multiple definition of same constant in list partitioning

- Error number: 1496; Symbol: [ER\\_PARTITION\\_ENTRY\\_ERROR](#); SQLSTATE: HY000

Message: Partitioning can not be used stand-alone in query

- Error number: 1497; Symbol: [ER\\_MIX\\_HANDLER\\_ERROR](#); SQLSTATE: HY000

Message: The mix of handlers in the partitions is not allowed in this version of MySQL

- Error number: 1498; Symbol: [ER\\_PARTITION\\_NOT\\_DEFINED\\_ERROR](#); SQLSTATE: HY000

Message: For the partitioned engine it is necessary to define all %s

- Error number: 1499; Symbol: [ER\\_TOO\\_MANY\\_PARTITIONS\\_ERROR](#); SQLSTATE: HY000

Message: Too many partitions (including subpartitions) were defined

- Error number: 1500; Symbol: [ER\\_SUBPARTITION\\_ERROR](#); SQLSTATE: HY000

Message: It is only possible to mix RANGE/LIST partitioning with HASH/KEY partitioning for subpartitioning

- Error number: 1501; Symbol: [ER\\_CANT\\_CREATE\\_HANDLER\\_FILE](#); SQLSTATE: HY000

Message: Failed to create specific handler file

- Error number: 1502; Symbol: [ER\\_BLOB\\_FIELD\\_IN\\_PART\\_FUNC\\_ERROR](#); SQLSTATE: HY000

Message: A BLOB field is not allowed in partition function

- Error number: 1503; Symbol: [ER\\_UNIQUE\\_KEY\\_NEED\\_ALL\\_FIELDS\\_IN\\_PF](#); SQLSTATE: HY000

Message: A %s must include all columns in the table's partitioning function (prefixed columns are not considered).

- Error number: 1504; Symbol: [ER\\_NO\\_PARTS\\_ERROR](#); SQLSTATE: HY000

Message: Number of %s = 0 is not an allowed value

- Error number: 1505; Symbol: [ER\\_PARTITION\\_MGMT\\_ON\\_NONPARTITIONED](#); SQLSTATE: HY000

Message: Partition management on a not partitioned table is not possible

- Error number: 1506; Symbol: [ER\\_FOREIGN\\_KEY\\_ON\\_PARTITIONED](#); SQLSTATE: HY000

Message: Foreign keys are not yet supported in conjunction with partitioning

- Error number: 1507; Symbol: [ER\\_DROP\\_PARTITION\\_NON\\_EXISTENT](#); SQLSTATE: HY000

Message: Error in list of partitions to %s

- Error number: 1508; Symbol: [ER\\_DROP\\_LAST\\_PARTITION](#); SQLSTATE: HY000

Message: Cannot remove all partitions, use DROP TABLE instead

- Error number: 1509; Symbol: [ER\\_COALESCE\\_ONLY\\_ON\\_HASH\\_PARTITION](#); SQLSTATE: HY000

Message: COALESCE PARTITION can only be used on HASH/KEY partitions

- Error number: 1510; Symbol: [ER\\_REORG\\_HASH\\_ONLY\\_ON\\_SAME\\_NO](#); SQLSTATE: HY000

Message: REORGANIZE PARTITION can only be used to reorganize partitions not to change their numbers

- 
- Error number: [1511](#); Symbol: [ER\\_REORG\\_NO\\_PARAM\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: REORGANIZE PARTITION without parameters can only be used on auto-partitioned tables using HASH PARTITIONS
  - Error number: [1512](#); Symbol: [ER\\_ONLY\\_ON\\_RANGE\\_LIST\\_PARTITION](#); SQLSTATE: [HY000](#)  
Message: %s PARTITION can only be used on RANGE/LIST partitions
  - Error number: [1513](#); Symbol: [ER\\_ADD\\_PARTITION\\_SUBPART\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Trying to Add partition(s) with wrong number of subpartitions
  - Error number: [1514](#); Symbol: [ER\\_ADD\\_PARTITION\\_NO\\_NEW\\_PARTITION](#); SQLSTATE: [HY000](#)  
Message: At least one partition must be added
  - Error number: [1515](#); Symbol: [ER\\_COALESCE\\_PARTITION\\_NO\\_PARTITION](#); SQLSTATE: [HY000](#)  
Message: At least one partition must be coalesced
  - Error number: [1516](#); Symbol: [ER\\_REORG\\_PARTITION\\_NOT\\_EXIST](#); SQLSTATE: [HY000](#)  
Message: More partitions to reorganize than there are partitions
  - Error number: [1517](#); Symbol: [ER\\_SAME\\_NAME\\_PARTITION](#); SQLSTATE: [HY000](#)  
Message: Duplicate partition name %s
  - Error number: [1518](#); Symbol: [ER\\_NO\\_BINLOG\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: It is not allowed to shut off binlog on this command
  - Error number: [1519](#); Symbol: [ER\\_CONSECUTIVE\\_REORG\\_PARTITIONS](#); SQLSTATE: [HY000](#)  
Message: When reorganizing a set of partitions they must be in consecutive order
  - Error number: [1520](#); Symbol: [ER\\_REORG\\_OUTSIDE\\_RANGE](#); SQLSTATE: [HY000](#)  
Message: Reorganize of range partitions cannot change total ranges except for last partition where it can extend the range
  - Error number: [1521](#); Symbol: [ER\\_PARTITION\\_FUNCTION\\_FAILURE](#); SQLSTATE: [HY000](#)  
Message: Partition function not supported in this version for this handler
  - Error number: [1523](#); Symbol: [ER\\_LIMITED\\_PART\\_RANGE](#); SQLSTATE: [HY000](#)  
Message: The %s handler only supports 32 bit integers in VALUES
  - Error number: [1524](#); Symbol: [ER\\_PLUGIN\\_IS\\_NOT\\_LOADED](#); SQLSTATE: [HY000](#)  
Message: Plugin '%s' is not loaded
  - Error number: [1525](#); Symbol: [ER\\_WRONG\\_VALUE](#); SQLSTATE: [HY000](#)  
Message: Incorrect %s value: '%s'
  - Error number: [1526](#); Symbol: [ER\\_NO\\_PARTITION\\_FOR\\_GIVEN\\_VALUE](#); SQLSTATE: [HY000](#)  
Message: Table has no partition for value %s
  - Error number: [1527](#); Symbol: [ER\\_FILEGROUP\\_OPTION\\_ONLY\\_ONCE](#); SQLSTATE: [HY000](#)  
Message: It is not allowed to specify %s more than once



- 
- Error number: 1528; Symbol: [ER\\_CREATE\\_FILEGROUP\\_FAILED](#); SQLSTATE: HY000  
Message: Failed to create %s
  - Error number: 1529; Symbol: [ER\\_DROP\\_FILEGROUP\\_FAILED](#); SQLSTATE: HY000  
Message: Failed to drop %s
  - Error number: 1530; Symbol: [ER\\_TABLESPACE\\_AUTO\\_EXTEND\\_ERROR](#); SQLSTATE: HY000  
Message: The handler doesn't support autoextend of tablespaces
  - Error number: 1531; Symbol: [ER\\_WRONG\\_SIZE\\_NUMBER](#); SQLSTATE: HY000  
Message: A size parameter was incorrectly specified, either number or on the form 10M
  - Error number: 1532; Symbol: [ER\\_SIZE\\_OVERFLOW\\_ERROR](#); SQLSTATE: HY000  
Message: The size number was correct but we don't allow the digit part to be more than 2 billion
  - Error number: 1533; Symbol: [ER\\_ALTER\\_FILEGROUP\\_FAILED](#); SQLSTATE: HY000  
Message: Failed to alter: %s
  - Error number: 1534; Symbol: [ER\\_BINLOG\\_ROW\\_LOGGING\\_FAILED](#); SQLSTATE: HY000  
Message: Writing one row to the row-based binary log failed
  - Error number: 1537; Symbol: [ER\\_EVENT\\_ALREADY\\_EXISTS](#); SQLSTATE: HY000  
Message: Event '%s' already exists
  - Error number: 1539; Symbol: [ER\\_EVENT\\_DOES\\_NOT\\_EXIST](#); SQLSTATE: HY000  
Message: Unknown event '%s'
  - Error number: 1542; Symbol: [ER\\_EVENT\\_INTERVAL\\_NOT\\_POSITIVE\\_OR\\_TOO\\_BIG](#); SQLSTATE: HY000  
Message: INTERVAL is either not positive or too big
  - Error number: 1543; Symbol: [ER\\_EVENT\\_ENDS\\_BEFORE\\_STARTS](#); SQLSTATE: HY000  
Message: ENDS is either invalid or before STARTS
  - Error number: 1544; Symbol: [ER\\_EVENT\\_EXEC\\_TIME\\_IN\\_THE\\_PAST](#); SQLSTATE: HY000  
Message: Event execution time is in the past. Event has been disabled
  - Error number: 1551; Symbol: [ER\\_EVENT\\_SAME\\_NAME](#); SQLSTATE: HY000  
Message: Same old and new event name
  - Error number: 1553; Symbol: [ER\\_DROP\\_INDEX\\_FK](#); SQLSTATE: HY000  
Message: Cannot drop index '%s': needed in a foreign key constraint

[InnoDB](#) reports this error when you attempt to drop the last index that can enforce a particular referential constraint.

For optimal performance with DML statements, [InnoDB](#) requires an index to exist on [foreign key](#) columns, so that [UPDATE](#) and [DELETE](#) operations on a [parent table](#) can easily check whether corresponding rows exist in the [child table](#). MySQL creates or drops such indexes automatically when needed, as a side-effect of [CREATE TABLE](#), [CREATE INDEX](#), and [ALTER TABLE](#) statements.

---

When you drop an index, [InnoDB](#) checks if the index is used for checking a foreign key constraint. It is still OK to drop the index if there is another index that can be used to enforce the same constraint. [InnoDB](#) prevents you from dropping the last index that can enforce a particular referential constraint.

- Error number: [1554](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_SYNTAX\\_WITH\\_VER](#); SQLSTATE: [HY000](#)  
Message: The syntax '%s' is deprecated and will be removed in MySQL %s. Please use %s instead
- Error number: [1556](#); Symbol: [ER\\_CANT\\_LOCK\\_LOG\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: You can't use locks with log tables.
- Error number: [1557](#); Symbol: [ER\\_FOREIGN\\_DUPLICATE\\_KEY\\_OLD\\_UNUSED](#); SQLSTATE: [23000](#)  
Message: Upholding foreign key constraints for table '%s', entry '%s', key %d would lead to a duplicate entry
- Error number: [1558](#); Symbol: [ER\\_COL\\_COUNT\\_DOESNT\\_MATCH\\_PLEASE\\_UPDATE](#); SQLSTATE: [HY000](#)  
Message: The column count of mysql.%s is wrong. Expected %d, found %d. Created with MySQL %d, now running %d. Please perform the MySQL upgrade procedure.
- Error number: [1560](#); Symbol: [ER\\_STORED\\_FUNCTION\\_PREVENTS\\_SWITCH\\_BINLOG\\_FORMAT](#); SQLSTATE: [HY000](#)  
Message: Cannot change the binary logging format inside a stored function or trigger
- Error number: [1562](#); Symbol: [ER\\_PARTITION\\_NO\\_TEMPORARY](#); SQLSTATE: [HY000](#)  
Message: Cannot create temporary table with partitions
- Error number: [1563](#); Symbol: [ER\\_PARTITION\\_CONST\\_DOMAIN\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Partition constant is out of partition function domain
- Error number: [1564](#); Symbol: [ER\\_PARTITION\\_FUNCTION\\_IS\\_NOT\\_ALLOWED](#); SQLSTATE: [HY000](#)  
Message: This partition function is not allowed
- Error number: [1566](#); Symbol: [ER\\_NULL\\_IN\\_VALUES\\_LESS\\_THAN](#); SQLSTATE: [HY000](#)  
Message: Not allowed to use NULL value in VALUES LESS THAN
- Error number: [1567](#); Symbol: [ER\\_WRONG\\_PARTITION\\_NAME](#); SQLSTATE: [HY000](#)  
Message: Incorrect partition name
- Error number: [1568](#); Symbol: [ER\\_CANT\\_CHANGE\\_TX\\_CHARACTERISTICS](#); SQLSTATE: [25001](#)  
Message: Transaction characteristics can't be changed while a transaction is in progress
- Error number: [1569](#); Symbol: [ER\\_DUP\\_ENTRY\\_AUTOINCREMENT\\_CASE](#); SQLSTATE: [HY000](#)  
Message: ALTER TABLE causes auto\_increment resequencing, resulting in duplicate entry '%s' for key '%s'
- Error number: [1571](#); Symbol: [ER\\_EVENT\\_SET\\_VAR\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Error during starting/stopping of the scheduler. Error code %u
- Error number: [1572](#); Symbol: [ER\\_PARTITION\\_MERGE\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Engine cannot be used in partitioned tables

- 
- Error number: [1575](#); Symbol: [ER\\_BASE64\\_DECODE\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Decoding of base64 string failed
  - Error number: [1576](#); Symbol: [ER\\_EVENT\\_RECURSION\\_FORBIDDEN](#); SQLSTATE: [HY000](#)  
Message: Recursion of EVENT DDL statements is forbidden when body is present
  - Error number: [1578](#); Symbol: [ER\\_ONLY\\_INTEGERS\\_ALLOWED](#); SQLSTATE: [HY000](#)  
Message: Only integers allowed as number here
  - Error number: [1579](#); Symbol: [ER\\_UNSUPPORTED\\_LOG\\_ENGINE](#); SQLSTATE: [HY000](#)  
Message: This storage engine cannot be used for log tables
  - Error number: [1580](#); Symbol: [ER\\_BAD\\_LOG\\_STATEMENT](#); SQLSTATE: [HY000](#)  
Message: You cannot '%s' a log table if logging is enabled
  - Error number: [1581](#); Symbol: [ER\\_CANT\\_RENAME\\_LOG\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Cannot rename '%s'. When logging enabled, rename to/from log table must rename two tables: the log table to an archive table and another table back to '%s'
  - Error number: [1582](#); Symbol: [ER\\_WRONG\\_PARAMCOUNT\\_TO\\_NATIVE\\_FCT](#); SQLSTATE: [42000](#)  
Message: Incorrect parameter count in the call to native function '%s'
  - Error number: [1583](#); Symbol: [ER\\_WRONG\\_PARAMETERS\\_TO\\_NATIVE\\_FCT](#); SQLSTATE: [42000](#)  
Message: Incorrect parameters in the call to native function '%s'
  - Error number: [1584](#); Symbol: [ER\\_WRONG\\_PARAMETERS\\_TO\\_STORED\\_FCT](#); SQLSTATE: [42000](#)  
Message: Incorrect parameters in the call to stored function %s
  - Error number: [1585](#); Symbol: [ER\\_NATIVE\\_FCT\\_NAME\\_COLLISION](#); SQLSTATE: [HY000](#)  
Message: This function '%s' has the same name as a native function
  - Error number: [1586](#); Symbol: [ER\\_DUP\\_ENTRY\\_WITH\\_KEY\\_NAME](#); SQLSTATE: [23000](#)  
Message: Duplicate entry '%s' for key '%s'  
  
The format string for this error is also used with [ER\\_DUP\\_ENTRY](#).
  - Error number: [1587](#); Symbol: [ER\\_BINLOG\\_PURGE\\_EMFILE](#); SQLSTATE: [HY000](#)  
Message: Too many files opened, please execute the command again
  - Error number: [1588](#); Symbol: [ER\\_EVENT\\_CANNOT\\_CREATE\\_IN\\_THE\\_PAST](#); SQLSTATE: [HY000](#)  
Message: Event execution time is in the past and ON COMPLETION NOT PRESERVE is set. The event was dropped immediately after creation.
  - Error number: [1589](#); Symbol: [ER\\_EVENT\\_CANNOT\\_ALTER\\_IN\\_THE\\_PAST](#); SQLSTATE: [HY000](#)  
Message: Event execution time is in the past and ON COMPLETION NOT PRESERVE is set. The event was not changed. Specify a time in the future.
  - Error number: [1591](#); Symbol: [ER\\_NO\\_PARTITION\\_FOR\\_GIVEN\\_VALUE\\_SILENT](#); SQLSTATE: [HY000](#)  
Message: Table has no partition for some existing values

- 
- Error number: [1592](#); Symbol: [ER\\_BINLOG\\_UNSAFE\\_STATEMENT](#); SQLSTATE: [HY000](#)  
Message: Unsafe statement written to the binary log using statement format since BINLOG\_FORMAT = STATEMENT. %s
  - Error number: [1593](#); Symbol: [ER\\_BINLOG\\_FATAL\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Fatal error: %s
  - Error number: [1598](#); Symbol: [ER\\_BINLOG\\_LOGGING\\_IMPOSSIBLE](#); SQLSTATE: [HY000](#)  
Message: Binary logging not possible. Message: %s
  - Error number: [1599](#); Symbol: [ER\\_VIEW\\_NO\\_CREATION\\_CTX](#); SQLSTATE: [HY000](#)  
Message: View `%s`.`%s` has no creation context
  - Error number: [1600](#); Symbol: [ER\\_VIEW\\_INVALID\\_CREATION\\_CTX](#); SQLSTATE: [HY000](#)  
Message: Creation context of view `%s`.`%s` is invalid
  - Error number: [1602](#); Symbol: [ER\\_TRG\\_CORRUPTED\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Corrupted TRG file for table `%s`.`%s`
  - Error number: [1603](#); Symbol: [ER\\_TRG\\_NO\\_CREATION\\_CTX](#); SQLSTATE: [HY000](#)  
Message: Triggers for table `%s`.`%s` have no creation context
  - Error number: [1604](#); Symbol: [ER\\_TRG\\_INVALID\\_CREATION\\_CTX](#); SQLSTATE: [HY000](#)  
Message: Trigger creation context of table `%s`.`%s` is invalid
  - Error number: [1605](#); Symbol: [ER\\_EVENT\\_INVALID\\_CREATION\\_CTX](#); SQLSTATE: [HY000](#)  
Message: Creation context of event `%s`.`%s` is invalid
  - Error number: [1606](#); Symbol: [ER\\_TRG\\_CANT\\_OPEN\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Cannot open table for trigger `%s`.`%s`
  - Error number: [1609](#); Symbol: [ER\\_NO\\_FORMAT\\_DESCRIPTION\\_EVENT\\_BEFORE\\_BINLOG\\_STATEMENT](#); SQLSTATE: [HY000](#)  
Message: The BINLOG statement of type `%s` was not preceded by a format description BINLOG statement.
  - Error number: [1610](#); Symbol: [ER\\_REPLICA\\_CORRUPT\\_EVENT](#); SQLSTATE: [HY000](#)  
Message: Corrupted replication event was detected
  - Error number: [1612](#); Symbol: [ER\\_LOG\\_PURGE\\_NO\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Being purged log %s was not found
  - Error number: [1613](#); Symbol: [ER\\_XA\\_RBTIMEOUT](#); SQLSTATE: [XA106](#)  
Message: XA\_RBTIMEOUT: Transaction branch was rolled back: took too long
  - Error number: [1614](#); Symbol: [ER\\_XA\\_RBDEADLOCK](#); SQLSTATE: [XA102](#)  
Message: XA\_RBDEADLOCK: Transaction branch was rolled back: deadlock was detected
  - Error number: [1615](#); Symbol: [ER\\_NEED\\_REPREPARE](#); SQLSTATE: [HY000](#)

---

Message: Prepared statement needs to be re-prepared

- Error number: 1617; Symbol: [WARN\\_NO\\_CONNECTION\\_METADATA](#); SQLSTATE: HY000

Message: The connection metadata structure does not exist

- Error number: 1618; Symbol: [WARN\\_OPTION\\_IGNORED](#); SQLSTATE: HY000

Message: <%s> option ignored

- Error number: 1619; Symbol: [ER\\_PLUGIN\\_DELETE\\_BUILTIN](#); SQLSTATE: HY000

Message: Built-in plugins cannot be deleted

- Error number: 1620; Symbol: [WARN\\_PLUGIN\\_BUSY](#); SQLSTATE: HY000

Message: Plugin is busy and will be uninstalled on shutdown

- Error number: 1621; Symbol: [ER\\_VARIABLE\\_IS\\_READONLY](#); SQLSTATE: HY000

Message: %s variable '%s' is read-only. Use SET %s to assign the value

- Error number: 1622; Symbol: [ER\\_WARN\\_ENGINE\\_TRANSACTION\\_ROLLBACK](#); SQLSTATE: HY000

Message: Storage engine %s does not support rollback for this statement. Transaction rolled back and must be restarted

- Error number: 1624; Symbol: [ER\\_REPLICA\\_HEARTBEAT\\_VALUE\\_OUT\\_OF\\_RANGE](#); SQLSTATE: HY000

Message: The requested value for the heartbeat period is either negative or exceeds the maximum allowed (%s seconds).

- Error number: 1625; Symbol: [ER\\_NDB\\_REPLICATION\\_SCHEMA\\_ERROR](#); SQLSTATE: HY000

Message: Bad schema for mysql.ndb\_replication table. Message: %s

- Error number: 1626; Symbol: [ER\\_CONFLICT\\_FN\\_PARSE\\_ERROR](#); SQLSTATE: HY000

Message: Error in parsing conflict function. Message: %s

- Error number: 1627; Symbol: [ER\\_EXCEPTIONS\\_WRITE\\_ERROR](#); SQLSTATE: HY000

Message: Write to exceptions table failed. Message: %s

- Error number: 1628; Symbol: [ER\\_TOO\\_LONG\\_TABLE\\_COMMENT](#); SQLSTATE: HY000

Message: Comment for table '%s' is too long (max = %lu)

- Error number: 1629; Symbol: [ER\\_TOO\\_LONG\\_FIELD\\_COMMENT](#); SQLSTATE: HY000

Message: Comment for field '%s' is too long (max = %lu)

- Error number: 1630; Symbol: [ER\\_FUNC\\_INEXISTENT\\_NAME\\_COLLISION](#); SQLSTATE: 42000

Message: FUNCTION %s does not exist. Check the 'Function Name Parsing and Resolution' section in the Reference Manual

- Error number: 1631; Symbol: [ER\\_DATABASE\\_NAME](#); SQLSTATE: HY000

Message: Database

- Error number: 1632; Symbol: [ER\\_TABLE\\_NAME](#); SQLSTATE: HY000

---

Message: Table

- Error number: 1633; Symbol: [ER\\_PARTITION\\_NAME](#); SQLSTATE: HY000

Message: Partition

- Error number: 1634; Symbol: [ER\\_SUBPARTITION\\_NAME](#); SQLSTATE: HY000

Message: Subpartition

- Error number: 1635; Symbol: [ER\\_TEMPORARY\\_NAME](#); SQLSTATE: HY000

Message: Temporary

- Error number: 1636; Symbol: [ER\\_RENAMED\\_NAME](#); SQLSTATE: HY000

Message: Renamed

- Error number: 1637; Symbol: [ER\\_TOO\\_MANY\\_CONCURRENT\\_TRXS](#); SQLSTATE: HY000

Message: Too many active concurrent transactions

- Error number: 1638; Symbol: [WARN\\_NON\\_ASCII\\_SEPARATOR\\_NOT\\_IMPLEMENTED](#); SQLSTATE: HY000

Message: Non-ASCII separator arguments are not fully supported

- Error number: 1639; Symbol: [ER\\_DEBUG\\_SYNC\\_TIMEOUT](#); SQLSTATE: HY000

Message: debug sync point wait timed out

- Error number: 1640; Symbol: [ER\\_DEBUG\\_SYNC\\_HIT\\_LIMIT](#); SQLSTATE: HY000

Message: debug sync point hit limit reached

- Error number: 1641; Symbol: [ER\\_DUP\\_SIGNAL\\_SET](#); SQLSTATE: 42000

Message: Duplicate condition information item '%s'

- Error number: 1642; Symbol: [ER\\_SIGNAL\\_WARN](#); SQLSTATE: 01000

Message: Unhandled user-defined warning condition

- Error number: 1643; Symbol: [ER\\_SIGNAL\\_NOT\\_FOUND](#); SQLSTATE: 02000

Message: Unhandled user-defined not found condition

- Error number: 1644; Symbol: [ER\\_SIGNAL\\_EXCEPTION](#); SQLSTATE: HY000

Message: Unhandled user-defined exception condition

- Error number: 1645; Symbol: [ER\\_RESIGNAL\\_WITHOUT\\_ACTIVE\\_HANDLER](#); SQLSTATE: 0K000

Message: RESIGNAL when handler not active

- Error number: 1646; Symbol: [ER\\_SIGNAL\\_BAD\\_CONDITION\\_TYPE](#); SQLSTATE: HY000

Message: SIGNAL/RESIGNAL can only use a CONDITION defined with SQLSTATE

- Error number: 1647; Symbol: [WARN\\_COND\\_ITEM\\_TRUNCATED](#); SQLSTATE: HY000

Message: Data truncated for condition item '%s'

- Error number: 1648; Symbol: [ER\\_COND\\_ITEM\\_TOO\\_LONG](#); SQLSTATE: HY000

---

Message: Data too long for condition item '%s'

- Error number: 1649; Symbol: [ER\\_UNKNOWN\\_LOCALE](#); SQLSTATE: HY000

Message: Unknown locale: '%s'

- Error number: 1650; Symbol: [ER\\_REPLICA\\_IGNORE\\_SERVER\\_IDS](#); SQLSTATE: HY000

Message: The requested server id %d clashes with the replica startup option --replicate-same-server-id

- Error number: 1652; Symbol: [ER\\_SAME\\_NAME\\_PARTITION\\_FIELD](#); SQLSTATE: HY000

Message: Duplicate partition field name '%s'

- Error number: 1653; Symbol: [ER\\_PARTITION\\_COLUMN\\_LIST\\_ERROR](#); SQLSTATE: HY000

Message: Inconsistency in usage of column lists for partitioning

- Error number: 1654; Symbol: [ER\\_WRONG\\_TYPE\\_COLUMN\\_VALUE\\_ERROR](#); SQLSTATE: HY000

Message: Partition column values of incorrect type

- Error number: 1655; Symbol: [ER\\_TOO\\_MANY\\_PARTITION\\_FUNC\\_FIELDS\\_ERROR](#); SQLSTATE: HY000

Message: Too many fields in '%s'

- Error number: 1656; Symbol: [ER\\_MAXVALUE\\_IN\\_VALUES\\_IN](#); SQLSTATE: HY000

Message: Cannot use MAXVALUE as value in VALUES IN

- Error number: 1657; Symbol: [ER\\_TOO\\_MANY\\_VALUES\\_ERROR](#); SQLSTATE: HY000

Message: Cannot have more than one value for this type of %s partitioning

- Error number: 1658; Symbol: [ER\\_ROW\\_SINGLE\\_PARTITION\\_FIELD\\_ERROR](#); SQLSTATE: HY000

Message: Row expressions in VALUES IN only allowed for multi-field column partitioning

- Error number: 1659; Symbol: [ER\\_FIELD\\_TYPE\\_NOT\\_ALLOWED\\_AS\\_PARTITION\\_FIELD](#); SQLSTATE: HY000

Message: Field '%s' is of a not allowed type for this type of partitioning

- Error number: 1660; Symbol: [ER\\_PARTITION\\_FIELDS\\_TOO\\_LONG](#); SQLSTATE: HY000

Message: The total length of the partitioning fields is too large

- Error number: 1661; Symbol: [ER\\_BINLOG\\_ROW\\_ENGINE\\_AND\\_STMT\\_ENGINE](#); SQLSTATE: HY000

Message: Cannot execute statement: impossible to write to binary log since both row-incapable engines and statement-incapable engines are involved.

- Error number: 1662; Symbol: [ER\\_BINLOG\\_ROW\\_MODE\\_AND\\_STMT\\_ENGINE](#); SQLSTATE: HY000

Message: Cannot execute statement: impossible to write to binary log since BINLOG\_FORMAT = ROW and at least one table uses a storage engine limited to statement-based logging.

- Error number: 1663; Symbol: [ER\\_BINLOG\\_UNSAFE\\_AND\\_STMT\\_ENGINE](#); SQLSTATE: HY000

Message: Cannot execute statement: impossible to write to binary log since statement is unsafe, storage engine is limited to statement-based logging, and BINLOG\_FORMAT = MIXED. %s

- 
- Error number: 1664; Symbol: [ER\\_BINLOG\\_ROW\\_INJECTION\\_AND\\_STMT\\_ENGINE](#); SQLSTATE: HY000  
  
Message: Cannot execute statement: impossible to write to binary log since statement is in row format and at least one table uses a storage engine limited to statement-based logging.
  - Error number: 1665; Symbol: [ER\\_BINLOG\\_STMT\\_MODE\\_AND\\_ROW\\_ENGINE](#); SQLSTATE: HY000  
  
Message: Cannot execute statement: impossible to write to binary log since BINLOG\_FORMAT = STATEMENT and at least one table uses a storage engine limited to row-based logging.%s
  - Error number: 1666; Symbol: [ER\\_BINLOG\\_ROW\\_INJECTION\\_AND\\_STMT\\_MODE](#); SQLSTATE: HY000  
  
Message: Cannot execute statement: impossible to write to binary log since statement is in row format and BINLOG\_FORMAT = STATEMENT.
  - Error number: 1667; Symbol: [ER\\_BINLOG\\_MULTIPLE\\_ENGINES\\_AND\\_SELF\\_LOGGING\\_ENGINE](#); SQLSTATE: HY000  
  
Message: Cannot execute statement: impossible to write to binary log since more than one engine is involved and at least one engine is self-logging.
  - Error number: 1668; Symbol: [ER\\_BINLOG\\_UNSAFE\\_LIMIT](#); SQLSTATE: HY000  
  
Message: The statement is unsafe because it uses a LIMIT clause. This is unsafe because the set of rows included cannot be predicted.
  - Error number: 1670; Symbol: [ER\\_BINLOG\\_UNSAFE\\_SYSTEM\\_TABLE](#); SQLSTATE: HY000  
  
Message: The statement is unsafe because it uses the general log, slow query log, or performance\_schema table(s). This is unsafe because system tables may differ on replicas.
  - Error number: 1671; Symbol: [ER\\_BINLOG\\_UNSAFE\\_AUTOINC\\_COLUMNS](#); SQLSTATE: HY000  
  
Message: Statement is unsafe because it invokes a trigger or a stored function that inserts into an AUTO\_INCREMENT column. Inserted values cannot be logged correctly.
  - Error number: 1672; Symbol: [ER\\_BINLOG\\_UNSAFE\\_UDF](#); SQLSTATE: HY000  
  
Message: Statement is unsafe because it uses a UDF which may not return the same value on the replica.
  - Error number: 1673; Symbol: [ER\\_BINLOG\\_UNSAFE\\_SYSTEM\\_VARIABLE](#); SQLSTATE: HY000  
  
Message: Statement is unsafe because it uses a system variable that may have a different value on the replica.
  - Error number: 1674; Symbol: [ER\\_BINLOG\\_UNSAFE\\_SYSTEM\\_FUNCTION](#); SQLSTATE: HY000  
  
Message: Statement is unsafe because it uses a system function that may return a different value on the replica.
  - Error number: 1675; Symbol: [ER\\_BINLOG\\_UNSAFE\\_NONTRANS\\_AFTER\\_TRANS](#); SQLSTATE: HY000  
  
Message: Statement is unsafe because it accesses a non-transactional table after accessing a transactional table within the same transaction.
  - Error number: 1676; Symbol: [ER\\_MESSAGE\\_AND\\_STATEMENT](#); SQLSTATE: HY000  
  
Message: %s Statement: %s



- 
- Error number: 1678; Symbol: [ER\\_REPLICA\\_CANT\\_CREATE\\_CONVERSION](#); SQLSTATE: HY000  
Message: Can't create conversion table for table '%s.%s'
  - Error number: 1679; Symbol: [ER\\_INSIDE\\_TRANSACTION\\_PREVENTS\\_SWITCH\\_BINLOG\\_FORMAT](#); SQLSTATE: HY000  
Message: Cannot modify @@session.binlog\_format inside a transaction
  - Error number: 1680; Symbol: [ER\\_PATH\\_LENGTH](#); SQLSTATE: HY000  
Message: The path specified for %s is too long.
  - Error number: 1681; Symbol: [ER\\_WARN\\_DEPRECATED\\_SYNTAX\\_NO\\_REPLACEMENT](#); SQLSTATE: HY000  
Message: '%s' is deprecated and will be removed in a future release.
  - Error number: 1682; Symbol: [ER\\_WRONG\\_NATIVE\\_TABLE\\_STRUCTURE](#); SQLSTATE: HY000  
Message: Native table '%s'.'%s' has the wrong structure
  - Error number: 1683; Symbol: [ER\\_WRONG\\_PERFSCHEMA\\_USAGE](#); SQLSTATE: HY000  
Message: Invalid performance\_schema usage.
  - Error number: 1684; Symbol: [ER\\_WARN\\_I\\_S\\_SKIPPED\\_TABLE](#); SQLSTATE: HY000  
Message: Table '%s'.'%s' was skipped since its definition is being modified by concurrent DDL statement
  - Error number: 1685; Symbol: [ER\\_INSIDE\\_TRANSACTION\\_PREVENTS\\_SWITCH\\_BINLOG\\_DIRECT](#); SQLSTATE: HY000  
Message: Cannot modify @@session.binlog\_direct\_non\_transactional\_updates inside a transaction
  - Error number: 1686; Symbol: [ER\\_STORED\\_FUNCTION\\_PREVENTS\\_SWITCH\\_BINLOG\\_DIRECT](#); SQLSTATE: HY000  
Message: Cannot change the binlog direct flag inside a stored function or trigger
  - Error number: 1687; Symbol: [ER\\_SPATIAL\\_MUST\\_HAVE\\_GEOM\\_COL](#); SQLSTATE: 42000  
Message: A SPATIAL index may only contain a geometrical type column
  - Error number: 1688; Symbol: [ER\\_TOO\\_LONG\\_INDEX\\_COMMENT](#); SQLSTATE: HY000  
Message: Comment for index '%s' is too long (max = %lu)
  - Error number: 1689; Symbol: [ER\\_LOCK\\_ABORTED](#); SQLSTATE: HY000  
Message: Wait on a lock was aborted due to a pending exclusive lock
  - Error number: 1690; Symbol: [ER\\_DATA\\_OUT\\_OF\\_RANGE](#); SQLSTATE: 22003  
Message: %s value is out of range in '%s'
  - Error number: 1692; Symbol: [ER\\_BINLOG\\_UNSAFE\\_MULTIPLE\\_ENGINES\\_AND\\_SELF\\_LOGGING\\_ENGINE](#); SQLSTATE: HY000  
Message: Mixing self-logging and non-self-logging engines in a statement is unsafe.
  - Error number: 1693; Symbol: [ER\\_BINLOG\\_UNSAFE\\_MIXED\\_STATEMENT](#); SQLSTATE: HY000
-

---

Message: Statement accesses nontransactional table as well as transactional or temporary table, and writes to any of them.

- Error number: 1694; Symbol: ER\_INSIDE\_TRANSACTION\_PREVENTS\_SWITCH\_SQL\_LOG\_BIN; SQLSTATE: HY000

Message: Cannot modify @@session.sql\_log\_bin inside a transaction

- Error number: 1695; Symbol: ER\_STORED\_FUNCTION\_PREVENTS\_SWITCH\_SQL\_LOG\_BIN; SQLSTATE: HY000

Message: Cannot change the sql\_log\_bin inside a stored function or trigger

- Error number: 1696; Symbol: ER\_FAILED\_READ\_FROM\_PAR\_FILE; SQLSTATE: HY000

Message: Failed to read from the .par file

- Error number: 1697; Symbol: ER\_VALUES\_IS\_NOT\_INT\_TYPE\_ERROR; SQLSTATE: HY000

Message: VALUES value for partition '%s' must have type INT

- Error number: 1698; Symbol: ER\_ACCESS\_DENIED\_NO\_PASSWORD\_ERROR; SQLSTATE: 28000

Message: Access denied for user '%s'@'%s'

- Error number: 1701; Symbol: ER\_TRUNCATE\_ILLEGAL\_FK; SQLSTATE: 42000

Message: Cannot truncate a table referenced in a foreign key constraint (%s)

- Error number: 1702; Symbol: ER\_PLUGIN\_IS\_PERMANENT; SQLSTATE: HY000

Message: Plugin '%s' is force\_plus\_permanent and can not be unloaded

- Error number: 1703; Symbol: ER\_REPLICA\_HEARTBEAT\_VALUE\_OUT\_OF\_RANGE\_MIN; SQLSTATE: HY000

Message: The requested value for the heartbeat period is less than 1 millisecond. The value is reset to 0, meaning that heartbeating will effectively be disabled.

- Error number: 1704; Symbol: ER\_REPLICA\_HEARTBEAT\_VALUE\_OUT\_OF\_RANGE\_MAX; SQLSTATE: HY000

Message: The requested value for the heartbeat period exceeds the value of `replica\_net\_timeout` seconds. A sensible value for the period should be less than the timeout.

- Error number: 1705; Symbol: ER\_STMT\_CACHE\_FULL; SQLSTATE: HY000

Message: Multi-row statements required more than 'max\_binlog\_stmt\_cache\_size' bytes of storage; increase this mysqld variable and try again

- Error number: 1706; Symbol: ER\_MULTI\_UPDATE\_KEY\_CONFLICT; SQLSTATE: HY000

Message: Primary key/partition key update is not allowed since the table is updated both as '%s' and '%s'.

- Error number: 1707; Symbol: ER\_TABLE\_NEEDS\_REBUILD; SQLSTATE: HY000

Message: Table rebuild required. Please do "ALTER TABLE `s` FORCE" or dump/reload to fix it!

- Error number: 1708; Symbol: WARN\_OPTION\_BELOW\_LIMIT; SQLSTATE: HY000

Message: The value of '%s' should be no less than the value of '%s'

- Error number: 1709; Symbol: ER\_INDEX\_COLUMN\_TOO\_LONG; SQLSTATE: HY000

---

Message: Index column size too large. The maximum column size is %lu bytes.

- Error number: 1710; Symbol: [ER\\_ERROR\\_IN\\_TRIGGER\\_BODY](#); SQLSTATE: HY000

Message: Trigger '%s' has an error in its body: '%s'

- Error number: 1711; Symbol: [ER\\_ERROR\\_IN\\_UNKNOWN\\_TRIGGER\\_BODY](#); SQLSTATE: HY000

Message: Unknown trigger has an error in its body: '%s'

- Error number: 1712; Symbol: [ER\\_INDEX\\_CORRUPT](#); SQLSTATE: HY000

Message: Index %s is corrupted

- Error number: 1713; Symbol: [ER\\_UNDO\\_RECORD\\_TOO\\_BIG](#); SQLSTATE: HY000

Message: Undo log record is too big.

- Error number: 1714; Symbol: [ER\\_BINLOG\\_UNSAFE\\_INSERT\\_IGNORE\\_SELECT](#); SQLSTATE: HY000

Message: INSERT IGNORE... SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are ignored. This order cannot be predicted and may differ on source and the replica.

- Error number: 1715; Symbol: [ER\\_BINLOG\\_UNSAFE\\_INSERT\\_SELECT\\_UPDATE](#); SQLSTATE: HY000

Message: INSERT... SELECT... ON DUPLICATE KEY UPDATE is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are updated. This order cannot be predicted and may differ on source and the replica.

- Error number: 1716; Symbol: [ER\\_BINLOG\\_UNSAFE\\_REPLACE\\_SELECT](#); SQLSTATE: HY000

Message: REPLACE... SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are replaced. This order cannot be predicted and may differ on source and the replica.

- Error number: 1717; Symbol: [ER\\_BINLOG\\_UNSAFE\\_CREATE\\_IGNORE\\_SELECT](#); SQLSTATE: HY000

Message: CREATE... IGNORE SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are ignored. This order cannot be predicted and may differ on source and the replica.

- Error number: 1718; Symbol: [ER\\_BINLOG\\_UNSAFE\\_CREATE\\_REPLACE\\_SELECT](#); SQLSTATE: HY000

Message: CREATE... REPLACE SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are replaced. This order cannot be predicted and may differ on source and the replica.

- Error number: 1719; Symbol: [ER\\_BINLOG\\_UNSAFE\\_UPDATE\\_IGNORE](#); SQLSTATE: HY000

Message: UPDATE IGNORE is unsafe because the order in which rows are updated determines which (if any) rows are ignored. This order cannot be predicted and may differ on source and the replica.

- Error number: 1720; Symbol: [ER\\_PLUGIN\\_NO\\_UNINSTALL](#); SQLSTATE: HY000

Message: Plugin '%s' is marked as not dynamically uninstallable. You have to stop the server to uninstall it.

- 
- Error number: 1721; Symbol: [ER\\_PLUGIN\\_NO\\_INSTALL](#); SQLSTATE: HY000  
Message: Plugin '%s' is marked as not dynamically installable. You have to stop the server to install it.
  - Error number: 1722; Symbol: [ER\\_BINLOG\\_UNSAFE\\_WRITE\\_AUTOINC\\_SELECT](#); SQLSTATE: HY000  
Message: Statements writing to a table with an auto-increment column after selecting from another table are unsafe because the order in which rows are retrieved determines what (if any) rows will be written. This order cannot be predicted and may differ on source and the replica.
  - Error number: 1723; Symbol: [ER\\_BINLOG\\_UNSAFE\\_CREATE\\_SELECT\\_AUTOINC](#); SQLSTATE: HY000  
Message: CREATE TABLE... SELECT... on a table with an auto-increment column is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are inserted. This order cannot be predicted and may differ on source and the replica.
  - Error number: 1724; Symbol: [ER\\_BINLOG\\_UNSAFE\\_INSERT\\_TWO\\_KEYS](#); SQLSTATE: HY000  
Message: INSERT... ON DUPLICATE KEY UPDATE on a table with more than one UNIQUE KEY is unsafe
  - Error number: 1725; Symbol: [ER\\_TABLE\\_IN\\_FK\\_CHECK](#); SQLSTATE: HY000  
Message: Table is being used in foreign key check.
  - Error number: 1726; Symbol: [ER\\_UNSUPPORTED\\_ENGINE](#); SQLSTATE: HY000  
Message: Storage engine '%s' does not support system tables. [%s.%s]
  - Error number: 1727; Symbol: [ER\\_BINLOG\\_UNSAFE\\_AUTOINC\\_NOT\\_FIRST](#); SQLSTATE: HY000  
Message: INSERT into autoincrement field which is not the first part in the composed primary key is unsafe.
  - Error number: 1728; Symbol: [ER\\_CANNOT\\_LOAD\\_FROM\\_TABLE\\_V2](#); SQLSTATE: HY000  
Message: Cannot load from %s.%s. The table is probably corrupted
  - Error number: 1729; Symbol: [ER\\_SOURCE\\_DELAY\\_VALUE\\_OUT\\_OF\\_RANGE](#); SQLSTATE: HY000  
Message: The requested value %s for the source delay exceeds the maximum %u
  - Error number: 1730; Symbol: [ER\\_ONLY\\_FD\\_AND\\_RBR\\_EVENTS\\_ALLOWED\\_IN\\_BINLOG\\_STATEMENT](#); SQLSTATE: HY000  
Message: Only Format\_description\_log\_event and row events are allowed in BINLOG statements (but %s was provided)
  - Error number: 1731; Symbol: [ER\\_PARTITION\\_EXCHANGE\\_DIFFERENT\\_OPTION](#); SQLSTATE: HY000  
Message: Non matching attribute '%s' between partition and table
  - Error number: 1732; Symbol: [ER\\_PARTITION\\_EXCHANGE\\_PART\\_TABLE](#); SQLSTATE: HY000  
Message: Table to exchange with partition is partitioned: '%s'
  - Error number: 1733; Symbol: [ER\\_PARTITION\\_EXCHANGE\\_TEMP\\_TABLE](#); SQLSTATE: HY000  
Message: Table to exchange with partition is temporary: '%s'

- 
- Error number: 1734; Symbol: [ER\\_PARTITION\\_INSTEAD\\_OF\\_SUBPARTITION](#); SQLSTATE: HY000  
Message: Subpartitioned table, use subpartition instead of partition
  - Error number: 1735; Symbol: [ER\\_UNKNOWN\\_PARTITION](#); SQLSTATE: HY000  
Message: Unknown partition '%s' in table '%s'
  - Error number: 1736; Symbol: [ER\\_TABLES\\_DIFFERENT\\_METADATA](#); SQLSTATE: HY000  
Message: Tables have different definitions
  - Error number: 1737; Symbol: [ER\\_ROW\\_DOES\\_NOT\\_MATCH\\_PARTITION](#); SQLSTATE: HY000  
Message: Found a row that does not match the partition
  - Error number: 1738; Symbol: [ER\\_BINLOG\\_CACHE\\_SIZE\\_GREATER\\_THAN\\_MAX](#); SQLSTATE: HY000  
Message: Option binlog\_cache\_size (%lu) is greater than max\_binlog\_cache\_size (%lu); setting binlog\_cache\_size equal to max\_binlog\_cache\_size.
  - Error number: 1739; Symbol: [ER\\_WARN\\_INDEX\\_NOT\\_APPLICABLE](#); SQLSTATE: HY000  
Message: Cannot use %s access on index '%s' due to type or collation conversion on field '%s'
  - Error number: 1740; Symbol: [ER\\_PARTITION\\_EXCHANGE\\_FOREIGN\\_KEY](#); SQLSTATE: HY000  
Message: Table to exchange with partition has foreign key references: '%s'
  - Error number: 1742; Symbol: [ER\\_RPL\\_INFO\\_DATA\\_TOO\\_LONG](#); SQLSTATE: HY000  
Message: Data for column '%s' too long
  - Error number: 1745; Symbol: [ER\\_BINLOG\\_STMT\\_CACHE\\_SIZE\\_GREATER\\_THAN\\_MAX](#); SQLSTATE: HY000  
Message: Option binlog\_stmt\_cache\_size (%lu) is greater than max\_binlog\_stmt\_cache\_size (%lu); setting binlog\_stmt\_cache\_size equal to max\_binlog\_stmt\_cache\_size.
  - Error number: 1746; Symbol: [ER\\_CANT\\_UPDATE\\_TABLE\\_IN\\_CREATE\\_TABLE\\_SELECT](#); SQLSTATE: HY000  
Message: Can't update table '%s' while '%s' is being created.
  - Error number: 1747; Symbol: [ER\\_PARTITION\\_CLAUSE\\_ON\\_NONPARTITIONED](#); SQLSTATE: HY000  
Message: PARTITION () clause on non partitioned table
  - Error number: 1748; Symbol: [ER\\_ROW\\_DOES\\_NOT\\_MATCH\\_GIVEN\\_PARTITION\\_SET](#); SQLSTATE: HY000  
Message: Found a row not matching the given partition set
  - Error number: 1750; Symbol: [ER\\_CHANGE\\_RPL\\_INFO\\_REPOSITORY\\_FAILURE](#); SQLSTATE: HY000  
Message: Failure while changing the type of replication repository: %s.
  - Error number: 1751; Symbol: [ER\\_WARNING\\_NOT\\_COMPLETE\\_ROLLBACK\\_WITH\\_CREATED\\_TEMP\\_TABLE](#); SQLSTATE: HY000  
Message: The creation of some temporary tables could not be rolled back.
-

- 
- Error number: 1752; Symbol: [ER\\_WARNING\\_NOT\\_COMPLETE\\_ROLLBACK\\_WITH\\_DROPPED\\_TEMP\\_TABLE](#); SQLSTATE: HY000  
Message: Some temporary tables were dropped, but these operations could not be rolled back.
  - Error number: 1753; Symbol: [ER\\_MTA\\_FEATURE\\_IS\\_NOT\\_SUPPORTED](#); SQLSTATE: HY000  
Message: %s is not supported in multi-threaded replica mode. %s
  - Error number: 1754; Symbol: [ER\\_MTA\\_UPDATED\\_DBS\\_GREATER\\_MAX](#); SQLSTATE: HY000  
Message: The number of modified databases exceeds the maximum %d; the database names will not be included in the replication event metadata.
  - Error number: 1755; Symbol: [ER\\_MTA\\_CANT\\_PARALLEL](#); SQLSTATE: HY000  
Message: Cannot execute the current event group in the parallel mode. Encountered event %s, relay-log name %s, position %s which prevents execution of this event group in parallel mode. Reason: %s.
  - Error number: 1756; Symbol: [ER\\_MTA\\_INCONSISTENT\\_DATA](#); SQLSTATE: HY000  
Message: %s
  - Error number: 1757; Symbol: [ER\\_FULLTEXT\\_NOT\\_SUPPORTED\\_WITH\\_PARTITIONING](#); SQLSTATE: HY000  
Message: FULLTEXT index is not supported for partitioned tables.
  - Error number: 1758; Symbol: [ER\\_DA\\_INVALID\\_CONDITION\\_NUMBER](#); SQLSTATE: 35000  
Message: Invalid condition number
  - Error number: 1759; Symbol: [ER\\_INSECURE\\_PLAIN\\_TEXT](#); SQLSTATE: HY000  
Message: Sending passwords in plain text without SSL/TLS is extremely insecure.
  - Error number: 1760; Symbol: [ER\\_INSECURE\\_CHANGE\\_SOURCE](#); SQLSTATE: HY000  
Message: Storing MySQL user name or password information in the connection metadata repository is not secure and is therefore not recommended. Please consider using the USER and PASSWORD connection options for START REPLICA; see the 'START REPLICA Syntax' in the MySQL Manual for more information.
  - Error number: 1761; Symbol: [ER\\_FOREIGN\\_DUPLICATE\\_KEY\\_WITH\\_CHILD\\_INFO](#); SQLSTATE: 23000  
Message: Foreign key constraint for table '%s', record '%s' would lead to a duplicate entry in table '%s', key '%s'
  - Error number: 1762; Symbol: [ER\\_FOREIGN\\_DUPLICATE\\_KEY\\_WITHOUT\\_CHILD\\_INFO](#); SQLSTATE: 23000  
Message: Foreign key constraint for table '%s', record '%s' would lead to a duplicate entry in a child table
  - Error number: 1763; Symbol: [ER\\_SQLTHREAD\\_WITH\\_SECURE\\_REPLICA](#); SQLSTATE: HY000  
Message: Setting authentication options is not possible when only the Replica SQL Thread is being started.
  - Error number: 1764; Symbol: [ER\\_TABLE\\_HAS\\_NO\\_FT](#); SQLSTATE: HY000  
Message: The table does not have FULLTEXT index to support this query

- 
- Error number: 1765; Symbol: `ER_VARIABLE_NOT_SETTABLE_IN_SF_OR_TRIGGER`; SQLSTATE: `HY000`  
Message: The system variable %s cannot be set in stored functions or triggers.
  - Error number: 1766; Symbol: `ER_VARIABLE_NOT_SETTABLE_IN_TRANSACTION`; SQLSTATE: `HY000`  
Message: The system variable %s cannot be set when there is an ongoing transaction.
  - Error number: 1769; Symbol: `ER_SET_STATEMENT_CANNOT_INVOKE_FUNCTION`; SQLSTATE: `HY000`  
Message: The statement 'SET %s' cannot invoke a stored function.
  - Error number: 1770; Symbol: `ER_GTID_NEXT_CANT_BE_AUTOMATIC_IF_GTID_NEXT_LIST_IS_NON_NULL`; SQLSTATE: `HY000`  
Message: The system variable @@SESSION.GTID\_NEXT cannot be 'AUTOMATIC' when @@SESSION.GTID\_NEXT\_LIST is non-NULL.
  - Error number: 1772; Symbol: `ER_MALFORMED_GTID_SET_SPECIFICATION`; SQLSTATE: `HY000`  
Message: Malformed GTID set specification '%s'.
  - Error number: 1773; Symbol: `ER_MALFORMED_GTID_SET_ENCODING`; SQLSTATE: `HY000`  
Message: Malformed GTID set encoding.
  - Error number: 1774; Symbol: `ER_MALFORMED_GTID_SPECIFICATION`; SQLSTATE: `HY000`  
Message: Malformed GTID specification '%s'.
  - Error number: 1775; Symbol: `ER_GNO_EXHAUSTED`; SQLSTATE: `HY000`  
Message: Impossible to generate GTID: the integer component reached the maximum value. Restart the server with a new server\_uuid.
  - Error number: 1776; Symbol: `ER_BAD_REPLICA_AUTO_POSITION`; SQLSTATE: `HY000`  
Message: Parameters SOURCE\_LOG\_FILE, SOURCE\_LOG\_POS, RELAY\_LOG\_FILE and RELAY\_LOG\_POS cannot be set when SOURCE\_AUTO\_POSITION is active.
  - Error number: 1777; Symbol: `ER_AUTO_POSITION_REQUIRES_GTID_MODE_NOT_OFF`; SQLSTATE: `HY000`  
Message: CHANGE REPLICATION SOURCE TO SOURCE\_AUTO\_POSITION = 1 cannot be executed because @@GLOBAL.GTID\_MODE = OFF.
  - Error number: 1778; Symbol: `ER_CANT_DO_IMPLICIT_COMMIT_IN_TRX_WHEN_GTID_NEXT_IS_SET`; SQLSTATE: `HY000`  
Message: Cannot execute statements with implicit commit inside a transaction when @@SESSION.GTID\_NEXT == 'UUID:NUMBER'.
  - Error number: 1779; Symbol: `ER_GTID_MODE_ON_REQUIRES_ENFORCE_GTID_CONSISTENCY_ON`; SQLSTATE: `HY000`  
Message: GTID\_MODE = ON requires ENFORCE\_GTID\_CONSISTENCY = ON.
  - Error number: 1781; Symbol: `ER_CANT_SET_GTID_NEXT_TO_GTID_WHEN_GTID_MODE_IS_OFF`; SQLSTATE: `HY000`
-

---

Message: @@SESSION.GTID\_NEXT cannot be set to UUID:NUMBER when @@GLOBAL.GTID\_MODE = OFF.

- Error number: 1782; Symbol: ER\_CANT\_SET\_GTID\_NEXT\_TO\_ANONYMOUS\_WHEN\_GTID\_MODE\_IS\_ON; SQLSTATE: HY000

Message: @@SESSION.GTID\_NEXT cannot be set to ANONYMOUS when @@GLOBAL.GTID\_MODE = ON.

- Error number: 1783; Symbol: ER\_CANT\_SET\_GTID\_NEXT\_LIST\_TO\_NON\_NULL\_WHEN\_GTID\_MODE\_IS\_OFF; SQLSTATE: HY000

Message: @@SESSION.GTID\_NEXT\_LIST cannot be set to a non-NULL value when @@GLOBAL.GTID\_MODE = OFF.

- Error number: 1785; Symbol: ER\_GTID\_UNSAFE\_NON\_TRANSACTIONAL\_TABLE; SQLSTATE: HY000

Message: Statement violates GTID consistency: Updates to non-transactional tables can only be done in either autocommitted statements or single-statement transactions, and never in the same statement as updates to transactional tables.

- Error number: 1786; Symbol: ER\_GTID\_UNSAFE\_CREATE\_SELECT; SQLSTATE: HY000

Message: Statement violates GTID consistency: CREATE TABLE ... SELECT.

- Error number: 1788; Symbol: ER\_GTID\_MODE\_CAN\_ONLY\_CHANGE\_ONE\_STEP\_AT\_A\_TIME; SQLSTATE: HY000

Message: The value of @@GLOBAL.GTID\_MODE can only be changed one step at a time: OFF <-> OFF\_PERMISSIVE <-> ON\_PERMISSIVE <-> ON. Also note that this value must be stepped up or down simultaneously on all servers. See the Manual for instructions.

- Error number: 1789; Symbol: ER\_SOURCE\_HAS\_PURGED\_REQUIRED\_GTIDS; SQLSTATE: HY000

Message: Cannot replicate because the source purged required binary logs. Replicate the missing transactions from elsewhere, or provision a new replica from backup. Consider increasing the source's binary log expiration period. %s

- Error number: 1790; Symbol: ER\_CANT\_SET\_GTID\_NEXT\_WHEN\_OWNING\_GTID; SQLSTATE: HY000

Message: @@SESSION.GTID\_NEXT cannot be changed by a client that owns a GTID. The client owns %s. Ownership is released on COMMIT or ROLLBACK.

- Error number: 1791; Symbol: ER\_UNKNOWN\_EXPLAIN\_FORMAT; SQLSTATE: HY000

Message: Unknown EXPLAIN format name: '%s'

- Error number: 1792; Symbol: ER\_CANT\_EXECUTE\_IN\_READ\_ONLY\_TRANSACTION; SQLSTATE: 25006

Message: Cannot execute statement in a READ ONLY transaction.

- Error number: 1793; Symbol: ER\_TOO\_LONG\_TABLE\_PARTITION\_COMMENT; SQLSTATE: HY000

Message: Comment for table partition '%s' is too long (max = %lu)



- 
- Error number: 1794; Symbol: [ER\\_REPLICA\\_CONFIGURATION](#); SQLSTATE: HY000  
Message: Replica is not configured or failed to initialize properly. You must at least set --server-id to enable either a source or a replica. Additional error messages can be found in the MySQL error log.
  - Error number: 1795; Symbol: [ER\\_INNOODB\\_FT\\_LIMIT](#); SQLSTATE: HY000  
Message: InnoDB presently supports one FULLTEXT index creation at a time
  - Error number: 1796; Symbol: [ER\\_INNOODB\\_NO\\_FT\\_TEMP\\_TABLE](#); SQLSTATE: HY000  
Message: Cannot create FULLTEXT index on temporary InnoDB table
  - Error number: 1797; Symbol: [ER\\_INNOODB\\_FT\\_WRONG\\_DOCID\\_COLUMN](#); SQLSTATE: HY000  
Message: Column '%s' is of wrong type for an InnoDB FULLTEXT index
  - Error number: 1798; Symbol: [ER\\_INNOODB\\_FT\\_WRONG\\_DOCID\\_INDEX](#); SQLSTATE: HY000  
Message: Index '%s' is of wrong type for an InnoDB FULLTEXT index
  - Error number: 1799; Symbol: [ER\\_INNOODB\\_ONLINE\\_LOG\\_TOO\\_BIG](#); SQLSTATE: HY000  
Message: Creating index '%s' required more than 'innodb\_online\_alter\_log\_max\_size' bytes of modification log. Please try again.
  - Error number: 1800; Symbol: [ER\\_UNKNOWN\\_ALTER\\_ALGORITHM](#); SQLSTATE: HY000  
Message: Unknown ALGORITHM '%s'
  - Error number: 1801; Symbol: [ER\\_UNKNOWN\\_ALTER\\_LOCK](#); SQLSTATE: HY000  
Message: Unknown LOCK type '%s'
  - Error number: 1802; Symbol: [ER\\_MTA\\_CHANGE\\_SOURCE\\_CANT\\_RUN\\_WITH\\_GAPS](#); SQLSTATE: HY000  
Message: CHANGE REPLICATION SOURCE cannot be executed when the replica was stopped with an error or killed in MTA mode. Consider using RESET REPLICA or START REPLICA UNTIL.
  - Error number: 1803; Symbol: [ER\\_MTA\\_RECOVERY\\_FAILURE](#); SQLSTATE: HY000  
Message: Cannot recover after REPLICA errored out in parallel execution mode. Additional error messages can be found in the MySQL error log.
  - Error number: 1804; Symbol: [ER\\_MTA\\_RESET\\_WORKERS](#); SQLSTATE: HY000  
Message: Cannot clean up worker info tables. Additional error messages can be found in the MySQL error log.
  - Error number: 1805; Symbol: [ER\\_COL\\_COUNT\\_DOESNT\\_MATCH\\_CORRUPTED\\_V2](#); SQLSTATE: HY000  
Message: Column count of %s.%s is wrong. Expected %d, found %d. The table is probably corrupted
  - Error number: 1806; Symbol: [ER\\_REPLICA\\_SILENT\\_RETRY\\_TRANSACTION](#); SQLSTATE: HY000  
Message: Replica must silently retry current transaction
  - Error number: 1807; Symbol: [ER\\_DISCARD\\_FK\\_CHECKS\\_RUNNING](#); SQLSTATE: HY000  
Message: There is a foreign key check running on table '%s'. Cannot discard the table.
  - Error number: 1808; Symbol: [ER\\_TABLE\\_SCHEMA\\_MISMATCH](#); SQLSTATE: HY000

---

Message: Schema mismatch (%s)

- Error number: 1809; Symbol: [ER\\_TABLE\\_IN\\_SYSTEM\\_TABLESPACE](#); SQLSTATE: HY000

Message: Table '%s' in system tablespace

- Error number: 1810; Symbol: [ER\\_IO\\_READ\\_ERROR](#); SQLSTATE: HY000

Message: IO Read error: (%lu, %s) %s

- Error number: 1811; Symbol: [ER\\_IO\\_WRITE\\_ERROR](#); SQLSTATE: HY000

Message: IO Write error: (%lu, %s) %s

- Error number: 1812; Symbol: [ER\\_TABLESPACE\\_MISSING](#); SQLSTATE: HY000

Message: Tablespace is missing for table %s.

- Error number: 1813; Symbol: [ER\\_TABLESPACE\\_EXISTS](#); SQLSTATE: HY000

Message: Tablespace '%s' exists.

- Error number: 1814; Symbol: [ER\\_TABLESPACE\\_DISCARDED](#); SQLSTATE: HY000

Message: Tablespace has been discarded for table '%s'

- Error number: 1815; Symbol: [ER\\_INTERNAL\\_ERROR](#); SQLSTATE: HY000

Message: Internal error: %s

- Error number: 1816; Symbol: [ER\\_INNODB\\_IMPORT\\_ERROR](#); SQLSTATE: HY000

Message: ALTER TABLE %s IMPORT TABLESPACE failed with error %lu : '%s'

- Error number: 1817; Symbol: [ER\\_INNODB\\_INDEX\\_CORRUPT](#); SQLSTATE: HY000

Message: Index corrupt: %s

- Error number: 1818; Symbol: [ER\\_INVALID\\_YEAR\\_COLUMN\\_LENGTH](#); SQLSTATE: HY000

Message: Invalid display width. Use YEAR instead.

- Error number: 1819; Symbol: [ER\\_NOT\\_VALID\\_PASSWORD](#); SQLSTATE: HY000

Message: Your password does not satisfy the current policy requirements

- Error number: 1820; Symbol: [ER\\_MUST\\_CHANGE\\_PASSWORD](#); SQLSTATE: HY000

Message: You must reset your password using ALTER USER statement before executing this statement.

- Error number: 1821; Symbol: [ER\\_FK\\_NO\\_INDEX\\_CHILD](#); SQLSTATE: HY000

Message: Failed to add the foreign key constraint. Missing index for constraint '%s' in the foreign table '%s'

- Error number: 1822; Symbol: [ER\\_FK\\_NO\\_INDEX\\_PARENT](#); SQLSTATE: HY000

Message: Failed to add the foreign key constraint. Missing index for constraint '%s' in the referenced table '%s'

- Error number: 1823; Symbol: [ER\\_FK\\_FAIL\\_ADD\\_SYSTEM](#); SQLSTATE: HY000

Message: Failed to add the foreign key constraint '%s' to system tables

- 
- Error number: 1824; Symbol: [ER\\_FK\\_CANNOT\\_OPEN\\_PARENT](#); SQLSTATE: HY000  
Message: Failed to open the referenced table '%s'
  - Error number: 1825; Symbol: [ER\\_FK\\_INCORRECT\\_OPTION](#); SQLSTATE: HY000  
Message: Failed to add the foreign key constraint on table '%s'. Incorrect options in FOREIGN KEY constraint '%s'
  - Error number: 1826; Symbol: [ER\\_FK\\_DUP\\_NAME](#); SQLSTATE: HY000  
Message: Duplicate foreign key constraint name '%s'
  - Error number: 1827; Symbol: [ER\\_PASSWORD\\_FORMAT](#); SQLSTATE: HY000  
Message: The password hash doesn't have the expected format.
  - Error number: 1828; Symbol: [ER\\_FK\\_COLUMN\\_CANNOT\\_DROP](#); SQLSTATE: HY000  
Message: Cannot drop column '%s': needed in a foreign key constraint '%s'
  - Error number: 1829; Symbol: [ER\\_FK\\_COLUMN\\_CANNOT\\_DROP\\_CHILD](#); SQLSTATE: HY000  
Message: Cannot drop column '%s': needed in a foreign key constraint '%s' of table '%s'
  - Error number: 1830; Symbol: [ER\\_FK\\_COLUMN\\_NOT\\_NULL](#); SQLSTATE: HY000  
Message: Column '%s' cannot be NOT NULL: needed in a foreign key constraint '%s' SET NULL
  - Error number: 1831; Symbol: [ER\\_DUP\\_INDEX](#); SQLSTATE: HY000  
Message: Duplicate index '%s' defined on the table '%s.%s'. This is deprecated and will be disallowed in a future release.
  - Error number: 1832; Symbol: [ER\\_FK\\_COLUMN\\_CANNOT\\_CHANGE](#); SQLSTATE: HY000  
Message: Cannot change column '%s': used in a foreign key constraint '%s'
  - Error number: 1833; Symbol: [ER\\_FK\\_COLUMN\\_CANNOT\\_CHANGE\\_CHILD](#); SQLSTATE: HY000  
Message: Cannot change column '%s': used in a foreign key constraint '%s' of table '%s'
  - Error number: 1835; Symbol: [ER\\_MALFORMED\\_PACKET](#); SQLSTATE: HY000  
Message: Malformed communication packet.
  - Error number: 1836; Symbol: [ER\\_READ\\_ONLY\\_MODE](#); SQLSTATE: HY000  
Message: Running in read-only mode
  - Error number: 1837; Symbol: [ER\\_GTID\\_NEXT\\_TYPE\\_UNDEFINED\\_GTID](#); SQLSTATE: HY000  
Message: When @@SESSION.GTID\_NEXT is set to a GTID, you must explicitly set it to a different value after a COMMIT or ROLLBACK. Please check GTID\_NEXT variable manual page for detailed explanation. Current @@SESSION.GTID\_NEXT is '%s'.
  - Error number: 1838; Symbol: [ER\\_VARIABLE\\_NOT\\_SETTABLE\\_IN\\_SP](#); SQLSTATE: HY000  
Message: The system variable %s cannot be set in stored procedures.
  - Error number: 1840; Symbol: [ER\\_CANT\\_SET\\_GTID\\_PURGED\\_WHEN\\_GTID\\_EXECUTED\\_IS\\_NOT\\_EMPTY](#); SQLSTATE: HY000  
Message: @@GLOBAL.GTID\_PURGED can only be set when @@GLOBAL.GTID\_EXECUTED is empty.

- 
- Error number: 1841; Symbol: `ER_CANT_SET_GTID_PURGED_WHEN_OWNED_GTIDS_IS_NOT_EMPTY`; SQLSTATE: HY000  
Message: @@GLOBAL.GTID\_PURGED can only be set when there are no ongoing transactions (not even in other clients).
  - Error number: 1842; Symbol: `ER_GTID_PURGED_WAS_CHANGED`; SQLSTATE: HY000  
Message: @@GLOBAL.GTID\_PURGED was changed from '%s' to '%s'.
  - Error number: 1843; Symbol: `ER_GTID_EXECUTED_WAS_CHANGED`; SQLSTATE: HY000  
Message: @@GLOBAL.GTID\_EXECUTED was changed from '%s' to '%s'.
  - Error number: 1844; Symbol: `ER_BINLOG_STMT_MODE_AND_NO_REPL_TABLES`; SQLSTATE: HY000  
Message: Cannot execute statement: impossible to write to binary log since BINLOG\_FORMAT = STATEMENT, and both replicated and non replicated tables are written to.
  - Error number: 1845; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED`; SQLSTATE: 0A000  
Message: %s is not supported for this operation. Try %s.
  - Error number: 1846; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON`; SQLSTATE: 0A000  
Message: %s is not supported. Reason: %s. Try %s.
  - Error number: 1847; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_COPY`; SQLSTATE: HY000  
Message: COPY algorithm requires a lock
  - Error number: 1848; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_PARTITION`; SQLSTATE: HY000  
Message: Partition specific operations do not yet support LOCK/ALGORITHM
  - Error number: 1849; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_FK_RENAME`; SQLSTATE: HY000  
Message: Columns participating in a foreign key are renamed
  - Error number: 1850; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_COLUMN_TYPE`; SQLSTATE: HY000  
Message: Cannot change column type INPLACE
  - Error number: 1851; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_FK_CHECK`; SQLSTATE: HY000  
Message: Adding foreign keys needs foreign\_key\_checks=OFF
  - Error number: 1853; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_NOPK`; SQLSTATE: HY000  
Message: Dropping a primary key is not allowed without also adding a new primary key
  - Error number: 1854; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_AUTOINC`; SQLSTATE: HY000  
Message: Adding an auto-increment column requires a lock

- 
- Error number: 1855; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTEDED_REASON_HIDDEN_FTS`; SQLSTATE: `HY000`  
Message: Cannot replace hidden FTS\_DOC\_ID with a user-visible one
  - Error number: 1856; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTEDED_REASON_CHANGE_FTS`; SQLSTATE: `HY000`  
Message: Cannot drop or rename FTS\_DOC\_ID
  - Error number: 1857; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTEDED_REASON_FTS`; SQLSTATE: `HY000`  
Message: Fulltext index creation requires a lock
  - Error number: 1859; Symbol: `ER_DUP_UNKNOWN_IN_INDEX`; SQLSTATE: `23000`  
Message: Duplicate entry for key '%s'
  - Error number: 1860; Symbol: `ER_IDENT_CAUSES_TOO_LONG_PATH`; SQLSTATE: `HY000`  
Message: Long database name and identifier for object resulted in path length exceeding %d characters. Path: '%s'.
  - Error number: 1861; Symbol: `ER_ALTER_OPERATION_NOT_SUPPORTEDED_REASON_NOT_NULL`; SQLSTATE: `HY000`  
Message: cannot silently convert NULL values, as required in this SQL\_MODE
  - Error number: 1862; Symbol: `ER_MUST_CHANGE_PASSWORD_LOGIN`; SQLSTATE: `HY000`  
Message: Your password has expired. To log in you must change it using a client that supports expired passwords.
  - Error number: 1863; Symbol: `ER_ROW_IN_WRONG_PARTITION`; SQLSTATE: `HY000`  
Message: Found a row in wrong partition %s
  - Error number: 1864; Symbol: `ER_MTA_EVENT_BIGGER_PENDING_JOBS_SIZE_MAX`; SQLSTATE: `HY000`  
Message: Cannot schedule event %s, relay-log name %s, position %s to Worker thread because its size %lu exceeds %lu of replica\_pending\_jobs\_size\_max.
  - Error number: 1866; Symbol: `ER_BINLOG_LOGICAL_CORRUPTION`; SQLSTATE: `HY000`  
Message: The binary log file '%s' is logically corrupted: %s
  - Error number: 1867; Symbol: `ER_WARN_PURGE_LOG_IN_USE`; SQLSTATE: `HY000`  
Message: file %s was not purged because it was being read by %d thread(s), purged only %d out of %d files.
  - Error number: 1868; Symbol: `ER_WARN_PURGE_LOG_IS_ACTIVE`; SQLSTATE: `HY000`  
Message: file %s was not purged because it is the active log file.
  - Error number: 1869; Symbol: `ER_AUTO_INCREMENT_CONFLICT`; SQLSTATE: `HY000`  
Message: Auto-increment value in UPDATE conflicts with internally generated values
-

- 
- Error number: [1870](#); Symbol: [WARN\\_ON\\_BLOCKHOLE\\_IN\\_RBR](#); SQLSTATE: [HY000](#)  
Message: Row events are not logged for %s statements that modify BLACKHOLE tables in row format. Table(s): '%s'
  - Error number: [1871](#); Symbol: [ER\\_REPLICA\\_CM\\_INIT\\_REPOSITORY](#); SQLSTATE: [HY000](#)  
Message: Replica failed to initialize connection metadata structure from the repository
  - Error number: [1872](#); Symbol: [ER\\_REPLICA\\_AM\\_INIT\\_REPOSITORY](#); SQLSTATE: [HY000](#)  
Message: Replica failed to initialize applier metadata structure from the repository
  - Error number: [1873](#); Symbol: [ER\\_ACCESS\\_DENIED\\_CHANGE\\_USER\\_ERROR](#); SQLSTATE: [28000](#)  
Message: Access denied trying to change to user '%s'@'%s' (using password: %s). Disconnecting.
  - Error number: [1874](#); Symbol: [ER\\_INNODB\\_READ\\_ONLY](#); SQLSTATE: [HY000](#)  
Message: InnoDB is in read only mode.
  - Error number: [1875](#); Symbol: [ER\\_STOP\\_REPLICA\\_SQL\\_THREAD\\_TIMEOUT](#); SQLSTATE: [HY000](#)  
Message: STOP REPLICA command execution is incomplete: Replica SQL thread got the stop signal, thread is busy, SQL thread will stop once the current task is complete.
  - Error number: [1876](#); Symbol: [ER\\_STOP\\_REPLICA\\_IO\\_THREAD\\_TIMEOUT](#); SQLSTATE: [HY000](#)  
Message: STOP REPLICA command execution is incomplete: Replica IO thread got the stop signal, thread is busy, IO thread will stop once the current task is complete.
  - Error number: [1877](#); Symbol: [ER\\_TABLE\\_CORRUPT](#); SQLSTATE: [HY000](#)  
Message: Operation cannot be performed. The table '%s.%s' is missing, corrupt or contains bad data.
  - Error number: [1878](#); Symbol: [ER\\_TEMP\\_FILE\\_WRITE\\_FAILURE](#); SQLSTATE: [HY000](#)  
Message: Temporary file write failure.
  - Error number: [1879](#); Symbol: [ER\\_INNODB\\_FT\\_AUX\\_NOT\\_HEX\\_ID](#); SQLSTATE: [HY000](#)  
Message: Upgrade index name failed, please use create index(alter table) algorithm copy to rebuild index.
  - Error number: [1880](#); Symbol: [ER\\_OLD\\_TEMPORALS\\_UPGRADED](#); SQLSTATE: [HY000](#)  
Message: TIME/TIMESTAMP/DATETIME columns of old format have been upgraded to the new format.
  - Error number: [1881](#); Symbol: [ER\\_INNODB\\_FORCED\\_RECOVERY](#); SQLSTATE: [HY000](#)  
Message: Operation not allowed when innodb\_force\_recovery > 0.
  - Error number: [1882](#); Symbol: [ER\\_AES\\_INVALID\\_IV](#); SQLSTATE: [HY000](#)  
Message: The initialization vector supplied to %s is too short. Must be at least %d bytes long
  - Error number: [1883](#); Symbol: [ER\\_PLUGIN\\_CANNOT\\_BE\\_UNINSTALLED](#); SQLSTATE: [HY000](#)  
Message: Plugin '%s' cannot be uninstalled now. %s
  - Error number: [1884](#); Symbol: [ER\\_GTID\\_UNSAFE\\_BINLOG\\_SPLITTABLE\\_STATEMENT\\_AND\\_ASSIGNED\\_GTID](#); SQLSTATE: [HY000](#)

---

Message: Cannot execute statement because it needs to be written to the binary log as multiple statements, and this is not allowed when @@SESSION.GTID\_NEXT == 'UUID:NUMBER'.

- Error number: 1885; Symbol: [ER\\_REPLICA\\_HAS\\_MORE\\_GTIDS\\_THAN\\_SOURCE](#); SQLSTATE: HY000

Message: Replica has more GTIDs than the source has, using the source's SERVER\_UUID. This may indicate that the the last binary log file was truncated or lost, e.g., after a power failure when sync\_binlog != 1. The source may have rolled back transactions that were already replicated to the replica. Replicate any transactions that source has rolled back from replica to source, and/or commit empty transactions on source to account for transactions that have been committed on source but are not included in GTID\_EXECUTED.

- Error number: 1886; Symbol: [ER\\_MISSING\\_KEY](#); SQLSTATE: HY000

Message: The table '%s.%s' does not have the necessary key(s) defined on it. Please check the table definition and create index(s) accordingly.

- Error number: 1887; Symbol: [WARN\\_NAMED\\_PIPE\\_ACCESS\\_EVERYONE](#); SQLSTATE: HY000

Message: Setting named\_pipe\_full\_access\_group='%s' is insecure. Consider using a Windows group with fewer members.

- Error number: 3000; Symbol: [ER\\_FILE\\_CORRUPT](#); SQLSTATE: HY000

Message: File %s is corrupted

- Error number: 3001; Symbol: [ER\\_ERROR\\_ON\\_SOURCE](#); SQLSTATE: HY000

Message: Query partially completed on the source (error on source: %d) and was aborted. There is a chance that your source is inconsistent at this point. If you are sure that your source is ok, run this query manually on the replica and then restart the replica with SET GLOBAL SQL\_REPLICA\_SKIP\_COUNTER=1; START REPLICA;. Query:'%s'

- Error number: 3003; Symbol: [ER\\_STORAGE\\_ENGINE\\_NOT\\_LOADED](#); SQLSTATE: HY000

Message: Storage engine for table '%s'.'%s' is not loaded.

- Error number: 3004; Symbol: [ER\\_GET\\_STACKED\\_DA\\_WITHOUT\\_ACTIVE\\_HANDLER](#); SQLSTATE: 0Z002

Message: GET STACKED DIAGNOSTICS when handler not active

- Error number: 3005; Symbol: [ER\\_WARN\\_LEGACY\\_SYNTAX\\_CONVERTED](#); SQLSTATE: HY000

Message: %s is no longer supported. The statement was converted to %s.

- Error number: 3006; Symbol: [ER\\_BINLOG\\_UNSAFE\\_FULLTEXT\\_PLUGIN](#); SQLSTATE: HY000

Message: Statement is unsafe because it uses a fulltext parser plugin which may not return the same value on the replica.

- Error number: 3007; Symbol: [ER\\_CANNOT\\_DISCARD\\_TEMPORARY\\_TABLE](#); SQLSTATE: HY000

Message: Cannot DISCARD/IMPORT tablespace associated with temporary table

- Error number: 3008; Symbol: [ER\\_FK\\_DEPTH\\_EXCEEDED](#); SQLSTATE: HY000

Message: Foreign key cascade delete/update exceeds max depth of %d.

- Error number: 3009; Symbol: [ER\\_COL\\_COUNT\\_DOESNT\\_MATCH\\_PLEASE\\_UPDATE\\_V2](#); SQLSTATE: HY000

---

Message: The column count of %s.%s is wrong. Expected %d, found %d. Created with MySQL %d, now running %d. Please perform the MySQL upgrade procedure.

- Error number: 3010; Symbol: [ER\\_WARN\\_TRIGGER\\_DOESNT\\_HAVE\\_CREATED](#); SQLSTATE: HY000  
Message: Trigger %s.%s.%s does not have CREATED attribute.
- Error number: 3011; Symbol: [ER\\_REFERENCED\\_TRG\\_DOES\\_NOT\\_EXIST](#); SQLSTATE: HY000  
Message: Referenced trigger '%s' for the given action time and event type does not exist.
- Error number: 3012; Symbol: [ER\\_EXPLAIN\\_NOT\\_SUPPORTED](#); SQLSTATE: HY000  
Message: EXPLAIN FOR CONNECTION command is supported only for SELECT/UPDATE/INSERT/DELETE/REPLACE
- Error number: 3013; Symbol: [ER\\_INVALID\\_FIELD\\_SIZE](#); SQLSTATE: HY000  
Message: Invalid size for column '%s'.
- Error number: 3014; Symbol: [ER\\_MISSING\\_HA\\_CREATE\\_OPTION](#); SQLSTATE: HY000  
Message: Table storage engine '%s' found required create option missing
- Error number: 3015; Symbol: [ER\\_ENGINE\\_OUT\\_OF\\_MEMORY](#); SQLSTATE: HY000  
Message: Out of memory in storage engine '%s'.
- Error number: 3016; Symbol: [ER\\_PASSWORD\\_EXPIRE\\_ANONYMOUS\\_USER](#); SQLSTATE: HY000  
Message: The password for anonymous user cannot be expired.
- Error number: 3017; Symbol: [ER\\_REPLICA\\_SQL\\_THREAD\\_MUST\\_STOP](#); SQLSTATE: HY000  
Message: This operation cannot be performed with a running replica sql thread; run STOP REPLICA SQL\_THREAD first
- Error number: 3018; Symbol: [ER\\_NO\\_FT\\_MATERIALIZED\\_SUBQUERY](#); SQLSTATE: HY000  
Message: Cannot create FULLTEXT index on materialized subquery
- Error number: 3019; Symbol: [ER\\_INNODEB\\_UNDO\\_LOG\\_FULL](#); SQLSTATE: HY000  
Message: Undo Log error: %s
- Error number: 3020; Symbol: [ER\\_INVALID\\_ARGUMENT\\_FOR\\_LOGARITHM](#); SQLSTATE: 2201E  
Message: Invalid argument for logarithm
- Error number: 3021; Symbol: [ER\\_REPLICA\\_CHANNEL\\_IO\\_THREAD\\_MUST\\_STOP](#); SQLSTATE: HY000  
Message: This operation cannot be performed with a running replica io thread; run STOP REPLICA IO\_THREAD FOR CHANNEL '%s' first.
- Error number: 3022; Symbol: [ER\\_WARN\\_OPEN\\_TEMP\\_TABLES\\_MUST\\_BE\\_ZERO](#); SQLSTATE: HY000  
Message: This operation may not be safe when the replica has temporary tables. The tables will be kept open until the server restarts or until the tables are deleted by any replicated DROP statement. Suggest to wait until replica\_open\_temp\_tables = 0.
- Error number: 3023; Symbol: [ER\\_WARN\\_ONLY\\_SOURCE\\_LOG\\_FILE\\_NO\\_POS](#); SQLSTATE: HY000



---

Message: CHANGE REPLICATION SOURCE TO with a SOURCE\_LOG\_FILE clause but no SOURCE\_LOG\_POS clause may not be safe. The old position value may not be valid for the new binary log file.

- Error number: 3024; Symbol: [ER\\_QUERY\\_TIMEOUT](#); SQLSTATE: HY000

Message: Query execution was interrupted, maximum statement execution time exceeded

- Error number: 3025; Symbol: [ER\\_NON\\_RO\\_SELECT\\_DISABLE\\_TIMER](#); SQLSTATE: HY000

Message: Select is not a read only statement, disabling timer

- Error number: 3026; Symbol: [ER\\_DUP\\_LIST\\_ENTRY](#); SQLSTATE: HY000

Message: Duplicate entry '%s'.

- Error number: 3028; Symbol: [ER\\_AGGREGATE\\_ORDER\\_FOR\\_UNION](#); SQLSTATE: HY000

Message: Expression #%u of ORDER BY contains aggregate function and applies to a UNION, EXCEPT or INTERSECT

- Error number: 3029; Symbol: [ER\\_AGGREGATE\\_ORDER\\_NON\\_AGG\\_QUERY](#); SQLSTATE: HY000

Message: Expression #%u of ORDER BY contains aggregate function and applies to the result of a non-aggregated query

- Error number: 3030; Symbol: [ER\\_REPLICA\\_WORKER\\_STOPPED\\_PREVIOUS\\_THD\\_ERROR](#); SQLSTATE: HY000

Message: Replica worker has stopped after at least one previous worker encountered an error when replica-preserve-commit-order was enabled. To preserve commit order, the last transaction executed by this thread has not been committed. When restarting the replica after fixing any failed threads, you should fix this worker as well.

- Error number: 3031; Symbol: [ER\\_DONT\\_SUPPORT\\_REPLICA\\_PRESERVE\\_COMMIT\\_ORDER](#); SQLSTATE: HY000

Message: replica\_preserve\_commit\_order is not supported %s.

- Error number: 3032; Symbol: [ER\\_SERVER\\_OFFLINE\\_MODE](#); SQLSTATE: HY000

Message: The server is currently in offline mode

- Error number: 3033; Symbol: [ER\\_GIS\\_DIFFERENT\\_SRIDS](#); SQLSTATE: HY000

Message: Binary geometry function %s given two geometries of different srids: %u and %u, which should have been identical.

Geometry values passed as arguments to spatial functions must have the same SRID value.

- Error number: 3034; Symbol: [ER\\_GIS\\_UNSUPPORTED\\_ARGUMENT](#); SQLSTATE: HY000

Message: Calling geometry function %s with unsupported types of arguments.

A spatial function was called with a combination of argument types that the function does not support.

- Error number: 3035; Symbol: [ER\\_GIS\\_UNKNOWN\\_ERROR](#); SQLSTATE: HY000

Message: Unknown GIS error occurred in function %s.

- Error number: 3036; Symbol: [ER\\_GIS\\_UNKNOWN\\_EXCEPTION](#); SQLSTATE: HY000

---

Message: Unknown exception caught in GIS function %s.

- Error number: 3037; Symbol: [ER\\_GIS\\_INVALID\\_DATA](#); SQLSTATE: 22023

Message: Invalid GIS data provided to function %s.

A spatial function was called with an argument not recognized as a valid geometry value.

- Error number: 3038; Symbol: [ER\\_BOOST\\_GEOMETRY\\_EMPTY\\_INPUT\\_EXCEPTION](#); SQLSTATE: [HY000](#)

Message: The geometry has no data in function %s.

- Error number: 3039; Symbol: [ER\\_BOOST\\_GEOMETRY\\_CENTROID\\_EXCEPTION](#); SQLSTATE: [HY000](#)

Message: Unable to calculate centroid because geometry is empty in function %s.

- Error number: 3040; Symbol: [ER\\_BOOST\\_GEOMETRY\\_OVERLAY\\_INVALID\\_INPUT\\_EXCEPTION](#); SQLSTATE: [HY000](#)

Message: Geometry overlay calculation error: geometry data is invalid in function %s.

- Error number: 3041; Symbol: [ER\\_BOOST\\_GEOMETRY\\_TURN\\_INFO\\_EXCEPTION](#); SQLSTATE: [HY000](#)

Message: Geometry turn info calculation error: geometry data is invalid in function %s.

- Error number: 3042; Symbol: [ER\\_BOOST\\_GEOMETRY\\_SELF\\_INTERSECTION\\_POINT\\_EXCEPTION](#); SQLSTATE: [HY000](#)

Message: Analysis procedures of intersection points interrupted unexpectedly in function %s.

- Error number: 3043; Symbol: [ER\\_BOOST\\_GEOMETRY\\_UNKNOWN\\_EXCEPTION](#); SQLSTATE: [HY000](#)

Message: Unknown exception thrown in function %s.

- Error number: 3044; Symbol: [ER\\_STD\\_BAD\\_ALLOC\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Memory allocation error: %s in function %s.

- Error number: 3045; Symbol: [ER\\_STD\\_DOMAIN\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Domain error: %s in function %s.

- Error number: 3046; Symbol: [ER\\_STD\\_LENGTH\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Length error: %s in function %s.

- Error number: 3047; Symbol: [ER\\_STD\\_INVALID\\_ARGUMENT](#); SQLSTATE: [HY000](#)

Message: Invalid argument error: %s in function %s.

- Error number: 3048; Symbol: [ER\\_STD\\_OUT\\_OF\\_RANGE\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Out of range error: %s in function %s.

- Error number: 3049; Symbol: [ER\\_STD\\_OVERFLOW\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Overflow error: %s in function %s.

- Error number: 3050; Symbol: [ER\\_STD\\_RANGE\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Range error: %s in function %s.

- 
- Error number: 3051; Symbol: [ER\\_STD\\_UNDERFLOW\\_ERROR](#); SQLSTATE: HY000  
Message: Underflow error: %s in function %s.
  - Error number: 3052; Symbol: [ER\\_STD\\_LOGIC\\_ERROR](#); SQLSTATE: HY000  
Message: Logic error: %s in function %s.
  - Error number: 3053; Symbol: [ER\\_STD\\_RUNTIME\\_ERROR](#); SQLSTATE: HY000  
Message: Runtime error: %s in function %s.
  - Error number: 3054; Symbol: [ER\\_STD\\_UNKNOWN\\_EXCEPTION](#); SQLSTATE: HY000  
Message: Unknown exception: %s in function %s.
  - Error number: 3055; Symbol: [ER\\_GIS\\_DATA\\_WRONG\\_ENDIANNESS](#); SQLSTATE: HY000  
Message: Geometry byte string must be little endian.
  - Error number: 3056; Symbol: [ER\\_CHANGE\\_SOURCE\\_PASSWORD\\_LENGTH](#); SQLSTATE: HY000  
Message: The password provided for the replication user exceeds the maximum length of 32 characters
  - Error number: 3057; Symbol: [ER\\_USER\\_LOCK\\_WRONG\\_NAME](#); SQLSTATE: 42000  
Message: Incorrect user-level lock name '%s'. The name is empty, NULL, or can not be expressed in the current character-set.
  - Error number: 3058; Symbol: [ER\\_USER\\_LOCK\\_DEADLOCK](#); SQLSTATE: HY000  
Message: Deadlock found when trying to get user-level lock; try rolling back transaction/releasing locks and restarting lock acquisition.  
  
This error is returned when the metadata locking subsystem detects a deadlock for an attempt to acquire a named lock with [GET\\_LOCK](#).
  - Error number: 3059; Symbol: [ER\\_REPLACE\\_INACCESSIBLE\\_ROWS](#); SQLSTATE: HY000  
Message: REPLACE cannot be executed as it requires deleting rows that are not in the view
  - Error number: 3060; Symbol: [ER\\_ALTER\\_OPERATION\\_NOT\\_SUPPORTED\\_REASON\\_GIS](#); SQLSTATE: HY000  
Message: Do not support online operation on table with GIS index
  - Error number: 3061; Symbol: [ER\\_ILLEGAL\\_USER\\_VAR](#); SQLSTATE: 42000  
Message: User variable name '%s' is illegal
  - Error number: 3062; Symbol: [ER\\_GTID\\_MODE\\_OFF](#); SQLSTATE: HY000  
Message: Cannot %s when GTID\_MODE = OFF.
  - Error number: 3064; Symbol: [ER\\_INCORRECT\\_TYPE](#); SQLSTATE: HY000  
Message: Incorrect type for argument %s in function %s.
  - Error number: 3065; Symbol: [ER\\_FIELD\\_IN\\_ORDER\\_NOT\\_SELECT](#); SQLSTATE: HY000  
Message: Expression #%u of ORDER BY clause is not in SELECT list, references column '%s' which is not in SELECT list; this is incompatible with %s
-

- 
- Error number: 3066; Symbol: [ER\\_AGGREGATE\\_IN\\_ORDER\\_NOT\\_SELECT](#); SQLSTATE: HY000  
Message: Expression #%u of ORDER BY clause is not in SELECT list, contains aggregate function; this is incompatible with %s
  - Error number: 3067; Symbol: [ER\\_INVALID\\_RPL\\_WILD\\_TABLE\\_FILTER\\_PATTERN](#); SQLSTATE: HY000  
Message: Supplied filter list contains a value which is not in the required format 'db\_pattern.table\_pattern'
  - Error number: 3068; Symbol: [ER\\_NET\\_OK\\_PACKET\\_TOO\\_LARGE](#); SQLSTATE: 08S01  
Message: OK packet too large
  - Error number: 3069; Symbol: [ER\\_INVALID\\_JSON\\_DATA](#); SQLSTATE: HY000  
Message: Invalid JSON data provided to function %s: %s
  - Error number: 3070; Symbol: [ER\\_INVALID\\_GEOJSON\\_MISSING\\_MEMBER](#); SQLSTATE: HY000  
Message: Invalid GeoJSON data provided to function %s: Missing required member '%s'
  - Error number: 3071; Symbol: [ER\\_INVALID\\_GEOJSON\\_WRONG\\_TYPE](#); SQLSTATE: HY000  
Message: Invalid GeoJSON data provided to function %s: Member '%s' must be of type '%s'
  - Error number: 3072; Symbol: [ER\\_INVALID\\_GEOJSON\\_UNSPECIFIED](#); SQLSTATE: HY000  
Message: Invalid GeoJSON data provided to function %s
  - Error number: 3073; Symbol: [ER\\_DIMENSION\\_UNSUPPORTED](#); SQLSTATE: HY000  
Message: Unsupported number of coordinate dimensions in function %s: Found %u, expected %u
  - Error number: 3074; Symbol: [ER\\_REPLICA\\_CHANNEL\\_DOES\\_NOT\\_EXIST](#); SQLSTATE: HY000  
Message: Replica channel '%s' does not exist.
  - Error number: 3076; Symbol: [ER\\_REPLICA\\_CHANNEL\\_NAME\\_INVALID\\_OR\\_TOO\\_LONG](#); SQLSTATE: HY000  
Message: Couldn't create channel: Channel name is either invalid or too long.
  - Error number: 3077; Symbol: [ER\\_REPLICA\\_NEW\\_CHANNEL\\_WRONG\\_REPOSITORY](#); SQLSTATE: HY000  
Message: To have multiple channels, repository cannot be of type FILE; Please check the repository configuration and convert them to TABLE.
  - Error number: 3079; Symbol: [ER\\_REPLICA\\_MULTIPLE\\_CHANNELS\\_CMD](#); SQLSTATE: HY000  
Message: Multiple channels exist on the replica. Please provide channel name as an argument.
  - Error number: 3080; Symbol: [ER\\_REPLICA\\_MAX\\_CHANNELS\\_EXCEEDED](#); SQLSTATE: HY000  
Message: Maximum number of replication channels allowed exceeded.
  - Error number: 3081; Symbol: [ER\\_REPLICA\\_CHANNEL\\_MUST\\_STOP](#); SQLSTATE: HY000  
Message: This operation cannot be performed with running replication threads; run STOP REPLICA FOR CHANNEL '%s' first
  - Error number: 3082; Symbol: [ER\\_REPLICA\\_CHANNEL\\_NOT\\_RUNNING](#); SQLSTATE: HY000

---

Message: This operation requires running replication threads; configure replica and run START REPLICATION FOR CHANNEL '%s'

- Error number: 3083; Symbol: [ER\\_REPLICA\\_CHANNEL\\_WAS\\_RUNNING](#); SQLSTATE: HY000

Message: Replication thread(s) for channel '%s' are already running.

- Error number: 3084; Symbol: [ER\\_REPLICA\\_CHANNEL\\_WAS\\_NOT\\_RUNNING](#); SQLSTATE: HY000

Message: Replication thread(s) for channel '%s' are already stopped.

- Error number: 3085; Symbol: [ER\\_REPLICA\\_CHANNEL\\_SQL\\_THREAD\\_MUST\\_STOP](#); SQLSTATE: HY000

Message: This operation cannot be performed with a running replica sql thread; run STOP REPLICATION SQL\_THREAD FOR CHANNEL '%s' first.

- Error number: 3086; Symbol: [ER\\_REPLICA\\_CHANNEL\\_SQL\\_SKIP\\_COUNTER](#); SQLSTATE: HY000

Message: When sql\_replica\_skip\_counter > 0, it is not allowed to start more than one SQL thread by using 'START REPLICATION [SQL\_THREAD]'. Value of sql\_replica\_skip\_counter can only be used by one SQL thread at a time. Please use 'START REPLICATION [SQL\_THREAD] FOR CHANNEL' to start the SQL thread which will use the value of sql\_replica\_skip\_counter.

- Error number: 3087; Symbol: [ER\\_WRONG\\_FIELD\\_WITH\\_GROUP\\_V2](#); SQLSTATE: HY000

Message: Expression #%u of %s is not in GROUP BY clause and contains nonaggregated column '%s' which is not functionally dependent on columns in GROUP BY clause; this is incompatible with sql\_mode=only\_full\_group\_by

- Error number: 3088; Symbol: [ER\\_MIX\\_OF\\_GROUP\\_FUNC\\_AND\\_FIELDS\\_V2](#); SQLSTATE: HY000

Message: In aggregated query without GROUP BY, expression #%u of %s contains nonaggregated column '%s'; this is incompatible with sql\_mode=only\_full\_group\_by

- Error number: 3089; Symbol: [ER\\_WARN\\_DEPRECATED\\_SYSVAR\\_UPDATE](#); SQLSTATE: HY000

Message: Updating '%s' is deprecated. It will be made read-only in a future release.

- Error number: 3090; Symbol: [ER\\_WARN\\_DEPRECATED\\_SQLMODE](#); SQLSTATE: HY000

Message: Changing sql mode '%s' is deprecated. It will be removed in a future release.

- Error number: 3091; Symbol: [ER\\_CANNOT\\_LOG\\_PARTIAL\\_DROP\\_DATABASE\\_WITH\\_GTID](#); SQLSTATE: HY000

Message: DROP DATABASE failed; some tables may have been dropped but the database directory remains. The GTID has not been added to GTID\_EXECUTED and the statement was not written to the binary log. Fix this as follows: (1) remove all files from the database directory %s; (2) SET GTID\_NEXT='%s'; (3) DROP DATABASE `'%s`.

- Error number: 3092; Symbol: [ER\\_GROUP\\_REPLICATION\\_CONFIGURATION](#); SQLSTATE: HY000

Message: The server is not configured properly to be an active member of the group. Please see more details on error log.

- Error number: 3093; Symbol: [ER\\_GROUP\\_REPLICATION\\_RUNNING](#); SQLSTATE: HY000

Message: The START GROUP\_REPLICATION command failed since the group is already running.

- Error number: 3094; Symbol: [ER\\_GROUP\\_REPLICATION\\_APPLIER\\_INIT\\_ERROR](#); SQLSTATE: HY000

---

Message: The START GROUP\_REPLICATION command failed as the applier module failed to start.

- Error number: 3095; Symbol: ER\_GROUP\_REPLICATION\_STOP\_APPLIER\_THREAD\_TIMEOUT; SQLSTATE: HY000

Message: The STOP GROUP\_REPLICATION command execution is incomplete: The applier thread got the stop signal while it was busy. The applier thread will stop once the current task is complete.

- Error number: 3096; Symbol: ER\_GROUP\_REPLICATION\_COMMUNICATION\_LAYER\_SESSION\_ERROR; SQLSTATE: HY000

Message: The START GROUP\_REPLICATION command failed as there was an error when initializing the group communication layer.

- Error number: 3097; Symbol: ER\_GROUP\_REPLICATION\_COMMUNICATION\_LAYER\_JOIN\_ERROR; SQLSTATE: HY000

Message: The START GROUP\_REPLICATION command failed as there was an error when joining the communication group.

- Error number: 3098; Symbol: ER\_BEFORE\_DML\_VALIDATION\_ERROR; SQLSTATE: HY000

Message: The table does not comply with the requirements by an external plugin.

- Error number: 3099; Symbol: ER\_PREVENTS\_VARIABLE\_WITHOUT\_RBR; SQLSTATE: HY000

Message: Cannot change the value of variable %s without binary log format as ROW.

In 8.3.0: `transaction_write_set_extraction` option value is set and `binlog_format` is not ROW.

- Error number: 3100; Symbol: ER\_RUN\_HOOK\_ERROR; SQLSTATE: HY000

Message: Error on observer while running replication hook '%s'.

- Error number: 3101; Symbol: ER\_TRANSACTION\_ROLLBACK\_DURING\_COMMIT; SQLSTATE: 40000

Message: Plugin instructed the server to rollback the current transaction.

When using Group Replication, this means that a transaction failed the group certification process, due to one or more members detecting a potential conflict, and was thus rolled back. See [Group Replication](#).

- Error number: 3102; Symbol: ER\_GENERATED\_COLUMN\_FUNCTION\_IS\_NOT\_ALLOWED; SQLSTATE: HY000

Message: Expression of generated column '%s' contains a disallowed function.

- Error number: 3103; Symbol: ER\_UNSUPPORTED\_ALTER\_INPLACE\_ON\_VIRTUAL\_COLUMN; SQLSTATE: HY000

Message: INPLACE ADD or DROP of virtual columns cannot be combined with other ALTER TABLE actions

- Error number: 3104; Symbol: ER\_WRONG\_FK\_OPTION\_FOR\_GENERATED\_COLUMN; SQLSTATE: HY000

Message: Cannot define foreign key with %s clause on a generated column.

- Error number: 3105; Symbol: ER\_NON\_DEFAULT\_VALUE\_FOR\_GENERATED\_COLUMN; SQLSTATE: HY000

---

Message: The value specified for generated column '%s' in table '%s' is not allowed.

- Error number: 3106; Symbol: [ER\\_UNSUPPORTED\\_ACTION\\_ON\\_GENERATED\\_COLUMN](#); SQLSTATE: HY000

Message: '%s' is not supported for generated columns.

- Error number: 3107; Symbol: [ER\\_GENERATED\\_COLUMN\\_NON\\_PRIOR](#); SQLSTATE: HY000

Message: Generated column can refer only to generated columns defined prior to it.

To address this issue, change the table definition to define each generated column later than any generated columns to which it refers.

- Error number: 3108; Symbol: [ER\\_DEPENDENT\\_BY\\_GENERATED\\_COLUMN](#); SQLSTATE: HY000

Message: Column '%s' has a generated column dependency.

You cannot drop or rename a generated column if another column refers to it. You must either drop those columns as well, or redefine them not to refer to the generated column.

- Error number: 3109; Symbol: [ER\\_GENERATED\\_COLUMN\\_REF\\_AUTO\\_INC](#); SQLSTATE: HY000

Message: Generated column '%s' cannot refer to auto-increment column.

- Error number: 3110; Symbol: [ER\\_FEATURE\\_NOT\\_AVAILABLE](#); SQLSTATE: HY000

Message: The '%s' feature is not available; you need to remove '%s' or use MySQL built with '%s'

- Error number: 3111; Symbol: [ER\\_CANT\\_SET\\_GTID\\_MODE](#); SQLSTATE: HY000

Message: SET @@GLOBAL.GTID\_MODE = %s is not allowed because %s.

- Error number: 3112; Symbol: [ER\\_CANT\\_USE\\_AUTO\\_POSITION\\_WITH\\_GTID\\_MODE\\_OFF](#); SQLSTATE: HY000

Message: The replication receiver thread %s cannot start in AUTO\_POSITION mode: this server uses @@GLOBAL.GTID\_MODE = OFF.

- Error number: 3116; Symbol: [ER\\_CANT\\_ENFORCE\\_GTID\\_CONSISTENCY\\_WITH\\_ONGOING\\_GTID\\_VIOLATING\\_TX](#); SQLSTATE: HY000

Message: Cannot set ENFORCE\_GTID\_CONSISTENCY = ON because there are ongoing transactions that violate GTID consistency.

[ER\\_CANT\\_SET\\_ENFORCE\\_GTID\\_CONSISTENCY\\_ON\\_WITH\\_ONGOING\\_GTID\\_VIOLATING\\_TRANSACTIONS](#) was renamed to [ER\\_CANT\\_ENFORCE\\_GTID\\_CONSISTENCY\\_WITH\\_ONGOING\\_GTID\\_VIOLATING\\_TX](#).

- Error number: 3117; Symbol: [ER\\_ENFORCE\\_GTID\\_CONSISTENCY\\_WARN\\_WITH\\_ONGOING\\_GTID\\_VIOLATING\\_TX](#); SQLSTATE: HY000

Message: There are ongoing transactions that violate GTID consistency.

[ER\\_SET\\_ENFORCE\\_GTID\\_CONSISTENCY\\_WARN\\_WITH\\_ONGOING\\_GTID\\_VIOLATING\\_TRANSACTIONS](#) was renamed to [ER\\_ENFORCE\\_GTID\\_CONSISTENCY\\_WARN\\_WITH\\_ONGOING\\_GTID\\_VIOLATING\\_TX](#).

- 
- Error number: 3118; Symbol: [ER\\_ACCOUNT\\_HAS\\_BEEN\\_LOCKED](#); SQLSTATE: HY000  
Message: Access denied for user '%s'@'%s'. Account is locked.  
The account was locked with [CREATE USER ... ACCOUNT LOCK](#) or [ALTER USER ... ACCOUNT LOCK](#). An administrator can unlock it with [ALTER USER ... ACCOUNT UNLOCK](#).
  - Error number: 3119; Symbol: [ER\\_WRONG\\_TABLESPACE\\_NAME](#); SQLSTATE: 42000  
Message: Incorrect tablespace name `%s`
  - Error number: 3120; Symbol: [ER\\_TABLESPACE\\_IS\\_NOT\\_EMPTY](#); SQLSTATE: HY000  
Message: Tablespace `%s` is not empty.
  - Error number: 3121; Symbol: [ER\\_WRONG\\_FILE\\_NAME](#); SQLSTATE: HY000  
Message: Incorrect File Name '%s'.
  - Error number: 3122; Symbol: [ER\\_BOOST\\_GEOMETRY\\_INCONSISTENT\\_TURNS\\_EXCEPTION](#); SQLSTATE: HY000  
Message: Inconsistent intersection points.
  - Error number: 3123; Symbol: [ER\\_WARN\\_OPTIMIZER\\_HINT\\_SYNTAX\\_ERROR](#); SQLSTATE: HY000  
Message: Optimizer hint syntax error
  - Error number: 3124; Symbol: [ER\\_WARN\\_BAD\\_MAX\\_EXECUTION\\_TIME](#); SQLSTATE: HY000  
Message: Unsupported MAX\_EXECUTION\_TIME
  - Error number: 3125; Symbol: [ER\\_WARN\\_UNSUPPORTED\\_MAX\\_EXECUTION\\_TIME](#); SQLSTATE: HY000  
Message: MAX\_EXECUTION\_TIME hint is supported by top-level standalone SELECT statements only  
The [MAX\\_EXECUTION\\_TIME](#) optimizer hint is supported only for [SELECT](#) statements.
  - Error number: 3126; Symbol: [ER\\_WARN\\_CONFLICTING\\_HINT](#); SQLSTATE: HY000  
Message: Hint %s is ignored as conflicting/duplicated
  - Error number: 3127; Symbol: [ER\\_WARN\\_UNKNOWN\\_QB\\_NAME](#); SQLSTATE: HY000  
Message: Query block name %s is not found for %s hint
  - Error number: 3128; Symbol: [ER\\_UNRESOLVED\\_HINT\\_NAME](#); SQLSTATE: HY000  
Message: Unresolved name %s for %s hint
  - Error number: 3129; Symbol: [ER\\_WARN\\_ON\\_MODIFYING\\_GTID\\_EXECUTED\\_TABLE](#); SQLSTATE: HY000  
Message: Please do not modify the %s table. This is a mysql internal system table to store GTIDs for committed transactions. Modifying it can lead to an inconsistent GTID state.
  - Error number: 3130; Symbol: [ER\\_PLUGGABLE\\_PROTOCOL\\_COMMAND\\_NOT\\_SUPPORTED](#); SQLSTATE: HY000  
Message: Command not supported by pluggable protocols
  - Error number: 3131; Symbol: [ER\\_LOCKING\\_SERVICE\\_WRONG\\_NAME](#); SQLSTATE: 42000



---

Message: Incorrect locking service lock name '%s'.

A locking service name was specified as `NULL`, the empty string, or a string longer than 64 characters. Namespace and lock names must be non-`NULL`, nonempty, and no more than 64 characters long.

- Error number: 3132; Symbol: `ER_LOCKING_SERVICE_DEADLOCK`; SQLSTATE: `HY000`

Message: Deadlock found when trying to get locking service lock; try releasing locks and restarting lock acquisition.

- Error number: 3133; Symbol: `ER_LOCKING_SERVICE_TIMEOUT`; SQLSTATE: `HY000`

Message: Service lock wait timeout exceeded.

- Error number: 3134; Symbol: `ER_GIS_MAX_POINTS_IN_GEOMETRY_OVERFLOWED`; SQLSTATE: `HY000`

Message: Parameter %s exceeds the maximum number of points in a geometry (%lu) in function %s.

- Error number: 3135; Symbol: `ER_SQL_MODE_MERGED`; SQLSTATE: `HY000`

Message: 'NO\_ZERO\_DATE', 'NO\_ZERO\_IN\_DATE' and 'ERROR\_FOR\_DIVISION\_BY\_ZERO' sql modes should be used with strict mode. They will be merged with strict mode in a future release.

- Error number: 3136; Symbol: `ER_VTOKEN_PLUGIN_TOKEN_MISMATCH`; SQLSTATE: `HY000`

Message: Version token mismatch for %.\*s. Correct value %.\*s

The client has set its `version_tokens_session` system variable to the list of tokens it requires the server to match, but the server token list has at least one matching token name that has a value different from what the client requires. See [Version Tokens](#).

- Error number: 3137; Symbol: `ER_VTOKEN_PLUGIN_TOKEN_NOT_FOUND`; SQLSTATE: `HY000`

Message: Version token %.\*s not found.

The client has set its `version_tokens_session` system variable to the list of tokens it requires the server to match, but the server token list is missing at least one of those tokens. See [Version Tokens](#).

- Error number: 3138; Symbol: `ER_CANT_SET_VARIABLE_WHEN_OWNING_GTID`; SQLSTATE: `HY000`

Message: Variable %s cannot be changed by a client that owns a GTID. The client owns %s. Ownership is released on COMMIT or ROLLBACK.

- Error number: 3139; Symbol: `ER_REPLICA_CHANNEL_OPERATION_NOT_ALLOWED`; SQLSTATE: `HY000`

Message: %s cannot be performed on channel '%s'.

- Error number: 3140; Symbol: `ER_INVALID_JSON_TEXT`; SQLSTATE: `22032`

Message: Invalid JSON text: "%s" at position %u in value for column '%s'.

- Error number: 3141; Symbol: `ER_INVALID_JSON_TEXT_IN_PARAM`; SQLSTATE: `22032`

Message: Invalid JSON text in argument %u to function %s: "%s" at position %u.%s

- Error number: 3142; Symbol: `ER_INVALID_JSON_BINARY_DATA`; SQLSTATE: `HY000`

Message: The JSON binary value contains invalid data.

- 
- Error number: 3143; Symbol: [ER\\_INVALID\\_JSON\\_PATH](#); SQLSTATE: 42000  
Message: Invalid JSON path expression. The error is around character position %u.%s
  - Error number: 3144; Symbol: [ER\\_INVALID\\_JSON\\_CHARSET](#); SQLSTATE: 22032  
Message: Cannot create a JSON value from a string with CHARACTER SET '%s'.
  - Error number: 3145; Symbol: [ER\\_INVALID\\_JSON\\_CHARSET\\_IN\\_FUNCTION](#); SQLSTATE: 22032  
Message: Invalid JSON character data provided to function %s: '%s'; utf8 is required.
  - Error number: 3146; Symbol: [ER\\_INVALID\\_TYPE\\_FOR\\_JSON](#); SQLSTATE: 22032  
Message: Invalid data type for JSON data in argument %u to function %s; a JSON string or JSON type is required.
  - Error number: 3147; Symbol: [ER\\_INVALID\\_CAST\\_TO\\_JSON](#); SQLSTATE: 22032  
Message: Cannot CAST value to JSON.
  - Error number: 3148; Symbol: [ER\\_INVALID\\_JSON\\_PATH\\_CHARSET](#); SQLSTATE: 42000  
Message: A path expression must be encoded in the utf8 character set. The path expression '%s' is encoded in character set '%s'.
  - Error number: 3149; Symbol: [ER\\_INVALID\\_JSON\\_PATH\\_WILDCARD](#); SQLSTATE: 42000  
Message: In this situation, path expressions may not contain the \* and \*\* tokens or an array range.
  - Error number: 3150; Symbol: [ER\\_JSON\\_VALUE\\_TOO\\_BIG](#); SQLSTATE: 22032  
Message: The JSON value is too big to be stored in a JSON column.
  - Error number: 3151; Symbol: [ER\\_JSON\\_KEY\\_TOO\\_BIG](#); SQLSTATE: 22032  
Message: The JSON object contains a key name that is too long.
  - Error number: 3152; Symbol: [ER\\_JSON\\_USED\\_AS\\_KEY](#); SQLSTATE: 42000  
Message: JSON column '%s' supports indexing only via generated columns on a specified JSON path.
  - Error number: 3153; Symbol: [ER\\_JSON\\_VACUOUS\\_PATH](#); SQLSTATE: 42000  
Message: The path expression '\$' is not allowed in this context.
  - Error number: 3154; Symbol: [ER\\_JSON\\_BAD\\_ONE\\_OR\\_ALL\\_ARG](#); SQLSTATE: 42000  
Message: The oneOrAll argument to %s may take these values: 'one' or 'all'.
  - Error number: 3155; Symbol: [ER\\_NUMERIC\\_JSON\\_VALUE\\_OUT\\_OF\\_RANGE](#); SQLSTATE: 22003  
Message: Out of range JSON value for CAST to %s%s from column %s at row %ld
  - Error number: 3156; Symbol: [ER\\_INVALID\\_JSON\\_VALUE\\_FOR\\_CAST](#); SQLSTATE: 22018  
Message: Invalid JSON value for CAST to %s%s from column %s at row %ld
  - Error number: 3157; Symbol: [ER\\_JSON\\_DOCUMENT\\_TOO\\_DEEP](#); SQLSTATE: 22032  
Message: The JSON document exceeds the maximum depth.
  - Error number: 3158; Symbol: [ER\\_JSON\\_DOCUMENT\\_NULL\\_KEY](#); SQLSTATE: 22032

---

Message: JSON documents may not contain NULL member names.

- Error number: 3159; Symbol: `ER_SECURE_TRANSPORT_REQUIRED`; SQLSTATE: HY000

Message: Connections using insecure transport are prohibited while `--require_secure_transport=ON`.

With the `require_secure_transport` system variable, clients can connect only using secure transports. Qualifying connections are those using SSL, a Unix socket file, or shared memory.

- Error number: 3160; Symbol: `ER_NO_SECURE_TRANSPORTS_CONFIGURED`; SQLSTATE: HY000

Message: No secure transports (SSL or Shared Memory) are configured, unable to set `--require_secure_transport=ON`.

The `require_secure_transport` system variable cannot be enabled if the server does not support at least one secure transport. Configure the server with the required SSL keys/certificates to enable SSL connections, or enable the `shared_memory` system variable to enable shared-memory connections.

- Error number: 3161; Symbol: `ER_DISABLED_STORAGE_ENGINE`; SQLSTATE: HY000

Message: Storage engine %s is disabled (Table creation is disallowed).

An attempt was made to create a table or tablespace using a storage engine listed in the value of the `disabled_storage_engines` system variable, or to change an existing table or tablespace to such an engine. Choose a different storage engine.

- Error number: 3162; Symbol: `ER_USER_DOES_NOT_EXIST`; SQLSTATE: HY000

Message: Authorization ID %s does not exist.

- Error number: 3163; Symbol: `ER_USER_ALREADY_EXISTS`; SQLSTATE: HY000

Message: Authorization ID %s already exists.

- Error number: 3164; Symbol: `ER_AUDIT_API_ABORT`; SQLSTATE: HY000

Message: Aborted by Audit API ('%s';%d).

This error indicates that an audit plugin terminated execution of an event. The message typically indicates the event subclass name and a numeric status value.

- Error number: 3165; Symbol: `ER_INVALID_JSON_PATH_ARRAY_CELL`; SQLSTATE: 42000

Message: A path expression is not a path to a cell in an array.

- Error number: 3166; Symbol: `ER_BUFPOOL_RESIZE_INPROGRESS`; SQLSTATE: HY000

Message: Another buffer pool resize is already in progress.

- Error number: 3167; Symbol: `ER_FEATURE_DISABLED_SEE_DOC`; SQLSTATE: HY000

Message: The '%s' feature is disabled; see the documentation for '%s'

- Error number: 3168; Symbol: `ER_SERVER_ISNT_AVAILABLE`; SQLSTATE: HY000

Message: Server isn't available

- Error number: 3169; Symbol: `ER_SESSION_WAS_KILLED`; SQLSTATE: HY000

Message: Session was killed

- Error number: 3170; Symbol: `ER_CAPACITY_EXCEEDED`; SQLSTATE: HY000

---

Message: Memory capacity of %llu bytes for '%s' exceeded. %s

- Error number: 3171; Symbol: [ER\\_CAPACITY\\_EXCEEDED\\_IN\\_RANGE\\_OPTIMIZER](#); SQLSTATE: HY000

Message: Range optimization was not done for this query.

- Error number: 3173; Symbol: [ER\\_CANT\\_WAIT\\_FOR\\_EXECUTED\\_GTID\\_SET\\_WHILE\\_OWNING\\_A\\_GTID](#); SQLSTATE: HY000

Message: The client holds ownership of the GTID %s. Therefore, WAIT\_FOR\_EXECUTED\_GTID\_SET cannot wait for this GTID.

- Error number: 3174; Symbol: [ER\\_CANNOT\\_ADD\\_FOREIGN\\_BASE\\_COL\\_VIRTUAL](#); SQLSTATE: HY000

Message: Cannot add foreign key on the base column of indexed virtual column.

- Error number: 3175; Symbol: [ER\\_CANNOT\\_CREATE\\_VIRTUAL\\_INDEX\\_CONSTRAINT](#); SQLSTATE: HY000

Message: Cannot create index on virtual column whose base column has foreign constraint.

- Error number: 3176; Symbol: [ER\\_ERROR\\_ON\\_MODIFYING\\_GTID\\_EXECUTED\\_TABLE](#); SQLSTATE: HY000

Message: Please do not modify the %s table with an XA transaction. This is an internal system table used to store GTIDs for committed transactions. Although modifying it can lead to an inconsistent GTID state, if necessary you can modify it with a non-XA transaction.

- Error number: 3177; Symbol: [ER\\_LOCK\\_REFUSED\\_BY\\_ENGINE](#); SQLSTATE: HY000

Message: Lock acquisition refused by storage engine.

- Error number: 3178; Symbol: [ER\\_UNSUPPORTED\\_ALTER\\_ONLINE\\_ON\\_VIRTUAL\\_COLUMN](#); SQLSTATE: HY000

Message: ADD COLUMN col...VIRTUAL, ADD INDEX(col)

- Error number: 3179; Symbol: [ER\\_MASTER\\_KEY\\_ROTATION\\_NOT\\_SUPPORTED\\_BY\\_SE](#); SQLSTATE: HY000

Message: Master key rotation is not supported by storage engine.

- Error number: 3181; Symbol: [ER\\_MASTER\\_KEY\\_ROTATION\\_BINLOG\\_FAILED](#); SQLSTATE: HY000

Message: Write to binlog failed. However, master key rotation has been completed successfully.

- Error number: 3182; Symbol: [ER\\_MASTER\\_KEY\\_ROTATION\\_SE\\_UNAVAILABLE](#); SQLSTATE: HY000

Message: Storage engine is not available.

- Error number: 3183; Symbol: [ER\\_TABLESPACE\\_CANNOT\\_ENCRYPT](#); SQLSTATE: HY000

Message: This tablespace can't be encrypted.

- Error number: 3184; Symbol: [ER\\_INVALID\\_ENCRYPTION\\_OPTION](#); SQLSTATE: HY000

Message: Invalid encryption option.

- Error number: 3185; Symbol: [ER\\_CANNOT\\_FIND\\_KEY\\_IN\\_KEYRING](#); SQLSTATE: HY000

---

Message: Can't find master key from keyring, please check in the server log if a keyring is loaded and initialized successfully.

- Error number: 3186; Symbol: [ER\\_CAPACITY\\_EXCEEDED\\_IN\\_PARSER](#); SQLSTATE: HY000

Message: Parser bailed out for this query.

- Error number: 3187; Symbol: [ER\\_UNSUPPORTED\\_ALTER\\_ENCRYPTION\\_INPLACE](#); SQLSTATE: HY000

Message: Cannot alter encryption attribute by inplace algorithm.

- Error number: 3188; Symbol: [ER\\_KEYRING\\_UDF\\_KEYRING\\_SERVICE\\_ERROR](#); SQLSTATE: HY000

Message: Function '%s' failed because underlying keyring service returned an error. Please check if a keyring is installed and that provided arguments are valid for the keyring you are using.

- Error number: 3189; Symbol: [ER\\_USER\\_COLUMN\\_OLD\\_LENGTH](#); SQLSTATE: HY000

Message: It seems that your db schema is old. The %s column is 77 characters long and should be 93 characters long. Please perform the MySQL upgrade procedure.

- Error number: 3190; Symbol: [ER\\_CANT\\_RESET\\_SOURCE](#); SQLSTATE: HY000

Message: RESET BINARY LOGS AND GTIDS is not allowed because %s.

- Error number: 3191; Symbol: [ER\\_GROUP\\_REPLICATION\\_MAX\\_GROUP\\_SIZE](#); SQLSTATE: HY000

Message: The START GROUP\_REPLICATION command failed since the group already has 9 members.

- Error number: 3192; Symbol: [ER\\_CANNOT\\_ADD\\_FOREIGN\\_BASE\\_COL\\_STORED](#); SQLSTATE: HY000

Message: Cannot add foreign key on the base column of stored column.

- Error number: 3193; Symbol: [ER\\_TABLE\\_REFERENCED](#); SQLSTATE: HY000

Message: Cannot complete the operation because table is referenced by another connection.

- Error number: 3197; Symbol: [ER\\_XA\\_RETRY](#); SQLSTATE: HY000

Message: The resource manager is not able to commit the transaction branch at this time. Please retry later.

- Error number: 3198; Symbol: [ER\\_KEYRING\\_AWS\\_UDF\\_AWS\\_KMS\\_ERROR](#); SQLSTATE: HY000

Message: Function %s failed due to: %s.

- Error number: 3199; Symbol: [ER\\_BINLOG\\_UNSAFE\\_XA](#); SQLSTATE: HY000

Message: Statement is unsafe because it is being used inside a XA transaction. Concurrent XA transactions may deadlock on replicas when replicated using statements.

- Error number: 3200; Symbol: [ER\\_UDF\\_ERROR](#); SQLSTATE: HY000

Message: %s UDF failed; %s

- Error number: 3201; Symbol: [ER\\_KEYRING\\_MIGRATION\\_FAILURE](#); SQLSTATE: HY000

Message: Can not perform keyring migration : %s

- Error number: 3202; Symbol: [ER\\_KEYRING\\_ACCESS\\_DENIED\\_ERROR](#); SQLSTATE: 42000

---

Message: Access denied; you need %s privileges for this operation

- Error number: 3203; Symbol: [ER\\_KEYRING\\_MIGRATION\\_STATUS](#); SQLSTATE: HY000

Message: Keyring migration %s.

- Error number: 3218; Symbol: [ER\\_AUDIT\\_LOG\\_UDF\\_READ\\_INVALID\\_MAX\\_ARRAY\\_LENGTH\\_ARG\\_VALUE](#); SQLSTATE: HY000

Message: Invalid "max\_array\_length" argument value.

- Error number: 3231; Symbol: [ER\\_WRITE\\_SET\\_EXCEEDS\\_LIMIT](#); SQLSTATE: HY000

Message: The size of writeset data for the current transaction exceeds a limit imposed by an external component. If using Group Replication check 'group\_replication\_transaction\_size\_limit'.

- Error number: 3235; Symbol: [ER\\_AES\\_INVALID\\_KDF\\_NAME](#); SQLSTATE: HY000

Message: KDF method name is not valid. Please use hkdf or pbkdf2\_hmac method name

- Error number: 3236; Symbol: [ER\\_AES\\_INVALID\\_KDF\\_ITERATIONS](#); SQLSTATE: HY000

Message: For KDF method pbkdf2\_hmac iterations value less than 1000 or more than 65535 is not allowed due to security reasons. Please provide iterations >= 1000 and iterations < 65535

- Error number: 3237; Symbol: [WARN\\_AES\\_KEY\\_SIZE](#); SQLSTATE: HY000

Message: AES key size should be %d bytes length or secure KDF methods hkdf or pbkdf2\_hmac should be used, please provide exact AES key size or use KDF methods for better security.

- Error number: 3238; Symbol: [ER\\_AES\\_INVALID\\_KDF\\_OPTION\\_SIZE](#); SQLSTATE: HY000

Message: KDF option size is invalid, please provide valid size < %d bytes and not NULL

- Error number: 3500; Symbol: [ER\\_UNUNSUPPORT\\_COMPRESSED\\_TEMPORARY\\_TABLE](#); SQLSTATE: HY000

Message: CREATE TEMPORARY TABLE is not allowed with ROW\_FORMAT=COMPRESSED or KEY\_BLOCK\_SIZE.

- Error number: 3501; Symbol: [ER\\_ACL\\_OPERATION\\_FAILED](#); SQLSTATE: HY000

Message: The ACL operation failed due to the following error from SE: errcode %d - %s

- Error number: 3502; Symbol: [ER\\_UNUNSUPPORTED\\_INDEX\\_ALGORITHM](#); SQLSTATE: HY000

Message: This storage engine does not support the %s index algorithm, storage engine default was used instead.

- Error number: 3503; Symbol: [ER\\_NO\\_SUCH\\_DB](#); SQLSTATE: 42Y07

Message: Database '%s' doesn't exist

- Error number: 3504; Symbol: [ER\\_TOO\\_BIG\\_ENUM](#); SQLSTATE: HY000

Message: Too many enumeration values for column %s.

- Error number: 3505; Symbol: [ER\\_TOO\\_LONG\\_SET\\_ENUM\\_VALUE](#); SQLSTATE: HY000

Message: Too long enumeration/set value for column %s.

- Error number: 3506; Symbol: [ER\\_INVALID\\_DD\\_OBJECT](#); SQLSTATE: HY000

---

Message: %s dictionary object is invalid. (%s)

- Error number: 3507; Symbol: [ER\\_UPDATING\\_DD\\_TABLE](#); SQLSTATE: HY000

Message: Failed to update %s dictionary object.

- Error number: 3508; Symbol: [ER\\_INVALID\\_DD\\_OBJECT\\_ID](#); SQLSTATE: HY000

Message: Dictionary object id (%lu) does not exist.

- Error number: 3509; Symbol: [ER\\_INVALID\\_DD\\_OBJECT\\_NAME](#); SQLSTATE: HY000

Message: Dictionary object name '%s' is invalid. (%s)

- Error number: 3510; Symbol: [ER\\_TABLESPACE\\_MISSING\\_WITH\\_NAME](#); SQLSTATE: HY000

Message: Tablespace %s doesn't exist.

- Error number: 3511; Symbol: [ER\\_TOO\\_LONG\\_ROUTINE\\_COMMENT](#); SQLSTATE: HY000

Message: Comment for routine '%s' is too long (max = %lu)

- Error number: 3512; Symbol: [ER\\_SP\\_LOAD\\_FAILED](#); SQLSTATE: HY000

Message: Failed to load routine '%s'.

- Error number: 3513; Symbol: [ER\\_INVALID\\_BITWISE\\_OPERANDS\\_SIZE](#); SQLSTATE: HY000

Message: Binary operands of bitwise operators must be of equal length

- Error number: 3514; Symbol: [ER\\_INVALID\\_BITWISE\\_AGGREGATE\\_OPERANDS\\_SIZE](#); SQLSTATE: HY000

Message: Aggregate bitwise functions cannot accept arguments longer than 511 bytes; consider using the SUBSTRING() function

- Error number: 3515; Symbol: [ER\\_WARN\\_UNSUPPORTED\\_HINT](#); SQLSTATE: HY000

Message: Hints aren't supported in %s

- Error number: 3516; Symbol: [ER\\_UNEXPECTED\\_GEOMETRY\\_TYPE](#); SQLSTATE: 22S01

Message: %s value is a geometry of unexpected type %s in %s.

- Error number: 3517; Symbol: [ER\\_SRS\\_PARSE\\_ERROR](#); SQLSTATE: SR002

Message: Can't parse the spatial reference system definition of SRID %u.

- Error number: 3518; Symbol: [ER\\_SRS\\_PROJ\\_PARAMETER\\_MISSING](#); SQLSTATE: SR003

Message: The spatial reference system definition for SRID %u does not specify the mandatory %s (EPSG %u) projection parameter.

- Error number: 3519; Symbol: [ER\\_WARN\\_SRS\\_NOT\\_FOUND](#); SQLSTATE: 01000

Message: There's no spatial reference system with SRID %u.

- Error number: 3520; Symbol: [ER\\_SRS\\_NOT\\_CARTESIAN](#); SQLSTATE: 22S00

Message: Function %s is only defined for Cartesian spatial reference systems, but one of its arguments is in SRID %u, which is not Cartesian.

- Error number: 3521; Symbol: [ER\\_SRS\\_NOT\\_CARTESIAN\\_UNDEFINED](#); SQLSTATE: SR001

---

Message: Function %s is only defined for Cartesian spatial reference systems, but one of its arguments is in SRID %u, which has not been defined.

- Error number: 3522; Symbol: [ER\\_PK\\_INDEX\\_CANT\\_BE\\_INVISIBLE](#); SQLSTATE: HY000

Message: A primary key index cannot be invisible

- Error number: 3523; Symbol: [ER\\_UNKNOWN\\_AUTHID](#); SQLSTATE: HY000

Message: Unknown authorization ID `%s`@`%s`

- Error number: 3524; Symbol: [ER\\_FAILED\\_ROLE\\_GRANT](#); SQLSTATE: HY000

Message: Failed to grant %s` to %s

- Error number: 3525; Symbol: [ER\\_OPEN\\_ROLE\\_TABLES](#); SQLSTATE: HY000

Message: Failed to open the security system tables

- Error number: 3526; Symbol: [ER\\_FAILED\\_DEFAULT\\_ROLES](#); SQLSTATE: HY000

Message: Failed to set default roles

- Error number: 3527; Symbol: [ER\\_COMPONENTS\\_NO\\_SCHEME](#); SQLSTATE: HY000

Message: Cannot find schema in specified URN: '%s'.

- Error number: 3528; Symbol: [ER\\_COMPONENTS\\_NO\\_SCHEME\\_SERVICE](#); SQLSTATE: HY000

Message: Cannot acquire scheme load service implementation for schema '%s' in specified URN: '%s'.

- Error number: 3529; Symbol: [ER\\_COMPONENTS\\_CANT\\_LOAD](#); SQLSTATE: HY000

Message: Cannot load component from specified URN: '%s'.

- Error number: 3530; Symbol: [ER\\_ROLE\\_NOT\\_GRANTED](#); SQLSTATE: HY000

Message: `%s`@`%s` is not granted to `%s`@`%s`

- Error number: 3531; Symbol: [ER\\_FAILED\\_REVOKE\\_ROLE](#); SQLSTATE: HY000

Message: Could not revoke role from `%s`@`%s`

- Error number: 3532; Symbol: [ER\\_RENAME\\_ROLE](#); SQLSTATE: HY000

Message: Renaming of a role identifier is forbidden

- Error number: 3533; Symbol: [ER\\_COMPONENTS\\_CANT\\_ACQUIRE\\_SERVICE\\_IMPLEMENTATION](#); SQLSTATE: HY000

Message: Cannot acquire specified service implementation: '%s'.

- Error number: 3534; Symbol: [ER\\_COMPONENTS\\_CANT\\_SATISFY\\_DEPENDENCY](#); SQLSTATE: HY000

Message: Cannot satisfy dependency for service '%s' required by component '%s'.

- Error number: 3535; Symbol: [ER\\_COMPONENTS\\_LOAD\\_CANT\\_REGISTER\\_SERVICE\\_IMPLEMENTATION](#); SQLSTATE: HY000

Message: Cannot register service implementation '%s' provided by component '%s'.



- 
- Error number: 3536; Symbol: `ER_COMPONENTS_LOAD_CANT_INITIALIZE`; SQLSTATE: `HY000`  
Message: Initialization method provided by component '%s' failed.
  - Error number: 3537; Symbol: `ER_COMPONENTS_UNLOAD_NOT_LOADED`; SQLSTATE: `HY000`  
Message: Component specified by URN '%s' to unload has not been loaded before.
  - Error number: 3538; Symbol: `ER_COMPONENTS_UNLOAD_CANT_DEINITIALIZE`; SQLSTATE: `HY000`  
Message: De-initialization method provided by component '%s' failed.
  - Error number: 3539; Symbol: `ER_COMPONENTS_CANT_RELEASE_SERVICE`; SQLSTATE: `HY000`  
Message: Release of previously acquired service implementation failed.
  - Error number: 3540; Symbol: `ER_COMPONENTS_UNLOAD_CANT_UNREGISTER_SERVICE`; SQLSTATE: `HY000`  
Message: Unregistration of service implementation '%s' provided by component '%s' failed during unloading of the component.
  - Error number: 3541; Symbol: `ER_COMPONENTS_CANT_UNLOAD`; SQLSTATE: `HY000`  
Message: Cannot unload component from specified URN: '%s'.
  - Error number: 3542; Symbol: `ER_WARN_UNLOAD_THE_NOT_PERSISTED`; SQLSTATE: `HY000`  
Message: The Persistent Dynamic Loader was used to unload a component '%s', but it was not used to load that component before.
  - Error number: 3543; Symbol: `ER_COMPONENT_TABLE_INCORRECT`; SQLSTATE: `HY000`  
Message: The mysql.component table is missing or has an incorrect definition.
  - Error number: 3544; Symbol: `ER_COMPONENT_MANIPULATE_ROW_FAILED`; SQLSTATE: `HY000`  
Message: Failed to manipulate component '%s' persistence data. Error code %d from storage engine.
  - Error number: 3545; Symbol: `ER_COMPONENTS_UNLOAD_DUPLICATE_IN_GROUP`; SQLSTATE: `HY000`  
Message: The component with specified URN: '%s' was specified in group more than once.
  - Error number: 3546; Symbol: `ER_CANT_SET_GTID_PURGED_DUE_SETS_CONSTRAINTS`; SQLSTATE: `HY000`  
Message: @@GLOBAL.GTID\_PURGED cannot be changed: %s
  - Error number: 3547; Symbol: `ER_CANNOT_LOCK_USER_MANAGEMENT_CACHES`; SQLSTATE: `HY000`  
Message: Can not lock user management caches for processing.
  - Error number: 3548; Symbol: `ER_SRS_NOT_FOUND`; SQLSTATE: `SR001`  
Message: There's no spatial reference system with SRID %u.
  - Error number: 3549; Symbol: `ER_VARIABLE_NOT_PERSISTED`; SQLSTATE: `HY000`  
Message: Variables cannot be persisted. Please retry.

- 
- Error number: 3550; Symbol: [ER\\_IS\\_QUERY\\_INVALID\\_CLAUSE](#); SQLSTATE: HY000  
Message: Information schema queries do not support the '%s' clause.
  - Error number: 3551; Symbol: [ER\\_UNABLE\\_TO\\_STORE\\_STATISTICS](#); SQLSTATE: HY000  
Message: Unable to store dynamic %s statistics into data dictionary.
  - Error number: 3552; Symbol: [ER\\_NO\\_SYSTEM\\_SCHEMA\\_ACCESS](#); SQLSTATE: HY000  
Message: Access to system schema '%s' is rejected.
  - Error number: 3553; Symbol: [ER\\_NO\\_SYSTEM\\_TABLESPACE\\_ACCESS](#); SQLSTATE: HY000  
Message: Access to system tablespace '%s' is rejected.
  - Error number: 3554; Symbol: [ER\\_NO\\_SYSTEM\\_TABLE\\_ACCESS](#); SQLSTATE: HY000  
Message: Access to %s '%s.%s' is rejected.
  - Error number: 3555; Symbol: [ER\\_NO\\_SYSTEM\\_TABLE\\_ACCESS\\_FOR\\_DICTIONARY\\_TABLE](#); SQLSTATE: HY000  
Message: data dictionary table
  - Error number: 3556; Symbol: [ER\\_NO\\_SYSTEM\\_TABLE\\_ACCESS\\_FOR\\_SYSTEM\\_TABLE](#); SQLSTATE: HY000  
Message: system table
  - Error number: 3557; Symbol: [ER\\_NO\\_SYSTEM\\_TABLE\\_ACCESS\\_FOR\\_TABLE](#); SQLSTATE: HY000  
Message: table
  - Error number: 3558; Symbol: [ER\\_INVALID\\_OPTION\\_KEY](#); SQLSTATE: 22023  
Message: Invalid option key '%s' in function %s.
  - Error number: 3559; Symbol: [ER\\_INVALID\\_OPTION\\_VALUE](#); SQLSTATE: 22023  
Message: Invalid value '%s' for option '%s' in function '%s'.
  - Error number: 3560; Symbol: [ER\\_INVALID\\_OPTION\\_KEY\\_VALUE\\_PAIR](#); SQLSTATE: 22023  
Message: The string '%s' is not a valid key %c value pair in function %s.
  - Error number: 3561; Symbol: [ER\\_INVALID\\_OPTION\\_START\\_CHARACTER](#); SQLSTATE: 22023  
Message: The options argument in function %s starts with the invalid character '%c'.
  - Error number: 3562; Symbol: [ER\\_INVALID\\_OPTION\\_END\\_CHARACTER](#); SQLSTATE: 22023  
Message: The options argument in function %s ends with the invalid character '%c'.
  - Error number: 3563; Symbol: [ER\\_INVALID\\_OPTION\\_CHARACTERS](#); SQLSTATE: 22023  
Message: The options argument in function %s contains the invalid character sequence '%s'.
  - Error number: 3564; Symbol: [ER\\_DUPLICATE\\_OPTION\\_KEY](#); SQLSTATE: 22023  
Message: Duplicate option key '%s' in funtion '%s'.
  - Error number: 3565; Symbol: [ER\\_WARN\\_SRS\\_NOT\\_FOUND\\_AXIS\\_ORDER](#); SQLSTATE: 01000  
Message: There's no spatial reference system with SRID %u. The axis order is unknown.

- 
- Error number: 3566; Symbol: [ER\\_NO\\_ACCESS\\_TO\\_NATIVE\\_FCT](#); SQLSTATE: HY000  
Message: Access to native function '%s' is rejected.
  - Error number: 3567; Symbol: [ER\\_RESET\\_SOURCE\\_TO\\_VALUE\\_OUT\\_OF\\_RANGE](#); SQLSTATE: HY000  
Message: The requested value '%llu' for the next binary log index is out of range. Please use a value between '1' and '%lu'.
  - Error number: 3568; Symbol: [ER\\_UNRESOLVED\\_TABLE\\_LOCK](#); SQLSTATE: HY000  
Message: Unresolved table name %s in locking clause.
  - Error number: 3569; Symbol: [ER\\_DUPLICATE\\_TABLE\\_LOCK](#); SQLSTATE: HY000  
Message: Table %s appears in multiple locking clauses.
  - Error number: 3570; Symbol: [ER\\_BINLOG\\_UNSAFE\\_SKIP\\_LOCKED](#); SQLSTATE: HY000  
Message: Statement is unsafe because it uses SKIP LOCKED. The set of inserted values is non-deterministic.
  - Error number: 3571; Symbol: [ER\\_BINLOG\\_UNSAFE\\_NOWAIT](#); SQLSTATE: HY000  
Message: Statement is unsafe because it uses NOWAIT. Whether the command will succeed or fail is not deterministic.
  - Error number: 3572; Symbol: [ER\\_LOCK\\_NOWAIT](#); SQLSTATE: HY000  
Message: Statement aborted because lock(s) could not be acquired immediately and NOWAIT is set.
  - Error number: 3573; Symbol: [ER\\_CTE\\_RECURSIVE\\_REQUIRES\\_UNION](#); SQLSTATE: HY000  
Message: Recursive Common Table Expression '%s' should contain a UNION
  - Error number: 3574; Symbol: [ER\\_CTE\\_RECURSIVE\\_REQUIRES\\_NONRECURSIVE\\_FIRST](#); SQLSTATE: HY000  
Message: Recursive Common Table Expression '%s' should have one or more non-recursive query blocks followed by one or more recursive ones
  - Error number: 3575; Symbol: [ER\\_CTE\\_RECURSIVE\\_FORBIDS\\_AGGREGATION](#); SQLSTATE: HY000  
Message: Recursive Common Table Expression '%s' can contain neither aggregation nor window functions in recursive query block
  - Error number: 3576; Symbol: [ER\\_CTE\\_RECURSIVE\\_FORBIDDEN\\_JOIN\\_ORDER](#); SQLSTATE: HY000  
Message: In recursive query block of Recursive Common Table Expression '%s', the recursive table must neither be in the right argument of a LEFT JOIN, nor be forced to be non-first with join order hints
  - Error number: 3577; Symbol: [ER\\_CTE\\_RECURSIVE\\_REQUIRES\\_SINGLE\\_REFERENCE](#); SQLSTATE: HY000  
Message: In recursive query block of Recursive Common Table Expression '%s', the recursive table must be referenced only once, and not in any subquery
  - Error number: 3578; Symbol: [ER\\_SWITCH\\_TMP\\_ENGINE](#); SQLSTATE: HY000  
Message: '%s' requires @@internal\_tmp\_disk\_storage\_engine=InnoDB

- 
- Error number: 3579; Symbol: [ER\\_WINDOW\\_NO\\_SUCH\\_WINDOW](#); SQLSTATE: HY000  
Message: Window name '%s' is not defined.
  - Error number: 3580; Symbol: [ER\\_WINDOW\\_CIRCULARITY\\_IN\\_WINDOW\\_GRAPH](#); SQLSTATE: HY000  
Message: There is a circularity in the window dependency graph.
  - Error number: 3581; Symbol: [ER\\_WINDOW\\_NO\\_CHILD\\_PARTITIONING](#); SQLSTATE: HY000  
Message: A window which depends on another cannot define partitioning.
  - Error number: 3582; Symbol: [ER\\_WINDOW\\_NO\\_INHERIT\\_FRAME](#); SQLSTATE: HY000  
Message: Window '%s' has a frame definition, so cannot be referenced by another window.
  - Error number: 3583; Symbol: [ER\\_WINDOW\\_NO\\_REDEFINE\\_ORDER\\_BY](#); SQLSTATE: HY000  
Message: Window '%s' cannot inherit '%s' since both contain an ORDER BY clause.
  - Error number: 3584; Symbol: [ER\\_WINDOW\\_FRAME\\_START\\_ILLEGAL](#); SQLSTATE: HY000  
Message: Window '%s': frame start cannot be UNBOUNDED FOLLOWING.
  - Error number: 3585; Symbol: [ER\\_WINDOW\\_FRAME\\_END\\_ILLEGAL](#); SQLSTATE: HY000  
Message: Window '%s': frame end cannot be UNBOUNDED PRECEDING.
  - Error number: 3586; Symbol: [ER\\_WINDOW\\_FRAME\\_ILLEGAL](#); SQLSTATE: HY000  
Message: Window '%s': frame start or end is negative, NULL or of non-integral type
  - Error number: 3587; Symbol: [ER\\_WINDOW\\_RANGE\\_FRAME\\_ORDER\\_TYPE](#); SQLSTATE: HY000  
Message: Window '%s' with RANGE N PRECEDING/FOLLOWING frame requires exactly one ORDER BY expression, of numeric or temporal type
  - Error number: 3588; Symbol: [ER\\_WINDOW\\_RANGE\\_FRAME\\_TEMPORAL\\_TYPE](#); SQLSTATE: HY000  
Message: Window '%s' with RANGE frame has ORDER BY expression of datetime type. Only INTERVAL bound value allowed.
  - Error number: 3589; Symbol: [ER\\_WINDOW\\_RANGE\\_FRAME\\_NUMERIC\\_TYPE](#); SQLSTATE: HY000  
Message: Window '%s' with RANGE frame has ORDER BY expression of numeric type, INTERVAL bound value not allowed.
  - Error number: 3590; Symbol: [ER\\_WINDOW\\_RANGE\\_BOUND\\_NOT\\_CONSTANT](#); SQLSTATE: HY000  
Message: Window '%s' has a non-constant frame bound.
  - Error number: 3591; Symbol: [ER\\_WINDOW\\_DUPLICATE\\_NAME](#); SQLSTATE: HY000  
Message: Window '%s' is defined twice.
  - Error number: 3592; Symbol: [ER\\_WINDOW\\_ILLEGAL\\_ORDER\\_BY](#); SQLSTATE: HY000  
Message: Window '%s': ORDER BY or PARTITION BY uses legacy position indication which is not supported, use expression.
  - Error number: 3593; Symbol: [ER\\_WINDOW\\_INVALID\\_WINDOW\\_FUNC\\_USE](#); SQLSTATE: HY000  
Message: You cannot use the window function '%s' in this context.'

- 
- Error number: 3594; Symbol: [ER\\_WINDOW\\_INVALID\\_WINDOW\\_FUNC\\_ALIAS\\_USE](#); SQLSTATE: HY000  
Message: You cannot use the alias '%s' of an expression containing a window function in this context.'
  - Error number: 3595; Symbol: [ER\\_WINDOW\\_NESTED\\_WINDOW\\_FUNC\\_USE\\_IN\\_WINDOW\\_SPEC](#); SQLSTATE: HY000  
Message: You cannot nest a window function in the specification of window '%s'.
  - Error number: 3596; Symbol: [ER\\_WINDOW\\_ROWS\\_INTERVAL\\_USE](#); SQLSTATE: HY000  
Message: Window '%s': INTERVAL can only be used with RANGE frames.
  - Error number: 3597; Symbol: [ER\\_WINDOW\\_NO\\_GROUP\\_ORDER\\_UNUSED](#); SQLSTATE: HY000  
Message: ASC or DESC with GROUP BY isn't allowed with window functions; put ASC or DESC in ORDER BY
  - Error number: 3598; Symbol: [ER\\_WINDOW\\_EXPLAIN\\_JSON](#); SQLSTATE: HY000  
Message: To get information about window functions use EXPLAIN FORMAT=JSON
  - Error number: 3599; Symbol: [ER\\_WINDOW\\_FUNCTION\\_IGNORES\\_FRAME](#); SQLSTATE: HY000  
Message: Window function '%s' ignores the frame clause of window '%s' and aggregates over the whole partition
  - Error number: 3600; Symbol: [ER\\_WL9236\\_NOW\\_UNUSED](#); SQLSTATE: HY000  
Message: Windowing requires @@internal\_tmp\_mem\_storage\_engine=TempTable.
  - Error number: 3601; Symbol: [ER\\_INVALID\\_NO\\_OF\\_ARGS](#); SQLSTATE: HY000  
Message: Too many arguments for function %s: %lu; maximum allowed is %s.
  - Error number: 3602; Symbol: [ER\\_FIELD\\_IN\\_GROUPING\\_NOT\\_GROUP\\_BY](#); SQLSTATE: HY000  
Message: Argument #%u of GROUPING function is not in GROUP BY
  - Error number: 3603; Symbol: [ER\\_TOO\\_LONG\\_TABLESPACE\\_COMMENT](#); SQLSTATE: HY000  
Message: Comment for tablespace '%s' is too long (max = %lu)
  - Error number: 3604; Symbol: [ER\\_ENGINE\\_CANT\\_DROP\\_TABLE](#); SQLSTATE: HY000  
Message: Storage engine can't drop table '%s'
  - Error number: 3605; Symbol: [ER\\_ENGINE\\_CANT\\_DROP\\_MISSING\\_TABLE](#); SQLSTATE: HY000  
Message: Storage engine can't drop table '%s' because it is missing. Use DROP TABLE IF EXISTS to remove it from data-dictionary.
  - Error number: 3606; Symbol: [ER\\_TABLESPACE\\_DUP\\_FILENAME](#); SQLSTATE: HY000  
Message: Duplicate file name for tablespace '%s'
  - Error number: 3607; Symbol: [ER\\_DB\\_DROP\\_RMDIR2](#); SQLSTATE: HY000  
Message: Problem while dropping database. Can't remove database directory (%s). Please remove it manually.
  - Error number: 3608; Symbol: [ER\\_IMP\\_NO\\_FILES\\_MATCHED](#); SQLSTATE: HY000

---

Message: No SDI files matched the pattern '%s'

- Error number: 3609; Symbol: [ER\\_IMP\\_SCHEMA\\_DOES\\_NOT\\_EXIST](#); SQLSTATE: HY000

Message: Schema '%s', referenced in SDI, does not exist.

- Error number: 3610; Symbol: [ER\\_IMP\\_TABLE\\_ALREADY\\_EXISTS](#); SQLSTATE: HY000

Message: Table '%s.%s', referenced in SDI, already exists.

- Error number: 3611; Symbol: [ER\\_IMP\\_INCOMPATIBLE\\_MYSQLD\\_VERSION](#); SQLSTATE: HY000

Message: Imported mysqld\_version (%llu) is not compatible with current (%llu)

- Error number: 3612; Symbol: [ER\\_IMP\\_INCOMPATIBLE\\_DD\\_VERSION](#); SQLSTATE: HY000

Message: Imported dd version (%u) is not compatible with current (%u)

- Error number: 3613; Symbol: [ER\\_IMP\\_INCOMPATIBLE\\_SDI\\_VERSION](#); SQLSTATE: HY000

Message: Imported sdi version (%llu) is not compatible with current (%llu)

- Error number: 3614; Symbol: [ER\\_WARN\\_INVALID\\_HINT](#); SQLSTATE: HY000

Message: Invalid number of arguments for hint %s

- Error number: 3615; Symbol: [ER\\_VAR\\_DOES\\_NOT\\_EXIST](#); SQLSTATE: HY000

Message: Variable %s does not exist in persisted config file

- Error number: 3616; Symbol: [ER\\_LONGITUDE\\_OUT\\_OF\\_RANGE](#); SQLSTATE: 22S02

Message: Longitude %f is out of range in function %s. It must be within (%f, %f].

- Error number: 3617; Symbol: [ER\\_LATITUDE\\_OUT\\_OF\\_RANGE](#); SQLSTATE: 22S03

Message: Latitude %f is out of range in function %s. It must be within [%f, %f].

- Error number: 3618; Symbol: [ER\\_NOT\\_IMPLEMENTED\\_FOR\\_GEOGRAPHIC\\_SRS](#); SQLSTATE: 22S00

Message: %s(%s) has not been implemented for geographic spatial reference systems.

- Error number: 3619; Symbol: [ER\\_ILLEGAL\\_PRIVILEGE\\_LEVEL](#); SQLSTATE: HY000

Message: Illegal privilege level specified for %s

- Error number: 3620; Symbol: [ER\\_NO\\_SYSTEM\\_VIEW\\_ACCESS](#); SQLSTATE: HY000

Message: Access to system view INFORMATION\_SCHEMA.'%s' is rejected.

- Error number: 3621; Symbol: [ER\\_COMPONENT\\_FILTER\\_FLABBERGASTED](#); SQLSTATE: HY000

Message: The log-filter component "%s" got confused at "%s" ...

- Error number: 3622; Symbol: [ER\\_PART\\_EXPR\\_TOO\\_LONG](#); SQLSTATE: HY000

Message: Partitioning expression is too long.

- Error number: 3623; Symbol: [ER\\_UDF\\_DROP\\_DYNAMICALLY\\_REGISTERED](#); SQLSTATE: HY000

Message: DROP FUNCTION can't drop a dynamically registered user defined function

- Error number: 3624; Symbol: [ER\\_UNABLE\\_TO\\_STORE\\_COLUMN\\_STATISTICS](#); SQLSTATE: HY000

---

Message: Unable to store column statistics for column '%s' in table '%s'. '%s'

- Error number: 3625; Symbol: [ER\\_UNABLE\\_TO\\_UPDATE\\_COLUMN\\_STATISTICS](#); SQLSTATE: HY000

Message: Unable to update column statistics for column '%s' in table '%s'. '%s'

- Error number: 3626; Symbol: [ER\\_UNABLE\\_TO\\_DROP\\_COLUMN\\_STATISTICS](#); SQLSTATE: HY000

Message: Unable to remove column statistics for column '%s' in table '%s'. '%s'

- Error number: 3627; Symbol: [ER\\_UNABLE\\_TO\\_BUILD\\_HISTOGRAM](#); SQLSTATE: HY000

Message: Unable to build histogram statistics for column '%s' in table '%s'. '%s'

- Error number: 3628; Symbol: [ER\\_MANDATORY\\_ROLE](#); SQLSTATE: HY000

Message: The role %s is a mandatory role and can't be revoked or dropped. The restriction can be lifted by excluding the role identifier from the global variable mandatory\_roles.

- Error number: 3629; Symbol: [ER\\_MISSING\\_TABLESPACE\\_FILE](#); SQLSTATE: HY000

Message: Tablespace '%s' does not have a file named '%s'

- Error number: 3630; Symbol: [ER\\_PERSIST\\_ONLY\\_ACCESS\\_DENIED\\_ERROR](#); SQLSTATE: 42000

Message: Access denied; you need %s privileges for this operation

- Error number: 3631; Symbol: [ER\\_CMD\\_NEED\\_SUPER](#); SQLSTATE: HY000

Message: You need the SUPER privilege for command '%s'

- Error number: 3632; Symbol: [ER\\_PATH\\_IN\\_DATADIR](#); SQLSTATE: HY000

Message: Path is within the current data directory '%s'

- Error number: 3633; Symbol: [ER\\_CLONE\\_DDL\\_IN\\_PROGRESS](#); SQLSTATE: HY000

Message: Concurrent DDL is performed during clone operation. Please try again.

- Error number: 3634; Symbol: [ER\\_CLONE\\_TOO\\_MANY\\_CONCURRENT\\_CLONES](#); SQLSTATE: HY000

Message: Too many concurrent clone operations. Maximum allowed - %d.

- Error number: 3635; Symbol: [ER\\_APPLIER\\_LOG\\_EVENT\\_VALIDATION\\_ERROR](#); SQLSTATE: HY000

Message: The table in transaction %s does not comply with the requirements by an external plugin.

- Error number: 3636; Symbol: [ER\\_CTE\\_MAX\\_RECURSION\\_DEPTH](#); SQLSTATE: HY000

Message: Recursive query aborted after %u iterations. Try increasing @@cte\_max\_recursion\_depth to a larger value.

- Error number: 3637; Symbol: [ER\\_NOT\\_HINT\\_UPDATABLE\\_VARIABLE](#); SQLSTATE: HY000

Message: Variable %s cannot be set using SET\_VAR hint.

- Error number: 3638; Symbol: [ER\\_CREDENTIALS\\_CONTRADICT\\_TO\\_HISTORY](#); SQLSTATE: HY000

Message: Cannot use these credentials for '%.\*s@%.\*s' because they contradict the password history policy

- 
- Error number: 3639; Symbol: [ER\\_WARNING\\_PASSWORD\\_HISTORY\\_CLAUSES\\_VOID](#); SQLSTATE: HY000  
Message: Non-zero password history clauses ignored for user '%s'@'%s' as its authentication plugin %s does not support password history
  - Error number: 3640; Symbol: [ER\\_CLIENT\\_DOES\\_NOT\\_SUPPORT](#); SQLSTATE: HY000  
Message: The client doesn't support %s
  - Error number: 3641; Symbol: [ER\\_I\\_S\\_SKIPPED\\_TABLESPACE](#); SQLSTATE: HY000  
Message: Tablespace '%s' was skipped since its definition is being modified by concurrent DDL statement
  - Error number: 3642; Symbol: [ER\\_TABLESPACE\\_ENGINE\\_MISMATCH](#); SQLSTATE: HY000  
Message: Engine '%s' does not match stored engine '%s' for tablespace '%s'
  - Error number: 3643; Symbol: [ER\\_WRONG\\_SRID\\_FOR\\_COLUMN](#); SQLSTATE: HY000  
Message: The SRID of the geometry does not match the SRID of the column '%s'. The SRID of the geometry is %lu, but the SRID of the column is %lu. Consider changing the SRID of the geometry or the SRID property of the column.
  - Error number: 3644; Symbol: [ER\\_CANNOT\\_ALTER\\_SRID\\_DUE\\_TO\\_INDEX](#); SQLSTATE: HY000  
Message: The SRID specification on the column '%s' cannot be changed because there is a spatial index on the column. Please remove the spatial index before altering the SRID specification.
  - Error number: 3645; Symbol: [ER\\_WARN\\_BINLOG\\_PARTIAL\\_UPDATES\\_DISABLED](#); SQLSTATE: HY000  
Message: When %s, the option binlog\_row\_value\_options=%s will be ignored and updates will be written in full format to binary log.
  - Error number: 3647; Symbol: [ER\\_WARN\\_BINLOG\\_PARTIAL\\_UPDATES\\_SUGGESTS\\_PARTIAL\\_IMAGES](#); SQLSTATE: HY000  
Message: When %s, the option binlog\_row\_value\_options=%s will be used only for the after-image. Full values will be written in the before-image, so the saving in disk space due to binlog\_row\_value\_options is limited to less than 50%%.
  - Error number: 3648; Symbol: [ER\\_COULD\\_NOT\\_APPLY\\_JSON\\_DIFF](#); SQLSTATE: HY000  
Message: Could not apply JSON diff in table %.\*s, column %s.
  - Error number: 3649; Symbol: [ER\\_CORRUPTED\\_JSON\\_DIFF](#); SQLSTATE: HY000  
Message: Corrupted JSON diff for table %.\*s, column %s.
  - Error number: 3650; Symbol: [ER\\_RESOURCE\\_GROUP\\_EXISTS](#); SQLSTATE: HY000  
Message: Resource Group '%s' exists
  - Error number: 3651; Symbol: [ER\\_RESOURCE\\_GROUP\\_NOT\\_EXISTS](#); SQLSTATE: HY000  
Message: Resource Group '%s' does not exist.
  - Error number: 3652; Symbol: [ER\\_INVALID\\_VCPU\\_ID](#); SQLSTATE: HY000  
Message: Invalid cpu id %u
  - Error number: 3653; Symbol: [ER\\_INVALID\\_VCPU\\_RANGE](#); SQLSTATE: HY000



---

Message: Invalid VCPU range %u-%u

- Error number: 3654; Symbol: [ER\\_INVALID\\_THREAD\\_PRIORITY](#); SQLSTATE: HY000

Message: Invalid thread priority value %d for %s resource group %s. Allowed range is [%d, %d].

- Error number: 3655; Symbol: [ER\\_DISALLOWED\\_OPERATION](#); SQLSTATE: HY000

Message: %s operation is disallowed on %s

- Error number: 3656; Symbol: [ER\\_RESOURCE\\_GROUP\\_BUSY](#); SQLSTATE: HY000

Message: Resource group %s is busy.

- Error number: 3657; Symbol: [ER\\_RESOURCE\\_GROUP\\_DISABLED](#); SQLSTATE: HY000

Message: Resource group %s is disabled.

- Error number: 3658; Symbol: [ER\\_FEATURE\\_UNSUPPORTED](#); SQLSTATE: HY000

Message: Feature %s is unsupported (%s).

- Error number: 3659; Symbol: [ER\\_ATTRIBUTE\\_IGNORED](#); SQLSTATE: HY000

Message: Attribute %s is ignored (%s).

- Error number: 3660; Symbol: [ER\\_INVALID\\_THREAD\\_ID](#); SQLSTATE: HY000

Message: Invalid thread id (%llu).

- Error number: 3661; Symbol: [ER\\_RESOURCE\\_GROUP\\_BIND\\_FAILED](#); SQLSTATE: HY000

Message: Unable to bind resource group %s with thread id (%llu).(%)s).

- Error number: 3662; Symbol: [ER\\_INVALID\\_USE\\_OF\\_FORCE\\_OPTION](#); SQLSTATE: HY000

Message: Option FORCE invalid as DISABLE option is not specified.

- Error number: 3663; Symbol: [ER\\_GROUP\\_REPLICATION\\_COMMAND\\_FAILURE](#); SQLSTATE: HY000

Message: The %s command encountered a failure. %s

- Error number: 3664; Symbol: [ER\\_SDI\\_OPERATION\\_FAILED](#); SQLSTATE: HY000

Message: Failed to %s SDI '%s.%s' in tablespace '%s'.

- Error number: 3665; Symbol: [ER\\_MISSING\\_JSON\\_TABLE\\_VALUE](#); SQLSTATE: 22035

Message: Missing value for JSON\_TABLE column '%s'

- Error number: 3666; Symbol: [ER\\_WRONG\\_JSON\\_TABLE\\_VALUE](#); SQLSTATE: 2203F

Message: Can't store an array or an object in the scalar JSON\_TABLE column '%s'

- Error number: 3667; Symbol: [ER\\_TF\\_MUST\\_HAVE\\_ALIAS](#); SQLSTATE: 42000

Message: Every table function must have an alias

- Error number: 3668; Symbol: [ER\\_TF\\_FORBIDDEN\\_JOIN\\_TYPE](#); SQLSTATE: HY000

Message: INNER or LEFT JOIN must be used for LATERAL references made by '%s'

- Error number: 3669; Symbol: [ER\\_JT\\_VALUE\\_OUT\\_OF\\_RANGE](#); SQLSTATE: 22003

---

Message: Value is out of range for JSON\_TABLE's column '%s'

- Error number: 3670; Symbol: [ER\\_JT\\_MAX\\_NESTED\\_PATH](#); SQLSTATE: 42000

Message: More than supported %u NESTED PATHs were found in JSON\_TABLE '%s'

- Error number: 3671; Symbol: [ER\\_PASSWORD\\_EXPIRATION\\_NOT\\_SUPPORTED\\_BY\\_AUTH\\_METHOD](#); SQLSTATE: HY000

Message: The selected authentication method %.\*s does not support password expiration

- Error number: 3672; Symbol: [ER\\_INVALID\\_GEOJSON CRS\\_NOT\\_TOP\\_LEVEL](#); SQLSTATE: HY000

Message: Invalid GeoJSON data provided to function %s: Member 'crs' must be specified in the top level object.

- Error number: 3673; Symbol: [ER\\_BAD\\_NULL\\_ERROR\\_NOT\\_IGNORED](#); SQLSTATE: 23000

Message: Column '%s' cannot be null

- Error number: 3674; Symbol: [WARN\\_USELESS\\_SPATIAL\\_INDEX](#); SQLSTATE: HY000

Message: The spatial index on column '%s' will not be used by the query optimizer since the column does not have an SRID attribute. Consider adding an SRID attribute to the column.

- Error number: 3675; Symbol: [ER\\_DISK\\_FULL\\_NOWAIT](#); SQLSTATE: HY000

Message: Create table/tablespace '%s' failed, as disk is full

- Error number: 3676; Symbol: [ER\\_PARSE\\_ERROR\\_IN\\_DIGEST\\_FN](#); SQLSTATE: HY000

Message: Could not parse argument to digest function: "%s".

- Error number: 3677; Symbol: [ER\\_UNDISCLOSED\\_PARSE\\_ERROR\\_IN\\_DIGEST\\_FN](#); SQLSTATE: HY000

Message: Could not parse argument to digest function.

- Error number: 3678; Symbol: [ER\\_SCHEMA\\_DIR\\_EXISTS](#); SQLSTATE: HY000

Message: Schema directory '%s' already exists. This must be resolved manually (e.g. by moving the schema directory to another location).

- Error number: 3679; Symbol: [ER\\_SCHEMA\\_DIR\\_MISSING](#); SQLSTATE: HY000

Message: Schema directory '%s' does not exist

- Error number: 3680; Symbol: [ER\\_SCHEMA\\_DIR\\_CREATE\\_FAILED](#); SQLSTATE: HY000

Message: Failed to create schema directory '%s' (errno: %d - %s)

- Error number: 3681; Symbol: [ER\\_SCHEMA\\_DIR\\_UNKNOWN](#); SQLSTATE: HY000

Message: Schema '%s' does not exist, but schema directory '%s' was found. This must be resolved manually (e.g. by moving the schema directory to another location).

- Error number: 3682; Symbol: [ER\\_ONLY\\_IMPLEMENTED\\_FOR\\_SRID\\_0\\_AND\\_4326](#); SQLSTATE: 22S00

Message: Function %s is only defined for SRID 0 and SRID 4326.

- Error number: 3684; Symbol: [ER\\_REGEXP\\_BUFFER\\_OVERFLOW](#); SQLSTATE: HY000

---

Message: The result string is larger than the result buffer.

- Error number: 3685; Symbol: [ER\\_REGEXP\\_ILLEGAL\\_ARGUMENT](#); SQLSTATE: HY000  
Message: Illegal argument to a regular expression.
- Error number: 3686; Symbol: [ER\\_REGEXP\\_INDEX\\_OUTOFBOUNDS\\_ERROR](#); SQLSTATE: HY000  
Message: Index out of bounds in regular expression search.
- Error number: 3687; Symbol: [ER\\_REGEXP\\_INTERNAL\\_ERROR](#); SQLSTATE: HY000  
Message: Internal error in the regular expression library.
- Error number: 3688; Symbol: [ER\\_REGEXP\\_RULE\\_SYNTAX](#); SQLSTATE: HY000  
Message: Syntax error in regular expression on line %u, character %u.
- Error number: 3689; Symbol: [ER\\_REGEXP\\_BAD\\_ESCAPE\\_SEQUENCE](#); SQLSTATE: HY000  
Message: Unrecognized escape sequence in regular expression.
- Error number: 3690; Symbol: [ER\\_REGEXP\\_UNIMPLEMENTED](#); SQLSTATE: HY000  
Message: The regular expression contains a feature that is not implemented in this library version.
- Error number: 3691; Symbol: [ER\\_REGEXP\\_MISMATCHED\\_PAREN](#); SQLSTATE: HY000  
Message: Mismatched parenthesis in regular expression.
- Error number: 3692; Symbol: [ER\\_REGEXP\\_BAD\\_INTERVAL](#); SQLSTATE: HY000  
Message: Incorrect description of a {min,max} interval.
- Error number: 3693; Symbol: [ER\\_REGEXP\\_MAX\\_LT\\_MIN](#); SQLSTATE: HY000  
Message: The maximum is less than the minimum in a {min,max} interval.
- Error number: 3694; Symbol: [ER\\_REGEXP\\_INVALID\\_BACK\\_REF](#); SQLSTATE: HY000  
Message: Invalid back-reference in regular expression.
- Error number: 3695; Symbol: [ER\\_REGEXP\\_LOOK\\_BEHIND\\_LIMIT](#); SQLSTATE: HY000  
Message: The look-behind assertion exceeds the limit in regular expression.
- Error number: 3696; Symbol: [ER\\_REGEXP\\_MISSING\\_CLOSE\\_BRACKET](#); SQLSTATE: HY000  
Message: The regular expression contains an unclosed bracket expression.
- Error number: 3697; Symbol: [ER\\_REGEXP\\_INVALID\\_RANGE](#); SQLSTATE: HY000  
Message: The regular expression contains an [x-y] character range where x comes after y.
- Error number: 3698; Symbol: [ER\\_REGEXP\\_STACK\\_OVERFLOW](#); SQLSTATE: HY000  
Message: Overflow in the regular expression backtrack stack.
- Error number: 3699; Symbol: [ER\\_REGEXP\\_TIME\\_OUT](#); SQLSTATE: HY000  
Message: Timeout exceeded in regular expression match.
- Error number: 3700; Symbol: [ER\\_REGEXP\\_PATTERN\\_TOO\\_BIG](#); SQLSTATE: HY000  
Message: The regular expression pattern exceeds limits on size or complexity.

- 
- Error number: 3701; Symbol: [ER\\_CANT\\_SET\\_ERROR\\_LOG\\_SERVICE](#); SQLSTATE: HY000  
Message: Value for %s got confusing at or around "%s". Syntax may be wrong, component may not be INSTALLED, or a component that does not support instances may be listed more than once.
  - Error number: 3702; Symbol: [ER\\_EMPTY\\_PIPELINE\\_FOR\\_ERROR\\_LOG\\_SERVICE](#); SQLSTATE: HY000  
Message: Setting an empty %s pipeline disables error logging!
  - Error number: 3703; Symbol: [ER\\_COMPONENT\\_FILTER\\_DIAGNOSTICS](#); SQLSTATE: HY000  
Message: filter %s: %s
  - Error number: 3704; Symbol: [ER\\_NOT\\_IMPLEMENTED\\_FOR\\_CARTESIAN\\_SRS](#); SQLSTATE: 22S00  
Message: %s(%s) has not been implemented for Cartesian spatial reference systems.
  - Error number: 3705; Symbol: [ER\\_NOT\\_IMPLEMENTED\\_FOR\\_PROJECTED\\_SRS](#); SQLSTATE: 22S00  
Message: %s(%s) has not been implemented for projected spatial reference systems.
  - Error number: 3706; Symbol: [ER\\_NONPOSITIVE\\_RADIUS](#); SQLSTATE: 22003  
Message: Invalid radius provided to function %s: Radius must be greater than zero.
  - Error number: 3707; Symbol: [ER\\_RESTART\\_SERVER\\_FAILED](#); SQLSTATE: HY000  
Message: Restart server failed (%s).
  - Error number: 3708; Symbol: [ER\\_SRS\\_MISSING\\_MANDATORY\\_ATTRIBUTE](#); SQLSTATE: SR006  
Message: Missing mandatory attribute %s.
  - Error number: 3709; Symbol: [ER\\_SRS\\_MULTIPLE\\_ATTRIBUTE\\_DEFINITIONS](#); SQLSTATE: SR006  
Message: Multiple definitions of attribute %s.
  - Error number: 3710; Symbol: [ER\\_SRS\\_NAME\\_CANT\\_BE\\_EMPTY\\_OR\\_WHITESPACE](#); SQLSTATE: SR006  
Message: The spatial reference system name can't be an empty string or start or end with whitespace.
  - Error number: 3711; Symbol: [ER\\_SRS\\_ORGANIZATION\\_CANT\\_BE\\_EMPTY\\_OR\\_WHITESPACE](#); SQLSTATE: SR006  
Message: The organization name can't be an empty string or start or end with whitespace.
  - Error number: 3712; Symbol: [ER\\_SRS\\_ID\\_ALREADY\\_EXISTS](#); SQLSTATE: SR004  
Message: There is already a spatial reference system with SRID %u.
  - Error number: 3713; Symbol: [ER\\_WARN\\_SRS\\_ID\\_ALREADY\\_EXISTS](#); SQLSTATE: 01S00  
Message: There is already a spatial reference system with SRID %u.
  - Error number: 3714; Symbol: [ER\\_CANT\\_MODIFY\\_SRID\\_0](#); SQLSTATE: SR000  
Message: SRID 0 is not modifiable.
  - Error number: 3715; Symbol: [ER\\_WARN\\_RESERVED\\_SRID\\_RANGE](#); SQLSTATE: 01S01

---

Message: The SRID range [%u, %u] has been reserved for system use. SRSs in this range may be added, modified or removed without warning during upgrade.

- Error number: 3716; Symbol: [ER\\_CANT\\_MODIFY\\_SRS\\_USED\\_BY\\_COLUMN](#); SQLSTATE: SR005

Message: Can't modify SRID %u. There is at least one column depending on it.

- Error number: 3717; Symbol: [ER\\_SRS\\_INVALID\\_CHARACTER\\_IN\\_ATTRIBUTE](#); SQLSTATE: SR006

Message: Invalid character in attribute %s.

- Error number: 3718; Symbol: [ER\\_SRS\\_ATTRIBUTE\\_STRING\\_TOO\\_LONG](#); SQLSTATE: SR006

Message: Attribute %s is too long. The maximum length is %u characters.

- Error number: 3719; Symbol: [ER\\_DEPRECATED\\_UTF8\\_ALIAS](#); SQLSTATE: HY000

Message: 'utf8' is currently an alias for the character set UTF8MB3, but will be an alias for UTF8MB4 in a future release. Please consider using UTF8MB4 in order to be unambiguous.

- Error number: 3720; Symbol: [ER\\_DEPRECATED\\_NATIONAL](#); SQLSTATE: HY000

Message: NATIONAL/NCHAR/NVARCHAR implies the character set UTF8MB3, which will be replaced by UTF8MB4 in a future release. Please consider using CHAR(x) CHARACTER SET UTF8MB4 in order to be unambiguous.

- Error number: 3721; Symbol: [ER\\_INVALID\\_DEFAULT\\_UTF8MB4\\_COLLATION](#); SQLSTATE: HY000

Message: Invalid default collation %s: utf8mb4\_0900\_ai\_ci or utf8mb4\_general\_ci expected

- Error number: 3722; Symbol: [ER\\_UNABLE\\_TO\\_COLLECT\\_LOG\\_STATUS](#); SQLSTATE: HY000

Message: Unable to collect information for column '%s': %s.

- Error number: 3723; Symbol: [ER\\_RESERVED\\_TABLESPACE\\_NAME](#); SQLSTATE: HY000

Message: The table '%s' may not be created in the reserved tablespace '%s'.

- Error number: 3724; Symbol: [ER\\_UNABLE\\_TO\\_SET\\_OPTION](#); SQLSTATE: HY000

Message: This option cannot be set %s.

- Error number: 3725; Symbol: [ER\\_REPLICA\\_POSSIBLY\\_DIVERGED\\_AFTER\\_DDL](#); SQLSTATE: HY000

Message: A commit for an atomic DDL statement was unsuccessful on the source and the replica. The replica supports atomic DDL statements but the source does not, so the action taken by the replica and source might differ. Check that their states have not diverged before proceeding.

- Error number: 3726; Symbol: [ER\\_SRS\\_NOT\\_GEOGRAPHIC](#); SQLSTATE: 22S00

Message: Function %s is only defined for geographic spatial reference systems, but one of its arguments is in SRID %u, which is not geographic.

- Error number: 3727; Symbol: [ER\\_POLYGON\\_TOO\\_LARGE](#); SQLSTATE: 22023

Message: Function %s encountered a polygon that was too large. Polygons must cover less than half the planet.

- Error number: 3728; Symbol: [ER\\_SPATIAL\\_UNIQUE\\_INDEX](#); SQLSTATE: HY000

Message: Spatial indexes can't be primary or unique indexes.

- 
- Error number: 3729; Symbol: [ER\\_INDEX\\_TYPE\\_NOT\\_SUPPORTEDED\\_FOR\\_SPATIAL\\_INDEX](#); SQLSTATE: [HY000](#)  
Message: The index type %s is not supported for spatial indexes.
  - Error number: 3730; Symbol: [ER\\_FK\\_CANNOT\\_DROP\\_PARENT](#); SQLSTATE: [HY000](#)  
Message: Cannot drop table '%s' referenced by a foreign key constraint '%s' on table '%s'.
  - Error number: 3731; Symbol: [ER\\_GEOMETRY\\_PARAM\\_LONGITUDE\\_OUT\\_OF\\_RANGE](#); SQLSTATE: [22S02](#)  
Message: A parameter of function %s contains a geometry with longitude %f, which is out of range. It must be within (%f, %f].
  - Error number: 3732; Symbol: [ER\\_GEOMETRY\\_PARAM\\_LATITUDE\\_OUT\\_OF\\_RANGE](#); SQLSTATE: [22S03](#)  
Message: A parameter of function %s contains a geometry with latitude %f, which is out of range. It must be within [%f, %f].
  - Error number: 3733; Symbol: [ER\\_FK\\_CANNOT\\_USE\\_VIRTUAL\\_COLUMN](#); SQLSTATE: [HY000](#)  
Message: Foreign key '%s' uses virtual column '%s' which is not supported.
  - Error number: 3734; Symbol: [ER\\_FK\\_NO\\_COLUMN\\_PARENT](#); SQLSTATE: [HY000](#)  
Message: Failed to add the foreign key constraint. Missing column '%s' for constraint '%s' in the referenced table '%s'
  - Error number: 3735; Symbol: [ER\\_CANT\\_SET\\_ERROR\\_SUPPRESSION\\_LIST](#); SQLSTATE: [HY000](#)  
Message: %s: Could not add suppression rule for code "%s". Rule-set may be full, or code may not correspond to an error-log message.
  - Error number: 3736; Symbol: [ER\\_SRS\\_GEOGCS\\_INVALID\\_AXES](#); SQLSTATE: [SR002](#)  
Message: The spatial reference system definition for SRID %u specifies invalid geographic axes '%s' and '%s'. One axis must be NORTH or SOUTH and the other must be EAST or WEST.
  - Error number: 3737; Symbol: [ER\\_SRS\\_INVALID\\_SEMI\\_MAJOR\\_AXIS](#); SQLSTATE: [SR002](#)  
Message: The length of the semi-major axis must be a positive number.
  - Error number: 3738; Symbol: [ER\\_SRS\\_INVALID\\_INVERSE\\_FLATTENING](#); SQLSTATE: [SR002](#)  
Message: The inverse flattening must be larger than 1.0, or 0.0 if the ellipsoid is a sphere.
  - Error number: 3739; Symbol: [ER\\_SRS\\_INVALID\\_ANGULAR\\_UNIT](#); SQLSTATE: [SR002](#)  
Message: The angular unit conversion factor must be a positive number.
  - Error number: 3740; Symbol: [ER\\_SRS\\_INVALID\\_PRIME\\_MERIDIAN](#); SQLSTATE: [SR002](#)  
Message: The prime meridian must be within (-180, 180] degrees, specified in the SRS angular unit.
  - Error number: 3741; Symbol: [ER\\_TRANSFORM\\_SOURCE\\_SRS\\_NOT\\_SUPPORTED](#); SQLSTATE: [22S00](#)  
Message: Transformation from SRID %u is not supported.
  - Error number: 3742; Symbol: [ER\\_TRANSFORM\\_TARGET\\_SRS\\_NOT\\_SUPPORTED](#); SQLSTATE: [22S00](#)

---

Message: Transformation to SRID %u is not supported.

- Error number: 3743; Symbol: [ER\\_TRANSFORM\\_SOURCE\\_SRS\\_MISSING\\_TOWGS84](#); SQLSTATE: 22S00

Message: Transformation from SRID %u is not supported. The spatial reference system has no TOWGS84 clause.

- Error number: 3744; Symbol: [ER\\_TRANSFORM\\_TARGET\\_SRS\\_MISSING\\_TOWGS84](#); SQLSTATE: 22S00

Message: Transformation to SRID %u is not supported. The spatial reference system has no TOWGS84 clause.

- Error number: 3745; Symbol: [ER\\_TEMP\\_TABLE\\_PREVENTS\\_SWITCH\\_SESSION\\_BINLOG\\_FORMAT](#); SQLSTATE: HY000

Message: Changing @@session.binlog\_format is disallowed when the session has open temporary table(s). You could wait until these temporary table(s) are dropped and try again.

- Error number: 3746; Symbol: [ER\\_TEMP\\_TABLE\\_PREVENTS\\_SWITCH\\_GLOBAL\\_BINLOG\\_FORMAT](#); SQLSTATE: HY000

Message: Changing @@global.binlog\_format or @@persist.binlog\_format is disallowed when any replication channel has open temporary table(s). You could wait until Replica\_open\_temp\_tables = 0 and try again

- Error number: 3747; Symbol: [ER\\_RUNNING\\_APPLIER\\_PREVENTS\\_SWITCH\\_GLOBAL\\_BINLOG\\_FORMAT](#); SQLSTATE: HY000

Message: Changing @@global.binlog\_format or @@persist.binlog\_format is disallowed when any replication channel applier thread is running. You could execute STOP REPLICAS SQL\_THREAD and try again.

- Error number: 3748; Symbol: [ER\\_CLIENT\\_GTID\\_UNSAFE\\_CREATE\\_DROP\\_TEMP\\_TABLE\\_IN\\_TRX\\_IN\\_SBR](#); SQLSTATE: HY000

Message: Statement violates GTID consistency: CREATE TEMPORARY TABLE and DROP TEMPORARY TABLE are not allowed inside a transaction or inside a procedure in a transactional context when @@session.binlog\_format=STATEMENT.

- Error number: 3750; Symbol: [ER\\_TABLE\\_WITHOUT\\_PK](#); SQLSTATE: HY000

Message: Unable to create or change a table without a primary key, when the system variable 'sql\_require\_primary\_key' is set. Add a primary key to the table or unset this variable to avoid this message. Note that tables without a primary key can cause performance problems in row-based replication, so please consult your DBA before changing this setting.

- Error number: 3751; Symbol: [ER\\_WARN\\_DATA\\_TRUNCATED\\_FUNCTIONAL\\_INDEX](#); SQLSTATE: 01000

Message: Data truncated for functional index '%s' at row %ld

- Error number: 3752; Symbol: [ER\\_WARN\\_DATA\\_OUT\\_OF\\_RANGE\\_FUNCTIONAL\\_INDEX](#); SQLSTATE: 22003

Message: Value is out of range for functional index '%s' at row %ld

- Error number: 3753; Symbol: [ER\\_FUNCTIONAL\\_INDEX\\_ON\\_JSON\\_OR\\_GEOMETRY\\_FUNCTION](#); SQLSTATE: 42000

Message: Cannot create a functional index on a function that returns a JSON or GEOMETRY value.

- 
- Error number: 3754; Symbol: [ER\\_FUNCTIONAL\\_INDEX\\_REF\\_AUTO\\_INCREMENT](#); SQLSTATE: HY000  
Message: Functional index '%s' cannot refer to an auto-increment column.
  - Error number: 3755; Symbol: [ER\\_CANNOT\\_DROP\\_COLUMN\\_FUNCTIONAL\\_INDEX](#); SQLSTATE: HY000  
Message: Cannot drop column '%s' because it is used by a functional index. In order to drop the column, you must remove the functional index.
  - Error number: 3756; Symbol: [ER\\_FUNCTIONAL\\_INDEX\\_PRIMARY\\_KEY](#); SQLSTATE: HY000  
Message: The primary key cannot be a functional index
  - Error number: 3757; Symbol: [ER\\_FUNCTIONAL\\_INDEX\\_ON\\_LOB](#); SQLSTATE: HY000  
Message: Cannot create a functional index on an expression that returns a BLOB or TEXT. Please consider using CAST.
  - Error number: 3758; Symbol: [ER\\_FUNCTIONAL\\_INDEX\\_FUNCTION\\_IS\\_NOT\\_ALLOWED](#); SQLSTATE: HY000  
Message: Expression of functional index '%s' contains a disallowed function.
  - Error number: 3759; Symbol: [ER\\_FULLTEXT\\_FUNCTIONAL\\_INDEX](#); SQLSTATE: HY000  
Message: Fulltext functional index is not supported.
  - Error number: 3760; Symbol: [ER\\_SPATIAL\\_FUNCTIONAL\\_INDEX](#); SQLSTATE: HY000  
Message: Spatial functional index is not supported.
  - Error number: 3761; Symbol: [ER\\_WRONG\\_KEY\\_COLUMN\\_FUNCTIONAL\\_INDEX](#); SQLSTATE: HY000  
Message: The used storage engine cannot index the expression '%s'.
  - Error number: 3762; Symbol: [ER\\_FUNCTIONAL\\_INDEX\\_ON\\_FIELD](#); SQLSTATE: HY000  
Message: Functional index on a column is not supported. Consider using a regular index instead.
  - Error number: 3763; Symbol: [ER\\_GENERATED\\_COLUMN\\_NAMED\\_FUNCTION\\_IS\\_NOT\\_ALLOWED](#); SQLSTATE: HY000  
Message: Expression of generated column '%s' contains a disallowed function: %s.
  - Error number: 3764; Symbol: [ER\\_GENERATED\\_COLUMN\\_ROW\\_VALUE](#); SQLSTATE: HY000  
Message: Expression of generated column '%s' cannot refer to a row value.
  - Error number: 3765; Symbol: [ER\\_GENERATED\\_COLUMN\\_VARIABLES](#); SQLSTATE: HY000  
Message: Expression of generated column '%s' cannot refer user or system variables.
  - Error number: 3766; Symbol: [ER\\_DEPENDENT\\_BY\\_DEFAULT\\_GENERATED\\_VALUE](#); SQLSTATE: HY000  
Message: Column '%s' of table '%s' has a default value expression dependency and cannot be dropped or renamed.
  - Error number: 3767; Symbol: [ER\\_DEFAULT\\_VAL\\_GENERATED\\_NON\\_PRIOR](#); SQLSTATE: HY000  
Message: Default value expression of column '%s' cannot refer to a column defined after it if that column is a generated column or has an expression as default value.



- 
- Error number: 3768; Symbol: [ER\\_DEFAULT\\_VAL\\_GENERATED\\_REF\\_AUTO\\_INC](#); SQLSTATE: HY000  
Message: Default value expression of column '%s' cannot refer to an auto-increment column.
  - Error number: 3769; Symbol: [ER\\_DEFAULT\\_VAL\\_GENERATED\\_FUNCTION\\_IS\\_NOT\\_ALLOWED](#); SQLSTATE: HY000  
Message: Default value expression of column '%s' contains a disallowed function.
  - Error number: 3770; Symbol: [ER\\_DEFAULT\\_VAL\\_GENERATED\\_NAMED\\_FUNCTION\\_IS\\_NOT\\_ALLOWED](#); SQLSTATE: HY000  
Message: Default value expression of column '%s' contains a disallowed function: %s.
  - Error number: 3771; Symbol: [ER\\_DEFAULT\\_VAL\\_GENERATED\\_ROW\\_VALUE](#); SQLSTATE: HY000  
Message: Default value expression of column '%s' cannot refer to a row value.
  - Error number: 3772; Symbol: [ER\\_DEFAULT\\_VAL\\_GENERATED\\_VARIABLES](#); SQLSTATE: HY000  
Message: Default value expression of column '%s' cannot refer user or system variables.
  - Error number: 3773; Symbol: [ER\\_DEFAULT\\_AS\\_VAL\\_GENERATED](#); SQLSTATE: HY000  
Message: DEFAULT function cannot be used with default value expressions
  - Error number: 3774; Symbol: [ER\\_UNSUPPORTED\\_ACTION\\_ON\\_DEFAULT\\_VAL\\_GENERATED](#); SQLSTATE: HY000  
Message: '%s' is not supported for default value expressions.
  - Error number: 3775; Symbol: [ER\\_GTID\\_UNSAFE\\_ALTER\\_ADD\\_COL\\_WITH\\_DEFAULT\\_EXPRESSION](#); SQLSTATE: HY000  
Message: Statement violates GTID consistency: ALTER TABLE ... ADD COLUMN .. with expression as DEFAULT.
  - Error number: 3776; Symbol: [ER\\_FK\\_CANNOT\\_CHANGE\\_ENGINE](#); SQLSTATE: HY000  
Message: Cannot change table's storage engine because the table participates in a foreign key constraint.
  - Error number: 3777; Symbol: [ER\\_WARN\\_DEPRECATED\\_USER\\_SET\\_EXPR](#); SQLSTATE: HY000  
Message: Setting user variables within expressions is deprecated and will be removed in a future release. Consider alternatives: 'SET variable=expression, ...', or 'SELECT expression(s) INTO variables(s)'.
  - Error number: 3778; Symbol: [ER\\_WARN\\_DEPRECATED\\_UTF8MB3\\_COLLATION](#); SQLSTATE: HY000  
Message: '%s' is a collation of the deprecated character set UTF8MB3. Please consider using UTF8MB4 with an appropriate collation instead.
  - Error number: 3779; Symbol: [ER\\_WARN\\_DEPRECATED\\_NESTED\\_COMMENT\\_SYNTAX](#); SQLSTATE: HY000  
Message: Nested comment syntax is deprecated and will be removed in a future release.
  - Error number: 3780; Symbol: [ER\\_FK\\_INCOMPATIBLE\\_COLUMNS](#); SQLSTATE: HY000  
Message: Referencing column '%s' and referenced column '%s' in foreign key constraint '%s' are incompatible.
-

- 
- Error number: 3781; Symbol: `ER_GR_HOLD_WAIT_TIMEOUT`; SQLSTATE: `HY000`  
Message: Timeout exceeded for held statement while new Group Replication primary member is applying backlog.
  - Error number: 3782; Symbol: `ER_GR_HOLD_KILLED`; SQLSTATE: `HY000`  
Message: Held statement aborted because Group Replication plugin got shut down or thread was killed while new primary member was applying backlog.
  - Error number: 3783; Symbol: `ER_GR_HOLD_MEMBER_STATUS_ERROR`; SQLSTATE: `HY000`  
Message: Held statement was aborted due to member being in error state, while backlog is being applied during Group Replication primary election.
  - Error number: 3784; Symbol: `ER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY`; SQLSTATE: `HY000`  
Message: Failed to fetch key from keyring, please check if keyring is loaded.
  - Error number: 3785; Symbol: `ER_RPL_ENCRYPTION_KEY_NOT_FOUND`; SQLSTATE: `HY000`  
Message: Can't find key from keyring, please check in the server log if a keyring is loaded and initialized successfully.
  - Error number: 3786; Symbol: `ER_RPL_ENCRYPTION_KEYRING_INVALID_KEY`; SQLSTATE: `HY000`  
Message: Fetched an invalid key from keyring.
  - Error number: 3787; Symbol: `ER_RPL_ENCRYPTION_HEADER_ERROR`; SQLSTATE: `HY000`  
Message: Error reading a replication log encryption header: %s.
  - Error number: 3788; Symbol: `ER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS`; SQLSTATE: `HY000`  
Message: Failed to rotate some logs after changing binlog encryption settings. Please fix the problem and rotate the logs manually.
  - Error number: 3789; Symbol: `ER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED`; SQLSTATE: `HY000`  
Message: Key %s exists unexpected.
  - Error number: 3790; Symbol: `ER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY`; SQLSTATE: `HY000`  
Message: Failed to generate key, please check if keyring is loaded.
  - Error number: 3791; Symbol: `ER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY`; SQLSTATE: `HY000`  
Message: Failed to store key, please check if keyring is loaded.
  - Error number: 3792; Symbol: `ER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY`; SQLSTATE: `HY000`  
Message: Failed to remove key, please check if keyring is loaded.
  - Error number: 3793; Symbol: `ER_RPL_ENCRYPTION_UNABLE_TO_CHANGE_OPTION`; SQLSTATE: `HY000`  
Message: Failed to change binlog\_encryption value. %s.

- 
- Error number: 3794; Symbol: `ER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED`; SQLSTATE: `HY000`  
Message: Unable to recover binlog encryption master key, please check if keyring is loaded.
  - Error number: 3795; Symbol: `ER_SLOW_LOG_MODE_IGNORED_WHEN_NOT_LOGGING_TO_FILE`; SQLSTATE: `HY000`  
Message: slow query log file format changed as requested, but setting will have no effect when not actually logging to a file.
  - Error number: 3796; Symbol: `ER_GRP_TRX_CONSISTENCY_NOT_ALLOWED`; SQLSTATE: `HY000`  
Message: The option group\_replication\_consistency cannot be used on the current member state.
  - Error number: 3797; Symbol: `ER_GRP_TRX_CONSISTENCY_BEFORE`; SQLSTATE: `HY000`  
Message: Error while waiting for group transactions commit on group\_replication\_consistency='BEFORE'.
  - Error number: 3798; Symbol: `ER_GRP_TRX_CONSISTENCY_AFTER_ON_TRX_BEGIN`; SQLSTATE: `HY000`  
Message: Error while waiting for transactions with group\_replication\_consistency='AFTER' to commit.
  - Error number: 3799; Symbol: `ER_GRP_TRX_CONSISTENCY_BEGIN_NOT_ALLOWED`; SQLSTATE: `HY000`  
Message: The Group Replication plugin is stopping, therefore new transactions are not allowed to start.
  - Error number: 3800; Symbol: `ER_FUNCTIONAL_INDEX_ROW_VALUE_IS_NOT_ALLOWED`; SQLSTATE: `HY000`  
Message: Expression of functional index '%s' cannot refer to a row value.
  - Error number: 3801; Symbol: `ER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT`; SQLSTATE: `HY000`  
Message: Failed to encrypt content to write into binlog file: %s.
  - Error number: 3802; Symbol: `ER_PAGE_TRACKING_NOT_STARTED`; SQLSTATE: `HY000`  
Message: Page Tracking is not started yet.
  - Error number: 3803; Symbol: `ER_PAGE_TRACKING_RANGE_NOT_TRACKED`; SQLSTATE: `HY000`  
Message: Tracking was not enabled for the LSN range specified
  - Error number: 3804; Symbol: `ER_PAGE_TRACKING_CANNOT_PURGE`; SQLSTATE: `HY000`  
Message: Cannot purge data when concurrent clone is in progress. Try later.
  - Error number: 3805; Symbol: `ER_RPL_ENCRYPTION_CANNOT_ROTATE_BINLOG_MASTER_KEY`; SQLSTATE: `HY000`  
Message: Cannot rotate binary log master key when 'binlog-encryption' is off.
  - Error number: 3806; Symbol: `ER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATION`; SQLSTATE: `HY000`  
Message: Unable to recover binary log master key, the combination of new\_master\_key\_seqno=%u, master\_key\_seqno=%u and old\_master\_key\_seqno=%u are wrong.
-

- 
- Error number: 3807; Symbol: [ER\\_BINLOG\\_MASTER\\_KEY\\_ROTATION\\_FAIL\\_TO\\_OPERATE\\_KEY](#); SQLSTATE: HY000  
Message: Failed to operate binary log master key on keyring, please check if keyring is loaded. The statement had no effect: the old binary log master key is still in use, the keyring, binary and relay log files are unchanged, and the server could not start using a new binary log master key for encrypting new binary and relay log files.
  - Error number: 3808; Symbol: [ER\\_BINLOG\\_MASTER\\_KEY\\_ROTATION\\_FAIL\\_TO\\_ROTATE\\_LOGS](#); SQLSTATE: HY000  
Message: Failed to rotate one or more binary or relay log files. A new binary log master key was generated and will be used to encrypt new binary and relay log files. There may still exist binary or relay log files using the previous binary log master key.
  - Error number: 3809; Symbol: [ER\\_BINLOG\\_MASTER\\_KEY\\_ROTATION\\_FAIL\\_TO\\_REENCRYPT\\_LOG](#); SQLSTATE: HY000  
Message: %s. A new binary log master key was generated and will be used to encrypt new binary and relay log files. There may still exist binary or relay log files using the previous binary log master key.
  - Error number: 3810; Symbol: [ER\\_BINLOG\\_MASTER\\_KEY\\_ROTATION\\_FAIL\\_TO\\_CLEANUP\\_UNUSED\\_KEYS](#); SQLSTATE: HY000  
Message: Failed to remove unused binary log encryption keys from the keyring, please check if keyring is loaded. The unused binary log encryption keys may still exist in the keyring, and they will be removed upon server restart or next 'ALTER INSTANCE ROTATE BINLOG MASTER KEY' execution.
  - Error number: 3811; Symbol: [ER\\_BINLOG\\_MASTER\\_KEY\\_ROTATION\\_FAIL\\_TO\\_CLEANUP\\_AUX\\_KEY](#); SQLSTATE: HY000  
Message: Failed to remove auxiliary binary log encryption key from keyring, please check if keyring is loaded. The cleanup of the binary log master key rotation process did not finish as expected and the cleanup will take place upon server restart or next 'ALTER INSTANCE ROTATE BINLOG MASTER KEY' execution.
  - Error number: 3812; Symbol: [ER\\_NON\\_BOOLEAN\\_EXPR\\_FOR\\_CHECK\\_CONSTRAINT](#); SQLSTATE: HY000  
Message: An expression of non-boolean type specified to a check constraint '%s'.
  - Error number: 3813; Symbol: [ER\\_COLUMN\\_CHECK\\_CONSTRAINT\\_REFERENCES\\_OTHER\\_COLUMN](#); SQLSTATE: HY000  
Message: Column check constraint '%s' references other column.
  - Error number: 3814; Symbol: [ER\\_CHECK\\_CONSTRAINT\\_NAMED\\_FUNCTION\\_IS\\_NOT\\_ALLOWED](#); SQLSTATE: HY000  
Message: An expression of a check constraint '%s' contains disallowed function: %s.
  - Error number: 3815; Symbol: [ER\\_CHECK\\_CONSTRAINT\\_FUNCTION\\_IS\\_NOT\\_ALLOWED](#); SQLSTATE: HY000  
Message: An expression of a check constraint '%s' contains disallowed function.
  - Error number: 3816; Symbol: [ER\\_CHECK\\_CONSTRAINT\\_VARIABLES](#); SQLSTATE: HY000  
Message: An expression of a check constraint '%s' cannot refer to a user or system variable.
  - Error number: 3817; Symbol: [ER\\_CHECK\\_CONSTRAINT\\_ROW\\_VALUE](#); SQLSTATE: HY000

---

Message: Check constraint '%s' cannot refer to a row value.

- Error number: 3818; Symbol: [ER\\_CHECK\\_CONSTRAINT\\_REFERS\\_AUTO\\_INCREMENT\\_COLUMN](#); SQLSTATE: [HY000](#)

Message: Check constraint '%s' cannot refer to an auto-increment column.

- Error number: 3819; Symbol: [ER\\_CHECK\\_CONSTRAINT\\_VIOLATED](#); SQLSTATE: [HY000](#)

Message: Check constraint '%s' is violated.

- Error number: 3820; Symbol: [ER\\_CHECK\\_CONSTRAINT\\_REFERS\\_UNKNOWN\\_COLUMN](#); SQLSTATE: [HY000](#)

Message: Check constraint '%s' refers to non-existing column '%s'.

- Error number: 3821; Symbol: [ER\\_CHECK\\_CONSTRAINT\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)

Message: Check constraint '%s' is not found in the table.

- Error number: 3822; Symbol: [ER\\_CHECK\\_CONSTRAINT\\_DUP\\_NAME](#); SQLSTATE: [HY000](#)

Message: Duplicate check constraint name '%s'.

- Error number: 3823; Symbol: [ER\\_CHECK\\_CONSTRAINT\\_CLAUSE\\_USING\\_FK\\_REFER\\_ACTION\\_COLUMN](#); SQLSTATE: [HY000](#)

Message: Column '%s' cannot be used in a check constraint '%s': needed in a foreign key constraint '%s' referential action.

- Error number: 3824; Symbol: [WARN\\_UNENCRYPTED\\_TABLE\\_IN\\_ENCRYPTED\\_DB](#); SQLSTATE: [HY000](#)

Message: Creating an unencrypted table in a database with default encryption enabled.

- Error number: 3825; Symbol: [ER\\_INVALID\\_ENCRYPTION\\_REQUEST](#); SQLSTATE: [HY000](#)

Message: Request to create %s table while using an %s tablespace.

- Error number: 3826; Symbol: [ER\\_CANNOT\\_SET\\_TABLE\\_ENCRYPTION](#); SQLSTATE: [HY000](#)

Message: Table encryption differ from its database default encryption, and user doesn't have enough privilege.

- Error number: 3827; Symbol: [ER\\_CANNOT\\_SET\\_DATABASE\\_ENCRYPTION](#); SQLSTATE: [HY000](#)

Message: Database default encryption differ from 'default\_table\_encryption' setting, and user doesn't have enough privilege.

- Error number: 3828; Symbol: [ER\\_CANNOT\\_SET\\_TABLESPACE\\_ENCRYPTION](#); SQLSTATE: [HY000](#)

Message: Tablespace encryption differ from 'default\_table\_encryption' setting, and user doesn't have enough privilege.

- Error number: 3829; Symbol: [ER\\_TABLESPACE\\_CANNOT\\_BE\\_ENCRYPTED](#); SQLSTATE: [HY000](#)

Message: This tablespace can't be encrypted, because one of table's schema has default encryption OFF and user doesn't have enough privilege.

- Error number: 3830; Symbol: [ER\\_TABLESPACE\\_CANNOT\\_BE\\_DECRYPTED](#); SQLSTATE: [HY000](#)

Message: This tablespace can't be decrypted, because one of table's schema has default encryption ON and user doesn't have enough privilege.

- 
- Error number: 3831; Symbol: [ER\\_TABLESPACE\\_TYPE\\_UNKNOWN](#); SQLSTATE: HY000  
Message: Cannot determine the type of the tablespace named '%s'.
  - Error number: 3832; Symbol: [ER\\_TARGET\\_TABLESPACE\\_UNENCRYPTED](#); SQLSTATE: HY000  
Message: Source tablespace is encrypted but target tablespace is not.
  - Error number: 3833; Symbol: [ER\\_CANNOT\\_USE\\_ENCRYPTION\\_CLAUSE](#); SQLSTATE: HY000  
Message: ENCRYPTION clause is not valid for %s tablespace.
  - Error number: 3834; Symbol: [ER\\_INVALID\\_MULTIPLE\\_CLAUSES](#); SQLSTATE: HY000  
Message: Multiple %s clauses
  - Error number: 3835; Symbol: [ER\\_UNSUPPORTED\\_USE\\_OF\\_GRANT\\_AS](#); SQLSTATE: HY000  
Message: GRANT ... AS is currently supported only for global privileges.
  - Error number: 3836; Symbol: [ER\\_UNKNOWN\\_AUTH\\_ID\\_OR\\_ACCESS\\_DENIED\\_FOR\\_GRANT\\_AS](#); SQLSTATE: HY000  
Message: Either some of the authorization IDs in the AS clause are invalid or the current user lacks privileges to execute the statement.
  - Error number: 3837; Symbol: [ER\\_DEPENDENT\\_BY\\_FUNCTIONAL\\_INDEX](#); SQLSTATE: HY000  
Message: Column '%s' has a functional index dependency and cannot be dropped or renamed.
  - Error number: 3838; Symbol: [ER\\_PLUGIN\\_NOT\\_EARLY](#); SQLSTATE: HY000  
Message: Plugin '%s' is not to be used as an "early" plugin. Don't add it to --early-plugin-load, keyring migration etc.
  - Error number: 3839; Symbol: [ER\\_INNOBDB\\_REDO\\_LOG\\_ARCHIVE\\_START\\_SUBDIR\\_PATH](#); SQLSTATE: HY000  
Message: Redo log archiving start prohibits path name in 'subdir' argument
  - Error number: 3840; Symbol: [ER\\_INNOBDB\\_REDO\\_LOG\\_ARCHIVE\\_START\\_TIMEOUT](#); SQLSTATE: HY000  
Message: Redo log archiving start timed out
  - Error number: 3841; Symbol: [ER\\_INNOBDB\\_REDO\\_LOG\\_ARCHIVE\\_DIRS\\_INVALID](#); SQLSTATE: HY000  
Message: Server variable 'innodb\_redo\_log\_archive\_dirs' is NULL or empty
  - Error number: 3842; Symbol: [ER\\_INNOBDB\\_REDO\\_LOG\\_ARCHIVE\\_LABEL\\_NOT\\_FOUND](#); SQLSTATE: HY000  
Message: Label '%s' not found in server variable 'innodb\_redo\_log\_archive\_dirs'
  - Error number: 3843; Symbol: [ER\\_INNOBDB\\_REDO\\_LOG\\_ARCHIVE\\_DIR\\_EMPTY](#); SQLSTATE: HY000  
Message: Directory is empty after label '%s' in server variable 'innodb\_redo\_log\_archive\_dirs'
  - Error number: 3844; Symbol: [ER\\_INNOBDB\\_REDO\\_LOG\\_ARCHIVE\\_NO\\_SUCH\\_DIR](#); SQLSTATE: HY000  
Message: Redo log archive directory '%s' does not exist or is not a directory

- 
- Error number: 3845; Symbol: [ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_DIR\\_CLASH](#); SQLSTATE: HY000  
Message: Redo log archive directory '%s' is in, under, or over server directory '%s' - '%s'
  - Error number: 3846; Symbol: [ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_DIR\\_PERMISSIONS](#); SQLSTATE: HY000  
Message: Redo log archive directory '%s' is accessible to all OS users
  - Error number: 3847; Symbol: [ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_FILE\\_CREATE](#); SQLSTATE: HY000  
Message: Cannot create redo log archive file '%s' (OS errno: %d - %s)
  - Error number: 3848; Symbol: [ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_ACTIVE](#); SQLSTATE: HY000  
Message: Redo log archiving has been started on '%s' - Call `innodb_redo_log_archive_stop()` first
  - Error number: 3849; Symbol: [ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_INACTIVE](#); SQLSTATE: HY000  
Message: Redo log archiving is not active
  - Error number: 3850; Symbol: [ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_FAILED](#); SQLSTATE: HY000  
Message: Redo log archiving failed: %s
  - Error number: 3851; Symbol: [ER\\_INNODB\\_REDO\\_LOG\\_ARCHIVE\\_SESSION](#); SQLSTATE: HY000  
Message: Redo log archiving has not been started by this session
  - Error number: 3852; Symbol: [ER\\_STD\\_REGEX\\_ERROR](#); SQLSTATE: HY000  
Message: Regex error: %s in function %s.
  - Error number: 3853; Symbol: [ER\\_INVALID\\_JSON\\_TYPE](#); SQLSTATE: 22032  
Message: Invalid JSON type in argument %u to function %s; an %s is required.
  - Error number: 3854; Symbol: [ER\\_CANNOT\\_CONVERT\\_STRING](#); SQLSTATE: HY000  
Message: Cannot convert string '%s' from %s to %s
  - Error number: 3855; Symbol: [ER\\_DEPENDENT\\_BY\\_PARTITION\\_FUNC](#); SQLSTATE: HY000  
Message: Column '%s' has a partitioning function dependency and cannot be dropped or renamed.
  - Error number: 3856; Symbol: [ER\\_WARN\\_DEPRECATED\\_FLOAT\\_AUTO\\_INCREMENT](#); SQLSTATE: HY000  
Message: AUTO\_INCREMENT support for FLOAT/DOUBLE columns is deprecated and will be removed in a future release. Consider removing AUTO\_INCREMENT from column '%s'.
  - Error number: 3857; Symbol: [ER\\_RPL\\_CANT\\_STOP\\_REPLICA\\_WHILE\\_LOCKED\\_BACKUP](#); SQLSTATE: HY000  
Message: Cannot stop the replica SQL thread while the instance is locked for backup. Try running ``UNLOCK INSTANCE`` first.
  - Error number: 3858; Symbol: [ER\\_WARN\\_DEPRECATED\\_FLOAT\\_DIGITS](#); SQLSTATE: HY000  
Message: Specifying number of digits for floating point data types is deprecated and will be removed in a future release.
  - Error number: 3859; Symbol: [ER\\_WARN\\_DEPRECATED\\_FLOAT\\_UNSIGNED](#); SQLSTATE: HY000

---

Message: UNSIGNED for decimal and floating point data types is deprecated and support for it will be removed in a future release.

- Error number: 3860; Symbol: [ER\\_WARN\\_DEPRECATED\\_INTEGER\\_DISPLAY\\_WIDTH](#); SQLSTATE: [HY000](#)

Message: Integer display width is deprecated and will be removed in a future release.

- Error number: 3861; Symbol: [ER\\_WARN\\_DEPRECATED\\_ZEROFILL](#); SQLSTATE: [HY000](#)

Message: The ZEROFILL attribute is deprecated and will be removed in a future release. Use the LPAD function to zero-pad numbers, or store the formatted numbers in a CHAR column.

- Error number: 3862; Symbol: [ER\\_CLONE\\_DONOR](#); SQLSTATE: [HY000](#)

Message: Clone Donor Error: %s.

- Error number: 3863; Symbol: [ER\\_CLONE\\_PROTOCOL](#); SQLSTATE: [HY000](#)

Message: Clone received unexpected response from Donor : %s.

- Error number: 3864; Symbol: [ER\\_CLONE\\_DONOR\\_VERSION](#); SQLSTATE: [HY000](#)

Message: Clone Donor MySQL version: %s is different from Recipient MySQL version %s.

- Error number: 3865; Symbol: [ER\\_CLONE\\_OS](#); SQLSTATE: [HY000](#)

Message: Clone Donor OS: %s is different from Recipient OS: %s.

- Error number: 3866; Symbol: [ER\\_CLONE\\_PLATFORM](#); SQLSTATE: [HY000](#)

Message: Clone Donor platform: %s is different from Recipient platform: %s.

- Error number: 3867; Symbol: [ER\\_CLONE\\_CHARSET](#); SQLSTATE: [HY000](#)

Message: Clone Donor collation: %s is unavailable in Recipient.

- Error number: 3868; Symbol: [ER\\_CLONE\\_CONFIG](#); SQLSTATE: [HY000](#)

Message: Clone Configuration %s: Donor value: %s is different from Recipient value: %s.

- Error number: 3869; Symbol: [ER\\_CLONE\\_SYS\\_CONFIG](#); SQLSTATE: [HY000](#)

Message: Clone system configuration: %s

- Error number: 3870; Symbol: [ER\\_CLONE\\_PLUGIN\\_MATCH](#); SQLSTATE: [HY000](#)

Message: Clone Donor plugin %s is not active in Recipient.

- Error number: 3871; Symbol: [ER\\_CLONE\\_LOOPBACK](#); SQLSTATE: [HY000](#)

Message: Clone cannot use loop back connection while cloning into current data directory.

- Error number: 3872; Symbol: [ER\\_CLONE\\_ENCRYPTION](#); SQLSTATE: [HY000](#)

Message: Clone needs SSL connection for encrypted table.

- Error number: 3873; Symbol: [ER\\_CLONE\\_DISK\\_SPACE](#); SQLSTATE: [HY000](#)

Message: Clone estimated database size is %s. Available space %s is not enough.

- Error number: 3874; Symbol: [ER\\_CLONE\\_IN\\_PROGRESS](#); SQLSTATE: [HY000](#)

Message: Concurrent clone in progress. Please try after clone is complete.



- 
- Error number: 3875; Symbol: [ER\\_CLONE\\_DISALLOWED](#); SQLSTATE: HY000  
Message: The clone operation cannot be executed when %s.
  - Error number: 3876; Symbol: [ER\\_CANNOT\\_GRANT\\_ROLES\\_TO\\_ANONYMOUS\\_USER](#); SQLSTATE: HY000  
Message: Cannot grant roles to an anonymous user.
  - Error number: 3877; Symbol: [ER\\_SECONDARY\\_ENGINE\\_PLUGIN](#); SQLSTATE: HY000  
Message: %s
  - Error number: 3878; Symbol: [ER\\_SECOND\\_PASSWORD\\_CANNOT\\_BE\\_EMPTY](#); SQLSTATE: HY000  
Message: Empty password can not be retained as second password for user '%s'@'%s'.
  - Error number: 3879; Symbol: [ER\\_DB\\_ACCESS\\_DENIED](#); SQLSTATE: HY000  
Message: Access denied for AuthId `%s`@`%s` to database '%s'.
  - Error number: 3880; Symbol: [ER\\_DA\\_AUTH\\_ID\\_WITH\\_SYSTEM\\_USER\\_PRIV\\_IN\\_MANDATORY\\_ROLES](#); SQLSTATE: HY000  
Message: Cannot set mandatory\_roles: AuthId `%s`@`%s` has '%s' privilege.
  - Error number: 3881; Symbol: [ER\\_DA\\_RPL\\_GTID\\_TABLE\\_CANNOT\\_OPEN](#); SQLSTATE: HY000  
Message: Gtid table is not ready to be used. Table '%s.%s' cannot be opened.
  - Error number: 3882; Symbol: [ER\\_GEOMETRY\\_IN\\_UNKNOWN\\_LENGTH\\_UNIT](#); SQLSTATE: SU001  
Message: The geometry passed to function %s is in SRID 0, which doesn't specify a length unit. Can't convert to '%s'.
  - Error number: 3883; Symbol: [ER\\_DA\\_PLUGIN\\_INSTALL\\_ERROR](#); SQLSTATE: HY000  
Message: Error installing plugin '%s': %s
  - Error number: 3884; Symbol: [ER\\_NO\\_SESSION\\_TEMP](#); SQLSTATE: HY000  
Message: Storage engine could not allocate temporary tablespace for this session.
  - Error number: 3885; Symbol: [ER\\_DA\\_UNKNOWN\\_ERROR\\_NUMBER](#); SQLSTATE: HY000  
Message: Got unknown error: %d
  - Error number: 3886; Symbol: [ER\\_COLUMN\\_CHANGE\\_SIZE](#); SQLSTATE: HY000  
Message: Could not change column '%s' of table '%s'. The resulting size of index '%s' would exceed the max key length of %d bytes.
  - Error number: 3887; Symbol: [ER\\_REGEXP\\_INVALID\\_CAPTURE\\_GROUP\\_NAME](#); SQLSTATE: HY000  
Message: A capture group has an invalid name.
  - Error number: 3888; Symbol: [ER\\_DA\\_SSL\\_LIBRARY\\_ERROR](#); SQLSTATE: HY000  
Message: Failed to set up SSL because of the following SSL library error: %s
  - Error number: 3889; Symbol: [ER\\_SECONDARY\\_ENGINE](#); SQLSTATE: HY000  
Message: Secondary engine operation failed. %s.
-

- 
- Error number: 3890; Symbol: [ER\\_SECONDARY\\_ENGINE\\_DDL](#); SQLSTATE: HY000  
Message: DDLs on a table with a secondary engine defined are not allowed.
  - Error number: 3891; Symbol: [ER\\_INCORRECT\\_CURRENT\\_PASSWORD](#); SQLSTATE: HY000  
Message: Incorrect current password. Specify the correct password which has to be replaced.
  - Error number: 3892; Symbol: [ER\\_MISSING\\_CURRENT\\_PASSWORD](#); SQLSTATE: HY000  
Message: Current password needs to be specified in the REPLACE clause in order to change it.
  - Error number: 3893; Symbol: [ER\\_CURRENT\\_PASSWORD\\_NOT\\_REQUIRED](#); SQLSTATE: HY000  
Message: Do not specify the current password while changing it for other users.
  - Error number: 3894; Symbol: [ER\\_PASSWORD\\_CANNOT\\_BE\\_RETAINED\\_ON\\_PLUGIN\\_CHANGE](#); SQLSTATE: HY000  
Message: Current password can not be retained for user '%s'@'%s' because authentication plugin is being changed.
  - Error number: 3895; Symbol: [ER\\_CURRENT\\_PASSWORD\\_CANNOT\\_BE\\_RETAINED](#); SQLSTATE: HY000  
Message: Current password can not be retained for user '%s'@'%s' because new password is empty.
  - Error number: 3896; Symbol: [ER\\_PARTIAL\\_REVOKES\\_EXIST](#); SQLSTATE: HY000  
Message: At least one partial revoke exists on a database. The system variable '@@partial\_revokes' must be set to ON.
  - Error number: 3897; Symbol: [ER\\_CANNOT\\_GRANT\\_SYSTEM\\_PRIV\\_TO\\_MANDATORY\\_ROLE](#); SQLSTATE: HY000  
Message: AuthId '%s'@'%s' is set as mandatory\_roles. Cannot grant the '%s' privilege.
  - Error number: 3898; Symbol: [ER\\_XA\\_REPLICATION\\_FILTERS](#); SQLSTATE: HY000  
Message: The use of replication filters with XA transactions is not supported, and can lead to an undefined state in the replica.
  - Error number: 3899; Symbol: [ER\\_UNSUPPORTED\\_SQL\\_MODE](#); SQLSTATE: HY000  
Message: sql\_mode=0x%08x is not supported.
  - Error number: 3900; Symbol: [ER\\_REGEXP\\_INVALID\\_FLAG](#); SQLSTATE: HY000  
Message: Invalid match mode flag in regular expression.
  - Error number: 3901; Symbol: [ER\\_PARTIAL\\_REVOKE\\_AND\\_DB\\_GRANT\\_BOTH\\_EXISTS](#); SQLSTATE: HY000  
Message: '%s' privilege for database '%s' exists both as partial revoke and mysql.db simultaneously. It could mean that the 'mysql' schema is corrupted.
  - Error number: 3902; Symbol: [ER\\_UNIT\\_NOT\\_FOUND](#); SQLSTATE: SU001  
Message: There's no unit of measure named '%s'.
  - Error number: 3903; Symbol: [ER\\_INVALID\\_JSON\\_VALUE\\_FOR\\_FUNC\\_INDEX](#); SQLSTATE: 22018  
Message: Invalid JSON value for CAST for functional index '%s'.

- 
- Error number: 3904; Symbol: `ER_JSON_VALUE_OUT_OF_RANGE_FOR_FUNC_INDEX`; SQLSTATE: 22003  
Message: Out of range JSON value for CAST for functional index '%s'.
  - Error number: 3905; Symbol: `ER_EXCEEDED_MV_KEYS_NUM`; SQLSTATE: HY000  
Message: Exceeded max number of values per record for multi-valued index '%s' by %u value(s).
  - Error number: 3906; Symbol: `ER_EXCEEDED_MV_KEYS_SPACE`; SQLSTATE: HY000  
Message: Exceeded max total length of values per record for multi-valued index '%s' by %u bytes.
  - Error number: 3907; Symbol: `ER_FUNCTIONAL_INDEX_DATA_IS_TOO_LONG`; SQLSTATE: 22001  
Message: Data too long for functional index '%s'.
  - Error number: 3908; Symbol: `ER_WRONG_MVI_VALUE`; SQLSTATE: HY000  
Message: Cannot store an array or an object in a scalar key part of the index '%s'.
  - Error number: 3909; Symbol: `ER_WARN_FUNC_INDEX_NOT_APPLICABLE`; SQLSTATE: HY000  
Message: Cannot use functional index '%s' due to type or collation conversion.
  - Error number: 3910; Symbol: `ER_GRP_RPL_UDF_ERROR`; SQLSTATE: HY000  
Message: The function '%s' failed. %s
  - Error number: 3911; Symbol: `ER_UPDATE_GTID_PURGED_WITH_GR`; SQLSTATE: HY000  
Message: Cannot update GTID\_PURGED with the Group Replication plugin running
  - Error number: 3912; Symbol: `ER_GROUPING_ON_TIMESTAMP_IN_DST`; SQLSTATE: HY000  
Message: Grouping on temporal is non-deterministic for timezones having DST. Please consider switching to UTC for this query.
  - Error number: 3913; Symbol: `ER_TABLE_NAME_CAUSES_TOO_LONG_PATH`; SQLSTATE: HY000  
Message: Long database name and identifier for object resulted in a path length too long for table '%s'. Please check the path limit for your OS.
  - Error number: 3914; Symbol: `ER_AUDIT_LOG_INSUFFICIENT_PRIVILEGE`; SQLSTATE: HY000  
Message: Request ignored for '%s'@'%s'. Role needed to perform operation: '%s'
  - Error number: 3916; Symbol: `ER_DA_GRP_RPL_STARTED_AUTO_REJOIN`; SQLSTATE: HY000  
Message: Started auto-rejoin procedure attempt %lu of %lu
  - Error number: 3917; Symbol: `ER_SYSVAR_CHANGE_DURING_QUERY`; SQLSTATE: HY000  
Message: A plugin was loaded or unloaded during a query, a system variable table was changed.
  - Error number: 3918; Symbol: `ER_GLOBSTAT_CHANGE_DURING_QUERY`; SQLSTATE: HY000  
Message: A plugin was loaded or unloaded during a query, a global status variable was changed.
  - Error number: 3919; Symbol: `ER_GRP_RPL_MESSAGE_SERVICE_INIT_FAILURE`; SQLSTATE: HY000  
Message: The START GROUP\_REPLICATION command failed to start its message service.
-

- 
- Error number: 3920; Symbol: [ER\\_CHANGE\\_SOURCE\\_WRONG\\_COMPRESSION\\_ALGORITHM\\_CLIENT](#); SQLSTATE: [HY000](#)  
Message: Invalid SOURCE\_COMPRESSION\_ALGORITHMS '%s' for channel '%s'.
  - Error number: 3921; Symbol: [ER\\_CHANGE\\_SOURCE\\_WRONG\\_COMPRESSION\\_LEVEL\\_CLIENT](#); SQLSTATE: [HY000](#)  
Message: Invalid SOURCE\_ZSTD\_COMPRESSION\_LEVEL %u for channel '%s'.
  - Error number: 3922; Symbol: [ER\\_WRONG\\_COMPRESSION\\_ALGORITHM\\_CLIENT](#); SQLSTATE: [HY000](#)  
Message: Invalid compression algorithm '%s'.
  - Error number: 3923; Symbol: [ER\\_WRONG\\_COMPRESSION\\_LEVEL\\_CLIENT](#); SQLSTATE: [HY000](#)  
Message: Invalid zstd compression level for algorithm '%s'.
  - Error number: 3924; Symbol: [ER\\_CHANGE\\_SOURCE\\_WRONG\\_COMPRESSION\\_ALGORITHM\\_LIST\\_CLIENT](#); SQLSTATE: [HY000](#)  
Message: Specified compression algorithm list '%s' exceeds total count of 3 for channel '%s'.
  - Error number: 3925; Symbol: [ER\\_CLIENT\\_PRIVILEGE\\_CHECKS\\_USER\\_CANNOT\\_BE\\_ANONYMOUS](#); SQLSTATE: [HY000](#)  
Message: PRIVILEGE\_CHECKS\_USER for replication channel '%s' was set to ``@`%s`, but anonymous users are disallowed for PRIVILEGE\_CHECKS\_USER.
  - Error number: 3926; Symbol: [ER\\_CLIENT\\_PRIVILEGE\\_CHECKS\\_USER\\_DOES\\_NOT\\_EXIST](#); SQLSTATE: [HY000](#)  
Message: PRIVILEGE\_CHECKS\_USER for replication channel '%s' was set to `%s`@`%s`, but this is not an existing user.
  - Error number: 3927; Symbol: [ER\\_CLIENT\\_PRIVILEGE\\_CHECKS\\_USER\\_CORRUPT](#); SQLSTATE: [HY000](#)  
Message: Invalid, corrupted PRIVILEGE\_CHECKS\_USER was found in the replication configuration repository for channel '%s'. Use CHANGE REPLICATION SOURCE TO PRIVILEGE\_CHECKS\_USER to correct the configuration.
  - Error number: 3928; Symbol: [ER\\_CLIENT\\_PRIVILEGE\\_CHECKS\\_USER\\_NEEDS\\_RPL\\_APPLIER\\_PRIV](#); SQLSTATE: [HY000](#)  
Message: PRIVILEGE\_CHECKS\_USER for replication channel '%s' was set to `%s`@`%s`, but this user does not have REPLICATION\_APPLIER privilege.
  - Error number: 3929; Symbol: [ER\\_WARN\\_DA\\_PRIVILEGE\\_NOT\\_REGISTERED](#); SQLSTATE: [HY000](#)  
Message: Dynamic privilege '%s' is not registered with the server.
  - Error number: 3930; Symbol: [ER\\_CLIENT\\_KEYRING\\_UDF\\_KEY\\_INVALID](#); SQLSTATE: [HY000](#)  
Message: Function '%s' failed because key is invalid.
  - Error number: 3931; Symbol: [ER\\_CLIENT\\_KEYRING\\_UDF\\_KEY\\_TYPE\\_INVALID](#); SQLSTATE: [HY000](#)  
Message: Function '%s' failed because key type is invalid.
  - Error number: 3932; Symbol: [ER\\_CLIENT\\_KEYRING\\_UDF\\_KEY\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)

---

Message: Function '%s' failed because key length is too long.

- Error number: 3933; Symbol: [ER\\_CLIENT\\_KEYRING\\_UDF\\_KEY\\_TYPE\\_TOO\\_LONG](#); SQLSTATE: HY000

Message: Function '%s' failed because key type is too long.

- Error number: 3934; Symbol: [ER\\_JSON\\_SCHEMA\\_VALIDATION\\_ERROR\\_WITH\\_DETAILED\\_REPORT](#); SQLSTATE: HY000

Message: %s.

- Error number: 3935; Symbol: [ER\\_DA\\_UDF\\_INVALID\\_CHARSET\\_SPECIFIED](#); SQLSTATE: HY000

Message: Invalid character set '%s' was specified. It must be either character set name or collation name as supported by server.

- Error number: 3936; Symbol: [ER\\_DA\\_UDF\\_INVALID\\_CHARSET](#); SQLSTATE: HY000

Message: Invalid character set '%s' was specified. It must be a character set name as supported by server.

- Error number: 3937; Symbol: [ER\\_DA\\_UDF\\_INVALID\\_COLLATION](#); SQLSTATE: HY000

Message: Invalid collation '%s' was specified. It must be a collation name as supported by server.

- Error number: 3938; Symbol: [ER\\_DA\\_UDF\\_INVALID\\_EXTENSION\\_ARGUMENT\\_TYPE](#); SQLSTATE: HY000

Message: Invalid extension argument type '%s' was specified. Refer the MySQL manual for the valid UDF extension arguments type.

- Error number: 3939; Symbol: [ER\\_MULTIPLE\\_CONSTRAINTS\\_WITH\\_SAME\\_NAME](#); SQLSTATE: HY000

Message: Table has multiple constraints with the name '%s'. Please use constraint specific '%s' clause.

- Error number: 3940; Symbol: [ER\\_CONSTRAINT\\_NOT\\_FOUND](#); SQLSTATE: HY000

Message: Constraint '%s' does not exist.

- Error number: 3941; Symbol: [ER\\_ALTER\\_CONSTRAINT\\_ENFORCEMENT\\_NOT\\_SUPPORTED](#); SQLSTATE: HY000

Message: Altering constraint enforcement is not supported for the constraint '%s'. Enforcement state alter is not supported for the PRIMARY, UNIQUE and FOREIGN KEY type constraints.

- Error number: 3942; Symbol: [ER\\_TABLE\\_VALUE\\_CONSTRUCTOR\\_MUST\\_HAVE\\_COLUMNS](#); SQLSTATE: HY000

Message: Each row of a VALUES clause must have at least one column, unless when used as source in an INSERT statement.

- Error number: 3943; Symbol: [ER\\_TABLE\\_VALUE\\_CONSTRUCTOR\\_CANNOT\\_HAVE\\_DEFAULT](#); SQLSTATE: HY000

Message: A VALUES clause cannot use DEFAULT values, unless used as a source in an INSERT statement.

- Error number: 3944; Symbol: [ER\\_CLIENT\\_QUERY\\_FAILURE\\_INVALID\\_NON\\_ROW\\_FORMAT](#); SQLSTATE: HY000

---

Message: The query does not comply with variable require\_row\_format restrictions.

- Error number: 3945; Symbol: [ER\\_REQUIRE\\_ROW\\_FORMAT\\_INVALID\\_VALUE](#); SQLSTATE: HY000

Message: The requested value %s is invalid for REQUIRE\_ROW\_FORMAT, must be either 0 or 1.

- Error number: 3946; Symbol: [ER\\_FAILED\\_TO\\_DETERMINE\\_IF\\_ROLE\\_IS\\_MANDATORY](#); SQLSTATE: HY000

Message: Failed to acquire lock on user management service, unable to determine if role `%s`@`%s` is mandatory

- Error number: 3947; Symbol: [ER\\_FAILED\\_TO\\_FETCH\\_MANDATORY\\_ROLE\\_LIST](#); SQLSTATE: HY000

Message: Failed to acquire lock on user management service, unable to fetch mandatory role list

- Error number: 3948; Symbol: [ER\\_CLIENT\\_LOCAL\\_FILES\\_DISABLED](#); SQLSTATE: 42000

Message: Loading local data is disabled; this must be enabled on both the client and server sides

- Error number: 3949; Symbol: [ER\\_IMP\\_INCOMPATIBLE\\_CFG\\_VERSION](#); SQLSTATE: HY000

Message: Failed to import %s because the CFG file version (%u) is not compatible with the current version (%u)

- Error number: 3950; Symbol: [ER\\_DA\\_OOM](#); SQLSTATE: HY000

Message: Out of memory

- Error number: 3951; Symbol: [ER\\_DA\\_UDF\\_INVALID\\_ARGUMENT\\_TO\\_SET\\_CHARSET](#); SQLSTATE: HY000

Message: Character set can be set only for the UDF argument type STRING.

- Error number: 3952; Symbol: [ER\\_DA\\_UDF\\_INVALID\\_RETURN\\_TYPE\\_TO\\_SET\\_CHARSET](#); SQLSTATE: HY000

Message: Character set can be set only for the UDF RETURN type STRING.

- Error number: 3953; Symbol: [ER\\_MULTIPLE\\_INTO\\_CLAUSES](#); SQLSTATE: HY000

Message: Multiple INTO clauses in one query block.

- Error number: 3954; Symbol: [ER\\_MISPLACED\\_INTO](#); SQLSTATE: HY000

Message: Misplaced INTO clause, INTO is not allowed inside subqueries, and must be placed at end of UNION clauses.

- Error number: 3955; Symbol: [ER\\_USER\\_ACCESS\\_DENIED\\_FOR\\_USER\\_ACCOUNT\\_BLOCKED\\_BY\\_PASSWORD\\_LOCK](#); SQLSTATE: HY000

Message: Access denied for user '%s'@'%s'. Account is blocked for %s day(s) (%s day(s) remaining) due to %u consecutive failed logins.

- Error number: 3956; Symbol: [ER\\_WARN\\_DEPRECATED\\_YEAR\\_UNSIGNED](#); SQLSTATE: HY000

Message: UNSIGNED for the YEAR data type is deprecated and support for it will be removed in a future release.

- Error number: 3957; Symbol: [ER\\_CLONE\\_NETWORK\\_PACKET](#); SQLSTATE: HY000

---

Message: Clone needs max\_allowed\_packet value to be %u or more. Current value is %u

- Error number: 3958; Symbol: [ER\\_SDI\\_OPERATION\\_FAILED\\_MISSING\\_RECORD](#); SQLSTATE: [HY000](#)

Message: Failed to %s sdi for %s.%s in %s due to missing record.

- Error number: 3959; Symbol: [ER\\_DEPENDENT\\_BY\\_CHECK\\_CONSTRAINT](#); SQLSTATE: [HY000](#)

Message: Check constraint '%s' uses column '%s', hence column cannot be dropped or renamed.

- Error number: 3960; Symbol: [ER\\_GRP\\_OPERATION\\_NOT\\_ALLOWED\\_GR\\_MUST\\_STOP](#); SQLSTATE: [HY000](#)

Message: This operation cannot be performed while Group Replication is running; run STOP GROUP\_REPLICATION first

- Error number: 3961; Symbol: [ER\\_WARN\\_DEPRECATED\\_JSON\\_TABLE\\_ON\\_ERROR\\_ON\\_EMPTY](#); SQLSTATE: [HY000](#)

Message: Specifying an ON EMPTY clause after the ON ERROR clause in a JSON\_TABLE column definition is deprecated syntax and will be removed in a future release. Specify ON EMPTY before ON ERROR instead.

- Error number: 3962; Symbol: [ER\\_WARN\\_DEPRECATED\\_INNER\\_INTO](#); SQLSTATE: [HY000](#)

Message: The INTO clause is deprecated inside query blocks of query expressions and will be removed in a future release. Please move the INTO clause to the end of statement instead.

- Error number: 3963; Symbol: [ER\\_WARN\\_DEPRECATED\\_VALUES\\_FUNCTION\\_ALWAYS\\_NULL](#); SQLSTATE: [HY000](#)

Message: The VALUES function is deprecated and will be removed in a future release. It always returns NULL in this context. If you meant to access a value from the VALUES clause of the INSERT statement, consider using an alias (INSERT INTO ... VALUES (...) AS alias) and reference alias.col instead of VALUES(col) in the ON DUPLICATE KEY UPDATE clause.

- Error number: 3964; Symbol: [ER\\_WARN\\_DEPRECATED\\_SQL\\_CALC\\_FOUND\\_ROWS](#); SQLSTATE: [HY000](#)

Message: SQL\_CALC\_FOUND\_ROWS is deprecated and will be removed in a future release. Consider using two separate queries instead.

- Error number: 3965; Symbol: [ER\\_WARN\\_DEPRECATED\\_FOUND\\_ROWS](#); SQLSTATE: [HY000](#)

Message: FOUND\_ROWS() is deprecated and will be removed in a future release. Consider using COUNT(\*) instead.

- Error number: 3966; Symbol: [ER\\_MISSING\\_JSON\\_VALUE](#); SQLSTATE: [22035](#)

Message: No value was found by '%s' on the specified path.

- Error number: 3967; Symbol: [ER\\_MULTIPLE\\_JSON\\_VALUES](#); SQLSTATE: [22034](#)

Message: More than one value was found by '%s' on the specified path.

- Error number: 3968; Symbol: [ER\\_HOSTNAME\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)

Message: Hostname cannot be longer than %d characters.

- Error number: 3969; Symbol: [ER\\_WARN\\_CLIENT\\_DEPRECATED\\_PARTITION\\_PREFIX\\_KEY](#); SQLSTATE: [HY000](#)

---

Message: Column '%s.%s.%s' having prefix key part '%s(%u)' is ignored by the partitioning function. Use of prefixed columns in the PARTITION BY KEY() clause is deprecated and will be removed in a future release.

- Error number: 3970; Symbol: [ER\\_GROUP\\_REPLICATION\\_USER\\_EMPTY\\_MSG](#); SQLSTATE: HY000

Message: The START GROUP\_REPLICATION command failed since the username provided for recovery channel is empty.

- Error number: 3971; Symbol: [ER\\_GROUP\\_REPLICATION\\_USER\\_MANDATORY\\_MSG](#); SQLSTATE: HY000

Message: The START GROUP\_REPLICATION command failed since the USER option was not provided with PASSWORD for recovery channel.

- Error number: 3972; Symbol: [ER\\_GROUP\\_REPLICATION\\_PASSWORD\\_LENGTH](#); SQLSTATE: HY000

Message: The START GROUP\_REPLICATION command failed since the password provided for the recovery channel exceeds the maximum length of 32 characters.

- Error number: 3973; Symbol: [ER\\_SUBQUERY\\_TRANSFORM\\_REJECTED](#); SQLSTATE: HY000

Message: Statement requires a transform of a subquery to a non-SET operation (like IN2EXISTS, or subquery-to-LATERAL-derived-table). This is not allowed with optimizer switch 'subquery\_to\_derived' on.

- Error number: 3974; Symbol: [ER\\_DA\\_GRP\\_RPL\\_RECOVERY\\_ENDPOINT\\_FORMAT](#); SQLSTATE: HY000

Message: Invalid input value for recovery socket endpoints '%s'. Please, provide a valid, comma separated, list of endpoints (IP:port).

- Error number: 3975; Symbol: [ER\\_DA\\_GRP\\_RPL\\_RECOVERY\\_ENDPOINT\\_INVALID](#); SQLSTATE: HY000

Message: The server is not listening on endpoint '%s'. Only endpoints that the server is listening on are valid recovery endpoints.

- Error number: 3976; Symbol: [ER\\_WRONG\\_VALUE\\_FOR\\_VAR\\_PLUS\\_ACTIONABLE\\_PART](#); SQLSTATE: HY000

Message: Variable '%s' cannot be set to the value of '%s'. %s

- Error number: 3977; Symbol: [ER\\_STATEMENT\\_NOT\\_ALLOWED\\_AFTER\\_START\\_TRANSACTION](#); SQLSTATE: HY000

Message: Only BINLOG INSERT, COMMIT and ROLLBACK statements are allowed after CREATE TABLE with START TRANSACTION statement.

- Error number: 3978; Symbol: [ER\\_FOREIGN\\_KEY\\_WITH\\_ATOMIC\\_CREATE\\_SELECT](#); SQLSTATE: HY000

Message: Foreign key creation is not allowed with CREATE TABLE as SELECT and CREATE TABLE with START TRANSACTION statement.

- Error number: 3979; Symbol: [ER\\_NOT\\_ALLOWED\\_WITH\\_START\\_TRANSACTION](#); SQLSTATE: HY000

Message: START TRANSACTION clause cannot be used %s

- Error number: 3980; Symbol: [ER\\_INVALID\\_JSON\\_ATTRIBUTE](#); SQLSTATE: HY000



---

Message: Invalid json attribute, error: "%s" at pos %u: '%s'

- Error number: 3981; Symbol: [ER\\_ENGINE\\_ATTRIBUTE\\_NOT\\_SUPPORTED](#); SQLSTATE: HY000

Message: Storage engine '%s' does not support ENGINE\_ATTRIBUTE.

- Error number: 3982; Symbol: [ER\\_INVALID\\_USER\\_ATTRIBUTE\\_JSON](#); SQLSTATE: HY000

Message: The user attribute must be a valid JSON object

- Error number: 3983; Symbol: [ER\\_INNODB\\_REDO\\_DISABLED](#); SQLSTATE: HY000

Message: Cannot perform operation as InnoDB redo logging is disabled. Please retry after enabling redo log with ALTER INSTANCE

- Error number: 3984; Symbol: [ER\\_INNODB\\_REDO\\_ARCHIVING\\_ENABLED](#); SQLSTATE: HY000

Message: Cannot perform operation as InnoDB is archiving redo log. Please retry after stopping redo archive by invoking innodb\_redo\_log\_archive\_stop()

- Error number: 3985; Symbol: [ER\\_MDL\\_OUT\\_OF\\_RESOURCES](#); SQLSTATE: HY000

Message: Not enough resources to complete lock request.

- Error number: 3986; Symbol: [ER\\_IMPLICIT\\_COMPARISON\\_FOR\\_JSON](#); SQLSTATE: HY000

Message: Evaluating a JSON value in SQL boolean context does an implicit comparison against JSON integer 0; if this is not what you want, consider converting JSON to a SQL numeric type with JSON\_VALUE RETURNING

- Error number: 3987; Symbol: [ER\\_FUNCTION\\_DOES\\_NOT\\_SUPPORT\\_CHARACTER\\_SET](#); SQLSTATE: HY000

Message: The function %s does not support the character set '%s'.

- Error number: 3988; Symbol: [ER\\_IMPOSSIBLE\\_STRING\\_CONVERSION](#); SQLSTATE: HY000

Message: Conversion from collation %s into %s impossible for %s

- Error number: 3989; Symbol: [ER\\_SCHEMA\\_READ\\_ONLY](#); SQLSTATE: HY000

Message: Schema '%s' is in read only mode.

- Error number: 3990; Symbol: [ER\\_RPL\\_ASYNC\\_RECONNECT\\_GTID\\_MODE\\_OFF](#); SQLSTATE: HY000

Message: Failed to enable Asynchronous Replication Connection Failover feature. The CHANGE REPLICATION SOURCE TO SOURCE\_CONNECTION\_AUTO\_FAILOVER = 1 can only be set when @@GLOBAL.GTID\_MODE = ON.

- Error number: 3991; Symbol: [ER\\_RPL\\_ASYNC\\_RECONNECT\\_AUTO\\_POSITION\\_OFF](#); SQLSTATE: HY000

Message: Failed to enable Asynchronous Replication Connection Failover feature. The CHANGE REPLICATION SOURCE TO SOURCE\_CONNECTION\_AUTO\_FAILOVER = 1 can only be set when SOURCE\_AUTO\_POSITION option of CHANGE REPLICATION SOURCE TO is enabled.

- Error number: 3992; Symbol: [ER\\_DISABLE\\_GTID\\_MODE\\_REQUIRES\\_ASYNC\\_RECONNECT\\_OFF](#); SQLSTATE: HY000

Message: The @@GLOBAL.GTID\_MODE = %s cannot be executed because Asynchronous Replication Connection Failover is enabled i.e. CHANGE REPLICATION SOURCE TO SOURCE\_CONNECTION\_AUTO\_FAILOVER = 1.

- 
- Error number: 3993; Symbol: [ER\\_DISABLE\\_AUTO\\_POSITION\\_REQUIRES\\_ASYNC\\_RECONNECT\\_OFF](#); SQLSTATE: HY000  
Message: CHANGE REPLICATION SOURCE TO SOURCE\_AUTO\_POSITION = 0 cannot be executed because Asynchronous Replication Connection Failover is enabled i.e. CHANGE REPLICATION SOURCE TO SOURCE\_CONNECTION\_AUTO\_FAILOVER = 1.
  - Error number: 3994; Symbol: [ER\\_INVALID\\_PARAMETER\\_USE](#); SQLSTATE: HY000  
Message: Invalid use of parameters in '%s'
  - Error number: 3995; Symbol: [ER\\_CHARACTER\\_SET\\_MISMATCH](#); SQLSTATE: HY000  
Message: Character set '%s' cannot be used in conjunction with '%s' in call to %s.
  - Error number: 3996; Symbol: [ER\\_WARN\\_VAR\\_VALUE\\_CHANGE\\_NOT\\_SUPPORTED](#); SQLSTATE: HY000  
Message: Changing %s not supported on this platform. Falling back to the default.
  - Error number: 3997; Symbol: [ER\\_INVALID\\_TIME\\_ZONE\\_INTERVAL](#); SQLSTATE: HY000  
Message: Invalid time zone interval: '%s'
  - Error number: 3998; Symbol: [ER\\_INVALID\\_CAST](#); SQLSTATE: HY000  
Message: Cannot cast value to %s.
  - Error number: 3999; Symbol: [ER\\_HYPERGRAPH\\_NOT\\_SUPPORTED\\_YET](#); SQLSTATE: 42000  
Message: The hypergraph optimizer does not yet support '%s'
  - Error number: 4000; Symbol: [ER\\_WARN\\_HYPERGRAPH\\_EXPERIMENTAL](#); SQLSTATE: HY000  
Message: The hypergraph optimizer is highly experimental and is meant for testing only. Do not enable it unless you are a MySQL developer.
  - Error number: 4001; Symbol: [ER\\_DA\\_NO\\_ERROR\\_LOG\\_PARSER\\_CONFIGURED](#); SQLSTATE: HY000  
Message: None of the log-sinks selected with --log-error-services=... provides a log-parser. The server will not be able to make the previous runs' error-logs available in performance\_schema.error\_log.
  - Error number: 4002; Symbol: [ER\\_DA\\_ERROR\\_LOG\\_TABLE\\_DISABLED](#); SQLSTATE: HY000  
Message: None of the log-sinks selected in @@global.log\_error\_services supports writing to the performance schema. The server will not be able to make the current runs' error events available in performance\_schema.error\_log. To change this, add a log-sink that supports the performance schema to @@global.log\_error\_services.
  - Error number: 4003; Symbol: [ER\\_DA\\_ERROR\\_LOG\\_MULTIPLE\\_FILTERS](#); SQLSTATE: HY000  
Message: @@global.log\_error\_services lists more than one log-filter service. This is discouraged as it will make it hard to understand which rule in which filter affected a log-event.
  - Error number: 4004; Symbol: [ER\\_DA\\_CANT\\_OPEN\\_ERROR\\_LOG](#); SQLSTATE: HY000  
Message: Could not open file '%s' for error logging%s%s
  - Error number: 4005; Symbol: [ER\\_USER\\_REFERENCED\\_AS\\_DEFINER](#); SQLSTATE: HY000  
Message: User %s is referenced as a definer account in %s.
  - Error number: 4006; Symbol: [ER\\_CANNOT\\_USER\\_REFERENCED\\_AS\\_DEFINER](#); SQLSTATE: HY000

---

Message: Operation %s failed for %s as it is referenced as a definer account in %s.

- Error number: 4007; Symbol: `ER_REGEX_NUMBER_TOO_BIG`; SQLSTATE: `HY000`

Message: Decimal number in regular expression is too large.

- Error number: 4008; Symbol: `ER_SPVAR_NONINTEGER_TYPE`; SQLSTATE: `HY000`

Message: The variable "%s" has a non-integer based type

- Error number: 4009; Symbol: `WARN_UNSUPPORTED_ACL_TABLES_READ`; SQLSTATE: `HY000`

Message: Reads with serializable isolation/SELECT FOR SHARE are not supported for ACL tables.

- Error number: 4010; Symbol: `ER_BINLOG_UNSAFE_ACL_TABLE_READ_IN_DML_DDL`; SQLSTATE: `HY000`

Message: The statement is unsafe because it updates a table depending on ACL table read operation. As storage engine row locks are skipped for ACL table, it may not have same effect on source and replica.

- Error number: 4011; Symbol: `ER_STOP_REPLICA_MONITOR_IO_THREAD_TIMEOUT`; SQLSTATE: `HY000`

Message: STOP REPLICA command execution is incomplete: Replica Monitor thread got the stop signal, thread is busy, Monitor thread will stop once the current task is complete.

- Error number: 4012; Symbol: `ER_STARTING_REPLICA_MONITOR_IO_THREAD`; SQLSTATE: `HY000`

Message: The Replica Monitor thread failed to start.

- Error number: 4013; Symbol: `ER_CANT_USE_ANONYMOUS_TO_GTID_WITH_GTID_MODE_NOT_ON`; SQLSTATE: `HY000`

Message: Replication cannot start%s with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>` as this server uses `@@GLOBAL.GTID_MODE <> ON`.

- Error number: 4014; Symbol: `ER_CANT_COMBINE_ANONYMOUS_TO_GTID_AND_AUTOPOSITION`; SQLSTATE: `HY000`

Message: The options `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>` and `SOURCE_AUTO_POSITION = 1` cannot be used together.

- Error number: 4015; Symbol: `ER_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS_REQUIRES_GTID_MODE_ON`; SQLSTATE: `HY000`

Message: CHANGE REPLICATION SOURCE TO `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>` cannot be executed because `@@GLOBAL.GTID_MODE <> ON`.

- Error number: 4016; Symbol: `ER_SQL_REPLICA_SKIP_COUNTER_USED_WITH_GTID_MODE_ON`; SQLSTATE: `HY000`

Message: The value of `sql_replica_skip_counter` will only take effect for channels running with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS <> OFF`.

- Error number: 4017; Symbol: `ER_USING_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS_AS_LOCAL_OR_UUID`; SQLSTATE: `HY000`

---

Message: Using `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS` creates limitations on the replication topology - you cannot fail over between downstream and upstream servers. Only use this option if it is not possible to enable GTIDs on the source, for instance, because of lack of permissions. If possible, use the procedure for enabling GTID transactions online instead, as described in the documentation.

- Error number: 4019; Symbol: `ER_CANT_SET_SQL_AFTER_OR_BEFORE_GTIDS_WITH_ANONYMOUS_TO_GTID`; SQLSTATE: HY000

Message: The `SQL_AFTER_GTIDS` or `SQL_BEFORE_GTIDS` clauses for `START REPLICA` cannot be used when the replication channel is configured with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>`.

- Error number: 4020; Symbol: `ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_GROUP_NAME`; SQLSTATE: HY000

Message: Replication '%s' is configured with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = <UUID>` where the UUID value is equal to the `group_replication_group_name`

- Error number: 4021; Symbol: `ER_CANT_USE_SAME_UUID_AS_GROUP_NAME`; SQLSTATE: HY000

Message: `CHANGE REPLICATION SOURCE TO ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = <UUID>` cannot be executed because the UUID value is equal to the `group_replication_group_name`.

- Error number: 4022; Symbol: `ER_GRP_RPL_RECOVERY_CHANNEL_STILL_RUNNING`; SQLSTATE: HY000

Message: The `group_replication_recovery` channel is still running, most likely it is waiting for a database/table lock, which is preventing the channel from stopping. Please check database/table locks, including the ones created by backup tools.

- Error number: 4023; Symbol: `ER_INNODB_INVALID_AUTOEXTEND_SIZE_VALUE`; SQLSTATE: HY000

Message: `AUTOEXTEND_SIZE` should be a multiple of %uM

- Error number: 4024; Symbol: `ER_INNODB_INCOMPATIBLE_WITH_TABLESPACE`; SQLSTATE: HY000

Message: InnoDB: "%s" not allowed with general tablespaces

- Error number: 4025; Symbol: `ER_INNODB_AUTOEXTEND_SIZE_OUT_OF_RANGE`; SQLSTATE: HY000

Message: `AUTOEXTEND_SIZE` value should be between %uM and %uM

- Error number: 4026; Symbol: `ER_CANNOT_USE_AUTOEXTEND_SIZE_CLAUSE`; SQLSTATE: HY000

Message: `AUTOEXTEND_SIZE` clause is not valid for %s tablespace.

- Error number: 4027; Symbol: `ER_ROLE_GRANTED_TO_ITSELF`; SQLSTATE: HY000

Message: User account %s is directly or indirectly granted to the role %s. The GRANT would create a loop

- Error number: 4028; Symbol: `ER_TABLE_MUST_HAVE_A_VISIBLE_COLUMN`; SQLSTATE: HY000

Message: A table must have at least one visible column.

- Error number: 4029; Symbol: `ER_INNODB_COMPRESSION_FAILURE`; SQLSTATE: HY000

---

Message: Compression failed with the following error : %s

- Error number: 4030; Symbol: [ER\\_WARN\\_ASYNC\\_CONN\\_FAILOVER\\_NETWORK\\_NAMESPACE](#); SQLSTATE: HY000

Message: The parameter network\_namespace is reserved for future use. Please use the CHANGE REPLICATION SOURCE command to set channel network\_namespace parameter.

- Error number: 4031; Symbol: [ER\\_CLIENT\\_INTERACTION\\_TIMEOUT](#); SQLSTATE: HY000

Message: The client was disconnected by the server because of inactivity. See wait\_timeout and interactive\_timeout for configuring this behavior.

- Error number: 4032; Symbol: [ER\\_INVALID\\_CAST\\_TO\\_GEOMETRY](#); SQLSTATE: 22S01

Message: Invalid cast from %s to %s.

- Error number: 4033; Symbol: [ER\\_INVALID\\_CAST\\_POLYGON\\_RING\\_DIRECTION](#); SQLSTATE: 22S04

Message: Invalid cast from %s to %s. A polygon ring is in the wrong direction.

- Error number: 4034; Symbol: [ER\\_GIS\\_DIFFERENT\\_SRIDS\\_AGGREGATION](#); SQLSTATE: 22S05

Message: Arguments to function %s contains geometries with different SRIDs: %u and %u. All geometries must have the same SRID.

- Error number: 4035; Symbol: [ER\\_RELOAD\\_KEYRING\\_FAILURE](#); SQLSTATE: HY000

Message: Keyring reload failed. Please check error log for more details.

- Error number: 4036; Symbol: [ER\\_SDI\\_GET\\_KEYS\\_INVALID\\_TABLESPACE](#); SQLSTATE: HY000

Message: Tablespace '%s' is invalid for SDI operations.

- Error number: 4037; Symbol: [ER\\_CHANGE\\_RPL\\_SRC\\_WRONG\\_COMPRESSION\\_ALGORITHM\\_SIZE](#); SQLSTATE: HY000

Message: Value too long setting SOURCE\_COMPRESSION\_ALGORITHMS option to a %d chars long string for channel '%s'.

- Error number: 4039; Symbol: [ER\\_CANT\\_USE\\_SAME\\_UUID\\_AS\\_VIEW\\_CHANGE\\_UUID](#); SQLSTATE: HY000

Message: CHANGE REPLICATION SOURCE TO ASSIGN\_GTIDS\_TO\_ANONYMOUS\_TRANSACTIONS = <UUID> cannot be executed because the UUID value is equal to the group\_replication\_view\_change\_uuid.

- Error number: 4040; Symbol: [ER\\_ANONYMOUS\\_TO\\_GTID\\_UUID\\_SAME\\_AS\\_VIEW\\_CHANGE\\_UUID](#); SQLSTATE: HY000

Message: Replication '%s' is configured with ASSIGN\_GTIDS\_TO\_ANONYMOUS\_TRANSACTIONS = <UUID> where the UUID value is equal to the group\_replication\_view\_change\_uuid

- Error number: 4041; Symbol: [ER\\_GRP\\_RPL\\_VIEW\\_CHANGE\\_UUID\\_FAIL\\_GET\\_VARIABLE](#); SQLSTATE: HY000

Message: Unable to retrieve group\_replication\_view\_change\_uuid variable during server checks on replication operations.

- Error number: 4042; Symbol: [ER\\_WARN\\_ADUIT\\_LOG\\_MAX\\_SIZE\\_AND\\_PRUNE\\_SECONDS](#); SQLSTATE: HY000

---

Message: Both audit\_log\_max\_size and audit\_log\_prune\_seconds are set to non-zero. audit\_log\_max\_size takes precedence and audit\_log\_prune\_seconds is ignored

- Error number: 4043; Symbol: ER\_WARN\_ADUIT\_LOG\_MAX\_SIZE\_CLOSE\_TO\_ROTATE\_ON\_SIZE; SQLSTATE: HY000

Message: audit\_log\_rotate\_on\_size is not granular enough for the value of audit\_log\_max\_size supplied. Should be at least %d times smaller.

- Error number: 4044; Symbol: ER\_KERBEROS\_CREATE\_USER; SQLSTATE: HY000

Message: Create/Alter user has failed, Configured user realm as authentication string is empty, Please make sure to configure authentication string as user realm.

- Error number: 4045; Symbol: ER\_INSTALL\_PLUGIN\_CONFLICT\_CLIENT; SQLSTATE: HY000

Message: Cannot install the %s plugin when the %s plugin is installed.

- Error number: 4046; Symbol: ER\_DA\_ERROR\_LOG\_COMPONENT\_FLUSH\_FAILED; SQLSTATE: HY000

Message: %d error logging component(s) failed to flush. For file-based logs this can happen when the path or permissions of the log-file have changed. Failure to flush filed-based logs may affect log-rotation.

- Error number: 4047; Symbol: ER\_WARN\_SQL\_AFTER\_MTS\_GAPS\_GAP\_NOT\_CALCULATED; SQLSTATE: HY000

Message: The until clause SQL\_AFTER\_MTS\_GAPS is being used for channel '%s' when GTID\_MODE = ON and SOURCE\_AUTO\_POSITION=1 meaning the server did not compute internally what gaps may exist in the relay log transaction execution. To close any execution gaps use either the SQL\_BEFORE\_GTIDS or SQL\_AFTER\_GTIDS until clause.

- Error number: 4048; Symbol: ER\_INVALID\_ASSIGNMENT\_TARGET; SQLSTATE: 42000

Message: Invalid target for assignment in INSERT or UPDATE statement '%s'.

- Error number: 4049; Symbol: ER\_OPERATION\_NOT\_ALLOWED\_ON\_GR\_SECONDARY; SQLSTATE: HY000

Message: This operation cannot be performed on a Group Replication secondary member, it must be done on the group primary.

- Error number: 4050; Symbol: ER\_GRP\_RPL\_FAILOVER\_CHANNEL\_STATUS\_PROPAGATION; SQLSTATE: HY000

Message: Unable to propagate the SOURCE\_CONNECTION\_AUTO\_FAILOVER value for channel '%s' to group replication members. Please retry the operation.

- Error number: 4051; Symbol: ER\_WARN\_AUDIT\_LOG\_FORMAT\_UNIX\_TIMESTAMP\_ONLY\_WHEN\_JSON; SQLSTATE: HY000

Message: audit\_log\_format\_unix\_timestamp is applicable only when audit\_log\_format = JSON.

- Error number: 4052; Symbol: ER\_INVALID\_MFA\_PLUGIN\_SPECIFIED; SQLSTATE: HY000

Message: Invalid plugin "%s" specified as %d factor during "%s".

- Error number: 4053; Symbol: ER\_IDENTIFIED\_BY\_UNSUPPORTED; SQLSTATE: HY000

Message: IDENTIFIED BY clause during "%s" not supported for plugin "%s".

- Error number: 4054; Symbol: ER\_INVALID\_PLUGIN\_FOR\_REGISTRATION; SQLSTATE: HY000

---

Message: This operation is not supported for plugin "%s".

- Error number: 4055; Symbol: [ER\\_PLUGIN\\_REQUIRES\\_REGISTRATION](#); SQLSTATE: HY000

Message: Authentication plugin requires registration. Please refer ALTER USER syntax or set --fido-register-factor command line option to do registration.

- Error number: 4056; Symbol: [ER\\_MFA\\_METHOD\\_EXISTS](#); SQLSTATE: HY000

Message: %d factor authentication method exists. Please do ALTER USER... DROP %d factor before doing this operation OR do ALTER USER... MODIFY %d factor... to modify existing %d factor authentication method.

- Error number: 4057; Symbol: [ER\\_MFA\\_METHOD\\_NOT\\_EXISTS](#); SQLSTATE: HY000

Message: %d factor authentication method doesn't exist. Please do ALTER USER... ADD %d factor... before doing this operation.

- Error number: 4058; Symbol: [ER\\_AUTHENTICATION\\_POLICY\\_MISMATCH](#); SQLSTATE: HY000

Message: %d factor authentication method does not match against authentication policy. Please refer @@authentication\_policy system variable.

- Error number: 4059; Symbol: [ER\\_PLUGIN\\_REGISTRATION\\_DONE](#); SQLSTATE: HY000

Message: The registration for %d factor authentication method is already completed. You cannot perform registration multiple times.

- Error number: 4060; Symbol: [ER\\_INVALID\\_USER\\_FOR\\_REGISTRATION](#); SQLSTATE: HY000

Message: The registration operation is not allowed for user '%s'@'%s'. The operation can only be performed in user's own session.

- Error number: 4061; Symbol: [ER\\_USER\\_REGISTRATION\\_FAILED](#); SQLSTATE: HY000

Message: Authentication plugin's registration failed.

- Error number: 4062; Symbol: [ER\\_MFA\\_METHODS\\_INVALID\\_ORDER](#); SQLSTATE: HY000

Message: %d factor authentication method should be added before %d factor authentication method.

- Error number: 4063; Symbol: [ER\\_MFA\\_METHODS\\_IDENTICAL](#); SQLSTATE: HY000

Message: Authentication factor should be different.

- Error number: 4064; Symbol: [ER\\_INVALID\\_MFA\\_OPERATIONS\\_FOR\\_PASSWORDLESS\\_USER](#); SQLSTATE: HY000

Message: The operation "%s" cannot be performed for user '%s'@'%s' configured to connect without a password.

- Error number: 4065; Symbol: [ER\\_CHANGE\\_REPLICATION\\_SOURCE\\_NO\\_OPTIONS\\_FOR\\_GTID\\_ONLY](#); SQLSTATE: HY000

Message: GTID\_ONLY cannot be enabled for replication channel '%s'. You need GTID\_MODE = ON, SOURCE\_AUTO\_POSITION = 1 and REQUIRE\_ROW\_FORMAT = 1.

- Error number: 4066; Symbol: [ER\\_CHANGE\\_REP\\_SOURCE\\_CANT\\_DISABLE\\_REQ\\_ROW\\_FORMAT\\_WITH\\_GTID\\_ONLY](#); SQLSTATE: HY000

Message: REQUIRE\_ROW\_FORMAT cannot be disabled for replication channel '%s' when GTID\_ONLY=1.

- 
- Error number: 4067; Symbol: [ER\\_CHANGE\\_REP\\_SOURCE\\_CANT\\_DISABLE\\_AUTO\\_POSITION\\_WITH\\_GTID\\_ONLY](#); SQLSTATE: HY000  
Message: SOURCE\_AUTO\_POSITION cannot be disabled for replication channel '%s' when GTID\_ONLY=1.
  - Error number: 4068; Symbol: [ER\\_CHANGE\\_REP\\_SOURCE\\_CANT\\_DISABLE\\_GTID\\_ONLY\\_WITHOUT\\_POSITIONS](#); SQLSTATE: HY000  
Message: When disabling GTID\_ONLY and SOURCE\_AUTO\_POSITION FOR CHANNEL '%s' you must provide SOURCE\_LOG\_FILE and SOURCE\_LOG\_POS as source positions are invalid.
  - Error number: 4069; Symbol: [ER\\_CHANGE\\_REP\\_SOURCE\\_CANT\\_DISABLE\\_AUTO\\_POS\\_WITHOUT\\_POSITIONS](#); SQLSTATE: HY000  
Message: When disabling SOURCE\_AUTO\_POSITION FOR CHANNEL '%s' you must provide SOURCE\_LOG\_FILE and SOURCE\_LOG\_POS as source positions are invalid.
  - Error number: 4070; Symbol: [ER\\_CHANGE\\_REP\\_SOURCE\\_GR\\_CHANNEL\\_WITH\\_GTID\\_MODE\\_NOT\\_ON](#); SQLSTATE: HY000  
Message: When configuring a group replication channel you must do it when GTID\_MODE = ON.
  - Error number: 4071; Symbol: [ER\\_CANT\\_USE\\_GTID\\_ONLY\\_WITH\\_GTID\\_MODE\\_NOT\\_ON](#); SQLSTATE: HY000  
Message: Replication cannot start%s with GTID\_ONLY = 1 as this server uses @@GLOBAL.GTID\_MODE <> ON.
  - Error number: 4072; Symbol: [ER\\_WARN\\_C\\_DISABLE\\_GTID\\_ONLY\\_WITH\\_SOURCE\\_AUTO\\_POS\\_INVALID\\_POS](#); SQLSTATE: HY000  
Message: The replication positions relative to the source may be out-of-date on channel '%s', due to the use of GTID\_ONLY=1. The out-of-date positions can still be used in some cases so, in order to update them, we suggest that you start the replication to receive and apply at least one transaction, which will set the positions to valid values.
  - Error number: 4073; Symbol: [ER\\_DA\\_SSL\\_FIPS\\_MODE\\_ERROR](#); SQLSTATE: HY000  
Message: SSL fips mode error: %s
  - Error number: 4074; Symbol: [ER\\_VALUE\\_OUT\\_OF\\_RANGE](#); SQLSTATE: HY000  
Message: %s=%llu is outside the valid range [%llu,%llu]. %llu will be used.
  - Error number: 4075; Symbol: [ER\\_FULLTEXT\\_WITH\\_ROLLUP](#); SQLSTATE: HY000  
Message: MATCH does not support ROLLUP columns.
  - Error number: 4076; Symbol: [ER\\_REGEXP\\_MISSING\\_RESOURCE](#); SQLSTATE: HY000  
Message: Missing locale resource in regular expression library.
  - Error number: 4077; Symbol: [ER\\_WARN\\_REGEXP\\_USING\\_DEFAULT](#); SQLSTATE: HY000  
Message: Regular expression library used default (root) locale.
  - Error number: 4078; Symbol: [ER\\_REGEXP\\_MISSING\\_FILE](#); SQLSTATE: HY000



---

Message: Missing data file in regular expression library.

- Error number: 4079; Symbol: [ER\\_WARN\\_DEPRECATED\\_COLLATION](#); SQLSTATE: HY000

Message: '%s' is a collation of the deprecated character set %s. Please consider using %s with an appropriate collation instead.

- Error number: 4080; Symbol: [ER\\_CONCURRENT\\_PROCEDURE\\_USAGE](#); SQLSTATE: HY000

Message: The %s was called when there was already another concurrent call to this procedure. No action was taken. Wait for other calls to %s to finish before retrying.

- Error number: 4081; Symbol: [ER\\_DA\\_GLOBAL\\_CONN\\_LIMIT](#); SQLSTATE: HY000

Message: Connection closed. Global connection memory limit %llu bytes exceeded. Consumed %llu bytes.

- Error number: 4082; Symbol: [ER\\_DA\\_CONN\\_LIMIT](#); SQLSTATE: HY000

Message: Connection closed. Connection memory limit %llu bytes exceeded. Consumed %llu bytes.

- Error number: 4083; Symbol: [ER\\_ALTER\\_OPERATION\\_NOT\\_SUPPORTED\\_REASON\\_COLUMN\\_TYPE\\_INSTANT](#); SQLSTATE: HY000

Message: Need to rebuild the table to change column type

- Error number: 4084; Symbol: [ER\\_WARN\\_SF\\_UDF\\_NAME\\_COLLISION](#); SQLSTATE: HY000

Message: This function '%s' has the same name as a loadable function (UDF). To invoke the stored function, it is necessary to qualify it with the schema name.

- Error number: 4085; Symbol: [ER\\_CANNOT\\_PURGE\\_BINLOG\\_WITH\\_BACKUP\\_LOCK](#); SQLSTATE: HY000

Message: Could not purge binary logs since another session is executing LOCK INSTANCE FOR BACKUP. Wait for that session to release the lock.

- Error number: 4086; Symbol: [ER\\_TOO\\_MANY\\_WINDOWS](#); SQLSTATE: HY000

Message: Too many windows in SELECT: %d. Maximum allowed is %d. Use named windows to share windows between window functions.

- Error number: 4087; Symbol: [ER\\_MYSQLBACKUP\\_CLIENT\\_MSG](#); SQLSTATE: HY000

Message: %s

- Error number: 4088; Symbol: [ER\\_COMMENT\\_CONTAINS\\_INVALID\\_STRING](#); SQLSTATE: HY000

Message: Comment for %s '%s' contains an invalid %s character string: '%s'.

- Error number: 4089; Symbol: [ER\\_DEFINITION\\_CONTAINS\\_INVALID\\_STRING](#); SQLSTATE: HY000

Message: Definition of %s '%s.%s' contains an invalid %s character string: '%s'.

- Error number: 4090; Symbol: [ER\\_CANT\\_EXECUTE\\_COMMAND\\_WITH\\_ASSIGNED\\_GTID\\_NEXT](#); SQLSTATE: HY000

Message: Can't execute the given command when @@SESSION.GTID\_NEXT == 'UUID:NUMBER'.

- Error number: 4091; Symbol: [ER\\_XA\\_TEMP\\_TABLE](#); SQLSTATE: HY000

---

Message: XA: Temporary tables cannot be accessed inside XA transactions when xa\_detach\_on\_prepare=ON

- Error number: 4092; Symbol: [ER\\_INNODB\\_MAX\\_ROW\\_VERSION](#); SQLSTATE: HY000

Message: Maximum row versions reached for table %s. No more columns can be added or dropped instantly. Please use COPY/INPLACE.

- Error number: 4094; Symbol: [ER\\_OPERATION\\_NOT\\_ALLOWED\\_WHILE\\_PRIMARY\\_CHANGE\\_IS\\_RUNNING](#); SQLSTATE: HY000

Message: All queries have been blocked while function 'group\_replication\_set\_as\_primary()' is executing. Please refer timeout parameter of function 'group\_replication\_set\_as\_primary()'.

- Error number: 4095; Symbol: [ER\\_WARN\\_DEPRECATED\\_DATETIME\\_DELIMITER](#); SQLSTATE: HY000

Message: Delimiter '%s' in position %d in datetime value '%s' at row %d is deprecated. Prefer the standard '%c'.

- Error number: 4096; Symbol: [ER\\_WARN\\_DEPRECATED\\_SUPERFLUOUS\\_DELIMITER](#); SQLSTATE: HY000

Message: Delimiter '%s' in position %d in datetime value '%s' at row %d is superfluous and is deprecated. Please remove.

- Error number: 4097; Symbol: [ER\\_CANNOT\\_PERSIST\\_SENSITIVE\\_VARIABLES](#); SQLSTATE: HY000

Message: Cannot persist SENSITIVE system variable '%s' because keyring component support is unavailable.

- Error number: 4098; Symbol: [ER\\_WARN\\_CANNOT\\_SECURELY\\_PERSIST\\_SENSITIVE\\_VARIABLES](#); SQLSTATE: HY000

Message: SENSITIVE system variable '%s' was persisted without encryption. Consider restarting server with keyring component support to persist SENSITIVE variables securely.

- Error number: 4099; Symbol: [ER\\_WARN\\_TRG\\_ALREADY\\_EXISTS](#); SQLSTATE: HY000

Message: Trigger '%s' already exists on the table '%s'. '%s'.

- Error number: 4100; Symbol: [ER\\_IF\\_NOT\\_EXISTS\\_UNSUPPORTED\\_TRG\\_EXISTS\\_ON\\_DIFFERENT\\_TABLE](#); SQLSTATE: HY000

Message: Trigger '%s'. '%s' already exists on a different table. The 'IF NOT EXISTS' clause is only supported for triggers associated with the same table.

- Error number: 4101; Symbol: [ER\\_IF\\_NOT\\_EXISTS\\_UNSUPPORTED\\_UDF\\_NATIVE\\_FCT\\_NAME\\_COLLISION](#); SQLSTATE: HY000

Message: This function '%s' has the same name as a native function. The 'IF NOT EXISTS' clause is not supported while creating a loadable function with the same name as a native function.

- Error number: 4102; Symbol: [ER\\_SET\\_PASSWORD\\_AUTH\\_PLUGIN\\_ERROR](#); SQLSTATE: HY000

Message: SET PASSWORD has no significance for user '%s'@'%s' as the authentication method used doesn't store authentication data in the MySQL server. Please consider using ALTER USER instead if you want to change authentication parameters.

- Error number: 4105; Symbol: [ER\\_SRS\\_INVALID\\_LATITUDE\\_OF\\_ORIGIN](#); SQLSTATE: SR002

---

Message: Latitude of origin must be within [-90, 90] degrees, specified in the SRS angular unit.

- Error number: 4106; Symbol: `ER_SRS_INVALID_LONGITUDE_OF_ORIGIN`; SQLSTATE: `SR002`

Message: Longitude of origin must be within (-180, 180] degrees, specified in the SRS angular unit.

- Error number: 4107; Symbol: `ER_SRS_UNUSED_PROJ_PARAMETER_PRESENT`; SQLSTATE: `SR002`

Message: The spatial reference system definition for SRID %u contains unused projection parameter "%s".

- Error number: 4108; Symbol: `ER_GIPK_COLUMN_EXISTS`; SQLSTATE: `HY000`

Message: Failed to generate invisible primary key. Column 'my\_row\_id' already exists.

- Error number: 4109; Symbol: `ER_GIPK_FAILED_AUTOINC_COLUMN_EXISTS`; SQLSTATE: `HY000`

Message: Failed to generate invisible primary key. Auto-increment column already exists.

- Error number: 4110; Symbol: `ER_GIPK_COLUMN_ALTER_NOT_ALLOWED`; SQLSTATE: `HY000`

Message: Altering generated invisible primary key column 'my\_row\_id' is not allowed.

- Error number: 4111; Symbol: `ER_DROP_PK_COLUMN_TO_DROP_GIPK`; SQLSTATE: `HY000`

Message: Please drop primary key column to be able to drop generated invisible primary key.

- Error number: 4112; Symbol: `ER_CREATE_SELECT_WITH_GIPK_DISALLOWED_IN_SBR`; SQLSTATE: `HY000`

Message: Generating an invisible primary key for a table created using CREATE TABLE ... SELECT ... is disallowed when binlog\_format=STATEMENT. It cannot be guaranteed that the SELECT retrieves rows in the same order on source and replica. Therefore, it cannot be guaranteed that the value generated for the generated implicit primary key column will be the same on source and replica for all rows. Use binlog\_format=ROW or MIXED to execute this statement.

- Error number: 4114; Symbol: `ER_CTE_RECURSIVE_NOT_UNION`; SQLSTATE: `HY000`

Message: Recursive table reference in EXCEPT or INTERSECT operand is not allowed.

- Error number: 4115; Symbol: `ER_COMMAND_BACKEND_FAILED_TO_FETCH_SECURITY_CTX`; SQLSTATE: `HY000`

Message: Error when trying to fetch information from security context object, when trying to connect the server.

- Error number: 4116; Symbol: `ER_COMMAND_SERVICE_BACKEND_FAILED`; SQLSTATE: `HY000`

Message: Error in command service backend interface, because of : "%s"

- Error number: 4117; Symbol: `ER_CLIENT_FILE_PRIVILEGE_FOR_REPLICATION_CHECKS`; SQLSTATE: `HY000`

Message: The PRIVILEGE\_CHECKS\_USER for channel '%s' would need FILE privilege to execute a LOAD DATA INFILE statement replicated in statement format. Consider using binlog\_format=ROW on source. If the replicated events are trusted, recover from the failure by temporarily granting FILE to the PRIVILEGE\_CHECKS\_USER.

- Error number: 4118; Symbol: `ER_GROUP_REPLICATION_FORCE_MEMBERS_COMMAND_FAILURE`; SQLSTATE: `HY000`

Message: The 'SET GLOBAL group\_replication\_force\_members=%s' command encountered a failure. %s

- 
- Error number: 4119; Symbol: `ER_WARN_DEPRECATED_IDENT`; SQLSTATE: `HY000`  
Message: Using %s as unquoted identifier is deprecated, please use quotes or rename the identifier.
  - Error number: 4120; Symbol: `ER_INTERSECT_ALL_MAX_DUPLICATES_EXCEEDED`; SQLSTATE: `HY000`  
Message: Max number of duplicate rows in INTERSECT ALL exceeded.
  - Error number: 4121; Symbol: `ER_TP_QUERY_THRS_PER_GRP_EXCEEDS_TXN_THR_LIMIT`; SQLSTATE: `HY000`  
Message: Query threads count(%u) exceeds transaction threads limit(%u) per group. Please use query threads count per group smaller or equal to max transaction threads limit per group
  - Error number: 4122; Symbol: `ER_BAD_TIMESTAMP_FORMAT`; SQLSTATE: `HY000`  
Message: Invalid timestamp format in %s udf
  - Error number: 4123; Symbol: `ER_SHAPE_PREDICTION_UDF`; SQLSTATE: `HY000`  
Message: SHAPE\_PREDICTION UDF %s got error because of %s.
  - Error number: 4124; Symbol: `ER_SRS_INVALID_HEIGHT`; SQLSTATE: `SR002`  
Message: Height parameter must be non negative.
  - Error number: 4125; Symbol: `ER_SRS_INVALID_SCALING`; SQLSTATE: `SR002`  
Message: Scaling parameter must be non negative.
  - Error number: 4126; Symbol: `ER_SRS_INVALID_ZONE_WIDTH`; SQLSTATE: `SR002`  
Message: Zone width parameter must be an integer between 1-60.
  - Error number: 4127; Symbol: `ER_SRS_INVALID_LATITUDE_POLAR_STERE_VAR_A`; SQLSTATE: `SR002`  
Message: Latitude of origin must be +-90 degrees, specified in the SRS angular unit, in Polar Stereographic (variant A) projection method (EPSG:9810).
  - Error number: 4128; Symbol: `ER_WARN_DEPRECATED_CLIENT_NO_SCHEMA_OPTION`; SQLSTATE: `HY000`  
Message: The client is using a deprecated CLIENT\_NO\_SCHEMA client option. CLIENT\_NO\_SCHEMA will be removed in a future release.
  - Error number: 4129; Symbol: `ER_TABLE_NOT_EMPTY`; SQLSTATE: `HY000`  
Message: Table '%s' is not empty.
  - Error number: 4130; Symbol: `ER_TABLE_NO_PRIMARY_KEY`; SQLSTATE: `HY000`  
Message: Table '%s' has no primary key.
  - Error number: 4131; Symbol: `ER_TABLE_IN_SHARED_TABLESPACE`; SQLSTATE: `HY000`  
Message: Table '%s' is in a shared tablespace.
  - Error number: 4132; Symbol: `ER_INDEX_OTHER_THAN_PK`; SQLSTATE: `HY000`  
Message: Table '%s' has indexes other than primary key.
  - Error number: 4133; Symbol: `ER_LOAD_BULK_DATA_UNSORTED`; SQLSTATE: `HY000`

---

Message: [IN PRIMARY KEY ORDER] specified but data not sorted: '%s'

- Error number: 4134; Symbol: [ER\\_BULK\\_EXECUTOR\\_ERROR](#); SQLSTATE: HY000

Message: Bulk executor error: %s

- Error number: 4135; Symbol: [ER\\_BULK\\_READER\\_LIBCURL\\_INIT\\_FAILED](#); SQLSTATE: HY000

Message: Bulk reader failed to initialize libcurl

- Error number: 4136; Symbol: [ER\\_BULK\\_READER\\_LIBCURL\\_ERROR](#); SQLSTATE: HY000

Message: Bulk reader got libcurl error: %s

- Error number: 4137; Symbol: [ER\\_BULK\\_READER\\_SERVER\\_ERROR](#); SQLSTATE: HY000

Message: Bulk reader got error response from server: %ld

- Error number: 4138; Symbol: [ER\\_BULK\\_READER\\_COMMUNICATION\\_ERROR](#); SQLSTATE: HY000

Message: Bulk reader got error in communication with source server, check the error log for additional details.

- Error number: 4139; Symbol: [ER\\_BULK\\_LOAD\\_DATA\\_FAILED](#); SQLSTATE: HY000

Message: Bulk loader failed in Innodb storage engine, check the error log for additional details.

- Error number: 4140; Symbol: [ER\\_BULK\\_LOADER\\_COLUMN\\_TOO\\_BIG\\_FOR\\_LEFTOVER\\_BUFFER](#); SQLSTATE: HY000

Message: CSV column too big for leftover buffer.

- Error number: 4141; Symbol: [ER\\_BULK\\_LOADER\\_COMPONENT\\_ERROR](#); SQLSTATE: HY000

Message: Bulk loader component error: %s

- Error number: 4142; Symbol: [ER\\_BULK\\_LOADER\\_FILE\\_CONTAINS\\_LESS\\_LINES\\_THAN\\_IGNORE\\_CLAUSE](#); SQLSTATE: HY000

Message: The first file being loaded contained less lines than the ignore clause

- Error number: 4143; Symbol: [ER\\_BULK\\_PARSER\\_MISSING\\_ENCLOSED\\_BY](#); SQLSTATE: HY000

Message: Missing ENCLOSED BY character at row %ld in file '%s'. Add OPTIONALLY to the ENCLOSED BY clause to allow this input.

- Error number: 4144; Symbol: [ER\\_BULK\\_PARSER\\_ROW\\_BUFFER\\_MAX\\_TOTAL\\_COLS\\_EXCEEDED](#); SQLSTATE: HY000

Message: The number of input columns that need to be buffered for parsing exceeded predefined buffer max size for file '%s'.

- Error number: 4145; Symbol: [ER\\_BULK\\_PARSER\\_COPY\\_BUFFER\\_SIZE\\_EXCEEDED](#); SQLSTATE: HY000

Message: The column data that needed to be copied due to escaped characters exceeded the size of the internal copy buffer for file '%s'.

- Error number: 4146; Symbol: [ER\\_BULK\\_PARSER\\_UNEXPECTED\\_END\\_OF\\_INPUT](#); SQLSTATE: HY000

Message: Unexpected end of input found at row %ld in file '%s'. Data for some columns is missing.

- 
- Error number: 4147; Symbol: [ER\\_BULK\\_PARSER\\_UNEXPECTED\\_ROW\\_TERMINATOR](#); SQLSTATE: HY000  
Message: Unexpected row terminator found at row %ld in file '%s'. Data for some columns is missing.
  - Error number: 4148; Symbol: [ER\\_BULK\\_PARSER\\_UNEXPECTED\\_CHAR\\_AFTER\\_ENDING\\_ENCLOSED\\_BY](#); SQLSTATE: HY000  
Message: Unexpected characters after ending ENCLOSED BY character found at row %ld in file '%s'.
  - Error number: 4149; Symbol: [ER\\_BULK\\_PARSER\\_UNEXPECTED\\_CHAR\\_AFTER\\_NULL\\_ESCAPE](#); SQLSTATE: HY000  
Message: Unexpected characters after NULL escape (\N) found at row %ld in file '%s'.
  - Error number: 4150; Symbol: [ER\\_BULK\\_PARSER\\_UNEXPECTED\\_CHAR\\_AFTER\\_COLUMN\\_TERMINATOR](#); SQLSTATE: HY000  
Message: Unexpected characters after column terminator found at row %ld in file '%s'.
  - Error number: 4151; Symbol: [ER\\_BULK\\_PARSER\\_INCOMPLETE\\_ESCAPE\\_SEQUENCE](#); SQLSTATE: HY000  
Message: Unexpected end of input found at row %ld in file '%s' resulting in incomplete escape sequence.
  - Error number: 4152; Symbol: [ER\\_LOAD\\_BULK\\_DATA\\_FAILED](#); SQLSTATE: HY000  
Message: LOAD BULK DATA into table '%s' failed: %s
  - Error number: 4153; Symbol: [ER\\_LOAD\\_BULK\\_DATA\\_WRONG\\_VALUE\\_FOR\\_FIELD](#); SQLSTATE: HY000  
Message: Incorrect %s value: '%s' for column '%s' at row %ld in file '%s'
  - Error number: 4154; Symbol: [ER\\_LOAD\\_BULK\\_DATA\\_WARN\\_NULL\\_TO\\_NOTNULL](#); SQLSTATE: HY000  
Message: NULL supplied to NOT NULL column '%s' at row %ld in file '%s'
  - Error number: 4155; Symbol: [ER\\_REQUIRE\\_TABLE\\_PRIMARY\\_KEY\\_CHECK\\_GENERATE\\_WITH\\_GR](#); SQLSTATE: HY000  
Message: On a Group Replication channel, setting REQUIRE\_TABLE\_PRIMARY\_KEY\_CHECK to 'GENERATE' is not allowed.
  - Error number: 4156; Symbol: [ER\\_CANT\\_CHANGE\\_SYS\\_VAR\\_IN\\_READ\\_ONLY\\_MODE](#); SQLSTATE: HY000  
Message: Cannot change the '%s' system variable in read-only mode.
  - Error number: 4157; Symbol: [ER\\_INNODB\\_INSTANT\\_ADD\\_DROP\\_NOT\\_SUPPORTEDED\\_MAX\\_SIZE](#); SQLSTATE: HY000  
Message: Column can't be added or dropped with ALGORITHM=INSTANT as either max possible row size already crosses max permissible row size or may cross it after add. Try ALGORITHM=INPLACE/COPY.
  - Error number: 4158; Symbol: [ER\\_INNODB\\_INSTANT\\_ADD\\_NOT\\_SUPPORTEDED\\_MAX\\_FIELDS](#); SQLSTATE: HY000

---

Message: Column can't be added to '%s' with ALGORITHM=INSTANT anymore. Please try ALGORITHM=INPLACE/COPY.

- Error number: 4159; Symbol: [ER\\_CANT\\_SET\\_PERSISTED](#); SQLSTATE: HY000

Message: Failed to set persisted options.

- Error number: 4160; Symbol: [ER\\_INSTALL\\_COMPONENT\\_SET\\_NULL\\_VALUE](#); SQLSTATE: HY000

Message: The value supplied for %s in the SET list cannot be null

- Error number: 4161; Symbol: [ER\\_INSTALL\\_COMPONENT\\_SET\\_UNUSED\\_VALUE](#); SQLSTATE: HY000

Message: The assignment of %s in SET doesn't match any of the variables registered by the component(s)

- Error number: 4162; Symbol: [ER\\_WARN\\_DEPRECATED\\_USER\\_DEFINED\\_COLLATIONS](#); SQLSTATE: HY000

Message: '%s' is a user defined collation. User defined collations are deprecated and will be removed in a future release. Consider using a compiled collation instead.

- Error number: 4163; Symbol: [ER\\_USER\\_LOCK\\_OVERLONG\\_NAME](#); SQLSTATE: 42000

Message: User-level lock name '%s' should not exceed %d characters.

- Error number: 4164; Symbol: [ER\\_WARN\\_NO\\_SPACE\\_VERSION\\_COMMENT](#); SQLSTATE: HY000

Message: Immediately starting the version comment after the version number is deprecated and may change behavior in a future release. Please insert a white-space character after the version number.

- Error number: 4165; Symbol: [ER\\_VALIDATE\\_PASSWORD\\_INSUFFICIENT\\_CHANGED\\_CHARACTERS](#); SQLSTATE: HY000

Message: The new password must have at least '%u' characters that are different from the old password. It has only '%u' character(s) different. For this comparison, uppercase letters and lowercase letters are considered to be equal.

- Error number: 4166; Symbol: [ER\\_WARN\\_DEPRECATED\\_WITH\\_NOTE](#); SQLSTATE: HY000

Message: '%s' is deprecated and will be removed in a future release. %s

- Error number: 6000; Symbol: [ER\\_LANGUAGE\\_COMPONENT](#); SQLSTATE: HY000

Message: %s

- Error number: 6001; Symbol: [ER\\_LANGUAGE\\_COMPONENT\\_NOT\\_AVAILABLE](#); SQLSTATE: HY000

Message: No Language component available

- Error number: 6002; Symbol: [ER\\_LANGUAGE\\_COMPONENT\\_UNSUPPORTED\\_LANGUAGE](#); SQLSTATE: HY000

Message: Unsupported external language: %s

- Error number: 6003; Symbol: [ER\\_LANGUAGE\\_COMPONENT\\_CANNOT\\_UNINSTALL](#); SQLSTATE: HY000

Message: Cannot uninstall Multilingual Engine - there are sessions still connected. Please disconnect all sessions and try again.

- Error number: 6004; Symbol: [ER\\_SP\\_NO\\_ALTER\\_LANGUAGE](#); SQLSTATE: HY000

---

Message: Altering the language of an existing routine is not possible.

- Error number: 6005; Symbol: ER\_EXPLAIN\_INT0\_ANALYZE\_NOT\_SUPPORTED; SQLSTATE: 0A000

Message: EXPLAIN ANALYZE does not support the INTO clause.

- Error number: 6006; Symbol: ER\_EXPLAIN\_INT0\_IMPLICIT\_FORMAT\_NOT\_SUPPORTED; SQLSTATE: 0A000

Message: EXPLAIN INTO does not support implicit FORMAT.

- Error number: 6007; Symbol: ER\_EXPLAIN\_INT0\_FORMAT\_NOT\_SUPPORTED; SQLSTATE: 0A000

Message: EXPLAIN INTO does not support FORMAT=%s.

- Error number: 6008; Symbol: ER\_NULL\_CANT\_BE\_PERSISTED\_FOR\_READONLY; SQLSTATE: HY000

Message: Trying to persist a NULL into a variable '%s' that's settable only on command line is not supported

- Error number: 6009; Symbol: ER\_EXPLAIN\_INT0\_FOR\_CONNECTION\_NOT\_SUPPORTED; SQLSTATE: 0A000

Message: EXPLAIN FOR CONNECTION does not support the INTO clause.

- Error number: 6010; Symbol: ER\_INNOQB\_IMPORT\_WRONG\_DROPPED\_ENUM\_LENGTH; SQLSTATE: HY000

Message: Enum element name length %lu, is invalid for column %s

- Error number: 6011; Symbol: ER\_INNOQB\_IMPORT\_WRONG\_NUMBER\_OF\_INDEXES\_ZERO; SQLSTATE: HY000

Message: Number of indexes in meta-data file is 0

- Error number: 6012; Symbol: ER\_INNOQB\_IMPORT\_WRONG\_NUMBER\_OF\_INDEXES\_TOO\_HIGH; SQLSTATE: HY000

Message: Number of indexes in meta-data file is too high: %llu

- Error number: 6013; Symbol: ER\_INNOQB\_IMPORT\_DROP\_COL\_METADATA\_MISMATCH; SQLSTATE: HY000

Message: DD metadata for INSTANT DROP column %s in target table doesn't match with CFG.

- Error number: 6014; Symbol: ER\_INNOQB\_IMPORT\_ENUM\_NULL\_TERMINATOR\_MISSING; SQLSTATE: HY000

Message: Enum/Set element name missing null terminator for column '%s'

- Error number: 6015; Symbol: ER\_SIMULATED\_INJECTION\_ERROR; SQLSTATE: HY000

Message: %s %s %zu.

- Error number: 6016; Symbol: ER\_WARN\_DEPRECATED\_DYNAMIC\_PRIV\_IN\_GRANT; SQLSTATE: HY000

Message: The privilege '%s' is deprecated.

- Error number: 6017; Symbol: ER\_BULK\_MULTI\_READER\_OPEN\_FILE\_FAILED; SQLSTATE: HY000



---

Message: Bulk Multi Reader: Failed to open file

- Error number: 6018; Symbol: [ER\\_BULK\\_MULTI\\_READER\\_READ\\_FILE\\_FAILED](#); SQLSTATE: HY000

Message: Bulk Multi Reader: Failed to read file

- Error number: 6019; Symbol: [ER\\_BULK\\_MERGE\\_INVALID\\_CHUNK](#); SQLSTATE: HY000

Message: Bulk Merge Loader: Invalid Chunk

- Error number: 6020; Symbol: [ER\\_BULK\\_MERGE\\_NOT\\_ALL\\_CHUNKS\\_CONSUMED](#); SQLSTATE: HY000

Message: Bulk Merge Loader: Not all chunks consumed

- Error number: 6021; Symbol: [ER\\_BULK\\_WRITER\\_LIBCURL\\_INIT\\_FAILED](#); SQLSTATE: HY000

Message: Bulk writer failed to initialize libcurl

- Error number: 6022; Symbol: [ER\\_BULK\\_WRITER\\_LIBCURL\\_ERROR](#); SQLSTATE: HY000

Message: Bulk writer got libcurl error: %s

- Error number: 6023; Symbol: [ER\\_BULK\\_SORTING\\_LOADER\\_WRITE](#); SQLSTATE: HY000

Message: Bulk Sorting Loader: Failed to write data to temporary file

- Error number: 6024; Symbol: [ER\\_BULK\\_SORTING\\_LOADER\\_WAIT](#); SQLSTATE: HY000

Message: Bulk Sorting Loader: Interrupted while waiting

- Error number: 6025; Symbol: [ER\\_BULK\\_READER\\_OPEN\\_FILE\\_FAILED](#); SQLSTATE: HY000

Message: Bulk Reader: Failed to access file %s

- Error number: 6026; Symbol: [ER\\_BULK\\_LOAD\\_TABLE\\_HAS\\_INSTANT\\_COLS](#); SQLSTATE: HY000

Message: Bulk Loader: Table '%s' has instantly added/dropped columns. Please TRUNCATE TABLE and retry.

- Error number: 6027; Symbol: [ER\\_BULK\\_LOAD\\_RESOURCE](#); SQLSTATE: HY000

Message: Bulk Loader: Not enough memory available. Memory needed for loading %s data: %s for %u threads, %s with minimal configuration. Total configured memory is %s, Available memory is %s.

- Error number: 6028; Symbol: [ER\\_BULK\\_LOAD\\_SECONDARY\\_ENGINE](#); SQLSTATE: HY000

Message: LOAD DATA with BULK Algorithm is not supported on a table with secondary engine.

- Error number: 6029; Symbol: [ER\\_BULK\\_READER\\_ERROR](#); SQLSTATE: HY000

Message: Bulk reader error: %s

- Error number: 6030; Symbol: [ER\\_BULK\\_READER\\_FILE\\_DOESNT\\_EXIST](#); SQLSTATE: HY000

Message: File not found, check whether it exists: %s

- Error number: 6031; Symbol: [ER\\_BULK\\_READER\\_COULDNT\\_RESOLVE\\_HOST](#); SQLSTATE: HY000

Message: Couldn't resolve host: %s

- Error number: 6032; Symbol: [ER\\_START\\_REPLICA\\_CHANNEL\\_INVALID\\_CONFIGURATION](#); SQLSTATE: HY000

---

Message: Cannot start replication channel '%s' because %s.

- Error number: 6033; Symbol: [ER\\_CANNOT\\_EXECUTE\\_IN\\_PRIMARY](#); SQLSTATE: HY000

Message: '%s' is not supported

- Error number: 6034; Symbol: [ER\\_TOO\\_MANY\\_GROUP\\_BY\\_MODIFIER\\_BRANCHES](#); SQLSTATE: HY000

Message: '%s' is supported with maximum %d elements in the GROUP BY list

- Error number: 6035; Symbol: [ER\\_WARN\\_DEPRECATED\\_ENGINE\\_SYNTAX\\_NO\\_REPLACEMENT](#); SQLSTATE: HY000

Message: '%s' for '%s' storage engine is deprecated and will be removed in a future release.

- Error number: 6036; Symbol: [ER\\_QUALIFY\\_WITHOUT\\_WINDOW\\_FUNCTION](#); SQLSTATE: HY000

Message: QUALIFY clause cannot be used without a window function.

- Error number: 6037; Symbol: [ER\\_SUPPORTED\\_ONLY\\_WITH\\_HYPERGRAPH](#); SQLSTATE: HY000

Message: '%s' can be used only if the hypergraph optimizer is enabled.

- Error number: 6038; Symbol: [ER\\_SPECIFIC\\_ACCESS\\_DENIED](#); SQLSTATE: HY000

Message: Access denied; you need %s privilege(s) for this operation

- Error number: 6039; Symbol: [ER\\_CANT\\_SET\\_GTID\\_NEXT\\_TO\\_AUTOMATIC\\_TAGGED\\_WHEN\\_GTID\\_MODE\\_IS\\_OFF](#); SQLSTATE: HY000

Message: @@SESSION.GTID\_NEXT cannot be set to AUTOMATIC:<TAG> when @@GLOBAL.GTID\_MODE = OFF or OFF\_PERMISSIVE

- Error number: 6040; Symbol: [ER\\_GTID\\_NEXT\\_TAG\\_GTID\\_MODE\\_OFF](#); SQLSTATE: HY000

Message: @@SESSION.GTID\_NEXT cannot be set to UUID:TAG:NUMBER when @@GLOBAL.GTID\_MODE = OFF.

- Error number: 6041; Symbol: [ER\\_LH\\_COL\\_NOT\\_NULLABLE](#); SQLSTATE: HY000

Message: Column %d of %s : Column contains null but it is not nullable.

- Error number: 6042; Symbol: [ER\\_LH\\_WARN\\_COL\\_MISSING\\_NOT\\_NULLABLE](#); SQLSTATE: HY000

Message: Column %d of %s : Column is missing, but it is not nullable and no explicit default value is provided.

- Error number: 6043; Symbol: [ER\\_LH\\_COL\\_IS\\_EMPTY](#); SQLSTATE: HY000

Message: Column %d of %s : Column is empty.

- Error number: 6044; Symbol: [ER\\_LH\\_COL\\_IS\\_EMPTY\\_WARN](#); SQLSTATE: HY000

Message: Column %d of %s : Column is empty, setting default value.

- Error number: 6045; Symbol: [ER\\_LH\\_BAD\\_VALUE](#); SQLSTATE: HY000

Message: Column %d of %s : Invalid %s value.

- Error number: 6046; Symbol: [ER\\_LH\\_DECIMAL\\_UNKNOWN\\_ERR](#); SQLSTATE: HY000

---

Message: Column %d of %s : Unknown error while parsing decimal.

- Error number: 6047; Symbol: [ER\\_LH\\_DECIMAL\\_OOM\\_ERR](#); SQLSTATE: HY000

Message: Column %d of %s : Out of memory loading decimal.

- Error number: 6048; Symbol: [ER\\_LH\\_WARN\\_DECIMAL\\_ROUNDING](#); SQLSTATE: HY000

Message: Column %d of %s : Fraction exceeds schema, rounding value.

- Error number: 6049; Symbol: [ER\\_LH\\_DECIMAL\\_PRECISION\\_EXCEEDS\\_SCHEMA](#); SQLSTATE: HY000

Message: Column %d of %s : decimal precision exceeds schema.

- Error number: 6050; Symbol: [ER\\_LH\\_EXCEEDS\\_MIN](#); SQLSTATE: HY000

Message: Column %d of %s : %s exceeds min.

- Error number: 6051; Symbol: [ER\\_LH\\_EXCEEDS\\_MAX](#); SQLSTATE: HY000

Message: Column %d of %s : %s exceeds max.

- Error number: 6052; Symbol: [ER\\_LH\\_WARN\\_EXCEEDS\\_MIN\\_TRUNCATING](#); SQLSTATE: HY000

Message: Column %d of %s : %s exceeds min, setting to min value possible.

- Error number: 6053; Symbol: [ER\\_LH\\_WARN\\_EXCEEDS\\_MAX\\_TRUNCATING](#); SQLSTATE: HY000

Message: Column %d of %s : %s exceeds max, setting to max value possible.

- Error number: 6054; Symbol: [ER\\_LH\\_REAL\\_IS\\_NAN](#); SQLSTATE: HY000

Message: Column %d of %s : Real value is NaN.

- Error number: 6055; Symbol: [ER\\_LH\\_OUT\\_OF\\_RANGE](#); SQLSTATE: HY000

Message: Column %d of %s : %s value is out of range.

- Error number: 6056; Symbol: [ER\\_LH\\_DATETIME\\_FORMAT](#); SQLSTATE: HY000

Message: Column %d of %s : Error while applying %s format.

- Error number: 6057; Symbol: [ER\\_LH\\_WARN\\_TRUNCATED](#); SQLSTATE: HY000

Message: Column %d of %s : %s value was truncated.

- Error number: 6058; Symbol: [ER\\_LH\\_CANNOT\\_CONVERT\\_STRING](#); SQLSTATE: HY000

Message: Column %d of %s : Cannot convert string %s.

- Error number: 6059; Symbol: [ER\\_LH\\_RESOURCE\\_PRINCIPAL\\_ERR](#); SQLSTATE: HY000

Message: Resource principal error.

- Error number: 6060; Symbol: [ER\\_LH\\_AWS\\_AUTH\\_ERR](#); SQLSTATE: HY000

Message: AWS authentication error.

- Error number: 6061; Symbol: [ER\\_LH\\_CSV\\_PARSING\\_ERR](#); SQLSTATE: HY000

Message: %s:%lu: Parsing error found. %s.

- Error number: 6062; Symbol: [ER\\_LH\\_COLUMN\\_MISMATCH\\_ERR](#); SQLSTATE: HY000

- 
- Message: %s: Mismatch in the number of columns. Expected %u, found %u.
- Error number: 6063; Symbol: [ER\\_LH\\_COLUMN\\_MAX\\_ERR](#); SQLSTATE: HY000  
Message: %s: More than %u column(s) found.
  - Error number: 6064; Symbol: [ER\\_LH\\_CHARSET\\_UNSUPPORTED](#); SQLSTATE: HY000  
Message: Column %d in %s: Charset is not supported.
  - Error number: 6065; Symbol: [ER\\_LH\\_PARQUET\\_DECIMAL\\_CONVERSION\\_ERR](#); SQLSTATE: HY000  
Message: Column %d in %s: Decimal conversion error.
  - Error number: 6066; Symbol: [ER\\_LH\\_STRING\\_TOO\\_LONG](#); SQLSTATE: HY000  
Message: Column %d in %s: String is too long.
  - Error number: 6067; Symbol: [ER\\_LH\\_RESOURCE\\_PRINCIPAL\\_BUCKET\\_ERR](#); SQLSTATE: HY000  
Message: Resource Principal endpoint is not configured. Cannot access following buckets: %s.
  - Error number: 6068; Symbol: [ER\\_LH\\_NO\\_FILES\\_FOUND](#); SQLSTATE: HY000  
Message: No files found corresponding to the following data locations: %s.
  - Error number: 6069; Symbol: [ER\\_LH\\_EMPTY\\_FILE](#); SQLSTATE: HY000  
Message: File %s is empty.
  - Error number: 6070; Symbol: [ER\\_LH\\_DUPLICATE\\_FILE](#); SQLSTATE: HY000  
Message: File %s was not processed (duplicate).
  - Error number: 6071; Symbol: [ER\\_LH\\_AVRO\\_SCHEMA\\_DEPTH\\_EXCEEDS\\_MAX](#); SQLSTATE: HY000  
Message: File %s: Avro schema depth exceeds max allowed depth.
  - Error number: 6072; Symbol: [ER\\_LH\\_AVRO\\_HEADER\\_MISMATCH](#); SQLSTATE: HY000  
Message: File %s: Header does not match other files.
  - Error number: 6073; Symbol: [ER\\_LH\\_AVRO\\_ENUM\\_CANNOT\\_CONVERT\\_CHARSET](#); SQLSTATE: HY000  
Message: File %s: Enum symbol can't convert to column charset.
  - Error number: 6074; Symbol: [ER\\_LH\\_AVRO\\_ENUM\\_MISMATCH](#); SQLSTATE: HY000  
Message: File %s: Enum symbols are not the same, or are not in the same order.
  - Error number: 6075; Symbol: [ER\\_LH\\_AVRO\\_TYPE\\_CANNOT\\_CONVERT](#); SQLSTATE: HY000  
Message: Column %d in %s: Avro value of physical type %.\*s logical type %.\*s cannot be converted to mysql type %s.
  - Error number: 6076; Symbol: [ER\\_LH\\_AVRO\\_FILE\\_ENDS\\_UNEXPECTEDLY](#); SQLSTATE: HY000  
Message: File %.\*s: Ends unexpectedly.
  - Error number: 6077; Symbol: [ER\\_LH\\_AVRO\\_FILE\\_DATA\\_CORRUPT](#); SQLSTATE: HY000  
Message: File %.\*s: File data might be corrupt.

- 
- Error number: 6078; Symbol: [ER\\_LH\\_AVRO\\_INVALID\\_UNION](#); SQLSTATE: HY000  
Message: Column %d in %s: Invalid union encountered. Unions are only supported to represent nullable columns. One of the two types of the union must be null.
  - Error number: 6079; Symbol: [ER\\_LH\\_AVRO\\_INVALID\\_BLOCK\\_SIZE](#); SQLSTATE: HY000  
Message: File %.\*s: Invalid avro block size.
  - Error number: 6080; Symbol: [ER\\_LH\\_AVRO\\_INVALID\\_BLOCK\\_RECORD\\_COUNT](#); SQLSTATE: HY000  
Message: File %.\*s: Invalid Avro block record count.
  - Error number: 6081; Symbol: [ER\\_LH\\_FORMAT\\_HEADER\\_NO\\_MAGIC\\_BYTES](#); SQLSTATE: HY000  
Message: File %.\*s: Cannot locate %s specific metadata. Either the file is corrupted or this is not an %s file.
  - Error number: 6082; Symbol: [ER\\_LH\\_AVRO\\_HEADER\\_METADATA\\_ERR](#); SQLSTATE: HY000  
Message: File %.\*s: Could not process Avro header metadata. The metadata is corrupted or invalid.
  - Error number: 6083; Symbol: [ER\\_LH\\_AVRO\\_HEADER\\_NO\\_SCHEMA](#); SQLSTATE: HY000  
Message: File %.\*s: No schema in Avro header metadata.
  - Error number: 6084; Symbol: [ER\\_LH\\_AVRO\\_NO\\_CODEC\\_IN\\_HEADER](#); SQLSTATE: HY000  
Message: File %.\*s: No codec in Avro header metadata.
  - Error number: 6085; Symbol: [ER\\_LH\\_AVRO\\_INVALID\\_NAME\\_IN\\_SCHEMA](#); SQLSTATE: HY000  
Message: File %.\*s: Invalid name in Avro schema.
  - Error number: 6086; Symbol: [ER\\_LH\\_AVRO\\_DECODING\\_ERR](#); SQLSTATE: HY000  
Message: File %.\*s: Error decoding Avro %.\*s. %s
  - Error number: 6087; Symbol: [ER\\_LH\\_PARQUET\\_NON\\_UTF8\\_FILE\\_ENC](#); SQLSTATE: HY000  
Message: Column %d in %s: String with non-utf8 file encoding.
  - Error number: 6088; Symbol: [ER\\_LH\\_PARQUET\\_SCHEMA\\_MISMATCH](#); SQLSTATE: HY000  
Message: Difference in schema among Parquet files.
  - Error number: 6089; Symbol: [ER\\_LH\\_PARQUET\\_ROW\\_GROUP\\_SIZE\\_EXCEEDS\\_MAX](#); SQLSTATE: HY000  
Message: File %s: Size of row group %ld is larger than maximum allowed size (%d).
  - Error number: 6090; Symbol: [ER\\_LH\\_PARQUET\\_CANNOT\\_LOCATE\\_OFFSET](#); SQLSTATE: HY000  
Message: File %s: Cannot locate offset of row group %ld in metadata.
  - Error number: 6091; Symbol: [ER\\_LH\\_PARQUET\\_TYPE\\_CANNOT\\_CONVERT](#); SQLSTATE: HY000  
Message: Column %d in parquet table cannot be converted to mysql format.
  - Error number: 6092; Symbol: [ER\\_LH\\_PARQUET\\_CANNOT\\_LOCATE\\_SCHEMA](#); SQLSTATE: HY000  
Message: Cannot locate schema in %s.
-

- 
- Error number: 6093; Symbol: [ER\\_LH\\_INFER\\_SCHEMA\\_MISMATCH](#); SQLSTATE: HY000  
Message: Found files with mismatched schemas.
  - Error number: 6094; Symbol: [ER\\_LH\\_OOM](#); SQLSTATE: HY000  
Message: Insufficient memory.
  - Error number: 6095; Symbol: [ER\\_LH\\_WARN\\_INFER\\_SKIPPED\\_LINES](#); SQLSTATE: HY000  
Message: Skipped %lu line(s) due to mismatched num of cols.
  - Error number: 6096; Symbol: [ER\\_LH\\_WARN\\_INFER\\_SKIPPED\\_FILES](#); SQLSTATE: HY000  
Message: Skipped %lu file(s) due to mismatched num of cols.
  - Error number: 6097; Symbol: [ER\\_LH\\_INFER\\_FILE\\_HAS\\_NO\\_DATA](#); SQLSTATE: HY000  
Message: File %s is skipped because it has no valid data. File is either empty or all rows are skipped.
  - Error number: 6098; Symbol: [ER\\_LH\\_INFER\\_NO\\_DATA](#); SQLSTATE: HY000  
Message: No valid data found for processing.
  - Error number: 6099; Symbol: [ER\\_LH\\_INFER\\_NO\\_FILES](#); SQLSTATE: HY000  
Message: No valid files found for processing.
  - Error number: 6100; Symbol: [ER\\_LH\\_WARN\\_INFER\\_USE\\_DEFAULT\\_COL\\_NAMES](#); SQLSTATE: HY000  
Message: Used default column names for column index(s) %s as they are %s.
  - Error number: 6101; Symbol: [ER\\_LH\\_PARQUET\\_CANNOT\\_READ\\_HEADER](#); SQLSTATE: HY000  
Message: File %s: Unable to read Parquet header.
  - Error number: 6102; Symbol: [ER\\_LH\\_INFER\\_WARN\\_GOT\\_EXCEPTION](#); SQLSTATE: HY000  
Message: Got an exception while trying to process file task.
  - Error number: 6103; Symbol: [ER\\_LH\\_AVRO\\_CANNOT\\_PARSE\\_HEADER](#); SQLSTATE: HY000  
Message: File %.\*s: Could not parse avro header. Probably corrupted avro file.
  - Error number: 6104; Symbol: [ER\\_LH\\_PARQUET\\_CANT\\_OPEN\\_FILE](#); SQLSTATE: HY000  
Message: Parquet reader cannot open %s. %s
  - Error number: MY-010000; Symbol: [ER\\_PARSER\\_TRACE](#); SQLSTATE: XX999  
Message: Parser saw: %s
  - Error number: MY-010001; Symbol: [ER\\_BOOTSTRAP\\_CANT\\_THREAD](#); SQLSTATE: HY000  
Message: Can't create thread to handle bootstrap (errno: %d)
  - Error number: MY-010002; Symbol: [ER\\_TRIGGER\\_INVALID\\_VALUE](#); SQLSTATE: HY000  
Message: Trigger for table '%s'. '%s': invalid %s value (%s).
  - Error number: MY-010003; Symbol: [ER\\_OPT\\_WRONG\\_TREE](#); SQLSTATE: HY000  
Message: Wrong tree: %s

- 
- Error number: [MY-010004](#); Symbol: [ER\\_DD\\_FAILSAFE](#); SQLSTATE: [HY000](#)  
Message: Error: Invalid %s
  - Error number: [MY-010005](#); Symbol: [ER\\_DD\\_NO\\_WRITES\\_NO\\_REPOPULATION](#); SQLSTATE: [HY000](#)  
Message: Skip re-populating collations and character sets tables in %s%read-only mode.
  - Error number: [MY-010006](#); Symbol: [ER\\_DD\\_VERSION\\_FOUND](#); SQLSTATE: [HY000](#)  
Message: Using data dictionary with version '%d'.
  - Error number: [MY-010007](#); Symbol: [ER\\_DD\\_VERSION\\_INSTALLED](#); SQLSTATE: [HY000](#)  
Message: Installed data dictionary with version %d
  - Error number: [MY-010008](#); Symbol: [ER\\_DD\\_VERSION\\_UNSUPPORTED](#); SQLSTATE: [HY000](#)  
Message: Data Dictionary version '%d' not supported.
  - Error number: [MY-010010](#); Symbol: [ER\\_LOG\\_SYSLOG\\_CANNOT\\_OPEN](#); SQLSTATE: [HY000](#)  
Message: Cannot open %s; check privileges, or remove syseventlog from --log-error-services!
  - Error number: [MY-010011](#); Symbol: [ER\\_LOG\\_SLOW\\_CANNOT\\_OPEN](#); SQLSTATE: [HY000](#)  
Message: either restart the query logging by using "SET GLOBAL SLOW\_QUERY\_LOG=ON" or
  - Error number: [MY-010012](#); Symbol: [ER\\_LOG\\_GENERAL\\_CANNOT\\_OPEN](#); SQLSTATE: [HY000](#)  
Message: either restart the query logging by using "SET GLOBAL GENERAL\_LOG=ON" or
  - Error number: [MY-010013](#); Symbol: [ER\\_LOG\\_CANNOT\\_WRITE](#); SQLSTATE: [HY000](#)  
Message: Failed to write to %s: %s
  - Error number: [MY-010014](#); Symbol: [ER\\_RPL\\_ZOMBIE\\_ENCOUNTERED](#); SQLSTATE: [HY000](#)  
Message: While initializing dump thread for replica with %s <%s>, found a zombie dump thread with the same %s. Source is killing the zombie dump thread(%u).
  - Error number: [MY-010015](#); Symbol: [ER\\_RPL\\_GTID\\_TABLE\\_CANNOT\\_OPEN](#); SQLSTATE: [HY000](#)  
Message: Gtid table is not ready to be used. Table '%s.%s' cannot be opened.
  - Error number: [MY-010016](#); Symbol: [ER\\_SYSTEM\\_SCHEMA\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)  
Message: System schema directory does not exist.
  - Error number: [MY-010017](#); Symbol: [ER\\_DD\\_INIT\\_UPGRADE\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Error in initializing dictionary, upgrade will do a cleanup and exit
  - Error number: [MY-010018](#); Symbol: [ER\\_VIEW\\_UNKNOWN\\_CHARSET\\_OR\\_COLLATION](#); SQLSTATE: [HY000](#)  
Message: View '%s'. '%s': unknown charset name and/or collation name (client: '%s'; connection: '%s').
  - Error number: [MY-010019](#); Symbol: [ER\\_DD\\_VIEW\\_CANT\\_ALLOC\\_CHARSET](#); SQLSTATE: [HY000](#)  
Message: Error in allocating memory for character set name for view %s.%s.
  - Error number: [MY-010020](#); Symbol: [ER\\_DD\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)
-

---

Message: Data Dictionary initialization failed.

- Error number: `MY-010021`; Symbol: `ER_DD_UPDATING_PLUGIN_MD_FAILED`; SQLSTATE: `HY000`

Message: Failed to update plugin metadata in dictionary tables.

- Error number: `MY-010022`; Symbol: `ER_DD_POPULATING_TABLES_FAILED`; SQLSTATE: `HY000`

Message: Failed to Populate DD tables.

- Error number: `MY-010023`; Symbol: `ER_DD_VIEW_CANT_CREATE`; SQLSTATE: `HY000`

Message: Error in Creating View %s.%s

- Error number: `MY-010024`; Symbol: `ER_DD_METADATA_NOT_FOUND`; SQLSTATE: `HY000`

Message: Unable to start server. Cannot find the meta data for data dictionary table '%s'.

- Error number: `MY-010025`; Symbol: `ER_DD_CACHE_NOT_EMPTY_AT_SHUTDOWN`; SQLSTATE: `HY000`

Message: Dictionary cache not empty at shutdown.

- Error number: `MY-010026`; Symbol: `ER_DD_OBJECT_REMAINS`; SQLSTATE: `HY000`

Message: Dictionary objects used but not released.

- Error number: `MY-010027`; Symbol: `ER_DD_OBJECT_REMAINS_IN_RELEASER`; SQLSTATE: `HY000`

Message: Dictionary objects left in default releaser.

- Error number: `MY-010028`; Symbol: `ER_DD_OBJECT_RELEASER_REMAINS`; SQLSTATE: `HY000`

Message: Dictionary object auto releaser not deleted

- Error number: `MY-010029`; Symbol: `ER_DD_CANT_GET_OBJECT_KEY`; SQLSTATE: `HY000`

Message: Error: Unable to create primary object key

- Error number: `MY-010030`; Symbol: `ER_DD_CANT_CREATE_OBJECT_KEY`; SQLSTATE: `HY000`

Message: Error: Unable to create object key

- Error number: `MY-010031`; Symbol: `ER_CANT_CREATE_HANDLE_MGR_THREAD`; SQLSTATE: `HY000`

Message: Can't create handle\_manager thread (errno= %d)

- Error number: `MY-010032`; Symbol: `ER_RPL_REPO_HAS_GAPS`; SQLSTATE: `HY000`

Message: It is not possible to change the type of the relay log's repository because there are workers' repositories with gaps. Please, fix the gaps first before doing such change.

- Error number: `MY-010033`; Symbol: `ER_INVALID_VALUE_FOR_ENFORCE_GTID_CONSISTENCY`; SQLSTATE: `HY000`

Message: option 'enforce-gtid-consistency': value '%s' was not recognized. Setting enforce-gtid-consistency to OFF.

- Error number: `MY-010034`; Symbol: `ER_CHANGED_ENFORCE_GTID_CONSISTENCY`; SQLSTATE: `HY000`



---

Message: Changed ENFORCE\_GTID\_CONSISTENCY from %s to %s.

- Error number: [MY-010035](#); Symbol: [ER\\_CHANGED\\_GTID\\_MODE](#); SQLSTATE: [HY000](#)

Message: Changed GTID\_MODE from %s to %s.

- Error number: [MY-010036](#); Symbol: [ER\\_DISABLED\\_STORAGE\\_ENGINE\\_AS\\_DEFAULT](#); SQLSTATE: [HY000](#)

Message: %s is set to a disabled storage engine %s.

- Error number: [MY-010037](#); Symbol: [ER\\_DEBUG\\_SYNC\\_HIT](#); SQLSTATE: [HY000](#)

Message: Debug sync points hit: %s

- Error number: [MY-010038](#); Symbol: [ER\\_DEBUG\\_SYNC\\_EXECUTED](#); SQLSTATE: [HY000](#)

Message: Debug sync points executed: %s

- Error number: [MY-010039](#); Symbol: [ER\\_DEBUG\\_SYNC\\_THREAD\\_MAX](#); SQLSTATE: [HY000](#)

Message: Debug sync points max active per thread: %s

- Error number: [MY-010040](#); Symbol: [ER\\_DEBUG\\_SYNC\\_OOM](#); SQLSTATE: [HY000](#)

Message: Debug Sync Facility disabled due to lack of memory.

- Error number: [MY-010041](#); Symbol: [ER\\_CANT\\_INIT\\_TC\\_LOG](#); SQLSTATE: [HY000](#)

Message: Can't init tc log

- Error number: [MY-010042](#); Symbol: [ER\\_EVENT\\_CANT\\_INIT\\_QUEUE](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: Can't initialize the execution queue

- Error number: [MY-010043](#); Symbol: [ER\\_EVENT\\_PURGING\\_QUEUE](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: Purging the queue. %u events

- Error number: [MY-010044](#); Symbol: [ER\\_EVENT\\_LAST\\_EXECUTION](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: Last execution of %s.%s. %s

- Error number: [MY-010045](#); Symbol: [ER\\_EVENT\\_MESSAGE\\_STACK](#); SQLSTATE: [HY000](#)

Message: %\*s

- Error number: [MY-010046](#); Symbol: [ER\\_EVENT\\_EXECUTION\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: [%s].[%s.%s] event execution failed.

- Error number: [MY-010047](#); Symbol: [ER\\_CANT\\_INIT\\_SCHEDULER\\_THREAD](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: Cannot initialize the scheduler thread

- Error number: [MY-010048](#); Symbol: [ER\\_SCHEDULER\\_STOPPED](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: Stopped

- Error number: [MY-010049](#); Symbol: [ER\\_CANT\\_CREATE\\_SCHEDULER\\_THREAD](#); SQLSTATE: [HY000](#)

Message: Event scheduler: Failed to start scheduler, Can not create thread for event scheduler (errno=%d)

- 
- Error number: [MY-010050](#); Symbol: [ER\\_SCHEDULER\\_WAITING](#); SQLSTATE: [HY000](#)  
Message: Event Scheduler: Waiting for the scheduler thread to reply
  - Error number: [MY-010051](#); Symbol: [ER\\_SCHEDULER\\_STARTED](#); SQLSTATE: [HY000](#)  
Message: Event Scheduler: scheduler thread started with id %u
  - Error number: [MY-010052](#); Symbol: [ER\\_SCHEDULER\\_STOPPING\\_FAILED\\_TO\\_GET\\_EVENT](#); SQLSTATE: [HY000](#)  
Message: Event Scheduler: Serious error during getting next event to execute. Stopping
  - Error number: [MY-010053](#); Symbol: [ER\\_SCHEDULER\\_STOPPING\\_FAILED\\_TO\\_CREATE\\_WORKER](#); SQLSTATE: [HY000](#)  
Message: Event\_scheduler::execute\_top: Can not create event worker thread (errno=%d). Stopping event scheduler
  - Error number: [MY-010054](#); Symbol: [ER\\_SCHEDULER\\_KILLING](#); SQLSTATE: [HY000](#)  
Message: Event Scheduler: Killing the scheduler thread, thread id %u
  - Error number: [MY-010055](#); Symbol: [ER\\_UNABLE\\_TO\\_RESOLVE\\_IP](#); SQLSTATE: [HY000](#)  
Message: IP address '%s' could not be resolved: %s
  - Error number: [MY-010056](#); Symbol: [ER\\_UNABLE\\_TO\\_RESOLVE\\_HOSTNAME](#); SQLSTATE: [HY000](#)  
Message: Host name '%s' could not be resolved: %s
  - Error number: [MY-010057](#); Symbol: [ER\\_HOSTNAME\\_RESEMBLES\\_IPV4](#); SQLSTATE: [HY000](#)  
Message: IP address '%s' has been resolved to the host name '%s', which resembles IPv4-address itself.
  - Error number: [MY-010058](#); Symbol: [ER\\_HOSTNAME\\_DOESNT\\_RESOLVE\\_TO](#); SQLSTATE: [HY000](#)  
Message: Hostname '%s' does not resolve to '%s'.
  - Error number: [MY-010059](#); Symbol: [ER\\_ADDRESSES\\_FOR\\_HOSTNAME\\_HEADER](#); SQLSTATE: [HY000](#)  
Message: Hostname '%s' has the following IP addresses:
  - Error number: [MY-010060](#); Symbol: [ER\\_ADDRESSES\\_FOR\\_HOSTNAME\\_LIST\\_ITEM](#); SQLSTATE: [HY000](#)  
Message: - %s
  - Error number: [MY-010061](#); Symbol: [ER\\_TRG\\_WITHOUT\\_DEFINER](#); SQLSTATE: [HY000](#)  
Message: Definer clause is missing in Trigger of Table %s. Rebuild Trigger to fix definer.
  - Error number: [MY-010062](#); Symbol: [ER\\_TRG\\_NO\\_CLIENT\\_CHARSET](#); SQLSTATE: [HY000](#)  
Message: Client character set is missing for trigger of table %s. Using default character set.
  - Error number: [MY-010063](#); Symbol: [ER\\_PARSING\\_VIEW](#); SQLSTATE: [HY000](#)  
Message: Error in parsing view %s.%s
  - Error number: [MY-010064](#); Symbol: [ER\\_COMPONENTS\\_INFRASTRUCTURE\\_BOOTSTRAP](#); SQLSTATE: [HY000](#)

---

Message: Failed to bootstrap components infrastructure.

- Error number: [MY-010065](#); Symbol: [ER\\_COMPONENTS\\_INFRASTRUCTURE\\_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: Failed to shutdown components infrastructure.

- Error number: [MY-010066](#); Symbol: [ER\\_COMPONENTS\\_PERSIST\\_LOADER\\_BOOTSTRAP](#); SQLSTATE: [HY000](#)

Message: Failed to bootstrap persistent components loader.

- Error number: [MY-010067](#); Symbol: [ER\\_DEPART\\_WITH\\_GRACE](#); SQLSTATE: [HY000](#)

Message: Giving %d client threads a chance to die gracefully

- Error number: [MY-010068](#); Symbol: [ER\\_CA\\_SELF\\_SIGNED](#); SQLSTATE: [HY000](#)

Message: CA certificate %s is self signed.

- Error number: [MY-010069](#); Symbol: [ER\\_SSL\\_LIBRARY\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Failed to set up SSL because of the following SSL library error: %s

- Error number: [MY-010070](#); Symbol: [ER\\_NO\\_THD\\_NO\\_UUID](#); SQLSTATE: [HY000](#)

Message: Failed to generate a server UUID because it is failed to allocate the THD.

- Error number: [MY-010071](#); Symbol: [ER\\_UUID\\_SALT](#); SQLSTATE: [HY000](#)

Message: Salting uuid generator variables, current\_pid: %lu, server\_start\_time: %lu, bytes\_sent: %llu,

- Error number: [MY-010072](#); Symbol: [ER\\_UUID\\_IS](#); SQLSTATE: [HY000](#)

Message: Generated uuid: '%s', server\_start\_time: %lu, bytes\_sent: %llu

- Error number: [MY-010073](#); Symbol: [ER\\_UUID\\_INVALID](#); SQLSTATE: [HY000](#)

Message: The server\_uuid stored in auto.cnf file is not a valid UUID.

- Error number: [MY-010074](#); Symbol: [ER\\_UUID\\_SCRUB](#); SQLSTATE: [HY000](#)

Message: Garbage characters found at the end of the server\_uuid value in auto.cnf file. It should be of length '%d' (UUID\_LENGTH). Clear it and restart the server.

- Error number: [MY-010075](#); Symbol: [ER\\_CREATING\\_NEW\\_UUID](#); SQLSTATE: [HY000](#)

Message: No existing UUID has been found, so we assume that this is the first time that this server has been started. Generating a new UUID: %s.

- Error number: [MY-010076](#); Symbol: [ER\\_CANT\\_CREATE\\_UUID](#); SQLSTATE: [HY000](#)

Message: Initialization of the server's UUID failed because it could not be read from the auto.cnf file. If this is a new server, the initialization failed because it was not possible to generate a new UUID.

- Error number: [MY-010077](#); Symbol: [ER\\_UNKNOWN\\_UNSUPPORTED\\_STORAGE\\_ENGINE](#); SQLSTATE: [HY000](#)

Message: Unknown/unsupported storage engine: %s

- Error number: [MY-010078](#); Symbol: [ER\\_SECURE\\_AUTH\\_VALUE\\_UNSUPPORTED](#); SQLSTATE: [HY000](#)

---

Message: Unsupported value 0 for secure-auth

- Error number: [MY-010079](#); Symbol: [ER\\_INVALID\\_INSTRUMENT](#); SQLSTATE: [HY000](#)

Message: Invalid instrument name or value for performance\_schema\_instrument '%s'.

- Error number: [MY-010080](#); Symbol: [ER\\_INNODEB\\_MANDATORY](#); SQLSTATE: [HY000](#)

Message: The use of InnoDB is mandatory since MySQL 5.7. The former options like '--innodb=0/1/OFF/ON' or '--skip-innodb' are ignored.

- Error number: [MY-010083](#); Symbol: [ER\\_VERBOSE\\_REQUIRES\\_HELP](#); SQLSTATE: [HY000](#)

Message: --verbose is for use with --help; did you mean --log-error-verbosity?

- Error number: [MY-010084](#); Symbol: [ER\\_POINTLESS\\_WITHOUT\\_SLOWLOG](#); SQLSTATE: [HY000](#)

Message: options --log-slow-admin-statements, --log-queries-not-using-indexes and --log-slow-replica-statements have no effect if --slow-query-log is not set

- Error number: [MY-010085](#); Symbol: [ER\\_WASTEFUL\\_NET\\_BUFFER\\_SIZE](#); SQLSTATE: [HY000](#)

Message: net\_buffer\_length (%lu) is set to be larger than max\_allowed\_packet (%lu). Please rectify.

- Error number: [MY-010086](#); Symbol: [ER\\_DEPRECATED\\_TIMESTAMP\\_IMPLICIT\\_DEFAULTS](#); SQLSTATE: [HY000](#)

Message: TIMESTAMP with implicit DEFAULT value is deprecated. Please use --explicit\_defaults\_for\_timestamp server option (see documentation for more details).

- Error number: [MY-010087](#); Symbol: [ER\\_FT\\_BOOL\\_SYNTAX\\_INVALID](#); SQLSTATE: [HY000](#)

Message: Invalid ft-boolean-syntax string: %s

- Error number: [MY-010088](#); Symbol: [ER\\_CREDENTIALLESS\\_AUTO\\_USER\\_BAD](#); SQLSTATE: [HY000](#)

Message: 'NO\_AUTO\_CREATE\_USER' sql mode was not set.

- Error number: [MY-010089](#); Symbol: [ER\\_CONNECTION\\_HANDLING\\_OOM](#); SQLSTATE: [HY000](#)

Message: Could not allocate memory for connection handling

- Error number: [MY-010090](#); Symbol: [ER\\_THREAD\\_HANDLING\\_OOM](#); SQLSTATE: [HY000](#)

Message: Could not allocate memory for thread handling

- Error number: [MY-010091](#); Symbol: [ER\\_CANT\\_CREATE\\_TEST\\_FILE](#); SQLSTATE: [HY000](#)

Message: Can't create test file %s

- Error number: [MY-010092](#); Symbol: [ER\\_CANT\\_CREATE\\_PID\\_FILE](#); SQLSTATE: [HY000](#)

Message: Can't start server: can't create PID file: %s

- Error number: [MY-010093](#); Symbol: [ER\\_CANT\\_REMOVE\\_PID\\_FILE](#); SQLSTATE: [HY000](#)

Message: Unable to delete pid file: %s

- Error number: [MY-010094](#); Symbol: [ER\\_CANT\\_CREATE\\_SHUTDOWN\\_THREAD](#); SQLSTATE: [HY000](#)

Message: Can't create thread to handle shutdown requests (errno= %d)

- Error number: [MY-010095](#); Symbol: [ER\\_SEC\\_FILE\\_PRIV\\_CANT\\_ACCESS\\_DIR](#); SQLSTATE: [HY000](#)

---

Message: Failed to access directory for --secure-file-priv. Please make sure that directory exists and is accessible by MySQL Server. Supplied value : %s

- Error number: [MY-010096](#); Symbol: [ER\\_SEC\\_FILE\\_PRIV\\_IGNORED](#); SQLSTATE: [HY000](#)

Message: Ignoring --secure-file-priv value as server is running with --initialize(-insecure).

- Error number: [MY-010097](#); Symbol: [ER\\_SEC\\_FILE\\_PRIV\\_EMPTY](#); SQLSTATE: [HY000](#)

Message: Insecure configuration for --secure-file-priv: Current value does not restrict location of generated files. Consider setting it to a valid, non-empty path.

- Error number: [MY-010098](#); Symbol: [ER\\_SEC\\_FILE\\_PRIV\\_NULL](#); SQLSTATE: [HY000](#)

Message: --secure-file-priv is set to NULL. Operations related to importing and exporting data are disabled

- Error number: [MY-010099](#); Symbol: [ER\\_SEC\\_FILE\\_PRIV\\_DIRECTORY\\_INSECURE](#); SQLSTATE: [HY000](#)

Message: Insecure configuration for --secure-file-priv: %s is accessible through --secure-file-priv. Consider choosing a different directory.

- Error number: [MY-010100](#); Symbol: [ER\\_SEC\\_FILE\\_PRIV\\_CANT\\_STAT](#); SQLSTATE: [HY000](#)

Message: Failed to get stat for directory pointed out by --secure-file-priv

- Error number: [MY-010101](#); Symbol: [ER\\_SEC\\_FILE\\_PRIV\\_DIRECTORY\\_PERMISSIONS](#); SQLSTATE: [HY000](#)

Message: Insecure configuration for --secure-file-priv: Location is accessible to all OS users. Consider choosing a different directory.

- Error number: [MY-010102](#); Symbol: [ER\\_SEC\\_FILE\\_PRIV\\_ARGUMENT\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)

Message: Value for --secure-file-priv is longer than maximum limit of %d

- Error number: [MY-010103](#); Symbol: [ER\\_CANT\\_CREATE\\_NAMED\\_PIPES\\_THREAD](#); SQLSTATE: [HY000](#)

Message: Can't create thread to handle named pipes (errno= %d)

- Error number: [MY-010104](#); Symbol: [ER\\_CANT\\_CREATE\\_TCPIP\\_THREAD](#); SQLSTATE: [HY000](#)

Message: Can't create thread to handle TCP/IP (errno= %d)

- Error number: [MY-010105](#); Symbol: [ER\\_CANT\\_CREATE\\_SHM\\_THREAD](#); SQLSTATE: [HY000](#)

Message: Can't create thread to handle shared memory (errno= %d)

- Error number: [MY-010106](#); Symbol: [ER\\_CANT\\_CREATE\\_INTERRUPT\\_THREAD](#); SQLSTATE: [HY000](#)

Message: Can't create interrupt-thread (error %d, errno: %d)

- Error number: [MY-010107](#); Symbol: [ER\\_WRITABLE\\_CONFIG\\_REMOVED](#); SQLSTATE: [HY000](#)

Message: World-writable config file '%s' has been removed.

- Error number: [MY-010108](#); Symbol: [ER\\_CORE\\_VALUES](#); SQLSTATE: [HY000](#)

Message: setrlimit could not change the size of core files to 'infinity'; We may not be able to generate a core file on signals

- 
- Error number: [MY-010109](#); Symbol: [ER\\_WRONG\\_DATETIME\\_SPEC](#); SQLSTATE: [HY000](#)  
Message: Wrong date/time format specifier: %s
  - Error number: [MY-010110](#); Symbol: [ER\\_RPL\\_BINLOG\\_FILTERS\\_OOM](#); SQLSTATE: [HY000](#)  
Message: Could not allocate replication and binlog filters: %s
  - Error number: [MY-010111](#); Symbol: [ER\\_KEYCACHE\\_OOM](#); SQLSTATE: [HY000](#)  
Message: Cannot allocate the keycache
  - Error number: [MY-010112](#); Symbol: [ER\\_CONFIRMING\\_THE\\_FUTURE](#); SQLSTATE: [HY000](#)  
Message: Current time has got past year 2038. Validating current time with %d iterations before initiating the normal server shutdown process.
  - Error number: [MY-010113](#); Symbol: [ER\\_BACK\\_IN\\_TIME](#); SQLSTATE: [HY000](#)  
Message: Iteration %d: Obtained valid current time from system
  - Error number: [MY-010114](#); Symbol: [ER\\_FUTURE\\_DATE](#); SQLSTATE: [HY000](#)  
Message: Iteration %d: Current time obtained from system is greater than 2038
  - Error number: [MY-010115](#); Symbol: [ER\\_UNSUPPORTED\\_DATE](#); SQLSTATE: [HY000](#)  
Message: This MySQL server doesn't support dates later then 2038
  - Error number: [MY-010116](#); Symbol: [ER\\_STARTING\\_AS](#); SQLSTATE: [HY000](#)  
Message: %s (mysqld %s) starting as process %lu
  - Error number: [MY-010117](#); Symbol: [ER\\_SHUTTING\\_DOWN\\_REPLICA\\_THREADS](#); SQLSTATE: [HY000](#)  
Message: Shutting down replica threads
  - Error number: [MY-010118](#); Symbol: [ER\\_DISCONNECTING\\_REMAINING\\_CLIENTS](#); SQLSTATE: [HY000](#)  
Message: Forcefully disconnecting %d remaining clients
  - Error number: [MY-010119](#); Symbol: [ER\\_ABORTING](#); SQLSTATE: [HY000](#)  
Message: Aborting
  - Error number: [MY-010120](#); Symbol: [ER\\_BINLOG\\_END](#); SQLSTATE: [HY000](#)  
Message: Binlog end
  - Error number: [MY-010121](#); Symbol: [ER\\_CALL\\_ME\\_LOCALHOST](#); SQLSTATE: [HY000](#)  
Message: gethostname failed, using '%s' as hostname
  - Error number: [MY-010122](#); Symbol: [ER\\_USER\\_REQUIRES\\_ROOT](#); SQLSTATE: [HY000](#)  
Message: One can only use the --user switch if running as root
  - Error number: [MY-010123](#); Symbol: [ER\\_REALLY\\_RUN\\_AS\\_ROOT](#); SQLSTATE: [HY000](#)  
Message: Fatal error: Please read "Security" section of the manual to find out how to run mysqld as root!

- 
- Error number: [MY-010124](#); Symbol: [ER\\_USER\\_WHAT\\_USER](#); SQLSTATE: [HY000](#)  
Message: Fatal error: Can't change to run as user '%s' ; Please check that the user exists!
  - Error number: [MY-010125](#); Symbol: [ER\\_TRANSPORTS\\_WHAT\\_TRANSPORTS](#); SQLSTATE: [HY000](#)  
Message: Server is started with --require-secure-transport=ON but no secure transports (SSL or Shared Memory) are configured.
  - Error number: [MY-010126](#); Symbol: [ER\\_FAIL\\_SETGID](#); SQLSTATE: [HY000](#)  
Message: setgid: %s
  - Error number: [MY-010127](#); Symbol: [ER\\_FAIL\\_SETUID](#); SQLSTATE: [HY000](#)  
Message: setuid: %s
  - Error number: [MY-010128](#); Symbol: [ER\\_FAIL\\_SETREGID](#); SQLSTATE: [HY000](#)  
Message: setregid: %s
  - Error number: [MY-010129](#); Symbol: [ER\\_FAIL\\_SETREUID](#); SQLSTATE: [HY000](#)  
Message: setreuid: %s
  - Error number: [MY-010130](#); Symbol: [ER\\_FAIL\\_CHROOT](#); SQLSTATE: [HY000](#)  
Message: chroot: %s
  - Error number: [MY-010131](#); Symbol: [ER\\_WIN\\_LISTEN\\_BUT\\_HOW](#); SQLSTATE: [HY000](#)  
Message: TCP/IP, --shared-memory, or --named-pipe should be configured on NT OS
  - Error number: [MY-010132](#); Symbol: [ER\\_NOT\\_RIGHT\\_NOW](#); SQLSTATE: [HY000](#)  
Message: CTRL-C ignored during startup
  - Error number: [MY-010133](#); Symbol: [ER\\_FIXING\\_CLIENT\\_CHARSET](#); SQLSTATE: [HY000](#)  
Message: '%s' can not be used as client character set. '%s' will be used as default client character set.
  - Error number: [MY-010134](#); Symbol: [ER\\_OOM](#); SQLSTATE: [HY000](#)  
Message: Out of memory
  - Error number: [MY-010135](#); Symbol: [ER\\_FAILED\\_TO\\_LOCK\\_MEM](#); SQLSTATE: [HY000](#)  
Message: Failed to lock memory. Errno: %d
  - Error number: [MY-010136](#); Symbol: [ER\\_MYINIT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: my\_init() failed.
  - Error number: [MY-010137](#); Symbol: [ER\\_BEG\\_INITFILE](#); SQLSTATE: [HY000](#)  
Message: Execution of init\_file '%s\' started.
  - Error number: [MY-010138](#); Symbol: [ER\\_END\\_INITFILE](#); SQLSTATE: [HY000](#)  
Message: Execution of init\_file '%s\' ended.
  - Error number: [MY-010139](#); Symbol: [ER\\_CHANGED\\_MAX\\_OPEN\\_FILES](#); SQLSTATE: [HY000](#)  
Message: Changed limits: max\_open\_files: %lu (requested %lu)

- 
- Error number: [MY-010140](#); Symbol: [ER\\_CANT\\_INCREASE\\_MAX\\_OPEN\\_FILES](#); SQLSTATE: [HY000](#)  
Message: Could not increase number of max\_open\_files to more than %lu (request: %lu)
  - Error number: [MY-010141](#); Symbol: [ER\\_CHANGED\\_MAX\\_CONNECTIONS](#); SQLSTATE: [HY000](#)  
Message: Changed limits: max\_connections: %lu (requested %lu)
  - Error number: [MY-010142](#); Symbol: [ER\\_CHANGED\\_TABLE\\_OPEN\\_CACHE](#); SQLSTATE: [HY000](#)  
Message: Changed limits: table\_open\_cache: %lu (requested %lu)
  - Error number: [MY-010143](#); Symbol: [ER\\_THE\\_USER\\_ABIDES](#); SQLSTATE: [HY000](#)  
Message: Ignoring user change to '%s' because the user was set to '%s' earlier on the command line
  - Error number: [MY-010144](#); Symbol: [ER\\_RPL\\_CANT\\_ADD\\_DO\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Could not add do table rule '%s'!
  - Error number: [MY-010145](#); Symbol: [ER\\_RPL\\_CANT\\_ADD\\_IGNORE\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Could not add ignore table rule '%s'!
  - Error number: [MY-010146](#); Symbol: [ER\\_TRACK\\_VARIABLES\\_BOGUS](#); SQLSTATE: [HY000](#)  
Message: The variable session\_track\_system\_variables either has duplicate values or invalid values.
  - Error number: [MY-010147](#); Symbol: [ER\\_EXCESS\\_ARGUMENTS](#); SQLSTATE: [HY000](#)  
Message: Too many arguments (first extra is '%s').
  - Error number: [MY-010148](#); Symbol: [ER\\_VERBOSE\\_HINT](#); SQLSTATE: [HY000](#)  
Message: Use --verbose --help to get a list of available options!
  - Error number: [MY-010149](#); Symbol: [ER\\_CANT\\_READ\\_ERRMSG](#); SQLSTATE: [HY000](#)  
Message: Unable to read errmsg.sys file
  - Error number: [MY-010150](#); Symbol: [ER\\_CANT\\_INIT\\_DBS](#); SQLSTATE: [HY000](#)  
Message: Can't init databases
  - Error number: [MY-010151](#); Symbol: [ER\\_LOG\\_OUTPUT\\_CONTRADICTORY](#); SQLSTATE: [HY000](#)  
Message: There were other values specified to log-output besides NONE. Disabling slow and general logs anyway.
  - Error number: [MY-010152](#); Symbol: [ER\\_NO\\_CSV\\_NO\\_LOG\\_TABLES](#); SQLSTATE: [HY000](#)  
Message: CSV engine is not present, falling back to the log files
  - Error number: [MY-010153](#); Symbol: [ER\\_RPL\\_REWRITEDB\\_MISSING\\_ARROW](#); SQLSTATE: [HY000](#)  
Message: Bad syntax in replicate-rewrite-db - missing '->'!
  - Error number: [MY-010154](#); Symbol: [ER\\_RPL\\_REWRITEDB\\_EMPTY\\_FROM](#); SQLSTATE: [HY000](#)  
Message: Bad syntax in replicate-rewrite-db - empty FROM db!
  - Error number: [MY-010155](#); Symbol: [ER\\_RPL\\_REWRITEDB\\_EMPTY\\_TO](#); SQLSTATE: [HY000](#)  
Message: Bad syntax in replicate-rewrite-db - empty TO db!



- 
- Error number: [MY-010156](#); Symbol: [ER\\_LOG\\_FILES\\_GIVEN\\_LOG\\_OUTPUT\\_IS\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Although a path was specified for the %, log tables are used. To enable logging to files use the --log-output=file option.
  - Error number: [MY-010157](#); Symbol: [ER\\_LOG\\_FILE\\_INVALID](#); SQLSTATE: [HY000](#)  
Message: Invalid value for %s: %s
  - Error number: [MY-010158](#); Symbol: [ER\\_LOWER\\_CASE\\_TABLE\\_NAMES\\_CS\\_DD\\_ON\\_CI\\_FS\\_UNSUPPORTED](#); SQLSTATE: [HY000](#)  
Message: The server option 'lower\_case\_table\_names' is configured to use case sensitive table names but the data directory is on a case-insensitive file system which is an unsupported combination. Please consider either using a case sensitive file system for your data directory or switching to a case-insensitive table name mode.
  - Error number: [MY-010159](#); Symbol: [ER\\_LOWER\\_CASE\\_TABLE\\_NAMES\\_USING\\_2](#); SQLSTATE: [HY000](#)  
Message: Setting lower\_case\_table\_names=2 because file system for %s is case insensitive
  - Error number: [MY-010160](#); Symbol: [ER\\_LOWER\\_CASE\\_TABLE\\_NAMES\\_USING\\_0](#); SQLSTATE: [HY000](#)  
Message: lower\_case\_table\_names was set to 2, even though your the file system '%s' is case sensitive. Now setting lower\_case\_table\_names to 0 to avoid future problems.
  - Error number: [MY-010161](#); Symbol: [ER\\_NEED\\_LOG\\_BIN](#); SQLSTATE: [HY000](#)  
Message: You need to use --log-bin to make %s work.
  - Error number: [MY-010162](#); Symbol: [ER\\_NEED\\_FILE\\_INSTEAD\\_OF\\_DIR](#); SQLSTATE: [HY000](#)  
Message: Path '%s' is a directory name, please specify a file name for %s option
  - Error number: [MY-010163](#); Symbol: [ER\\_LOG\\_BIN\\_BETTER\\_WITH\\_NAME](#); SQLSTATE: [HY000](#)  
Message: No argument was provided to --log-bin, and --log-bin-index was not used; so replication may break when this MySQL server acts as a source and has his hostname changed!! Please use '--log-bin=%s' to avoid this problem.
  - Error number: [MY-010164](#); Symbol: [ER\\_BINLOG\\_NEEDS\\_SERVERID](#); SQLSTATE: [HY000](#)  
Message: You have enabled the binary log, but you haven't provided the mandatory server-id. Please refer to the proper server start-up parameters documentation
  - Error number: [MY-010165](#); Symbol: [ER\\_RPL\\_CANT\\_MAKE\\_PATHS](#); SQLSTATE: [HY000](#)  
Message: Unable to create replication path names: out of memory or path names too long (path name exceeds %d or file name exceeds %d).
  - Error number: [MY-010166](#); Symbol: [ER\\_CANT\\_INITIALIZE\\_GTID](#); SQLSTATE: [HY000](#)  
Message: Failed to initialize GTID structures.
  - Error number: [MY-010167](#); Symbol: [ER\\_CANT\\_INITIALIZE\\_EARLY\\_PLUGINS](#); SQLSTATE: [HY000](#)  
Message: Failed to initialize early plugins.
  - Error number: [MY-010168](#); Symbol: [ER\\_CANT\\_INITIALIZE\\_BUILTIN\\_PLUGINS](#); SQLSTATE: [HY000](#)
-

---

Message: Failed to initialize builtin plugins.

- Error number: [MY-010169](#); Symbol: [ER\\_CANT\\_INITIALIZE\\_DYNAMIC\\_PLUGINS](#); SQLSTATE: [HY000](#)

Message: Failed to initialize dynamic plugins.

- Error number: [MY-010170](#); Symbol: [ER\\_PERFSHEMA\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Performance schema disabled (reason: init failed).

- Error number: [MY-010171](#); Symbol: [ER\\_STACKSIZE\\_UNEXPECTED](#); SQLSTATE: [HY000](#)

Message: Asked for %lu thread stack, but got %ld

- Error number: [MY-010173](#); Symbol: [ER\\_CANT\\_STAT\\_DATADIR](#); SQLSTATE: [HY000](#)

Message: Can't read data directory's stats (%d): %s. Assuming that it's not owned by the same user/group

- Error number: [MY-010174](#); Symbol: [ER\\_CANT\\_CHOWN\\_DATADIR](#); SQLSTATE: [HY000](#)

Message: Can't change data directory owner to %s

- Error number: [MY-010175](#); Symbol: [ER\\_CANT\\_SET\\_UP\\_PERSISTED\\_VALUES](#); SQLSTATE: [HY000](#)

Message: Setting persistent options failed.

- Error number: [MY-010176](#); Symbol: [ER\\_CANT\\_SAVE\\_GTIDS](#); SQLSTATE: [HY000](#)

Message: Failed to save the set of Global Transaction Identifiers of the last binary log into the `mysql.gtid_executed` table while the server was shutting down. The next server restart will make another attempt to save Global Transaction Identifiers into the table.

- Error number: [MY-010177](#); Symbol: [ER\\_AUTH\\_CANT\\_SET\\_DEFAULT\\_PLUGIN](#); SQLSTATE: [HY000](#)

Message: Can't start server: Invalid value for --default-authentication-plugin

- Error number: [MY-010178](#); Symbol: [ER\\_CANT\\_JOIN\\_SHUTDOWN\\_THREAD](#); SQLSTATE: [HY000](#)

Message: Could not join %sthread. error:%d

- Error number: [MY-010179](#); Symbol: [ER\\_CANT\\_HASH\\_DO\\_AND\\_IGNORE\\_RULES](#); SQLSTATE: [HY000](#)

Message: An error occurred while building `do_table` and `ignore_table` rules to hashes for global replication filter.

- Error number: [MY-010180](#); Symbol: [ER\\_CANT\\_OPEN\\_CA](#); SQLSTATE: [HY000](#)

Message: Error opening CA certificate file

- Error number: [MY-010181](#); Symbol: [ER\\_CANT\\_ACCESS\\_CAPATH](#); SQLSTATE: [HY000](#)

Message: Error accessing directory pointed by --ssl-capath

- Error number: [MY-010182](#); Symbol: [ER\\_SSL\\_TRYING\\_DATADIR\\_DEFAULTS](#); SQLSTATE: [HY000](#)

Message: Found %s, %s and %s in data directory. Trying to enable SSL support using them.

- Error number: [MY-010183](#); Symbol: [ER\\_AUTO\\_OPTIONS\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to create %s(file: '%s', errno %d)

- 
- Error number: [MY-010184](#); Symbol: [ER\\_CANT\\_INIT\\_TIMER](#); SQLSTATE: [HY000](#)  
Message: Failed to initialize timer component (errno %d).
  - Error number: [MY-010185](#); Symbol: [ER\\_SERVERID\\_TOO\\_LARGE](#); SQLSTATE: [HY000](#)  
Message: server-id configured is too large to represent with server-id-bits configured.
  - Error number: [MY-010186](#); Symbol: [ER\\_DEFAULT\\_SE\\_UNAVAILABLE](#); SQLSTATE: [HY000](#)  
Message: Default%s storage engine (%s) is not available
  - Error number: [MY-010187](#); Symbol: [ER\\_CANT\\_OPEN\\_ERROR\\_LOG](#); SQLSTATE: [HY000](#)  
Message: Could not open file '%s' for error logging%s%s
  - Error number: [MY-010188](#); Symbol: [ER\\_INVALID\\_ERROR\\_LOG\\_NAME](#); SQLSTATE: [HY000](#)  
Message: Invalid log file name after expanding symlinks: '%s'
  - Error number: [MY-010189](#); Symbol: [ER\\_RPL\\_INFINITY\\_DENIED](#); SQLSTATE: [HY000](#)  
Message: using --replicate-same-server-id in conjunction with --log-replica-updates is impossible, it would lead to infinite loops in this server.
  - Error number: [MY-010190](#); Symbol: [ER\\_RPL\\_INFINITY\\_IGNORED](#); SQLSTATE: [HY000](#)  
Message: using --replicate-same-server-id in conjunction with --log-replica-updates would lead to infinite loops in this server. However this will be ignored as the --log-bin option is not defined or your server is running with global transaction identifiers enabled.
  - Error number: [MY-010192](#); Symbol: [ER\\_TABLE\\_CHECK\\_INTACT](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-010193](#); Symbol: [ER\\_DD\\_TABLESPACE\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)  
Message: Unable to start server. The data dictionary tablespace '%s' does not exist.
  - Error number: [MY-010194](#); Symbol: [ER\\_DD\\_TRG\\_CONNECTION\\_COLLATION\\_MISSING](#); SQLSTATE: [HY000](#)  
Message: Connection collation is missing for trigger of table %s. Using default connection collation.
  - Error number: [MY-010195](#); Symbol: [ER\\_DD\\_TRG\\_DB\\_COLLATION\\_MISSING](#); SQLSTATE: [HY000](#)  
Message: Database collation is missing for trigger of table %s. Using Default character set.
  - Error number: [MY-010196](#); Symbol: [ER\\_DD\\_TRG\\_DEFINER\\_OOM](#); SQLSTATE: [HY000](#)  
Message: Error in Memory allocation for Definer %s for Trigger.
  - Error number: [MY-010197](#); Symbol: [ER\\_DD\\_TRG\\_FILE\\_UNREADABLE](#); SQLSTATE: [HY000](#)  
Message: Error in reading %s.TRG file.
  - Error number: [MY-010198](#); Symbol: [ER\\_TRG\\_CANT\\_PARSE](#); SQLSTATE: [HY000](#)  
Message: Error in parsing Triggers from %s.TRG file.
  - Error number: [MY-010199](#); Symbol: [ER\\_DD\\_TRG\\_CANT\\_ADD](#); SQLSTATE: [HY000](#)  
Message: Error in creating DD entry for Trigger %s.%s
-

- 
- Error number: [MY-010200](#); Symbol: [ER\\_DD\\_CANT\\_RESOLVE\\_VIEW](#); SQLSTATE: [HY000](#)  
Message: Resolving dependency for the view '%s.%s' failed. View is no more valid to use
  - Error number: [MY-010201](#); Symbol: [ER\\_DD\\_VIEW\\_WITHOUT\\_DEFINER](#); SQLSTATE: [HY000](#)  
Message: %s.%s has no definer (as per an old view format). Current user is used as definer. Please recreate the view.
  - Error number: [MY-010202](#); Symbol: [ER\\_PLUGIN\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Plugin '%s' init function returned error.
  - Error number: [MY-010203](#); Symbol: [ER\\_RPL\\_TRX\\_DELEGATES\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Initialization of transaction delegates failed. Please report a bug.
  - Error number: [MY-010204](#); Symbol: [ER\\_RPL\\_BINLOG\\_STORAGE\\_DELEGATES\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Initialization binlog storage delegates failed. Please report a bug.
  - Error number: [MY-010205](#); Symbol: [ER\\_RPL\\_BINLOG\\_TRANSMIT\\_DELEGATES\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Initialization of binlog transmit delegates failed. Please report a bug.
  - Error number: [MY-010206](#); Symbol: [ER\\_RPL\\_BINLOG\\_RELAY\\_DELEGATES\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Initialization binlog relay IO delegates failed. Please report a bug.
  - Error number: [MY-010207](#); Symbol: [ER\\_RPL\\_PLUGIN\\_FUNCTION\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Run function '...' in plugin '%s' failed
  - Error number: [MY-010208](#); Symbol: [ER\\_SQL\\_HA\\_READ\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: mysql\_ha\_read: Got error %d when reading table '%s'
  - Error number: [MY-010209](#); Symbol: [ER\\_SR\\_BOGUS\\_VALUE](#); SQLSTATE: [HY000](#)  
Message: Stored routine '%s'. '%s': invalid value in column %s.
  - Error number: [MY-010210](#); Symbol: [ER\\_SR\\_INVALID\\_CONTEXT](#); SQLSTATE: [HY000](#)  
Message: Invalid creation context '%s.%s'.
  - Error number: [MY-010211](#); Symbol: [ER\\_READING\\_TABLE\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Got error %d when reading table '%s'
  - Error number: [MY-010212](#); Symbol: [ER\\_DES\\_FILE\\_WRONG\\_KEY](#); SQLSTATE: [HY000](#)  
Message: load\_des\_file: Found wrong key\_number: %c
  - Error number: [MY-010214](#); Symbol: [ER\\_JSON\\_PARSE\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Persisted config file is corrupt. Please ensure mysqld-auto.cnf file is valid JSON.
  - Error number: [MY-010215](#); Symbol: [ER\\_CONFIG\\_OPTION\\_WITHOUT\\_GROUP](#); SQLSTATE: [HY000](#)  
Message: Found option without preceding group in config file

- 
- Error number: [MY-010216](#); Symbol: [ER\\_VALGRIND\\_DO\\_QUICK\\_LEAK\\_CHECK](#); SQLSTATE: [HY000](#)  
Message: VALGRIND\_DO\_QUICK\_LEAK\_CHECK
  - Error number: [MY-010217](#); Symbol: [ER\\_VALGRIND\\_COUNT\\_LEAKS](#); SQLSTATE: [HY000](#)  
Message: VALGRIND\_COUNT\_LEAKS reports %lu leaked bytes for query '%.\*s'
  - Error number: [MY-010218](#); Symbol: [ER\\_LOAD\\_DATA\\_INFILE\\_FAILED\\_IN\\_UNEXPECTED\\_WAY](#); SQLSTATE: [HY000](#)  
Message: LOAD DATA INFILE in the replica SQL Thread can only read from --replica-load-tmpdir. Please, report a bug.
  - Error number: [MY-010219](#); Symbol: [ER\\_UNKNOWN\\_ERROR\\_NUMBER](#); SQLSTATE: [HY000](#)  
Message: Got unknown error: %d
  - Error number: [MY-010220](#); Symbol: [ER\\_UDF\\_CANT\\_ALLOC\\_FOR\\_STRUCTURES](#); SQLSTATE: [HY000](#)  
Message: Can't allocate memory for udf structures
  - Error number: [MY-010221](#); Symbol: [ER\\_UDF\\_CANT\\_ALLOC\\_FOR\\_FUNCTION](#); SQLSTATE: [HY000](#)  
Message: Can't alloc memory for udf function: '%s'
  - Error number: [MY-010222](#); Symbol: [ER\\_UDF\\_INVALID\\_ROW\\_IN\\_FUNCTION\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Invalid row in mysql.func table for function '%s'
  - Error number: [MY-010223](#); Symbol: [ER\\_UDF\\_CANT\\_OPEN\\_FUNCTION\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Could not open the mysql.func table. Please perform the MySQL upgrade procedure.
  - Error number: [MY-010224](#); Symbol: [ER\\_XA\\_RECOVER\\_FOUND\\_TRX\\_IN\\_SE](#); SQLSTATE: [HY000](#)  
Message: Found %d prepared transaction(s) in %s
  - Error number: [MY-010225](#); Symbol: [ER\\_XA\\_RECOVER\\_FOUND\\_XA\\_TRX](#); SQLSTATE: [HY000](#)  
Message: Found %d prepared XA transactions
  - Error number: [MY-010229](#); Symbol: [ER\\_XA\\_STARTING\\_RECOVERY](#); SQLSTATE: [HY000](#)  
Message: Starting XA crash recovery...
  - Error number: [MY-010230](#); Symbol: [ER\\_XA\\_NO\\_MULTI\\_2PC\\_HEURISTIC\\_RECOVER](#); SQLSTATE: [HY000](#)  
Message: --tc-heuristic-recover rollback strategy is not safe on systems with more than one 2-phase-commit-capable storage engine. Aborting crash recovery.
  - Error number: [MY-010231](#); Symbol: [ER\\_XA\\_RECOVER\\_EXPLANATION](#); SQLSTATE: [HY000](#)  
Message: Found %d prepared transactions! It means that mysqld was not shut down properly last time and critical recovery information (last binlog or %s file) was manually deleted after a crash. You have to start mysqld with --tc-heuristic-recover switch to commit or rollback pending transactions.
  - Error number: [MY-010232](#); Symbol: [ER\\_XA\\_RECOVERY\\_DONE](#); SQLSTATE: [HY000](#)  
Message: XA crash recovery finished.
-

- 
- Error number: [MY-010233](#); Symbol: [ER\\_TRX\\_GTID\\_COLLECT\\_REJECT](#); SQLSTATE: [HY000](#)  
Message: Failed to collect GTID to send in the response packet!
  - Error number: [MY-010234](#); Symbol: [ER\\_SQL\\_AUTHOR\\_DEFAULT\\_ROLES\\_FAIL](#); SQLSTATE: [HY000](#)  
Message: MYSQL.DEFAULT\_ROLES couldn't be updated for authorization identifier %s
  - Error number: [MY-010235](#); Symbol: [ER\\_SQL\\_USER\\_TABLE\\_CREATE\\_WARNING](#); SQLSTATE: [HY000](#)  
Message: Following users were specified in CREATE USER IF NOT EXISTS but they already exist. Corresponding entry in binary log used default authentication plugin '%s' to rewrite authentication information (if any) for them: %s
  - Error number: [MY-010236](#); Symbol: [ER\\_SQL\\_USER\\_TABLE\\_ALTER\\_WARNING](#); SQLSTATE: [HY000](#)  
Message: Following users were specified in ALTER USER IF EXISTS but they do not exist. Corresponding entry in binary log used default authentication plugin '%s' to rewrite authentication information (if any) for them: %s
  - Error number: [MY-010237](#); Symbol: [ER\\_ROW\\_IN\\_WRONG\\_PARTITION\\_PLEASE\\_REPAIR](#); SQLSTATE: [HY000](#)  
Message: Table '%s' corrupted: row in wrong partition: %s -- Please REPAIR the table!
  - Error number: [MY-010238](#); Symbol: [ER\\_MYISAM\\_CRASHED\\_ERROR\\_IN\\_THREAD](#); SQLSTATE: [HY000](#)  
Message: Got an error from thread\_id=%u, %s:%d
  - Error number: [MY-010239](#); Symbol: [ER\\_MYISAM\\_CRASHED\\_ERROR\\_IN](#); SQLSTATE: [HY000](#)  
Message: Got an error from unknown thread, %s:%d
  - Error number: [MY-010240](#); Symbol: [ER\\_TOO\\_MANY\\_STORAGE\\_ENGINES](#); SQLSTATE: [HY000](#)  
Message: Too many storage engines!
  - Error number: [MY-010241](#); Symbol: [ER\\_SE\\_TYPECODE\\_CONFLICT](#); SQLSTATE: [HY000](#)  
Message: Storage engine '%s' has conflicting typecode. Assigning value %d.
  - Error number: [MY-010242](#); Symbol: [ER\\_TRX\\_WRITE\\_SET\\_OOM](#); SQLSTATE: [HY000](#)  
Message: Out of memory on transaction write set extraction
  - Error number: [MY-010243](#); Symbol: [ER\\_HANDLER\\_TON\\_OOM](#); SQLSTATE: [HY000](#)  
Message: Unable to allocate memory for plugin '%s' handlerton.
  - Error number: [MY-010244](#); Symbol: [ER\\_CONN\\_SHM\\_LISTENER](#); SQLSTATE: [HY000](#)  
Message: Shared memory setting up listener
  - Error number: [MY-010245](#); Symbol: [ER\\_CONN\\_SHM\\_CANT\\_CREATE\\_SERVICE](#); SQLSTATE: [HY000](#)  
Message: Can't create shared memory service: %s. : %s
  - Error number: [MY-010246](#); Symbol: [ER\\_CONN\\_SHM\\_CANT\\_CREATE\\_CONNECTION](#); SQLSTATE: [HY000](#)  
Message: Can't create shared memory connection: %s. : %s

- 
- Error number: [MY-010247](#); Symbol: [ER\\_CONN\\_PIP\\_CANT\\_CREATE\\_EVENT](#); SQLSTATE: [HY000](#)  
Message: Can't create event, last error=%u
  - Error number: [MY-010248](#); Symbol: [ER\\_CONN\\_PIP\\_CANT\\_CREATE\\_PIPE](#); SQLSTATE: [HY000](#)  
Message: Can't create new named pipe!: %s
  - Error number: [MY-010249](#); Symbol: [ER\\_CONN\\_PER\\_THREAD\\_NO\\_THREAD](#); SQLSTATE: [HY000](#)  
Message: Can't create thread to handle new connection(errno= %d)
  - Error number: [MY-010250](#); Symbol: [ER\\_CONN\\_TCP\\_NO\\_SOCKET](#); SQLSTATE: [HY000](#)  
Message: Failed to create a socket for %s '%s': errno: %d.
  - Error number: [MY-010251](#); Symbol: [ER\\_CONN\\_TCP\\_CREATED](#); SQLSTATE: [HY000](#)  
Message: Server socket created on IP: '%s'.
  - Error number: [MY-010252](#); Symbol: [ER\\_CONN\\_TCP\\_ADDRESS](#); SQLSTATE: [HY000](#)  
Message: Server hostname (bind-address): '%s'; port: %d
  - Error number: [MY-010253](#); Symbol: [ER\\_CONN\\_TCP\\_IPV6\\_AVAILABLE](#); SQLSTATE: [HY000](#)  
Message: IPv6 is available.
  - Error number: [MY-010254](#); Symbol: [ER\\_CONN\\_TCP\\_IPV6\\_UNAVAILABLE](#); SQLSTATE: [HY000](#)  
Message: IPv6 is not available.
  - Error number: [MY-010255](#); Symbol: [ER\\_CONN\\_TCP\\_ERROR\\_WITH\\_STRERROR](#); SQLSTATE: [HY000](#)  
Message: Can't create IP socket: %s
  - Error number: [MY-010256](#); Symbol: [ER\\_CONN\\_TCP\\_CANT\\_RESOLVE\\_HOSTNAME](#); SQLSTATE: [HY000](#)  
Message: Can't start server: cannot resolve hostname!
  - Error number: [MY-010257](#); Symbol: [ER\\_CONN\\_TCP\\_IS\\_THERE\\_ANOTHER\\_USING\\_PORT](#); SQLSTATE: [HY000](#)  
Message: Do you already have another mysqld server running on port: %d ?
  - Error number: [MY-010258](#); Symbol: [ER\\_CONN\\_UNIX\\_IS\\_THERE\\_ANOTHER\\_USING\\_SOCKET](#); SQLSTATE: [HY000](#)  
Message: Do you already have another mysqld server running on socket: %s ?
  - Error number: [MY-010259](#); Symbol: [ER\\_CONN\\_UNIX\\_PID\\_CLAIMED\\_SOCKET\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Another process with pid %d is using unix socket file.
  - Error number: [MY-010260](#); Symbol: [ER\\_CONN\\_TCP\\_CANT\\_RESET\\_V6ONLY](#); SQLSTATE: [HY000](#)  
Message: Failed to reset IPV6\_V6ONLY flag (error: %d). The server will listen to IPv6 addresses only.
  - Error number: [MY-010261](#); Symbol: [ER\\_CONN\\_TCP\\_BIND\\_RETRY](#); SQLSTATE: [HY000](#)  
Message: Retrying bind on TCP/IP port %u
-

- 
- Error number: [MY-010262](#); Symbol: [ER\\_CONN\\_TCP\\_BIND\\_FAIL](#); SQLSTATE: [HY000](#)  
Message: Can't start server: Bind on TCP/IP port: %s
  - Error number: [MY-010263](#); Symbol: [ER\\_CONN\\_TCP\\_IP\\_NOT\\_LOGGED](#); SQLSTATE: [HY000](#)  
Message: Fails to print out IP-address.
  - Error number: [MY-010264](#); Symbol: [ER\\_CONN\\_TCP\\_RESOLVE\\_INFO](#); SQLSTATE: [HY000](#)  
Message: - '%s' resolves to '%s';
  - Error number: [MY-010265](#); Symbol: [ER\\_CONN\\_TCP\\_START\\_FAIL](#); SQLSTATE: [HY000](#)  
Message: Can't start server: listen() on TCP/IP port: %s
  - Error number: [MY-010266](#); Symbol: [ER\\_CONN\\_TCP\\_LISTEN\\_FAIL](#); SQLSTATE: [HY000](#)  
Message: listen() on TCP/IP failed with error %d
  - Error number: [MY-010267](#); Symbol: [ER\\_CONN\\_UNIX\\_PATH\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)  
Message: The socket file path is too long (> %u): %s
  - Error number: [MY-010268](#); Symbol: [ER\\_CONN\\_UNIX\\_LOCK\\_FILE\\_FAIL](#); SQLSTATE: [HY000](#)  
Message: Unable to setup unix socket lock file.
  - Error number: [MY-010269](#); Symbol: [ER\\_CONN\\_UNIX\\_NO\\_FD](#); SQLSTATE: [HY000](#)  
Message: Can't start server: UNIX Socket : %s
  - Error number: [MY-010270](#); Symbol: [ER\\_CONN\\_UNIX\\_NO\\_BIND\\_NO\\_START](#); SQLSTATE: [HY000](#)  
Message: Can't start server : Bind on unix socket: %s
  - Error number: [MY-010271](#); Symbol: [ER\\_CONN\\_UNIX\\_LISTEN\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: listen() on Unix socket failed with error %d
  - Error number: [MY-010272](#); Symbol: [ER\\_CONN\\_UNIX\\_LOCK\\_FILE\\_GIVING\\_UP](#); SQLSTATE: [HY000](#)  
Message: Unable to create unix socket lock file %s after retries.
  - Error number: [MY-010273](#); Symbol: [ER\\_CONN\\_UNIX\\_LOCK\\_FILE\\_CANT\\_CREATE](#); SQLSTATE: [HY000](#)  
Message: Could not create unix socket lock file %s.
  - Error number: [MY-010274](#); Symbol: [ER\\_CONN\\_UNIX\\_LOCK\\_FILE\\_CANT\\_OPEN](#); SQLSTATE: [HY000](#)  
Message: Could not open unix socket lock file %s.
  - Error number: [MY-010275](#); Symbol: [ER\\_CONN\\_UNIX\\_LOCK\\_FILE\\_CANT\\_READ](#); SQLSTATE: [HY000](#)  
Message: Could not read unix socket lock file %s.
  - Error number: [MY-010276](#); Symbol: [ER\\_CONN\\_UNIX\\_LOCK\\_FILE\\_EMPTY](#); SQLSTATE: [HY000](#)  
Message: Unix socket lock file is empty %s.



- 
- Error number: [MY-010277](#); Symbol: [ER\\_CONN\\_UNIX\\_LOCK\\_FILE\\_PIDLESS](#); SQLSTATE: [HY000](#)  
Message: Invalid pid in unix socket lock file %s.
  - Error number: [MY-010278](#); Symbol: [ER\\_CONN\\_UNIX\\_LOCK\\_FILE\\_CANT\\_WRITE](#); SQLSTATE: [HY000](#)  
Message: Could not write unix socket lock file %s errno %d.
  - Error number: [MY-010279](#); Symbol: [ER\\_CONN\\_UNIX\\_LOCK\\_FILE\\_CANT\\_DELETE](#); SQLSTATE: [HY000](#)  
Message: Could not remove unix socket lock file %s errno %d.
  - Error number: [MY-010280](#); Symbol: [ER\\_CONN\\_UNIX\\_LOCK\\_FILE\\_CANT\\_SYNC](#); SQLSTATE: [HY000](#)  
Message: Could not sync unix socket lock file %s errno %d.
  - Error number: [MY-010281](#); Symbol: [ER\\_CONN\\_UNIX\\_LOCK\\_FILE\\_CANT\\_CLOSE](#); SQLSTATE: [HY000](#)  
Message: Could not close unix socket lock file %s errno %d.
  - Error number: [MY-010282](#); Symbol: [ER\\_CONN\\_SOCKET\\_SELECT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: mysqld: Got error %d from select
  - Error number: [MY-010283](#); Symbol: [ER\\_CONN\\_SOCKET\\_ACCEPT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Error in accept: %s
  - Error number: [MY-010284](#); Symbol: [ER\\_AUTH\\_RSA\\_CANT\\_FIND](#); SQLSTATE: [HY000](#)  
Message: RSA %s key file not found: %s. Some authentication plugins will not work.
  - Error number: [MY-010285](#); Symbol: [ER\\_AUTH\\_RSA\\_CANT\\_PARSE](#); SQLSTATE: [HY000](#)  
Message: Failure to parse RSA %s key (file exists): %s: %s
  - Error number: [MY-010286](#); Symbol: [ER\\_AUTH\\_RSA\\_CANT\\_READ](#); SQLSTATE: [HY000](#)  
Message: Failure to read key file: %s
  - Error number: [MY-010287](#); Symbol: [ER\\_AUTH\\_RSA\\_FILES\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)  
Message: RSA key files not found. Some authentication plugins will not work.
  - Error number: [MY-010288](#); Symbol: [ER\\_CONN\\_ATTR\\_TRUNCATED](#); SQLSTATE: [HY000](#)  
Message: Connection attributes of length %lu were truncated (%d bytes lost) for connection %llu, user %s@%s (as %s), auth: %s
  - Error number: [MY-010289](#); Symbol: [ER\\_X509\\_CIPHERS\\_MISMATCH](#); SQLSTATE: [HY000](#)  
Message: X.509 ciphers mismatch: should be '%s' but is '%s'
  - Error number: [MY-010290](#); Symbol: [ER\\_X509\\_ISSUER\\_MISMATCH](#); SQLSTATE: [HY000](#)  
Message: X.509 issuer mismatch: should be '%s' but is '%s'
  - Error number: [MY-010291](#); Symbol: [ER\\_X509\\_SUBJECT\\_MISMATCH](#); SQLSTATE: [HY000](#)  
Message: X.509 subject mismatch: should be '%s' but is '%s'

- 
- Error number: [MY-010292](#); Symbol: [ER\\_AUTH\\_CANT\\_ACTIVATE\\_ROLE](#); SQLSTATE: [HY000](#)  
Message: Failed to activate default role %s for %s
  - Error number: [MY-010293](#); Symbol: [ER\\_X509\\_NEEDS\\_RSA\\_PRIVKEY](#); SQLSTATE: [HY000](#)  
Message: Could not generate RSA private key required for X.509 certificate.
  - Error number: [MY-010294](#); Symbol: [ER\\_X509\\_CANT\\_WRITE\\_KEY](#); SQLSTATE: [HY000](#)  
Message: Could not write key file: %s
  - Error number: [MY-010295](#); Symbol: [ER\\_X509\\_CANT\\_CHMOD\\_KEY](#); SQLSTATE: [HY000](#)  
Message: Could not set file permission for %s
  - Error number: [MY-010296](#); Symbol: [ER\\_X509\\_CANT\\_READ\\_CA\\_KEY](#); SQLSTATE: [HY000](#)  
Message: Could not read CA key file: %s
  - Error number: [MY-010297](#); Symbol: [ER\\_X509\\_CANT\\_READ\\_CA\\_CERT](#); SQLSTATE: [HY000](#)  
Message: Could not read CA certificate file: %s
  - Error number: [MY-010298](#); Symbol: [ER\\_X509\\_CANT\\_CREATE\\_CERT](#); SQLSTATE: [HY000](#)  
Message: Could not generate X.509 certificate.
  - Error number: [MY-010299](#); Symbol: [ER\\_X509\\_CANT\\_WRITE\\_CERT](#); SQLSTATE: [HY000](#)  
Message: Could not write certificate file: %s
  - Error number: [MY-010300](#); Symbol: [ER\\_AUTH\\_CANT\\_CREATE\\_RSA\\_PAIR](#); SQLSTATE: [HY000](#)  
Message: Could not generate RSA Private/Public key pair
  - Error number: [MY-010301](#); Symbol: [ER\\_AUTH\\_CANT\\_WRITE\\_PRIVKEY](#); SQLSTATE: [HY000](#)  
Message: Could not write private key file: %s
  - Error number: [MY-010302](#); Symbol: [ER\\_AUTH\\_CANT\\_WRITE\\_PUBKEY](#); SQLSTATE: [HY000](#)  
Message: Could not write public key file: %s
  - Error number: [MY-010303](#); Symbol: [ER\\_AUTH\\_SSL\\_CONF\\_PREVENTS\\_CERT\\_GENERATION](#); SQLSTATE: [HY000](#)  
Message: Skipping generation of SSL certificates as options related to SSL are specified.
  - Error number: [MY-010304](#); Symbol: [ER\\_AUTH\\_USING\\_EXISTING\\_CERTS](#); SQLSTATE: [HY000](#)  
Message: Skipping generation of SSL certificates as certificate files are present in data directory.
  - Error number: [MY-010305](#); Symbol: [ER\\_AUTH\\_CERTS\\_SAVED\\_TO\\_DATADIR](#); SQLSTATE: [HY000](#)  
Message: Auto generated SSL certificates are placed in data directory.
  - Error number: [MY-010306](#); Symbol: [ER\\_AUTH\\_CERT\\_GENERATION\\_DISABLED](#); SQLSTATE: [HY000](#)  
Message: Skipping generation of SSL certificates as --auto\_generate\_certs is set to OFF.
  - Error number: [MY-010307](#); Symbol: [ER\\_AUTH\\_RSA\\_CONF\\_PREVENTS\\_KEY\\_GENERATION](#); SQLSTATE: [HY000](#)

---

Message: Skipping generation of RSA key pair through %s as options related to RSA keys are specified.

- Error number: [MY-010308](#); Symbol: [ER\\_AUTH\\_KEY\\_GENERATION\\_SKIPPED\\_PAIR\\_PRESENT](#); SQLSTATE: [HY000](#)

Message: Skipping generation of RSA key pair through %s as key files are present in data directory.

- Error number: [MY-010309](#); Symbol: [ER\\_AUTH\\_KEYS\\_SAVED\\_TO\\_DATADIR](#); SQLSTATE: [HY000](#)

Message: Auto generated RSA key files through %s are placed in data directory.

- Error number: [MY-010310](#); Symbol: [ER\\_AUTH\\_KEY\\_GENERATION\\_DISABLED](#); SQLSTATE: [HY000](#)

Message: Skipping generation of RSA key pair as %s is set to OFF.

- Error number: [MY-010311](#); Symbol: [ER\\_AUTHCACHE\\_PROXIES\\_PRIV\\_SKIPPED\\_NEEDS\\_RESOLVE](#); SQLSTATE: [HY000](#)

Message: 'proxies\_priv' entry '%s@%s %s@%s' ignored in --skip-name-resolve mode.

- Error number: [MY-010312](#); Symbol: [ER\\_AUTHCACHE\\_PLUGIN\\_MISSING](#); SQLSTATE: [HY000](#)

Message: The plugin '%.\*s' used to authenticate user '%s'@'%.\*s' is not loaded. Nobody can currently login using this account.

- Error number: [MY-010313](#); Symbol: [ER\\_AUTHCACHE\\_PLUGIN\\_CONFIG](#); SQLSTATE: [HY000](#)

Message: The plugin '%s' is used to authenticate user '%s'@'%.\*s', %s configured. Nobody can currently login using this account.

- Error number: [MY-010315](#); Symbol: [ER\\_AUTHCACHE\\_USER\\_SKIPPED\\_NEEDS\\_RESOLVE](#); SQLSTATE: [HY000](#)

Message: 'user' entry '%s@%s' ignored in --skip-name-resolve mode.

- Error number: [MY-010316](#); Symbol: [ER\\_AUTHCACHE\\_USER\\_TABLE\\_DODGY](#); SQLSTATE: [HY000](#)

Message: Fatal error: Could not read the column 'authentication\_string' from table 'mysql.user'. Please perform the MySQL upgrade procedure.

- Error number: [MY-010317](#); Symbol: [ER\\_AUTHCACHE\\_USER\\_IGNORED\\_DEPRECATED\\_PASSWORD](#); SQLSTATE: [HY000](#)

Message: User entry '%s'@'%s' has a deprecated pre-4.1 password. The user will be ignored and no one can login with this user anymore.

- Error number: [MY-010318](#); Symbol: [ER\\_AUTHCACHE\\_USER\\_IGNORED\\_NEEDS\\_PLUGIN](#); SQLSTATE: [HY000](#)

Message: User entry '%s'@'%s' has an empty plugin value. The user will be ignored and no one can login with this user anymore.

- Error number: [MY-010319](#); Symbol: [ER\\_AUTHCACHE\\_USER\\_IGNORED\\_INVALID\\_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Found invalid password for user: '%s@%s'; Ignoring user

- Error number: [MY-010320](#); Symbol: [ER\\_AUTHCACHE\\_EXPIRED\\_PASSWORD\\_UNSUPPORTED](#); SQLSTATE: [HY000](#)

Message: 'user' entry '%s@%s' has the password ignore flag raised, but its authentication plugin doesn't support password expiration. The user id will be ignored.

- Error number: [MY-010321](#); Symbol: [ER\\_NO\\_SUPER\\_WITHOUT\\_USER\\_PLUGIN](#); SQLSTATE: [HY000](#)

Message: Some of the user accounts with SUPER privileges were disabled because of empty mysql.user.plugin value. If you are upgrading from MySQL 5.6 to MySQL 5.7 it means that substitution for the empty plugin column was not possible. Probably because of pre 4.1 password hash. If your account is disabled you will need to perform the MySQL upgrade procedure. For complete instructions on how to upgrade MySQL to a new version please see the 'Upgrading MySQL' section from the MySQL manual.
- Error number: [MY-010322](#); Symbol: [ER\\_AUTHCACHE\\_DB\\_IGNORED\\_EMPTY\\_NAME](#); SQLSTATE: [HY000](#)

Message: Found an entry in the 'db' table with empty database name; Skipped
- Error number: [MY-010323](#); Symbol: [ER\\_AUTHCACHE\\_DB\\_SKIPPED\\_NEEDS\\_RESOLVE](#); SQLSTATE: [HY000](#)

Message: 'db' entry '%s %s@%s' ignored in --skip-name-resolve mode.
- Error number: [MY-010324](#); Symbol: [ER\\_AUTHCACHE\\_DB\\_ENTRY\\_LOWERCASED\\_REVOKE\\_WILL\\_FAIL](#); SQLSTATE: [HY000](#)

Message: 'db' entry '%s %s@%s' had database in mixed case that has been forced to lowercase because lower\_case\_table\_names is set. It will not be possible to remove this privilege using REVOKE.
- Error number: [MY-010325](#); Symbol: [ER\\_AUTHCACHE\\_TABLE\\_PROXIES\\_PRIV\\_MISSING](#); SQLSTATE: [HY000](#)

Message: The system table mysql.proxies\_priv is missing. Please perform the MySQL upgrade procedure.
- Error number: [MY-010326](#); Symbol: [ER\\_AUTHCACHE\\_CANT\\_OPEN\\_AND\\_LOCK\\_PRIVILEGE\\_TABLES](#); SQLSTATE: [HY000](#)

Message: Fatal error: Can't open and lock privilege tables: %s
- Error number: [MY-010327](#); Symbol: [ER\\_AUTHCACHE\\_CANT\\_INIT\\_GRANT\\_SUBSYSTEM](#); SQLSTATE: [HY000](#)

Message: Fatal: can't initialize grant subsystem - '%s'
- Error number: [MY-010328](#); Symbol: [ER\\_AUTHCACHE\\_PROCS\\_PRIV\\_SKIPPED\\_NEEDS\\_RESOLVE](#); SQLSTATE: [HY000](#)

Message: 'procs\_priv' entry '%s %s@%s' ignored in --skip-name-resolve mode.
- Error number: [MY-010329](#); Symbol: [ER\\_AUTHCACHE\\_PROCS\\_PRIV\\_ENTRY\\_IGNORED\\_BAD\\_ROUTINE\\_TYPE](#); SQLSTATE: [HY000](#)

Message: 'procs\_priv' entry '%s' ignored, bad routine type
- Error number: [MY-010330](#); Symbol: [ER\\_AUTHCACHE\\_TABLES\\_PRIV\\_SKIPPED\\_NEEDS\\_RESOLVE](#); SQLSTATE: [HY000](#)

Message: 'tables\_priv' entry '%s %s@%s' ignored in --skip-name-resolve mode.
- Error number: [MY-010331](#); Symbol: [ER\\_USER\\_NOT\\_IN\\_EXTRA\\_USERS\\_BINLOG\\_POSSIBLY\\_INCOMPLETE](#); SQLSTATE: [HY000](#)

Message: Failed to add %s in extra\_users. Binary log entry may miss some of the users.
- Error number: [MY-010332](#); Symbol: [ER\\_DD\\_SCHEMA\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)

---

Message: Unable to start server. The data dictionary schema '%s' does not exist.

- Error number: [MY-010333](#); Symbol: [ER\\_DD\\_TABLE\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)

Message: Unable to start server. The data dictionary table '%s' does not exist.

- Error number: [MY-010334](#); Symbol: [ER\\_DD\\_SE\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to initialize DD Storage Engine

- Error number: [MY-010335](#); Symbol: [ER\\_DD\\_ABORTING\\_PARTIAL\\_UPGRADE](#); SQLSTATE: [HY000](#)

Message: Found partially upgraded DD. Aborting upgrade and deleting all DD tables. Start the upgrade process again.

- Error number: [MY-010336](#); Symbol: [ER\\_DD\\_FRM\\_EXISTS\\_FOR\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Found .frm file with same name as one of the Dictionary Tables.

- Error number: [MY-010337](#); Symbol: [ER\\_DD\\_CREATED\\_FOR\\_UPGRADE](#); SQLSTATE: [HY000](#)

Message: Created Data Dictionary for upgrade

- Error number: [MY-010338](#); Symbol: [ER\\_ERRMSG\\_CANT\\_FIND\\_FILE](#); SQLSTATE: [HY000](#)

Message: Can't find error-message file '%s'. Check error-message file location and 'lc-messages-dir' configuration directive.

- Error number: [MY-010339](#); Symbol: [ER\\_ERRMSG\\_LOADING\\_55\\_STYLE](#); SQLSTATE: [HY000](#)

Message: Using pre 5.5 semantics to load error messages from %s. If this is not intended, refer to the documentation for valid usage of --lc-messages-dir and --language parameters.

- Error number: [MY-010340](#); Symbol: [ER\\_ERRMSG\\_MISSING\\_IN\\_FILE](#); SQLSTATE: [HY000](#)

Message: Error message file '%s' had only %d error messages, but it should contain at least %d error messages. Check that the above file is the right version for this program!

- Error number: [MY-010341](#); Symbol: [ER\\_ERRMSG\\_OOM](#); SQLSTATE: [HY000](#)

Message: Not enough memory for messagefile '%s'

- Error number: [MY-010342](#); Symbol: [ER\\_ERRMSG\\_CANT\\_READ](#); SQLSTATE: [HY000](#)

Message: Can't read from messagefile '%s'

- Error number: [MY-010343](#); Symbol: [ER\\_TABLE\\_INCOMPATIBLE\\_DECIMAL\\_FIELD](#); SQLSTATE: [HY000](#)

Message: Found incompatible DECIMAL field '%s' in %s; Please do "ALTER TABLE ` %s ` FORCE" to fix it!

- Error number: [MY-010344](#); Symbol: [ER\\_TABLE\\_INCOMPATIBLE\\_YEAR\\_FIELD](#); SQLSTATE: [HY000](#)

Message: Found incompatible YEAR(x) field '%s' in %s; Please do "ALTER TABLE ` %s ` FORCE" to fix it!

- Error number: [MY-010345](#); Symbol: [ER\\_INVALID\\_CHARSET\\_AND\\_DEFAULT\\_IS\\_MB](#); SQLSTATE: [HY000](#)

Message: '%s' had no or invalid character set, and default character set is multi-byte, so character column sizes may have changed

- 
- Error number: `MY-010346`; Symbol: `ER_TABLE_WRONG_KEY_DEFINITION`; SQLSTATE: `HY000`  
Message: Found wrong key definition in %s; Please do "ALTER TABLE ` %s ` FORCE " to fix it!
  - Error number: `MY-010347`; Symbol: `ER_CANT_OPEN_FRM_FILE`; SQLSTATE: `HY000`  
Message: Unable to open file %s
  - Error number: `MY-010348`; Symbol: `ER_CANT_READ_FRM_FILE`; SQLSTATE: `HY000`  
Message: Error in reading file %s
  - Error number: `MY-010349`; Symbol: `ER_TABLE_CREATED_WITH_DIFFERENT_VERSION`; SQLSTATE: `HY000`  
Message: Table '%s' was created with a different version of MySQL and cannot be read
  - Error number: `MY-010350`; Symbol: `ER_VIEW_UNPARSABLE`; SQLSTATE: `HY000`  
Message: Unable to read view %s
  - Error number: `MY-010351`; Symbol: `ER_FILE_TYPE_UNKNOWN`; SQLSTATE: `HY000`  
Message: File %s has unknown type in its header.
  - Error number: `MY-010352`; Symbol: `ER_INVALID_INFO_IN_FRM`; SQLSTATE: `HY000`  
Message: Incorrect information in file %s
  - Error number: `MY-010353`; Symbol: `ER_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLES`; SQLSTATE: `HY000`  
Message: Can't open and lock privilege tables: %s
  - Error number: `MY-010354`; Symbol: `ER_AUDIT_PLUGIN_DOES_NOT_SUPPORT_AUDIT_AUTH_EVENTS`; SQLSTATE: `HY000`  
Message: Plugin '%s' cannot subscribe to `MYSQL_AUDIT_AUTHORIZATION` events. Currently not supported.
  - Error number: `MY-010355`; Symbol: `ER_AUDIT_PLUGIN_HAS_INVALID_DATA`; SQLSTATE: `HY000`  
Message: Plugin '%s' has invalid data.
  - Error number: `MY-010356`; Symbol: `ER_TZ_OOM_INITIALIZING_TIME_ZONES`; SQLSTATE: `HY000`  
Message: Fatal error: OOM while initializing time zones
  - Error number: `MY-010357`; Symbol: `ER_TZ_CANT_OPEN_AND_LOCK_TIME_ZONE_TABLE`; SQLSTATE: `HY000`  
Message: Can't open and lock time zone table: %s trying to live without them
  - Error number: `MY-010358`; Symbol: `ER_TZ_OOM_LOADING_LEAP_SECOND_TABLE`; SQLSTATE: `HY000`  
Message: Fatal error: Out of memory while loading `mysql.time_zone_leap_second` table
  - Error number: `MY-010359`; Symbol: `ER_TZ_TOO_MANY_LEAPS_IN_LEAP_SECOND_TABLE`; SQLSTATE: `HY000`  
Message: Fatal error: While loading `mysql.time_zone_leap_second` table: too much leaps

- 
- Error number: [MY-010360](#); Symbol: [ER\\_TZ\\_ERROR\\_LOADING\\_LEAP\\_SECOND\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Fatal error: Error while loading mysql.time\_zone\_leap\_second table
  - Error number: [MY-010361](#); Symbol: [ER\\_TZ\\_UNKNOWN\\_OR\\_ILLEGAL\\_DEFAULT\\_TIME\\_ZONE](#); SQLSTATE: [HY000](#)  
Message: Fatal error: Illegal or unknown default time zone '%s'
  - Error number: [MY-010362](#); Symbol: [ER\\_TZ\\_CANT\\_FIND\\_DESCRIPTION\\_FOR\\_TIME\\_ZONE](#); SQLSTATE: [HY000](#)  
Message: Can't find description of time zone '%.\*s'
  - Error number: [MY-010363](#); Symbol: [ER\\_TZ\\_CANT\\_FIND\\_DESCRIPTION\\_FOR\\_TIME\\_ZONE\\_ID](#); SQLSTATE: [HY000](#)  
Message: Can't find description of time zone '%u'
  - Error number: [MY-010364](#); Symbol: [ER\\_TZ\\_TRANSITION\\_TYPE\\_TABLE\\_TYPE\\_TOO\\_LARGE](#); SQLSTATE: [HY000](#)  
Message: Error while loading time zone description from mysql.time\_zone\_transition\_type table: too big transition type id
  - Error number: [MY-010365](#); Symbol: [ER\\_TZ\\_TRANSITION\\_TYPE\\_TABLE\\_ABBREVIATIONS\\_EXCEED\\_SPACE](#); SQLSTATE: [HY000](#)  
Message: Error while loading time zone description from mysql.time\_zone\_transition\_type table: not enough room for abbreviations
  - Error number: [MY-010366](#); Symbol: [ER\\_TZ\\_TRANSITION\\_TYPE\\_TABLE\\_LOAD\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Error while loading time zone description from mysql.time\_zone\_transition\_type table
  - Error number: [MY-010367](#); Symbol: [ER\\_TZ\\_TRANSITION\\_TABLE\\_TOO\\_MANY\\_TRANSITIONS](#); SQLSTATE: [HY000](#)  
Message: Error while loading time zone description from mysql.time\_zone\_transition table: too much transitions
  - Error number: [MY-010368](#); Symbol: [ER\\_TZ\\_TRANSITION\\_TABLE\\_BAD\\_TRANSITION\\_TYPE](#); SQLSTATE: [HY000](#)  
Message: Error while loading time zone description from mysql.time\_zone\_transition table: bad transition type id
  - Error number: [MY-010369](#); Symbol: [ER\\_TZ\\_TRANSITION\\_TABLE\\_LOAD\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Error while loading time zone description from mysql.time\_zone\_transition table
  - Error number: [MY-010370](#); Symbol: [ER\\_TZ\\_NO\\_TRANSITION\\_TYPES\\_IN\\_TIME\\_ZONE](#); SQLSTATE: [HY000](#)  
Message: loading time zone without transition types
  - Error number: [MY-010371](#); Symbol: [ER\\_TZ\\_OOM\\_LOADING\\_TIME\\_ZONE\\_DESCRIPTION](#); SQLSTATE: [HY000](#)  
Message: Out of memory while loading time zone description
-

- 
- Error number: `MY-010372`; Symbol: `ER_TZ_CANT_BUILD_MKTIME_MAP`; SQLSTATE: `HY000`  
Message: Unable to build mktime map for time zone
  - Error number: `MY-010373`; Symbol: `ER_TZ_OOM_WHILE_LOADING_TIME_ZONE`; SQLSTATE: `HY000`  
Message: Out of memory while loading time zone
  - Error number: `MY-010374`; Symbol: `ER_TZ_OOM_WHILE_SETTING_TIME_ZONE`; SQLSTATE: `HY000`  
Message: Fatal error: Out of memory while setting new time zone
  - Error number: `MY-010375`; Symbol: `ER_REPLICA_SQL_THREAD_STOPPED_UNTIL_CONDITION_BAD`; SQLSTATE: `HY000`  
Message: Replica SQL thread is stopped because UNTIL condition is bad(%s:%llu).
  - Error number: `MY-010376`; Symbol: `ER_REPLICA_SQL_THREAD_STOPPED_UNTIL_POSITION_REACHED`; SQLSTATE: `HY000`  
Message: Replica SQL thread stopped because it reached its UNTIL position %llu
  - Error number: `MY-010377`; Symbol: `ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTIDS_ALREADY_APPLIED`; SQLSTATE: `HY000`  
Message: Replica SQL thread stopped because UNTIL SQL\_BEFORE\_GTIDS %s is already applied
  - Error number: `MY-010378`; Symbol: `ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTIDS_REACHED`; SQLSTATE: `HY000`  
Message: Replica SQL thread stopped because it reached UNTIL SQL\_BEFORE\_GTIDS %s
  - Error number: `MY-010379`; Symbol: `ER_REPLICA_SQL_THREAD_STOPPED_AFTER_GTIDS_REACHED`; SQLSTATE: `HY000`  
Message: Replica SQL thread stopped because it reached UNTIL SQL\_AFTER\_GTIDS %s
  - Error number: `MY-010380`; Symbol: `ER_REPLICA_SQL_THREAD_STOPPED_GAP_TRX_PROCESSED`; SQLSTATE: `HY000`  
Message: Replica SQL thread stopped according to UNTIL SQL\_AFTER\_MTS\_GAPS as it has processed all gap transactions left from the previous replica session.
  - Error number: `MY-010381`; Symbol: `ER_GROUP_REPLICATION_PLUGIN_NOT_INSTALLED`; SQLSTATE: `HY000`  
Message: Group Replication plugin is not installed.
  - Error number: `MY-010382`; Symbol: `ER_GTID_ALREADY_ADDED_BY_USER`; SQLSTATE: `HY000`  
Message: The transaction owned GTID is already in the %s table, which is caused by an explicit modifying from user client.
  - Error number: `MY-010383`; Symbol: `ER_FAILED_TO_DELETE_FROM_GTID_EXECUTED_TABLE`; SQLSTATE: `HY000`  
Message: Failed to delete the row: '%s' from the gtid\_executed table.
  - Error number: `MY-010384`; Symbol: `ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE`; SQLSTATE: `HY000`  
Message: Failed to compress the gtid\_executed table.



- 
- Error number: `MY-010385`; Symbol: `ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE_OOM`; SQLSTATE: `HY000`  
 Message: Failed to compress the `gtid_executed` table, because it is failed to allocate the THD.
  - Error number: `MY-010386`; Symbol: `ER_FAILED_TO_INIT_THREAD_ATTR_FOR_GTID_TABLE_COMPRESSION`; SQLSTATE: `HY000`  
 Message: Failed to initialize thread attribute when creating compression thread.
  - Error number: `MY-010387`; Symbol: `ER_FAILED_TO_CREATE_GTID_TABLE_COMPRESSION_THREAD`; SQLSTATE: `HY000`  
 Message: Can not create thread to compress `gtid_executed` table (errno= %d)
  - Error number: `MY-010388`; Symbol: `ER_FAILED_TO_JOIN_GTID_TABLE_COMPRESSION_THREAD`; SQLSTATE: `HY000`  
 Message: Could not join `gtid_executed` table compression thread. error:%d
  - Error number: `MY-010389`; Symbol: `ER_NPIPE_FAILED_TO_INIT_SECURITY_DESCRIPTOR`; SQLSTATE: `HY000`  
 Message: Can't start server : Initialize security descriptor: %s
  - Error number: `MY-010390`; Symbol: `ER_NPIPE_FAILED_TO_SET_SECURITY_DESCRIPTOR`; SQLSTATE: `HY000`  
 Message: Can't start server : Set security descriptor: %s
  - Error number: `MY-010391`; Symbol: `ER_NPIPE_PIPE_ALREADY_IN_USE`; SQLSTATE: `HY000`  
 Message: Can't start server : Named Pipe "%s" already in use.
  - Error number: `MY-010405`; Symbol: `ER_RPL_CANT_OPEN_INFO_TABLE`; SQLSTATE: `HY000`  
 Message: Info table is not ready to be used. Table '%s.%s' cannot be opened.
  - Error number: `MY-010406`; Symbol: `ER_RPL_CANT_SCAN_INFO_TABLE`; SQLSTATE: `HY000`  
 Message: Info table is not ready to be used. Table '%s.%s' cannot be scanned.
  - Error number: `MY-010407`; Symbol: `ER_RPL_CORRUPTED_INFO_TABLE`; SQLSTATE: `HY000`  
 Message: Corrupted table %s.%s. Check out table definition.
  - Error number: `MY-010408`; Symbol: `ER_RPL_CORRUPTED_KEYS_IN_INFO_TABLE`; SQLSTATE: `HY000`  
 Message: Info table has a problem with its key field(s). Table '%s.%s' expected field #%u to be '%s' but found '%s' instead.
  - Error number: `MY-010409`; Symbol: `ER_RPL_WORKER_ID_IS`; SQLSTATE: `HY000`  
 Message: Choosing worker id %lu, the following is going to be %lu
  - Error number: `MY-010410`; Symbol: `ER_RPL_INCONSISTENT_TIMESTAMPS_IN_TRX`; SQLSTATE: `HY000`  
 Message: Transaction is tagged with inconsistent logical timestamps: sequence\_number (%lld) <= last\_committed (%lld)
  - Error number: `MY-010411`; Symbol: `ER_RPL_INCONSISTENT_SEQUENCE_NO_IN_TRX`; SQLSTATE: `HY000`
-

---

Message: Transaction's sequence number is inconsistent with that of a preceding one:  
sequence\_number (%lld) <= previous sequence\_number (%lld)

- Error number: MY-010413; Symbol: ER\_RPL\_CHANNELS\_REQUIRE\_NON\_ZERO\_SERVER\_ID; SQLSTATE: HY000

Message: For the creation of replication channels the server id must be different from 0

- Error number: MY-010415; Symbol: ER\_RPL\_ERROR\_CREATING\_CONNECTION\_METADATA; SQLSTATE: HY000

Message: Error creating connection metadata: %s.

- Error number: MY-010418; Symbol: ER\_RPL\_ERROR\_CREATING\_APPLIER\_METADATA; SQLSTATE: HY000

Message: Error creating applier metadata: %s.

- Error number: MY-010420; Symbol: ER\_RPL\_FAILED\_TO\_DELETE\_FROM\_REPLICA\_WORKERS\_INFO\_REPOSITORY; SQLSTATE: HY000

Message: Could not delete from Replica Workers info repository.

- Error number: MY-010421; Symbol: ER\_RPL\_FAILED\_TO\_RESET\_STATE\_IN\_REPLICA\_INFO\_REPOSITORY; SQLSTATE: HY000

Message: Could not store the reset Replica Worker state into the replica info repository.

- Error number: MY-010423; Symbol: ER\_RPL\_REPLICA\_GENERIC\_MESSAGE; SQLSTATE: HY000

Message: Replica: %s

- Error number: MY-010424; Symbol: ER\_RPL\_REPLICA\_COULD\_NOT\_CREATE\_CHANNEL\_LIST; SQLSTATE: HY000

Message: Replica: Could not create channel list

- Error number: MY-010425; Symbol: ER\_RPL\_MULTISOURCE\_REQUIRES\_TABLE\_TYPE\_REPOSITORIES; SQLSTATE: HY000

Message: Replica: This replica was a multisourced replica previously which is supported only by both TABLE based connection metadata and applier metadata repositories. Found one or both of the info repos to be type FILE. Set both repos to type TABLE.

- Error number: MY-010426; Symbol: ER\_RPL\_REPLICA\_FAILED\_TO\_INIT\_A\_CONNECTION\_METADATA\_STRUCTURE; SQLSTATE: HY000

Message: Replica: Failed to initialize the connection metadata structure for channel '%s'; its record may still be present in the applier metadata repository, consider deleting it.

- Error number: MY-010427; Symbol: ER\_RPL\_REPLICA\_FAILED\_TO\_INIT\_CONNECTION\_METADATA\_STRUCTURE; SQLSTATE: HY000

Message: Failed to initialize the connection metadata structure%s

- Error number: MY-010428; Symbol: ER\_RPL\_REPLICA\_FAILED\_TO\_CREATE\_CHANNEL\_FROM\_CONNECTION\_METADATA; SQLSTATE: HY000

---

Message: Replica: Failed to create a channel from connection metadata repository.

- Error number: [MY-010429](#); Symbol: [ER\\_RPL\\_FAILED\\_TO\\_CREATE\\_NEW\\_INFO\\_FILE](#); SQLSTATE: [HY000](#)

Message: Failed to create a new info file (file '%s', errno %d)

- Error number: [MY-010430](#); Symbol: [ER\\_RPL\\_FAILED\\_TO\\_CREATE\\_CACHE\\_FOR\\_INFO\\_FILE](#); SQLSTATE: [HY000](#)

Message: Failed to create a cache on info file (file '%s')

- Error number: [MY-010431](#); Symbol: [ER\\_RPL\\_FAILED\\_TO\\_OPEN\\_INFO\\_FILE](#); SQLSTATE: [HY000](#)

Message: Failed to open the existing info file (file '%s', errno %d)

- Error number: [MY-010432](#); Symbol: [ER\\_RPL\\_GTID\\_MEMORY\\_FINALLY\\_AVAILABLE](#); SQLSTATE: [HY000](#)

Message: Server overcomes the temporary 'out of memory' in '%d' tries while allocating a new chunk of intervals for storing GTIDs.

- Error number: [MY-010433](#); Symbol: [ER\\_SERVER\\_COST\\_UNKNOWN\\_COST\\_CONSTANT](#); SQLSTATE: [HY000](#)

Message: Unknown cost constant "%s" in mysql.server\_cost table

- Error number: [MY-010434](#); Symbol: [ER\\_SERVER\\_COST\\_INVALID\\_COST\\_CONSTANT](#); SQLSTATE: [HY000](#)

Message: Invalid value for cost constant "%s" in mysql.server\_cost table: %.1f

- Error number: [MY-010435](#); Symbol: [ER\\_ENGINE\\_COST\\_UNKNOWN\\_COST\\_CONSTANT](#); SQLSTATE: [HY000](#)

Message: Unknown cost constant "%s" in mysql.engine\_cost table

- Error number: [MY-010436](#); Symbol: [ER\\_ENGINE\\_COST\\_UNKNOWN\\_STORAGE\\_ENGINE](#); SQLSTATE: [HY000](#)

Message: Unknown storage engine "%s" in mysql.engine\_cost table

- Error number: [MY-010437](#); Symbol: [ER\\_ENGINE\\_COST\\_INVALID\\_DEVICE\\_TYPE\\_FOR\\_SE](#); SQLSTATE: [HY000](#)

Message: Invalid device type %d for "%s" storage engine for cost constant "%s" in mysql.engine\_cost table

- Error number: [MY-010438](#); Symbol: [ER\\_ENGINE\\_COST\\_INVALID\\_CONST\\_CONSTANT\\_FOR\\_SE\\_AND\\_DEVICE](#); SQLSTATE: [HY000](#)

Message: Invalid value for cost constant "%s" for "%s" storage engine and device type %d in mysql.engine\_cost table: %.1f

- Error number: [MY-010439](#); Symbol: [ER\\_SERVER\\_COST\\_FAILED\\_TO\\_READ](#); SQLSTATE: [HY000](#)

Message: Error while reading from mysql.server\_cost table.

- Error number: [MY-010440](#); Symbol: [ER\\_ENGINE\\_COST\\_FAILED\\_TO\\_READ](#); SQLSTATE: [HY000](#)

Message: Error while reading from mysql.engine\_cost table.

- 
- Error number: `MY-010441`; Symbol: `ER_FAILED_TO_OPEN_COST_CONSTANT_TABLES`; SQLSTATE: `HY000`  
  
Message: Failed to open optimizer cost constant tables
  - Error number: `MY-010442`; Symbol: `ER_RPL_UNSUPPORTED_UNIGNORABLE_EVENT_IN_STREAM`; SQLSTATE: `HY000`  
  
Message: Unsupported non-ignorable event fed into the event stream.
  - Error number: `MY-010443`; Symbol: `ER_RPL_GTID_LOG_EVENT_IN_STREAM`; SQLSTATE: `HY000`  
  
Message: `GTID_LOG_EVENT`, `GTID_TAGGED_LOG_EVENT` or `ANONYMOUS_GTID_LOG_EVENT` is not expected in an event stream %s.
  - Error number: `MY-010444`; Symbol: `ER_RPL_UNEXPECTED_BEGIN_IN_STREAM`; SQLSTATE: `HY000`  
  
Message: `QUERY(BEGIN)` is not expected in an event stream in the middle of a %s.
  - Error number: `MY-010445`; Symbol: `ER_RPL_UNEXPECTED_COMMIT_ROLLBACK_OR_XID_LOG_EVENT_IN_STREAM`; SQLSTATE: `HY000`  
  
Message: `QUERY(COMMIT or ROLLBACK)` or `XID_LOG_EVENT` is not expected in an event stream %s.
  - Error number: `MY-010446`; Symbol: `ER_RPL_UNEXPECTED_XA_ROLLBACK_IN_STREAM`; SQLSTATE: `HY000`  
  
Message: `QUERY(XA ROLLBACK)` is not expected in an event stream %s.
  - Error number: `MY-010447`; Symbol: `ER_EVENT_EXECUTION_FAILED_CANT_AUTHENTICATE_USER`; SQLSTATE: `HY000`  
  
Message: Event Scheduler: [%s].[%s.%s] execution failed, failed to authenticate the user.
  - Error number: `MY-010448`; Symbol: `ER_EVENT_EXECUTION_FAILED_USER_LOST_EVENT_PRIVILEGE`; SQLSTATE: `HY000`  
  
Message: Event Scheduler: [%s].[%s.%s] execution failed, user no longer has `EVENT` privilege.
  - Error number: `MY-010449`; Symbol: `ER_EVENT_ERROR_DURING_COMPILATION`; SQLSTATE: `HY000`  
  
Message: Event Scheduler: %serror during compilation of %s.%s
  - Error number: `MY-010450`; Symbol: `ER_EVENT_DROPPING`; SQLSTATE: `HY000`  
  
Message: Event Scheduler: Dropping %s.%s
  - Error number: `MY-010452`; Symbol: `ER_RPL_INCOMPATIBLE_DECIMAL_IN_RBR`; SQLSTATE: `HY000`  
  
Message: In RBR mode, Replica received incompatible `DECIMAL` field (old-style decimal field) from Source while creating conversion table. Please consider changing datatype on Source to new style decimal by executing `ALTER` command for column Name: %s.%s.%s.
  - Error number: `MY-010453`; Symbol: `ER_INIT_ROOT_WITHOUT_PASSWORD`; SQLSTATE: `HY000`  
  
Message: `root@localhost` is created with an empty password ! Please consider switching off the `--initialize-insecure` option.

- 
- Error number: `MY-010454`; Symbol: `ER_INIT_GENERATING_TEMP_PASSWORD_FOR_ROOT`; SQLSTATE: `HY000`  
Message: A temporary password is generated for root@localhost: %s
  - Error number: `MY-010455`; Symbol: `ER_INIT_CANT_OPEN_BOOTSTRAP_FILE`; SQLSTATE: `HY000`  
Message: Failed to open the bootstrap file %s
  - Error number: `MY-010456`; Symbol: `ER_INIT_BOOTSTRAP_COMPLETE`; SQLSTATE: `HY000`  
Message: Bootstrapping complete
  - Error number: `MY-010457`; Symbol: `ER_INIT_DATADIR_NOT_EMPTY_WONT_INITIALIZE`; SQLSTATE: `HY000`  
Message: --initialize specified but the data directory has files in it. Aborting.
  - Error number: `MY-010458`; Symbol: `ER_INIT_DATADIR_EXISTS_WONT_INITIALIZE`; SQLSTATE: `HY000`  
Message: --initialize specified on an existing data directory.
  - Error number: `MY-010459`; Symbol: `ER_INIT_DATADIR_EXISTS_AND_PATH_TOO_LONG_WONT_INITIALIZE`; SQLSTATE: `HY000`  
Message: --initialize specified but the data directory exists and the path is too long. Aborting.
  - Error number: `MY-010460`; Symbol: `ER_INIT_DATADIR_EXISTS_AND_NOT_WRITABLE_WONT_INITIALIZE`; SQLSTATE: `HY000`  
Message: --initialize specified but the data directory exists and is not writable. Aborting.
  - Error number: `MY-010461`; Symbol: `ER_INIT_CREATING_DD`; SQLSTATE: `HY000`  
Message: Creating the data directory %s
  - Error number: `MY-010462`; Symbol: `ER_RPL_BINLOG_STARTING_DUMP`; SQLSTATE: `HY000`  
Message: Start binlog\_dump to source\_thread\_id(%u) replica\_server(%u), pos(%s, %llu)
  - Error number: `MY-010463`; Symbol: `ER_RPL_BINLOG_SOURCE_SENDS_HEARTBEAT`; SQLSTATE: `HY000`  
Message: source sends heartbeat message
  - Error number: `MY-010464`; Symbol: `ER_RPL_BINLOG_SKIPPING_REMAINING_HEARTBEAT_INFO`; SQLSTATE: `HY000`  
Message: the rest of heartbeat info skipped ...
  - Error number: `MY-010465`; Symbol: `ER_RPL_BINLOG_SOURCE_USES_CHECKSUM_AND_REPLICA_CANT`; SQLSTATE: `HY000`  
Message: Source is configured to log replication events with checksum, but will not send such events to replicas that cannot process them
  - Error number: `MY-010467`; Symbol: `ER_KILLING_THREAD`; SQLSTATE: `HY000`  
Message: Killing thread %lu
  - Error number: `MY-010468`; Symbol: `ER_DETACHING_SESSION_LEFT_BY_PLUGIN`; SQLSTATE: `HY000`
-

---

Message: Plugin %s is deinitializing a thread but left a session attached. Detaching it forcefully.

- Error number: MY-010469; Symbol: ER\_CANT\_DETACH\_SESSION\_LEFT\_BY\_PLUGIN; SQLSTATE: HY000

Message: Failed to detach the session.

- Error number: MY-010470; Symbol: ER\_DETACHED\_SESSIONS\_LEFT\_BY\_PLUGIN; SQLSTATE: HY000

Message: Closed forcefully %u session%s left opened by plugin %s

- Error number: MY-010471; Symbol: ER\_FAILED\_TO\_DECREMENT\_NUMBER\_OF\_THREADS; SQLSTATE: HY000

Message: Failed to decrement the number of threads

- Error number: MY-010472; Symbol: ER\_PLUGIN\_DID\_NOT\_DEINITIALIZE\_THREADS; SQLSTATE: HY000

Message: Plugin %s did not deinitialize %u threads

- Error number: MY-010473; Symbol: ER\_KILLED\_THREADS\_OF\_PLUGIN; SQLSTATE: HY000

Message: Killed %u threads of plugin %s

- Error number: MY-010517; Symbol: ER\_DEBUG\_CHECK\_SHARES\_OPEN; SQLSTATE: HY000

Message: debug\_check\_shares open:

- Error number: MY-010518; Symbol: ER\_DEBUG\_CHECK\_SHARES\_INFO; SQLSTATE: HY000

Message: %s.%s: state: %s(%u) use\_count: %u

- Error number: MY-010519; Symbol: ER\_DEBUG\_CHECK\_SHARES\_DROPPED; SQLSTATE: HY000

Message: debug\_check\_shares dropped:

- Error number: MY-010520; Symbol: ER\_INVALID\_OR\_OLD\_TABLE\_OR\_DB\_NAME; SQLSTATE: HY000

Message: Invalid (old?) table or database name '%s'

- Error number: MY-010521; Symbol: ER\_TC\_RECOVERING\_AFTER\_CRASH\_USING; SQLSTATE: HY000

Message: Recovering after a crash using %s

- Error number: MY-010522; Symbol: ER\_TC\_CANT\_AUTO\_RECOVER\_WITH\_TC\_HEURISTIC\_RECOVER; SQLSTATE: HY000

Message: Cannot perform automatic crash recovery when --tc-heuristic-recover is used

- Error number: MY-010523; Symbol: ER\_TC\_BAD\_MAGIC\_IN\_TC\_LOG; SQLSTATE: HY000

Message: Bad magic header in tc log

- Error number: MY-010524; Symbol: ER\_TC\_NEED\_N\_SE\_SUPPORTING\_2PC\_FOR\_RECOVERY; SQLSTATE: HY000

Message: Recovery failed! You must enable exactly %d storage engines that support two-phase commit protocol

- 
- Error number: `MY-010525`; Symbol: `ER_TC_RECOVERY_FAILED_THESE_ARE_YOUR_OPTIONS`; SQLSTATE: `HY000`  
 Message: Crash recovery failed. Either correct the problem (if it's, for example, out of memory error) and restart, or delete tc log and start mysqld with `--tc-heuristic-recover={commit|rollback}`
  - Error number: `MY-010526`; Symbol: `ER_TC_HEURISTIC_RECOVERY_MODE`; SQLSTATE: `HY000`  
 Message: Heuristic crash recovery mode
  - Error number: `MY-010527`; Symbol: `ER_TC_HEURISTIC_RECOVERY_FAILED`; SQLSTATE: `HY000`  
 Message: Heuristic crash recovery failed
  - Error number: `MY-010528`; Symbol: `ER_TC_RESTART_WITHOUT_TC_HEURISTIC_RECOVER`; SQLSTATE: `HY000`  
 Message: Please restart mysqld without `--tc-heuristic-recover`
  - Error number: `MY-010529`; Symbol: `ER_RPL_REPLICA_FAILED_TO_CREATE_OR_RECOVER_INFO_REPOSITORIES`; SQLSTATE: `HY000`  
 Message: Failed to create or recover replication info repositories.
  - Error number: `MY-010530`; Symbol: `ER_RPL_REPLICA_AUTO_POSITION_IS_1_AND_GTID_MODE_IS_OFF`; SQLSTATE: `HY000`  
 Message: Detected misconfiguration: replication channel '%s' was configured with `AUTO_POSITION = 1`, but the server was started with `--gtid-mode=off`. Either reconfigure replication using `CHANGE REPLICATION SOURCE TO SOURCE_AUTO_POSITION = 0 FOR CHANNEL '%s'`, or change `GTID_MODE` to some value other than `OFF`, before starting the replica receiver thread.
  - Error number: `MY-010531`; Symbol: `ER_RPL_REPLICA_CANT_START_REPLICA_FOR_CHANNEL`; SQLSTATE: `HY000`  
 Message: Replica: Could not start replica for channel '%s'. operation discontinued
  - Error number: `MY-010532`; Symbol: `ER_RPL_REPLICA_CANT_STOP_REPLICA_FOR_CHANNEL`; SQLSTATE: `HY000`  
 Message: Replica: Could not stop replica for channel '%s' operation discontinued
  - Error number: `MY-010533`; Symbol: `ER_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_SOURCE`; SQLSTATE: `HY000`  
 Message: Error during `--relay-log-recovery`: Could not locate rotate event from the source.
  - Error number: `MY-010534`; Symbol: `ER_RPL_RECOVERY_ERROR_READ_RELAY_LOG`; SQLSTATE: `HY000`  
 Message: Error during `--relay-log-recovery`: Error reading events from relay log: %d
  - Error number: `MY-010536`; Symbol: `ER_RPL_RECOVERY_SKIPPED_GROUP_REPLICATION_CHANNEL`; SQLSTATE: `HY000`  
 Message: Relay log recovery skipped for group replication channel.
  - Error number: `MY-010537`; Symbol: `ER_RPL_RECOVERY_ERROR`; SQLSTATE: `HY000`  
 Message: Error during `--relay-log-recovery`: %s
  - Error number: `MY-010538`; Symbol: `ER_RPL_RECOVERY_IO_ERROR_READING_RELAY_LOG_INDEX`; SQLSTATE: `HY000`

---

Message: Error during --relay-log-recovery: Could not read relay log index file due to an IO error.

- Error number: MY-010539; Symbol: ER\_RPL\_RECOVERY\_FILE\_SOURCE\_POS\_INFO; SQLSTATE: HY000

Message: Recovery from source pos %ld and file %s%s. Previous relay log pos and relay log file had been set to %lld, %s respectively.

- Error number: MY-010540; Symbol: ER\_RPL\_RECOVERY\_REPLICATE\_SAME\_SERVER\_ID\_REQUIRES\_POSITION; SQLSTATE: HY000

Message: Error during --relay-log-recovery: replicate\_same\_server\_id is in use and sql thread's positions are not initialized, hence relay log recovery cannot happen.

- Error number: MY-010541; Symbol: ER\_RPL\_MTA\_RECOVERY\_STARTING\_COORDINATOR; SQLSTATE: HY000

Message: MTA recovery: starting coordinator thread to fill MTA gaps.

- Error number: MY-010542; Symbol: ER\_RPL\_MTA\_RECOVERY\_FAILED\_TO\_START\_COORDINATOR; SQLSTATE: HY000

Message: MTA recovery: failed to start the coordinator thread. Check the error log for additional details.

- Error number: MY-010543; Symbol: ER\_RPL\_MTA\_AUTOMATIC\_RECOVERY\_FAILED; SQLSTATE: HY000

Message: MTA recovery: automatic recovery failed. Either the replica server had stopped due to an error during an earlier session or relay logs are corrupted. Fix the cause of the replica side error and restart the replica server or consider using RESET REPLICA.

- Error number: MY-010544; Symbol: ER\_RPL\_MTA\_RECOVERY\_CANT\_OPEN\_RELAY\_LOG; SQLSTATE: HY000

Message: Failed to open the relay log '%s' (relay\_log\_pos %s).

- Error number: MY-010545; Symbol: ER\_RPL\_MTA\_RECOVERY\_SUCCESSFUL; SQLSTATE: HY000

Message: MTA recovery: completed successfully.

- Error number: MY-010546; Symbol: ER\_RPL\_SERVER\_ID\_MISSING; SQLSTATE: HY000

Message: Server id not set, will not start replica%s

- Error number: MY-010547; Symbol: ER\_RPL\_CANT\_CREATE\_REPLICA\_THREAD; SQLSTATE: HY000

Message: Can't create replica thread%s.

- Error number: MY-010548; Symbol: ER\_RPL\_REPLICA\_IO\_THREAD\_WAS\_KILLED; SQLSTATE: HY000

Message: The replica IO thread%s was killed while executing initialization query '%s'

- Error number: MY-010550; Symbol: ER\_RPL\_REPLICA\_USES\_CHECKSUM\_AND\_SOURCE\_PRE\_50; SQLSTATE: HY000

Message: Found a source with MySQL server version older than 5.0. With checksums enabled on the replica, replication might not work correctly. To ensure correct replication, restart the replica server with --replica\_sql\_verify\_checksum=0.



- Error number: `MY-010551`; Symbol: `ER_RPL_REPLICA_SECONDS_BEHIND_SOURCE_DUBIOUS`; SQLSTATE: `HY000`  
 Message: "SELECT UNIX\_TIMESTAMP()" failed on source, do not trust column Seconds\_Behind\_Source of SHOW REPLICA STATUS. Error: %s (%d)
- Error number: `MY-010552`; Symbol: `ER_RPL_REPLICA_CANT_FLUSH_CONNECTION_METADATA_REPOS`; SQLSTATE: `HY000`  
 Message: Failed to flush connection metadata repository.
- Error number: `MY-010553`; Symbol: `ER_RPL_REPLICA_REPORT_HOST_TOO_LONG`; SQLSTATE: `HY000`  
 Message: The length of report\_host is %zu. It is larger than the max length(%d), so this replica cannot be registered to the source%s.
- Error number: `MY-010554`; Symbol: `ER_RPL_REPLICA_REPORT_USER_TOO_LONG`; SQLSTATE: `HY000`  
 Message: The length of report\_user is %zu. It is larger than the max length(%d), so this replica cannot be registered to the source%s.
- Error number: `MY-010555`; Symbol: `ER_RPL_REPLICA_REPORT_PASSWORD_TOO_LONG`; SQLSTATE: `HY000`  
 Message: The length of report\_password is %zu. It is larger than the max length(%d), so this replica cannot be registered to the source%s.
- Error number: `MY-010556`; Symbol: `ER_RPL_REPLICA_ERROR_RETRYING`; SQLSTATE: `HY000`  
 Message: Error on %s: %d %s, will retry in %d secs
- Error number: `MY-010557`; Symbol: `ER_RPL_REPLICA_ERROR_READING_FROM_SERVER`; SQLSTATE: `HY000`  
 Message: Error reading packet from server%s: %s (server\_errno=%d)
- Error number: `MY-010558`; Symbol: `ER_RPL_REPLICA_DUMP_THREAD_KILLED_BY_SOURCE`; SQLSTATE: `HY000`  
 Message: Replica%s: received end packet from server due to dump thread being killed on source. Dump threads are killed for example during source shutdown, explicitly by a user, or when the source receives a binlog send request from a duplicate server UUID <%s> : Error %s
- Error number: `MY-010559`; Symbol: `ER_RPL_MTA_STATISTICS`; SQLSTATE: `HY000`  
 Message: Multi-threaded replica statistics%s: seconds elapsed = %lu; events assigned = %llu; worker queues filled over overrun level = %lu; waited due a Worker queue full = %lu; waited due the total size = %lu; waited at clock conflicts = %llu waited (count) when Workers occupied = %lu waited when Workers occupied = %llu
- Error number: `MY-010560`; Symbol: `ER_RPL_MTA_RECOVERY_COMPLETE`; SQLSTATE: `HY000`  
 Message: Replica%s: MTA Recovery has completed at relay log %s, position %llu source log %s, position %llu.
- Error number: `MY-010561`; Symbol: `ER_RPL_REPLICA_CANT_INIT_RELAY_LOG_POSITION`; SQLSTATE: `HY000`  
 Message: Error initializing relay log position%s: %s
- Error number: `MY-010563`; Symbol: `ER_RPL_REPLICA_IO_THREAD_KILLED`; SQLSTATE: `HY000`

---

Message: Replica I/O thread%s killed while connecting to source

- Error number: MY-010564; Symbol: ER\_RPL\_REPLICA\_IO\_THREAD\_CANT\_REGISTER\_ON\_SOURCE; SQLSTATE: HY000

Message: Replica I/O thread couldn't register on source

- Error number: MY-010565; Symbol: ER\_RPL\_REPLICA\_FORCING\_TO\_RECONNECT\_IO\_THREAD; SQLSTATE: HY000

Message: Forcing to reconnect replica I/O thread%s

- Error number: MY-010566; Symbol: ER\_RPL\_REPLICA\_ERROR\_REQUESTING\_BINLOG\_DUMP; SQLSTATE: HY000

Message: Failed on request\_dump()%s

- Error number: MY-010567; Symbol: ER\_RPL\_LOG\_ENTRY\_EXCEEDS\_REPLICA\_MAX\_ALLOWED\_PACKET; SQLSTATE: HY000

Message: Log entry on source is longer than replica\_max\_allowed\_packet (%lu) on replica. If the entry is correct, restart the server with a higher value of replica\_max\_allowed\_packet

- Error number: MY-010568; Symbol: ER\_RPL\_REPLICA\_STOPPING\_AS\_SOURCE\_OOM; SQLSTATE: HY000

Message: Stopping replica I/O thread due to out-of-memory error from source

- Error number: MY-010569; Symbol: ER\_RPL\_REPLICA\_IO\_THREAD\_ABORTED\_WAITING\_FOR\_RELAY\_LOG\_SPACE; SQLSTATE: HY000

Message: Replica I/O thread aborted while waiting for relay log space

- Error number: MY-010570; Symbol: ER\_RPL\_REPLICA\_IO\_THREAD\_EXITING; SQLSTATE: HY000

Message: Replica I/O thread exiting%s, read up to log '%s', position %s

- Error number: MY-010571; Symbol: ER\_RPL\_REPLICA\_CANT\_INITIALIZE\_REPLICA\_WORKER; SQLSTATE: HY000

Message: Failed during replica worker initialization%s

- Error number: MY-010572; Symbol: ER\_RPL\_MTA\_GROUP\_RECOVERY\_APPLIER\_METADATA\_FOR\_WORKER; SQLSTATE: HY000

Message: Replica: MTA group recovery applier metadata based on Worker-Id %lu, group\_relay\_log\_name %s, group\_relay\_log\_pos %llu group\_source\_log\_name %s, group\_source\_log\_pos %llu

- Error number: MY-010573; Symbol: ER\_RPL\_ERROR\_LOOKING\_FOR\_LOG; SQLSTATE: HY000

Message: Error looking for %s.

- Error number: MY-010574; Symbol: ER\_RPL\_MTA\_GROUP\_RECOVERY\_APPLIER\_METADATA; SQLSTATE: HY000

Message: Replica: MTA group recovery applier metadata group\_source\_log\_name %s, event\_source\_log\_pos %llu.

- Error number: MY-010575; Symbol: ER\_RPL\_CANT\_FIND\_FOLLOWUP\_FILE; SQLSTATE: HY000

---

Message: Error looking for file after %s.

- Error number: [MY-010576](#); Symbol: [ER\\_RPL\\_MTA\\_CHECKPOINT\\_PERIOD\\_DIFFERS\\_FROM\\_CNT](#); SQLSTATE: [HY000](#)

Message: This an error cnt != mta\_checkpoint\_period

- Error number: [MY-010577](#); Symbol: [ER\\_RPL\\_REPLICA\\_WORKER\\_THREAD\\_CREATION\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed during replica worker thread creation%s

- Error number: [MY-010578](#); Symbol: [ER\\_RPL\\_REPLICA\\_WORKER\\_THREAD\\_CREATION\\_FAILED\\_WITH\\_ERRNO](#); SQLSTATE: [HY000](#)

Message: Failed during replica worker thread creation%s (errno= %d)

- Error number: [MY-010579](#); Symbol: [ER\\_RPL\\_REPLICA\\_FAILED\\_TO\\_INIT\\_PARTITIONS\\_HASH](#); SQLSTATE: [HY000](#)

Message: Failed to init partitions hash

- Error number: [MY-010581](#); Symbol: [ER\\_RPL\\_REPLICA\\_SQL\\_THREAD\\_STARTING](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread%s initialized, starting replication in log '%s' at position %s, relay log '%s' position: %s

- Error number: [MY-010582](#); Symbol: [ER\\_RPL\\_REPLICA\\_SKIP\\_COUNTER\\_EXECUTED](#); SQLSTATE: [HY000](#)

Message: 'SQL\_REPLICA\_SKIP\_COUNTER=%ld' executed at relay\_log\_file='%s', relay\_log\_pos=%ld', source\_log\_name='%s', source\_log\_pos=%ld' and new position at relay\_log\_file='%s', relay\_log\_pos=%ld', source\_log\_name='%s', source\_log\_pos=%ld'

- Error number: [MY-010583](#); Symbol: [ER\\_RPL\\_REPLICA\\_ADDITIONAL\\_ERROR\\_INFO\\_FROM\\_DA](#); SQLSTATE: [HY000](#)

Message: Replica (additional info): %s Error\_code: MY-%06d

- Error number: [MY-010584](#); Symbol: [ER\\_RPL\\_REPLICA\\_ERROR\\_INFO\\_FROM\\_DA](#); SQLSTATE: [HY000](#)

Message: Replica: %s Error\_code: MY-%06d

- Error number: [MY-010585](#); Symbol: [ER\\_RPL\\_REPLICA\\_ERROR\\_LOADING\\_USER\\_DEFINED\\_LIBRARY](#); SQLSTATE: [HY000](#)

Message: Error loading user-defined library, replica SQL thread aborted. Install the missing library, and restart the replica SQL thread with "START REPLICA". We stopped at log '%s' position %s

- Error number: [MY-010586](#); Symbol: [ER\\_RPL\\_REPLICA\\_ERROR\\_RUNNING\\_QUERY](#); SQLSTATE: [HY000](#)

Message: Error running query, replica SQL thread aborted. Fix the problem, and restart the replica SQL thread with "START REPLICA". We stopped at log '%s' position %s

- Error number: [MY-010587](#); Symbol: [ER\\_RPL\\_REPLICA\\_SQL\\_THREAD\\_EXITING](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread%s exiting, replication stopped in log '%s' at position %s

- Error number: `MY-010588`; Symbol: `ER_RPL_REPLICA_READ_INVALID_EVENT_FROM_SOURCE`; SQLSTATE: `HY000`  
  
Message: Read invalid event from source: '%s', source could be corrupt but a more likely cause of this is a bug
- Error number: `MY-010589`; Symbol: `ER_RPL_REPLICA_QUEUE_EVENT_FAILED_INVALID_CONFIGURATION`; SQLSTATE: `HY000`  
  
Message: The queue event failed for channel '%s' as its configuration is invalid.
- Error number: `MY-010590`; Symbol: `ER_RPL_REPLICA_IO_THREAD_DETECTED_UNEXPECTED_EVENT_SEQUENCE`; SQLSTATE: `HY000`  
  
Message: An unexpected event sequence was detected by the IO thread while queuing the event received from source '%s' binary log file, at position %llu.
- Error number: `MY-010591`; Symbol: `ER_RPL_REPLICA_CANT_USE_CHARSET`; SQLSTATE: `HY000`  
  
Message: '%s' can not be used as client character set. '%s' will be used as default client character set while connecting to source.
- Error number: `MY-010592`; Symbol: `ER_RPL_REPLICA_CONNECTED_TO_SOURCE_REPLICATION_RESUMED`; SQLSTATE: `HY000`  
  
Message: Replica%s: connected to source '%s@%s:%d', replication resumed in log '%s' at position %s
- Error number: `MY-010593`; Symbol: `ER_RPL_REPLICA_NEXT_LOG_IS_ACTIVE`; SQLSTATE: `HY000`  
  
Message: next log '%s' is active
- Error number: `MY-010594`; Symbol: `ER_RPL_REPLICA_NEXT_LOG_IS_INACTIVE`; SQLSTATE: `HY000`  
  
Message: next log '%s' is not active
- Error number: `MY-010595`; Symbol: `ER_RPL_REPLICA_SQL_THREAD_IO_ERROR_READING_EVENT`; SQLSTATE: `HY000`  
  
Message: Replica SQL thread%s: I/O error reading event (errno: %d cur\_log->error: %d)
- Error number: `MY-010596`; Symbol: `ER_RPL_REPLICA_ERROR_READING_RELAY_LOG_EVENTS`; SQLSTATE: `HY000`  
  
Message: Error reading relay log event%s: %s
- Error number: `MY-010597`; Symbol: `ER_REPLICA_CHANGE_SOURCE_TO_EXECUTED`; SQLSTATE: `HY000`  
  
Message: 'CHANGE REPLICATION SOURCE TO%s executed'. Previous state source\_host='%s', source\_port= %u, source\_log\_file='%s', source\_log\_pos= %ld, source\_bind='%s'. New state source\_host='%s', source\_port= %u, source\_log\_file='%s', source\_log\_pos= %ld, source\_bind='%s'.
- Error number: `MY-010598`; Symbol: `ER_RPL_REPLICA_NEW_C_M_NEEDS_REPOS_TYPE_OTHER_THAN_FILE`; SQLSTATE: `HY000`  
  
Message: Replica: Cannot create new connection metadata structure when repositories are of type FILE. Convert replica repositories to TABLE to replicate from multiple sources.

- 
- Error number: `MY-010599`; Symbol: `ER_RPL_FAILED_TO_STAT_LOG_IN_INDEX`; SQLSTATE: `HY000`  
Message: log %s listed in the index, but failed to stat.
  - Error number: `MY-010600`; Symbol: `ER_RPL_LOG_NOT_FOUND_WHILE_COUNTING_RELAY_LOG_SPACE`; SQLSTATE: `HY000`  
Message: Could not find first log while counting relay log space.
  - Error number: `MY-010601`; Symbol: `ER_REPLICA_CANT_USE_TMPDIR`; SQLSTATE: `HY000`  
Message: Unable to use replica's temporary directory '%s'.
  - Error number: `MY-010602`; Symbol: `ER_RPL_RELAY_LOG_NEEDS_FILE_NOT_DIRECTORY`; SQLSTATE: `HY000`  
Message: Path '%s' is a directory name, please specify a file name for --relay-log option.
  - Error number: `MY-010603`; Symbol: `ER_RPL_RELAY_LOG_INDEX_NEEDS_FILE_NOT_DIRECTORY`; SQLSTATE: `HY000`  
Message: Path '%s' is a directory name, please specify a file name for --relay-log-index option.
  - Error number: `MY-010604`; Symbol: `ER_RPL_PLEASE_USE_OPTION_RELAY_LOG`; SQLSTATE: `HY000`  
Message: Neither --relay-log nor --relay-log-index were used; so replication may break when this MySQL server acts as a replica and has his hostname changed!! Please use '--relay-log=%s' to avoid this problem.
  - Error number: `MY-010605`; Symbol: `ER_RPL_OPEN_INDEX_FILE_FAILED`; SQLSTATE: `HY000`  
Message: Failed in open\_index\_file() called from Relay\_log\_info::rli\_init\_info().
  - Error number: `MY-010606`; Symbol: `ER_RPL_CANT_INITIALIZE_GTID_SETS_IN_AM_INIT_INFO`; SQLSTATE: `HY000`  
Message: Failed in init\_gtid\_sets() called from Relay\_log\_info::rli\_init\_info().
  - Error number: `MY-010607`; Symbol: `ER_RPL_CANT_OPEN_LOG_IN_AM_INIT_INFO`; SQLSTATE: `HY000`  
Message: Failed in open\_log() called from Relay\_log\_info::rli\_init\_info().
  - Error number: `MY-010608`; Symbol: `ER_RPL_ERROR_WRITING_RELAY_LOG_CONFIGURATION`; SQLSTATE: `HY000`  
Message: Error writing relay log configuration.
  - Error number: `MY-010709`; Symbol: `ER_TREE_CORRUPT_PARENT_SHOULD_POINT_AT_PARENT`; SQLSTATE: `HY000`  
Message: Wrong tree: Parent doesn't point at parent
  - Error number: `MY-010710`; Symbol: `ER_TREE_CORRUPT_ROOT_SHOULD_BE_BLACK`; SQLSTATE: `HY000`  
Message: Wrong tree: Root should be black
  - Error number: `MY-010711`; Symbol: `ER_TREE_CORRUPT_2_CONSECUTIVE_REDS`; SQLSTATE: `HY000`  
Message: Wrong tree: Found two red in a row

- Error number: `MY-010712`; Symbol: `ER_TREE_CORRUPT_RIGHT_IS_LEFT`; SQLSTATE: `HY000`  
Message: Wrong tree: Found right == left
- Error number: `MY-010713`; Symbol: `ER_TREE_CORRUPT_INCORRECT_BLACK_COUNT`; SQLSTATE: `HY000`  
Message: Wrong tree: Incorrect black-count: %d - %d
- Error number: `MY-010714`; Symbol: `ER_WRONG_COUNT_FOR_ORIGIN`; SQLSTATE: `HY000`  
Message: Use\_count: Wrong count %lu for origin %p
- Error number: `MY-010715`; Symbol: `ER_WRONG_COUNT_FOR_KEY`; SQLSTATE: `HY000`  
Message: Use\_count: Wrong count for key at %p, %lu should be %lu
- Error number: `MY-010716`; Symbol: `ER_WRONG_COUNT_OF_ELEMENTS`; SQLSTATE: `HY000`  
Message: Wrong number of elements: %u (should be %u) for tree at %p
- Error number: `MY-010717`; Symbol: `ER_RPL_ERROR_READING_REPLICA_WORKER_CONFIGURATION`; SQLSTATE: `HY000`  
Message: Error reading replica worker configuration
- Error number: `MY-010719`; Symbol: `ER_RPL_FAILED_TO_OPEN_RELAY_LOG`; SQLSTATE: `HY000`  
Message: Failed to open relay log %s, error: %s
- Error number: `MY-010720`; Symbol: `ER_RPL_WORKER_CANT_READ_RELAY_LOG`; SQLSTATE: `HY000`  
Message: Error when worker read relay log events, relay log name %s, position %llu
- Error number: `MY-010721`; Symbol: `ER_RPL_WORKER_CANT_FIND_NEXT_RELAY_LOG`; SQLSTATE: `HY000`  
Message: Failed to find next relay log when retrying the transaction, current relay log is %s
- Error number: `MY-010722`; Symbol: `ER_RPL_MTA_REPLICA_COORDINATOR_HAS_WAITED`; SQLSTATE: `HY000`  
Message: Multi-threaded replica: Coordinator has waited %lu times hitting replica\_pending\_jobs\_size\_max; current event size = %zu.
- Error number: `MY-010723`; Symbol: `ER_BINLOG_FAILED_TO_WRITE_DROP_FOR_TEMP_TABLES`; SQLSTATE: `HY000`  
Message: Failed to write the DROP statement for temporary tables to binary log
- Error number: `MY-010724`; Symbol: `ER_BINLOG_OOM_WRITING_DELETE_WHILE_OPENING_HEAP_TABLE`; SQLSTATE: `HY000`  
Message: When opening HEAP table, could not allocate memory to write 'DELETE FROM `%s`.`%s`' to the binary log
- Error number: `MY-010725`; Symbol: `ER_FAILED_TO_REPAIR_TABLE`; SQLSTATE: `HY000`  
Message: Couldn't repair table: %s.%s
- Error number: `MY-010726`; Symbol: `ER_FAILED_TO_REMOVE_TEMP_TABLE`; SQLSTATE: `HY000`  
Message: Could not remove temporary table: '%s', error: %d

- 
- Error number: [MY-010727](#); Symbol: [ER\\_SYSTEM\\_TABLE\\_NOT\\_TRANSACTIONAL](#); SQLSTATE: [HY000](#)  
Message: System table '%.\*s' is expected to be transactional.
  - Error number: [MY-010728](#); Symbol: [ER\\_RPL\\_ERROR\\_WRITING\\_SOURCE\\_CONFIGURATION](#); SQLSTATE: [HY000](#)  
Message: Error writing source configuration.
  - Error number: [MY-010729](#); Symbol: [ER\\_RPL\\_ERROR\\_READING\\_SOURCE\\_CONFIGURATION](#); SQLSTATE: [HY000](#)  
Message: Error reading source configuration.
  - Error number: [MY-010730](#); Symbol: [ER\\_RPL\\_SSL\\_INFO\\_IN\\_CONNECTION\\_METADATA\\_IGNORED](#); SQLSTATE: [HY000](#)  
Message: SSL information in the connection metadata repository are ignored because this MySQL replica was compiled without SSL support.
  - Error number: [MY-010731](#); Symbol: [ER\\_PLUGIN\\_FAILED\\_DEINITIALIZATION](#); SQLSTATE: [HY000](#)  
Message: Plugin '%s' of type %s failed deinitialization
  - Error number: [MY-010732](#); Symbol: [ER\\_PLUGIN\\_HAS\\_NONZERO\\_REFCOUNT\\_AFTER\\_DEINITIALIZATION](#); SQLSTATE: [HY000](#)  
Message: Plugin '%s' has ref\_count=%d after deinitialization.
  - Error number: [MY-010733](#); Symbol: [ER\\_PLUGIN\\_SHUTTING\\_DOWN\\_PLUGIN](#); SQLSTATE: [HY000](#)  
Message: Shutting down plugin '%s'
  - Error number: [MY-010734](#); Symbol: [ER\\_PLUGIN\\_REGISTRATION\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Plugin '%s' registration as a %s failed.
  - Error number: [MY-010735](#); Symbol: [ER\\_PLUGIN\\_CANT\\_OPEN\\_PLUGIN\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Could not open the mysql.plugin table. Please perform the MySQL upgrade procedure.
  - Error number: [MY-010736](#); Symbol: [ER\\_PLUGIN\\_CANT\\_LOAD](#); SQLSTATE: [HY000](#)  
Message: Couldn't load plugin named '%s' with soname '%s'.
  - Error number: [MY-010737](#); Symbol: [ER\\_PLUGIN\\_LOAD\\_PARAMETER\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)  
Message: plugin-load parameter too long
  - Error number: [MY-010738](#); Symbol: [ER\\_PLUGIN\\_FORCING\\_SHUTDOWN](#); SQLSTATE: [HY000](#)  
Message: Plugin '%s' will be forced to shutdown
  - Error number: [MY-010739](#); Symbol: [ER\\_PLUGIN\\_HAS\\_NONZERO\\_REFCOUNT\\_AFTER\\_SHUTDOWN](#); SQLSTATE: [HY000](#)  
Message: Plugin '%s' has ref\_count=%d after shutdown.
  - Error number: [MY-010740](#); Symbol: [ER\\_PLUGIN\\_UNKNOWN\\_VARIABLE\\_TYPE](#); SQLSTATE: [HY000](#)
-

---

Message: Unknown variable type code 0x%x in plugin '%s'.

- Error number: [MY-010741](#); Symbol: [ER\\_PLUGIN\\_VARIABLE\\_SET\\_READ\\_ONLY](#); SQLSTATE: [HY000](#)

Message: Server variable %s of plugin %s was forced to be read-only: string variable without update\_func and PLUGIN\_VAR\_MEMALLOC flag

- Error number: [MY-010742](#); Symbol: [ER\\_PLUGIN\\_VARIABLE\\_MISSING\\_NAME](#); SQLSTATE: [HY000](#)

Message: Missing variable name in plugin '%s'.

- Error number: [MY-010743](#); Symbol: [ER\\_PLUGIN\\_VARIABLE\\_NOT\\_ALLOCATED\\_THREAD\\_LOCAL](#); SQLSTATE: [HY000](#)

Message: Thread local variable '%s' not allocated in plugin '%s'.

- Error number: [MY-010744](#); Symbol: [ER\\_PLUGIN\\_OOM](#); SQLSTATE: [HY000](#)

Message: Out of memory for plugin '%s'.

- Error number: [MY-010745](#); Symbol: [ER\\_PLUGIN\\_BAD\\_OPTIONS](#); SQLSTATE: [HY000](#)

Message: Bad options for plugin '%s'.

- Error number: [MY-010746](#); Symbol: [ER\\_PLUGIN\\_PARSING\\_OPTIONS\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Parsing options for plugin '%s' failed.

- Error number: [MY-010747](#); Symbol: [ER\\_PLUGIN\\_DISABLED](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' is disabled.

- Error number: [MY-010748](#); Symbol: [ER\\_PLUGIN\\_HAS\\_CONFLICTING\\_SYSTEM\\_VARIABLES](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' has conflicting system variables

- Error number: [MY-010749](#); Symbol: [ER\\_PLUGIN\\_CANT\\_SET\\_PERSISTENT\\_OPTIONS](#); SQLSTATE: [HY000](#)

Message: Setting persistent options for plugin '%s' failed.

- Error number: [MY-010750](#); Symbol: [ER\\_MY\\_NET\\_WRITE\\_FAILED\\_FALLING\\_BACK\\_ON\\_STDERR](#); SQLSTATE: [HY000](#)

Message: Failed on my\_net\_write, writing to stderr instead: %s

- Error number: [MY-010751](#); Symbol: [ER\\_RETRYING\\_REPAIR\\_WITHOUT\\_QUICK](#); SQLSTATE: [HY000](#)

Message: Retrying repair of: '%s' without quick

- Error number: [MY-010752](#); Symbol: [ER\\_RETRYING\\_REPAIR\\_WITH\\_KEYCACHE](#); SQLSTATE: [HY000](#)

Message: Retrying repair of: '%s' with keycache

- Error number: [MY-010753](#); Symbol: [ER\\_FOUND\\_ROWS\\_WHILE\\_REPAIRING](#); SQLSTATE: [HY000](#)

Message: Found %s of %s rows when repairing '%s'



- 
- Error number: [MY-010754](#); Symbol: [ER\\_ERROR\\_DURING\\_OPTIMIZE\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Warning: Optimize table got errno %d on %s.%s, retrying
  - Error number: [MY-010755](#); Symbol: [ER\\_ERROR\\_ENABLING\\_KEYS](#); SQLSTATE: [HY000](#)  
Message: Warning: Enabling keys got errno %d on %s.%s, retrying
  - Error number: [MY-010756](#); Symbol: [ER\\_CHECKING\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Checking table: '%s'
  - Error number: [MY-010757](#); Symbol: [ER\\_RECOVERING\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Recovering table: '%s'
  - Error number: [MY-010758](#); Symbol: [ER\\_CANT\\_CREATE\\_TABLE\\_SHARE\\_FROM\\_FRM](#); SQLSTATE: [HY000](#)  
Message: Error in creating TABLE\_SHARE from %s.frm file.
  - Error number: [MY-010759](#); Symbol: [ER\\_CANT\\_LOCK\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Unable to acquire lock on %s.%s
  - Error number: [MY-010760](#); Symbol: [ER\\_CANT\\_ALLOC\\_TABLE\\_OBJECT](#); SQLSTATE: [HY000](#)  
Message: Error in allocation memory for TABLE object.
  - Error number: [MY-010761](#); Symbol: [ER\\_CANT\\_CREATE\\_HANDLER\\_OBJECT\\_FOR\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Error in creating handler object for table %s.%s
  - Error number: [MY-010762](#); Symbol: [ER\\_CANT\\_SET\\_HANDLER\\_REFERENCE\\_FOR\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Error in setting handler reference for table %s.%s
  - Error number: [MY-010763](#); Symbol: [ER\\_CANT\\_LOCK\\_TABLESPACE](#); SQLSTATE: [HY000](#)  
Message: Unable to acquire lock on tablespace name %s
  - Error number: [MY-010764](#); Symbol: [ER\\_CANT\\_UPGRADE\\_GENERATED\\_COLUMNS\\_TO\\_DD](#); SQLSTATE: [HY000](#)  
Message: Error in processing generated columns for table %s.%s
  - Error number: [MY-010765](#); Symbol: [ER\\_DD\\_ERROR\\_CREATING\\_ENTRY](#); SQLSTATE: [HY000](#)  
Message: Error in Creating DD entry for %s.%s
  - Error number: [MY-010766](#); Symbol: [ER\\_DD\\_CANT\\_FETCH\\_TABLE\\_DATA](#); SQLSTATE: [HY000](#)  
Message: Error in fetching %s.%s table data from dictionary
  - Error number: [MY-010767](#); Symbol: [ER\\_DD\\_CANT\\_FIX\\_SE\\_DATA](#); SQLSTATE: [HY000](#)  
Message: Error in fixing SE data for %s.%s
  - Error number: [MY-010768](#); Symbol: [ER\\_DD\\_CANT\\_CREATE\\_SP](#); SQLSTATE: [HY000](#)  
Message: Error in creating stored program '%s.%s'
-

- 
- Error number: [MY-010769](#); Symbol: [ER\\_CANT\\_OPEN\\_DB\\_OPT\\_USING\\_DEFAULT\\_CHARSET](#); SQLSTATE: [HY000](#)  
Message: Unable to open db.opt file %s. Using default Character set.
  - Error number: [MY-010770](#); Symbol: [ER\\_CANT\\_CREATE\\_CACHE\\_FOR\\_DB\\_OPT](#); SQLSTATE: [HY000](#)  
Message: Unable to initialize IO cache to open db.opt file %s.
  - Error number: [MY-010771](#); Symbol: [ER\\_CANT\\_IDENTIFY\\_CHARSET\\_USING\\_DEFAULT](#); SQLSTATE: [HY000](#)  
Message: Unable to identify the charset in %s. Using default character set.
  - Error number: [MY-010772](#); Symbol: [ER\\_DB\\_OPT\\_NOT\\_FOUND\\_USING\\_DEFAULT\\_CHARSET](#); SQLSTATE: [HY000](#)  
Message: db.opt file not found for %s database. Using default Character set.
  - Error number: [MY-010773](#); Symbol: [ER\\_EVENT\\_CANT\\_GET\\_TIMEZONE\\_FROM\\_FIELD](#); SQLSTATE: [HY000](#)  
Message: Event '%s'. '%s': invalid value in column mysql.event.time\_zone.  
  
This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.event` system table and migrates its contents to the internal data dictionary.
  - Error number: [MY-010774](#); Symbol: [ER\\_EVENT\\_CANT\\_FIND\\_TIMEZONE](#); SQLSTATE: [HY000](#)  
Message: Event '%s'. '%s': has invalid time zone value  
  
This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.event` system table and migrates its contents to the internal data dictionary.
  - Error number: [MY-010775](#); Symbol: [ER\\_EVENT\\_CANT\\_GET\\_CHARSET](#); SQLSTATE: [HY000](#)  
Message: Event '%s'. '%s': invalid value in column mysql.event.character\_set\_client.  
  
This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.event` system table and migrates its contents to the internal data dictionary.
  - Error number: [MY-010776](#); Symbol: [ER\\_EVENT\\_CANT\\_GET\\_COLLATION](#); SQLSTATE: [HY000](#)  
Message: Event '%s'. '%s': invalid value in column mysql.event.collation\_connection.  
  
This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.event` system table and migrates its contents to the internal data dictionary.
  - Error number: [MY-010777](#); Symbol: [ER\\_EVENT\\_CANT\\_OPEN\\_TABLE\\_MYSQL\\_EVENT](#); SQLSTATE: [HY000](#)  
Message: Failed to open mysql.event Table.  
  
This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.event` system table and migrates its contents to the internal data dictionary.
  - Error number: [MY-010778](#); Symbol: [ER\\_CANT\\_PARSE\\_STORED\\_ROUTINE\\_BODY](#); SQLSTATE: [HY000](#)

---

Message: Parsing '%s.%s' routine body failed.%s

- Error number: [MY-010779](#); Symbol: [ER\\_CANT\\_OPEN\\_TABLE\\_MYSQL\\_PROC](#); SQLSTATE: [HY000](#)

Message: Failed to open mysql.proc Table.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.proc` system table and migrates its contents to the internal data dictionary.

- Error number: [MY-010780](#); Symbol: [ER\\_CANT\\_READ\\_TABLE\\_MYSQL\\_PROC](#); SQLSTATE: [HY000](#)

Message: Failed to read mysql.proc table.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.proc` system table and migrates its contents to the internal data dictionary.

- Error number: [MY-010781](#); Symbol: [ER\\_FILE\\_EXISTS\\_DURING\\_UPGRADE](#); SQLSTATE: [HY000](#)

Message: Found %s file in mysql schema. DD will create .ibd file with same name. Please rename table and start upgrade process again.

- Error number: [MY-010782](#); Symbol: [ER\\_CANT\\_OPEN\\_DATADIR\\_AFTER\\_UPGRADE\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Unable to open the data directory %s during clean up after upgrade failed

- Error number: [MY-010783](#); Symbol: [ER\\_CANT\\_SET\\_PATH\\_FOR](#); SQLSTATE: [HY000](#)

Message: Failed to set path %s

- Error number: [MY-010784](#); Symbol: [ER\\_CANT\\_OPEN\\_DIR](#); SQLSTATE: [HY000](#)

Message: Failed to open dir %s

- Error number: [MY-010801](#); Symbol: [ER\\_EVENT\\_ERROR\\_CREATING\\_QUERY\\_TO\\_WRITE\\_TO\\_BINLOG](#); SQLSTATE: [HY000](#)

Message: Event Error: An error occurred while creating query string, before writing it into binary log.

- Error number: [MY-010802](#); Symbol: [ER\\_EVENT\\_SCHEDULER\\_ERROR\\_LOADING\\_FROM\\_DB](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: Error while loading from disk.

- Error number: [MY-010803](#); Symbol: [ER\\_EVENT\\_SCHEDULER\\_ERROR\\_GETTING\\_EVENT\\_OBJECT](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: Error getting event object.

- Error number: [MY-010804](#); Symbol: [ER\\_EVENT\\_SCHEDULER\\_GOT\\_BAD\\_DATA\\_FROM\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: Error while loading events from mysql.events. The table probably contains bad data or is corrupted

- Error number: [MY-010805](#); Symbol: [ER\\_EVENT\\_CANT\\_GET\\_LOCK\\_FOR\\_DROPPING\\_EVENT](#); SQLSTATE: [HY000](#)

Message: Unable to obtain lock for dropping event %s from schema %s

- Error number: [MY-010806](#); Symbol: [ER\\_EVENT\\_UNABLE\\_TO\\_DROP\\_EVENT](#); SQLSTATE: [HY000](#)

---

Message: Unable to drop event %s from schema %s

- Error number: [MY-010808](#); Symbol: [ER\\_BINLOG\\_CANT\\_RESIZE\\_CACHE](#); SQLSTATE: [HY000](#)

Message: Unable to resize binlog IOCACHE auxiliary file

- Error number: [MY-010809](#); Symbol: [ER\\_BINLOG\\_FILE\\_BEING\\_READ\\_NOT\\_PURGED](#); SQLSTATE: [HY000](#)

Message: file %s was not purged because it was being read by thread number %u

- Error number: [MY-010810](#); Symbol: [ER\\_BINLOG\\_IO\\_ERROR\\_READING\\_HEADER](#); SQLSTATE: [HY000](#)

Message: I/O error reading the header from the binary log, errno=%d, io cache code=%d

- Error number: [MY-010813](#); Symbol: [ER\\_BINLOG\\_FILE\\_EXTENSION\\_NUMBER\\_EXHAUSTED](#); SQLSTATE: [HY000](#)

Message: Log filename extension number exhausted: %06lu. Please fix this by archiving old logs and updating the index files.

- Error number: [MY-010814](#); Symbol: [ER\\_BINLOG\\_FILE\\_NAME\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)

Message: Log filename too large: %s%s (%zu). Please fix this by archiving old logs and updating the index files.

- Error number: [MY-010815](#); Symbol: [ER\\_BINLOG\\_FILE\\_EXTENSION\\_NUMBER\\_RUNNING\\_LOW](#); SQLSTATE: [HY000](#)

Message: Next log extension: %lu. Remaining log filename extensions: %lu. Please consider archiving some logs.

- Error number: [MY-010816](#); Symbol: [ER\\_BINLOG\\_CANT\\_OPEN\\_FOR\\_LOGGING](#); SQLSTATE: [HY000](#)

Message: Could not open %s for logging (error %d). Turning logging off for the whole duration of the MySQL server process. To turn it on again: fix the cause, shutdown the MySQL server and restart it.

- Error number: [MY-010817](#); Symbol: [ER\\_BINLOG\\_FAILED\\_TO\\_SYNC\\_INDEX\\_FILE](#); SQLSTATE: [HY000](#)

Message: MYSQL\_BIN\_LOG::open\_index\_file failed to sync the index file.

- Error number: [MY-010818](#); Symbol: [ER\\_BINLOG\\_ERROR\\_READING\\_GTIDS\\_FROM\\_RELAY\\_LOG](#); SQLSTATE: [HY000](#)

Message: Error reading GTIDs from relaylog: %d

- Error number: [MY-010819](#); Symbol: [ER\\_BINLOG\\_EVENTS\\_READ\\_FROM\\_APPLIER\\_METADATA](#); SQLSTATE: [HY000](#)

Message: %lu events read in relaylog file '%s' for updating Retrieved\_Gtid\_Set and/or IO thread transaction parser state.

- Error number: [MY-010820](#); Symbol: [ER\\_BINLOG\\_ERROR\\_READING\\_GTIDS\\_FROM\\_BINARY\\_LOG](#); SQLSTATE: [HY000](#)

Message: Error reading GTIDs from binary log: %d

- Error number: [MY-010821](#); Symbol: [ER\\_BINLOG\\_EVENTS\\_READ\\_FROM\\_BINLOG\\_INFO](#); SQLSTATE: [HY000](#)

Message: Read %lu events from binary log file '%s' to determine the GTIDs purged from binary logs.

- 
- Error number: `MY-010822`; Symbol: `ER_BINLOG_CANT_GENERATE_NEW_FILE_NAME`; SQLSTATE: `HY000`  
Message: `MYSQL_BIN_LOG::open` failed to generate new file name.
  - Error number: `MY-010823`; Symbol: `ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE_IN_OPEN`; SQLSTATE: `HY000`  
Message: `MYSQL_BIN_LOG::open` failed to sync the index file.
  - Error number: `MY-010824`; Symbol: `ER_BINLOG_CANT_USE_FOR_LOGGING`; SQLSTATE: `HY000`  
Message: Could not use %s for logging (error %d). Turning logging off for the whole duration of the MySQL server process. To turn it on again: fix the cause, shutdown the MySQL server and restart it.
  - Error number: `MY-010825`; Symbol: `ER_BINLOG_FAILED_TO_CLOSE_INDEX_FILE_WHILE_REBUILDING`; SQLSTATE: `HY000`  
Message: While rebuilding index file %s: Failed to close the index file.
  - Error number: `MY-010826`; Symbol: `ER_BINLOG_FAILED_TO_DELETE_INDEX_FILE_WHILE_REBUILDING`; SQLSTATE: `HY000`  
Message: While rebuilding index file %s: Failed to delete the existing index file. It could be that file is being used by some other process.
  - Error number: `MY-010827`; Symbol: `ER_BINLOG_FAILED_TO_RENAME_INDEX_FILE_WHILE_REBUILDING`; SQLSTATE: `HY000`  
Message: While rebuilding index file %s: Failed to rename the new index file to the existing index file.
  - Error number: `MY-010828`; Symbol: `ER_BINLOG_FAILED_TO_OPEN_INDEX_FILE_AFTER_REBUILDING`; SQLSTATE: `HY000`  
Message: After rebuilding the index file %s: Failed to open the index file.
  - Error number: `MY-010829`; Symbol: `ER_BINLOG_CANT_APPEND_LOG_TO_TMP_INDEX`; SQLSTATE: `HY000`  
Message: `MYSQL_BIN_LOG::add_log_to_index` failed to append log file name: %s, to crash safe index file.
  - Error number: `MY-010830`; Symbol: `ER_BINLOG_CANT_LOCATE_OLD_BINLOG_OR_RELAY_LOG_FILES`; SQLSTATE: `HY000`  
Message: Failed to locate old binlog or relay log files
  - Error number: `MY-010831`; Symbol: `ER_BINLOG_CANT_DELETE_FILE`; SQLSTATE: `HY000`  
Message: Failed to delete file '%s'
  - Error number: `MY-010832`; Symbol: `ER_BINLOG_CANT_SET_TMP_INDEX_NAME`; SQLSTATE: `HY000`  
Message: `MYSQL_BIN_LOG::set_crash_safe_index_file_name` failed to set file name.
  - Error number: `MY-010833`; Symbol: `ER_BINLOG_FAILED_TO_OPEN_TEMPORARY_INDEX_FILE`; SQLSTATE: `HY000`  
Message: `MYSQL_BIN_LOG::open_crash_safe_index_file` failed to open temporary index file.
  - Error number: `MY-010835`; Symbol: `ER_BINLOG_CANT_OPEN_TMP_INDEX`; SQLSTATE: `HY000`  
Message: %s failed to open the crash safe index file.
-

- 
- Error number: `MY-010836`; Symbol: `ER_BINLOG_CANT_COPY_INDEX_TO_TMP`; SQLSTATE: `HY000`  
Message: %s failed to copy index file to crash safe index file.
  - Error number: `MY-010837`; Symbol: `ER_BINLOG_CANT_CLOSE_TMP_INDEX`; SQLSTATE: `HY000`  
Message: %s failed to close the crash safe index file.
  - Error number: `MY-010838`; Symbol: `ER_BINLOG_CANT_MOVE_TMP_TO_INDEX`; SQLSTATE: `HY000`  
Message: %s failed to move crash safe index file to index file.
  - Error number: `MY-010839`; Symbol: `ER_BINLOG_PURGE_LOGS_CALLED_WITH_FILE_NOT_IN_INDEX`; SQLSTATE: `HY000`  
Message: MYSQL\_BIN\_LOG::purge\_logs was called with file %s not listed in the index.
  - Error number: `MY-010840`; Symbol: `ER_BINLOG_PURGE_LOGS_CANT_SYNC_INDEX_FILE`; SQLSTATE: `HY000`  
Message: MYSQL\_BIN\_LOG::purge\_logs failed to sync the index file.
  - Error number: `MY-010841`; Symbol: `ER_BINLOG_PURGE_LOGS_CANT_COPY_TO_REGISTER_FILE`; SQLSTATE: `HY000`  
Message: MYSQL\_BIN\_LOG::purge\_logs failed to copy %s to register file.
  - Error number: `MY-010842`; Symbol: `ER_BINLOG_PURGE_LOGS_CANT_FLUSH_REGISTER_FILE`; SQLSTATE: `HY000`  
Message: MYSQL\_BIN\_LOG::purge\_logs failed to flush register file.
  - Error number: `MY-010843`; Symbol: `ER_BINLOG_PURGE_LOGS_CANT_UPDATE_INDEX_FILE`; SQLSTATE: `HY000`  
Message: MYSQL\_BIN\_LOG::purge\_logs failed to update the index file
  - Error number: `MY-010844`; Symbol: `ER_BINLOG_PURGE_LOGS_FAILED_TO_PURGE_LOG`; SQLSTATE: `HY000`  
Message: MYSQL\_BIN\_LOG::purge\_logs failed to process registered files that would be purged.
  - Error number: `MY-010845`; Symbol: `ER_BINLOG_FAILED_TO_SET_PURGE_INDEX_FILE_NAME`; SQLSTATE: `HY000`  
Message: MYSQL\_BIN\_LOG::set\_purge\_index\_file\_name failed to set file name.
  - Error number: `MY-010846`; Symbol: `ER_BINLOG_FAILED_TO_OPEN_REGISTER_FILE`; SQLSTATE: `HY000`  
Message: MYSQL\_BIN\_LOG::open\_purge\_index\_file failed to open register file.
  - Error number: `MY-010847`; Symbol: `ER_BINLOG_FAILED_TO_REINIT_REGISTER_FILE`; SQLSTATE: `HY000`  
Message: MYSQL\_BIN\_LOG::purge\_index\_entry failed to reinit register file for read
  - Error number: `MY-010848`; Symbol: `ER_BINLOG_FAILED_TO_READ_REGISTER_FILE`; SQLSTATE: `HY000`  
Message: MYSQL\_BIN\_LOG::purge\_index\_entry error %d reading from register file.

- 
- Error number: [MY-010849](#); Symbol: [ER\\_CANT\\_STAT\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Failed to execute `mysql_file_stat` on file '%s'
  - Error number: [MY-010850](#); Symbol: [ER\\_BINLOG\\_CANT\\_DELETE\\_LOG\\_FILE\\_DOES\\_INDEX\\_MATCH\\_FILES](#); SQLSTATE: [HY000](#)  
Message: Failed to delete log file '%s'; consider examining correspondence of your binlog index file to the actual binlog files
  - Error number: [MY-010851](#); Symbol: [ER\\_BINLOG\\_CANT\\_DELETE\\_FILE\\_AND\\_READ\\_BINLOG\\_INDEX](#); SQLSTATE: [HY000](#)  
Message: Failed to delete file '%s' and read the binlog index file
  - Error number: [MY-010852](#); Symbol: [ER\\_BINLOG\\_FAILED\\_TO\\_DELETE\\_LOG\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Failed to delete log file '%s'
  - Error number: [MY-010853](#); Symbol: [ER\\_BINLOG\\_LOGGING\\_INCIDENT\\_TO\\_STOP\\_REPLICAS](#); SQLSTATE: [HY000](#)  
Message: %s An incident event has been written to the binary log which will stop the replicas.
  - Error number: [MY-010854](#); Symbol: [ER\\_BINLOG\\_CANT\\_FIND\\_LOG\\_IN\\_INDEX](#); SQLSTATE: [HY000](#)  
Message: `find_log_pos()` failed (error: %d)
  - Error number: [MY-010855](#); Symbol: [ER\\_BINLOG\\_RECOVERING\\_AFTER\\_CRASH\\_USING](#); SQLSTATE: [HY000](#)  
Message: Recovering after a crash using %s
  - Error number: [MY-010856](#); Symbol: [ER\\_BINLOG\\_CANT\\_OPEN\\_CRASHED\\_BINLOG](#); SQLSTATE: [HY000](#)  
Message: Failed to open the crashed binlog file when source server is recovering it.
  - Error number: [MY-010857](#); Symbol: [ER\\_BINLOG\\_CANT\\_TRIM\\_CRASHED\\_BINLOG](#); SQLSTATE: [HY000](#)  
Message: Failed to trim the crashed binlog file when source server is recovering it.
  - Error number: [MY-010858](#); Symbol: [ER\\_BINLOG\\_CRASHED\\_BINLOG\\_TRIMMED](#); SQLSTATE: [HY000](#)  
Message: Crashed binlog file %s size is %llu, but recovered up to %llu. Binlog trimmed to %llu bytes.
  - Error number: [MY-010859](#); Symbol: [ER\\_BINLOG\\_CANT\\_CLEAR\\_IN\\_USE\\_FLAG\\_FOR\\_CRASHED\\_BINLOG](#); SQLSTATE: [HY000](#)  
Message: Failed to clear `LOG_EVENT_BINLOG_IN_USE_F` for the crashed binlog file when source server is recovering it.
  - Error number: [MY-010860](#); Symbol: [ER\\_BINLOG\\_FAILED\\_TO\\_RUN\\_AFTER\\_SYNC\\_HOOK](#); SQLSTATE: [HY000](#)  
Message: Failed to run 'after\_sync' hooks
  - Error number: [MY-010861](#); Symbol: [ER\\_TURNING\\_LOGGING\\_OFF\\_FOR\\_THE\\_DURATION](#); SQLSTATE: [HY000](#)
-

---

Message: %s Hence turning logging off for the whole duration of the MySQL server process. To turn it on again: fix the cause, shutdown the MySQL server and restart it.

- Error number: [MY-010862](#); Symbol: [ER\\_BINLOG\\_FAILED\\_TO\\_RUN\\_AFTER\\_FLUSH\\_HOOK](#); SQLSTATE: [HY000](#)

Message: Failed to run 'after\_flush' hooks

- Error number: [MY-010864](#); Symbol: [ER\\_BINLOG\\_WARNING\\_SUPPRESSED](#); SQLSTATE: [HY000](#)

Message: The following warning was suppressed %d times during the last %d seconds in the error log

- Error number: [MY-010865](#); Symbol: [ER\\_NDB\\_LOG\\_ENTRY](#); SQLSTATE: [HY000](#)

Message: NDB: %s

- Error number: [MY-010866](#); Symbol: [ER\\_NDB\\_LOG\\_ENTRY\\_WITH\\_PREFIX](#); SQLSTATE: [HY000](#)

Message: NDB %s: %s

- Error number: [MY-010868](#); Symbol: [ER\\_INNOBDB\\_UNKNOWN\\_COLLATION](#); SQLSTATE: [HY000](#)

Message: Unknown collation #%lu.

- Error number: [MY-010869](#); Symbol: [ER\\_INNOBDB\\_INVALID\\_LOG\\_GROUP\\_HOME\\_DIR](#); SQLSTATE: [HY000](#)

Message: syntax error in innodb\_log\_group\_home\_dir

- Error number: [MY-010870](#); Symbol: [ER\\_INNOBDB\\_INVALID\\_INNOBDB\\_UNDO\\_DIRECTORY](#); SQLSTATE: [HY000](#)

Message: syntax error in innodb\_undo\_directory

- Error number: [MY-010871](#); Symbol: [ER\\_INNOBDB\\_ILLEGAL\\_COLON\\_IN\\_POOL](#); SQLSTATE: [HY000](#)

Message: InnoDB: innodb\_buffer\_pool\_filename cannot have colon (:) in the file name.

- Error number: [MY-010872](#); Symbol: [ER\\_INNOBDB\\_INVALID\\_PAGE\\_SIZE](#); SQLSTATE: [HY000](#)

Message: InnoDB: Invalid page size=%lu.

- Error number: [MY-010873](#); Symbol: [ER\\_INNOBDB\\_DIRTY\\_WATER\\_MARK\\_NOT\\_LOW](#); SQLSTATE: [HY000](#)

Message: InnoDB: innodb\_max\_dirty\_pages\_pct\_lwm cannot be set higher than innodb\_max\_dirty\_pages\_pct. Setting innodb\_max\_dirty\_pages\_pct\_lwm to %lf

- Error number: [MY-010874](#); Symbol: [ER\\_INNOBDB\\_IO\\_CAPACITY\\_EXCEEDS\\_MAX](#); SQLSTATE: [HY000](#)

Message: InnoDB: innodb\_io\_capacity cannot be set higher than innodb\_io\_capacity\_max. Setting innodb\_io\_capacity to %lu

- Error number: [MY-010875](#); Symbol: [ER\\_INNOBDB\\_FILES\\_SAME](#); SQLSTATE: [HY000](#)

Message: %s and %s file names seem to be the same.

- Error number: [MY-010876](#); Symbol: [ER\\_INNOBDB\\_UNREGISTERED\\_TRX\\_ACTIVE](#); SQLSTATE: [HY000](#)

Message: Transaction not registered for MySQL 2PC, but transaction is active



- 
- Error number: [MY-010877](#); Symbol: [ER\\_INNODB\\_CLOSING\\_CONNECTION\\_ROLLS\\_BACK](#); SQLSTATE: [HY000](#)  
  
Message: MySQL is closing a connection that has an active InnoDB transaction. %llu row modifications will roll back.
  - Error number: [MY-010878](#); Symbol: [ER\\_INNODB\\_TRX\\_XLATION\\_TABLE\\_OOM](#); SQLSTATE: [HY000](#)  
  
Message: InnoDB: fail to allocate memory for index translation table. Number of Index:%lu, array size:%lu
  - Error number: [MY-010879](#); Symbol: [ER\\_INNODB\\_CANT\\_FIND\\_INDEX\\_IN\\_INNODB\\_DD](#); SQLSTATE: [HY000](#)  
  
Message: Cannot find index %s in InnoDB index dictionary.
  - Error number: [MY-010880](#); Symbol: [ER\\_INNODB\\_INDEX\\_COLUMN\\_INFO\\_UNLIKE\\_MYSQLS](#); SQLSTATE: [HY000](#)  
  
Message: Found index %s whose column info does not match that of MySQL.
  - Error number: [MY-010882](#); Symbol: [ER\\_INNODB\\_CANT\\_BUILD\\_INDEX\\_XLATION\\_TABLE\\_FOR](#); SQLSTATE: [HY000](#)  
  
Message: Build InnoDB index translation table for Table %s failed
  - Error number: [MY-010883](#); Symbol: [ER\\_INNODB\\_PK\\_NOT\\_IN\\_MYSQL](#); SQLSTATE: [HY000](#)  
  
Message: Table %s has a primary key in InnoDB data dictionary, but not in MySQL!
  - Error number: [MY-010884](#); Symbol: [ER\\_INNODB\\_PK\\_ONLY\\_IN\\_MYSQL](#); SQLSTATE: [HY000](#)  
  
Message: Table %s has no primary key in InnoDB data dictionary, but has one in MySQL! If you created the table with a MySQL version < 3.23.54 and did not define a primary key, but defined a unique key with all non-NULL columns, then MySQL internally treats that key as the primary key. You can fix this error by dump + DROP + CREATE + reimport of the table.
  - Error number: [MY-010885](#); Symbol: [ER\\_INNODB\\_CLUSTERED\\_INDEX\\_PRIVATE](#); SQLSTATE: [HY000](#)  
  
Message: Table %s key\_used\_on\_scan is %lu even though there is no primary key inside InnoDB.
  - Error number: [MY-010887](#); Symbol: [ER\\_ERRMSG\\_REPLACEMENT\\_DODGY](#); SQLSTATE: [HY000](#)  
  
Message: Cannot replace error message (%s,%s,%s) "%s" with "%s"; wrong number or type of %% substitutions.
  - Error number: [MY-010888](#); Symbol: [ER\\_ERRMSG\\_REPLACEMENTS\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Table for error message replacements could not be found or read, or one or more replacements could not be applied.
  - Error number: [MY-010889](#); Symbol: [ER\\_NPIPE\\_CANT\\_CREATE](#); SQLSTATE: [HY000](#)  
  
Message: %s: %s
  - Error number: [MY-010890](#); Symbol: [ER\\_PARTITION\\_MOVE\\_CREATED\\_DUPLICATE\\_ROW\\_PLEASE\\_FIX](#); SQLSTATE: [HY000](#)  
  
Message: Table '%s': Delete from part %d failed with error %d. But it was already inserted into part %d, when moving the misplaced row! Please manually fix the duplicate row: %s
  - Error number: [MY-010891](#); Symbol: [ER\\_AUDIT\\_CANT\\_ABORT\\_COMMAND](#); SQLSTATE: [HY000](#)
-

---

Message: Command '%s' cannot be aborted. The trigger error was (%d) [%s]: %s

- Error number: [MY-010892](#); Symbol: [ER\\_AUDIT\\_CANT\\_ABORT\\_EVENT](#); SQLSTATE: [HY000](#)

Message: Event '%s' cannot be aborted. The trigger error was (%d) [%s]: %s

- Error number: [MY-010893](#); Symbol: [ER\\_AUDIT\\_WARNING](#); SQLSTATE: [HY000](#)

Message: %s. The trigger error was (%d) [%s]: %s

- Error number: [MY-010897](#); Symbol: [ER\\_RPL\\_REPLICA\\_INSECURE\\_CHANGE\\_SOURCE](#); SQLSTATE: [HY000](#)

Message: Storing MySQL user name or password information in the connection metadata repository is not secure and is therefore not recommended. Please consider using the USER and PASSWORD connection options for START REPLICA; see the 'START REPLICA Syntax' in the MySQL Manual for more information.

- Error number: [MY-010899](#); Symbol: [ER\\_RPL\\_REPLICA\\_INCORRECT\\_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Replica channel '%s' does not exist.

- Error number: [MY-010900](#); Symbol: [ER\\_FAILED\\_TO\\_FIND\\_DL\\_ENTRY](#); SQLSTATE: [HY000](#)

Message: Can't find symbol '%s' in library.

- Error number: [MY-010901](#); Symbol: [ER\\_FAILED\\_TO\\_OPEN\\_SHARED\\_LIBRARY](#); SQLSTATE: [HY000](#)

Message: Can't open shared library '%s' (errno: %d %s).

- Error number: [MY-010902](#); Symbol: [ER\\_THREAD\\_PRIORITY\\_IGNORED](#); SQLSTATE: [HY000](#)

Message: Thread priority attribute setting in Resource Group SQL shall be ignored due to unsupported platform or insufficient privilege.

- Error number: [MY-010903](#); Symbol: [ER\\_BINLOG\\_CACHE\\_SIZE\\_TOO\\_LARGE](#); SQLSTATE: [HY000](#)

Message: Option binlog\_cache\_size (%lu) is greater than max\_binlog\_cache\_size (%lu); setting binlog\_cache\_size equal to max\_binlog\_cache\_size.

- Error number: [MY-010904](#); Symbol: [ER\\_BINLOG\\_STMT\\_CACHE\\_SIZE\\_TOO\\_LARGE](#); SQLSTATE: [HY000](#)

Message: Option binlog\_stmt\_cache\_size (%lu) is greater than max\_binlog\_stmt\_cache\_size (%lu); setting binlog\_stmt\_cache\_size equal to max\_binlog\_stmt\_cache\_size.

- Error number: [MY-010905](#); Symbol: [ER\\_FAILED\\_TO\\_GENERATE\\_UNIQUE\\_LOGFILE](#); SQLSTATE: [HY000](#)

Message: Can't generate a unique log-filename %s.(1-999).

- Error number: [MY-010906](#); Symbol: [ER\\_FAILED\\_TO\\_READ\\_FILE](#); SQLSTATE: [HY000](#)

Message: Error reading file '%s' (errno: %d - %s)

- Error number: [MY-010907](#); Symbol: [ER\\_FAILED\\_TO\\_WRITE\\_TO\\_FILE](#); SQLSTATE: [HY000](#)

Message: Error writing file '%s' (errno: %d - %s)

- Error number: [MY-010908](#); Symbol: [ER\\_BINLOG\\_UNSAFE\\_MESSAGE\\_AND\\_STATEMENT](#); SQLSTATE: [HY000](#)

---

Message: %s Statement: %s

- Error number: [MY-010909](#); Symbol: [ER\\_FORCE\\_CLOSE\\_THREAD](#); SQLSTATE: [HY000](#)

Message: %s: Forcing close of thread %ld user: '%s'.

- Error number: [MY-010910](#); Symbol: [ER\\_SERVER\\_SHUTDOWN\\_COMPLETE](#); SQLSTATE: [HY000](#)

Message: %s: Shutdown complete (mysqld %s) %s.

- Error number: [MY-010911](#); Symbol: [ER\\_RPL\\_CANT\\_HAVE\\_SAME\\_BASENAME](#); SQLSTATE: [HY000](#)

Message: Cannot have same base name '%s' for both binary and relay logs. Please check %s (default '%s' if --log-bin option is not used, default '%s' if --log-bin option is used without argument) and %s (default '%s') options to ensure they do not conflict.

- Error number: [MY-010912](#); Symbol: [ER\\_RPL\\_GTID\\_MODE\\_REQUIRES\\_ENFORCE\\_GTID\\_CONSISTENCY\\_ON](#); SQLSTATE: [HY000](#)

Message: GTID\_MODE = ON requires ENFORCE\_GTID\_CONSISTENCY = ON.

- Error number: [MY-010913](#); Symbol: [ER\\_WARN\\_NO\\_SERVERID\\_SPECIFIED](#); SQLSTATE: [HY000](#)

Message: You have not provided a mandatory server-id. Servers in a replication topology must have unique server-ids. Please refer to the proper server start-up parameters documentation.

- Error number: [MY-010914](#); Symbol: [ER\\_ABORTING\\_USER\\_CONNECTION](#); SQLSTATE: [HY000](#)

Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s).

- Error number: [MY-010915](#); Symbol: [ER\\_SQL\\_MODE\\_MERGED\\_WITH\\_STRICT\\_MODE](#); SQLSTATE: [HY000](#)

Message: 'NO\_ZERO\_DATE', 'NO\_ZERO\_IN\_DATE' and 'ERROR\_FOR\_DIVISION\_BY\_ZERO' sql modes should be used with strict mode. They will be merged with strict mode in a future release.

- Error number: [MY-010916](#); Symbol: [ER\\_GTID\\_PURGED\\_WAS\\_UPDATED](#); SQLSTATE: [HY000](#)

Message: @@GLOBAL.GTID\_PURGED was changed from '%s' to '%s'.

- Error number: [MY-010917](#); Symbol: [ER\\_GTID\\_EXECUTED\\_WAS\\_UPDATED](#); SQLSTATE: [HY000](#)

Message: @@GLOBAL.GTID\_EXECUTED was changed from '%s' to '%s'.

- Error number: [MY-010918](#); Symbol: [ER\\_DEPRECATED\\_MSG\\_WITH\\_REPLACEMENT](#); SQLSTATE: [HY000](#)

Message: '%s' is deprecated and will be removed in a future release. Please use %s instead.

- Error number: [MY-010919](#); Symbol: [ER\\_TRG\\_CREATION\\_CTX\\_NOT\\_SET](#); SQLSTATE: [HY000](#)

Message: Triggers for table `%s`.`%s` have no creation context

- Error number: [MY-010920](#); Symbol: [ER\\_FILE\\_HAS\\_OLD\\_FORMAT](#); SQLSTATE: [HY000](#)

Message: '%s' has an old format, you should re-create the '%s' object(s)

- Error number: [MY-010921](#); Symbol: [ER\\_VIEW\\_CREATION\\_CTX\\_NOT\\_SET](#); SQLSTATE: [HY000](#)

Message: View `%s`.`%s` has no creation context

- Error number: [MY-010923](#); Symbol: [ER\\_TABLE\\_UPGRADE\\_REQUIRED](#); SQLSTATE: [HY000](#)

---

Message: Table upgrade required. Please do "REPAIR TABLE `%'s`" or dump/reload to fix it!

- Error number: [MY-010924](#); Symbol: [ER\\_GET\\_ERRNO\\_FROM\\_STORAGE\\_ENGINE](#); SQLSTATE: [HY000](#)

Message: Got error %d - '%s' from storage engine.

- Error number: [MY-010925](#); Symbol: [ER\\_ACCESS\\_DENIED\\_ERROR\\_WITHOUT\\_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Access denied for user '%s'@'%s'

- Error number: [MY-010926](#); Symbol: [ER\\_ACCESS\\_DENIED\\_ERROR\\_WITH\\_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Access denied for user '%s'@'%s' (using password: %s)

- Error number: [MY-010927](#); Symbol: [ER\\_ACCESS\\_DENIED\\_FOR\\_USER\\_ACCOUNT\\_LOCKED](#); SQLSTATE: [HY000](#)

Message: Access denied for user '%s'@'%s'. Account is locked.

- Error number: [MY-010929](#); Symbol: [ER\\_SYSTEM\\_TABLES\\_NOT\\_SUPPORTED\\_BY\\_STORAGE\\_ENGINE](#); SQLSTATE: [HY000](#)

Message: Storage engine '%s' does not support system tables. [%s.%s].

- Error number: [MY-010931](#); Symbol: [ER\\_SERVER\\_STARTUP\\_MSG](#); SQLSTATE: [HY000](#)

Message: %s: ready for connections. Version: '%s' socket: '%s' port: %d %s.

- Error number: [MY-010932](#); Symbol: [ER\\_FAILED\\_TO\\_FIND\\_LOCALE\\_NAME](#); SQLSTATE: [HY000](#)

Message: Unknown locale: '%s'.

- Error number: [MY-010933](#); Symbol: [ER\\_FAILED\\_TO\\_FIND\\_COLLATION\\_NAME](#); SQLSTATE: [HY000](#)

Message: Unknown collation: '%s'.

- Error number: [MY-010934](#); Symbol: [ER\\_SERVER\\_OUT\\_OF\\_RESOURCES](#); SQLSTATE: [HY000](#)

Message: Out of memory; check if mysqld or some other process uses all available memory; if not, you may have to use 'ulimit' to allow mysqld to use more memory or you can add more swap space

- Error number: [MY-010935](#); Symbol: [ER\\_SERVER\\_OUTOFMEMORY](#); SQLSTATE: [HY000](#)

Message: Out of memory; restart server and try again (needed %d bytes)

- Error number: [MY-010936](#); Symbol: [ER\\_INVALID\\_COLLATION\\_FOR\\_CHARSET](#); SQLSTATE: [HY000](#)

Message: COLLATION '%s' is not valid for CHARACTER SET '%s'

- Error number: [MY-010937](#); Symbol: [ER\\_CANT\\_START\\_ERROR\\_LOG\\_SERVICE](#); SQLSTATE: [HY000](#)

Message: Failed to set %s at or around "%s" -- service is valid, but can not be initialized; please check its configuration and make sure it can read its input(s) and write to its output(s).

- Error number: [MY-010938](#); Symbol: [ER\\_CREATING\\_NEW\\_UUID\\_FIRST\\_START](#); SQLSTATE: [HY000](#)

Message: Generating a new UUID: %s.

- 
- Error number: `MY-010939`; Symbol: `ER_FAILED_TO_GET_ABSOLUTE_PATH`; SQLSTATE: `HY000`  
Message: Failed to get absolute path of program executable %s
  - Error number: `MY-010940`; Symbol: `ER_PERFSCHEMA_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP`; SQLSTATE: `HY000`  
Message: Failed to bootstrap performance schema components infrastructure.
  - Error number: `MY-010941`; Symbol: `ER_PERFSCHEMA_COMPONENTS_INFRASTRUCTURE_SHUTDOWN`; SQLSTATE: `HY000`  
Message: Failed to deinit performance schema components infrastructure.
  - Error number: `MY-010942`; Symbol: `ER_DUP_FD_OPEN_FAILED`; SQLSTATE: `HY000`  
Message: Could not open duplicate fd for %s: %s.
  - Error number: `MY-010943`; Symbol: `ER_SYSTEM_VIEW_INIT_FAILED`; SQLSTATE: `HY000`  
Message: System views initialization failed.
  - Error number: `MY-010944`; Symbol: `ER_RESOURCE_GROUP_POST_INIT_FAILED`; SQLSTATE: `HY000`  
Message: Resource group post initialization failed.
  - Error number: `MY-010945`; Symbol: `ER_RESOURCE_GROUP_SUBSYSTEM_INIT_FAILED`; SQLSTATE: `HY000`  
Message: Resource Group subsystem initialization failed.
  - Error number: `MY-010946`; Symbol: `ER_FAILED_START_MYSQLD_DAEMON`; SQLSTATE: `HY000`  
Message: Failed to start mysqld daemon. Check mysqld error log.
  - Error number: `MY-010947`; Symbol: `ER_CANNOT_CHANGE_TO_ROOT_DIR`; SQLSTATE: `HY000`  
Message: Cannot change to root directory: %s.
  - Error number: `MY-010948`; Symbol: `ER_PERSISTENT_PRIVILEGES_BOOTSTRAP`; SQLSTATE: `HY000`  
Message: Failed to bootstrap persistent privileges.
  - Error number: `MY-010949`; Symbol: `ER_BASEDIR_SET_TO`; SQLSTATE: `HY000`  
Message: Basedir set to %s.
  - Error number: `MY-010950`; Symbol: `ER_RPL_FILTER_ADD_WILD_DO_TABLE_FAILED`; SQLSTATE: `HY000`  
Message: Could not add wild do table rule '%s'!
  - Error number: `MY-010951`; Symbol: `ER_RPL_FILTER_ADD_WILD_IGNORE_TABLE_FAILED`; SQLSTATE: `HY000`  
Message: Could not add wild ignore table rule '%s'!
  - Error number: `MY-010952`; Symbol: `ER_PRIVILEGE_SYSTEM_INIT_FAILED`; SQLSTATE: `HY000`  
Message: The privilege system failed to initialize correctly. For complete instructions on how to upgrade MySQL to a new version please see the 'Upgrading MySQL' section from the MySQL manual.

- 
- Error number: [MY-010953](#); Symbol: [ER\\_CANNOT\\_SET\\_LOG\\_ERROR\\_SERVICES](#); SQLSTATE: [HY000](#)  
Message: Cannot set services "%s" requested in --log-error-services, using defaults.
  - Error number: [MY-010954](#); Symbol: [ER\\_PERFSCHEMA\\_TABLES\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Performance schema tables initialization failed.
  - Error number: [MY-010958](#); Symbol: [ER\\_BINLOG\\_FILE\\_OPEN\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: %s.
  - Error number: [MY-010959](#); Symbol: [ER\\_BINLOG\\_EVENT\\_WRITE\\_TO\\_STMT\\_CACHE\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to write an incident event into stmt\_cache.
  - Error number: [MY-010960](#); Symbol: [ER\\_REPLICA\\_RELAY\\_LOG\\_TRUNCATE\\_INFO](#); SQLSTATE: [HY000](#)  
Message: Relaylog file %s size was %llu, but was truncated at %llu.
  - Error number: [MY-010961](#); Symbol: [ER\\_REPLICA\\_RELAY\\_LOG\\_PURGE\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Unable to purge relay log files. %s:%s.
  - Error number: [MY-010962](#); Symbol: [ER\\_RPL\\_REPLICA\\_FILTER\\_CREATE\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Replica: failed in creating filter for channel '%s'.
  - Error number: [MY-010963](#); Symbol: [ER\\_RPL\\_REPLICA\\_GLOBAL\\_FILTERS\\_COPY\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Replica: failed in copying the global filters to its own per-channel filters on configuration for channel '%s'.
  - Error number: [MY-010964](#); Symbol: [ER\\_RPL\\_REPLICA\\_RESET\\_FILTER\\_OPTIONS](#); SQLSTATE: [HY000](#)  
Message: There are per-channel replication filter(s) configured for channel '%s' which does not exist. The filter(s) have been discarded.
  - Error number: [MY-010965](#); Symbol: [ER\\_MISSING\\_GRANT\\_SYSTEM\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: The system table mysql.global\_grants is missing. Please perform the MySQL upgrade procedure.
  - Error number: [MY-010966](#); Symbol: [ER\\_MISSING\\_ACL\\_SYSTEM\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: ACL table mysql.%.\*s missing. Some operations may fail.
  - Error number: [MY-010967](#); Symbol: [ER\\_ANONYMOUS\\_AUTH\\_ID\\_NOT\\_ALLOWED\\_IN\\_MANDATORY\\_ROLES](#); SQLSTATE: [HY000](#)  
Message: Can't set mandatory\_role %s@%s: Anonymous authorization IDs are not allowed as roles.
  - Error number: [MY-010968](#); Symbol: [ER\\_UNKNOWN\\_AUTH\\_ID\\_IN\\_MANDATORY\\_ROLE](#); SQLSTATE: [HY000](#)  
Message: Can't set mandatory\_role: There's no such authorization ID %s@%s.

- 
- Error number: `MY-010969`; Symbol: `ER_WRITE_ROW_TO_PARTITION_FAILED`; SQLSTATE: `HY000`  
Message: Table '%s' failed to move/insert a row from part %d into part %d: %s.
  - Error number: `MY-010970`; Symbol: `ER_RESOURCE_GROUP_METADATA_UPDATE_SKIPPED`; SQLSTATE: `HY000`  
Message: Skipped updating resource group metadata in InnoDB read only mode.
  - Error number: `MY-010971`; Symbol: `ER_FAILED_TO_PERSIST_RESOURCE_GROUP_METADATA`; SQLSTATE: `HY000`  
Message: Failed to persist resource group %s to Data Dictionary.
  - Error number: `MY-010972`; Symbol: `ER_FAILED_TO_DESERIALIZE_RESOURCE_GROUP`; SQLSTATE: `HY000`  
Message: Failed to deserialize resource group %s.
  - Error number: `MY-010973`; Symbol: `ER_FAILED_TO_UPDATE_RESOURCE_GROUP`; SQLSTATE: `HY000`  
Message: Update of resource group %s failed.
  - Error number: `MY-010974`; Symbol: `ER_RESOURCE_GROUP_VALIDATION_FAILED`; SQLSTATE: `HY000`  
Message: Validation of resource group %s failed. Resource group is disabled.
  - Error number: `MY-010975`; Symbol: `ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP`; SQLSTATE: `HY000`  
Message: Unable to allocate memory for Resource Group %s.
  - Error number: `MY-010976`; Symbol: `ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP_HASH`; SQLSTATE: `HY000`  
Message: Failed to allocate memory for resource group hash.
  - Error number: `MY-010977`; Symbol: `ER_FAILED_TO_ADD_RESOURCE_GROUP_TO_MAP`; SQLSTATE: `HY000`  
Message: Failed to add resource group %s to resource group map.
  - Error number: `MY-010978`; Symbol: `ER_RESOURCE_GROUP_IS_DISABLED`; SQLSTATE: `HY000`  
Message: Resource group feature is disabled. (Server is compiled with `DISABLE_PSI_THREAD`).
  - Error number: `MY-010979`; Symbol: `ER_FAILED_TO_APPLY_RESOURCE_GROUP_CONTROLLER`; SQLSTATE: `HY000`  
Message: Unable to apply resource group controller %s.
  - Error number: `MY-010980`; Symbol: `ER_FAILED_TO_ACQUIRE_LOCK_ON_RESOURCE_GROUP`; SQLSTATE: `HY000`  
Message: Unable to acquire lock on the resource group %s. Hint to switch resource group shall be ignored.
  - Error number: `MY-010981`; Symbol: `ER_PFS_NOTIFICATION_FUNCTION_REGISTER_FAILED`; SQLSTATE: `HY000`  
Message: PFS %s notification function registration failed.

- 
- Error number: `MY-010982`; Symbol: `ER_RES_GRP_SET_THR_AFFINITY_FAILED`; SQLSTATE: `HY000`  
Message: Unable to bind thread id %llu to cpu id %u (error code %d - %s).
  - Error number: `MY-010983`; Symbol: `ER_RES_GRP_SET_THR_AFFINITY_TO_CPUS_FAILED`; SQLSTATE: `HY000`  
Message: Unable to bind thread id %llu to cpu ids (error code %d - %s).
  - Error number: `MY-010984`; Symbol: `ER_RES_GRP_THD_UNBIND_FROM_CPU_FAILED`; SQLSTATE: `HY000`  
Message: Unbind thread id %llu failed. (error code %d - %s).
  - Error number: `MY-010985`; Symbol: `ER_RES_GRP_SET_THREAD_PRIORITY_FAILED`; SQLSTATE: `HY000`  
Message: Setting thread priority %d to thread id %llu failed. (error code %d - %s).
  - Error number: `MY-010986`; Symbol: `ER_RES_GRP_FAILED_TO_DETERMINE_NICE_CAPABILITY`; SQLSTATE: `HY000`  
Message: Unable to determine CAP\_SYS\_NICE capability.
  - Error number: `MY-010987`; Symbol: `ER_RES_GRP_FAILED_TO_GET_THREAD_HANDLE`; SQLSTATE: `HY000`  
Message: %s failed: Failed to get handle for thread %llu.
  - Error number: `MY-010988`; Symbol: `ER_RES_GRP_GET_THREAD_PRIO_NOT_SUPPORTED`; SQLSTATE: `HY000`  
Message: Retrieval of thread priority unsupported on %s.
  - Error number: `MY-010989`; Symbol: `ER_RES_GRP_FAILED_DETERMINE_CPU_COUNT`; SQLSTATE: `HY000`  
Message: Unable to determine the number of CPUs.
  - Error number: `MY-010990`; Symbol: `ER_RES_GRP_FEATURE_NOT_AVAILABLE`; SQLSTATE: `HY000`  
Message: Resource group feature shall not be available. Incompatible thread handling option.
  - Error number: `MY-010991`; Symbol: `ER_RES_GRP_INVALID_THREAD_PRIORITY`; SQLSTATE: `HY000`  
Message: Invalid thread priority %d for a %s resource group. Allowed range is [%d, %d].
  - Error number: `MY-010992`; Symbol: `ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_CPUID_FAILED`; SQLSTATE: `HY000`  
Message: bind\_to\_cpu failed: processor\_bind for cpuid %u failed (error code %d - %s).
  - Error number: `MY-010993`; Symbol: `ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_THREAD_FAILED`; SQLSTATE: `HY000`  
Message: bind\_to\_cpu failed: processor\_bind for thread %llu with cpu id %u (error code %d - %s).
  - Error number: `MY-010994`; Symbol: `ER_RES_GRP_SOLARIS_PROCESSOR_AFFINITY_FAILED`; SQLSTATE: `HY000`  
Message: %s failed: processor\_affinity failed (error code %d - %s).



- 
- Error number: `MY-010995`; Symbol: `ER_DD_UPGRADE_RENAME_IDX_STATS_FILE_FAILED`; SQLSTATE: `HY000`  
  
Message: Error in renaming `mysql_index_stats.ibd`.
  - Error number: `MY-010996`; Symbol: `ER_DD_UPGRADE_DD_OPEN_FAILED`; SQLSTATE: `HY000`  
  
Message: Error in opening data directory %s.
  - Error number: `MY-010997`; Symbol: `ER_DD_UPGRADE_FAILED_TO_FETCH_TABLESPACES`; SQLSTATE: `HY000`  
  
Message: Error in fetching list of tablespaces.
  - Error number: `MY-010998`; Symbol: `ER_DD_UPGRADE_FAILED_TO_ACQUIRE_TABLESPACE`; SQLSTATE: `HY000`  
  
Message: Error in acquiring Tablespace for SDI insertion %s.
  - Error number: `MY-010999`; Symbol: `ER_DD_UPGRADE_FAILED_TO_RESOLVE_TABLESPACE_ENGINE`; SQLSTATE: `HY000`  
  
Message: Error in resolving Engine name for tablespace %s with engine %s.
  - Error number: `MY-011000`; Symbol: `ER_FAILED_TO_CREATE_SDI_FOR_TABLESPACE`; SQLSTATE: `HY000`  
  
Message: Error in creating SDI for %s tablespace.
  - Error number: `MY-011001`; Symbol: `ER_FAILED_TO_STORE_SDI_FOR_TABLESPACE`; SQLSTATE: `HY000`  
  
Message: Error in storing SDI for %s tablespace.
  - Error number: `MY-011002`; Symbol: `ER_DD_UPGRADE_FAILED_TO_FETCH_TABLES`; SQLSTATE: `HY000`  
  
Message: Error in fetching list of tables.
  - Error number: `MY-011003`; Symbol: `ER_DD_UPGRADE_DD_POPULATED`; SQLSTATE: `HY000`  
  
Message: Finished populating Data Dictionary tables with data.
  - Error number: `MY-011004`; Symbol: `ER_DD_UPGRADE_INFO_FILE_OPEN_FAILED`; SQLSTATE: `HY000`  
  
Message: Could not open the upgrade info file '%s' in the MySQL servers datadir, errno: %d.
  - Error number: `MY-011005`; Symbol: `ER_DD_UPGRADE_INFO_FILE_CLOSE_FAILED`; SQLSTATE: `HY000`  
  
Message: Could not close the upgrade info file '%s' in the MySQL servers datadir, errno: %d.
  - Error number: `MY-011006`; Symbol: `ER_DD_UPGRADE_TABLESPACE_MIGRATION_FAILED`; SQLSTATE: `HY000`  
  
Message: Got error %d from SE while migrating tablespaces.
  - Error number: `MY-011007`; Symbol: `ER_DD_UPGRADE_FAILED_TO_CREATE_TABLE_STATS`; SQLSTATE: `HY000`  
  
Message: Error in creating TABLE statistics entry. Fix statistics data by using ANALYZE command.
-

- 
- Error number: MY-011008; Symbol: ER\_DD\_UPGRADE\_TABLE\_STATS\_MIGRATE\_COMPLETED; SQLSTATE: HY000  
Message: Finished migrating TABLE statistics data.
  - Error number: MY-011009; Symbol: ER\_DD\_UPGRADE\_FAILED\_TO\_CREATE\_INDEX\_STATS; SQLSTATE: HY000  
Message: Error in creating Index statistics entry. Fix statistics data by using ANALYZE command.
  - Error number: MY-011010; Symbol: ER\_DD\_UPGRADE\_INDEX\_STATS\_MIGRATE\_COMPLETED; SQLSTATE: HY000  
Message: Finished migrating INDEX statistics data.
  - Error number: MY-011011; Symbol: ER\_DD\_UPGRADE\_FAILED\_FIND\_VALID\_DATA\_DIR; SQLSTATE: HY000  
Message: Failed to find valid data directory.
  - Error number: MY-011012; Symbol: ER\_DD\_UPGRADE\_START; SQLSTATE: HY000  
Message: Starting upgrade of data directory.
  - Error number: MY-011013; Symbol: ER\_DD\_UPGRADE\_FAILED\_INIT\_DD\_SE; SQLSTATE: HY000  
Message: Failed to initialize DD Storage Engine.
  - Error number: MY-011014; Symbol: ER\_DD\_UPGRADE\_FOUND\_PARTIALLY\_UPGRADED\_DD\_ABORT; SQLSTATE: HY000  
Message: Found partially upgraded DD. Aborting upgrade and deleting all DD tables. Start the upgrade process again.
  - Error number: MY-011015; Symbol: ER\_DD\_UPGRADE\_FOUND\_PARTIALLY\_UPGRADED\_DD\_CONTINUE; SQLSTATE: HY000  
Message: Found partially upgraded DD. Upgrade will continue and start the server.
  - Error number: MY-011016; Symbol: ER\_DD\_UPGRADE\_SE\_LOGS\_FAILED; SQLSTATE: HY000  
Message: Error in upgrading engine logs.
  - Error number: MY-011017; Symbol: ER\_DD\_UPGRADE\_SDI\_INFO\_UPDATE\_FAILED; SQLSTATE: HY000  
Message: Error in updating SDI information.
  - Error number: MY-011018; Symbol: ER\_SKIP\_UPDATING\_METADATA\_IN\_SE\_RO\_MODE; SQLSTATE: HY000  
Message: Skip updating %s metadata in InnoDB read-only mode.
  - Error number: MY-011019; Symbol: ER\_CREATED\_SYSTEM\_WITH\_VERSION; SQLSTATE: HY000  
Message: Created system views with I\_S version %d.
  - Error number: MY-011020; Symbol: ER\_UNKNOWN\_ERROR\_DETECTED\_IN\_SE; SQLSTATE: HY000  
Message: Unknown error detected %d in handler.
  - Error number: MY-011021; Symbol: ER\_READ\_LOG\_EVENT\_FAILED; SQLSTATE: HY000  
Message: Error in Log\_event::read\_log\_event(): '%s', data\_len: %lu, event\_type: %d.

- 
- Error number: `MY-011022`; Symbol: `ER_ROW_DATA_TOO_BIG_TO_WRITE_IN_BINLOG`; SQLSTATE: `HY000`  
Message: The row data is greater than 4GB, which is too big to write to the binary log.
  - Error number: `MY-011023`; Symbol: `ER_FAILED_TO_CONSTRUCT_DROP_EVENT_QUERY`; SQLSTATE: `HY000`  
Message: Unable to construct DROP EVENT SQL query string.
  - Error number: `MY-011024`; Symbol: `ER_FAILED_TO_BINLOG_DROP_EVENT`; SQLSTATE: `HY000`  
Message: Unable to binlog drop event %s.%s.
  - Error number: `MY-011025`; Symbol: `ER_FAILED_TO_START_REPLICA_THREAD`; SQLSTATE: `HY000`  
Message: Failed to start replica threads for channel '%s'.
  - Error number: `MY-011026`; Symbol: `ER_RPL_IO_THREAD_KILLED`; SQLSTATE: `HY000`  
Message: %s%s.
  - Error number: `MY-011027`; Symbol: `ER_REPLICA_RECONNECT_FAILED`; SQLSTATE: `HY000`  
Message: Failed registering on source, reconnecting to try again, log '%s' at position %s. %s.
  - Error number: `MY-011028`; Symbol: `ER_REPLICA_KILLED_AFTER_RECONNECT`; SQLSTATE: `HY000`  
Message: Replica I/O thread killed during or after reconnect.
  - Error number: `MY-011029`; Symbol: `ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS`; SQLSTATE: `HY000`  
Message: Some of the channels are not created/initialized properly. Check for additional messages above. You will not be able to start replication on those channels until the issue is resolved and the server restarted.
  - Error number: `MY-011030`; Symbol: `ER_FAILED_TO_ADD_RPL_FILTER`; SQLSTATE: `HY000`  
Message: Failed to add a replication filter into filter map for channel '%s'.
  - Error number: `MY-011031`; Symbol: `ER_PER_CHANNEL_RPL_FILTER_CONF_FOR_GRP_RPL`; SQLSTATE: `HY000`  
Message: There are per-channel replication filter(s) configured for group replication channel '%s' which is disallowed. The filter(s) have been discarded.
  - Error number: `MY-011032`; Symbol: `ER_RPL_FILTERS_NOT_ATTACHED_TO_CHANNEL`; SQLSTATE: `HY000`  
Message: There are per-channel replication filter(s) configured for channel '%s' which does not exist. The filter(s) have been discarded.
  - Error number: `MY-011033`; Symbol: `ER_FAILED_TO_BUILD_DO_AND_IGNORE_TABLE_HASHES`; SQLSTATE: `HY000`  
Message: An error occurred while building do\_table and ignore\_table rules to hashes for per-channel filter.
  - Error number: `MY-011034`; Symbol: `ER_CLONE_PLUGIN_NOT_LOADED_TRACE`; SQLSTATE: `HY000`
-

---

Message: Clone plugin cannot be loaded.

- Error number: [MY-011035](#); Symbol: [ER\\_CLONE\\_HANDLER\\_EXIST\\_TRACE](#); SQLSTATE: [HY000](#)

Message: Clone Handler exists.

- Error number: [MY-011036](#); Symbol: [ER\\_CLONE\\_CREATE\\_HANDLER\\_FAIL\\_TRACE](#); SQLSTATE: [HY000](#)

Message: Could not create Clone Handler.

- Error number: [MY-011037](#); Symbol: [ER\\_CYCLE\\_TIMER\\_IS\\_NOT\\_AVAILABLE](#); SQLSTATE: [HY000](#)

Message: The CYCLE timer is not available. WAIT events in the performance\_schema will not be timed.

- Error number: [MY-011038](#); Symbol: [ER\\_NANOSECOND\\_TIMER\\_IS\\_NOT\\_AVAILABLE](#); SQLSTATE: [HY000](#)

Message: The NANOSECOND timer is not available. IDLE/STAGE/STATEMENT/TRANSACTION events in the performance\_schema will not be timed.

- Error number: [MY-011039](#); Symbol: [ER\\_MICROSECOND\\_TIMER\\_IS\\_NOT\\_AVAILABLE](#); SQLSTATE: [HY000](#)

Message: The MICROSECOND timer is not available. IDLE/STAGE/STATEMENT/TRANSACTION events in the performance\_schema will not be timed.

- Error number: [MY-011040](#); Symbol: [ER\\_PFS\\_MALLOC\\_ARRAY\\_OVERFLOW](#); SQLSTATE: [HY000](#)

Message: Failed to allocate memory for %zu chunks each of size %zu for buffer '%s' due to overflow.

- Error number: [MY-011041](#); Symbol: [ER\\_PFS\\_MALLOC\\_ARRAY\\_OOM](#); SQLSTATE: [HY000](#)

Message: Failed to allocate %zu bytes for buffer '%s' due to out-of-memory.

- Error number: [MY-011042](#); Symbol: [ER\\_INNOQB\\_FAILED\\_TO\\_FIND\\_IDX\\_WITH\\_KEY\\_NO](#); SQLSTATE: [HY000](#)

Message: InnoDB could not find index %s key no %u for table %s through its index translation table.

- Error number: [MY-011043](#); Symbol: [ER\\_INNOQB\\_FAILED\\_TO\\_FIND\\_IDX](#); SQLSTATE: [HY000](#)

Message: Cannot find index %s in InnoDB index translation table.

- Error number: [MY-011044](#); Symbol: [ER\\_INNOQB\\_FAILED\\_TO\\_FIND\\_IDX\\_FROM\\_DICT\\_CACHE](#); SQLSTATE: [HY000](#)

Message: InnoDB could not find key no %u with name %s from dict cache for table %s.

- Error number: [MY-011045](#); Symbol: [ER\\_INNOQB\\_ACTIVE\\_INDEX\\_CHANGE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: InnoDB: change\_active\_index(%u) failed.

- Error number: [MY-011046](#); Symbol: [ER\\_INNOQB\\_DIFF\\_IN\\_REF\\_LEN](#); SQLSTATE: [HY000](#)

Message: Stored ref len is %lu, but table ref len is %lu.

- 
- Error number: [MY-011047](#); Symbol: [ER\\_WRONG\\_TYPE\\_FOR\\_COLUMN\\_PREFIX\\_IDX\\_FLD](#); SQLSTATE: [HY000](#)  
 Message: MySQL is trying to create a column prefix index field, on an inappropriate data type. Table name %s, column name %s.
  - Error number: [MY-011048](#); Symbol: [ER\\_INNOODB\\_CANNOT\\_CREATE\\_TABLE](#); SQLSTATE: [HY000](#)  
 Message: Cannot create table %s.
  - Error number: [MY-011049](#); Symbol: [ER\\_INNOODB\\_INTERNAL\\_INDEX](#); SQLSTATE: [HY000](#)  
 Message: Found index %s in InnoDB index list but not its MySQL index number. It could be an InnoDB internal index.
  - Error number: [MY-011050](#); Symbol: [ER\\_INNOODB\\_IDX\\_CNT\\_MORE\\_THAN\\_DEFINED\\_IN\\_MYSQL](#); SQLSTATE: [HY000](#)  
 Message: InnoDB: Table %s contains %lu indexes inside InnoDB, which is different from the number of indexes %u defined in MySQL.
  - Error number: [MY-011051](#); Symbol: [ER\\_INNOODB\\_IDX\\_CNT\\_FEWER\\_THAN\\_DEFINED\\_IN\\_MYSQL](#); SQLSTATE: [HY000](#)  
 Message: Table %s contains fewer indexes inside InnoDB than are defined in the MySQL. Have you mixed up with data dictionary from different installation?
  - Error number: [MY-011052](#); Symbol: [ER\\_INNOODB\\_IDX\\_COLUMN\\_CNT\\_DIFF](#); SQLSTATE: [HY000](#)  
 Message: Index %s of %s has %lu columns unique inside InnoDB, but MySQL is asking statistics for %lu columns. Have you mixed data dictionary from different installation?
  - Error number: [MY-011053](#); Symbol: [ER\\_INNOODB\\_USE\\_MONITOR\\_GROUP\\_NAME](#); SQLSTATE: [HY000](#)  
 Message: Monitor counter '%s' cannot be turned on/off individually. Please use its module name to turn on/off the counters in the module as a group.
  - Error number: [MY-011054](#); Symbol: [ER\\_INNOODB\\_MONITOR\\_DEFAULT\\_VALUE\\_NOT\\_DEFINED](#); SQLSTATE: [HY000](#)  
 Message: Default value is not defined for this set option. Please specify correct counter or module name.
  - Error number: [MY-011055](#); Symbol: [ER\\_INNOODB\\_MONITOR\\_IS\\_ENABLED](#); SQLSTATE: [HY000](#)  
 Message: InnoDB: Monitor %s is already enabled.
  - Error number: [MY-011056](#); Symbol: [ER\\_INNOODB\\_INVALID\\_MONITOR\\_COUNTER\\_NAME](#); SQLSTATE: [HY000](#)  
 Message: Invalid monitor counter : %s.
  - Error number: [MY-011057](#); Symbol: [ER\\_WIN\\_LOAD\\_LIBRARY\\_FAILED](#); SQLSTATE: [HY000](#)  
 Message: LoadLibrary("%s") failed: GetLastError returns %lu.
  - Error number: [MY-011058](#); Symbol: [ER\\_PARTITION\\_HANDLER\\_ADMIN\\_MSG](#); SQLSTATE: [HY000](#)  
 Message: %s.
  - Error number: [MY-011059](#); Symbol: [ER\\_RPL\\_AM\\_INIT\\_INFO\\_MSG](#); SQLSTATE: [HY000](#)  
 Message: %s.
-

- 
- Error number: [MY-011060](#); Symbol: [ER\\_DD\\_UPGRADE\\_TABLE\\_INTACT\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: %s.
  - Error number: [MY-011061](#); Symbol: [ER\\_SERVER\\_INIT\\_COMPILED\\_IN\\_COMMANDS](#); SQLSTATE: [HY000](#)  
Message: %s.
  - Error number: [MY-011062](#); Symbol: [ER\\_MYISAM\\_CHECK\\_METHOD\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: %s.
  - Error number: [MY-011063](#); Symbol: [ER\\_MYISAM\\_CRASHED\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: %s.
  - Error number: [MY-011064](#); Symbol: [ER\\_WAITPID\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Unable to wait for process %lld.
  - Error number: [MY-011065](#); Symbol: [ER\\_FAILED\\_TO\\_FIND\\_MYSQLD\\_STATUS](#); SQLSTATE: [HY000](#)  
Message: Unable to determine if daemon is running: %s (rc=%d).
  - Error number: [MY-011066](#); Symbol: [ER\\_INNODB\\_ERROR\\_LOGGER\\_MSG](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-011067](#); Symbol: [ER\\_INNODB\\_ERROR\\_LOGGER\\_FATAL\\_MSG](#); SQLSTATE: [HY000](#)  
Message: [FATAL] InnoDB: %s
  - Error number: [MY-011068](#); Symbol: [ER\\_DEPRECATED\\_SYNTAX\\_WITH\\_REPLACEMENT](#); SQLSTATE: [HY000](#)  
Message: The syntax '%s' is deprecated and will be removed in a future release. Please use %s instead.
  - Error number: [MY-011069](#); Symbol: [ER\\_DEPRECATED\\_SYNTAX\\_NO\\_REPLACEMENT](#); SQLSTATE: [HY000](#)  
Message: The syntax '%s' is deprecated and will be removed in a future release.
  - Error number: [MY-011070](#); Symbol: [ER\\_DEPRECATED\\_MSG\\_NO\\_REPLACEMENT](#); SQLSTATE: [HY000](#)  
Message: '%s' is deprecated and will be removed in a future release.
  - Error number: [MY-011071](#); Symbol: [ER\\_LOG\\_PRINTF\\_MSG](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-011072](#); Symbol: [ER\\_BINLOG\\_LOGGING\\_NOT\\_POSSIBLE](#); SQLSTATE: [HY000](#)  
Message: Binary logging not possible. Message: %s.
  - Error number: [MY-011073](#); Symbol: [ER\\_FAILED\\_TO\\_SET\\_PERSISTED\\_OPTIONS](#); SQLSTATE: [HY000](#)  
Message: Failed to set persisted options.
  - Error number: [MY-011074](#); Symbol: [ER\\_COMPONENTS\\_FAILED\\_TO\\_ACQUIRE\\_SERVICE\\_IMPLEMENTATION](#); SQLSTATE: [HY000](#)

---

Message: Cannot acquire specified service implementation: '%s'.

- Error number: [MY-011075](#); Symbol: [ER\\_RES\\_GRP\\_INVALID\\_VCPU\\_RANGE](#); SQLSTATE: [HY000](#)  
Message: Invalid VCPU range %u-%u.
- Error number: [MY-011076](#); Symbol: [ER\\_RES\\_GRP\\_INVALID\\_VCPU\\_ID](#); SQLSTATE: [HY000](#)  
Message: Invalid cpu id %u.
- Error number: [MY-011077](#); Symbol: [ER\\_ERROR\\_DURING\\_FLUSH\\_LOG\\_COMMIT\\_PHASE](#); SQLSTATE: [HY000](#)  
Message: Got error %d during FLUSH\_LOGS.
- Error number: [MY-011078](#); Symbol: [ER\\_DROP\\_DATABASE\\_FAILED\\_RMDIR\\_MANUALLY](#); SQLSTATE: [HY000](#)  
Message: Problem while dropping database. Can't remove database directory (%s). Please remove it manually.
- Error number: [MY-011080](#); Symbol: [ER\\_BINLOG\\_MALFORMED\\_OR\\_OLD\\_RELAY\\_LOG](#); SQLSTATE: [HY000](#)  
Message: malformed or very old relay log which does not have FormatDescriptor.
- Error number: [MY-011081](#); Symbol: [ER\\_DD\\_UPGRADE\\_VIEW\\_COLUMN\\_NAME\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)  
Message: Upgrade of view '%s.%s' failed. Re-create the view with the explicit column name lesser than 64 characters.
- Error number: [MY-011082](#); Symbol: [ER\\_TABLE\\_NEEDS\\_DUMP\\_UPGRADE](#); SQLSTATE: [HY000](#)  
Message: Table upgrade required for `%s`.`%s`. Please dump/reload table to fix it!
- Error number: [MY-011083](#); Symbol: [ER\\_DD\\_UPGRADE\\_FAILED\\_TO\\_UPDATE\\_VER\\_NO\\_IN\\_TABLESPACE](#); SQLSTATE: [HY000](#)  
Message: Error in updating version number in %s tablespace.
- Error number: [MY-011084](#); Symbol: [ER\\_KEYRING\\_MIGRATION\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Keyring migration failed.
- Error number: [MY-011085](#); Symbol: [ER\\_KEYRING\\_MIGRATION\\_SUCCESSFUL](#); SQLSTATE: [HY000](#)  
Message: Keyring migration successful.
- Error number: [MY-011086](#); Symbol: [ER\\_RESTART\\_RECEIVED\\_INFO](#); SQLSTATE: [HY000](#)  
Message: Received RESTART from user %s. Restarting mysqld (Version: %s).
- Error number: [MY-011087](#); Symbol: [ER\\_LCTN\\_CHANGED](#); SQLSTATE: [HY000](#)  
Message: Different lower\_case\_table\_names settings for server ('%u') and data dictionary ('%u').
- Error number: [MY-011088](#); Symbol: [ER\\_DD\\_INITIALIZE](#); SQLSTATE: [HY000](#)  
Message: Data dictionary initializing version '%u'.
- Error number: [MY-011089](#); Symbol: [ER\\_DD\\_RESTART](#); SQLSTATE: [HY000](#)  
Message: Data dictionary restarting version '%u'.

- 
- Error number: `MY-011090`; Symbol: `ER_DD_UPGRADE`; SQLSTATE: `HY000`  
Message: Data dictionary upgrading from version '%u' to '%u'.
  - Error number: `MY-011091`; Symbol: `ER_DD_UPGRADE_OFF`; SQLSTATE: `HY000`  
Message: Data dictionary upgrade prohibited by the command line option '--no\_dd\_upgrade'.
  - Error number: `MY-011092`; Symbol: `ER_DD_UPGRADE_VERSION_NOT_SUPPORTED`; SQLSTATE: `HY000`  
Message: Upgrading the data dictionary from dictionary version '%u' is not supported.
  - Error number: `MY-011093`; Symbol: `ER_DD_UPGRADE_SCHEMA_UNAVAILABLE`; SQLSTATE: `HY000`  
Message: Upgrading the data dictionary failed, temporary schema name '%s' not available.
  - Error number: `MY-011094`; Symbol: `ER_DD_MINOR_DOWNGRADE`; SQLSTATE: `HY000`  
Message: Data dictionary minor downgrade from version '%u' to '%u'.
  - Error number: `MY-011095`; Symbol: `ER_DD_MINOR_DOWNGRADE_VERSION_NOT_SUPPORTED`; SQLSTATE: `HY000`  
Message: Minor downgrade of the Data dictionary from dictionary version '%u' is not supported.
  - Error number: `MY-011096`; Symbol: `ER_DD_NO_VERSION_FOUND`; SQLSTATE: `HY000`  
Message: No data dictionary version number found.
  - Error number: `MY-011097`; Symbol: `ER_THREAD_POOL_NOT_SUPPORTED_ON_PLATFORM`; SQLSTATE: `HY000`  
Message: Thread pool not supported, requires a minimum of %s.
  - Error number: `MY-011098`; Symbol: `ER_THREAD_POOL_SIZE_TOO_LOW`; SQLSTATE: `HY000`  
Message: thread\_pool\_size=0 means thread pool disabled, Allowed range of thread\_pool\_size is %d-%d.
  - Error number: `MY-011099`; Symbol: `ER_THREAD_POOL_SIZE_TOO_HIGH`; SQLSTATE: `HY000`  
Message: thread\_pool\_size=%lu is too high, %d is maximum, thread pool is disabled. Allowed range of thread\_pool\_size is %d-%d.
  - Error number: `MY-011100`; Symbol: `ER_THREAD_POOL_ALGORITHM_INVALID`; SQLSTATE: `HY000`  
Message: thread\_pool\_algorithm can be set to 0 and 1, 0 indicates the default low concurrency algorithm, 1 means a high concurrency algorithm.
  - Error number: `MY-011101`; Symbol: `ER_THREAD_POOL_INVALID_STALL_LIMIT`; SQLSTATE: `HY000`  
Message: thread\_pool\_stall\_limit can be %d at minimum and %d at maximum, smaller values would render the thread pool fairly useless and higher values could make it possible to have undetected deadlock issues in the MySQL Server.
  - Error number: `MY-011102`; Symbol: `ER_THREAD_POOL_INVALID_PRIO_KICKUP_TIMER`; SQLSTATE: `HY000`  
Message: Invalid value of thread\_pool\_prio\_kickup\_timer specified. Value of thread\_pool\_prio\_kickup\_timer should be in range 0-4294967294.



- 
- Error number: `MY-011103`; Symbol: `ER_THREAD_POOL_MAX_UNUSED_THREADS_INVALID`; SQLSTATE: `HY000`  
Message: `thread_pool_max_unused_threads` cannot be set higher than %d.
  - Error number: `MY-011104`; Symbol: `ER_THREAD_POOL_CON_HANDLER_INIT_FAILED`; SQLSTATE: `HY000`  
Message: Failed to instantiate the connection handler object.
  - Error number: `MY-011105`; Symbol: `ER_THREAD_POOL_INIT_FAILED`; SQLSTATE: `HY000`  
Message: Failed to initialize thread pool plugin.
  - Error number: `MY-011107`; Symbol: `ER_THREAD_POOL_CANNOT_SET_THREAD_SPECIFIC_DATA`; SQLSTATE: `HY000`  
Message: Can't setup connection teardown thread-specific data.
  - Error number: `MY-011108`; Symbol: `ER_THREAD_POOL_FAILED_TO_CREATE_CONNECT_HANDLER_THD`; SQLSTATE: `HY000`  
Message: Creation of connect handler thread failed.
  - Error number: `MY-011109`; Symbol: `ER_THREAD_POOL_FAILED_TO_CREATE_THD_AND_AUTH_CONN`; SQLSTATE: `HY000`  
Message: Failed to create thd and authenticate connection.
  - Error number: `MY-011110`; Symbol: `ER_THREAD_POOL_FAILED_PROCESS_CONNECT_EVENT`; SQLSTATE: `HY000`  
Message: Failed to process connection event.
  - Error number: `MY-011111`; Symbol: `ER_THREAD_POOL_FAILED_TO_CREATE_POOL`; SQLSTATE: `HY000`  
Message: Can't create pool thread (error %d, errno: %d).
  - Error number: `MY-011112`; Symbol: `ER_THREAD_POOL_RATE_LIMITED_ERROR_MSGS`; SQLSTATE: `HY000`  
Message: %.\*s.
  - Error number: `MY-011113`; Symbol: `ER_THREAD_POOL_LOW_LEVEL_INIT_FAILED`; SQLSTATE: `HY000`  
Message: `tp_group_low_level_init()` failed.
  - Error number: `MY-011114`; Symbol: `ER_THREAD_POOL_LOW_LEVEL_REARM_FAILED`; SQLSTATE: `HY000`  
Message: Rearm failed even after 30 seconds, can't continue without notify socket.
  - Error number: `MY-011115`; Symbol: `ER_THREAD_POOL_BUFFER_TOO_SMALL`; SQLSTATE: `HY000`  
Message: %s: %s buffer is too small
  - Error number: `MY-011116`; Symbol: `ER_MECAB_NOT_SUPPORTED`; SQLSTATE: `HY000`  
Message: Mecab v%s is not supported, the lowest version supported is v%s.
  - Error number: `MY-011117`; Symbol: `ER_MECAB_NOT_VERIFIED`; SQLSTATE: `HY000`
-

---

Message: Mecab v%s is not verified, the highest version supported is v%s.

- Error number: MY-011118; Symbol: ER\_MECAB\_CREATING\_MODEL; SQLSTATE: HY000

Message: Mecab: Trying createModel(%s).

- Error number: MY-011119; Symbol: ER\_MECAB\_FAILED\_TO\_CREATE\_MODEL; SQLSTATE: HY000

Message: Mecab: createModel() failed: %s.

- Error number: MY-011120; Symbol: ER\_MECAB\_FAILED\_TO\_CREATE\_TRIGGER; SQLSTATE: HY000

Message: Mecab: createTagger() failed: %s.

- Error number: MY-011121; Symbol: ER\_MECAB\_UNSUPPORTED\_CHARSET; SQLSTATE: HY000

Message: Mecab: Unsupported dictionary charset %s.

- Error number: MY-011122; Symbol: ER\_MECAB\_CHARSET\_LOADED; SQLSTATE: HY000

Message: Mecab: Loaded dictionary charset is %s.

- Error number: MY-011123; Symbol: ER\_MECAB\_PARSE\_FAILED; SQLSTATE: HY000

Message: Mecab: parse() failed: %s.

- Error number: MY-011124; Symbol: ER\_MECAB\_OOM\_WHILE\_PARSING\_TEXT; SQLSTATE: HY000

Message: Mecab: parse() failed: out of memory.

- Error number: MY-011125; Symbol: ER\_MECAB\_CREATE\_LATTICE\_FAILED; SQLSTATE: HY000

Message: Mecab: createLattice() failed: %s.

- Error number: MY-011126; Symbol: ER\_SEMISYNC\_TRACE\_ENTER\_FUNC; SQLSTATE: HY000

Message: ---> %s enter.

- Error number: MY-011127; Symbol: ER\_SEMISYNC\_TRACE\_EXIT\_WITH\_INT\_EXIT\_CODE; SQLSTATE: HY000

Message: <--- %s exit (%d).

- Error number: MY-011128; Symbol: ER\_SEMISYNC\_TRACE\_EXIT\_WITH\_BOOL\_EXIT\_CODE; SQLSTATE: HY000

Message: <--- %s exit (%s).

- Error number: MY-011129; Symbol: ER\_SEMISYNC\_TRACE\_EXIT; SQLSTATE: HY000

Message: <--- %s exit.

- Error number: MY-011130; Symbol: ER\_SEMISYNC\_RPL\_INIT\_FOR\_TRX; SQLSTATE: HY000

Message: Semi-sync replication initialized for transactions.

- Error number: MY-011131; Symbol: ER\_SEMISYNC\_FAILED\_TO\_ALLOCATE\_TRX\_NODE; SQLSTATE: HY000

Message: %s: transaction node allocation failed for: (%s, %lu).

- Error number: MY-011132; Symbol: ER\_SEMISYNC\_BINLOG\_WRITE\_OUT\_OF\_ORDER; SQLSTATE: HY000

---

Message: %s: binlog write out-of-order, tail (%s, %lu), new node (%s, %lu).

- Error number: [MY-011133](#); Symbol: [ER\\_SEMISYNC\\_INSERT\\_LOG\\_INFO\\_IN\\_ENTRY](#); SQLSTATE: [HY000](#)

Message: %s: insert (%s, %lu) in entry(%u).

- Error number: [MY-011134](#); Symbol: [ER\\_SEMISYNC\\_PROBE\\_LOG\\_INFO\\_IN\\_ENTRY](#); SQLSTATE: [HY000](#)

Message: %s: probe (%s, %lu) in entry(%u).

- Error number: [MY-011135](#); Symbol: [ER\\_SEMISYNC\\_CLEARED\\_ALL\\_ACTIVE\\_TRANSACTION\\_NODES](#); SQLSTATE: [HY000](#)

Message: %s: cleared all nodes.

- Error number: [MY-011136](#); Symbol: [ER\\_SEMISYNC\\_CLEARED\\_ACTIVE\\_TRANSACTION\\_TILL\\_POS](#); SQLSTATE: [HY000](#)

Message: %s: cleared %d nodes back until pos (%s, %lu).

- Error number: [MY-011137](#); Symbol: [ER\\_SEMISYNC\\_REPLY\\_MAGIC\\_NO\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Read semi-sync reply magic number error.

- Error number: [MY-011138](#); Symbol: [ER\\_SEMISYNC\\_REPLY\\_PKT\\_LENGTH\\_TOO\\_SMALL](#); SQLSTATE: [HY000](#)

Message: Read semi-sync reply length error: packet is too small.

- Error number: [MY-011139](#); Symbol: [ER\\_SEMISYNC\\_REPLY\\_BINLOG\\_FILE\\_TOO\\_LARGE](#); SQLSTATE: [HY000](#)

Message: Read semi-sync reply binlog file length too large.

- Error number: [MY-011140](#); Symbol: [ER\\_SEMISYNC\\_SERVER\\_REPLY](#); SQLSTATE: [HY000](#)

Message: %s: Got reply(%s, %lu) from server %u.

- Error number: [MY-011141](#); Symbol: [ER\\_SEMISYNC\\_FUNCTION\\_CALLED\\_TWICE](#); SQLSTATE: [HY000](#)

Message: %s called twice.

- Error number: [MY-011142](#); Symbol: [ER\\_SEMISYNC\\_RPL\\_ENABLED\\_ON\\_SOURCE](#); SQLSTATE: [HY000](#)

Message: Semi-sync replication enabled on the source.

- Error number: [MY-011143](#); Symbol: [ER\\_SEMISYNC\\_SOURCE\\_OOM](#); SQLSTATE: [HY000](#)

Message: Cannot allocate memory to enable semi-sync on the source.

- Error number: [MY-011144](#); Symbol: [ER\\_SEMISYNC\\_DISABLED\\_ON\\_SOURCE](#); SQLSTATE: [HY000](#)

Message: Semi-sync replication disabled on the source.

- Error number: [MY-011145](#); Symbol: [ER\\_SEMISYNC\\_FORCED\\_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: SEMISYNC: Forced shutdown. Some updates might not be replicated.

- 
- Error number: [MY-011146](#); Symbol: [ER\\_SEMISYNC\\_SOURCE\\_GOT\\_REPLY\\_AT\\_POS](#); SQLSTATE: [HY000](#)  
Message: %s: Got reply at (%s, %lu).
  - Error number: [MY-011147](#); Symbol: [ER\\_SEMISYNC\\_SOURCE\\_SIGNAL\\_ALL\\_WAITING\\_THREADS](#); SQLSTATE: [HY000](#)  
Message: %s: signal all waiting threads.
  - Error number: [MY-011148](#); Symbol: [ER\\_SEMISYNC\\_SOURCE\\_TRX\\_WAIT\\_POS](#); SQLSTATE: [HY000](#)  
Message: %s: wait pos (%s, %lu), repl(%d).
  - Error number: [MY-011149](#); Symbol: [ER\\_SEMISYNC\\_BINLOG\\_REPLY\\_IS\\_AHEAD](#); SQLSTATE: [HY000](#)  
Message: %s: Binlog reply is ahead (%s, %lu).
  - Error number: [MY-011150](#); Symbol: [ER\\_SEMISYNC\\_MOVE\\_BACK\\_WAIT\\_POS](#); SQLSTATE: [HY000](#)  
Message: %s: move back wait position (%s, %lu).
  - Error number: [MY-011151](#); Symbol: [ER\\_SEMISYNC\\_INIT\\_WAIT\\_POS](#); SQLSTATE: [HY000](#)  
Message: %s: init wait position (%s, %lu).
  - Error number: [MY-011152](#); Symbol: [ER\\_SEMISYNC\\_WAIT\\_TIME\\_FOR\\_BINLOG\\_SENT](#); SQLSTATE: [HY000](#)  
Message: %s: wait %lu ms for binlog sent (%s, %lu).
  - Error number: [MY-011153](#); Symbol: [ER\\_SEMISYNC\\_WAIT\\_FOR\\_BINLOG\\_TIMEDOUT](#); SQLSTATE: [HY000](#)  
Message: Timeout waiting for reply of binlog (file: %s, pos: %lu), semi-sync up to file %s, position %lu.
  - Error number: [MY-011154](#); Symbol: [ER\\_SEMISYNC\\_WAIT\\_TIME\\_ASSESSMENT\\_FOR\\_COMMIT\\_TRX\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Assessment of waiting time for commitTrx failed at wait position (%s, %lu).
  - Error number: [MY-011155](#); Symbol: [ER\\_SEMISYNC\\_RPL\\_SWITCHED\\_OFF](#); SQLSTATE: [HY000](#)  
Message: Semi-sync replication switched OFF.
  - Error number: [MY-011156](#); Symbol: [ER\\_SEMISYNC\\_RPL\\_SWITCHED\\_ON](#); SQLSTATE: [HY000](#)  
Message: Semi-sync replication switched ON at (%s, %lu).
  - Error number: [MY-011157](#); Symbol: [ER\\_SEMISYNC\\_NO\\_SPACE\\_IN\\_THE\\_PKT](#); SQLSTATE: [HY000](#)  
Message: No enough space in the packet for semi-sync extra header, semi-sync replication disabled.
  - Error number: [MY-011158](#); Symbol: [ER\\_SEMISYNC\\_SYNC\\_HEADER\\_UPDATE\\_INFO](#); SQLSTATE: [HY000](#)  
Message: %s: server(%d), (%s, %lu) sync(%d), repl(%d).
  - Error number: [MY-011159](#); Symbol: [ER\\_SEMISYNC\\_FAILED\\_TO\\_INSERT\\_TRX\\_NODE](#); SQLSTATE: [HY000](#)  
Message: Semi-sync failed to insert tranx\_node for binlog file: %s, position: %lu.

- 
- Error number: `MY-011160`; Symbol: `ER_SEMISYNC_TRX_SKIPPED_AT_POS`; SQLSTATE: `HY000`  
Message: %s: Transaction skipped at (%s, %lu).
  - Error number: `MY-011161`; Symbol: `ER_SEMISYNC_SOURCE_FAILED_ON_NET_FLUSH`; SQLSTATE: `HY000`  
Message: Semi-sync source failed on net\_flush() before waiting for replica reply.
  - Error number: `MY-011162`; Symbol: `ER_SEMISYNC_RECEIVED_ACK_IS_SMALLER`; SQLSTATE: `HY000`  
Message: The received ack is smaller than m\_greatest\_ack.
  - Error number: `MY-011163`; Symbol: `ER_SEMISYNC_ADD_ACK_TO_SLOT`; SQLSTATE: `HY000`  
Message: Add the ack into slot %u.
  - Error number: `MY-011164`; Symbol: `ER_SEMISYNC_UPDATE_EXISTING_REPLICA_ACK`; SQLSTATE: `HY000`  
Message: Update an existing ack in slot %u.
  - Error number: `MY-011165`; Symbol: `ER_SEMISYNC_FAILED_TO_START_ACK_RECEIVER_THD`; SQLSTATE: `HY000`  
Message: Failed to start semi-sync ACK receiver thread, could not create thread(errno=%d).
  - Error number: `MY-011166`; Symbol: `ER_SEMISYNC_STARTING_ACK_RECEIVER_THD`; SQLSTATE: `HY000`  
Message: Starting ack receiver thread.
  - Error number: `MY-011167`; Symbol: `ER_SEMISYNC_FAILED_TO_WAIT_ON_DUMP_SOCKET`; SQLSTATE: `HY000`  
Message: Failed to wait on semi-sync dump sockets, error: errno=%d.
  - Error number: `MY-011168`; Symbol: `ER_SEMISYNC_STOPPING_ACK_RECEIVER_THREAD`; SQLSTATE: `HY000`  
Message: Stopping ack receiver thread.
  - Error number: `MY-011169`; Symbol: `ER_SEMISYNC_FAILED_REGISTER_REPLICA_TO_RECEIVER`; SQLSTATE: `HY000`  
Message: Failed to register replica to semi-sync ACK receiver thread.
  - Error number: `MY-011170`; Symbol: `ER_SEMISYNC_START_BINLOG_DUMP_TO_REPLICA`; SQLSTATE: `HY000`  
Message: Start %s binlog\_dump to replica (server\_id: %d), pos(%s, %lu).
  - Error number: `MY-011171`; Symbol: `ER_SEMISYNC_STOP_BINLOG_DUMP_TO_REPLICA`; SQLSTATE: `HY000`  
Message: Stop %s binlog\_dump to replica (server\_id: %d).
  - Error number: `MY-011172`; Symbol: `ER_SEMISYNC_UNREGISTER_TRX_OBSERVER_FAILED`; SQLSTATE: `HY000`  
Message: unregister\_trans\_observer failed.
-

- 
- Error number: MY-011173; Symbol: ER\_SEMISYNC\_UNREGISTER\_BINLOG\_STORAGE\_OBSERVER\_FAILED; SQLSTATE: HY000  
Message: unregister\_binlog\_storage\_observer failed.
  - Error number: MY-011174; Symbol: ER\_SEMISYNC\_UNREGISTER\_BINLOG\_TRANSMIT\_OBSERVER\_FAILED; SQLSTATE: HY000  
Message: unregister\_binlog\_transmit\_observer failed.
  - Error number: MY-011175; Symbol: ER\_SEMISYNC\_UNREGISTERED\_REPLICATOR; SQLSTATE: HY000  
Message: unregister\_replicator OK.
  - Error number: MY-011176; Symbol: ER\_SEMISYNC\_SOCKET\_FD\_TOO\_LARGE; SQLSTATE: HY000  
Message: Semisync replica socket fd is %u. select() cannot handle if the socket fd is bigger than %u (FD\_SETSIZE).
  - Error number: MY-011177; Symbol: ER\_SEMISYNC\_REPLICA\_REPLY; SQLSTATE: HY000  
Message: %s: reply - %d.
  - Error number: MY-011178; Symbol: ER\_SEMISYNC\_MISSING\_MAGIC\_NO\_FOR\_SEMISYNC\_PKT; SQLSTATE: HY000  
Message: Missing magic number for semi-sync packet, packet len: %lu.
  - Error number: MY-011179; Symbol: ER\_SEMISYNC\_REPLICA\_START; SQLSTATE: HY000  
Message: Replica I/O thread: Start %s replication to source '%s@%s:%d' in log '%s' at position %lu.
  - Error number: MY-011180; Symbol: ER\_SEMISYNC\_REPLICA\_REPLY\_WITH\_BINLOG\_INFO; SQLSTATE: HY000  
Message: %s: reply (%s, %lu).
  - Error number: MY-011181; Symbol: ER\_SEMISYNC\_REPLICA\_NET\_FLUSH\_REPLY\_FAILED; SQLSTATE: HY000  
Message: Semi-sync replica net\_flush() reply failed.
  - Error number: MY-011182; Symbol: ER\_SEMISYNC\_REPLICA\_SEND\_REPLY\_FAILED; SQLSTATE: HY000  
Message: Semi-sync replica send reply failed: %s (%d).
  - Error number: MY-011183; Symbol: ER\_SEMISYNC\_EXECUTION\_FAILED\_ON\_SOURCE; SQLSTATE: HY000  
Message: Execution failed on source: %s; error %d
  - Error number: MY-011184; Symbol: ER\_SEMISYNC\_NOT\_SUPPORTED\_BY\_SOURCE; SQLSTATE: HY000  
Message: Source server does not support semi-sync, fallback to asynchronous replication
  - Error number: MY-011185; Symbol: ER\_SEMISYNC\_REPLICA\_SET\_FAILED; SQLSTATE: HY000  
Message: Set 'rpl\_semi\_sync\_replica=1' on source failed
  - Error number: MY-011186; Symbol: ER\_SEMISYNC\_FAILED\_TO\_STOP\_ACK\_RECEIVER\_THD; SQLSTATE: HY000

---

Message: Failed to stop ack receiver thread on my\_thread\_join, errno(%d).

- Error number: MY-011187; Symbol: ER\_FIREWALL\_FAILED\_TO\_READ\_FIREWALL\_TABLES; SQLSTATE: HY000

Message: Failed to read the firewall tables

- Error number: MY-011188; Symbol: ER\_FIREWALL\_FAILED\_TO\_REG\_DYNAMIC\_PRIVILEGES; SQLSTATE: HY000

Message: Failed to register dynamic privileges

- Error number: MY-011189; Symbol: ER\_FIREWALL\_RECORDING\_STMT\_WAS\_TRUNCATED; SQLSTATE: HY000

Message: Statement was truncated and not recorded: %s

- Error number: MY-011190; Symbol: ER\_FIREWALL\_RECORDING\_STMT\_WITHOUT\_TEXT; SQLSTATE: HY000

Message: Statement with no text was not recorded

- Error number: MY-011191; Symbol: ER\_FIREWALL\_SUSPICIOUS\_STMT; SQLSTATE: HY000

Message: SUSPICIOUS STATEMENT from '%s'. Reason: %s Statement: %s

- Error number: MY-011192; Symbol: ER\_FIREWALL\_ACCESS\_DENIED; SQLSTATE: HY000

Message: ACCESS DENIED for '%s'. Reason: %s Statement: %s

- Error number: MY-011193; Symbol: ER\_FIREWALL\_SKIPPED\_UNKNOWN\_USER\_MODE; SQLSTATE: HY000

Message: Skipped unknown user mode '%s'

- Error number: MY-011194; Symbol: ER\_FIREWALL\_RELOADING\_CACHE; SQLSTATE: HY000

Message: Reloading cache from disk

- Error number: MY-011195; Symbol: ER\_FIREWALL\_RESET\_FOR\_USER; SQLSTATE: HY000

Message: FIREWALL RESET for '%s'

- Error number: MY-011196; Symbol: ER\_FIREWALL\_STATUS\_FLUSHED; SQLSTATE: HY000

Message: Counters are reset to zero

- Error number: MY-011197; Symbol: ER\_KEYRING\_LOGGER\_ERROR\_MSG; SQLSTATE: HY000

Message: %s

- Error number: MY-011198; Symbol: ER\_AUDIT\_LOG\_FILTER\_IS\_NOT\_INSTALLED; SQLSTATE: HY000

Message: Audit Log plugin supports filtering mode, which has not been installed yet. Audit Log plugin will run in the legacy mode, which will be removed in the next release.

- Error number: MY-011199; Symbol: ER\_AUDIT\_LOG\_SWITCHING\_TO\_INCLUDE\_LIST; SQLSTATE: HY000

Message: Previously exclude list is used, now we start using include list, exclude list is set to NULL.

- Error number: MY-011200; Symbol: ER\_AUDIT\_LOG\_CANNOT\_SET\_LOG\_POLICY\_WITH\_OTHER\_POLICIES; SQLSTATE: HY000

---

Message: Cannot set audit\_log\_policy simultaneously with either audit\_log\_connection\_policy or audit\_log\_statement\_policy, setting audit\_log\_connection\_policy and audit\_log\_statement\_policy based on audit\_log\_policy.

- Error number: MY-011201; Symbol: ER\_AUDIT\_LOG\_ONLY\_INCLUDE\_LIST\_USED; SQLSTATE: HY000

Message: Both include and exclude lists provided, include list is preferred, exclude list is set to NULL.

- Error number: MY-011202; Symbol: ER\_AUDIT\_LOG\_INDEX\_MAP\_CANNOT\_ACCESS\_DIR; SQLSTATE: HY000

Message: Could not access '%s' directory.

- Error number: MY-011203; Symbol: ER\_AUDIT\_LOG\_WRITER\_RENAME\_FILE\_FAILED; SQLSTATE: HY000

Message: Could not rename file from '%s' to '%s'.

- Error number: MY-011204; Symbol: ER\_AUDIT\_LOG\_WRITER\_DEST\_FILE\_ALREADY\_EXISTS; SQLSTATE: HY000

Message: File '%s' should not exist. It may be incomplete. The server crashed.

- Error number: MY-011205; Symbol: ER\_AUDIT\_LOG\_WRITER\_RENAME\_FILE\_FAILED\_REMOVE\_FILE\_MANUALLY; SQLSTATE: HY000

Message: Could not rename file from '%s' to '%s'. Remove the file manually.

- Error number: MY-011206; Symbol: ER\_AUDIT\_LOG\_WRITER\_INCOMPLETE\_FILE\_RENAMED; SQLSTATE: HY000

Message: Incomplete file renamed from '%s' to '%s'.

- Error number: MY-011207; Symbol: ER\_AUDIT\_LOG\_WRITER\_FAILED\_TO\_WRITE\_TO\_FILE; SQLSTATE: HY000

Message: Error writing file '%s' (errno: %d - %s).

- Error number: MY-011208; Symbol: ER\_AUDIT\_LOG\_EC\_WRITER\_FAILED\_TO\_INIT\_ENCRYPTION; SQLSTATE: HY000

Message: Could not initialize audit log file encryption.

- Error number: MY-011209; Symbol: ER\_AUDIT\_LOG\_EC\_WRITER\_FAILED\_TO\_INIT\_COMPRESSION; SQLSTATE: HY000

Message: Could not initialize audit log file compression.

- Error number: MY-011210; Symbol: ER\_AUDIT\_LOG\_EC\_WRITER\_FAILED\_TO\_CREATE\_FILE; SQLSTATE: HY000

Message: Could not create '%s' file for audit logging.

- Error number: MY-011211; Symbol: ER\_AUDIT\_LOG\_RENAME\_LOG\_FILE\_BEFORE\_FLUSH; SQLSTATE: HY000

Message: Audit log file (%s) must be manually renamed before audit\_log\_flush is set to true.

- Error number: MY-011212; Symbol: ER\_AUDIT\_LOG\_FILTER\_RESULT\_MSG; SQLSTATE: HY000



---

Message: %s

- Error number: `MY-011213`; Symbol: `ER_AUDIT_LOG_JSON_READER_FAILED_TO_PARSE`; SQLSTATE: `HY000`

Message: Error parsing JSON event. Event not accessible.

- Error number: `MY-011214`; Symbol: `ER_AUDIT_LOG_JSON_READER_BUF_TOO_SMALL`; SQLSTATE: `HY000`

Message: Buffer is too small to hold JSON event. Number of events skipped: %zu.

- Error number: `MY-011215`; Symbol: `ER_AUDIT_LOG_JSON_READER_FAILED_TO_OPEN_FILE`; SQLSTATE: `HY000`

Message: Could not open JSON file for reading. Reading next file if exists.

- Error number: `MY-011216`; Symbol: `ER_AUDIT_LOG_JSON_READER_FILE_PARSING_ERROR`; SQLSTATE: `HY000`

Message: JSON file parsing error. Reading next file if exists

- Error number: `MY-011219`; Symbol: `ER_AUDIT_LOG_FILTER_FAILED_TO_STORE_TABLE_FLDS`; SQLSTATE: `HY000`

Message: Could not store field of the %s table.

- Error number: `MY-011220`; Symbol: `ER_AUDIT_LOG_FILTER_FAILED_TO_UPDATE_TABLE`; SQLSTATE: `HY000`

Message: Could not update %s table.

- Error number: `MY-011221`; Symbol: `ER_AUDIT_LOG_FILTER_FAILED_TO_INSERT_INTO_TABLE`; SQLSTATE: `HY000`

Message: Could not insert into %s table.

- Error number: `MY-011222`; Symbol: `ER_AUDIT_LOG_FILTER_FAILED_TO_DELETE_FROM_TABLE`; SQLSTATE: `HY000`

Message: Could not delete from %s table.

- Error number: `MY-011223`; Symbol: `ER_AUDIT_LOG_FILTER_FAILED_TO_INIT_TABLE_FOR_READ`; SQLSTATE: `HY000`

Message: Could not initialize %s table for reading.

- Error number: `MY-011224`; Symbol: `ER_AUDIT_LOG_FILTER_FAILED_TO_READ_TABLE`; SQLSTATE: `HY000`

Message: Could not read %s table.

- Error number: `MY-011225`; Symbol: `ER_AUDIT_LOG_FILTER_FAILED_TO_CLOSE_TABLE_AFTER_READING`; SQLSTATE: `HY000`

Message: Could not close %s table reading.

- Error number: `MY-011226`; Symbol: `ER_AUDIT_LOG_FILTER_USER_AND_HOST_CANNOT_BE_EMPTY`; SQLSTATE: `HY000`

Message: Both user and host columns of %s table cannot be empty.

- 
- Error number: `MY-011227`; Symbol: `ER_AUDIT_LOG_FILTER_FLD_FILTERNAME_CANNOT_BE_EMPTY`; SQLSTATE: `HY000`  
Message: Filtername column of %s table cannot be empty.
  - Error number: `MY-011228`; Symbol: `ER_VALIDATE_PWD_DICT_FILE_NOT_SPECIFIED`; SQLSTATE: `HY000`  
Message: Dictionary file not specified
  - Error number: `MY-011229`; Symbol: `ER_VALIDATE_PWD_DICT_FILE_NOT_LOADED`; SQLSTATE: `HY000`  
Message: Dictionary file not loaded
  - Error number: `MY-011230`; Symbol: `ER_VALIDATE_PWD_DICT_FILE_TOO_BIG`; SQLSTATE: `HY000`  
Message: Dictionary file size exceeded `MAX_DICTIONARY_FILE_LENGTH`, not loaded
  - Error number: `MY-011231`; Symbol: `ER_VALIDATE_PWD_FAILED_TO_READ_DICT_FILE`; SQLSTATE: `HY000`  
Message: Exception while reading the dictionary file
  - Error number: `MY-011232`; Symbol: `ER_VALIDATE_PWD_FAILED_TO_GET_FLD_FROM_SECURITY_CTX`; SQLSTATE: `HY000`  
Message: Can't retrieve the %s from the security context
  - Error number: `MY-011233`; Symbol: `ER_VALIDATE_PWD_FAILED_TO_GET_SECURITY_CTX`; SQLSTATE: `HY000`  
Message: Can't retrieve the security context
  - Error number: `MY-011234`; Symbol: `ER_VALIDATE_PWD_LENGTH_CHANGED`; SQLSTATE: `HY000`  
Message: Effective value of `validate_password_length` is changed. New value is %d
  - Error number: `MY-011235`; Symbol: `ER_REWRITER_QUERY_ERROR_MSG`; SQLSTATE: `HY000`  
Message: %s
  - Error number: `MY-011236`; Symbol: `ER_REWRITER_QUERY_FAILED`; SQLSTATE: `HY000`  
Message: Rewritten query failed to parse:%s
  - Error number: `MY-011237`; Symbol: `ER_XPLUGIN_STARTUP_FAILED`; SQLSTATE: `HY000`  
Message: Startup failed with error "%s"
  - Error number: `MY-011240`; Symbol: `ER_XPLUGIN_USING_SSL_CONF_FROM_SERVER`; SQLSTATE: `HY000`  
Message: Using SSL configuration from MySQL Server
  - Error number: `MY-011241`; Symbol: `ER_XPLUGIN_USING_SSL_CONF_FROM_MYSQLX`; SQLSTATE: `HY000`  
Message: Using SSL configuration from Mysqlx Plugin
  - Error number: `MY-011242`; Symbol: `ER_XPLUGIN_FAILED_TO_USE_SSL_CONF`; SQLSTATE: `HY000`

---

Message: Neither MySQL Server nor Mysqlx Plugin has valid SSL configuration

- Error number: [MY-011243](#); Symbol: [ER\\_XPLUGIN\\_USING\\_SSL\\_FOR\\_TLS\\_CONNECTION](#); SQLSTATE: [HY000](#)

Message: Using %s for TLS connections

- Error number: [MY-011244](#); Symbol: [ER\\_XPLUGIN\\_REFERENCE\\_TO\\_SECURE\\_CONN\\_WITH\\_XPLUGIN](#); SQLSTATE: [HY000](#)

Message: For more information, please see the Using Secure Connections with X Plugin section in the MySQL documentation

- Error number: [MY-011245](#); Symbol: [ER\\_XPLUGIN\\_ERROR\\_MSG](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011246](#); Symbol: [ER\\_SHA\\_PWD\\_FAILED\\_TO\\_PARSE\\_AUTH\\_STRING](#); SQLSTATE: [HY000](#)

Message: Failed to parse stored authentication string for %s. Please check if mysql.user table not corrupted

- Error number: [MY-011247](#); Symbol: [ER\\_SHA\\_PWD\\_FAILED\\_TO\\_GENERATE\\_MULTI\\_ROUND\\_HASH](#); SQLSTATE: [HY000](#)

Message: Error in generating multi-round hash for %s. Plugin can not perform authentication without it. This may be a transient problem

- Error number: [MY-011248](#); Symbol: [ER\\_SHA\\_PWD\\_AUTH\\_REQUIRES\\_RSA\\_OR\\_SSL](#); SQLSTATE: [HY000](#)

Message: Authentication requires either RSA keys or SSL encryption

- Error number: [MY-011249](#); Symbol: [ER\\_SHA\\_PWD\\_RSA\\_KEY\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)

Message: RSA key cipher length of %u is too long. Max value is %u

- Error number: [MY-011250](#); Symbol: [ER\\_PLUGIN\\_COMMON\\_FAILED\\_TO\\_OPEN\\_FILTER\\_TABLES](#); SQLSTATE: [HY000](#)

Message: Failed to open the %s filter tables

- Error number: [MY-011251](#); Symbol: [ER\\_PLUGIN\\_COMMON\\_FAILED\\_TO\\_OPEN\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Failed to open '%s.%s' %s table

- Error number: [MY-011252](#); Symbol: [ER\\_AUTH\\_LDAP\\_ERROR\\_LOGGER\\_ERROR\\_MSG](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011253](#); Symbol: [ER\\_CONN\\_CONTROL\\_ERROR\\_MSG](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011254](#); Symbol: [ER\\_GRP\\_RPL\\_ERROR\\_MSG](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011255](#); Symbol: [ER\\_SHA\\_PWD\\_SALT\\_FOR\\_USER\\_CORRUPT](#); SQLSTATE: [HY000](#)

---

Message: Password salt for user '%s' is corrupt

- Error number: [MY-011256](#); Symbol: [ER\\_SYS\\_VAR\\_COMPONENT\\_OOM](#); SQLSTATE: [HY000](#)

Message: Out of memory for component system variable '%s'.

- Error number: [MY-011257](#); Symbol: [ER\\_SYS\\_VAR\\_COMPONENT\\_VARIABLE\\_SET\\_READ\\_ONLY](#); SQLSTATE: [HY000](#)

Message: variable %s of component %s was forced to be read-only: string variable without update\_func and PLUGIN\_VAR\_MEMALLOC flag.

- Error number: [MY-011258](#); Symbol: [ER\\_SYS\\_VAR\\_COMPONENT\\_UNKNOWN\\_VARIABLE\\_TYPE](#); SQLSTATE: [HY000](#)

Message: Unknown variable type code 0x%x in component '%s'.

- Error number: [MY-011259](#); Symbol: [ER\\_SYS\\_VAR\\_COMPONENT\\_FAILED\\_TO\\_PARSE\\_VARIABLE\\_OPTIONS](#); SQLSTATE: [HY000](#)

Message: Parsing options for variable '%s' failed.

- Error number: [MY-011260](#); Symbol: [ER\\_SYS\\_VAR\\_COMPONENT\\_FAILED\\_TO\\_MAKE\\_VARIABLE\\_PERSISTENT](#); SQLSTATE: [HY000](#)

Message: Setting persistent options for component variable '%s' failed.

- Error number: [MY-011261](#); Symbol: [ER\\_COMPONENT\\_FILTER\\_CONFUSED](#); SQLSTATE: [HY000](#)

Message: The log-filter component "%s" got confused at "%s" (state: %s) ...

- Error number: [MY-011262](#); Symbol: [ER\\_STOP\\_REPLICA\\_IO\\_THREAD\\_DISK\\_SPACE](#); SQLSTATE: [HY000](#)

Message: Waiting until I/O thread for channel '%s' finish writing to disk before stopping. Free some disk space or use 'KILL' to abort I/O thread operation. Notice that aborting the I/O thread while rotating the relay log might corrupt the relay logs, requiring a server restart to fix it.

- Error number: [MY-011263](#); Symbol: [ER\\_LOG\\_FILE\\_CANNOT\\_OPEN](#); SQLSTATE: [HY000](#)

Message: Could not use %s for logging (error %d - %s). Turning logging off for the server process. To turn it on again: fix the cause, then %s restart the MySQL server.

- Error number: [MY-011268](#); Symbol: [ER\\_PERSIST\\_OPTION\\_STATUS](#); SQLSTATE: [HY000](#)

Message: Configuring persisted options failed: "%s".

- Error number: [MY-011269](#); Symbol: [ER\\_NOT\\_IMPLEMENTED\\_GET\\_TABLESPACE\\_STATISTICS](#); SQLSTATE: [HY000](#)

Message: The storage engine '%s' does not provide dynamic table statistics

- Error number: [MY-011272](#); Symbol: [ER\\_SSL\\_FIPS\\_MODE\\_ERROR](#); SQLSTATE: [HY000](#)

Message: SSL fips mode error: %s

- Error number: [MY-011273](#); Symbol: [ER\\_CONN\\_INIT\\_CONNECT\\_IGNORED](#); SQLSTATE: [HY000](#)

Message: init\_connect variable is ignored for user: %s host: %s due to expired password.

- Error number: [MY-011275](#); Symbol: [ER\\_REWRITER\\_OOM](#); SQLSTATE: [HY000](#)

Message: Out of memory.

- 
- Error number: `MY-011276`; Symbol: `ER_REWRITER_TABLE_MALFORMED_ERROR`; SQLSTATE: `HY000`  
Message: Wrong column count or names when loading rules.
  - Error number: `MY-011277`; Symbol: `ER_REWRITER_LOAD_FAILED`; SQLSTATE: `HY000`  
Message: Some rules failed to load.
  - Error number: `MY-011278`; Symbol: `ER_REWRITER_READ_FAILED`; SQLSTATE: `HY000`  
Message: Got error from storage engine while refreshing rewrite rules.
  - Error number: `MY-011279`; Symbol: `ER_CONN_CONTROL_EVENT_COORDINATOR_INIT_FAILED`; SQLSTATE: `HY000`  
Message: Failed to initialize Connection\_event\_coordinator
  - Error number: `MY-011280`; Symbol: `ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED_UPDATE_FAILED`; SQLSTATE: `HY000`  
Message: Failed to update connection delay triggered stats
  - Error number: `MY-011281`; Symbol: `ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED_RESET_FAILED`; SQLSTATE: `HY000`  
Message: Failed to reset connection delay triggered stats
  - Error number: `MY-011282`; Symbol: `ER_CONN_CONTROL_INVALID_CONN_DELAY_TYPE`; SQLSTATE: `HY000`  
Message: Unexpected option type for connection delay.
  - Error number: `MY-011283`; Symbol: `ER_CONN_CONTROL_DELAY_ACTION_INIT_FAILED`; SQLSTATE: `HY000`  
Message: Failed to initialize Connection\_delay\_action
  - Error number: `MY-011284`; Symbol: `ER_CONN_CONTROL_FAILED_TO_SET_CONN_DELAY`; SQLSTATE: `HY000`  
Message: Could not set %s delay for connection delay.
  - Error number: `MY-011285`; Symbol: `ER_CONN_CONTROL_FAILED_TO_UPDATE_CONN_DELAY_HASH`; SQLSTATE: `HY000`  
Message: Failed to update connection delay hash for account : %s
  - Error number: `MY-011286`; Symbol: `ER_XPLUGIN_FORCE_STOP_CLIENT`; SQLSTATE: `HY000`  
Message: %s: Force stopping client because exception occurred: %s
  - Error number: `MY-011287`; Symbol: `ER_XPLUGIN_MAX_AUTH_ATTEMPTS_REACHED`; SQLSTATE: `HY000`  
Message: %s.%u: Maximum number of authentication attempts reached, login failed.
  - Error number: `MY-011288`; Symbol: `ER_XPLUGIN_BUFFER_PAGE_ALLOC_FAILED`; SQLSTATE: `HY000`  
Message: Error allocating Buffer\_page: %s
  - Error number: `MY-011289`; Symbol: `ER_XPLUGIN_DETECTED_HANGING_CLIENTS`; SQLSTATE: `HY000`

---

Message: Detected %u hanging client(s)

- Error number: [MY-011290](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_ACCEPT\\_CLIENT](#); SQLSTATE: [HY000](#)

Message: Error accepting client

- Error number: [MY-011291](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_SCHEDULE\\_CLIENT](#); SQLSTATE: [HY000](#)

Message: Internal error scheduling client for execution

- Error number: [MY-011292](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_PREPARE\\_IO\\_INTERFACES](#); SQLSTATE: [HY000](#)

Message: Preparation of I/O interfaces failed, X Protocol won't be accessible

- Error number: [MY-011293](#); Symbol: [ER\\_XPLUGIN\\_SRV\\_SESSION\\_INIT\\_THREAD\\_FAILED](#); SQLSTATE: [HY000](#)

Message: srv\_session\_init\_thread returned error

- Error number: [MY-011294](#); Symbol: [ER\\_XPLUGIN\\_UNABLE\\_TO\\_USE\\_USER\\_SESSION\\_ACCOUNT](#); SQLSTATE: [HY000](#)

Message: Unable to use user mysql.session account when connecting the server for internal plugin requests.

- Error number: [MY-011295](#); Symbol: [ER\\_XPLUGIN\\_REFERENCE\\_TO\\_USER\\_ACCOUNT\\_DOC\\_SECTION](#); SQLSTATE: [HY000](#)

Message: For more information, please see the X Plugin User Account section in the MySQL documentation

- Error number: [MY-011296](#); Symbol: [ER\\_XPLUGIN\\_UNEXPECTED\\_EXCEPTION\\_DISPATCHING\\_CMD](#); SQLSTATE: [HY000](#)

Message: %s: Unexpected exception dispatching command: %s

- Error number: [MY-011297](#); Symbol: [ER\\_XPLUGIN\\_EXCEPTION\\_IN\\_TASK\\_SCHEDULER](#); SQLSTATE: [HY000](#)

Message: Exception in post: %s

- Error number: [MY-011298](#); Symbol: [ER\\_XPLUGIN\\_TASK\\_SCHEDULING\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Internal error scheduling task

- Error number: [MY-011299](#); Symbol: [ER\\_XPLUGIN\\_EXCEPTION\\_IN\\_EVENT\\_LOOP](#); SQLSTATE: [HY000](#)

Message: Exception in event loop: "%s": %s

- Error number: [MY-011300](#); Symbol: [ER\\_XPLUGIN\\_LISTENER\\_SETUP\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Setup of %s failed, %s

- Error number: [MY-011301](#); Symbol: [ER\\_XPLUING\\_NET\\_STARTUP\\_FAILED](#); SQLSTATE: [HY000](#)

Message: %s

- 
- Error number: [MY-011302](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_AT\\_SSL\\_CONF](#); SQLSTATE: [HY000](#)  
Message: Failed at SSL configuration: "%s"
  - Error number: [MY-011305](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_CREATE\\_SESSION\\_FOR\\_CONN](#); SQLSTATE: [HY000](#)  
Message: %s: Error creating session for connection from %s
  - Error number: [MY-011306](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_INITIALIZE\\_SESSION](#); SQLSTATE: [HY000](#)  
Message: %s: Error initializing session for connection: %s
  - Error number: [MY-011307](#); Symbol: [ER\\_XPLUGIN\\_MESSAGE\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)  
Message: %s: Message of size %u received, exceeding the limit of %i
  - Error number: [MY-011308](#); Symbol: [ER\\_XPLUGIN\\_UNINITIALIZED\\_MESSAGE](#); SQLSTATE: [HY000](#)  
Message: Message is not properly initialized: %s
  - Error number: [MY-011309](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_SET\\_MIN\\_NUMBER\\_OF\\_WORKERS](#); SQLSTATE: [HY000](#)  
Message: Unable to set minimal number of workers to %u; actual value is %i
  - Error number: [MY-011310](#); Symbol: [ER\\_XPLUGIN\\_UNABLE\\_TO\\_ACCEPT\\_CONNECTION](#); SQLSTATE: [HY000](#)  
Message: Unable to accept connection, disconnecting client
  - Error number: [MY-011311](#); Symbol: [ER\\_XPLUGIN\\_ALL\\_IO\\_INTERFACES\\_DISABLED](#); SQLSTATE: [HY000](#)  
Message: All I/O interfaces are disabled, X Protocol won't be accessible
  - Error number: [MY-011314](#); Symbol: [ER\\_XPLUGIN\\_ERROR\\_READING\\_SOCKET](#); SQLSTATE: [HY000](#)  
Message: %s: Error reading from socket %s (%i)
  - Error number: [MY-011315](#); Symbol: [ER\\_XPLUGIN\\_PEER\\_DISCONNECTED\\_WHILE\\_READING\\_MSG\\_BODY](#); SQLSTATE: [HY000](#)  
Message: %s: peer disconnected while reading message body
  - Error number: [MY-011316](#); Symbol: [ER\\_XPLUGIN\\_READ\\_FAILED\\_CLOSING\\_CONNECTION](#); SQLSTATE: [HY000](#)  
Message: client\_id:%s - %s while reading from socket, closing connection
  - Error number: [MY-011322](#); Symbol: [ER\\_XPLUGIN\\_LISTENER\\_SYS\\_VARIABLE\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Please see the MySQL documentation for '%s' system variables to fix the error
  - Error number: [MY-011323](#); Symbol: [ER\\_XPLUGIN\\_LISTENER\\_STATUS\\_MSG](#); SQLSTATE: [HY000](#)  
Message: X Plugin ready for connections. %s
  - Error number: [MY-011324](#); Symbol: [ER\\_XPLUGIN\\_RETRYING\\_BIND\\_ON\\_PORT](#); SQLSTATE: [HY000](#)
-

---

Message: Retrying `bind()` on TCP/IP port %i

- Error number: MY-011327; Symbol: ER\_XPLUGIN\_EXISTING\_USER\_ACCOUNT\_WITH\_INCOMPLETE\_GRANTS; SQLSTATE: HY000

Message: Using existing %s account for authentication. Incomplete grants will be fixed

- Error number: MY-011332; Symbol: ER\_XPLUGIN\_IPv6\_AVAILABLE; SQLSTATE: HY000

Message: IPv6 is available

- Error number: MY-011334; Symbol: ER\_XPLUGIN\_CLIENT\_KILL\_MSG; SQLSTATE: HY000

Message: Kill client: %i %s

- Error number: MY-011335; Symbol: ER\_XPLUGIN\_FAILED\_TO\_GET\_SECURITY\_CTX; SQLSTATE: HY000

Message: Could not get security context for session

- Error number: MY-011337; Symbol: ER\_XPLUGIN\_FAILED\_TO\_CLOSE\_SQL\_SESSION; SQLSTATE: HY000

Message: Error closing SQL session

- Error number: MY-011338; Symbol: ER\_XPLUGIN\_FAILED\_TO\_EXECUTE\_ADMIN\_CMD; SQLSTATE: HY000

Message: Error executing admin command %s: %s

- Error number: MY-011339; Symbol: ER\_XPLUGIN\_EMPTY\_ADMIN\_CMD; SQLSTATE: HY000

Message: Error executing empty admin command

- Error number: MY-011340; Symbol: ER\_XPLUGIN\_FAILED\_TO\_GET\_SYS\_VAR; SQLSTATE: HY000

Message: Unable to retrieve system variable '%s'

- Error number: MY-011341; Symbol: ER\_XPLUGIN\_FAILED\_TO\_GET\_CREATION\_STMT; SQLSTATE: HY000

Message: Unable to get creation stmt for collection '%s'; query result size: %lu

- Error number: MY-011342; Symbol: ER\_XPLUGIN\_FAILED\_TO\_GET\_ENGINE\_INFO; SQLSTATE: HY000

Message: Unable to get engine info for collection '%s'; creation stmt: %s

- Error number: MY-011345; Symbol: ER\_XPLUGIN\_FAILED\_TO\_SET\_SO\_REUSEADDR\_FLAG; SQLSTATE: HY000

Message: Failed to set SO\_REUSEADDR flag (error: %d).

- Error number: MY-011346; Symbol: ER\_XPLUGIN\_FAILED\_TO\_OPEN\_INTERNAL\_SESSION; SQLSTATE: HY000

Message: Could not open internal MySQL session

- Error number: MY-011347; Symbol: ER\_XPLUGIN\_FAILED\_TO\_SWITCH\_CONTEXT; SQLSTATE: HY000

Message: Unable to switch context to user %s



- 
- Error number: [MY-011348](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_UNREGISTER\\_UDF](#); SQLSTATE: [HY000](#)  
Message: Can't unregister '%s' user defined function
  - Error number: [MY-011351](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_RESET\\_IPV6\\_V6ONLY\\_FLAG](#); SQLSTATE: [HY000](#)  
Message: Failed to reset IPV6\_V6ONLY flag (error: %d). The server will listen to IPv6 addresses only.
  - Error number: [MY-011352](#); Symbol: [ER\\_KEYRING\\_INVALID\\_KEY\\_TYPE](#); SQLSTATE: [HY000](#)  
Message: Invalid key type
  - Error number: [MY-011353](#); Symbol: [ER\\_KEYRING\\_INVALID\\_KEY\\_LENGTH](#); SQLSTATE: [HY000](#)  
Message: Invalid key length for given block cipher
  - Error number: [MY-011354](#); Symbol: [ER\\_KEYRING\\_FAILED\\_TO\\_CREATE\\_KEYRING\\_DIR](#); SQLSTATE: [HY000](#)  
Message: Could not create keyring directory. The keyring\_file will stay unusable until correct path to the keyring directory gets provided
  - Error number: [MY-011355](#); Symbol: [ER\\_KEYRING\\_FILE\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: keyring\_file initialization failure. Please check if the keyring\_file\_data points to readable keyring file or keyring file can be created in the specified location. The keyring\_file will stay unusable until correct path to the keyring file gets provided
  - Error number: [MY-011356](#); Symbol: [ER\\_KEYRING\\_INTERNAL\\_EXCEPTION\\_FAILED\\_FILE\\_INIT](#); SQLSTATE: [HY000](#)  
Message: keyring\_file initialization failure due to internal exception inside the plugin.
  - Error number: [MY-011357](#); Symbol: [ER\\_KEYRING\\_FAILED\\_TO\\_GENERATE\\_KEY](#); SQLSTATE: [HY000](#)  
Message: Failed to generate a key due to internal exception inside keyring\_file plugin
  - Error number: [MY-011358](#); Symbol: [ER\\_KEYRING\\_CHECK\\_KEY\\_FAILED\\_DUE\\_TO\\_INVALID\\_KEY](#); SQLSTATE: [HY000](#)  
Message: Error while %s key: invalid key\_type
  - Error number: [MY-011359](#); Symbol: [ER\\_KEYRING\\_CHECK\\_KEY\\_FAILED\\_DUE\\_TO\\_EMPTY\\_KEY\\_ID](#); SQLSTATE: [HY000](#)  
Message: Error while %s key: key\_id cannot be empty
  - Error number: [MY-011360](#); Symbol: [ER\\_KEYRING\\_OPERATION\\_FAILED\\_DUE\\_TO\\_INTERNAL\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Failed to %s due to internal exception inside %s plugin
  - Error number: [MY-011361](#); Symbol: [ER\\_KEYRING\\_INCORRECT\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Incorrect Keyring file
  - Error number: [MY-011362](#); Symbol: [ER\\_KEYRING\\_FOUND\\_MALFORMED\\_BACKUP\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Found malformed keyring backup file - removing it
-

- 
- Error number: [MY-011363](#); Symbol: [ER\\_KEYRING\\_FAILED\\_TO\\_RESTORE\\_FROM\\_BACKUP\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Error while restoring keyring from backup file cannot overwrite keyring with backup
  - Error number: [MY-011364](#); Symbol: [ER\\_KEYRING\\_FAILED\\_TO\\_FLUSH\\_KEYRING\\_TO\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Error while flushing in-memory keyring into keyring file
  - Error number: [MY-011365](#); Symbol: [ER\\_KEYRING\\_FAILED\\_TO\\_GET\\_FILE\\_STAT](#); SQLSTATE: [HY000](#)  
Message: Error while reading stat for %s. Please check if file %s was not removed. OS returned this error: %s
  - Error number: [MY-011366](#); Symbol: [ER\\_KEYRING\\_FAILED\\_TO\\_REMOVE\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Could not remove file %s OS returned this error: %s
  - Error number: [MY-011367](#); Symbol: [ER\\_KEYRING\\_FAILED\\_TO\\_TRUNCATE\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Could not truncate file %s. OS returned this error: %s
  - Error number: [MY-011368](#); Symbol: [ER\\_KEYRING\\_UNKNOWN\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Unknown error %d
  - Error number: [MY-011369](#); Symbol: [ER\\_KEYRING\\_FAILED\\_TO\\_SET\\_KEYRING\\_FILE\\_DATA](#); SQLSTATE: [HY000](#)  
Message: keyring\_file\_data cannot be set to new value as the keyring file cannot be created/ accessed in the provided path
  - Error number: [MY-011370](#); Symbol: [ER\\_KEYRING\\_FILE\\_IO\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-011371](#); Symbol: [ER\\_KEYRING\\_FAILED\\_TO\\_LOAD\\_KEYRING\\_CONTENT](#); SQLSTATE: [HY000](#)  
Message: Error while loading keyring content. The keyring might be malformed
  - Error number: [MY-011372](#); Symbol: [ER\\_KEYRING\\_FAILED\\_TO\\_FLUSH\\_KEYS\\_TO\\_KEYRING](#); SQLSTATE: [HY000](#)  
Message: Could not flush keys to keyring
  - Error number: [MY-011373](#); Symbol: [ER\\_KEYRING\\_FAILED\\_TO\\_FLUSH\\_KEYS\\_TO\\_KEYRING\\_BACKUP](#); SQLSTATE: [HY000](#)  
Message: Could not flush keys to keyring's backup
  - Error number: [MY-011374](#); Symbol: [ER\\_KEYRING\\_KEY\\_FETCH\\_FAILED\\_DUE\\_TO\\_EMPTY\\_KEY\\_ID](#); SQLSTATE: [HY000](#)  
Message: Error while fetching key: key\_id cannot be empty
  - Error number: [MY-011375](#); Symbol: [ER\\_KEYRING\\_FAILED\\_TO\\_REMOVE\\_KEY\\_DUE\\_TO\\_EMPTY\\_ID](#); SQLSTATE: [HY000](#)  
Message: Error while removing key: key\_id cannot be empty

- 
- Error number: `MY-011376`; Symbol: `ER_KEYRING_OKV_INCORRECT_KEY_VAULT_CONFIGURED`; SQLSTATE: `HY000`  
  
Message: For keyring\_okv to be initialized, please point keyring\_okv\_conf\_dir variable to a directory with Oracle Key Vault configuration file and ssl materials
  - Error number: `MY-011377`; Symbol: `ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INCORRECT_CONF`; SQLSTATE: `HY000`  
  
Message: keyring\_okv initialization failure. Please check that the keyring\_okv\_conf\_dir points to a readable directory and that the directory contains Oracle Key Vault configuration file and ssl materials. Please also check that Oracle Key Vault is up and running.
  - Error number: `MY-011378`; Symbol: `ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INTERNAL_ERROR`; SQLSTATE: `HY000`  
  
Message: keyring\_okv initialization failure due to internal exception inside the plugin
  - Error number: `MY-011379`; Symbol: `ER_KEYRING_OKV_INVALID_KEY_TYPE`; SQLSTATE: `HY000`  
  
Message: Invalid key type
  - Error number: `MY-011380`; Symbol: `ER_KEYRING_OKV_INVALID_KEY_LENGTH_FOR_CIPHER`; SQLSTATE: `HY000`  
  
Message: Invalid key length for given block cipher
  - Error number: `MY-011381`; Symbol: `ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY_DUE_TO_INTERNAL_ERROR`; SQLSTATE: `HY000`  
  
Message: Failed to generate a key due to internal exception inside keyring\_okv plugin
  - Error number: `MY-011382`; Symbol: `ER_KEYRING_OKV_FAILED_TO_FIND_SERVER_ENTRY`; SQLSTATE: `HY000`  
  
Message: Could not find entry for server in configuration file %s
  - Error number: `MY-011383`; Symbol: `ER_KEYRING_OKV_FAILED_TO_FIND_STANDBY_SERVER_ENTRY`; SQLSTATE: `HY000`  
  
Message: Could not find entry for standby server in configuration file %s
  - Error number: `MY-011384`; Symbol: `ER_KEYRING_OKV_FAILED_TO_PARSE_CONF_FILE`; SQLSTATE: `HY000`  
  
Message: Could not parse the %s file provided
  - Error number: `MY-011385`; Symbol: `ER_KEYRING_OKV_FAILED_TO_LOAD_KEY_UID`; SQLSTATE: `HY000`  
  
Message: Could not load keys' uids from the OKV server
  - Error number: `MY-011386`; Symbol: `ER_KEYRING_OKV_FAILED_TO_INIT_SSL_LAYER`; SQLSTATE: `HY000`  
  
Message: Could not initialize ssl layer
  - Error number: `MY-011387`; Symbol: `ER_KEYRING_OKV_FAILED_TO_INIT_CLIENT`; SQLSTATE: `HY000`  
  
Message: Could not initialize OKV client
-

- 
- Error number: [MY-011388](#); Symbol: [ER\\_KEYRING\\_OKV\\_CONNECTION\\_TO\\_SERVER\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Could not connect to the OKV server
  - Error number: [MY-011389](#); Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_REMOVE\\_KEY](#); SQLSTATE: [HY000](#)  
Message: Could not remove the key
  - Error number: [MY-011390](#); Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_ADD\\_ATTRIBUTE](#); SQLSTATE: [HY000](#)  
Message: Could not add attribute, attribute\_name=%s attribute value=%s
  - Error number: [MY-011391](#); Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_GENERATE\\_KEY](#); SQLSTATE: [HY000](#)  
Message: Could not generate the key.
  - Error number: [MY-011392](#); Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_STORE\\_KEY](#); SQLSTATE: [HY000](#)  
Message: Could not store the key.
  - Error number: [MY-011393](#); Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_ACTIVATE\\_KEYS](#); SQLSTATE: [HY000](#)  
Message: Could not activate the key.
  - Error number: [MY-011394](#); Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_FETCH\\_KEY](#); SQLSTATE: [HY000](#)  
Message: Could not fetch generated key
  - Error number: [MY-011395](#); Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_STORE\\_OR\\_GENERATE\\_KEY](#); SQLSTATE: [HY000](#)  
Message: Could not store/generate the key - failed to set key attribute x-key-ready
  - Error number: [MY-011396](#); Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_RETRIEVE\\_KEY\\_SIGNATURE](#); SQLSTATE: [HY000](#)  
Message: Could not retrieve key signature from custom attributes
  - Error number: [MY-011397](#); Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_RETRIEVE\\_KEY](#); SQLSTATE: [HY000](#)  
Message: Could not retrieve key from OKV
  - Error number: [MY-011398](#); Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_LOAD\\_SSL\\_TRUST\\_STORE](#); SQLSTATE: [HY000](#)  
Message: Error loading trust store
  - Error number: [MY-011399](#); Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_SET\\_CERTIFICATE\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Error setting the certificate file.
  - Error number: [MY-011400](#); Symbol: [ER\\_KEYRING\\_OKV\\_FAILED\\_TO\\_SET\\_KEY\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Error setting the key file.

- 
- Error number: `MY-011401`; Symbol: `ER_KEYRING_OKV_KEY_MISMATCH`; SQLSTATE: `HY000`  
Message: Private key does not match the certificate public key
  - Error number: `MY-011402`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_INCORRECT_KEYRING_FILE`; SQLSTATE: `HY000`  
Message: Incorrect Keyring file
  - Error number: `MY-011403`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_DECRYPTION_FAILED`; SQLSTATE: `HY000`  
Message: Keyring\_encrypted\_file decryption failed. Please verify --keyring-encrypted-file-password option value.
  - Error number: `MY-011404`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_FOUND_MALFORMED_BACKUP_FILE`; SQLSTATE: `HY000`  
Message: Found malformed keyring backup file - removing it
  - Error number: `MY-011405`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_RESTORE_KEYRING`; SQLSTATE: `HY000`  
Message: Error while restoring keyring from backup file cannot overwrite keyring with backup
  - Error number: `MY-011406`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_FLUSH_KEYRING`; SQLSTATE: `HY000`  
Message: Error while flushing in-memory keyring into keyring file
  - Error number: `MY-011407`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_ENCRYPTION_FAILED`; SQLSTATE: `HY000`  
Message: Keyring\_encrypted\_file encryption failed. Please verify --keyring-encrypted-file-password option value.
  - Error number: `MY-011408`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_INVALID_KEYRING_DIR`; SQLSTATE: `HY000`  
Message: keyring\_encrypted\_file\_data cannot be set to new value as the keyring file cannot be created/accessed in the provided path
  - Error number: `MY-011409`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_CREATE_KEYRING_DIR`; SQLSTATE: `HY000`  
Message: Could not create keyring directory The keyring\_encrypted\_file will stay unusable until correct path to the keyring directory gets provided
  - Error number: `MY-011410`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_INVALID`; SQLSTATE: `HY000`  
Message: The keyring\_encrypted\_file\_password must be set to a valid value.
  - Error number: `MY-011411`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_TOO_LONG`; SQLSTATE: `HY000`  
Message: Too long keyring\_encrypted\_file\_password value.
-

- 
- Error number: `MY-011412`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_INIT_FAILURE`; SQLSTATE: `HY000`

Message: `keyring_encrypted_file` initialization failure. Please check if the `keyring_encrypted_file_data` points to readable keyring file or keyring file can be created in the specified location or password to decrypt keyring file is correct.

- Error number: `MY-011413`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_INIT_FAILED_DUE_TO_INTERNAL_ERROR`; SQLSTATE: `HY000`

Message: `keyring_encrypted_file` initialization failure due to internal exception inside the plugin

- Error number: `MY-011414`; Symbol: `ER_KEYRING_ENCRYPTED_FILE_GEN_KEY_FAILED_DUE_TO_INTERNAL_ERROR`; SQLSTATE: `HY000`

Message: Failed to generate a key due to internal exception inside `keyring_encrypted_file` plugin

- Error number: `MY-011415`; Symbol: `ER_KEYRING_AWS_FAILED_TO_SET_CMK_ID`; SQLSTATE: `HY000`

Message: `keyring_aws_cmk_id` cannot be set to the new value as AWS KMS seems to not understand the id provided. Please check that CMK id provided is correct.

- Error number: `MY-011416`; Symbol: `ER_KEYRING_AWS_FAILED_TO_SET_REGION`; SQLSTATE: `HY000`

Message: `keyring_aws_region` cannot be set to the new value as AWS KMS seems to not understand the region provided. Please check that region provided is correct.

- Error number: `MY-011417`; Symbol: `ER_KEYRING_AWS_FAILED_TO_OPEN_CONF_FILE`; SQLSTATE: `HY000`

Message: Could not open `keyring_aws` configuration file: %s. OS returned this error: %s

- Error number: `MY-011418`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_ID_FROM_CONF_FILE`; SQLSTATE: `HY000`

Message: Could not read AWS access key id from `keyring_aws` configuration file: %s. OS returned this error: %s

- Error number: `MY-011419`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_FROM_CONF_FILE`; SQLSTATE: `HY000`

Message: Could not read AWS access key from `keyring_aws` configuration file: %s. OS returned this error: %s

- Error number: `MY-011420`; Symbol: `ER_KEYRING_AWS_INVALID_CONF_FILE_PATH`; SQLSTATE: `HY000`

Message: Path to `keyring_aws` configuration file cannot be empty

- Error number: `MY-011421`; Symbol: `ER_KEYRING_AWS_INVALID_DATA_FILE_PATH`; SQLSTATE: `HY000`

Message: Path to `keyring_aws` storage file cannot be empty.

- Error number: `MY-011422`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING_DIR`; SQLSTATE: `HY000`

Message: Unable to create/access keyring directory.

- 
- Error number: `MY-011423`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING_DATA_FILE`; SQLSTATE: `HY000`  
Message: Unable to create/access keyring\_aws storage file. Please check if keyring\_aws\_data\_file points to location where keyring file can be created/accessed. Please also make sure that MySQL server's user has high enough privileges to access this location.
  - Error number: `MY-011424`; Symbol: `ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_INTERNAL_ERROR`; SQLSTATE: `HY000`  
Message: keyring\_aws initialization failed due to internal error when initializing synchronization primitive - %s. OS returned this error: %s:
  - Error number: `MY-011425`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ACCESS_DATA_FILE`; SQLSTATE: `HY000`  
Message: Could not access keyring\_aws storage file in the path provided. Please check if the keyring\_aws directory can be accessed by MySQL Server
  - Error number: `MY-011426`; Symbol: `ER_KEYRING_AWS_CMK_ID_NOT_SET`; SQLSTATE: `HY000`  
Message: keyring\_aws\_cmk\_id has to be set
  - Error number: `MY-011427`; Symbol: `ER_KEYRING_AWS_FAILED_TO_GET_KMS_CREDENTIAL_FROM_CONF_FILE`; SQLSTATE: `HY000`  
Message: Could not get AWS KMS credentials from the configuration file
  - Error number: `MY-011428`; Symbol: `ER_KEYRING_AWS_INIT_FAILURE`; SQLSTATE: `HY000`  
Message: keyring\_aws initialization failure.
  - Error number: `MY-011429`; Symbol: `ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_PLUGIN_INTERNAL_ERROR`; SQLSTATE: `HY000`  
Message: keyring\_aws initialization failure due to internal exception inside the plugin
  - Error number: `MY-011430`; Symbol: `ER_KEYRING_AWS_INVALID_KEY_LENGTH_FOR_CIPHER`; SQLSTATE: `HY000`  
Message: Invalid key length for given block cipher
  - Error number: `MY-011431`; Symbol: `ER_KEYRING_AWS_FAILED_TO_GENERATE_KEY_DUE_TO_INTERNAL_ERROR`; SQLSTATE: `HY000`  
Message: Failed to generate a key due to internal exception inside keyring\_file plugin
  - Error number: `MY-011432`; Symbol: `ER_KEYRING_AWS_INCORRECT_FILE`; SQLSTATE: `HY000`  
Message: Incorrect Keyring file
  - Error number: `MY-011433`; Symbol: `ER_KEYRING_AWS_FOUND_MALFORMED_BACKUP_FILE`; SQLSTATE: `HY000`  
Message: Found malformed keyring backup file - removing it
  - Error number: `MY-011434`; Symbol: `ER_KEYRING_AWS_FAILED_TO_RESTORE_FROM_BACKUP_FILE`; SQLSTATE: `HY000`  
Message: Error while restoring keyring from backup file cannot overwrite keyring with backup
-

- 
- Error number: `MY-011435`; Symbol: `ER_KEYRING_AWS_FAILED_TO_FLUSH_KEYRING_TO_FILE`; SQLSTATE: `HY000`  
  
Message: Error while flushing in-memory keyring into keyring file
  - Error number: `MY-011436`; Symbol: `ER_KEYRING_AWS_INCORRECT_REGION`; SQLSTATE: `HY000`  
  
Message: Wrong region
  - Error number: `MY-011437`; Symbol: `ER_KEYRING_AWS_FAILED_TO_CONNECT_KMS`; SQLSTATE: `HY000`  
  
Message: Could not connect to AWS KMS with the credentials provided. Please make sure they are correct. AWS KMS returned this error: %s
  - Error number: `MY-011438`; Symbol: `ER_KEYRING_AWS_FAILED_TO_GENERATE_NEW_KEY`; SQLSTATE: `HY000`  
  
Message: Could not generate a new key. AWS KMS returned this error: %s
  - Error number: `MY-011439`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ENCRYPT_KEY`; SQLSTATE: `HY000`  
  
Message: Could not encrypt key. AWS KMS returned this error: %s
  - Error number: `MY-011440`; Symbol: `ER_KEYRING_AWS_FAILED_TO_RE_ENCRYPT_KEY`; SQLSTATE: `HY000`  
  
Message: Could not re-encrypt key. AWS KMS returned this error: %s
  - Error number: `MY-011441`; Symbol: `ER_KEYRING_AWS_FAILED_TO_DECRYPT_KEY`; SQLSTATE: `HY000`  
  
Message: Could not decrypt key. AWS KMS returned this error: %s
  - Error number: `MY-011442`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ROTATE_CMK`; SQLSTATE: `HY000`  
  
Message: Could not rotate the CMK. AWS KMS returned this error: %s
  - Error number: `MY-011443`; Symbol: `ER_GRP_RPL_GTID_ALREADY_USED`; SQLSTATE: `HY000`  
  
Message: The requested GTID '%s:%lld' was already used, the transaction will rollback.
  - Error number: `MY-011444`; Symbol: `ER_GRP_RPL_APPLIER_THD_KILLED`; SQLSTATE: `HY000`  
  
Message: The group replication applier thread was killed.
  - Error number: `MY-011445`; Symbol: `ER_GRP_RPL_EVENT_HANDLING_ERROR`; SQLSTATE: `HY000`  
  
Message: Error at event handling! Got error: %d.
  - Error number: `MY-011446`; Symbol: `ER_GRP_RPL_ERROR_GTID_EXECUTION_INFO`; SQLSTATE: `HY000`  
  
Message: Error when extracting group GTID execution information, some recovery operations may face future issues.
  - Error number: `MY-011447`; Symbol: `ER_GRP_RPL_CERTIFICATE_SIZE_ERROR`; SQLSTATE: `HY000`  
  
Message: An error occurred when trying to reduce the Certification information size for transmission.



- 
- Error number: [MY-011448](#); Symbol: [ER\\_GRP\\_RPL\\_CREATE\\_APPLIER\\_CACHE\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Failed to create group replication pipeline applier cache!
  - Error number: [MY-011449](#); Symbol: [ER\\_GRP\\_RPL\\_UNBLOCK\\_WAITING\\_THD](#); SQLSTATE: [HY000](#)  
Message: Unblocking the group replication thread waiting for applier to start, as the start group replication was killed.
  - Error number: [MY-011450](#); Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_PIPELINE\\_NOT\\_DISPOSED](#); SQLSTATE: [HY000](#)  
Message: The group replication applier pipeline was not properly disposed. Check the error log for further info.
  - Error number: [MY-011451](#); Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_THD\\_EXECUTION\\_ABORTED](#); SQLSTATE: [HY000](#)  
Message: The applier thread execution was aborted. Unable to process more transactions, this member will now leave the group.
  - Error number: [MY-011452](#); Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_EXECUTION\\_FATAL\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Fatal error during execution on the Applier process of Group Replication. The server will now leave the group.
  - Error number: [MY-011453](#); Symbol: [ER\\_GRP\\_RPL\\_ERROR\\_STOPPING\\_CHANNELS](#); SQLSTATE: [HY000](#)  
Message: Error stopping all replication channels while server was leaving the group. %s
  - Error number: [MY-011454](#); Symbol: [ER\\_GRP\\_RPL\\_ERROR\\_SENDING\\_SINGLE\\_PRIMARY\\_MSSG](#); SQLSTATE: [HY000](#)  
Message: Error sending single primary message informing that primary did apply relay logs.
  - Error number: [MY-011457](#); Symbol: [ER\\_GRP\\_RPL\\_BROADCAST\\_COMMIT\\_TRANS\\_MSSG\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Broadcast of committed transactions message failed.
  - Error number: [MY-011458](#); Symbol: [ER\\_GRP\\_RPL\\_GROUP\\_NAME\\_PARSE\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Unable to parse the group\_replication\_group\_name during the Certification module initialization.
  - Error number: [MY-011459](#); Symbol: [ER\\_GRP\\_RPL\\_ADD\\_GRPSID\\_TO\\_GRPGTIDSID\\_MAP\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Unable to add the group\_sid in the group\_gtid\_sid\_map during the Certification module initialization.
  - Error number: [MY-011460](#); Symbol: [ER\\_GRP\\_RPL\\_UPDATE\\_GRPGTID\\_EXECUTED\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Error updating group\_gtid\_executed GITD set during the Certification module initialization.
  - Error number: [MY-011461](#); Symbol: [ER\\_GRP\\_RPL\\_DONOR\\_TRANS\\_INFO\\_ERROR](#); SQLSTATE: [HY000](#)
-

---

Message: Unable to handle the donor's transaction information when initializing the conflict detection component. Possible out of memory error.

- Error number: [MY-011462](#); Symbol: [ER\\_GRP\\_RPL\\_SERVER\\_CONN\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Error when establishing a server connection during the Certification module initialization.

- Error number: [MY-011463](#); Symbol: [ER\\_GRP\\_RPL\\_ERROR\\_FETCHING\\_GTID\\_EXECUTED\\_SET](#); SQLSTATE: [HY000](#)

Message: Error when extracting this member GTID executed set. Certification module can't be properly initialized.

- Error number: [MY-011464](#); Symbol: [ER\\_GRP\\_RPL\\_ADD\\_GTID\\_TO\\_GRPGTID\\_EXECUTED\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Error while adding the server GTID EXECUTED set to the group\_gtid\_execute during the Certification module initialization.

- Error number: [MY-011465](#); Symbol: [ER\\_GRP\\_RPL\\_ERROR\\_FETCHING\\_GTID\\_SET](#); SQLSTATE: [HY000](#)

Message: Error when extracting this member retrieved set for its applier. Certification module can't be properly initialized.

- Error number: [MY-011466](#); Symbol: [ER\\_GRP\\_RPL\\_ADD\\_RETRIEVED\\_SET\\_TO\\_GRP\\_GTID\\_EXECUTED\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Error while adding the member retrieved set to the group\_gtid\_executed during the Certification module initialization.

- Error number: [MY-011467](#); Symbol: [ER\\_GRP\\_RPL\\_CERTIFICATION\\_INITIALIZATION\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Error during Certification module initialization.

- Error number: [MY-011468](#); Symbol: [ER\\_GRP\\_RPL\\_UPDATE\\_LAST\\_CONFLICT\\_FREE\\_TRANS\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Unable to update last conflict free transaction, this transaction will not be tracked on performance\_schema.replication\_group\_member\_stats.last\_conflict\_free\_transaction.

- Error number: [MY-011469](#); Symbol: [ER\\_GRP\\_RPL\\_UPDATE\\_TRANS\\_SNAPSHOT\\_REF\\_VER\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Error updating transaction snapshot version reference for internal storage.

- Error number: [MY-011472](#); Symbol: [ER\\_GRP\\_RPL\\_CANT\\_GENERATE\\_GTID](#); SQLSTATE: [HY000](#)

Message: Impossible to generate Global Transaction Identifier: the integer component reached the maximal value. Restart the group with a new group\_replication\_group\_name.

- Error number: [MY-011473](#); Symbol: [ER\\_GRP\\_RPL\\_INVALID\\_GTID\\_SET](#); SQLSTATE: [HY000](#)

Message: Invalid stable transactions set.

- Error number: [MY-011474](#); Symbol: [ER\\_GRP\\_RPL\\_UPDATE\\_GTID\\_SET\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Error updating stable transactions set.

- Error number: [MY-011475](#); Symbol: [ER\\_GRP\\_RPL\\_RECEIVED\\_SET\\_MISSING\\_GTIDS](#); SQLSTATE: [HY000](#)

---

Message: There was an error when filling the missing GTIDs on the applier channel received set. Despite not critical, on the long run this may cause performance issues.

- Error number: [MY-011477](#); Symbol: [ER\\_GRP\\_RPL\\_NULL\\_PACKET](#); SQLSTATE: [HY000](#)

Message: Null packet on certifier's queue.

- Error number: [MY-011478](#); Symbol: [ER\\_GRP\\_RPL\\_CANT\\_READ\\_GTID](#); SQLSTATE: [HY000](#)

Message: Error reading GTIDs from the message.

- Error number: [MY-011479](#); Symbol: [ER\\_GRP\\_RPL\\_PROCESS\\_GTID\\_SET\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Error processing stable transactions set.

- Error number: [MY-011480](#); Symbol: [ER\\_GRP\\_RPL\\_PROCESS\\_INTERSECTION\\_GTID\\_SET\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Error processing intersection of stable transactions set.

- Error number: [MY-011481](#); Symbol: [ER\\_GRP\\_RPL\\_SET\\_STABLE\\_TRANS\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Error setting stable transactions set.

- Error number: [MY-011482](#); Symbol: [ER\\_GRP\\_RPL\\_CANT\\_READ\\_GRP\\_GTID\\_EXTRACTED](#); SQLSTATE: [HY000](#)

Message: Error reading group\_gtid\_extracted from the View\_change\_log\_event.

- Error number: [MY-011483](#); Symbol: [ER\\_GRP\\_RPL\\_CANT\\_READ\\_WRITE\\_SET\\_ITEM](#); SQLSTATE: [HY000](#)

Message: Error reading the write set item '%s' from the View\_change\_log\_event.

- Error number: [MY-011484](#); Symbol: [ER\\_GRP\\_RPL\\_INIT\\_CERTIFICATION\\_INFO\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Error during certification\_info initialization.

- Error number: [MY-011485](#); Symbol: [ER\\_GRP\\_RPL\\_CONFLICT\\_DETECTION\\_DISABLED](#); SQLSTATE: [HY000](#)

Message: Primary had applied all relay logs, disabled conflict detection.

- Error number: [MY-011486](#); Symbol: [ER\\_GRP\\_RPL\\_MSG\\_DISCARDED](#); SQLSTATE: [HY000](#)

Message: Message received while the plugin is not ready, message discarded.

- Error number: [MY-011487](#); Symbol: [ER\\_GRP\\_RPL\\_MISSING\\_GRP\\_RPL\\_APPLIER](#); SQLSTATE: [HY000](#)

Message: Message received without a proper group replication applier.

- Error number: [MY-011488](#); Symbol: [ER\\_GRP\\_RPL\\_CERTIFIER\\_MSSG\\_PROCESS\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Error processing message in Certifier.

- Error number: [MY-011489](#); Symbol: [ER\\_GRP\\_RPL\\_SRV\\_NOT\\_ONLINE](#); SQLSTATE: [HY000](#)

Message: This server was not declared online since it is on status %s.

- 
- Error number: [MY-011490](#); Symbol: [ER\\_GRP\\_RPL\\_SRV\\_ONLINE](#); SQLSTATE: [HY000](#)  
Message: This server was declared online within the replication group.
  - Error number: [MY-011491](#); Symbol: [ER\\_GRP\\_RPL\\_DISABLE\\_SRV\\_READ\\_MODE\\_RESTRICTED](#); SQLSTATE: [HY000](#)  
Message: When declaring the plugin online it was not possible to disable the server read mode settings. Try to disable it manually.
  - Error number: [MY-011492](#); Symbol: [ER\\_GRP\\_RPL\\_MEM\\_ONLINE](#); SQLSTATE: [HY000](#)  
Message: The member with address %s:%u was declared online within the replication group.
  - Error number: [MY-011493](#); Symbol: [ER\\_GRP\\_RPL\\_MEM\\_UNREACHABLE](#); SQLSTATE: [HY000](#)  
Message: Member with address %s:%u has become unreachable.
  - Error number: [MY-011494](#); Symbol: [ER\\_GRP\\_RPL\\_MEM\\_REACHABLE](#); SQLSTATE: [HY000](#)  
Message: Member with address %s:%u is reachable again.
  - Error number: [MY-011495](#); Symbol: [ER\\_GRP\\_RPL\\_SRV\\_BLOCKED](#); SQLSTATE: [HY000](#)  
Message: This server is not able to reach a majority of members in the group. This server will now block all updates. The server will remain blocked until contact with the majority is restored. It is possible to use `group_replication_force_members` to force a new group membership.
  - Error number: [MY-011496](#); Symbol: [ER\\_GRP\\_RPL\\_SRV\\_BLOCKED\\_FOR\\_SECS](#); SQLSTATE: [HY000](#)  
Message: This server is not able to reach a majority of members in the group. This server will now block all updates. The server will remain blocked for the next %lu seconds. Unless contact with the majority is restored, after this time the member will error out and leave the group. It is possible to use `group_replication_force_members` to force a new group membership.
  - Error number: [MY-011497](#); Symbol: [ER\\_GRP\\_RPL\\_CHANGE\\_GRP\\_MEM\\_NOT\\_PROCESSED](#); SQLSTATE: [HY000](#)  
Message: A group membership change was received but the plugin is already leaving due to the configured timeout on `group_replication_unreachable_majority_timeout` option.
  - Error number: [MY-011498](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_CONTACT\\_RESTORED](#); SQLSTATE: [HY000](#)  
Message: The member has resumed contact with a majority of the members in the group. Regular operation is restored and transactions are unblocked.
  - Error number: [MY-011499](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_REMOVED](#); SQLSTATE: [HY000](#)  
Message: Members removed from the group: %s
  - Error number: [MY-011500](#); Symbol: [ER\\_GRP\\_RPL\\_PRIMARY\\_MEMBER\\_LEFT\\_GRP](#); SQLSTATE: [HY000](#)  
Message: Primary server with address %s left the group. Electing new Primary.
  - Error number: [MY-011501](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ADDED](#); SQLSTATE: [HY000](#)  
Message: Members joined the group: %s

- 
- Error number: `MY-011502`; Symbol: `ER_GRP_RPL_MEMBER_EXIT_PLUGIN_ERROR`; SQLSTATE: `HY000`  
  
Message: There was a previous plugin error while the member joined the group. The member will now exit the group.
  - Error number: `MY-011503`; Symbol: `ER_GRP_RPL_MEMBER_CHANGE`; SQLSTATE: `HY000`  
  
Message: Group membership changed to %s on view %s.
  - Error number: `MY-011504`; Symbol: `ER_GRP_RPL_MEMBER_LEFT_GRP`; SQLSTATE: `HY000`  
  
Message: Group membership changed: This member has left the group.
  - Error number: `MY-011505`; Symbol: `ER_GRP_RPL_MEMBER_EXPELLED`; SQLSTATE: `HY000`  
  
Message: Member was expelled from the group due to network failures, changing member status to ERROR.
  - Error number: `MY-011506`; Symbol: `ER_GRP_RPL_SESSION_OPEN_FAILED`; SQLSTATE: `HY000`  
  
Message: Unable to open session to (re)set read only mode. Skipping.
  - Error number: `MY-011507`; Symbol: `ER_GRP_RPL_NEW_PRIMARY_ELECTED`; SQLSTATE: `HY000`  
  
Message: A new primary with address %s:%u was elected. %s
  - Error number: `MY-011508`; Symbol: `ER_GRP_RPL_DISABLE_READ_ONLY_FAILED`; SQLSTATE: `HY000`  
  
Message: Unable to disable super read only flag. Try to disable it manually
  - Error number: `MY-011509`; Symbol: `ER_GRP_RPL_ENABLE_READ_ONLY_FAILED`; SQLSTATE: `HY000`  
  
Message: Unable to set super read only flag. Try to set it manually.
  - Error number: `MY-011510`; Symbol: `ER_GRP_RPL_SRV_PRIMARY_MEM`; SQLSTATE: `HY000`  
  
Message: This server is working as primary member.
  - Error number: `MY-011511`; Symbol: `ER_GRP_RPL_SRV_SECONDARY_MEM`; SQLSTATE: `HY000`  
  
Message: This server is working as secondary member with primary member address %s:%u.
  - Error number: `MY-011512`; Symbol: `ER_GRP_RPL_NO_SUITABLE_PRIMARY_MEM`; SQLSTATE: `HY000`  
  
Message: Unable to set any member as primary. No suitable candidate.
  - Error number: `MY-011513`; Symbol: `ER_GRP_RPL_SUPER_READ_ONLY_ACTIVATE_ERROR`; SQLSTATE: `HY000`  
  
Message: Error when activating super\_read\_only mode on start. The member will now exit the group.
  - Error number: `MY-011514`; Symbol: `ER_GRP_RPL_EXCEEDS_AUTO_INC_VALUE`; SQLSTATE: `HY000`  
  
Message: Group contains %lu members which is greater than group\_replication\_auto\_increment\_increment value of %lu. This can lead to a higher transactional abort rate.
-

- 
- Error number: `MY-011515`; Symbol: `ER_GRP_RPL_DATA_NOT_PROVIDED_BY_MEM`; SQLSTATE: `HY000`  
  
Message: Member with address '%s:%u' didn't provide any data during the last group change. Group information can be outdated and lead to errors on recovery.
  - Error number: `MY-011516`; Symbol: `ER_GRP_RPL_MEMBER_ALREADY_EXISTS`; SQLSTATE: `HY000`  
  
Message: There is already a member with server\_uuid %s. The member will now exit the group.
  - Error number: `MY-011518`; Symbol: `ER_GRP_RPL_GTID_EXECUTED_EXTRACT_ERROR`; SQLSTATE: `HY000`  
  
Message: Error when extracting this member GTID executed set. Operations and checks made to group joiners may be incomplete.
  - Error number: `MY-011519`; Symbol: `ER_GRP_RPL_GTID_SET_EXTRACT_ERROR`; SQLSTATE: `HY000`  
  
Message: Error when extracting this member retrieved set for its applier. Operations and checks made to group joiners may be incomplete.
  - Error number: `MY-011520`; Symbol: `ER_GRP_RPL_START_FAILED`; SQLSTATE: `HY000`  
  
Message: The START GROUP\_REPLICATION command failed since the group already has 9 members.
  - Error number: `MY-011521`; Symbol: `ER_GRP_RPL_MEMBER_VER_INCOMPATIBLE`; SQLSTATE: `HY000`  
  
Message: Member version is incompatible with the group.
  - Error number: `MY-011522`; Symbol: `ER_GRP_RPL_TRANS_NOT_PRESENT_IN_GRP`; SQLSTATE: `HY000`  
  
Message: The member contains transactions not present in the group. The member will now exit the group.
  - Error number: `MY-011523`; Symbol: `ER_GRP_RPL_TRANS_GREATER_THAN_GRP`; SQLSTATE: `HY000`  
  
Message: It was not possible to assess if the member has more transactions than the group. The member will now exit the group.
  - Error number: `MY-011524`; Symbol: `ER_GRP_RPL_MEMBER_VERSION_LOWER_THAN_GRP`; SQLSTATE: `HY000`  
  
Message: Member version is lower than some group member, but since option 'group\_replication\_allow\_local\_lower\_version\_join' is enabled, member will be allowed to join.
  - Error number: `MY-011525`; Symbol: `ER_GRP_RPL_LOCAL_GTID_SETS_PROCESS_ERROR`; SQLSTATE: `HY000`  
  
Message: Error processing local GTID sets when comparing this member transactions against the group.
  - Error number: `MY-011526`; Symbol: `ER_GRP_RPL_MEMBER_TRANS_GREATER_THAN_GRP`; SQLSTATE: `HY000`  
  
Message: This member has more executed transactions than those present in the group. Local transactions: %s > Group transactions: %s

- 
- Error number: [MY-011527](#); Symbol: [ER\\_GRP\\_RPL\\_BLOCK\\_SIZE\\_DIFF\\_FROM\\_GRP](#); SQLSTATE: [HY000](#)  
  
Message: The member is configured with a `group_replication_gtid_assignment_block_size` option value '%llu' different from the group '%llu'. The member will now exit the group.
  - Error number: [MY-011528](#); Symbol: [ER\\_GRP\\_RPL\\_TRANS\\_WRITE\\_SET\\_EXTRACT\\_DIFF\\_FROM\\_GRP](#); SQLSTATE: [HY000](#)  
  
Message: The member is configured with a transaction-write-set-extraction option value '%s' different from the group '%s'. The member will now exit the group.
  - Error number: [MY-011529](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_CFG\\_INCOMPATIBLE\\_WITH\\_GRP\\_CFG](#); SQLSTATE: [HY000](#)  
  
Message: The member configuration is not compatible with the group configuration. Variables such as `group_replication_single_primary_mode` or `group_replication_enforce_update_everywhere_checks` must have the same value on every server in the group. (member configuration option: [%s], group configuration option: [%s]).
  - Error number: [MY-011530](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_STOP\\_RPL\\_CHANNELS\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Error stopping all replication channels while server was leaving the group. %s
  - Error number: [MY-011531](#); Symbol: [ER\\_GRP\\_RPL\\_PURGE\\_APPLIER\\_LOGS](#); SQLSTATE: [HY000](#)  
  
Message: Detected previous RESET BINARY LOGS AND GTIDS invocation or an issue exists in the group replication applier relay log. Purging existing applier logs.
  - Error number: [MY-011532](#); Symbol: [ER\\_GRP\\_RPL\\_RESET\\_APPLIER\\_MODULE\\_LOGS\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Unknown error occurred while resetting applier's module logs.
  - Error number: [MY-011533](#); Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_THD\\_SETUP\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Failed to setup the group replication applier thread.
  - Error number: [MY-011534](#); Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_THD\\_START\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Error while starting the group replication applier thread
  - Error number: [MY-011535](#); Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_THD\\_STOP\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Failed to stop the group replication applier thread.
  - Error number: [MY-011536](#); Symbol: [ER\\_GRP\\_RPL\\_FETCH\\_TRANS\\_DATA\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Failed to fetch transaction data containing required transaction info for applier
  - Error number: [MY-011537](#); Symbol: [ER\\_GRP\\_RPL\\_REPLICA\\_IO\\_THD\\_PRIMARY\\_UNKNOWN](#); SQLSTATE: [HY000](#)  
  
Message: Can't start replica IO THREAD of channel '%s' when group replication is running with single-primary mode and the primary member is not known.
  - Error number: [MY-011538](#); Symbol: [ER\\_GRP\\_RPL\\_SALVE\\_IO\\_THD\\_ON\\_SECONDARY\\_MEMBER](#); SQLSTATE: [HY000](#)
-

---

Message: Can't start replica IO THREAD of channel '%s' when group replication is running with single-primary mode on a secondary member.

- Error number: [MY-011539](#); Symbol: [ER\\_GRP\\_RPL\\_REPLICA\\_SQL\\_THD\\_PRIMARY\\_UNKNOWN](#); SQLSTATE: [HY000](#)

Message: Can't start replica SQL THREAD of channel '%s' when group replication is running with single-primary mode and the primary member is not known.

- Error number: [MY-011540](#); Symbol: [ER\\_GRP\\_RPL\\_REPLICA\\_SQL\\_THD\\_ON\\_SECONDARY\\_MEMBER](#); SQLSTATE: [HY000](#)

Message: Can't start replica SQL THREAD of channel '%s' when group replication is running with single-primary mode on a secondary member.

- Error number: [MY-011541](#); Symbol: [ER\\_GRP\\_RPL\\_NEEDS\\_INNODB\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Table %s does not use the InnoDB storage engine. This is not compatible with Group Replication.

- Error number: [MY-011542](#); Symbol: [ER\\_GRP\\_RPL\\_PRIMARY\\_KEY\\_NOT\\_DEFINED](#); SQLSTATE: [HY000](#)

Message: Table %s does not have any PRIMARY KEY. This is not compatible with Group Replication.

- Error number: [MY-011543](#); Symbol: [ER\\_GRP\\_RPL\\_FK\\_WITH\\_CASCADE\\_UNSUPPORTED](#); SQLSTATE: [HY000](#)

Message: Table %s has a foreign key with 'CASCADE', 'SET NULL' or 'SET DEFAULT' clause. This is not compatible with Group Replication.

- Error number: [MY-011544](#); Symbol: [ER\\_GRP\\_RPL\\_AUTO\\_INC\\_RESET](#); SQLSTATE: [HY000](#)

Message: group\_replication\_auto\_increment\_increment is reset to %lu

- Error number: [MY-011545](#); Symbol: [ER\\_GRP\\_RPL\\_AUTO\\_INC\\_OFFSET\\_RESET](#); SQLSTATE: [HY000](#)

Message: auto\_increment\_offset is reset to %lu

- Error number: [MY-011546](#); Symbol: [ER\\_GRP\\_RPL\\_AUTO\\_INC\\_SET](#); SQLSTATE: [HY000](#)

Message: group\_replication\_auto\_increment\_increment is set to %lu

- Error number: [MY-011547](#); Symbol: [ER\\_GRP\\_RPL\\_AUTO\\_INC\\_OFFSET\\_SET](#); SQLSTATE: [HY000](#)

Message: auto\_increment\_offset is set to %lu

- Error number: [MY-011548](#); Symbol: [ER\\_GRP\\_RPL\\_FETCH\\_TRANS\\_CONTEXT\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to fetch transaction context containing required transaction info for certification

- Error number: [MY-011549](#); Symbol: [ER\\_GRP\\_RPL\\_FETCH\\_FORMAT\\_DESC\\_LOG\\_EVENT\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to fetch Format\_description\_log\_event containing required server info for applier



- 
- Error number: `MY-011550`; Symbol: `ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_FAILED`; SQLSTATE: `HY000`  
Message: Failed to fetch Transaction\_context\_log\_event containing required transaction info for certification
  - Error number: `MY-011551`; Symbol: `ER_GRP_RPL_FETCH_SNAPSHOT_VERSION_FAILED`; SQLSTATE: `HY000`  
Message: Failed to read snapshot version from transaction context event required for certification
  - Error number: `MY-011552`; Symbol: `ER_GRP_RPL_FETCH_GTID_LOG_EVENT_FAILED`; SQLSTATE: `HY000`  
Message: Failed to fetch Gtid\_log\_event containing required transaction info for certification
  - Error number: `MY-011553`; Symbol: `ER_GRP_RPL_UPDATE_SERV_CERTIFICATE_FAILED`; SQLSTATE: `HY000`  
Message: Unable to update certification result on server side, thread\_id: %lu
  - Error number: `MY-011554`; Symbol: `ER_GRP_RPL_ADD_GTID_INFO_WITH_LOCAL_GTID_FAILED`; SQLSTATE: `HY000`  
Message: Unable to add gtid information to the group\_gtid\_executed set when gtid was provided for local transactions
  - Error number: `MY-011555`; Symbol: `ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_LOCAL_GTID_FAILED`; SQLSTATE: `HY000`  
Message: Unable to add gtid information to the group\_gtid\_executed set when no gtid was provided for local transactions
  - Error number: `MY-011556`; Symbol: `ER_GRP_RPL_NOTIFY_CERTIFICATION_OUTCOME_FAILED`; SQLSTATE: `HY000`  
Message: Failed to notify certification outcome
  - Error number: `MY-011557`; Symbol: `ER_GRP_RPL_ADD_GTID_INFO_WITH_REMOTE_GTID_FAILED`; SQLSTATE: `HY000`  
Message: Unable to add gtid information to the group\_gtid\_executed set when gtid was provided for remote transactions
  - Error number: `MY-011558`; Symbol: `ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_REMOTE_GTID_FAILED`; SQLSTATE: `HY000`  
Message: Unable to add gtid information to the group\_gtid\_executed set when gtid was not provided for remote transactions
  - Error number: `MY-011559`; Symbol: `ER_GRP_RPL_FETCH_VIEW_CHANGE_LOG_EVENT_FAILED`; SQLSTATE: `HY000`  
Message: Failed to fetch View\_change\_log\_event containing required info for certification
  - Error number: `MY-011562`; Symbol: `ER_GRP_RPL_FETCH_LOG_EVENT_FAILED`; SQLSTATE: `HY000`  
Message: Failed to fetch Log\_event containing required server info for applier
-

- Error number: `MY-011563`; Symbol: `ER_GRP_RPL_START_GRP_RPL_FAILED`; SQLSTATE: `HY000`  
 Message: Unable to start Group Replication. Replication applier infrastructure is not initialized since the server was started with `--initialize`, `--initialize-insecure` or `--upgrade=MINIMAL` on a server upgrade.
- Error number: `MY-011564`; Symbol: `ER_GRP_RPL_CONN_INTERNAL_PLUGIN_FAIL`; SQLSTATE: `HY000`  
 Message: Failed to establish an internal server connection to execute plugin operations
- Error number: `MY-011565`; Symbol: `ER_GRP_RPL_SUPER_READ_ON`; SQLSTATE: `HY000`  
 Message: Setting `super_read_only=ON`.
- Error number: `MY-011566`; Symbol: `ER_GRP_RPL_SUPER_READ_OFF`; SQLSTATE: `HY000`  
 Message: Setting `super_read_only=OFF`.
- Error number: `MY-011567`; Symbol: `ER_GRP_RPL_KILLED_SESSION_ID`; SQLSTATE: `HY000`  
 Message: killed session id: %d status: %d
- Error number: `MY-011568`; Symbol: `ER_GRP_RPL_KILLED_FAILED_ID`; SQLSTATE: `HY000`  
 Message: killed failed id: %d failed: %d
- Error number: `MY-011569`; Symbol: `ER_GRP_RPL_INTERNAL_QUERY`; SQLSTATE: `HY000`  
 Message: Internal query: %s result in error. Error number: %ld
- Error number: `MY-011570`; Symbol: `ER_GRP_RPL_COPY_FROM_EMPTY_STRING`; SQLSTATE: `HY000`  
 Message: Error copying from empty string
- Error number: `MY-011571`; Symbol: `ER_GRP_RPL_QUERY_FAIL`; SQLSTATE: `HY000`  
 Message: Query execution resulted in failure. errno: %d
- Error number: `MY-011572`; Symbol: `ER_GRP_RPL_CREATE_SESSION_UNABLE`; SQLSTATE: `HY000`  
 Message: Unable to create a session for executing the queries on the server
- Error number: `MY-011573`; Symbol: `ER_GRP_RPL_MEMBER_NOT_FOUND`; SQLSTATE: `HY000`  
 Message: The member with address %s:%u has unexpectedly disappeared, killing the current group replication recovery connection
- Error number: `MY-011574`; Symbol: `ER_GRP_RPL_MAXIMUM_CONNECTION_RETRIES_REACHED`; SQLSTATE: `HY000`  
 Message: Maximum number of retries when trying to connect to a donor reached. Aborting group replication incremental recovery.
- Error number: `MY-011575`; Symbol: `ER_GRP_RPL_ALL_DONORS_LEFT_ABORT_RECOVERY`; SQLSTATE: `HY000`  
 Message: All donors left. Aborting group replication incremental recovery.
- Error number: `MY-011576`; Symbol: `ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_DONOR`; SQLSTATE: `HY000`

---

Message: Establishing group recovery connection with a possible donor. Attempt %d/%d

- Error number: [MY-011577](#); Symbol: [ER\\_GRP\\_RPL\\_ESTABLISH\\_RECOVERY\\_WITH\\_ANOTHER\\_DONOR](#); SQLSTATE: [HY000](#)

Message: Retrying group recovery connection with another donor. Attempt %d/%d

- Error number: [MY-011578](#); Symbol: [ER\\_GRP\\_RPL\\_NO\\_VALID\\_DONOR](#); SQLSTATE: [HY000](#)

Message: No valid donors exist in the group, retrying

- Error number: [MY-011579](#); Symbol: [ER\\_GRP\\_RPL\\_CONFIG\\_RECOVERY](#); SQLSTATE: [HY000](#)

Message: Error when configuring the asynchronous recovery channel connection to the donor.

- Error number: [MY-011580](#); Symbol: [ER\\_GRP\\_RPL\\_ESTABLISHING\\_CONN\\_GRP\\_REC\\_DONOR](#); SQLSTATE: [HY000](#)

Message: Establishing connection to a group replication recovery donor %s at %s port: %d.

- Error number: [MY-011581](#); Symbol: [ER\\_GRP\\_RPL\\_CREATE\\_GRP\\_RPL\\_REC\\_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Error while creating the group replication recovery channel with donor %s at %s port: %d.

- Error number: [MY-011582](#); Symbol: [ER\\_GRP\\_RPL\\_DONOR\\_SERVER\\_CONN](#); SQLSTATE: [HY000](#)

Message: There was an error when connecting to the donor server. Please check that group\_replication\_recovery channel credentials and all MEMBER\_HOST column values of performance\_schema.replication\_group\_members table are correct and DNS resolvable.

- Error number: [MY-011583](#); Symbol: [ER\\_GRP\\_RPL\\_CHECK\\_STATUS\\_TABLE](#); SQLSTATE: [HY000](#)

Message: For details please check performance\_schema.replication\_connection\_status table and error log messages of Replica I/O for channel group\_replication\_recovery.

- Error number: [MY-011584](#); Symbol: [ER\\_GRP\\_RPL\\_STARTING\\_GRP\\_REC](#); SQLSTATE: [HY000](#)

Message: Error while starting the group replication incremental recovery receiver/applier threads

- Error number: [MY-011585](#); Symbol: [ER\\_GRP\\_RPL\\_DONOR\\_CONN\\_TERMINATION](#); SQLSTATE: [HY000](#)

Message: Terminating existing group replication donor connection and purging the corresponding logs.

- Error number: [MY-011586](#); Symbol: [ER\\_GRP\\_RPL\\_STOPPING\\_GRP\\_REC](#); SQLSTATE: [HY000](#)

Message: Error when stopping the group replication incremental recovery's donor connection

- Error number: [MY-011587](#); Symbol: [ER\\_GRP\\_RPL\\_PURGE\\_REC](#); SQLSTATE: [HY000](#)

Message: Error when purging the group replication recovery's relay logs

- Error number: [MY-011588](#); Symbol: [ER\\_GRP\\_RPL\\_UNABLE\\_TO\\_KILL\\_CONN\\_REC\\_DONOR\\_APPLIER](#); SQLSTATE: [HY000](#)

Message: Unable to kill the current group replication recovery donor connection after an applier error. Incremental recovery will shutdown.

- Error number: [MY-011589](#); Symbol: [ER\\_GRP\\_RPL\\_UNABLE\\_TO\\_KILL\\_CONN\\_REC\\_DONOR\\_FAILOVER](#); SQLSTATE: [HY000](#)

---

Message: Unable to kill the current group replication recovery donor connection during failover. Incremental recovery will shutdown.

- Error number: `MY-011590`; Symbol: `ER_GRP_RPL_FAILED_TO_NOTIFY_GRP_MEMBERSHIP_EVENT`; SQLSTATE: `HY000`

Message: Unexpected error when notifying an internal component named %s regarding a group membership event.

- Error number: `MY-011591`; Symbol: `ER_GRP_RPL_FAILED_TO_BROADCAST_GRP_MEMBERSHIP_NOTIFICATION`; SQLSTATE: `HY000`

Message: An undefined error was found while broadcasting an internal group membership notification! This is likely to happen if your components or plugins are not properly loaded or are malfunctioning!

- Error number: `MY-011592`; Symbol: `ER_GRP_RPL_FAILED_TO_BROADCAST_MEMBER_STATUS_NOTIFICATION`; SQLSTATE: `HY000`

Message: An undefined error was found while broadcasting an internal group member status notification! This is likely to happen if your components or plugins are not properly loaded or are malfunctioning!

- Error number: `MY-011593`; Symbol: `ER_GRP_RPL_OOM_FAILED_TO_GENERATE_IDENTIFICATION_HASH`; SQLSTATE: `HY000`

Message: No memory to generate write identification hash

- Error number: `MY-011594`; Symbol: `ER_GRP_RPL_WRITE_IDENT_HASH_BASE64_ENCODING_FAILED`; SQLSTATE: `HY000`

Message: Base 64 encoding of the write identification hash failed

- Error number: `MY-011595`; Symbol: `ER_GRP_RPL_INVALID_BINLOG_FORMAT`; SQLSTATE: `HY000`

Message: Binlog format should be ROW for Group Replication

- Error number: `MY-011598`; Symbol: `ER_GRP_RPL_UNSUPPORTED_TRANS_ISOLATION`; SQLSTATE: `HY000`

Message: Transaction isolation level (tx\_isolation) is set to SERIALIZABLE, which is not compatible with Group Replication

- Error number: `MY-011599`; Symbol: `ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_STOPPING`; SQLSTATE: `HY000`

Message: Transaction cannot be executed while Group Replication is stopping.

- Error number: `MY-011600`; Symbol: `ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_RECOVERING`; SQLSTATE: `HY000`

Message: Transaction cannot be executed while Group Replication is recovering. Try again when the server is ONLINE.

- Error number: `MY-011601`; Symbol: `ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_ERROR_STATE`; SQLSTATE: `HY000`

Message: Transaction cannot be executed while Group Replication is on ERROR state. Check for errors and restart the plugin

- 
- Error number: `MY-011602`; Symbol: `ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_OFFLINE_MODE`; SQLSTATE: `HY000`  
Message: Transaction cannot be executed while Group Replication is OFFLINE. Check for errors and restart the plugin
  - Error number: `MY-011603`; Symbol: `ER_GRP_RPL_MULTIPLE_CACHE_TYPE_NOT_SUPPORTED_FOR_SESSION`; SQLSTATE: `HY000`  
Message: We can only use one cache type at a time on session %u
  - Error number: `MY-011604`; Symbol: `ER_GRP_RPL_FAILED_TO_REINIT_BINLOG_CACHE_FOR_READ`; SQLSTATE: `HY000`  
Message: Failed to reinit binlog cache log for read on session %u
  - Error number: `MY-011605`; Symbol: `ER_GRP_RPL_FAILED_TO_CREATE_TRANS_CONTEXT`; SQLSTATE: `HY000`  
Message: Failed to create the context of the current transaction on session %u
  - Error number: `MY-011606`; Symbol: `ER_GRP_RPL_FAILED_TO_EXTRACT_TRANS_WRITE_SET`; SQLSTATE: `HY000`  
Message: Failed to extract the set of items written during the execution of the current transaction on session %u
  - Error number: `MY-011607`; Symbol: `ER_GRP_RPL_FAILED_TO_GATHER_TRANS_WRITE_SET`; SQLSTATE: `HY000`  
Message: Failed to gather the set of items written during the execution of the current transaction on session %u
  - Error number: `MY-011608`; Symbol: `ER_GRP_RPL_TRANS_SIZE_EXCEEDS_LIMIT`; SQLSTATE: `HY000`  
Message: Error on session %u. Transaction of size %llu exceeds specified limit %lu. To increase the limit please adjust `group_replication_transaction_size_limit` option.
  - Error number: `MY-011611`; Symbol: `ER_GRP_RPL_WRITE_TO_TRANSACTION_MESSAGE_FAILED`; SQLSTATE: `HY000`  
Message: Error while writing to transaction message on session %u
  - Error number: `MY-011612`; Symbol: `ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_OUTCOME_NOTIFICATION`; SQLSTATE: `HY000`  
Message: Unable to register for getting notifications regarding the outcome of the transaction on session %u
  - Error number: `MY-011613`; Symbol: `ER_GRP_RPL_MSG_TOO_LONG_BROADCASTING_TRANS_FAILED`; SQLSTATE: `HY000`  
Message: Error broadcasting transaction to the group on session %u. Message is too big.
  - Error number: `MY-011614`; Symbol: `ER_GRP_RPL_BROADCASTING_TRANS_TO_GRP_FAILED`; SQLSTATE: `HY000`  
Message: Error while broadcasting the transaction to the group on session %u
  - Error number: `MY-011615`; Symbol: `ER_GRP_RPL_ERROR_WHILE_WAITING_FOR_CONFLICT_DETECTION`; SQLSTATE: `HY000`
-

---

Message: Error while waiting for conflict detection procedure to finish on session %u

- Error number: `MY-011620`; Symbol: `ER_GRP_RPL_FATAL_REC_PROCESS`; SQLSTATE: `HY000`

Message: Fatal error during the incremental recovery process of Group Replication. The server will leave the group.

- Error number: `MY-011622`; Symbol: `ER_GRP_RPL_UNABLE_TO_EVALUATE_APPLIER_STATUS`; SQLSTATE: `HY000`

Message: Unable to evaluate the group replication applier execution status. Group replication recovery will shutdown to avoid data corruption.

- Error number: `MY-011623`; Symbol: `ER_GRP_RPL_ONLY_ONE_SERVER_ALIVE`; SQLSTATE: `HY000`

Message: Only one server alive. Declaring this server as online within the replication group

- Error number: `MY-011624`; Symbol: `ER_GRP_RPL_CERTIFICATION_REC_PROCESS`; SQLSTATE: `HY000`

Message: Error when processing certification information in the incremental recovery process

- Error number: `MY-011625`; Symbol: `ER_GRP_RPL_UNABLE_TO_ENSURE_EXECUTION_REC`; SQLSTATE: `HY000`

Message: Unable to ensure the execution of group transactions received during recovery.

- Error number: `MY-011626`; Symbol: `ER_GRP_RPL_WHILE_SENDING_MSG_REC`; SQLSTATE: `HY000`

Message: Error while sending message in the group replication incremental recovery process.

- Error number: `MY-011628`; Symbol: `ER_GRP_RPL_READ_UNABLE_FOR_READ_ONLY_SUPER_READ_ONLY`; SQLSTATE: `HY000`

Message: Unable to read the server values for the `read_only` and `super_read_only` variables.

- Error number: `MY-011629`; Symbol: `ER_GRP_RPL_UNABLE_TO_RESET_SERVER_READ_MODE`; SQLSTATE: `HY000`

Message: Unable to reset the server read mode settings. Try to reset them manually.

- Error number: `MY-011630`; Symbol: `ER_GRP_RPL_UNABLE_TO_CERTIFY_PLUGIN_TRANS`; SQLSTATE: `HY000`

Message: Due to a plugin error, some transactions were unable to be certified and will now rollback.

- Error number: `MY-011631`; Symbol: `ER_GRP_RPL_UNBLOCK_CERTIFIED_TRANS`; SQLSTATE: `HY000`

Message: Error when trying to unblock non certified or consistent transactions. Check for consistency errors when restarting the service

- Error number: `MY-011633`; Symbol: `ER_GRP_RPL_FAILED_TO_START_WITH_INVALID_SERVER_ID`; SQLSTATE: `HY000`

Message: Unable to start Group Replication. Replication applier infrastructure is not initialized since the server was started with `server_id=0`. Please, restart the server with `server_id` larger than 0.

- Error number: `MY-011634`; Symbol: `ER_GRP_RPL_FORCE_MEMBERS_MUST_BE_EMPTY`; SQLSTATE: `HY000`

---

Message: group\_replication\_force\_members must be empty on group start. Current value: '%s'

- Error number: MY-011635; Symbol: ER\_GRP\_RPL\_PLUGIN\_STRUCT\_INIT\_NOT\_POSSIBLE\_ON\_SERVER\_START; SQLSTATE: HY000

Message: It was not possible to guarantee the initialization of plugin structures on server start

- Error number: MY-011636; Symbol: ER\_GRP\_RPL\_FAILED\_TO\_ENABLE\_SUPER\_READ\_ONLY\_MODE; SQLSTATE: HY000

Message: Could not enable the server read only mode and guarantee a safe recovery execution

- Error number: MY-011637; Symbol: ER\_GRP\_RPL\_FAILED\_TO\_INIT\_COMMUNICATION\_ENGINE; SQLSTATE: HY000

Message: Error on group communication engine initialization

- Error number: MY-011638; Symbol: ER\_GRP\_RPL\_FAILED\_TO\_START\_ON\_SECONDARY\_WITH\_ASYNC\_CHANNELS; SQLSTATE: HY000

Message: Can't start group replication on secondary member with single-primary mode while asynchronous replication channels are running.

- Error number: MY-011639; Symbol: ER\_GRP\_RPL\_FAILED\_TO\_START\_COMMUNICATION\_ENGINE; SQLSTATE: HY000

Message: Error on group communication engine start

- Error number: MY-011640; Symbol: ER\_GRP\_RPL\_TIMEOUT\_ON\_VIEW\_AFTER\_JOINING\_GRP; SQLSTATE: HY000

Message: Timeout on wait for view after joining group

- Error number: MY-011641; Symbol: ER\_GRP\_RPL\_FAILED\_TO\_CALL\_GRP\_COMMUNICATION\_INTERFACE; SQLSTATE: HY000

Message: Error calling group communication interfaces

- Error number: MY-011642; Symbol: ER\_GRP\_RPL\_MEMBER\_SERVER\_UUID\_IS\_INCOMPATIBLE\_WITH\_GRP; SQLSTATE: HY000

Message: Member server\_uuid is incompatible with the group. Server\_uuid %s matches group\_replication\_group\_name %s.

- Error number: MY-011643; Symbol: ER\_GRP\_RPL\_MEMBER\_CONF\_INFO; SQLSTATE: HY000

Message: Member configuration: member\_id: %lu; member\_uuid: "%s"; single-primary mode: "%s"; group\_replication\_auto\_increment\_increment: %lu; group\_replication\_view\_change\_uuid: "%s";

- Error number: MY-011644; Symbol: ER\_GRP\_RPL\_FAILED\_TO\_CONFIRM\_IF\_SERVER\_LEFT\_GRP; SQLSTATE: HY000

Message: Unable to confirm whether the server has left the group or not. Check performance\_schema.replication\_group\_members to check group membership information.

- Error number: MY-011645; Symbol: ER\_GRP\_RPL\_SERVER\_IS\_ALREADY\_LEAVING; SQLSTATE: HY000

Message: Skipping leave operation: concurrent attempt to leave the group is on-going.

- Error number: MY-011646; Symbol: ER\_GRP\_RPL\_SERVER\_ALREADY\_LEFT; SQLSTATE: HY000

---

Message: Skipping leave operation: member already left the group.

- Error number: MY-011647; Symbol: ER\_GRP\_RPL\_WAITING\_FOR\_VIEW\_UPDATE; SQLSTATE: HY000

Message: Going to wait for view modification

- Error number: MY-011648; Symbol: ER\_GRP\_RPL\_TIMEOUT\_RECEIVING\_VIEW\_CHANGE\_ON\_SHUTDOWN; SQLSTATE: HY000

Message: While leaving the group due to a stop, shutdown or failure there was a timeout receiving a view change. This can lead to a possible inconsistent state. Check the log for more details

- Error number: MY-011649; Symbol: ER\_GRP\_RPL\_REQUESTING\_NON\_MEMBER\_SERVER\_TO\_LEAVE; SQLSTATE: HY000

Message: Requesting to leave the group despite of not being a member

- Error number: MY-011650; Symbol: ER\_GRP\_RPL\_IS\_STOPPING; SQLSTATE: HY000

Message: Plugin 'group\_replication' is stopping.

- Error number: MY-011651; Symbol: ER\_GRP\_RPL\_IS\_STOPPED; SQLSTATE: HY000

Message: Plugin 'group\_replication' has been stopped.

- Error number: MY-011652; Symbol: ER\_GRP\_RPL\_FAILED\_TO\_ENABLE\_READ\_ONLY\_MODE\_ON\_SHUTDOWN; SQLSTATE: HY000

Message: On plugin shutdown it was not possible to enable the server read only mode. Local transactions will be accepted and committed.

- Error number: MY-011653; Symbol: ER\_GRP\_RPL\_RECOVERY\_MODULE\_TERMINATION\_TIMED\_OUT\_ON\_SHUTDOWN; SQLSTATE: HY000

Message: On shutdown there was a timeout on the Group Replication recovery module termination. Check the log for more details

- Error number: MY-011654; Symbol: ER\_GRP\_RPL\_APPLIER\_TERMINATION\_TIMED\_OUT\_ON\_SHUTDOWN; SQLSTATE: HY000

Message: On shutdown there was a timeout on the Group Replication applier termination.

- Error number: MY-011655; Symbol: ER\_GRP\_RPL\_FAILED\_TO\_SHUTDOWN\_REGISTRY\_MODULE; SQLSTATE: HY000

Message: Unexpected failure while shutting down registry module!

- Error number: MY-011656; Symbol: ER\_GRP\_RPL\_FAILED\_TO\_INIT\_HANDLER; SQLSTATE: HY000

Message: Failure during Group Replication handler initialization

- Error number: MY-011657; Symbol: ER\_GRP\_RPL\_FAILED\_TO\_REGISTER\_SERVER\_STATE\_OBSERVER; SQLSTATE: HY000

Message: Failure when registering the server state observers

- Error number: MY-011658; Symbol: ER\_GRP\_RPL\_FAILED\_TO\_REGISTER\_TRANS\_STATE\_OBSERVER; SQLSTATE: HY000

Message: Failure when registering the transactions state observers



- 
- Error number: [MY-011659](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_REGISTER\\_BINLOG\\_STATE\\_OBSERVER](#); SQLSTATE: [HY000](#)  
Message: Failure when registering the binlog state observers
  - Error number: [MY-011660](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_START\\_ON\\_BOOT](#); SQLSTATE: [HY000](#)  
Message: Unable to start Group Replication on boot
  - Error number: [MY-011661](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_STOP\\_ON\\_PLUGIN\\_UNINSTALL](#); SQLSTATE: [HY000](#)  
Message: Failure when stopping Group Replication on plugin uninstall
  - Error number: [MY-011662](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_UNREGISTER\\_SERVER\\_STATE\\_OBSERVER](#); SQLSTATE: [HY000](#)  
Message: Failure when unregistering the server state observers
  - Error number: [MY-011663](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_UNREGISTER\\_TRANS\\_STATE\\_OBSERVER](#); SQLSTATE: [HY000](#)  
Message: Failure when unregistering the transactions state observers
  - Error number: [MY-011664](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_UNREGISTER\\_BINLOG\\_STATE\\_OBSERVER](#); SQLSTATE: [HY000](#)  
Message: Failure when unregistering the binlog state observers
  - Error number: [MY-011665](#); Symbol: [ER\\_GRP\\_RPL\\_ALL\\_OBSERVERS\\_UNREGISTERED](#); SQLSTATE: [HY000](#)  
Message: All Group Replication server observers have been successfully unregistered
  - Error number: [MY-011666](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_PARSE\\_THE\\_GRP\\_NAME](#); SQLSTATE: [HY000](#)  
Message: Unable to parse the group\_replication\_group\_name.
  - Error number: [MY-011667](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_GENERATE\\_SIDNO\\_FOR\\_GRP](#); SQLSTATE: [HY000](#)  
Message: Unable to parse the group\_replication\_group\_name.
  - Error number: [MY-011668](#); Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_NOT\\_STARTED\\_DUE\\_TO\\_RUNNING\\_PREV\\_SHUTDOWN](#); SQLSTATE: [HY000](#)  
Message: Cannot start the Group Replication applier as a previous shutdown is still running: The thread will stop once its task is complete.
  - Error number: [MY-011669](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_INIT\\_APPLIER\\_MODULE](#); SQLSTATE: [HY000](#)  
Message: Unable to initialize the Group Replication applier module.
  - Error number: [MY-011670](#); Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_INITIALIZED](#); SQLSTATE: [HY000](#)  
Message: Group Replication applier module successfully initialized!
  - Error number: [MY-011671](#); Symbol: [ER\\_GRP\\_RPL\\_COMMUNICATION\\_SSL\\_CONF\\_INFO](#); SQLSTATE: [HY000](#)
-

---

Message: Group communication SSL configuration: group\_replication\_ssl\_mode: "%s"; server\_key\_file: "%s"; server\_cert\_file: "%s"; client\_key\_file: "%s"; client\_cert\_file: "%s"; ca\_file: "%s"; ca\_path: "%s"; cipher: "%s"; tls\_version: "%s"; tls\_ciphersuites: "%s"; crl\_file: "%s"; crl\_path: "%s"; ssl\_fips\_mode: "%s"

- Error number: [MY-011672](#); Symbol:

[ER\\_GRP\\_RPL\\_ABORTS\\_AS\\_SSL\\_NOT\\_SUPPORTED\\_BY\\_MYSQLD](#); SQLSTATE: HY000

Message: MySQL server does not have SSL support and group\_replication\_ssl\_mode is "%s", START GROUP\_REPLICATION will abort

- Error number: [MY-011673](#); Symbol: [ER\\_GRP\\_RPL\\_SSL\\_DISABLED](#); SQLSTATE: HY000

Message: Group communication SSL configuration: group\_replication\_ssl\_mode: "%s"

- Error number: [MY-011674](#); Symbol: [ER\\_GRP\\_RPL\\_UNABLE\\_TO\\_INIT\\_COMMUNICATION\\_ENGINE](#); SQLSTATE: HY000

Message: Unable to initialize the group communication engine

- Error number: [MY-011675](#); Symbol: [ER\\_GRP\\_RPL\\_BINLOG\\_DISABLED](#); SQLSTATE: HY000

Message: Binlog must be enabled for Group Replication

- Error number: [MY-011676](#); Symbol: [ER\\_GRP\\_RPL\\_GTID\\_MODE\\_OFF](#); SQLSTATE: HY000

Message: Gtid mode should be ON for Group Replication

- Error number: [MY-011677](#); Symbol: [ER\\_GRP\\_RPL\\_LOG\\_REPLICA\\_UPDATES\\_NOT\\_SET](#); SQLSTATE: HY000

Message: LOG\_REPLICA\_UPDATES should be ON for Group Replication

- Error number: [MY-011679](#); Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_METADATA\\_REPO\\_MUST\\_BE\\_TABLE](#); SQLSTATE: HY000

Message: Applier metadata repository must be set to TABLE

- Error number: [MY-011680](#); Symbol:

[ER\\_GRP\\_RPL\\_CONNECTION\\_METADATA\\_REPO\\_MUST\\_BE\\_TABLE](#); SQLSTATE: HY000

Message: Connection metadata repository must be set to TABLE.

- Error number: [MY-011681](#); Symbol:

[ER\\_GRP\\_RPL\\_INCORRECT\\_TYPE\\_SET\\_FOR\\_PARALLEL\\_APPLIER](#); SQLSTATE: HY000

Message: In order to use parallel applier on Group Replication, parameter replica-parallel-type must be set to 'LOGICAL\_CLOCK'.

- Error number: [MY-011682](#); Symbol:

[ER\\_GRP\\_RPL\\_REPLICA\\_PRESERVE\\_COMMIT\\_ORDER\\_NOT\\_SET](#); SQLSTATE: HY000

Message: Group Replication requires replica-preserve-commit-order to be set to ON when using more than 1 applier threads.

- Error number: [MY-011683](#); Symbol:

[ER\\_GRP\\_RPL\\_SINGLE\\_PRIM\\_MODE\\_NOT\\_ALLOWED\\_WITH\\_UPDATE\\_EVERYWHERE](#); SQLSTATE: HY000

Message: It is not allowed to run single primary mode with 'group\_replication\_enforce\_update\_everywhere\_checks' enabled.

- 
- Error number: `MY-011684`; Symbol: `ER_GRP_RPL_MODULE_TERMINATE_ERROR`; SQLSTATE: `HY000`  
Message: `error_message: %s`
  - Error number: `MY-011685`; Symbol: `ER_GRP_RPL_GRP_NAME_OPTION_MANDATORY`; SQLSTATE: `HY000`  
Message: The `group_replication_group_name` option is mandatory
  - Error number: `MY-011686`; Symbol: `ER_GRP_RPL_GRP_NAME_IS_TOO_LONG`; SQLSTATE: `HY000`  
Message: The `group_replication_group_name` '`%s`' is not a valid UUID, its length is too big
  - Error number: `MY-011687`; Symbol: `ER_GRP_RPL_GRP_NAME_IS_NOT_VALID_UUID`; SQLSTATE: `HY000`  
Message: The `group_replication_group_name` '`%s`' is not a valid UUID
  - Error number: `MY-011688`; Symbol: `ER_GRP_RPL_FLOW_CTRL_MIN_QUOTA_GREATER_THAN_MAX_QUOTA`; SQLSTATE: `HY000`  
Message: `group_replication_flow_control_min_quota` cannot be larger than `group_replication_flow_control_max_quota`
  - Error number: `MY-011689`; Symbol: `ER_GRP_RPL_FLOW_CTRL_MIN_RECOVERY_QUOTA_GREATER_THAN_MAX_QUOTA`; SQLSTATE: `HY000`  
Message: `group_replication_flow_control_min_recovery_quota` cannot be larger than `group_replication_flow_control_max_quota`
  - Error number: `MY-011690`; Symbol: `ER_GRP_RPL_FLOW_CTRL_MAX_QUOTA_SMALLER_THAN_MIN_QUOTAS`; SQLSTATE: `HY000`  
Message: `group_replication_flow_control_max_quota` cannot be smaller than `group_replication_flow_control_min_quota` or `group_replication_flow_control_min_recovery_quota`
  - Error number: `MY-011691`; Symbol: `ER_GRP_RPL_INVALID_SSL_RECOVERY_STRING`; SQLSTATE: `HY000`  
Message: The given value for recovery ssl option '`group_replication_%s`' is invalid as its length is beyond the limit
  - Error number: `MY-011694`; Symbol: `ER_GRP_RPL_GRP_COMMUNICATION_INIT_WITH_CONF`; SQLSTATE: `HY000`  
Message: Initialized group communication with configuration: `group_replication_group_name: '%s'`; `group_replication_local_address: '%s'`; `group_replication_group_seeds: '%s'`; `group_replication_bootstrap_group: '%s'`; `group_replication_poll_spin_loops: %lu`; `group_replication_compression_threshold: %lu`; `group_replication_ip_allowlist: '%s'`; `group_replication_communication_debug_options: '%s'`; `group_replication_member_expel_timeout: %lu`; `group_replication_communication_max_message_size: %lu`; `group_replication_message_cache_size: %lu`; `group_replication_communication_stack: %lu'`
  - Error number: `MY-011695`; Symbol: `ER_GRP_RPL_UNKNOWN_GRP_RPL_APPLIER_PIPELINE_REQUESTED`; SQLSTATE: `HY000`  
Message: Unknown group replication applier pipeline requested
  - Error number: `MY-011696`; Symbol: `ER_GRP_RPL_FAILED_TO_BOOTSTRAP_EVENT_HANDLING_INFRASTRUCTURE`; SQLSTATE: `HY000`
-

---

Message: Unable to bootstrap group replication event handling infrastructure. Unknown handler type: %d

- Error number: MY-011697; Symbol: ER\_GRP\_RPL\_APPLIER\_HANDLER\_NOT\_INITIALIZED; SQLSTATE: HY000

Message: One of the group replication applier handlers is null due to an initialization error

- Error number: MY-011698; Symbol: ER\_GRP\_RPL\_APPLIER\_HANDLER\_IS\_IN\_USE; SQLSTATE: HY000

Message: A group replication applier handler, marked as unique, is already in use.

- Error number: MY-011699; Symbol: ER\_GRP\_RPL\_APPLIER\_HANDLER\_ROLE\_IS\_IN\_USE; SQLSTATE: HY000

Message: A group replication applier handler role, that was marked as unique, is already in use.

- Error number: MY-011700; Symbol: ER\_GRP\_RPL\_FAILED\_TO\_INIT\_APPLIER\_HANDLER; SQLSTATE: HY000

Message: Error on group replication applier handler initialization

- Error number: MY-011701; Symbol: ER\_GRP\_RPL\_SQL\_SERVICE\_FAILED\_TO\_INIT\_SESSION\_THREAD; SQLSTATE: HY000

Message: Error when initializing a session thread for internal server connection.

- Error number: MY-011702; Symbol: ER\_GRP\_RPL\_SQL\_SERVICE\_COMM\_SESSION\_NOT\_INITIALIZED; SQLSTATE: HY000

Message: Error running internal SQL query: %s. The internal server communication session is not initialized

- Error number: MY-011703; Symbol: ER\_GRP\_RPL\_SQL\_SERVICE\_SERVER\_SESSION\_KILLED; SQLSTATE: HY000

Message: Error running internal SQL query: %s. The internal server session was killed or server is shutting down.

- Error number: MY-011704; Symbol: ER\_GRP\_RPL\_SQL\_SERVICE\_FAILED\_TO\_RUN\_SQL\_QUERY; SQLSTATE: HY000

Message: Error running internal SQL query: %s. Got internal SQL error: %s(%d)

- Error number: MY-011705; Symbol: ER\_GRP\_RPL\_SQL\_SERVICE\_SERVER\_INTERNAL\_FAILURE; SQLSTATE: HY000

Message: Error running internal SQL query: %s. Internal failure.

- Error number: MY-011706; Symbol: ER\_GRP\_RPL\_SQL\_SERVICE\_RETRIES\_EXCEEDED\_ON\_SESSION\_STATE; SQLSTATE: HY000

Message: Error, maximum number of retries exceeded when waiting for the internal server session state to be operating

- Error number: MY-011707; Symbol: ER\_GRP\_RPL\_SQL\_SERVICE\_FAILED\_TO\_FETCH\_SECURITY\_CTX; SQLSTATE: HY000

Message: Error when trying to fetch security context when contacting the server for internal plugin requests.

- 
- Error number: [MY-011708](#); Symbol: [ER\\_GRP\\_RPL\\_SQL\\_SERVICE\\_SERVER\\_ACCESS\\_DENIED\\_FOR\\_USER](#); SQLSTATE: [HY000](#)  
Message: There was an error when trying to access the server with user: %s. Make sure the user is present in the server and that the MySQL upgrade procedure was run correctly.
  - Error number: [MY-011709](#); Symbol: [ER\\_GRP\\_RPL\\_SQL\\_SERVICE\\_MAX\\_CONN\\_ERROR\\_FROM\\_SERVER](#); SQLSTATE: [HY000](#)  
Message: Failed to establish an internal server connection to execute plugin operations since the server does not have available connections, please increase @@GLOBAL.MAX\_CONNECTIONS. Server error: %i.
  - Error number: [MY-011710](#); Symbol: [ER\\_GRP\\_RPL\\_SQL\\_SERVICE\\_SERVER\\_ERROR\\_ON\\_CONN](#); SQLSTATE: [HY000](#)  
Message: Failed to establish an internal server connection to execute plugin operations. Server error: %i. Server error message: %s
  - Error number: [MY-011711](#); Symbol: [ER\\_GRP\\_RPL\\_UNREACHABLE\\_MAJORITY\\_TIMEOUT\\_FOR\\_MEMBER](#); SQLSTATE: [HY000](#)  
Message: This member could not reach a majority of the members for more than %ld seconds. The member will now leave the group as instructed by the group\_replication\_unreachable\_majority\_timeout option.
  - Error number: [MY-011712](#); Symbol: [ER\\_GRP\\_RPL\\_SERVER\\_SET\\_TO\\_READ\\_ONLY\\_DUE\\_TO\\_ERRORS](#); SQLSTATE: [HY000](#)  
Message: The server was automatically set into read only mode after an error was detected.
  - Error number: [MY-011713](#); Symbol: [ER\\_GRP\\_RPL\\_GMS\\_LISTENER\\_FAILED\\_TO\\_LOG\\_NOTIFICATION](#); SQLSTATE: [HY000](#)  
Message: Unable to log notification to table (errno: %lu) (res: %d)! Message: %s
  - Error number: [MY-011714](#); Symbol: [ER\\_GRP\\_RPL\\_GRP\\_COMMUNICATION\\_ENG\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failure in group communication engine '%s' initialization
  - Error number: [MY-011715](#); Symbol: [ER\\_GRP\\_RPL\\_SET\\_GRP\\_COMMUNICATION\\_ENG\\_LOGGER\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Unable to set the group communication engine logger
  - Error number: [MY-011716](#); Symbol: [ER\\_GRP\\_RPL\\_DEBUG\\_OPTIONS](#); SQLSTATE: [HY000](#)  
Message: Current debug options are: '%s'.
  - Error number: [MY-011717](#); Symbol: [ER\\_GRP\\_RPL\\_INVALID\\_DEBUG\\_OPTIONS](#); SQLSTATE: [HY000](#)  
Message: Some debug options in '%s' are not valid.
  - Error number: [MY-011718](#); Symbol: [ER\\_GRP\\_RPL\\_EXIT\\_GRP\\_GCS\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Error calling group communication interfaces while trying to leave the group
  - Error number: [MY-011719](#); Symbol: [ER\\_GRP\\_RPL\\_GRP\\_MEMBER\\_OFFLINE](#); SQLSTATE: [HY000](#)  
Message: Member is not ONLINE, it is not possible to force a new group membership
-

- 
- Error number: [MY-011720](#); Symbol: [ER\\_GRP\\_RPL\\_GCS\\_INTERFACE\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Error calling group communication interfaces
  - Error number: [MY-011721](#); Symbol: [ER\\_GRP\\_RPL\\_FORCE\\_MEMBER\\_VALUE\\_SET\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Error setting group\_replication\_force\_members value '%s' on group communication interfaces
  - Error number: [MY-011722](#); Symbol: [ER\\_GRP\\_RPL\\_FORCE\\_MEMBER\\_VALUE\\_SET](#); SQLSTATE: [HY000](#)  
Message: The group\_replication\_force\_members value '%s' was set in the group communication interfaces
  - Error number: [MY-011723](#); Symbol: [ER\\_GRP\\_RPL\\_FORCE\\_MEMBER\\_VALUE\\_TIME\\_OUT](#); SQLSTATE: [HY000](#)  
Message: Timeout on wait for view after setting group\_replication\_force\_members value '%s' into group communication interfaces
  - Error number: [MY-011724](#); Symbol: [ER\\_GRP\\_RPL\\_BROADCAST\\_COMMIT\\_MSSG\\_TOO\\_BIG](#); SQLSTATE: [HY000](#)  
Message: Broadcast of committed transactions message failed. Message is too big.
  - Error number: [MY-011725](#); Symbol: [ER\\_GRP\\_RPL\\_SEND\\_STATS\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Error while sending stats message
  - Error number: [MY-011726](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_STATS\\_INFO](#); SQLSTATE: [HY000](#)  
Message: Flow control - update member stats: %s stats certifier\_queue %d, applier\_queue %d certified %ld (%ld), applied %ld (%ld), local %ld (%ld), quota %ld (%ld) mode=%d
  - Error number: [MY-011727](#); Symbol: [ER\\_GRP\\_RPL\\_FLOW\\_CONTROL\\_STATS](#); SQLSTATE: [HY000](#)  
Message: Flow control: throttling to %ld commits per %ld sec, with %d writing and %d non-recovering members, min capacity %lld, lim throttle %lld
  - Error number: [MY-011728](#); Symbol: [ER\\_GRP\\_RPL\\_UNABLE\\_TO\\_CONVERT\\_PACKET\\_TO\\_EVENT](#); SQLSTATE: [HY000](#)  
Message: Unable to convert a packet into an event on the applier. Error: %s
  - Error number: [MY-011729](#); Symbol: [ER\\_GRP\\_RPL\\_PIPELINE\\_CREATE\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to create group replication pipeline cache.
  - Error number: [MY-011730](#); Symbol: [ER\\_GRP\\_RPL\\_PIPELINE\\_REINIT\\_FAILED\\_WRITE](#); SQLSTATE: [HY000](#)  
Message: Failed to reinit group replication pipeline cache for write.
  - Error number: [MY-011731](#); Symbol: [ER\\_GRP\\_RPL\\_UNABLE\\_TO\\_CONVERT\\_EVENT\\_TO\\_PACKET](#); SQLSTATE: [HY000](#)  
Message: Unable to convert the event into a packet on the applier. Error: %s
  - Error number: [MY-011732](#); Symbol: [ER\\_GRP\\_RPL\\_PIPELINE\\_FLUSH\\_FAIL](#); SQLSTATE: [HY000](#)  
Message: Failed to flush group replication pipeline cache.

- 
- Error number: `MY-011733`; Symbol: `ER_GRP_RPL_PIPELINE_REINIT_FAILED_READ`; SQLSTATE: `HY000`  
Message: Failed to reinit group replication pipeline cache for read.
  - Error number: `MY-011735`; Symbol: `ER_GRP_RPL_GCS_GR_ERROR_MSG`; SQLSTATE: `HY000`  
Message: %s
  - Error number: `MY-011736`; Symbol: `ER_GRP_RPL_REPLICA_IO_THREAD_UNBLOCKED`; SQLSTATE: `HY000`  
Message: The replica IO thread of channel '%s' is unblocked as the member is declared ONLINE now.
  - Error number: `MY-011737`; Symbol: `ER_GRP_RPL_REPLICA_IO_THREAD_ERROR_OUT`; SQLSTATE: `HY000`  
Message: The replica IO thread of channel '%s' will error out as the member failed to come ONLINE.
  - Error number: `MY-011738`; Symbol: `ER_GRP_RPL_REPLICA_APPLIER_THREAD_UNBLOCKED`; SQLSTATE: `HY000`  
Message: The replica applier thread of channel '%s' is unblocked as the member is declared ONLINE now.
  - Error number: `MY-011739`; Symbol: `ER_GRP_RPL_REPLICA_APPLIER_THREAD_ERROR_OUT`; SQLSTATE: `HY000`  
Message: The replica applier thread of channel '%s' will error out as the member failed to come ONLINE.
  - Error number: `MY-011740`; Symbol: `ER_LDAP_AUTH_FAILED_TO_CREATE_OR_GET_CONNECTION`; SQLSTATE: `HY000`  
Message: LDAP authentication initialize: failed to create/ get connection from the pool.
  - Error number: `MY-011741`; Symbol: `ER_LDAP_AUTH_DEINIT_FAILED`; SQLSTATE: `HY000`  
Message: LDAP authentication de\_initialize Failed
  - Error number: `MY-011742`; Symbol: `ER_LDAP_AUTH_SKIPPING_USER_GROUP_SEARCH`; SQLSTATE: `HY000`  
Message: Skipping group search, No group attribute mentioned
  - Error number: `MY-011743`; Symbol: `ER_LDAP_AUTH_POOL_DISABLE_MAX_SIZE_ZERO`; SQLSTATE: `HY000`  
Message: Pool max size is 0, connection pool is disabled
  - Error number: `MY-011744`; Symbol: `ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT_CREATOR`; SQLSTATE: `HY000`  
Message: Connection pool initialization, failed to create LDAP object creator
  - Error number: `MY-011745`; Symbol: `ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT`; SQLSTATE: `HY000`  
Message: Connection pool initialization, failed to create LDAP object
  - Error number: `MY-011746`; Symbol: `ER_LDAP_AUTH_TLS_CONF`; SQLSTATE: `HY000`  
Message: LDAP TLS configuration
-

- 
- Error number: [MY-011747](#); Symbol: [ER\\_LDAP\\_AUTH\\_TLS\\_CONNECTION](#); SQLSTATE: [HY000](#)  
Message: LDAP TLS connection
  - Error number: [MY-011748](#); Symbol: [ER\\_LDAP\\_AUTH\\_CONN\\_POOL\\_NOT\\_CREATED](#); SQLSTATE: [HY000](#)  
Message: LDAP pool is not created.
  - Error number: [MY-011749](#); Symbol: [ER\\_LDAP\\_AUTH\\_CONN\\_POOL\\_INITIALIZING](#); SQLSTATE: [HY000](#)  
Message: LDAP pool is initializing
  - Error number: [MY-011750](#); Symbol: [ER\\_LDAP\\_AUTH\\_CONN\\_POOL\\_DEINITIALIZING](#); SQLSTATE: [HY000](#)  
Message: LDAP pool is de-initializing
  - Error number: [MY-011751](#); Symbol: [ER\\_LDAP\\_AUTH\\_ZERO\\_MAX\\_POOL\\_SIZE\\_UNCHANGED](#); SQLSTATE: [HY000](#)  
Message: Pool max size old and new values are 0
  - Error number: [MY-011752](#); Symbol: [ER\\_LDAP\\_AUTH\\_POOL\\_REINITIALIZING](#); SQLSTATE: [HY000](#)  
Message: LDAP pool is re-initializing
  - Error number: [MY-011753](#); Symbol: [ER\\_LDAP\\_AUTH\\_FAILED\\_TO\\_WRITE\\_PACKET](#); SQLSTATE: [HY000](#)  
Message: Plug-in has failed to write the packet.
  - Error number: [MY-011754](#); Symbol: [ER\\_LDAP\\_AUTH\\_SETTING\\_USERNAME](#); SQLSTATE: [HY000](#)  
Message: Setting LDAP user name as : %s
  - Error number: [MY-011755](#); Symbol: [ER\\_LDAP\\_AUTH\\_USER\\_AUTH\\_DATA](#); SQLSTATE: [HY000](#)  
Message: User authentication data: %s size: %lu
  - Error number: [MY-011756](#); Symbol: [ER\\_LDAP\\_AUTH\\_INFO\\_FOR\\_USER](#); SQLSTATE: [HY000](#)  
Message: User is authenticated as: %s external user: %s
  - Error number: [MY-011757](#); Symbol: [ER\\_LDAP\\_AUTH\\_USER\\_GROUP\\_SEARCH\\_INFO](#); SQLSTATE: [HY000](#)  
Message: Group search information base DN: %s scope: %d filter: %s attribute: %s
  - Error number: [MY-011758](#); Symbol: [ER\\_LDAP\\_AUTH\\_GRP\\_SEARCH\\_SPECIAL\\_HDL](#); SQLSTATE: [HY000](#)  
Message: Special handling for group search, {GA} found
  - Error number: [MY-011759](#); Symbol: [ER\\_LDAP\\_AUTH\\_GRP\\_IS\\_FULL\\_DN](#); SQLSTATE: [HY000](#)  
Message: Group search special handling, group full DN found.
  - Error number: [MY-011760](#); Symbol: [ER\\_LDAP\\_AUTH\\_USER\\_NOT\\_FOUND\\_IN\\_ANY\\_GRP](#); SQLSTATE: [HY000](#)  
Message: User %s is not member of any group.



- 
- Error number: `MY-011761`; Symbol: `ER_LDAP_AUTH_USER_FOUND_IN_MANY_GRP`; SQLSTATE: `HY000`  
Message: User %s is member of more than one group
  - Error number: `MY-011762`; Symbol: `ER_LDAP_AUTH_USER_HAS_MULTIPLE_GRP_NAMES`; SQLSTATE: `HY000`  
Message: For user %s has multiple user group names. Please check if group attribute name is correct
  - Error number: `MY-011763`; Symbol: `ER_LDAP_AUTH_SEARCHED_USER_GRP_NAME`; SQLSTATE: `HY000`  
Message: Searched group name: %s
  - Error number: `MY-011764`; Symbol: `ER_LDAP_AUTH_OBJECT_CREATE_TIMESTAMP`; SQLSTATE: `HY000`  
Message: LDAP authentication object creation time\_stamp: %s dn: %s
  - Error number: `MY-011765`; Symbol: `ER_LDAP_AUTH_CERTIFICATE_NAME`; SQLSTATE: `HY000`  
Message: Certificate name: %s
  - Error number: `MY-011766`; Symbol: `ER_LDAP_AUTH_FAILED_TO_POOL_DEINIT`; SQLSTATE: `HY000`  
Message: Failed to pool de-initialized: pool is already reconstructing
  - Error number: `MY-011767`; Symbol: `ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_RECONSTRUCTING`; SQLSTATE: `HY000`  
Message: Pool initialization failed: pool is already initialized
  - Error number: `MY-011768`; Symbol: `ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_INIT_STATE`; SQLSTATE: `HY000`  
Message: Pool initialization failed: pool is initializing
  - Error number: `MY-011769`; Symbol: `ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_DEINIT_STATE`; SQLSTATE: `HY000`  
Message: Pool initialization failed: pool is de-initializing
  - Error number: `MY-011770`; Symbol: `ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_POOL_IN_RECONSTRUCT_STATE`; SQLSTATE: `HY000`  
Message: Failed to pool deinitialized: pool is already reconstructing
  - Error number: `MY-011771`; Symbol: `ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_NOT_READY_POOL`; SQLSTATE: `HY000`  
Message: Failed to pool deinitialized : pool is not ready
  - Error number: `MY-011772`; Symbol: `ER_LDAP_AUTH_FAILED_TO_GET_CONNECTION_AS_PLUGIN_NOT_READY`; SQLSTATE: `HY000`  
Message: Ldap\_connection\_pool::get: Failed to return connection as plug-in is not ready/initializing/de-initializing
  - Error number: `MY-011773`; Symbol: `ER_LDAP_AUTH_CONNECTION_POOL_INIT_FAILED`; SQLSTATE: `HY000`
-

---

Message: Connection pool has failed to initialized

- Error number: MY-011774; Symbol: ER\_LDAP\_AUTH\_MAX\_ALLOWED\_CONNECTION\_LIMIT\_HIT; SQLSTATE: HY000

Message: Ldap\_connetion\_pool::get LDAP maximum connection allowed size is reached. Increase the maximum limit.

- Error number: MY-011775; Symbol: ER\_LDAP\_AUTH\_MAX\_POOL\_SIZE\_SET\_FAILED; SQLSTATE: HY000

Message: Set max pool size failed.

- Error number: MY-011776; Symbol: ER\_LDAP\_AUTH\_PLUGIN\_FAILED\_TO\_READ\_PACKET; SQLSTATE: HY000

Message: Plug-in has failed to read the packet from client

- Error number: MY-011777; Symbol: ER\_LDAP\_AUTH\_CREATING\_LDAP\_CONNECTION; SQLSTATE: HY000

Message: Ldap\_authentication::initialize: creating new LDAP connection.

- Error number: MY-011778; Symbol: ER\_LDAP\_AUTH\_GETTING\_CONNECTION\_FROM\_POOL; SQLSTATE: HY000

Message: Ldap\_authentication::initialize: getting connection from pool.

- Error number: MY-011779; Symbol: ER\_LDAP\_AUTH\_RETURNING\_CONNECTION\_TO\_POOL; SQLSTATE: HY000

Message: Ldap\_authentication::de\_initialize putting back connection in the pool

- Error number: MY-011780; Symbol: ER\_LDAP\_AUTH\_SEARCH\_USER\_GROUP\_ATTR\_NOT\_FOUND; SQLSTATE: HY000

Message: Ldap\_authentication::search\_user\_group no group attribute found

- Error number: MY-011781; Symbol: ER\_LDAP\_AUTH\_LDAP\_INFO\_NULL; SQLSTATE: HY000

Message: Ldap\_connetion\_pool::put ldap info null

- Error number: MY-011782; Symbol: ER\_LDAP\_AUTH\_FREEING\_CONNECTION; SQLSTATE: HY000

Message: Ldap\_connection\_pool::put connection is freeing.

- Error number: MY-011783; Symbol: ER\_LDAP\_AUTH\_CONNECTION\_PUSHED\_TO\_POOL; SQLSTATE: HY000

Message: Ldap\_connection\_pool::put connection in pushed in the pool

- Error number: MY-011784; Symbol: ER\_LDAP\_AUTH\_CONNECTION\_CREATOR\_ENTER; SQLSTATE: HY000

Message: Ldap\_connection\_creator::Ldap\_connection\_creator

- Error number: MY-011785; Symbol: ER\_LDAP\_AUTH\_STARTING\_TLS; SQLSTATE: HY000

Message: starting TLS

- Error number: MY-011786; Symbol: ER\_LDAP\_AUTH\_CONNECTION\_GET\_LDAP\_INFO\_NULL; SQLSTATE: HY000

---

Message: Ldap\_connection\_pool::get: (ldap\_info == NULL)|| (\*ldap\_info)

- Error number: MY-011787; Symbol: ER\_LDAP\_AUTH\_DELETING\_CONNECTION\_KEY; SQLSTATE: HY000

Message: Ldap\_connection\_pool::deinit: deleting connection key %s

- Error number: MY-011788; Symbol: ER\_LDAP\_AUTH\_POOLED\_CONNECTION\_KEY; SQLSTATE: HY000

Message: Ldap\_connection\_pool::get pooled connection key: %s

- Error number: MY-011789; Symbol: ER\_LDAP\_AUTH\_CREATE\_CONNECTION\_KEY; SQLSTATE: HY000

Message: Ldap\_connection\_pool::get create connection key: %s

- Error number: MY-011790; Symbol: ER\_LDAP\_AUTH\_COMMUNICATION\_HOST\_INFO; SQLSTATE: HY000

Message: LDAP communication host %s port %u

- Error number: MY-011791; Symbol: ER\_LDAP\_AUTH\_METHOD\_TO\_CLIENT; SQLSTATE: HY000

Message: Sending authentication method to client : %s

- Error number: MY-011792; Symbol: ER\_LDAP\_AUTH\_SASL\_REQUEST\_FROM\_CLIENT; SQLSTATE: HY000

Message: SASL request received from mysql client: %s

- Error number: MY-011793; Symbol: ER\_LDAP\_AUTH\_SASL\_PROCESS\_SASL; SQLSTATE: HY000

Message: Ldap\_sasl\_authentication::process\_sasl rc: %s

- Error number: MY-011794; Symbol: ER\_LDAP\_AUTH\_SASL\_BIND\_SUCCESS\_INFO; SQLSTATE: HY000

Message: Ldap\_sasl\_authentication::process\_sasl sasl bind succeed. dn: %s method: %s server credential: %s

- Error number: MY-011795; Symbol: ER\_LDAP\_AUTH\_STARTED\_FOR\_USER; SQLSTATE: HY000

Message: LDAP authentication started for user name: %s

- Error number: MY-011796; Symbol: ER\_LDAP\_AUTH\_DISTINGUISHED\_NAME; SQLSTATE: HY000

Message: %s

- Error number: MY-011797; Symbol: ER\_LDAP\_AUTH\_INIT\_FAILED; SQLSTATE: HY000

Message: LDAP authentication initialize is failed with: %s

- Error number: MY-011798; Symbol: ER\_LDAP\_AUTH\_OR\_GROUP\_RETRIEVAL\_FAILED; SQLSTATE: HY000

Message: LDAP authentication failed or group retrieval failed: %s

- Error number: MY-011799; Symbol: ER\_LDAP\_AUTH\_USER\_GROUP\_SEARCH\_FAILED; SQLSTATE: HY000

Message: Search user group has failed: %s

- 
- Error number: `MY-011800`; Symbol: `ER_LDAP_AUTH_USER_BIND_FAILED`; SQLSTATE: `HY000`  
Message: LDAP user bind has failed: %s
  - Error number: `MY-011801`; Symbol: `ER_LDAP_AUTH_POOL_GET_FAILED_TO_CREATE_CONNECTION`; SQLSTATE: `HY000`  
Message: Connection pool get: Failed to create LDAP connection. %s
  - Error number: `MY-011802`; Symbol: `ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_CONNECTION`; SQLSTATE: `HY000`  
Message: Failed to create new LDAP connection: %s
  - Error number: `MY-011803`; Symbol: `ER_LDAP_AUTH_FAILED_TO_ESTABLISH_TLS_CONNECTION`; SQLSTATE: `HY000`  
Message: Failed to establish TLS connection: %s
  - Error number: `MY-011804`; Symbol: `ER_LDAP_AUTH_FAILED_TO_SEARCH_DN`; SQLSTATE: `HY000`  
Message: Failed to search user full dn: %s
  - Error number: `MY-011805`; Symbol: `ER_LDAP_AUTH_CONNECTION_POOL_REINIT_ENTER`; SQLSTATE: `HY000`  
Message: `Ldap_connection_pool::reinit`
  - Error number: `MY-011806`; Symbol: `ER_SYSTEMD_NOTIFY_PATH_TOO_LONG`; SQLSTATE: `HY000`  
Message: The path '%s', from the NOTIFY\_SOCKET environment variable, is too long. At %u bytes it exceeds the limit of %u bytes for an AF\_UNIX socket.
  - Error number: `MY-011807`; Symbol: `ER_SYSTEMD_NOTIFY_CONNECT_FAILED`; SQLSTATE: `HY000`  
Message: Failed to connect to systemd notification socket named %s. Error: '%s'
  - Error number: `MY-011808`; Symbol: `ER_SYSTEMD_NOTIFY_WRITE_FAILED`; SQLSTATE: `HY000`  
Message: Failed to write '%s' to systemd notification. Error: '%s'
  - Error number: `MY-011809`; Symbol: `ER_FOUND_MISSING_GTIDS`; SQLSTATE: `HY000`  
Message: Cannot replicate to server with server\_uuid='%s' because the present server has purged required binary logs. The connecting server needs to replicate the missing transactions from elsewhere, or be replaced by a new server created from a more recent backup. To prevent this error in the future, consider increasing the binary log expiration period on the present server. %s.
  - Error number: `MY-011810`; Symbol: `ER_PID_FILE_PRIV_DIRECTORY_INSECURE`; SQLSTATE: `HY000`  
Message: Insecure configuration for --pid-file: Location '%s' in the path is accessible to all OS users. Consider choosing a different directory.
  - Error number: `MY-011811`; Symbol: `ER_CANT_CHECK_PID_PATH`; SQLSTATE: `HY000`  
Message: Can't start server: can't check PID filepath: %s
  - Error number: `MY-011812`; Symbol: `ER_VALIDATE_PWD_STATUS_VAR_REGISTRATION_FAILED`; SQLSTATE: `HY000`  
Message: `validate_password` status variables registration failed.

- 
- Error number: `MY-011813`; Symbol: `ER_VALIDATE_PWD_STATUS_VAR_UNREGISTRATION_FAILED`; SQLSTATE: `HY000`  
Message: `validate_password` status variables unregistration failed.
  - Error number: `MY-011814`; Symbol: `ER_VALIDATE_PWD_DICT_FILE_OPEN_FAILED`; SQLSTATE: `HY000`  
Message: Dictionary file open failed
  - Error number: `MY-011815`; Symbol: `ER_VALIDATE_PWD_COULD_BE_NULL`; SQLSTATE: `HY000`  
Message: given password string could be null
  - Error number: `MY-011816`; Symbol: `ER_VALIDATE_PWD_STRING_CONV_TO_LOWERCASE_FAILED`; SQLSTATE: `HY000`  
Message: failed to convert the password string to lower case
  - Error number: `MY-011817`; Symbol: `ER_VALIDATE_PWD_STRING_CONV_TO_BUFFER_FAILED`; SQLSTATE: `HY000`  
Message: failed to convert the password string into a buffer
  - Error number: `MY-011818`; Symbol: `ER_VALIDATE_PWD_STRING_HANDLER_MEM_ALLOCATION_FAILED`; SQLSTATE: `HY000`  
Message: memory allocation failed for string handler
  - Error number: `MY-011819`; Symbol: `ER_VALIDATE_PWD_STRONG_POLICY_DICT_FILE_UNSPECIFIED`; SQLSTATE: `HY000`  
Message: Since the `validate_password_policy` is mentioned as Strong, dictionary file must be specified
  - Error number: `MY-011820`; Symbol: `ER_VALIDATE_PWD_CONVERT_TO_BUFFER_FAILED`; SQLSTATE: `HY000`  
Message: `convert_to_buffer` service failed
  - Error number: `MY-011821`; Symbol: `ER_VALIDATE_PWD_VARIABLE_REGISTRATION_FAILED`; SQLSTATE: `HY000`  
Message: `%s` variable registration failed.
  - Error number: `MY-011822`; Symbol: `ER_VALIDATE_PWD_VARIABLE_UNREGISTRATION_FAILED`; SQLSTATE: `HY000`  
Message: `%s` variable unregistration failed.
  - Error number: `MY-011823`; Symbol: `ER_KEYRING_MIGRATION_EXTRA_OPTIONS`; SQLSTATE: `HY000`  
Message: Please specify options specific to keyring migration. Any additional options can be ignored.  
NOTE: Although some options are valid, migration tool can still report error example: plugin variables for which plugin is not loaded yet.
  - Error number: `MY-011825`; Symbol: `ER_IB_MSG_0`; SQLSTATE: `HY000`  
Message: `%s`
  - Error number: `MY-011826`; Symbol: `ER_IB_MSG_1`; SQLSTATE: `HY000`  
Message: `%s`
-

- 
- Error number: [MY-011827](#); Symbol: [ER\\_IB\\_MSG\\_2](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-011828](#); Symbol: [ER\\_IB\\_MSG\\_3](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-011829](#); Symbol: [ER\\_IB\\_MSG\\_4](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-011830](#); Symbol: [ER\\_IB\\_MSG\\_5](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-011831](#); Symbol: [ER\\_IB\\_MSG\\_6](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-011832](#); Symbol: [ER\\_IB\\_MSG\\_7](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-011833](#); Symbol: [ER\\_IB\\_MSG\\_8](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-011834](#); Symbol: [ER\\_IB\\_MSG\\_9](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-011835](#); Symbol: [ER\\_IB\\_MSG\\_10](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-011836](#); Symbol: [ER\\_IB\\_MSG\\_11](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-011837](#); Symbol: [ER\\_IB\\_MSG\\_12](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-011838](#); Symbol: [ER\\_IB\\_MSG\\_13](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-011839](#); Symbol: [ER\\_IB\\_MSG\\_14](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-011840](#); Symbol: [ER\\_IB\\_MSG\\_15](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-011841](#); Symbol: [ER\\_IB\\_MSG\\_16](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-011842](#); Symbol: [ER\\_IB\\_MSG\\_17](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-011843](#); Symbol: [ER\\_IB\\_MSG\\_18](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-011844](#); Symbol: [ER\\_IB\\_MSG\\_19](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011845](#); Symbol: [ER\\_IB\\_MSG\\_20](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011846](#); Symbol: [ER\\_IB\\_MSG\\_21](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011847](#); Symbol: [ER\\_IB\\_MSG\\_22](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011848](#); Symbol: [ER\\_IB\\_MSG\\_23](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011849](#); Symbol: [ER\\_IB\\_MSG\\_24](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011850](#); Symbol: [ER\\_IB\\_MSG\\_25](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011851](#); Symbol: [ER\\_IB\\_MSG\\_26](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011852](#); Symbol: [ER\\_IB\\_MSG\\_27](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011853](#); Symbol: [ER\\_IB\\_MSG\\_28](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011854](#); Symbol: [ER\\_IB\\_MSG\\_29](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011855](#); Symbol: [ER\\_IB\\_MSG\\_30](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011856](#); Symbol: [ER\\_IB\\_MSG\\_31](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011857](#); Symbol: [ER\\_IB\\_MSG\\_32](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011858](#); Symbol: [ER\\_IB\\_MSG\\_33](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011859](#); Symbol: [ER\\_IB\\_MSG\\_34](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-011860](#); Symbol: [ER\\_IB\\_MSG\\_35](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011861](#); Symbol: [ER\\_IB\\_MSG\\_36](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011862](#); Symbol: [ER\\_IB\\_MSG\\_37](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011863](#); Symbol: [ER\\_IB\\_MSG\\_38](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011864](#); Symbol: [ER\\_IB\\_MSG\\_39](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011865](#); Symbol: [ER\\_IB\\_MSG\\_40](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011866](#); Symbol: [ER\\_IB\\_MSG\\_41](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011867](#); Symbol: [ER\\_IB\\_MSG\\_42](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011868](#); Symbol: [ER\\_IB\\_MSG\\_43](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011869](#); Symbol: [ER\\_IB\\_MSG\\_44](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011870](#); Symbol: [ER\\_IB\\_MSG\\_45](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011871](#); Symbol: [ER\\_IB\\_MSG\\_46](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011872](#); Symbol: [ER\\_IB\\_MSG\\_47](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011873](#); Symbol: [ER\\_IB\\_MSG\\_48](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011874](#); Symbol: [ER\\_IB\\_MSG\\_49](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011875](#); Symbol: [ER\\_IB\\_MSG\\_50](#); SQLSTATE: [HY000](#)



---

Message: %s

- Error number: [MY-011876](#); Symbol: [ER\\_IB\\_MSG\\_51](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011877](#); Symbol: [ER\\_IB\\_MSG\\_52](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011878](#); Symbol: [ER\\_IB\\_MSG\\_53](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011879](#); Symbol: [ER\\_IB\\_MSG\\_54](#); SQLSTATE: [HY000](#)

Message: Failed to set NUMA memory policy of buffer pool page frames with mbind(%p,%zu,  
%s,.....,%s) failed with %s

- Error number: [MY-011880](#); Symbol: [ER\\_IB\\_MSG\\_55](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011881](#); Symbol: [ER\\_IB\\_MSG\\_56](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011882](#); Symbol: [ER\\_IB\\_MSG\\_57](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011883](#); Symbol: [ER\\_IB\\_MSG\\_58](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011884](#); Symbol: [ER\\_IB\\_MSG\\_59](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011885](#); Symbol: [ER\\_IB\\_MSG\\_60](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011886](#); Symbol: [ER\\_IB\\_MSG\\_61](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011887](#); Symbol: [ER\\_IB\\_MSG\\_62](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011888](#); Symbol: [ER\\_IB\\_MSG\\_63](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011889](#); Symbol: [ER\\_IB\\_MSG\\_64](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011890](#); Symbol: [ER\\_IB\\_MSG\\_65](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011891](#); Symbol: [ER\\_IB\\_MSG\\_66](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-011892](#); Symbol: [ER\\_IB\\_MSG\\_67](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011893](#); Symbol: [ER\\_IB\\_MSG\\_68](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011894](#); Symbol: [ER\\_IB\\_MSG\\_69](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011895](#); Symbol: [ER\\_IB\\_MSG\\_70](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011896](#); Symbol: [ER\\_IB\\_MSG\\_71](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011897](#); Symbol: [ER\\_IB\\_MSG\\_72](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011898](#); Symbol: [ER\\_IB\\_MSG\\_73](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011899](#); Symbol: [ER\\_IB\\_MSG\\_74](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011900](#); Symbol: [ER\\_IB\\_MSG\\_75](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011901](#); Symbol: [ER\\_IB\\_MSG\\_76](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011902](#); Symbol: [ER\\_IB\\_MSG\\_77](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011903](#); Symbol: [ER\\_IB\\_MSG\\_78](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011904](#); Symbol: [ER\\_IB\\_MSG\\_79](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011905](#); Symbol: [ER\\_IB\\_MSG\\_80](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011906](#); Symbol: [ER\\_IB\\_MSG\\_81](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011907](#); Symbol: [ER\\_IB\\_MSG\\_82](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-011908](#); Symbol: [ER\\_IB\\_MSG\\_83](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011909](#); Symbol: [ER\\_IB\\_MSG\\_84](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011910](#); Symbol: [ER\\_IB\\_MSG\\_85](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011911](#); Symbol: [ER\\_IB\\_MSG\\_86](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011920](#); Symbol: [ER\\_IB\\_MSG\\_95](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011921](#); Symbol: [ER\\_IB\\_MSG\\_96](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011922](#); Symbol: [ER\\_IB\\_MSG\\_97](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011923](#); Symbol: [ER\\_IB\\_MSG\\_98](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011924](#); Symbol: [ER\\_IB\\_MSG\\_99](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011925](#); Symbol: [ER\\_IB\\_MSG\\_100](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011926](#); Symbol: [ER\\_IB\\_MSG\\_101](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011927](#); Symbol: [ER\\_IB\\_MSG\\_102](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011928](#); Symbol: [ER\\_IB\\_MSG\\_103](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011929](#); Symbol: [ER\\_IB\\_MSG\\_104](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011930](#); Symbol: [ER\\_IB\\_MSG\\_105](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011931](#); Symbol: [ER\\_IB\\_MSG\\_106](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-011932](#); Symbol: [ER\\_IB\\_MSG\\_107](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011933](#); Symbol: [ER\\_IB\\_MSG\\_108](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011934](#); Symbol: [ER\\_IB\\_MSG\\_109](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011935](#); Symbol: [ER\\_IB\\_MSG\\_110](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011936](#); Symbol: [ER\\_IB\\_MSG\\_111](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011937](#); Symbol: [ER\\_IB\\_MSG\\_112](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011944](#); Symbol: [ER\\_IB\\_MSG\\_119](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011945](#); Symbol: [ER\\_IB\\_MSG\\_120](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011946](#); Symbol: [ER\\_IB\\_MSG\\_121](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011947](#); Symbol: [ER\\_IB\\_MSG\\_122](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011948](#); Symbol: [ER\\_IB\\_MSG\\_123](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011949](#); Symbol: [ER\\_IB\\_MSG\\_124](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011950](#); Symbol: [ER\\_IB\\_MSG\\_125](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011951](#); Symbol: [ER\\_IB\\_MSG\\_126](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011952](#); Symbol: [ER\\_IB\\_MSG\\_127](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011953](#); Symbol: [ER\\_IB\\_MSG\\_128](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-011954](#); Symbol: [ER\\_IB\\_MSG\\_129](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011955](#); Symbol: [ER\\_IB\\_MSG\\_130](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011956](#); Symbol: [ER\\_IB\\_MSG\\_131](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011957](#); Symbol: [ER\\_IB\\_MSG\\_132](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011958](#); Symbol: [ER\\_IB\\_MSG\\_133](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011959](#); Symbol: [ER\\_IB\\_MSG\\_134](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011960](#); Symbol: [ER\\_IB\\_MSG\\_135](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011961](#); Symbol: [ER\\_IB\\_MSG\\_136](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011962](#); Symbol: [ER\\_IB\\_MSG\\_137](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011963](#); Symbol: [ER\\_IB\\_MSG\\_138](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011964](#); Symbol: [ER\\_IB\\_MSG\\_139](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011965](#); Symbol: [ER\\_IB\\_MSG\\_140](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011966](#); Symbol: [ER\\_IB\\_MSG\\_141](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011967](#); Symbol: [ER\\_IB\\_MSG\\_142](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011968](#); Symbol: [ER\\_IB\\_MSG\\_143](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011969](#); Symbol: [ER\\_IB\\_MSG\\_144](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-011970](#); Symbol: [ER\\_IB\\_MSG\\_145](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011971](#); Symbol: [ER\\_IB\\_MSG\\_146](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011972](#); Symbol: [ER\\_IB\\_MSG\\_147](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011973](#); Symbol: [ER\\_IB\\_MSG\\_148](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011974](#); Symbol: [ER\\_IB\\_CLONE\\_INTERNAL](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011975](#); Symbol: [ER\\_IB\\_CLONE\\_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011976](#); Symbol: [ER\\_IB\\_CLONE\\_STATUS\\_FILE](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011977](#); Symbol: [ER\\_IB\\_CLONE\\_SQL](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011978](#); Symbol: [ER\\_IB\\_CLONE\\_VALIDATE](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011979](#); Symbol: [ER\\_IB\\_CLONE\\_PUNCH\\_HOLE](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011980](#); Symbol: [ER\\_IB\\_CLONE\\_GTID\\_PERSIST](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011981](#); Symbol: [ER\\_IB\\_MSG\\_156](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011982](#); Symbol: [ER\\_IB\\_MSG\\_157](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011983](#); Symbol: [ER\\_IB\\_MSG\\_158](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011984](#); Symbol: [ER\\_IB\\_MSG\\_159](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011985](#); Symbol: [ER\\_IB\\_MSG\\_160](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-011986](#); Symbol: [ER\\_IB\\_MSG\\_161](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011987](#); Symbol: [ER\\_IB\\_MSG\\_162](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011988](#); Symbol: [ER\\_IB\\_MSG\\_163](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011989](#); Symbol: [ER\\_IB\\_MSG\\_164](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011990](#); Symbol: [ER\\_IB\\_MSG\\_165](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011991](#); Symbol: [ER\\_IB\\_MSG\\_166](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011992](#); Symbol: [ER\\_IB\\_MSG\\_167](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011993](#); Symbol: [ER\\_IB\\_MSG\\_168](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011994](#); Symbol: [ER\\_IB\\_MSG\\_169](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011995](#); Symbol: [ER\\_IB\\_MSG\\_170](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011996](#); Symbol: [ER\\_IB\\_MSG\\_171](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011997](#); Symbol: [ER\\_IB\\_MSG\\_172](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011998](#); Symbol: [ER\\_IB\\_MSG\\_173](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011999](#); Symbol: [ER\\_IB\\_MSG\\_174](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012000](#); Symbol: [ER\\_IB\\_MSG\\_175](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012001](#); Symbol: [ER\\_IB\\_MSG\\_176](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-012002](#); Symbol: [ER\\_IB\\_MSG\\_177](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012003](#); Symbol: [ER\\_IB\\_MSG\\_178](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012004](#); Symbol: [ER\\_IB\\_MSG\\_179](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012005](#); Symbol: [ER\\_IB\\_MSG\\_180](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012006](#); Symbol: [ER\\_IB\\_LONG\\_AHI\\_DISABLE\\_WAIT](#); SQLSTATE: [HY000](#)

Message: Waited for %u secs for hash index ref\_count (%zu) to drop to 0. index: "%s" table: "%s"

- Error number: [MY-012007](#); Symbol: [ER\\_IB\\_MSG\\_182](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012008](#); Symbol: [ER\\_IB\\_MSG\\_183](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012009](#); Symbol: [ER\\_IB\\_MSG\\_184](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012010](#); Symbol: [ER\\_IB\\_MSG\\_185](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012011](#); Symbol: [ER\\_IB\\_MSG\\_186](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012012](#); Symbol: [ER\\_IB\\_MSG\\_187](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012013](#); Symbol: [ER\\_IB\\_MSG\\_188](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012014](#); Symbol: [ER\\_IB\\_MSG\\_189](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012015](#); Symbol: [ER\\_IB\\_MSG\\_190](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012016](#); Symbol: [ER\\_IB\\_MSG\\_191](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012017](#); Symbol: [ER\\_IB\\_MSG\\_192](#); SQLSTATE: [HY000](#)



---

Message: %s

- Error number: [MY-012018](#); Symbol: [ER\\_IB\\_MSG\\_193](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012019](#); Symbol: [ER\\_IB\\_MSG\\_194](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012020](#); Symbol: [ER\\_IB\\_MSG\\_195](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012021](#); Symbol: [ER\\_IB\\_MSG\\_196](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012022](#); Symbol: [ER\\_IB\\_MSG\\_197](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012023](#); Symbol: [ER\\_IB\\_MSG\\_198](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012024](#); Symbol: [ER\\_IB\\_MSG\\_199](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012025](#); Symbol: [ER\\_IB\\_MSG\\_200](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012026](#); Symbol: [ER\\_IB\\_MSG\\_201](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012027](#); Symbol: [ER\\_IB\\_MSG\\_202](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012028](#); Symbol: [ER\\_IB\\_MSG\\_203](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012029](#); Symbol: [ER\\_IB\\_MSG\\_204](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012030](#); Symbol: [ER\\_IB\\_MSG\\_205](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012031](#); Symbol: [ER\\_IB\\_MSG\\_206](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012032](#); Symbol: [ER\\_IB\\_MSG\\_207](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012033](#); Symbol: [ER\\_IB\\_MSG\\_208](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-012034](#); Symbol: [ER\\_IB\\_MSG\\_209](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012035](#); Symbol: [ER\\_IB\\_MSG\\_210](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012036](#); Symbol: [ER\\_IB\\_MSG\\_211](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012037](#); Symbol: [ER\\_IB\\_MSG\\_212](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012038](#); Symbol: [ER\\_IB\\_MSG\\_213](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012039](#); Symbol: [ER\\_IB\\_MSG\\_214](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012040](#); Symbol: [ER\\_IB\\_MSG\\_215](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012041](#); Symbol: [ER\\_IB\\_MSG\\_216](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012042](#); Symbol: [ER\\_IB\\_MSG\\_217](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012043](#); Symbol: [ER\\_IB\\_MSG\\_218](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012044](#); Symbol: [ER\\_IB\\_MSG\\_219](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012045](#); Symbol: [ER\\_IB\\_MSG\\_220](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012046](#); Symbol: [ER\\_IB\\_MSG\\_221](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012047](#); Symbol: [ER\\_IB\\_MSG\\_222](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012048](#); Symbol: [ER\\_IB\\_MSG\\_223](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012049](#); Symbol: [ER\\_IB\\_MSG\\_224](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-012050](#); Symbol: [ER\\_IB\\_MSG\\_225](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012051](#); Symbol: [ER\\_IB\\_MSG\\_226](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012052](#); Symbol: [ER\\_IB\\_MSG\\_227](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012053](#); Symbol: [ER\\_IB\\_MSG\\_228](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012054](#); Symbol: [ER\\_IB\\_MSG\\_229](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012055](#); Symbol: [ER\\_IB\\_MSG\\_230](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012056](#); Symbol: [ER\\_IB\\_MSG\\_231](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012057](#); Symbol: [ER\\_IB\\_MSG\\_232](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012058](#); Symbol: [ER\\_IB\\_MSG\\_233](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012059](#); Symbol: [ER\\_IB\\_MSG\\_234](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012060](#); Symbol: [ER\\_IB\\_MSG\\_235](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012061](#); Symbol: [ER\\_IB\\_MSG\\_236](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012062](#); Symbol: [ER\\_IB\\_MSG\\_237](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012063](#); Symbol: [ER\\_IB\\_MSG\\_238](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012064](#); Symbol: [ER\\_IB\\_MSG\\_239](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012065](#); Symbol: [ER\\_IB\\_MSG\\_240](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-012066](#); Symbol: [ER\\_IB\\_MSG\\_241](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012067](#); Symbol: [ER\\_IB\\_MSG\\_242](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012068](#); Symbol: [ER\\_IB\\_MSG\\_243](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012069](#); Symbol: [ER\\_IB\\_MSG\\_244](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012070](#); Symbol: [ER\\_IB\\_MSG\\_245](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012071](#); Symbol: [ER\\_IB\\_MSG\\_246](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012072](#); Symbol: [ER\\_IB\\_MSG\\_247](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012073](#); Symbol: [ER\\_IB\\_MSG\\_248](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012074](#); Symbol: [ER\\_IB\\_MSG\\_249](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012075](#); Symbol: [ER\\_IB\\_MSG\\_250](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012076](#); Symbol: [ER\\_IB\\_MSG\\_251](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012077](#); Symbol: [ER\\_IB\\_MSG\\_252](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012078](#); Symbol: [ER\\_IB\\_MSG\\_253](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012079](#); Symbol: [ER\\_IB\\_MSG\\_254](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012080](#); Symbol: [ER\\_IB\\_MSG\\_255](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012081](#); Symbol: [ER\\_IB\\_MSG\\_256](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-012082](#); Symbol: [ER\\_IB\\_MSG\\_257](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012083](#); Symbol: [ER\\_IB\\_MSG\\_258](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012084](#); Symbol: [ER\\_IB\\_MSG\\_259](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012085](#); Symbol: [ER\\_IB\\_MSG\\_260](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012086](#); Symbol: [ER\\_IB\\_MSG\\_261](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012087](#); Symbol: [ER\\_IB\\_MSG\\_262](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012088](#); Symbol: [ER\\_IB\\_MSG\\_263](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012089](#); Symbol: [ER\\_IB\\_MSG\\_264](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012090](#); Symbol: [ER\\_IB\\_MSG\\_265](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012091](#); Symbol: [ER\\_IB\\_MSG\\_266](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012092](#); Symbol: [ER\\_IB\\_MSG\\_267](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012093](#); Symbol: [ER\\_IB\\_MSG\\_268](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012094](#); Symbol: [ER\\_IB\\_MSG\\_269](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012095](#); Symbol: [ER\\_IB\\_MSG\\_270](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012096](#); Symbol: [ER\\_IB\\_MSG\\_271](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012097](#); Symbol: [ER\\_IB\\_MSG\\_272](#); SQLSTATE: [HY000](#)

---

Message: Table flags are 0x%lx in the data dictionary but the flags in file %s are 0x%llx!

- Error number: [MY-012098](#); Symbol: [ER\\_IB\\_MSG\\_273](#); SQLSTATE: [HY000](#)

Message: Can't read encryption key from file %s!

- Error number: [MY-012103](#); Symbol: [ER\\_IB\\_MSG\\_278](#); SQLSTATE: [HY000](#)

Message: Tablespace %s, waiting for IO to stop for %lld seconds

- Error number: [MY-012105](#); Symbol: [ER\\_IB\\_MSG\\_280](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012106](#); Symbol: [ER\\_IB\\_MSG\\_281](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012107](#); Symbol: [ER\\_IB\\_MSG\\_282](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012108](#); Symbol: [ER\\_IB\\_MSG\\_283](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012109](#); Symbol: [ER\\_IB\\_MSG\\_284](#); SQLSTATE: [HY000](#)

Message: You must raise the value of `innodb_open_files` in `my.cnf`! Remember that InnoDB keeps all redo log files and all system tablespace files open for the whole time `mysqld` is running, and needs to open also some `.ibd` files if the file-per-table storage model is used. Current open files %zu, max allowed open files %zu.

- Error number: [MY-012110](#); Symbol: [ER\\_IB\\_MSG\\_285](#); SQLSTATE: [HY000](#)

Message: Max tablespace id is too high, %lu

- Error number: [MY-012111](#); Symbol: [ER\\_IB\\_WARN\\_ACCESSING\\_NONEXISTINC\\_SPACE](#); SQLSTATE: [HY000](#)

Message: Trying to access missing tablespace %lu

- Error number: [MY-012112](#); Symbol: [ER\\_IB\\_MSG\\_287](#); SQLSTATE: [HY000](#)

Message: Trying to close/delete tablespace '%s' but there are %lu pending operations on it.

- Error number: [MY-012113](#); Symbol: [ER\\_IB\\_MSG\\_288](#); SQLSTATE: [HY000](#)

Message: Trying to delete/close tablespace '%s' but there are %lu flushes and %zu pending I/O's on it.

- Error number: [MY-012114](#); Symbol: [ER\\_IB\\_MSG\\_289](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012116](#); Symbol: [ER\\_IB\\_MSG\\_291](#); SQLSTATE: [HY000](#)

Message: While deleting tablespace %lu in DISCARD TABLESPACE. File rename/delete failed: %s

- Error number: [MY-012117](#); Symbol: [ER\\_IB\\_MSG\\_292](#); SQLSTATE: [HY000](#)

Message: Cannot delete tablespace %lu in DISCARD TABLESPACE: %s

- Error number: [MY-012118](#); Symbol: [ER\\_IB\\_MSG\\_293](#); SQLSTATE: [HY000](#)

---

Message: Cannot rename '%s' to '%s' for space ID %lu because the source file does not exist.

- Error number: [MY-012119](#); Symbol: [ER\\_IB\\_MSG\\_294](#); SQLSTATE: [HY000](#)

Message: Cannot rename '%s' to '%s' for space ID %lu because the target file exists. Remove the target file and try again.

- Error number: [MY-012120](#); Symbol: [ER\\_IB\\_MSG\\_295](#); SQLSTATE: [HY000](#)

Message: Cannot rename file '%s' (space id %lu) retried %llu times. There are either pending IOs or flushes or the file is being extended.

- Error number: [MY-012121](#); Symbol: [ER\\_IB\\_MSG\\_296](#); SQLSTATE: [HY000](#)

Message: Cannot find space id %lu in the tablespace memory cache, though the file '%s' in a rename operation should have that ID.

- Error number: [MY-012122](#); Symbol: [ER\\_IB\\_MSG\\_297](#); SQLSTATE: [HY000](#)

Message: Rename waiting for IO to resume

- Error number: [MY-012123](#); Symbol: [ER\\_IB\\_MSG\\_298](#); SQLSTATE: [HY000](#)

Message: Cannot find tablespace for '%s' in the tablespace memory cache

- Error number: [MY-012124](#); Symbol: [ER\\_IB\\_MSG\\_299](#); SQLSTATE: [HY000](#)

Message: Cannot find tablespace for '%s' in the tablespace memory cache

- Error number: [MY-012125](#); Symbol: [ER\\_IB\\_MSG\\_300](#); SQLSTATE: [HY000](#)

Message: Tablespace '%s' is already in the tablespace memory cache

- Error number: [MY-012126](#); Symbol: [ER\\_IB\\_MSG\\_301](#); SQLSTATE: [HY000](#)

Message: Cannot create file '%s'

- Error number: [MY-012127](#); Symbol: [ER\\_IB\\_MSG\\_UNEXPECTED\\_FILE\\_EXISTS](#); SQLSTATE: [HY000](#)

Message: The file '%s' already exists though the corresponding table did not exist. Have you moved InnoDB .ibd files around without using the SQL commands DISCARD TABLESPACE and IMPORT TABLESPACE, or did mysqld crash in the middle of CREATE TABLE? You can resolve the problem by removing the file '%s' under the 'datadir' of MySQL.

- Error number: [MY-012128](#); Symbol: [ER\\_IB\\_MSG\\_303](#); SQLSTATE: [HY000](#)

Message: posix\_fallocate(): Failed to preallocate data for file %s, desired size %llu Operating system error number %d - %s. Check that the disk is not full or a disk quota exceeded. Make sure the file system supports this function. Refer to your operating system documentation for operating system error code information.

- Error number: [MY-012129](#); Symbol: [ER\\_IB\\_MSG\\_304](#); SQLSTATE: [HY000](#)

Message: Could not write the first page to tablespace '%s'

- Error number: [MY-012130](#); Symbol: [ER\\_IB\\_MSG\\_305](#); SQLSTATE: [HY000](#)

Message: File flush of tablespace '%s' failed

- Error number: [MY-012131](#); Symbol: [ER\\_IB\\_MSG\\_306](#); SQLSTATE: [HY000](#)

Message: Could not find a valid tablespace file for `%s`. %s

- 
- Error number: [MY-012132](#); Symbol: [ER\\_IB\\_MSG\\_307](#); SQLSTATE: [HY000](#)  
Message: Ignoring data file '%s' with space ID %lu. Another data file called '%s' exists with the same space ID
  - Error number: [MY-012133](#); Symbol: [ER\\_IB\\_MSG\\_308](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012134](#); Symbol: [ER\\_IB\\_MSG\\_309](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012135](#); Symbol: [ER\\_IB\\_MSG\\_310](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012136](#); Symbol: [ER\\_IB\\_MSG\\_311](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012137](#); Symbol: [ER\\_IB\\_MSG\\_312](#); SQLSTATE: [HY000](#)  
Message: Can't set encryption information for tablespace %s!
  - Error number: [MY-012138](#); Symbol: [ER\\_IB\\_MSG\\_313](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012139](#); Symbol: [ER\\_IB\\_MSG\\_314](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012140](#); Symbol: [ER\\_IB\\_MSG\\_315](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012141](#); Symbol: [ER\\_IB\\_MSG\\_316](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012142](#); Symbol: [ER\\_IB\\_MSG\\_317](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012143](#); Symbol: [ER\\_IB\\_MSG\\_318](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012144](#); Symbol: [ER\\_IB\\_MSG\\_319](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012145](#); Symbol: [ER\\_IB\\_MSG\\_320](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012146](#); Symbol: [ER\\_IB\\_MSG\\_321](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012147](#); Symbol: [ER\\_IB\\_MSG\\_322](#); SQLSTATE: [HY000](#)  
Message: %s



- 
- Error number: [MY-012148](#); Symbol: [ER\\_IB\\_MSG\\_323](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012149](#); Symbol: [ER\\_IB\\_MSG\\_324](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012150](#); Symbol: [ER\\_IB\\_MSG\\_325](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012151](#); Symbol: [ER\\_IB\\_MSG\\_326](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012153](#); Symbol: [ER\\_IB\\_MSG\\_328](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012154](#); Symbol: [ER\\_IB\\_MSG\\_329](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012155](#); Symbol: [ER\\_IB\\_MSG\\_330](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012156](#); Symbol: [ER\\_IB\\_MSG\\_331](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012157](#); Symbol: [ER\\_IB\\_MSG\\_332](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012158](#); Symbol: [ER\\_IB\\_MSG\\_333](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012159](#); Symbol: [ER\\_IB\\_MSG\\_334](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012160](#); Symbol: [ER\\_IB\\_MSG\\_335](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012161](#); Symbol: [ER\\_IB\\_MSG\\_336](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012162](#); Symbol: [ER\\_IB\\_MSG\\_337](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012163](#); Symbol: [ER\\_IB\\_MSG\\_338](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012164](#); Symbol: [ER\\_IB\\_MSG\\_339](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012165](#); Symbol: [ER\\_IB\\_MSG\\_340](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-012166](#); Symbol: [ER\\_IB\\_MSG\\_341](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012167](#); Symbol: [ER\\_IB\\_MSG\\_342](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012168](#); Symbol: [ER\\_IB\\_MSG\\_343](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012169](#); Symbol: [ER\\_IB\\_MSG\\_344](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012170](#); Symbol: [ER\\_IB\\_MSG\\_345](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012171](#); Symbol: [ER\\_IB\\_MSG\\_346](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012172](#); Symbol: [ER\\_IB\\_MSG\\_347](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012173](#); Symbol: [ER\\_IB\\_MSG\\_348](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012174](#); Symbol: [ER\\_IB\\_MSG\\_349](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012175](#); Symbol: [ER\\_IB\\_MSG\\_350](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012177](#); Symbol: [ER\\_IB\\_MSG\\_UNPROTECTED\\_LOCATION\\_ALLOWED](#); SQLSTATE: [HY000](#)

Message: The datafile '%s' for tablespace %s is in an unprotected location. This file cannot be recovered after a crash until this location is added to innodb\_directories.

- Error number: [MY-012179](#); Symbol: [ER\\_IB\\_MSG\\_354](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012180](#); Symbol: [ER\\_IB\\_MSG\\_355](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012181](#); Symbol: [ER\\_IB\\_MSG\\_356](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012182](#); Symbol: [ER\\_IB\\_MSG\\_357](#); SQLSTATE: [HY000](#)

Message: %s

- 
- Error number: [MY-012183](#); Symbol: [ER\\_IB\\_MSG\\_358](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012184](#); Symbol: [ER\\_IB\\_MSG\\_359](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012185](#); Symbol: [ER\\_IB\\_MSG\\_360](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012186](#); Symbol: [ER\\_IB\\_MSG\\_361](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012187](#); Symbol: [ER\\_IB\\_MSG\\_362](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012189](#); Symbol: [ER\\_IB\\_MSG\\_364](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012190](#); Symbol: [ER\\_IB\\_MSG\\_365](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012191](#); Symbol: [ER\\_IB\\_MSG\\_IGNORE\\_SCAN\\_PATH](#); SQLSTATE: [HY000](#)  
Message: Scan path '%s' is ignored because %s
  - Error number: [MY-012192](#); Symbol: [ER\\_IB\\_MSG\\_367](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012193](#); Symbol: [ER\\_IB\\_MSG\\_368](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012194](#); Symbol: [ER\\_IB\\_MSG\\_369](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012195](#); Symbol: [ER\\_IB\\_MSG\\_370](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012196](#); Symbol: [ER\\_IB\\_MSG\\_371](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012197](#); Symbol: [ER\\_IB\\_MSG\\_372](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012198](#); Symbol: [ER\\_IB\\_MSG\\_373](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012199](#); Symbol: [ER\\_IB\\_MSG\\_374](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012200](#); Symbol: [ER\\_IB\\_MSG\\_375](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-012201](#); Symbol: [ER\\_IB\\_MSG\\_376](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012202](#); Symbol: [ER\\_IB\\_MSG\\_377](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012203](#); Symbol: [ER\\_IB\\_MSG\\_378](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012204](#); Symbol: [ER\\_IB\\_MSG\\_379](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012205](#); Symbol: [ER\\_IB\\_MSG\\_380](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012206](#); Symbol: [ER\\_IB\\_MSG\\_381](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012207](#); Symbol: [ER\\_IB\\_MSG\\_382](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012208](#); Symbol: [ER\\_IB\\_MSG\\_383](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012209](#); Symbol: [ER\\_IB\\_MSG\\_384](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012210](#); Symbol: [ER\\_IB\\_MSG\\_385](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012211](#); Symbol: [ER\\_IB\\_MSG\\_386](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012212](#); Symbol: [ER\\_IB\\_MSG\\_387](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012213](#); Symbol: [ER\\_IB\\_MSG\\_GENERAL\\_TABLESPACE\\_UNDER\\_DATADIR](#); SQLSTATE: [HY000](#)

Message: A general tablespace cannot be located under the datadir. Cannot open file '%s'.

- Error number: [MY-012214](#); Symbol: [ER\\_IB\\_MSG\\_IMPLICIT\\_TABLESPACE\\_IN\\_DATADIR](#); SQLSTATE: [HY000](#)

Message: A file-per-table tablespace cannot be located in the datadir. Cannot open file '%s'.

- Error number: [MY-012215](#); Symbol: [ER\\_IB\\_MSG\\_390](#); SQLSTATE: [HY000](#)

Message: %s

- 
- Error number: [MY-012216](#); Symbol: [ER\\_IB\\_MSG\\_391](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012217](#); Symbol: [ER\\_IB\\_MSG\\_392](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012218](#); Symbol: [ER\\_IB\\_MSG\\_393](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012219](#); Symbol: [ER\\_IB\\_MSG\\_394](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012220](#); Symbol: [ER\\_IB\\_MSG\\_395](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012221](#); Symbol: [ER\\_IB\\_MSG\\_396](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012222](#); Symbol: [ER\\_IB\\_MSG\\_397](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012223](#); Symbol: [ER\\_IB\\_MSG\\_398](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012224](#); Symbol: [ER\\_IB\\_MSG\\_399](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012226](#); Symbol: [ER\\_IB\\_MSG\\_401](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012227](#); Symbol: [ER\\_IB\\_MSG\\_402](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012228](#); Symbol: [ER\\_IB\\_MSG\\_403](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012229](#); Symbol: [ER\\_IB\\_MSG\\_404](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012230](#); Symbol: [ER\\_IB\\_MSG\\_405](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012231](#); Symbol: [ER\\_IB\\_MSG\\_406](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012232](#); Symbol: [ER\\_IB\\_MSG\\_407](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012233](#); Symbol: [ER\\_IB\\_MSG\\_408](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-012234](#); Symbol: [ER\\_IB\\_MSG\\_409](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012235](#); Symbol: [ER\\_IB\\_MSG\\_410](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012236](#); Symbol: [ER\\_IB\\_MSG\\_411](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012237](#); Symbol: [ER\\_IB\\_MSG\\_412](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012238](#); Symbol: [ER\\_IB\\_MSG\\_413](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012239](#); Symbol: [ER\\_IB\\_MSG\\_414](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012240](#); Symbol: [ER\\_IB\\_MSG\\_415](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012241](#); Symbol: [ER\\_IB\\_MSG\\_416](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012242](#); Symbol: [ER\\_IB\\_MSG\\_417](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012243](#); Symbol: [ER\\_IB\\_MSG\\_418](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012244](#); Symbol: [ER\\_IB\\_MSG\\_419](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012245](#); Symbol: [ER\\_IB\\_MSG\\_420](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012246](#); Symbol: [ER\\_IB\\_MSG\\_421](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012247](#); Symbol: [ER\\_IB\\_MSG\\_422](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012248](#); Symbol: [ER\\_IB\\_MSG\\_423](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012249](#); Symbol: [ER\\_IB\\_MSG\\_424](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-012250](#); Symbol: [ER\\_IB\\_MSG\\_425](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012251](#); Symbol: [ER\\_IB\\_MSG\\_426](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012252](#); Symbol: [ER\\_IB\\_MSG\\_427](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012253](#); Symbol: [ER\\_IB\\_MSG\\_428](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012254](#); Symbol: [ER\\_IB\\_MSG\\_429](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012255](#); Symbol: [ER\\_IB\\_MSG\\_430](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012256](#); Symbol: [ER\\_IB\\_MSG\\_431](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012257](#); Symbol: [ER\\_IB\\_MSG\\_432](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012258](#); Symbol: [ER\\_IB\\_MSG\\_433](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012259](#); Symbol: [ER\\_IB\\_MSG\\_434](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012260](#); Symbol: [ER\\_IB\\_MSG\\_435](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012261](#); Symbol: [ER\\_IB\\_MSG\\_436](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012262](#); Symbol: [ER\\_IB\\_MSG\\_437](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012263](#); Symbol: [ER\\_IB\\_MSG\\_438](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012264](#); Symbol: [ER\\_IB\\_MSG\\_439](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012265](#); Symbol: [ER\\_IB\\_MSG\\_440](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-012266](#); Symbol: [ER\\_IB\\_MSG\\_441](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012267](#); Symbol: [ER\\_IB\\_MSG\\_442](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012268](#); Symbol: [ER\\_IB\\_MSG\\_443](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012269](#); Symbol: [ER\\_IB\\_MSG\\_444](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012270](#); Symbol: [ER\\_IB\\_MSG\\_445](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012271](#); Symbol: [ER\\_IB\\_MSG\\_446](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012272](#); Symbol: [ER\\_IB\\_MSG\\_447](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012273](#); Symbol: [ER\\_IB\\_MSG\\_448](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012274](#); Symbol: [ER\\_IB\\_MSG\\_449](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012275](#); Symbol: [ER\\_IB\\_MSG\\_450](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012276](#); Symbol: [ER\\_IB\\_MSG\\_451](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012277](#); Symbol: [ER\\_IB\\_MSG\\_452](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012278](#); Symbol: [ER\\_IB\\_MSG\\_453](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012279](#); Symbol: [ER\\_IB\\_MSG\\_454](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012280](#); Symbol: [ER\\_IB\\_MSG\\_455](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012281](#); Symbol: [ER\\_IB\\_MSG\\_456](#); SQLSTATE: [HY000](#)

Message: %s



- 
- Error number: [MY-012282](#); Symbol: [ER\\_IB\\_MSG\\_457](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012283](#); Symbol: [ER\\_IB\\_MSG\\_458](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012284](#); Symbol: [ER\\_IB\\_MSG\\_459](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012285](#); Symbol: [ER\\_IB\\_MSG\\_460](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012286](#); Symbol: [ER\\_IB\\_MSG\\_461](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012287](#); Symbol: [ER\\_IB\\_MSG\\_462](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012288](#); Symbol: [ER\\_IB\\_MSG\\_463](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012289](#); Symbol: [ER\\_IB\\_MSG\\_464](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012290](#); Symbol: [ER\\_IB\\_MSG\\_465](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012291](#); Symbol: [ER\\_IB\\_MSG\\_466](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012292](#); Symbol: [ER\\_IB\\_MSG\\_467](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012293](#); Symbol: [ER\\_IB\\_MSG\\_468](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012294](#); Symbol: [ER\\_IB\\_MSG\\_469](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012295](#); Symbol: [ER\\_IB\\_MSG\\_470](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012296](#); Symbol: [ER\\_IB\\_MSG\\_471](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012297](#); Symbol: [ER\\_IB\\_MSG\\_472](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012298](#); Symbol: [ER\\_IB\\_MSG\\_473](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-012299](#); Symbol: [ER\\_IB\\_MSG\\_474](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012300](#); Symbol: [ER\\_IB\\_MSG\\_475](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012301](#); Symbol: [ER\\_IB\\_MSG\\_476](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012302](#); Symbol: [ER\\_IB\\_MSG\\_477](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012303](#); Symbol: [ER\\_IB\\_MSG\\_478](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012304](#); Symbol: [ER\\_IB\\_MSG\\_479](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012305](#); Symbol: [ER\\_IB\\_MSG\\_480](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012306](#); Symbol: [ER\\_IB\\_MSG\\_481](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012307](#); Symbol: [ER\\_IB\\_MSG\\_482](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012308](#); Symbol: [ER\\_IB\\_MSG\\_483](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012309](#); Symbol: [ER\\_IB\\_MSG\\_484](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012310](#); Symbol: [ER\\_IB\\_MSG\\_485](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012311](#); Symbol: [ER\\_IB\\_MSG\\_486](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012312](#); Symbol: [ER\\_IB\\_MSG\\_487](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012313](#); Symbol: [ER\\_IB\\_MSG\\_488](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012314](#); Symbol: [ER\\_IB\\_MSG\\_489](#); SQLSTATE: [HY000](#)

Message: %s

- 
- Error number: [MY-012315](#); Symbol: [ER\\_IB\\_MSG\\_490](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012316](#); Symbol: [ER\\_IB\\_MSG\\_491](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012317](#); Symbol: [ER\\_IB\\_MSG\\_492](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012318](#); Symbol: [ER\\_IB\\_MSG\\_493](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012319](#); Symbol: [ER\\_IB\\_MSG\\_494](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012320](#); Symbol: [ER\\_IB\\_MSG\\_495](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012321](#); Symbol: [ER\\_IB\\_MSG\\_496](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012322](#); Symbol: [ER\\_IB\\_MSG\\_497](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012323](#); Symbol: [ER\\_IB\\_MSG\\_498](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012324](#); Symbol: [ER\\_IB\\_MSG\\_499](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012325](#); Symbol: [ER\\_IB\\_MSG\\_500](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012326](#); Symbol: [ER\\_IB\\_MSG\\_501](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012327](#); Symbol: [ER\\_IB\\_MSG\\_502](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012328](#); Symbol: [ER\\_IB\\_MSG\\_503](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012329](#); Symbol: [ER\\_IB\\_MSG\\_504](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012330](#); Symbol: [ER\\_IB\\_MSG\\_505](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012331](#); Symbol: [ER\\_IB\\_MSG\\_506](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-012332](#); Symbol: [ER\\_IB\\_MSG\\_507](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012333](#); Symbol: [ER\\_IB\\_MSG\\_508](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012334](#); Symbol: [ER\\_IB\\_MSG\\_509](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012335](#); Symbol: [ER\\_IB\\_MSG\\_510](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012336](#); Symbol: [ER\\_IB\\_MSG\\_511](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012337](#); Symbol: [ER\\_IB\\_MSG\\_512](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012338](#); Symbol: [ER\\_IB\\_MSG\\_513](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012339](#); Symbol: [ER\\_IB\\_MSG\\_514](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012340](#); Symbol: [ER\\_IB\\_MSG\\_515](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012341](#); Symbol: [ER\\_IB\\_MSG\\_516](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012342](#); Symbol: [ER\\_IB\\_MSG\\_517](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012343](#); Symbol: [ER\\_IB\\_MSG\\_518](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012344](#); Symbol: [ER\\_IB\\_MSG\\_519](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012345](#); Symbol: [ER\\_IB\\_MSG\\_520](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012346](#); Symbol: [ER\\_IB\\_MSG\\_521](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012347](#); Symbol: [ER\\_IB\\_MSG\\_522](#); SQLSTATE: [HY000](#)

Message: %s

- 
- Error number: [MY-012348](#); Symbol: [ER\\_IB\\_MSG\\_523](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012349](#); Symbol: [ER\\_IB\\_MSG\\_524](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012350](#); Symbol: [ER\\_IB\\_MSG\\_525](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012351](#); Symbol: [ER\\_IB\\_MSG\\_526](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012352](#); Symbol: [ER\\_IB\\_MSG\\_527](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012355](#); Symbol: [ER\\_IB\\_MSG\\_530](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012356](#); Symbol: [ER\\_IB\\_MSG\\_531](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012357](#); Symbol: [ER\\_IB\\_MSG\\_532](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012358](#); Symbol: [ER\\_IB\\_MSG\\_533](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012359](#); Symbol: [ER\\_IB\\_MSG\\_534](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012362](#); Symbol: [ER\\_IB\\_MSG\\_537](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012363](#); Symbol: [ER\\_IB\\_MSG\\_538](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012364](#); Symbol: [ER\\_IB\\_MSG\\_539](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012365](#); Symbol: [ER\\_IB\\_MSG\\_540](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012366](#); Symbol: [ER\\_IB\\_MSG\\_541](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012367](#); Symbol: [ER\\_IB\\_MSG\\_542](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012368](#); Symbol: [ER\\_IB\\_MSG\\_543](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-012369](#); Symbol: [ER\\_IB\\_MSG\\_544](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012370](#); Symbol: [ER\\_IB\\_MSG\\_545](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012371](#); Symbol: [ER\\_IB\\_MSG\\_546](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012372](#); Symbol: [ER\\_IB\\_MSG\\_547](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012373](#); Symbol: [ER\\_IB\\_MSG\\_548](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012374](#); Symbol: [ER\\_IB\\_MSG\\_549](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012375](#); Symbol: [ER\\_IB\\_MSG\\_550](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012376](#); Symbol: [ER\\_IB\\_MSG\\_551](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012377](#); Symbol: [ER\\_IB\\_MSG\\_552](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012378](#); Symbol: [ER\\_IB\\_MSG\\_553](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012379](#); Symbol: [ER\\_IB\\_MSG\\_554](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012380](#); Symbol: [ER\\_IB\\_MSG\\_555](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012381](#); Symbol: [ER\\_IB\\_MSG\\_556](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012382](#); Symbol: [ER\\_IB\\_MSG\\_557](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012383](#); Symbol: [ER\\_IB\\_MSG\\_558](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012384](#); Symbol: [ER\\_IB\\_MSG\\_559](#); SQLSTATE: [HY000](#)

Message: %s

- 
- Error number: [MY-012385](#); Symbol: [ER\\_IB\\_MSG\\_560](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012386](#); Symbol: [ER\\_IB\\_MSG\\_561](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012387](#); Symbol: [ER\\_IB\\_MSG\\_562](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012388](#); Symbol: [ER\\_IB\\_MSG\\_563](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012389](#); Symbol: [ER\\_IB\\_MSG\\_564](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012390](#); Symbol: [ER\\_IB\\_MSG\\_INVALID\\_LOCATION\\_FOR\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Cannot create a tablespace for table %s because the directory is not a valid location. %s
  - Error number: [MY-012391](#); Symbol: [ER\\_IB\\_MSG\\_566](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012392](#); Symbol: [ER\\_IB\\_MSG\\_567](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012393](#); Symbol: [ER\\_IB\\_MSG\\_568](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012394](#); Symbol: [ER\\_IB\\_MSG\\_569](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012395](#); Symbol: [ER\\_IB\\_MSG\\_570](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012396](#); Symbol: [ER\\_IB\\_MSG\\_571](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012398](#); Symbol: [ER\\_IB\\_MSG\\_573](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012399](#); Symbol: [ER\\_IB\\_MSG\\_574](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012403](#); Symbol: [ER\\_IB\\_MSG\\_578](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012404](#); Symbol: [ER\\_IB\\_MSG\\_579](#); SQLSTATE: [HY000](#)  
Message: %s

- 
- Error number: [MY-012405](#); Symbol: [ER\\_IB\\_MSG\\_580](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012406](#); Symbol: [ER\\_IB\\_MSG\\_581](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012407](#); Symbol: [ER\\_IB\\_MSG\\_582](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012408](#); Symbol: [ER\\_IB\\_MSG\\_583](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012409](#); Symbol: [ER\\_IB\\_MSG\\_584](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012410](#); Symbol: [ER\\_IB\\_MSG\\_585](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012411](#); Symbol: [ER\\_IB\\_MSG\\_586](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012412](#); Symbol: [ER\\_IB\\_MSG\\_587](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012413](#); Symbol: [ER\\_IB\\_MSG\\_588](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012414](#); Symbol: [ER\\_IB\\_MSG\\_589](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012415](#); Symbol: [ER\\_IB\\_MSG\\_590](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012416](#); Symbol: [ER\\_IB\\_MSG\\_591](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012417](#); Symbol: [ER\\_IB\\_MSG\\_592](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012418](#); Symbol: [ER\\_IB\\_MSG\\_593](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012419](#); Symbol: [ER\\_IB\\_MSG\\_594](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012420](#); Symbol: [ER\\_IB\\_MSG\\_595](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012421](#); Symbol: [ER\\_IB\\_MSG\\_596](#); SQLSTATE: [HY000](#)



---

Message: %s

- Error number: [MY-012422](#); Symbol: [ER\\_IB\\_MSG\\_597](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012423](#); Symbol: [ER\\_IB\\_MSG\\_598](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012424](#); Symbol: [ER\\_IB\\_MSG\\_599](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012425](#); Symbol: [ER\\_IB\\_MSG\\_600](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012426](#); Symbol: [ER\\_IB\\_MSG\\_601](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012427](#); Symbol: [ER\\_IB\\_MSG\\_602](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012428](#); Symbol: [ER\\_IB\\_MSG\\_603](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012429](#); Symbol: [ER\\_IB\\_MSG\\_604](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012430](#); Symbol: [ER\\_IB\\_MSG\\_605](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012431](#); Symbol: [ER\\_IB\\_MSG\\_606](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012432](#); Symbol: [ER\\_IB\\_MSG\\_607](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012433](#); Symbol: [ER\\_IB\\_MSG\\_608](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012434](#); Symbol: [ER\\_IB\\_MSG\\_609](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012435](#); Symbol: [ER\\_IB\\_MSG\\_610](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012436](#); Symbol: [ER\\_IB\\_MSG\\_611](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012437](#); Symbol: [ER\\_IB\\_MSG\\_612](#); SQLSTATE: [HY000](#)

Message: %s

- 
- Error number: [MY-012438](#); Symbol: [ER\\_IB\\_MSG\\_613](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012439](#); Symbol: [ER\\_IB\\_MSG\\_614](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012440](#); Symbol: [ER\\_IB\\_MSG\\_615](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012441](#); Symbol: [ER\\_IB\\_MSG\\_616](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012442](#); Symbol: [ER\\_IB\\_MSG\\_617](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012443](#); Symbol: [ER\\_IB\\_MSG\\_618](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012444](#); Symbol: [ER\\_IB\\_MSG\\_619](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012445](#); Symbol: [ER\\_IB\\_MSG\\_620](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012446](#); Symbol: [ER\\_IB\\_MSG\\_621](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012447](#); Symbol: [ER\\_IB\\_MSG\\_622](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012448](#); Symbol: [ER\\_IB\\_MSG\\_623](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012449](#); Symbol: [ER\\_IB\\_MSG\\_624](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012450](#); Symbol: [ER\\_IB\\_MSG\\_625](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012451](#); Symbol: [ER\\_IB\\_MSG\\_626](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012452](#); Symbol: [ER\\_IB\\_MSG\\_627](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012453](#); Symbol: [ER\\_IB\\_MSG\\_628](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012454](#); Symbol: [ER\\_IB\\_MSG\\_629](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-012455](#); Symbol: [ER\\_IB\\_MSG\\_630](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012456](#); Symbol: [ER\\_IB\\_MSG\\_631](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012457](#); Symbol: [ER\\_IB\\_MSG\\_632](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012458](#); Symbol: [ER\\_IB\\_MSG\\_633](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012459](#); Symbol: [ER\\_IB\\_MSG\\_634](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012460](#); Symbol: [ER\\_IB\\_MSG\\_635](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012461](#); Symbol: [ER\\_IB\\_MSG\\_636](#); SQLSTATE: [HY000](#)

Message: Blocked High Priority Transaction (ID %llu, Thread ID %s) forces rollback of the blocking transaction (ID %llu - %s).

- Error number: [MY-012462](#); Symbol: [ER\\_IB\\_MSG\\_637](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012463](#); Symbol: [ER\\_IB\\_MSG\\_638](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012464](#); Symbol: [ER\\_IB\\_MSG\\_639](#); SQLSTATE: [HY000](#)

Message: Blocked High Priority Transaction (Thread ID %s) waking up the blocking transaction (ID %llu) by pretending it's a deadlock victim.

- Error number: [MY-012467](#); Symbol: [ER\\_IB\\_MSG\\_642](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012468](#); Symbol: [ER\\_IB\\_MSG\\_643](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012469](#); Symbol: [ER\\_IB\\_MSG\\_644](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012470](#); Symbol: [ER\\_IB\\_MSG\\_645](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012471](#); Symbol: [ER\\_IB\\_MSG\\_646](#); SQLSTATE: [HY000](#)

Message: %s

- 
- Error number: [MY-012472](#); Symbol: [ER\\_IB\\_MSG\\_647](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012473](#); Symbol: [ER\\_IB\\_MSG\\_648](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012474](#); Symbol: [ER\\_IB\\_MSG\\_649](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012475](#); Symbol: [ER\\_IB\\_MSG\\_650](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012476](#); Symbol: [ER\\_IB\\_MSG\\_651](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012477](#); Symbol: [ER\\_IB\\_MSG\\_652](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012478](#); Symbol: [ER\\_IB\\_MSG\\_DDL\\_LOG\\_DELETE\\_BY\\_ID\\_OK](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012479](#); Symbol: [ER\\_IB\\_MSG\\_654](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012480](#); Symbol: [ER\\_IB\\_MSG\\_655](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012481](#); Symbol: [ER\\_IB\\_MSG\\_656](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012482](#); Symbol: [ER\\_IB\\_MSG\\_657](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012483](#); Symbol: [ER\\_IB\\_MSG\\_658](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012484](#); Symbol: [ER\\_IB\\_MSG\\_659](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012485](#); Symbol: [ER\\_IB\\_MSG\\_660](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012486](#); Symbol: [ER\\_IB\\_MSG\\_661](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012487](#); Symbol: [ER\\_IB\\_MSG\\_662](#); SQLSTATE: [HY000](#)  
Message: %s

- Error number: [MY-012488](#); Symbol: [ER\\_IB\\_MSG\\_663](#); SQLSTATE: [HY000](#)  
 Message: %s
- Error number: [MY-012519](#); Symbol: [ER\\_IB\\_MSG\\_694](#); SQLSTATE: [HY000](#)  
 Message: ##### CORRUPT LOG RECORD FOUND #####
- Error number: [MY-012520](#); Symbol: [ER\\_IB\\_MSG\\_695](#); SQLSTATE: [HY000](#)  
 Message: Log record type %d, page %lu:%lu. Log parsing proceeded successfully up to %llu. Previous log record type %d, is multi %llu Recv offset %zd, prev %llu
- Error number: [MY-012521](#); Symbol: [ER\\_IB\\_MSG\\_696](#); SQLSTATE: [HY000](#)  
 Message: Hex dump starting %llu bytes before and ending %llu bytes after the corrupted record:
- Error number: [MY-012522](#); Symbol: [ER\\_IB\\_MSG\\_697](#); SQLSTATE: [HY000](#)  
 Message: Set innodb\_force\_recovery to ignore this error.
- Error number: [MY-012523](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_CORRUPT](#); SQLSTATE: [HY000](#)  
 Message: The redo log file may have been corrupt and it is possible that the log scan did not proceed far enough in recovery! Please run CHECK TABLE on your InnoDB tables to check that they are ok! If mysqld crashes after this recovery; %s
- Error number: [MY-012524](#); Symbol: [ER\\_IB\\_MSG\\_699](#); SQLSTATE: [HY000](#)  
 Message: %llu pages with log records were left unprocessed!
- Error number: [MY-012525](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FORMAT\\_OLD\\_AND\\_LOG\\_CORRUPTED](#); SQLSTATE: [HY000](#)  
 Message: Upgrade after a crash is not supported. This redo log was created with %s, and it appears corrupted. Please follow the instructions at %s
- Error number: [MY-012526](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FORMAT\\_OLD\\_AND\\_NO\\_CLEAN\\_SHUTDOWN](#); SQLSTATE: [HY000](#)  
 Message: Upgrade is not supported after a crash or shutdown with innodb\_fast\_shutdown = 2. This redo log was created with %s, and it appears logically non empty. Please follow the instructions at %s
- Error number: [MY-012529](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FORMAT\\_BEFORE\\_8\\_0\\_30](#); SQLSTATE: [HY000](#)  
 Message: Redo log format is v%lu. The redo log was created before MySQL 8.0.30.
- Error number: [MY-012530](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_FORMAT\\_UNKNOWN](#); SQLSTATE: [HY000](#)  
 Message: Unknown redo log format (v%lu) in file %s. Please follow the instructions at %s
- Error number: [MY-012531](#); Symbol: [ER\\_IB\\_MSG\\_RECOVERY\\_CHECKPOINT\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)  
 Message: No valid checkpoint found (corrupted redo log). You can try --innodb-force-recovery=6 as a last resort.
- Error number: [MY-012532](#); Symbol: [ER\\_IB\\_MSG\\_707](#); SQLSTATE: [HY000](#)  
 Message: Applying a batch of %llu redo log records ...

- 
- Error number: [MY-012533](#); Symbol: [ER\\_IB\\_MSG\\_708](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012534](#); Symbol: [ER\\_IB\\_MSG\\_709](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012535](#); Symbol: [ER\\_IB\\_MSG\\_710](#); SQLSTATE: [HY000](#)  
Message: Apply batch completed!
  - Error number: [MY-012536](#); Symbol: [ER\\_IB\\_MSG\\_711](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012537](#); Symbol: [ER\\_IB\\_MSG\\_712](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012538](#); Symbol: [ER\\_IB\\_MSG\\_713](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012539](#); Symbol: [ER\\_IB\\_MSG\\_714](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012540](#); Symbol: [ER\\_IB\\_MSG\\_715](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012541](#); Symbol: [ER\\_IB\\_MSG\\_716](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012543](#); Symbol: [ER\\_IB\\_MSG\\_718](#); SQLSTATE: [HY000](#)  
Message: Extending tablespace : %lu space name: %s to new size: %lu pages during recovery.
  - Error number: [MY-012544](#); Symbol: [ER\\_IB\\_MSG\\_719](#); SQLSTATE: [HY000](#)  
Message: Could not extend tablespace: %lu space name: %s to new size: %lu pages during recovery.
  - Error number: [MY-012545](#); Symbol: [ER\\_IB\\_MSG\\_720](#); SQLSTATE: [HY000](#)  
Message: Log block %lu at lsn %llu has valid header, but checksum field contains %lu, should be %lu.
  - Error number: [MY-012546](#); Symbol: [ER\\_IB\\_MSG\\_RECOVERY\\_SKIPPED\\_IN\\_READ\\_ONLY\\_MODE](#); SQLSTATE: [HY000](#)  
Message: Skipped necessary redo log applying, --innodb-read-only set!
  - Error number: [MY-012547](#); Symbol: [ER\\_IB\\_MSG\\_722](#); SQLSTATE: [HY000](#)  
Message: Log scan progressed past the checkpoint LSN %llu.
  - Error number: [MY-012548](#); Symbol: [ER\\_IB\\_MSG\\_723](#); SQLSTATE: [HY000](#)  
Message: Log parsing buffer overflow. Recovery may have failed! Please set log\_buffer\_size to a value higher than %lu.

- 
- Error number: [MY-012549](#); Symbol: [ER\\_IB\\_MSG\\_724](#); SQLSTATE: [HY000](#)  
Message: Set innodb\_force\_recovery to ignore this error.
  - Error number: [MY-012550](#); Symbol: [ER\\_IB\\_MSG\\_725](#); SQLSTATE: [HY000](#)  
Message: Doing recovery: scanned up to log sequence number %llu
  - Error number: [MY-012551](#); Symbol: [ER\\_IB\\_MSG\\_726](#); SQLSTATE: [HY000](#)  
Message: Database was not shutdown normally!
  - Error number: [MY-012552](#); Symbol: [ER\\_IB\\_MSG\\_727](#); SQLSTATE: [HY000](#)  
Message: Starting crash recovery.
  - Error number: [MY-012553](#); Symbol: [ER\\_IB\\_MSG\\_728](#); SQLSTATE: [HY000](#)  
Message: The user has set SRV\_FORCE\_NO\_LOG\_REDO on, skipping log redo
  - Error number: [MY-012554](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILES\\_CREATED\\_BY\\_MEB\\_AND\\_READ\\_ONLY\\_MODE](#); SQLSTATE: [HY000](#)  
Message: Cannot restore from mysqlbackup, InnoDB running in read-only mode!
  - Error number: [MY-012555](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILES\\_CREATED\\_BY\\_MEB](#); SQLSTATE: [HY000](#)  
Message: The redo log file was created by mysqlbackup --apply-log at %s. The following crash recovery is part of a normal restore.
  - Error number: [MY-012556](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILES\\_CREATED\\_BY\\_CLONE](#); SQLSTATE: [HY000](#)  
Message: Opening cloned database
  - Error number: [MY-012557](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FORMAT\\_OLD](#); SQLSTATE: [HY000](#)  
Message: Redo log is from an earlier version, v%lu.
  - Error number: [MY-012559](#); Symbol: [ER\\_IB\\_MSG\\_RECOVERY\\_CHECKPOINT\\_FROM\\_BEFORE\\_CLEAN\\_SHUTDOWN](#); SQLSTATE: [HY000](#)  
Message: Are you sure you are using the right redo log files to start up the database? Log sequence number in the redo log files is %llu, less than the log sequence number in the first system tablespace file header, %llu.
  - Error number: [MY-012560](#); Symbol: [ER\\_IB\\_MSG\\_RECOVERY\\_IS\\_NEEDED](#); SQLSTATE: [HY000](#)  
Message: The log sequence number %llu in the system tablespace does not match the log sequence number %llu in the redo log files!
  - Error number: [MY-012561](#); Symbol: [ER\\_IB\\_MSG\\_RECOVERY\\_IN\\_READ\\_ONLY](#); SQLSTATE: [HY000](#)  
Message: Can't initiate database recovery, running in read-only-mode.
  - Error number: [MY-012562](#); Symbol: [ER\\_IB\\_MSG\\_737](#); SQLSTATE: [HY000](#)  
Message: We scanned the log up to %llu. A checkpoint was at %llu and the maximum LSN on a database page was %llu. It is possible that the database is now corrupt!
  - Error number: [MY-012563](#); Symbol: [ER\\_IB\\_MSG\\_738](#); SQLSTATE: [HY000](#)  
Message: Waiting for recv\_writer to finish flushing of buffer pool

- 
- Error number: [MY-012564](#); Symbol: [ER\\_IB\\_MSG\\_739](#); SQLSTATE: [HY000](#)  
Message: Recovery parsing buffer extended to %zu.
  - Error number: [MY-012565](#); Symbol: [ER\\_IB\\_MSG\\_740](#); SQLSTATE: [HY000](#)  
Message: Out of memory while resizing recovery parsing buffer.
  - Error number: [MY-012566](#); Symbol: [ER\\_IB\\_MSG\\_741](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012567](#); Symbol: [ER\\_IB\\_MSG\\_742](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012568](#); Symbol: [ER\\_IB\\_MSG\\_743](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012569](#); Symbol: [ER\\_IB\\_MSG\\_744](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012570](#); Symbol: [ER\\_IB\\_MSG\\_745](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012571](#); Symbol: [ER\\_IB\\_MSG\\_746](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012572](#); Symbol: [ER\\_IB\\_MSG\\_747](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012573](#); Symbol: [ER\\_IB\\_MSG\\_748](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012574](#); Symbol: [ER\\_IB\\_MSG\\_749](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012575](#); Symbol: [ER\\_IB\\_MSG\\_750](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012576](#); Symbol: [ER\\_IB\\_MSG\\_751](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012577](#); Symbol: [ER\\_IB\\_MSG\\_752](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012578](#); Symbol: [ER\\_IB\\_MSG\\_753](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012579](#); Symbol: [ER\\_IB\\_MSG\\_754](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012580](#); Symbol: [ER\\_IB\\_MSG\\_755](#); SQLSTATE: [HY000](#)



---

Message: %s

- Error number: [MY-012581](#); Symbol: [ER\\_IB\\_MSG\\_756](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012582](#); Symbol: [ER\\_IB\\_MSG\\_757](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012583](#); Symbol: [ER\\_IB\\_MSG\\_758](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012584](#); Symbol: [ER\\_IB\\_MSG\\_759](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012585](#); Symbol: [ER\\_IB\\_MSG\\_760](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012586](#); Symbol: [ER\\_IB\\_MSG\\_761](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012587](#); Symbol: [ER\\_IB\\_MSG\\_762](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012588](#); Symbol: [ER\\_IB\\_MSG\\_763](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012589](#); Symbol: [ER\\_IB\\_MSG\\_764](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012590](#); Symbol: [ER\\_IB\\_MSG\\_765](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012591](#); Symbol: [ER\\_IB\\_MSG\\_766](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012592](#); Symbol: [ER\\_IB\\_MSG\\_767](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012593](#); Symbol: [ER\\_IB\\_MSG\\_768](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012594](#); Symbol: [ER\\_IB\\_MSG\\_769](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012595](#); Symbol: [ER\\_IB\\_MSG\\_770](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012596](#); Symbol: [ER\\_IB\\_MSG\\_771](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-012597](#); Symbol: [ER\\_IB\\_MSG\\_772](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012598](#); Symbol: [ER\\_IB\\_MSG\\_773](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012599](#); Symbol: [ER\\_IB\\_MSG\\_774](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012600](#); Symbol: [ER\\_IB\\_MSG\\_775](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012601](#); Symbol: [ER\\_IB\\_MSG\\_776](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012602](#); Symbol: [ER\\_IB\\_MSG\\_777](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012603](#); Symbol: [ER\\_IB\\_MSG\\_778](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012604](#); Symbol: [ER\\_IB\\_MSG\\_779](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012605](#); Symbol: [ER\\_IB\\_MSG\\_780](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012606](#); Symbol: [ER\\_IB\\_MSG\\_781](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012607](#); Symbol: [ER\\_IB\\_MSG\\_782](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012608](#); Symbol: [ER\\_IB\\_MSG\\_783](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012609](#); Symbol: [ER\\_IB\\_MSG\\_784](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012610](#); Symbol: [ER\\_IB\\_MSG\\_785](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012611](#); Symbol: [ER\\_IB\\_MSG\\_786](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012612](#); Symbol: [ER\\_IB\\_MSG\\_787](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-012613](#); Symbol: [ER\\_IB\\_MSG\\_788](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012614](#); Symbol: [ER\\_IB\\_MSG\\_789](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012615](#); Symbol: [ER\\_IB\\_MSG\\_790](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012616](#); Symbol: [ER\\_IB\\_MSG\\_791](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012617](#); Symbol: [ER\\_IB\\_MSG\\_792](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012618](#); Symbol: [ER\\_IB\\_MSG\\_793](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012619](#); Symbol: [ER\\_IB\\_MSG\\_794](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012620](#); Symbol: [ER\\_IB\\_MSG\\_795](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012621](#); Symbol: [ER\\_IB\\_MSG\\_796](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012622](#); Symbol: [ER\\_IB\\_MSG\\_797](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012623](#); Symbol: [ER\\_IB\\_MSG\\_798](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012624](#); Symbol: [ER\\_IB\\_MSG\\_799](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012625](#); Symbol: [ER\\_IB\\_MSG\\_800](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012626](#); Symbol: [ER\\_IB\\_MSG\\_801](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012627](#); Symbol: [ER\\_IB\\_MSG\\_802](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012628](#); Symbol: [ER\\_IB\\_MSG\\_803](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-012629](#); Symbol: [ER\\_IB\\_MSG\\_804](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012630](#); Symbol: [ER\\_IB\\_MSG\\_805](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012631](#); Symbol: [ER\\_IB\\_MSG\\_806](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012632](#); Symbol: [ER\\_IB\\_MSG\\_807](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012633](#); Symbol: [ER\\_IB\\_MSG\\_808](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012634](#); Symbol: [ER\\_IB\\_MSG\\_809](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012635](#); Symbol: [ER\\_IB\\_MSG\\_810](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012636](#); Symbol: [ER\\_IB\\_MSG\\_811](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012637](#); Symbol: [ER\\_IB\\_MSG\\_812](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012638](#); Symbol: [ER\\_IB\\_MSG\\_813](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012639](#); Symbol: [ER\\_IB\\_MSG\\_814](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012640](#); Symbol: [ER\\_IB\\_MSG\\_815](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012641](#); Symbol: [ER\\_IB\\_MSG\\_816](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012642](#); Symbol: [ER\\_IB\\_MSG\\_817](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012643](#); Symbol: [ER\\_IB\\_MSG\\_818](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012644](#); Symbol: [ER\\_IB\\_MSG\\_819](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-012645](#); Symbol: [ER\\_IB\\_MSG\\_820](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012646](#); Symbol: [ER\\_IB\\_MSG\\_821](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012647](#); Symbol: [ER\\_IB\\_MSG\\_822](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012648](#); Symbol: [ER\\_IB\\_MSG\\_823](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012649](#); Symbol: [ER\\_IB\\_MSG\\_824](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012650](#); Symbol: [ER\\_IB\\_MSG\\_825](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012651](#); Symbol: [ER\\_IB\\_MSG\\_826](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012652](#); Symbol: [ER\\_IB\\_MSG\\_827](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012653](#); Symbol: [ER\\_IB\\_MSG\\_828](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012654](#); Symbol: [ER\\_IB\\_MSG\\_829](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012655](#); Symbol: [ER\\_IB\\_MSG\\_830](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012656](#); Symbol: [ER\\_IB\\_MSG\\_831](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012657](#); Symbol: [ER\\_IB\\_MSG\\_832](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012658](#); Symbol: [ER\\_IB\\_MSG\\_833](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012659](#); Symbol: [ER\\_IB\\_MSG\\_834](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012660](#); Symbol: [ER\\_IB\\_MSG\\_835](#); SQLSTATE: [HY000](#)

Message: %s

- 
- Error number: [MY-012661](#); Symbol: [ER\\_IB\\_MSG\\_836](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012662](#); Symbol: [ER\\_IB\\_MSG\\_837](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012663](#); Symbol: [ER\\_IB\\_MSG\\_838](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012664](#); Symbol: [ER\\_IB\\_MSG\\_839](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012665](#); Symbol: [ER\\_IB\\_MSG\\_840](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012666](#); Symbol: [ER\\_IB\\_MSG\\_841](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012667](#); Symbol: [ER\\_IB\\_MSG\\_842](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012668](#); Symbol: [ER\\_IB\\_MSG\\_CANT\\_ENCRYPT\\_REDO\\_LOG\\_DATA](#); SQLSTATE: [HY000](#)  
Message: Can't encrypt data of redo log
  - Error number: [MY-012669](#); Symbol: [ER\\_IB\\_MSG\\_844](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012670](#); Symbol: [ER\\_IB\\_MSG\\_845](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012671](#); Symbol: [ER\\_IB\\_MSG\\_846](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012672](#); Symbol: [ER\\_IB\\_MSG\\_847](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012673](#); Symbol: [ER\\_IB\\_MSG\\_848](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012674](#); Symbol: [ER\\_IB\\_MSG\\_849](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012675](#); Symbol: [ER\\_IB\\_MSG\\_850](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012676](#); Symbol: [ER\\_IB\\_MSG\\_851](#); SQLSTATE: [HY000](#)  
Message: %s

- 
- Error number: [MY-012677](#); Symbol: [ER\\_IB\\_MSG\\_852](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012678](#); Symbol: [ER\\_IB\\_MSG\\_853](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012679](#); Symbol: [ER\\_IB\\_MSG\\_854](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012680](#); Symbol: [ER\\_IB\\_MSG\\_855](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012681](#); Symbol: [ER\\_IB\\_MSG\\_856](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012682](#); Symbol: [ER\\_IB\\_MSG\\_857](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012683](#); Symbol: [ER\\_IB\\_MSG\\_858](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012684](#); Symbol: [ER\\_IB\\_MSG\\_859](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012685](#); Symbol: [ER\\_IB\\_MSG\\_860](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012686](#); Symbol: [ER\\_IB\\_MSG\\_861](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012687](#); Symbol: [ER\\_IB\\_MSG\\_862](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012688](#); Symbol: [ER\\_IB\\_MSG\\_863](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012689](#); Symbol: [ER\\_IB\\_MSG\\_864](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012690](#); Symbol: [ER\\_IB\\_MSG\\_865](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012691](#); Symbol: [ER\\_IB\\_MSG\\_866](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012692](#); Symbol: [ER\\_IB\\_MSG\\_867](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012693](#); Symbol: [ER\\_IB\\_MSG\\_868](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-012694](#); Symbol: [ER\\_IB\\_MSG\\_869](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012695](#); Symbol: [ER\\_IB\\_MSG\\_870](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012696](#); Symbol: [ER\\_IB\\_MSG\\_871](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012697](#); Symbol: [ER\\_IB\\_MSG\\_872](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012698](#); Symbol: [ER\\_IB\\_MSG\\_873](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012699](#); Symbol: [ER\\_IB\\_MSG\\_874](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012700](#); Symbol: [ER\\_IB\\_MSG\\_875](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012701](#); Symbol: [ER\\_IB\\_MSG\\_876](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012702](#); Symbol: [ER\\_IB\\_MSG\\_877](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012703](#); Symbol: [ER\\_IB\\_MSG\\_878](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012704](#); Symbol: [ER\\_IB\\_MSG\\_879](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012705](#); Symbol: [ER\\_IB\\_MSG\\_880](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012706](#); Symbol: [ER\\_IB\\_MSG\\_881](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012707](#); Symbol: [ER\\_IB\\_MSG\\_882](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012708](#); Symbol: [ER\\_IB\\_MSG\\_883](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012709](#); Symbol: [ER\\_IB\\_MSG\\_884](#); SQLSTATE: [HY000](#)



---

Message: %s

- Error number: [MY-012710](#); Symbol: [ER\\_IB\\_MSG\\_885](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012711](#); Symbol: [ER\\_IB\\_MSG\\_886](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012712](#); Symbol: [ER\\_IB\\_MSG\\_887](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012713](#); Symbol: [ER\\_IB\\_MSG\\_888](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012714](#); Symbol: [ER\\_IB\\_MSG\\_889](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012715](#); Symbol: [ER\\_IB\\_MSG\\_890](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012716](#); Symbol: [ER\\_IB\\_MSG\\_891](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012717](#); Symbol: [ER\\_IB\\_MSG\\_892](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012718](#); Symbol: [ER\\_IB\\_MSG\\_893](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012719](#); Symbol: [ER\\_IB\\_MSG\\_894](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012720](#); Symbol: [ER\\_IB\\_MSG\\_895](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012721](#); Symbol: [ER\\_IB\\_MSG\\_896](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012722](#); Symbol: [ER\\_IB\\_MSG\\_897](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012723](#); Symbol: [ER\\_IB\\_MSG\\_898](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012724](#); Symbol: [ER\\_IB\\_MSG\\_899](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012725](#); Symbol: [ER\\_IB\\_MSG\\_900](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-012726](#); Symbol: [ER\\_IB\\_MSG\\_901](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012727](#); Symbol: [ER\\_IB\\_MSG\\_902](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012728](#); Symbol: [ER\\_IB\\_MSG\\_903](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012729](#); Symbol: [ER\\_IB\\_MSG\\_904](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012730](#); Symbol: [ER\\_IB\\_MSG\\_905](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012731](#); Symbol: [ER\\_IB\\_MSG\\_906](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012732](#); Symbol: [ER\\_IB\\_MSG\\_907](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012733](#); Symbol: [ER\\_IB\\_MSG\\_908](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012734](#); Symbol: [ER\\_IB\\_MSG\\_909](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012735](#); Symbol: [ER\\_IB\\_MSG\\_910](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012736](#); Symbol: [ER\\_IB\\_MSG\\_911](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012737](#); Symbol: [ER\\_IB\\_MSG\\_912](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012738](#); Symbol: [ER\\_IB\\_MSG\\_913](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012739](#); Symbol: [ER\\_IB\\_MSG\\_914](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012740](#); Symbol: [ER\\_IB\\_MSG\\_915](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012741](#); Symbol: [ER\\_IB\\_MSG\\_916](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-012742](#); Symbol: [ER\\_IB\\_MSG\\_917](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012743](#); Symbol: [ER\\_IB\\_MSG\\_918](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012744](#); Symbol: [ER\\_IB\\_MSG\\_919](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012745](#); Symbol: [ER\\_IB\\_MSG\\_920](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012746](#); Symbol: [ER\\_IB\\_MSG\\_921](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012747](#); Symbol: [ER\\_IB\\_MSG\\_922](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012748](#); Symbol: [ER\\_IB\\_MSG\\_923](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012749](#); Symbol: [ER\\_IB\\_MSG\\_924](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012750](#); Symbol: [ER\\_IB\\_MSG\\_925](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012751](#); Symbol: [ER\\_IB\\_MSG\\_926](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012752](#); Symbol: [ER\\_IB\\_MSG\\_927](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012753](#); Symbol: [ER\\_IB\\_MSG\\_928](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012754](#); Symbol: [ER\\_IB\\_MSG\\_929](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012755](#); Symbol: [ER\\_IB\\_MSG\\_930](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012756](#); Symbol: [ER\\_IB\\_MSG\\_931](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012757](#); Symbol: [ER\\_IB\\_MSG\\_932](#); SQLSTATE: [HY000](#)

Message: %s

- 
- Error number: [MY-012758](#); Symbol: [ER\\_IB\\_MSG\\_933](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012759](#); Symbol: [ER\\_IB\\_MSG\\_934](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012760](#); Symbol: [ER\\_IB\\_MSG\\_935](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012761](#); Symbol: [ER\\_IB\\_MSG\\_936](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012762](#); Symbol: [ER\\_IB\\_MSG\\_937](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012763](#); Symbol: [ER\\_IB\\_MSG\\_938](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012764](#); Symbol: [ER\\_IB\\_MSG\\_939](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012765](#); Symbol: [ER\\_IB\\_MSG\\_940](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012766](#); Symbol: [ER\\_IB\\_MSG\\_941](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012767](#); Symbol: [ER\\_IB\\_MSG\\_942](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012768](#); Symbol: [ER\\_IB\\_MSG\\_943](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012769](#); Symbol: [ER\\_IB\\_MSG\\_944](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012770](#); Symbol: [ER\\_IB\\_MSG\\_945](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012771](#); Symbol: [ER\\_IB\\_MSG\\_946](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012772](#); Symbol: [ER\\_IB\\_IMPORT\\_INDEX\\_METADATA\\_READ\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: IO Error: %s
  - Error number: [MY-012773](#); Symbol: [ER\\_IB\\_MSG\\_948](#); SQLSTATE: [HY000](#)  
Message: %s

- 
- Error number: [MY-012774](#); Symbol: [ER\\_IB\\_MSG\\_949](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012775](#); Symbol: [ER\\_IB\\_MSG\\_950](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012776](#); Symbol: [ER\\_IB\\_MSG\\_951](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012777](#); Symbol: [ER\\_IB\\_MSG\\_952](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012778](#); Symbol: [ER\\_IB\\_MSG\\_953](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012779](#); Symbol: [ER\\_IB\\_MSG\\_954](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012780](#); Symbol: [ER\\_IB\\_MSG\\_955](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012781](#); Symbol: [ER\\_IB\\_MSG\\_956](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012782](#); Symbol: [ER\\_IB\\_MSG\\_957](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012783](#); Symbol: [ER\\_IB\\_MSG\\_958](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012784](#); Symbol: [ER\\_IB\\_MSG\\_959](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012785](#); Symbol: [ER\\_IB\\_MSG\\_960](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012786](#); Symbol: [ER\\_IB\\_MSG\\_961](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012787](#); Symbol: [ER\\_IB\\_MSG\\_962](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012788](#); Symbol: [ER\\_IB\\_MSG\\_963](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012789](#); Symbol: [ER\\_IB\\_MSG\\_964](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012790](#); Symbol: [ER\\_IB\\_MSG\\_965](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-012791](#); Symbol: [ER\\_IB\\_MSG\\_966](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012792](#); Symbol: [ER\\_IB\\_MSG\\_967](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012793](#); Symbol: [ER\\_IB\\_MSG\\_968](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012794](#); Symbol: [ER\\_IB\\_MSG\\_969](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012795](#); Symbol: [ER\\_IB\\_MSG\\_970](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012796](#); Symbol: [ER\\_IB\\_MSG\\_971](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012797](#); Symbol: [ER\\_IB\\_MSG\\_972](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012798](#); Symbol: [ER\\_IB\\_MSG\\_973](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012799](#); Symbol: [ER\\_IB\\_MSG\\_974](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012800](#); Symbol: [ER\\_IB\\_MSG\\_975](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012801](#); Symbol: [ER\\_IB\\_MSG\\_976](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012802](#); Symbol: [ER\\_IB\\_MSG\\_977](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012803](#); Symbol: [ER\\_IB\\_MSG\\_978](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012804](#); Symbol: [ER\\_IB\\_MSG\\_979](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012805](#); Symbol: [ER\\_IB\\_MSG\\_980](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012806](#); Symbol: [ER\\_IB\\_MSG\\_981](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-012807](#); Symbol: [ER\\_IB\\_MSG\\_982](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012808](#); Symbol: [ER\\_IB\\_MSG\\_983](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012809](#); Symbol: [ER\\_IB\\_MSG\\_984](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012810](#); Symbol: [ER\\_IB\\_MSG\\_985](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012811](#); Symbol: [ER\\_IB\\_MSG\\_986](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012812](#); Symbol: [ER\\_IB\\_MSG\\_987](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012813](#); Symbol: [ER\\_IB\\_MSG\\_988](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012814](#); Symbol: [ER\\_IB\\_MSG\\_989](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012815](#); Symbol: [ER\\_IB\\_MSG\\_990](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012816](#); Symbol: [ER\\_IB\\_MSG\\_991](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012817](#); Symbol: [ER\\_IB\\_MSG\\_992](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012818](#); Symbol: [ER\\_IB\\_MSG\\_993](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012819](#); Symbol: [ER\\_IB\\_MSG\\_994](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012820](#); Symbol: [ER\\_IB\\_MSG\\_995](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012821](#); Symbol: [ER\\_IB\\_MSG\\_996](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012822](#); Symbol: [ER\\_IB\\_MSG\\_997](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-012823](#); Symbol: [ER\\_IB\\_MSG\\_998](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012824](#); Symbol: [ER\\_IB\\_MSG\\_999](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012825](#); Symbol: [ER\\_IB\\_MSG\\_1000](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012826](#); Symbol: [ER\\_IB\\_MSG\\_1001](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012827](#); Symbol: [ER\\_IB\\_MSG\\_1002](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012828](#); Symbol: [ER\\_IB\\_MSG\\_1003](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012829](#); Symbol: [ER\\_IB\\_MSG\\_1004](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012830](#); Symbol: [ER\\_IB\\_MSG\\_1005](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012831](#); Symbol: [ER\\_IB\\_MSG\\_1006](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012832](#); Symbol: [ER\\_IB\\_MSG\\_1007](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012833](#); Symbol: [ER\\_IB\\_MSG\\_1008](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012834](#); Symbol: [ER\\_IB\\_MSG\\_1009](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012835](#); Symbol: [ER\\_IB\\_MSG\\_1010](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012836](#); Symbol: [ER\\_IB\\_MSG\\_1011](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012837](#); Symbol: [ER\\_IB\\_MSG\\_1012](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012838](#); Symbol: [ER\\_IB\\_MSG\\_1013](#); SQLSTATE: [HY000](#)

Message: %s



- 
- Error number: [MY-012839](#); Symbol: [ER\\_IB\\_IMPORT\\_START\\_CFG\\_NAME](#); SQLSTATE: [HY000](#)  
Message: Writing table metadata to '%s'
  - Error number: [MY-012840](#); Symbol: [ER\\_IB\\_MSG\\_1015](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012841](#); Symbol: [ER\\_IB\\_MSG\\_1016](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012842](#); Symbol: [ER\\_IB\\_MSG\\_1017](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012843](#); Symbol: [ER\\_IB\\_MSG\\_1018](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012844](#); Symbol: [ER\\_IB\\_MSG\\_1019](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012845](#); Symbol: [ER\\_IB\\_MSG\\_1020](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012846](#); Symbol: [ER\\_IB\\_MSG\\_1021](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012847](#); Symbol: [ER\\_IB\\_MSG\\_1022](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012848](#); Symbol: [ER\\_IB\\_MSG\\_1023](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012849](#); Symbol: [ER\\_IB\\_MSG\\_1024](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012850](#); Symbol: [ER\\_IB\\_MSG\\_1025](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012851](#); Symbol: [ER\\_IB\\_MSG\\_1026](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012852](#); Symbol: [ER\\_IB\\_MSG\\_1027](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012853](#); Symbol: [ER\\_IB\\_MSG\\_1028](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012854](#); Symbol: [ER\\_IB\\_MSG\\_1029](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012855](#); Symbol: [ER\\_IB\\_MSG\\_1030](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-012856](#); Symbol: [ER\\_IB\\_MSG\\_1031](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012857](#); Symbol: [ER\\_IB\\_MSG\\_1032](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012858](#); Symbol: [ER\\_IB\\_MSG\\_1033](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012859](#); Symbol: [ER\\_IB\\_MSG\\_1034](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012860](#); Symbol: [ER\\_IB\\_MSG\\_1035](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012861](#); Symbol: [ER\\_IB\\_MSG\\_1036](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012862](#); Symbol: [ER\\_IB\\_MSG\\_1037](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012863](#); Symbol: [ER\\_IB\\_MSG\\_1038](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012864](#); Symbol: [ER\\_IB\\_MSG\\_1039](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012865](#); Symbol: [ER\\_IB\\_MSG\\_1040](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012866](#); Symbol: [ER\\_IB\\_MSG\\_1041](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012867](#); Symbol: [ER\\_IB\\_MSG\\_1042](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012868](#); Symbol: [ER\\_IB\\_MSG\\_1043](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012869](#); Symbol: [ER\\_IB\\_MSG\\_1044](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012870](#); Symbol: [ER\\_IB\\_MSG\\_1045](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012871](#); Symbol: [ER\\_IB\\_MSG\\_1046](#); SQLSTATE: [HY000](#)

---

Message: Old log sequence number %llu was greater than the new log sequence number %llu.  
Please submit a bug report to <http://bugs.mysql.com>

- Error number: [MY-012872](#); Symbol: [ER\\_IB\\_MSG\\_1047](#); SQLSTATE: [HY000](#)

Message: Semaphore wait has lasted > %llu seconds. We intentionally crash the server because it appears to be hung.

- Error number: [MY-012873](#); Symbol: [ER\\_IB\\_MSG\\_1048](#); SQLSTATE: [HY000](#)

Message: Waiting for %llu table(s) to be dropped

- Error number: [MY-012874](#); Symbol: [ER\\_IB\\_MSG\\_1049](#); SQLSTATE: [HY000](#)

Message: Waiting for change buffer merge to complete number of bytes of change buffer just merged: %llu

- Error number: [MY-012876](#); Symbol: [ER\\_IB\\_MSG\\_1051](#); SQLSTATE: [HY000](#)

Message: Can't set undo tablespace(s) to be encrypted in read-only-mode.

- Error number: [MY-012877](#); Symbol: [ER\\_IB\\_MSG\\_1052](#); SQLSTATE: [HY000](#)

Message: Can't set undo tablespace '%s' to be encrypted.

- Error number: [MY-012878](#); Symbol: [ER\\_IB\\_MSG\\_1053](#); SQLSTATE: [HY000](#)

Message: Can't set undo tablespace '%s' to be encrypted. Failed to write header page.

- Error number: [MY-012879](#); Symbol: [ER\\_IB\\_MSG\\_1054](#); SQLSTATE: [HY000](#)

Message: Can't set undo tablespace '%s' to be encrypted. Error %d - %s

- Error number: [MY-012880](#); Symbol: [ER\\_IB\\_MSG\\_1055](#); SQLSTATE: [HY000](#)

Message: Encryption is enabled for undo tablespace '%s'.

- Error number: [MY-012881](#); Symbol: [ER\\_IB\\_MSG\\_1056](#); SQLSTATE: [HY000](#)

Message: Can't rotate encryption on undo tablespace '%s'.

- Error number: [MY-012882](#); Symbol: [ER\\_IB\\_MSG\\_1057](#); SQLSTATE: [HY000](#)

Message: Encryption is enabled for undo tablespace '%s'.

- Error number: [MY-012883](#); Symbol: [ER\\_IB\\_MSG\\_1058](#); SQLSTATE: [HY000](#)

Message: `os_file_get_status()` failed on '%s'. Can't determine file permissions.

- Error number: [MY-012884](#); Symbol: [ER\\_IB\\_MSG\\_1059](#); SQLSTATE: [HY000](#)

Message: %s can't be opened in %s mode.

- Error number: [MY-012885](#); Symbol: [ER\\_IB\\_MSG\\_1060](#); SQLSTATE: [HY000](#)

Message: '%s' not a regular file.

- Error number: [MY-012886](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_OS\\_CREATE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Cannot create %s

- Error number: [MY-012887](#); Symbol: [ER\\_IB\\_MSG\\_FILE\\_RESIZE](#); SQLSTATE: [HY000](#)

---

Message: Setting file %s size to %llu MB. Progress : %u%%

- Error number: MY-012888; Symbol: ER\_IB\_MSG\_LOG\_FILE\_RESIZE\_FAILED; SQLSTATE: HY000

Message: Cannot resize redo log file %s to %llu MB (%s)

- Error number: MY-012889; Symbol: ER\_IB\_MSG\_LOG\_FILES\_CREATE\_AND\_READ\_ONLY\_MODE; SQLSTATE: HY000

Message: Cannot create redo log files in read-only mode (--innodb-read-only).

- Error number: MY-012890; Symbol: ER\_IB\_MSG\_1065; SQLSTATE: HY000

Message: Redo log encryption is enabled, but the keyring is not loaded.

- Error number: MY-012891; Symbol: ER\_IB\_MSG\_LOG\_FILE\_PREPARE\_ON\_CREATE\_FAILED; SQLSTATE: HY000

Message: Failed to create redo log file %s (error: %d) for start LSN %llu

- Error number: MY-012893; Symbol: ER\_IB\_MSG\_LOG\_FILES\_INITIALIZED; SQLSTATE: HY000

Message: New redo log files created, LSN=%llu

- Error number: MY-012894; Symbol: ER\_IB\_MSG\_LOG\_FILE\_OPEN\_FAILED; SQLSTATE: HY000

Message: Unable to open '%s' (error: %d).

- Error number: MY-012895; Symbol: ER\_IB\_MSG\_1070; SQLSTATE: HY000

Message: Cannot create construction log file '%s' for undo tablespace '%s'.

- Error number: MY-012896; Symbol: ER\_IB\_MSG\_1071; SQLSTATE: HY000

Message: Creating UNDO Tablespace %s

- Error number: MY-012897; Symbol: ER\_IB\_MSG\_1072; SQLSTATE: HY000

Message: Setting file %s size to %llu MB

- Error number: MY-012898; Symbol: ER\_IB\_MSG\_1073; SQLSTATE: HY000

Message: Physically writing the file full

- Error number: MY-012899; Symbol: ER\_IB\_MSG\_1074; SQLSTATE: HY000

Message: Error in creating %s: probably out of disk space

- Error number: MY-012900; Symbol: ER\_IB\_MSG\_1075; SQLSTATE: HY000

Message: Can't set encryption metadata for space %s

- Error number: MY-012901; Symbol: ER\_IB\_MSG\_1076; SQLSTATE: HY000

Message: Cannot read first page of '%s' - %s

- Error number: MY-012902; Symbol: ER\_IB\_MSG\_1077; SQLSTATE: HY000

Message: Undo tablespace number %lu was being truncated when mysqld quit.

- Error number: MY-012903; Symbol: ER\_IB\_MSG\_1078; SQLSTATE: HY000

Message: Cannot recover a truncated undo tablespace in read-only mode

- 
- Error number: [MY-012904](#); Symbol: [ER\\_IB\\_MSG\\_1079](#); SQLSTATE: [HY000](#)  
Message: Reconstructing undo tablespace number %lu.
  - Error number: [MY-012905](#); Symbol: [ER\\_IB\\_MSG\\_1080](#); SQLSTATE: [HY000](#)  
Message: Cannot create %s because %s already uses Space ID=%lu! Did you change innodb\_undo\_directory?
  - Error number: [MY-012906](#); Symbol: [ER\\_IB\\_MSG\\_1081](#); SQLSTATE: [HY000](#)  
Message: UNDO tablespace %s must be %s
  - Error number: [MY-012907](#); Symbol: [ER\\_IB\\_MSG\\_1082](#); SQLSTATE: [HY000](#)  
Message: Error creating file for %s
  - Error number: [MY-012908](#); Symbol: [ER\\_IB\\_MSG\\_1083](#); SQLSTATE: [HY000](#)  
Message: Error reading encryption for %s
  - Error number: [MY-012909](#); Symbol: [ER\\_IB\\_MSG\\_CANNOT\\_OPEN\\_57\\_UNDO](#); SQLSTATE: [HY000](#)  
Message: Unable to open undo tablespace number %lu
  - Error number: [MY-012910](#); Symbol: [ER\\_IB\\_MSG\\_1085](#); SQLSTATE: [HY000](#)  
Message: Opened %llu existing undo tablespaces.
  - Error number: [MY-012911](#); Symbol: [ER\\_IB\\_MSG\\_1086](#); SQLSTATE: [HY000](#)  
Message: Cannot create undo tablespaces since innodb\_%s has been set. Using %llu existing undo tablespaces.
  - Error number: [MY-012912](#); Symbol: [ER\\_IB\\_MSG\\_1087](#); SQLSTATE: [HY000](#)  
Message: Cannot continue InnoDB startup in %s mode because there are no existing undo tablespaces found.
  - Error number: [MY-012913](#); Symbol: [ER\\_IB\\_MSG\\_1088](#); SQLSTATE: [HY000](#)  
Message: Could not create undo tablespace '%s'.
  - Error number: [MY-012914](#); Symbol: [ER\\_IB\\_MSG\\_1089](#); SQLSTATE: [HY000](#)  
Message: Error %d - %s - opening newly created undo tablespace '%s'.
  - Error number: [MY-012915](#); Symbol: [ER\\_IB\\_MSG\\_1090](#); SQLSTATE: [HY000](#)  
Message: Created %llu undo tablespaces.
  - Error number: [MY-012916](#); Symbol: [ER\\_IB\\_MSG\\_1091](#); SQLSTATE: [HY000](#)  
Message: Unable to create encrypted undo tablespace number %lu. please check if the keyring is initialized correctly
  - Error number: [MY-012917](#); Symbol: [ER\\_IB\\_MSG\\_1092](#); SQLSTATE: [HY000](#)  
Message: Encryption is enabled for undo tablespace number %lu.
  - Error number: [MY-012918](#); Symbol: [ER\\_IB\\_MSG\\_1093](#); SQLSTATE: [HY000](#)  
Message: Unable to initialize the header page in undo tablespace number %lu.

- 
- Error number: [MY-012919](#); Symbol: [ER\\_IB\\_MSG\\_1094](#); SQLSTATE: [HY000](#)  
Message: Cannot delete old undo tablespaces because they contain undo logs for XA PREPARED transactions.
  - Error number: [MY-012920](#); Symbol: [ER\\_IB\\_MSG\\_1095](#); SQLSTATE: [HY000](#)  
Message: Upgrading %zu existing undo tablespaces that were tracked in the system tablespace to %lu new independent undo tablespaces.
  - Error number: [MY-012921](#); Symbol: [ER\\_IB\\_MSG\\_1096](#); SQLSTATE: [HY000](#)  
Message: Deleting %llu new independent undo tablespaces that we just created.
  - Error number: [MY-012922](#); Symbol: [ER\\_IB\\_MSG\\_1097](#); SQLSTATE: [HY000](#)  
Message: Waiting for purge to start
  - Error number: [MY-012923](#); Symbol: [ER\\_IB\\_MSG\\_1098](#); SQLSTATE: [HY000](#)  
Message: Creating shared tablespace for temporary tables
  - Error number: [MY-012924](#); Symbol: [ER\\_IB\\_MSG\\_1099](#); SQLSTATE: [HY000](#)  
Message: The %s data file must be writable!
  - Error number: [MY-012925](#); Symbol: [ER\\_IB\\_MSG\\_1100](#); SQLSTATE: [HY000](#)  
Message: Could not create the shared %s.
  - Error number: [MY-012926](#); Symbol: [ER\\_IB\\_MSG\\_1101](#); SQLSTATE: [HY000](#)  
Message: Unable to create the shared %s.
  - Error number: [MY-012927](#); Symbol: [ER\\_IB\\_MSG\\_1102](#); SQLSTATE: [HY000](#)  
Message: The %s data file cannot be re-opened after check\_file\_spec() succeeded!
  - Error number: [MY-012928](#); Symbol: [ER\\_IB\\_MSG\\_1103](#); SQLSTATE: [HY000](#)  
Message: %d threads created by InnoDB had not exited at shutdown!
  - Error number: [MY-012929](#); Symbol: [ER\\_IB\\_MSG\\_1104](#); SQLSTATE: [HY000](#)  
Message: InnoDB Database creation was aborted %swith error %s. You may need to delete the ibdata1 file before trying to start up again.
  - Error number: [MY-012930](#); Symbol: [ER\\_IB\\_MSG\\_1105](#); SQLSTATE: [HY000](#)  
Message: Plugin initialization aborted %swith error %s.
  - Error number: [MY-012931](#); Symbol: [ER\\_IB\\_MSG\\_BUF\\_PENDING\\_IO](#); SQLSTATE: [HY000](#)  
Message: Waiting for %zu buffer page I/Os to complete.
  - Error number: [MY-012932](#); Symbol: [ER\\_IB\\_MSG\\_1107](#); SQLSTATE: [HY000](#)  
Message: PUNCH HOLE support available
  - Error number: [MY-012933](#); Symbol: [ER\\_IB\\_MSG\\_1108](#); SQLSTATE: [HY000](#)  
Message: PUNCH HOLE support not available
  - Error number: [MY-012934](#); Symbol: [ER\\_IB\\_MSG\\_1109](#); SQLSTATE: [HY000](#)

---

Message: Size of InnoDB's ulint is %zu but size of void\* is %zu. The sizes should be the same so that on a 64-bit platforms you can allocate more than 4 GB of memory.

- Error number: [MY-012935](#); Symbol: [ER\\_IB\\_MSG\\_1110](#); SQLSTATE: [HY000](#)

Message: Database upgrade cannot be accomplished in read-only mode.

- Error number: [MY-012936](#); Symbol: [ER\\_IB\\_MSG\\_1111](#); SQLSTATE: [HY000](#)

Message: Database upgrade cannot be accomplished with innodb\_force\_recovery > 0

- Error number: [MY-012937](#); Symbol: [ER\\_IB\\_MSG\\_1112](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012938](#); Symbol: [ER\\_IB\\_MSG\\_1113](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012939](#); Symbol: [ER\\_IB\\_MSG\\_1114](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012940](#); Symbol: [ER\\_IB\\_MSG\\_1115](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012941](#); Symbol: [ER\\_IB\\_MSG\\_1116](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012942](#); Symbol: [ER\\_IB\\_MSG\\_1117](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012944](#); Symbol: [ER\\_IB\\_MSG\\_1119](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012945](#); Symbol: [ER\\_IB\\_MSG\\_1120](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012946](#); Symbol: [ER\\_IB\\_MSG\\_1121](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012947](#); Symbol: [ER\\_IB\\_MSG\\_1122](#); SQLSTATE: [HY000](#)

Message: MySQL was built without a memory barrier capability on this architecture, which might allow a mutex/rw\_lock violation under high thread concurrency. This may cause a hang.

- Error number: [MY-012948](#); Symbol: [ER\\_IB\\_MSG\\_1123](#); SQLSTATE: [HY000](#)

Message: Compressed tables use zlib %s

- Error number: [MY-012949](#); Symbol: [ER\\_IB\\_MSG\\_1124](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012950](#); Symbol: [ER\\_IB\\_MSG\\_1125](#); SQLSTATE: [HY000](#)

Message: Startup called second time during the process lifetime. In the MySQL Embedded Server Library you cannot call server\_init() more than once during the process lifetime.

- 
- Error number: [MY-012951](#); Symbol: [ER\\_IB\\_MSG\\_1126](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012952](#); Symbol: [ER\\_IB\\_MSG\\_1127](#); SQLSTATE: [HY000](#)  
Message: Unable to create monitor file %s: %s
  - Error number: [MY-012953](#); Symbol: [ER\\_IB\\_MSG\\_1128](#); SQLSTATE: [HY000](#)  
Message: Disabling background ibuf IO read threads.
  - Error number: [MY-012954](#); Symbol: [ER\\_IB\\_MSG\\_1129](#); SQLSTATE: [HY000](#)  
Message: Cannot initialize AIO sub-system
  - Error number: [MY-012955](#); Symbol: [ER\\_IB\\_MSG\\_1130](#); SQLSTATE: [HY000](#)  
Message: Initializing buffer pool, total size = %lf%c, instances = %lu, chunk size =%lf%c
  - Error number: [MY-012956](#); Symbol: [ER\\_IB\\_MSG\\_1131](#); SQLSTATE: [HY000](#)  
Message: Cannot allocate memory for the buffer pool
  - Error number: [MY-012957](#); Symbol: [ER\\_IB\\_MSG\\_1132](#); SQLSTATE: [HY000](#)  
Message: Completed initialization of buffer pool
  - Error number: [MY-012958](#); Symbol: [ER\\_IB\\_MSG\\_1133](#); SQLSTATE: [HY000](#)  
Message: Small buffer pool size (%lluM), the flst\_validate() debug function can cause a deadlock if the buffer pool fills up.
  - Error number: [MY-012959](#); Symbol: [ER\\_IB\\_MSG\\_1134](#); SQLSTATE: [HY000](#)  
Message: Could not open or create the system tablespace. If you tried to add new data files to the system tablespace, and it failed here, you should now edit innodb\_data\_file\_path in my.cnf back to what it was, and remove the new ibdata files InnoDB created in this failed attempt. InnoDB only wrote those files full of zeros, but did not yet use them in any way. But be careful: do not remove old data files which contain your precious data!
  - Error number: [MY-012960](#); Symbol: [ER\\_IB\\_MSG\\_DATA\\_DIRECTORY\\_NOT\\_INITIALIZED\\_OR\\_CORRUPTED](#); SQLSTATE: [HY000](#)  
Message: Cannot create redo log files because data files are corrupt or the database was not shut down cleanly after creating the data files.
  - Error number: [MY-012961](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILES\\_INVALID\\_SET](#); SQLSTATE: [HY000](#)  
Message: Only one redo log file found
  - Error number: [MY-012962](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_SIZE\\_INVALID](#); SQLSTATE: [HY000](#)  
Message: The redo log file %s size %llu is not a multiple of innodb\_page\_size
  - Error number: [MY-012963](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILES\\_DIFFERENT\\_SIZES](#); SQLSTATE: [HY000](#)  
Message: The redo log file %s is of different size %llu bytes than other log files %llu bytes!
  - Error number: [MY-012964](#); Symbol: [ER\\_IB\\_MSG\\_1139](#); SQLSTATE: [HY000](#)  
Message: Use --innodb-directories to find the tablespace files. If that fails then use --innodb-force-recovery=1 to ignore this and to permanently lose all changes to the missing tablespace(s)



- 
- Error number: [MY-012965](#); Symbol: [ER\\_IB\\_MSG\\_RECOVERY\\_CORRUPT](#); SQLSTATE: [HY000](#)  
Message: The redo log file may have been corrupt and it is possible that the log scan or parsing did not proceed far enough in recovery. Please run CHECK TABLE on your InnoDB tables to check that they are ok! It may be safest to recover your InnoDB database from a backup!
  - Error number: [MY-012967](#); Symbol: [ER\\_IB\\_MSG\\_1142](#); SQLSTATE: [HY000](#)  
Message: Cannot open DD tablespace.
  - Error number: [MY-012968](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILES\\_REWRITING](#); SQLSTATE: [HY000](#)  
Message: Starting to delete and rewrite redo log files.
  - Error number: [MY-012969](#); Symbol: [ER\\_IB\\_MSG\\_1144](#); SQLSTATE: [HY000](#)  
Message: Undo from 5.7 found. It will be purged
  - Error number: [MY-012970](#); Symbol: [ER\\_IB\\_MSG\\_1145](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012971](#); Symbol: [ER\\_IB\\_MSG\\_1146](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012972](#); Symbol: [ER\\_IB\\_MSG\\_1147](#); SQLSTATE: [HY000](#)  
Message: Tablespace size stored in header is %lu pages, but the sum of data file sizes is %lu pages
  - Error number: [MY-012973](#); Symbol: [ER\\_IB\\_MSG\\_1148](#); SQLSTATE: [HY000](#)  
Message: Cannot start InnoDB. The tail of the system tablespace is missing. Have you edited innodb\_data\_file\_path in my.cnf in an inappropriate way, removing ibdata files from there? You can set innodb\_force\_recovery=1 in my.cnf to force a startup if you are trying to recover a badly corrupt database.
  - Error number: [MY-012974](#); Symbol: [ER\\_IB\\_MSG\\_1149](#); SQLSTATE: [HY000](#)  
Message: Tablespace size stored in header is %lu pages, but the sum of data file sizes is only %lu pages
  - Error number: [MY-012975](#); Symbol: [ER\\_IB\\_MSG\\_1150](#); SQLSTATE: [HY000](#)  
Message: Cannot start InnoDB. The tail of the system tablespace is missing. Have you edited innodb\_data\_file\_path in my.cnf in an InnoDB: inappropriate way, removing ibdata files from there? You can set innodb\_force\_recovery=1 in my.cnf to force InnoDB: a startup if you are trying to recover a badly corrupt database.
  - Error number: [MY-012976](#); Symbol: [ER\\_IB\\_MSG\\_1151](#); SQLSTATE: [HY000](#)  
Message: %s started; log sequence number %llu
  - Error number: [MY-012977](#); Symbol: [ER\\_IB\\_MSG\\_1152](#); SQLSTATE: [HY000](#)  
Message: Waiting for purge to complete
  - Error number: [MY-012979](#); Symbol: [ER\\_IB\\_MSG\\_1154](#); SQLSTATE: [HY000](#)  
Message: Query counter shows %lld queries still inside InnoDB at shutdown
  - Error number: [MY-012980](#); Symbol: [ER\\_IB\\_MSG\\_1155](#); SQLSTATE: [HY000](#)  
Message: Shutdown completed; log sequence number %llu
-

- 
- Error number: [MY-012981](#); Symbol: [ER\\_IB\\_MSG\\_1156](#); SQLSTATE: [HY000](#)  
Message: Cannot continue operation.
  - Error number: [MY-012982](#); Symbol: [ER\\_IB\\_MSG\\_1157](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012983](#); Symbol: [ER\\_IB\\_MSG\\_1158](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012984](#); Symbol: [ER\\_IB\\_MSG\\_1159](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012985](#); Symbol: [ER\\_IB\\_MSG\\_1160](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012986](#); Symbol: [ER\\_IB\\_MSG\\_1161](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012987](#); Symbol: [ER\\_IB\\_MSG\\_1162](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012988](#); Symbol: [ER\\_IB\\_MSG\\_1163](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012989](#); Symbol: [ER\\_IB\\_MSG\\_1164](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012990](#); Symbol: [ER\\_IB\\_MSG\\_1165](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-012991](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_FAIL\\_TO\\_READ\\_LOG\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Unable to read the existing undo truncate log file '%s'. The error is %s
  - Error number: [MY-012992](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_MARKED\\_FOR\\_TRUNCATE](#); SQLSTATE: [HY000](#)  
Message: Undo tablespace %s is marked for truncate
  - Error number: [MY-012994](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_START](#); SQLSTATE: [HY000](#)  
Message: Truncating UNDO tablespace %s
  - Error number: [MY-012996](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_DELAY\\_BY\\_LOG\\_CREATE](#); SQLSTATE: [HY000](#)  
Message: Cannot create truncate log for undo tablespace '%s'.
  - Error number: [MY-012998](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_DELAY\\_BY\\_FAILURE](#); SQLSTATE: [HY000](#)  
Message: Failed to truncate undo tablespace '%s'.

- 
- Error number: [MY-013000](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_COMPLETE](#); SQLSTATE: [HY000](#)  
Message: Completed truncate of undo tablespace %s.
  - Error number: [MY-013002](#); Symbol: [ER\\_IB\\_MSG\\_1177](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013003](#); Symbol: [ER\\_IB\\_MSG\\_1178](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013004](#); Symbol: [ER\\_IB\\_MSG\\_1179](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013005](#); Symbol: [ER\\_IB\\_MSG\\_1180](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013006](#); Symbol: [ER\\_IB\\_MSG\\_1181](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013007](#); Symbol: [ER\\_IB\\_MSG\\_1182](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013008](#); Symbol: [ER\\_IB\\_MSG\\_1183](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013009](#); Symbol: [ER\\_IB\\_MSG\\_1184](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013010](#); Symbol: [ER\\_IB\\_MSG\\_1185](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013011](#); Symbol: [ER\\_IB\\_MSG\\_1186](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013012](#); Symbol: [ER\\_IB\\_MSG\\_1187](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013013](#); Symbol: [ER\\_IB\\_MSG\\_1188](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013014](#); Symbol: [ER\\_IB\\_MSG\\_1189](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013015](#); Symbol: [ER\\_IB\\_MSG\\_TRX\\_RECOVERY\\_ROLLBACK\\_COMPLETED](#); SQLSTATE: [HY000](#)  
Message: Rollback of non-prepared transactions completed
  - Error number: [MY-013016](#); Symbol: [ER\\_IB\\_MSG\\_1191](#); SQLSTATE: [HY000](#)  
Message: %s

- 
- Error number: [MY-013017](#); Symbol: [ER\\_IB\\_MSG\\_1192](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013018](#); Symbol: [ER\\_IB\\_MSG\\_1193](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013019](#); Symbol: [ER\\_IB\\_MSG\\_1194](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013020](#); Symbol: [ER\\_IB\\_MSG\\_1195](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013021](#); Symbol: [ER\\_IB\\_MSG\\_1196](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013022](#); Symbol: [ER\\_IB\\_MSG\\_1197](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013023](#); Symbol: [ER\\_IB\\_MSG\\_1198](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013024](#); Symbol: [ER\\_IB\\_MSG\\_1199](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013025](#); Symbol: [ER\\_IB\\_MSG\\_1200](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013026](#); Symbol: [ER\\_IB\\_MSG\\_1201](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013027](#); Symbol: [ER\\_IB\\_MSG\\_1202](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013028](#); Symbol: [ER\\_IB\\_MSG\\_1203](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013029](#); Symbol: [ER\\_IB\\_MSG\\_1204](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013030](#); Symbol: [ER\\_IB\\_MSG\\_1205](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013031](#); Symbol: [ER\\_IB\\_MSG\\_1206](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013032](#); Symbol: [ER\\_IB\\_MSG\\_1207](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013033](#); Symbol: [ER\\_IB\\_MSG\\_1208](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-013034](#); Symbol: [ER\\_IB\\_MSG\\_1209](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013035](#); Symbol: [ER\\_IB\\_MSG\\_1210](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013036](#); Symbol: [ER\\_IB\\_MSG\\_1211](#); SQLSTATE: [HY000](#)

Message: Blocked High Priority Transaction (ID %llu, Thread ID %s) killed the blocking transaction (ID %llu - %s) by rolling it back.

- Error number: [MY-013037](#); Symbol: [ER\\_IB\\_MSG\\_1212](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013038](#); Symbol: [ER\\_IB\\_MSG\\_1213](#); SQLSTATE: [HY000](#)

Message: gettimeofday() failed: %s

- Error number: [MY-013039](#); Symbol: [ER\\_IB\\_MSG\\_1214](#); SQLSTATE: [HY000](#)

Message: Can't create UNDO tablespace %s %s

- Error number: [MY-013040](#); Symbol: [ER\\_IB\\_MSG\\_1215](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013041](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILES\\_RESIZE\\_ON\\_START](#); SQLSTATE: [HY000](#)

Message: Resizing redo log from %lluM to %lluM (LSN=%llu) synchronously. If this takes too long, consider starting the server with large `--innodb_redo_log_capacity`, and resizing the redo log online using SET.

- Error number: [MY-013042](#); Symbol: [ER\\_IB\\_MSG\\_1217](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013043](#); Symbol: [ER\\_IB\\_MSG\\_1218](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013044](#); Symbol: [ER\\_IB\\_MSG\\_1219](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013045](#); Symbol: [ER\\_IB\\_MSG\\_1220](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013046](#); Symbol: [ER\\_IB\\_MSG\\_1221](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013047](#); Symbol: [ER\\_IB\\_MSG\\_1222](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013048](#); Symbol: [ER\\_IB\\_MSG\\_1223](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: [MY-013049](#); Symbol: [ER\\_IB\\_MSG\\_1224](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013050](#); Symbol: [ER\\_IB\\_MSG\\_1225](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013051](#); Symbol: [ER\\_IB\\_MSG\\_1226](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013052](#); Symbol: [ER\\_IB\\_MSG\\_1227](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013053](#); Symbol: [ER\\_IB\\_MSG\\_1228](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013054](#); Symbol: [ER\\_IB\\_MSG\\_1229](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013056](#); Symbol: [ER\\_IB\\_MSG\\_1231](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013058](#); Symbol: [ER\\_IB\\_MSG\\_1233](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013059](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_WRITER\\_OUT\\_OF\\_SPACE](#); SQLSTATE: [HY000](#)

Message: Out of space in the redo log. Checkpoint LSN: %llu. Consider increasing innodb\_redo\_log\_capacity.

- Error number: [MY-013060](#); Symbol: [ER\\_IB\\_MSG\\_1235](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013061](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_WRITER\\_ABORTS\\_LOG\\_ARCHIVER](#); SQLSTATE: [HY000](#)

Message: Log writer waited too long for redo-archiver to advance (1 second). There are unarchived: %llu bytes. Archiver LSN: %llu. Aborted the redo-archiver. Consider increasing innodb\_redo\_log\_capacity.

- Error number: [MY-013062](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_WRITER\\_WAITING\\_FOR\\_ARCHIVER](#); SQLSTATE: [HY000](#)

Message: Log writer is waiting for redo-archiver to catch up unarchived: %llu bytes. Archiver LSN: %llu. Consider increasing innodb\_redo\_log\_capacity.

- Error number: [MY-013063](#); Symbol: [ER\\_IB\\_MSG\\_1238](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013064](#); Symbol: [ER\\_IB\\_MSG\\_1239](#); SQLSTATE: [HY000](#)

Message: %s

- 
- Error number: [MY-013066](#); Symbol: [ER\\_IB\\_MSG\\_1241](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013067](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILES\\_CANNOT\\_ENCRYPT\\_IN\\_READ\\_ONLY](#); SQLSTATE: [HY000](#)  
Message: Can't set redo log files to be encrypted in read-only mode.
  - Error number: [MY-013068](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILES\\_ENCRYPTION\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Can't set redo log files to be encrypted.
  - Error number: [MY-013070](#); Symbol: [ER\\_IB\\_MSG\\_1245](#); SQLSTATE: [HY000](#)  
Message: Redo log encryption is enabled.
  - Error number: [MY-013071](#); Symbol: [ER\\_IB\\_MSG\\_1246](#); SQLSTATE: [HY000](#)  
Message: Waiting for archiver to finish archiving page and log
  - Error number: [MY-013072](#); Symbol: [ER\\_IB\\_MSG\\_1247](#); SQLSTATE: [HY000](#)  
Message: Starting shutdown...
  - Error number: [MY-013073](#); Symbol: [ER\\_IB\\_MSG\\_1248](#); SQLSTATE: [HY000](#)  
Message: Waiting for %s to exit.
  - Error number: [MY-013074](#); Symbol: [ER\\_IB\\_MSG\\_1249](#); SQLSTATE: [HY000](#)  
Message: Waiting for rollback of %zu recovered transactions, before shutdown.
  - Error number: [MY-013075](#); Symbol: [ER\\_IB\\_MSG\\_1250](#); SQLSTATE: [HY000](#)  
Message: Waiting for master thread to be suspended.
  - Error number: [MY-013076](#); Symbol: [ER\\_IB\\_MSG\\_1251](#); SQLSTATE: [HY000](#)  
Message: Waiting for page\_cleaner to finish flushing of buffer pool.
  - Error number: [MY-013077](#); Symbol: [ER\\_IB\\_MSG\\_BUF\\_PENDING\\_IO\\_ON\\_SHUTDOWN](#); SQLSTATE: [HY000](#)  
Message: Shutdown is waiting for %zu buffer page I/Os to complete.
  - Error number: [MY-013078](#); Symbol: [ER\\_IB\\_MSG\\_1253](#); SQLSTATE: [HY000](#)  
Message: MySQL has requested a very fast shutdown without flushing the InnoDB buffer pool to data files. At the next mysqld startup InnoDB will do a crash recovery!
  - Error number: [MY-013080](#); Symbol: [ER\\_IB\\_MSG\\_1255](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013081](#); Symbol: [ER\\_IB\\_MSG\\_1256](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013082](#); Symbol: [ER\\_IB\\_MSG\\_1257](#); SQLSTATE: [HY000](#)  
Message: %s
-

- 
- Error number: [MY-013083](#); Symbol: [ER\\_IB\\_MSG\\_1258](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013084](#); Symbol: [ER\\_IB\\_MSG\\_1259](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013085](#); Symbol: [ER\\_IB\\_MSG\\_1260](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013086](#); Symbol: [ER\\_IB\\_MSG\\_1261](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013087](#); Symbol: [ER\\_IB\\_MSG\\_1262](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013088](#); Symbol: [ER\\_IB\\_MSG\\_1263](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013089](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_HEADER\\_INVALID\\_CHECKSUM](#); SQLSTATE: [HY000](#)  
Message: Invalid redo log header checksum.
  - Error number: [MY-013090](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FORMAT\\_BEFORE\\_5\\_7\\_9](#); SQLSTATE: [HY000](#)  
Message: Unsupported redo log format (v%lu). The redo log was created before MySQL 5.7.9
  - Error number: [MY-013091](#); Symbol: [ER\\_IB\\_MSG\\_1266](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013092](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_PARAMS\\_CONCURRENCY\\_MARGIN\\_UNSAFE](#); SQLSTATE: [HY000](#)  
Message: Cannot continue operation. The innodb\_redo\_log\_capacity=%lluM is too small for the innodb\_thread\_concurrency=%lu. The capacity of redo should be >= %lluM. To get mysqld running, set innodb\_thread\_concurrency to a smaller value or increase innodb\_redo\_log\_capacity. %s
  - Error number: [MY-013093](#); Symbol: [ER\\_IB\\_MSG\\_1268](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013094](#); Symbol: [ER\\_IB\\_MSG\\_1269](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013095](#); Symbol: [ER\\_IB\\_MSG\\_THREAD\\_CONCURRENCY\\_CHANGED](#); SQLSTATE: [HY000](#)  
Message: User has set innodb\_thread\_concurrency to %lu.
  - Error number: [MY-013096](#); Symbol: [ER\\_RPL\\_REPLICA\\_SQL\\_THREAD\\_STOP\\_CMD\\_EXEC\\_TIMEOUT](#); SQLSTATE: [HY000](#)  
Message: STOP REPLICA command execution is incomplete: Replica SQL thread got the stop signal, thread is busy, SQL thread will stop once the current task is complete.



- 
- Error number: [MY-013097](#); Symbol: [ER\\_RPL\\_REPLICA\\_IO\\_THREAD\\_STOP\\_CMD\\_EXEC\\_TIMEOUT](#); SQLSTATE: [HY000](#)  
  
Message: STOP REPLICA command execution is incomplete: Replica IO thread got the stop signal, thread is busy, IO thread will stop once the current task is complete.
  - Error number: [MY-013098](#); Symbol: [ER\\_RPL\\_GTID\\_UNSAFE\\_STMT\\_ON\\_NON\\_TRANS\\_TABLE](#); SQLSTATE: [HY000](#)  
  
Message: Statement violates GTID consistency: Updates to non-transactional tables can only be done in either autocommitted statements or single-statement transactions, and never in the same statement as updates to transactional tables.
  - Error number: [MY-013099](#); Symbol: [ER\\_RPL\\_GTID\\_UNSAFE\\_STMT\\_CREATE\\_SELECT](#); SQLSTATE: [HY000](#)  
  
Message: Statement violates GTID consistency: CREATE TABLE ... SELECT.
  - Error number: [MY-013101](#); Symbol: [ER\\_BINLOG\\_ROW\\_VALUE\\_OPTION\\_IGNORED](#); SQLSTATE: [HY000](#)  
  
Message: When %s, the option binlog\_row\_value\_options=%s will be ignored and updates will be written in full format to binary log.
  - Error number: [MY-013103](#); Symbol: [ER\\_BINLOG\\_ROW\\_VALUE\\_OPTION\\_USED\\_ONLY\\_FOR\\_AFTER\\_IMAGES](#); SQLSTATE: [HY000](#)  
  
Message: When %s, the option binlog\_row\_value\_options=%s will be used only for the after-image. Full values will be written in the before-image, so the saving in disk space due to binlog\_row\_value\_options is limited to less than 50%%.
  - Error number: [MY-013104](#); Symbol: [ER\\_CONNECTION\\_ABORTED](#); SQLSTATE: [HY000](#)  
  
Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s).
  - Error number: [MY-013105](#); Symbol: [ER\\_NORMAL\\_SERVER\\_SHUTDOWN](#); SQLSTATE: [HY000](#)  
  
Message: %s: Normal shutdown.
  - Error number: [MY-013106](#); Symbol: [ER\\_KEYRING\\_MIGRATE\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Can not perform keyring migration : %s.
  - Error number: [MY-013107](#); Symbol: [ER\\_GRP\\_RPL\\_LOWER\\_CASE\\_TABLE\\_NAMES\\_DIFF\\_FROM\\_GRP](#); SQLSTATE: [HY000](#)  
  
Message: The member is configured with a lower\_case\_table\_names option value '%u' different from the group '%u'. The member will now exit the group. If there is existing data on member, it may be incompatible with group if it was created with a lower\_case\_table\_names value different from the group.
  - Error number: [MY-013108](#); Symbol: [ER\\_OOM\\_SAVE\\_GTIDS](#); SQLSTATE: [HY000](#)  
  
Message: An out-of-memory error occurred while saving the set of GTIDs from the last binary log into the mysql.gtid\_executed table
  - Error number: [MY-013109](#); Symbol: [ER\\_LCTN\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)  
  
Message: The lower\_case\_table\_names setting for the data dictionary was not found. Starting the server using lower\_case\_table\_names = '%u'.
  - Error number: [MY-013111](#); Symbol: [ER\\_COMPONENT\\_FILTER\\_WRONG\\_VALUE](#); SQLSTATE: [HY000](#)
-

---

Message: Variable '%s' can't be set to the value of '%s'

- Error number: [MY-013112](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_STOP\\_SERVICES](#); SQLSTATE: [HY000](#)

Message: Stopping services failed with error "%s"

- Error number: [MY-013113](#); Symbol: [ER\\_INCONSISTENT\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Query caused different errors on source and replica. Error on source: message (format)='%s' error code=%d; Error on replica:actual message='%s', error code=%d. Default database:'%s'. Query:'%s'

- Error number: [MY-013114](#); Symbol: [ER\\_SERVER\\_SOURCE\\_FATAL\\_ERROR\\_READING\\_BINLOG](#); SQLSTATE: [HY000](#)

Message: Got fatal error %d from source when reading data from binary log: '%s'

- Error number: [MY-013115](#); Symbol: [ER\\_NETWORK\\_READ\\_EVENT\\_CHECKSUM\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Replication event checksum verification failed while reading from network.

- Error number: [MY-013116](#); Symbol: [ER\\_REPLICA\\_CREATE\\_EVENT\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Failed to create %s

- Error number: [MY-013117](#); Symbol: [ER\\_REPLICA\\_FATAL\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Fatal error: %s

- Error number: [MY-013118](#); Symbol: [ER\\_REPLICA\\_HEARTBEAT\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Unexpected source's heartbeat data: %s

- Error number: [MY-013119](#); Symbol: [ER\\_REPLICA\\_INCIDENT](#); SQLSTATE: [HY000](#)

Message: The incident %s occurred on the source. Message: %s

- Error number: [MY-013120](#); Symbol: [ER\\_REPLICA\\_SOURCE\\_COM\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Source command %s failed: %s

- Error number: [MY-013121](#); Symbol: [ER\\_REPLICA\\_RELAY\\_LOG\\_READ\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Relay log read failure: %s

- Error number: [MY-013122](#); Symbol: [ER\\_REPLICA\\_RELAY\\_LOG\\_WRITE\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Relay log write failure: %s

- Error number: [MY-013123](#); Symbol: [ER\\_SERVER\\_REPLICA\\_CM\\_INIT\\_REPOSITORY](#); SQLSTATE: [HY000](#)

Message: Replica failed to initialize connection metadata structure from the repository

- Error number: [MY-013124](#); Symbol: [ER\\_SERVER\\_REPLICA\\_AM\\_INIT\\_REPOSITORY](#); SQLSTATE: [HY000](#)

Message: Replica failed to initialize applier metadata structure from the repository

- 
- Error number: [MY-013125](#); Symbol: [ER\\_SERVER\\_NET\\_PACKET\\_TOO\\_LARGE](#); SQLSTATE: [HY000](#)  
Message: Got a packet bigger than 'max\_allowed\_packet' bytes
  - Error number: [MY-013126](#); Symbol: [ER\\_SERVER\\_NO\\_SYSTEM\\_TABLE\\_ACCESS](#); SQLSTATE: [HY000](#)  
Message: Access to %s '%s.%s' is rejected.
  - Error number: [MY-013128](#); Symbol: [ER\\_SERVER\\_UNKNOWN\\_SYSTEM\\_VARIABLE](#); SQLSTATE: [HY000](#)  
Message: Unknown system variable '%s'
  - Error number: [MY-013129](#); Symbol: [ER\\_SERVER\\_NO\\_SESSION\\_TO\\_SEND\\_TO](#); SQLSTATE: [HY000](#)  
Message: A message intended for a client cannot be sent there as no client-session is attached. Therefore, we're sending the information to the error-log instead: MY-%06d - %s
  - Error number: [MY-013130](#); Symbol: [ER\\_SERVER\\_NEW\\_ABORTING\\_CONNECTION](#); SQLSTATE: [08S01](#)  
Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s; diagnostics area: MY-%06d - %s)
  - Error number: [MY-013131](#); Symbol: [ER\\_SERVER\\_OUT\\_OF\\_SORTMEMORY](#); SQLSTATE: [HY000](#)  
Message: Out of sort memory, consider increasing server sort buffer size!
  - Error number: [MY-013132](#); Symbol: [ER\\_SERVER\\_RECORD\\_FILE\\_FULL](#); SQLSTATE: [HY000](#)  
Message: The table '%s' is full!
  - Error number: [MY-013133](#); Symbol: [ER\\_SERVER\\_DISK\\_FULL\\_NOWAIT](#); SQLSTATE: [HY000](#)  
Message: Create table/tablespace '%s' failed, as disk is full.
  - Error number: [MY-013134](#); Symbol: [ER\\_SERVER\\_HANDLER\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Handler reported error %d - %s
  - Error number: [MY-013135](#); Symbol: [ER\\_SERVER\\_NOT\\_FORM\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Incorrect information in file: '%s'
  - Error number: [MY-013136](#); Symbol: [ER\\_SERVER\\_CANT\\_OPEN\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Can't open file: '%s' (OS errno: %d - %s)
  - Error number: [MY-013137](#); Symbol: [ER\\_SERVER\\_FILE\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)  
Message: Can't find file: '%s' (OS errno: %d - %s)
  - Error number: [MY-013138](#); Symbol: [ER\\_SERVER\\_FILE\\_USED](#); SQLSTATE: [HY000](#)  
Message: '%s' is locked against change (OS errno: %d - %s)
  - Error number: [MY-013139](#); Symbol: [ER\\_SERVER\\_CANNOT\\_LOAD\\_FROM\\_TABLE\\_V2](#); SQLSTATE: [HY000](#)  
Message: Cannot load from %s.%s. The table is probably corrupted!
  - Error number: [MY-013140](#); Symbol: [ER\\_ERROR\\_INFO\\_FROM\\_DA](#); SQLSTATE: [HY000](#)  
Message: Error in diagnostics area: MY-%06d - %s

- 
- Error number: [MY-013141](#); Symbol: [ER\\_SERVER\\_TABLE\\_CHECK\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Incorrect definition of table %s.%s: expected column '%s' at position %d, found '%s'.
  - Error number: [MY-013142](#); Symbol: [ER\\_SERVER\\_COL\\_COUNT\\_DOESNT\\_MATCH\\_PLEASE\\_UPDATE\\_V2](#); SQLSTATE: [HY000](#)  
Message: The column count of %s.%s is wrong. Expected %d, found %d. Created with MySQL %d, now running %d. Please perform the MySQL upgrade procedure.
  - Error number: [MY-013143](#); Symbol: [ER\\_SERVER\\_COL\\_COUNT\\_DOESNT\\_MATCH\\_CORRUPTED\\_V2](#); SQLSTATE: [HY000](#)  
Message: Column count of %s.%s is wrong. Expected %d, found %d. The table is probably corrupted.
  - Error number: [MY-013144](#); Symbol: [ER\\_SERVER\\_ACL\\_TABLE\\_ERROR](#); SQLSTATE: [HY000](#)  
Message:
  - Error number: [MY-013145](#); Symbol: [ER\\_SERVER\\_REPLICA\\_INIT\\_QUERY\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Replica SQL thread aborted. Can't execute init\_replica query, MY-%06d - '%s'
  - Error number: [MY-013146](#); Symbol: [ER\\_SERVER\\_REPLICA\\_CONVERSION\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Column %d of table '%s.%s' cannot be converted from type '%s' to type '%s'
  - Error number: [MY-013147](#); Symbol: [ER\\_SERVER\\_REPLICA\\_IGNORED\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Replica SQL thread ignored the query because of replicate-\*table rules
  - Error number: [MY-013148](#); Symbol: [ER\\_CANT\\_REPLICATE\\_ANONYMOUS\\_WITH\\_AUTO\\_POSITION](#); SQLSTATE: [HY000](#)  
Message: Cannot replicate anonymous transaction when AUTO\_POSITION = 1, at file %s, position %lld.
  - Error number: [MY-013149](#); Symbol: [ER\\_CANT\\_REPLICATE\\_ANONYMOUS\\_WITH\\_GTID\\_MODE\\_ON](#); SQLSTATE: [HY000](#)  
Message: Cannot replicate anonymous transaction when @@GLOBAL.GTID\_MODE = ON, at file %s, position %lld.
  - Error number: [MY-013150](#); Symbol: [ER\\_CANT\\_REPLICATE\\_GTID\\_WITH\\_GTID\\_MODE\\_OFF](#); SQLSTATE: [HY000](#)  
Message: Cannot replicate GTID-transaction when @@GLOBAL.GTID\_MODE = OFF, at file %s, position %lld.
  - Error number: [MY-013151](#); Symbol: [ER\\_SERVER\\_TEST\\_MESSAGE](#); SQLSTATE: [HY000](#)  
Message: Simulated error
  - Error number: [MY-013152](#); Symbol: [ER\\_AUDIT\\_LOG\\_JSON\\_FILTER\\_PARSING\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013153](#); Symbol: [ER\\_AUDIT\\_LOG\\_JSON\\_FILTERING\\_NOT\\_ENABLED](#); SQLSTATE: [HY000](#)

---

Message: Audit Log filtering has not been installed.

- Error number: [MY-013154](#); Symbol: [ER\\_PLUGIN\\_FAILED\\_TO\\_OPEN\\_TABLES](#); SQLSTATE: [HY000](#)

Message: Failed to open the %s filter tables.

- Error number: [MY-013155](#); Symbol: [ER\\_PLUGIN\\_FAILED\\_TO\\_OPEN\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Failed to open '%s.%s' %s table.

- Error number: [MY-013156](#); Symbol: [ER\\_AUDIT\\_LOG\\_JSON\\_FILTER\\_NAME\\_CANNOT\\_BE\\_EMPTY](#); SQLSTATE: [HY000](#)

Message: Filter name cannot be empty.

- Error number: [MY-013157](#); Symbol: [ER\\_AUDIT\\_LOG\\_USER\\_NAME\\_INVALID\\_CHARACTER](#); SQLSTATE: [HY000](#)

Message: Invalid character in the user name.

- Error number: [MY-013158](#); Symbol: [ER\\_AUDIT\\_LOG\\_UDF\\_INSUFFICIENT\\_PRIVILEGE](#); SQLSTATE: [HY000](#)

Message: Request ignored for '%s'@'%s'. SUPER or AUDIT\_ADMIN needed to perform operation

- Error number: [MY-013159](#); Symbol: [ER\\_AUDIT\\_LOG\\_NO\\_KEYRING\\_PLUGIN\\_INSTALLED](#); SQLSTATE: [HY000](#)

Message: No keyring installed.

- Error number: [MY-013160](#); Symbol: [ER\\_AUDIT\\_LOG\\_HOST\\_NAME\\_INVALID\\_CHARACTER](#); SQLSTATE: [HY000](#)

Message: Invalid character in the host name.

- Error number: [MY-013161](#); Symbol: [ER\\_AUDIT\\_LOG\\_ENCRYPTION\\_PASSWORD\\_HAS\\_NOT\\_BEEN\\_SET](#); SQLSTATE: [HY000](#)

Message: Audit log encryption password has not been set; it will be generated automatically. Use `audit_log_encryption_password_get` to obtain the password or `audit_log_encryption_password_set` to set a new one.

- Error number: [MY-013162](#); Symbol: [ER\\_AUDIT\\_LOG\\_COULD\\_NOT\\_CREATE\\_AES\\_KEY](#); SQLSTATE: [HY000](#)

Message: Could not create AES key. OpenSSL's EVP\_BytesToKey function failed.

- Error number: [MY-013163](#); Symbol: [ER\\_AUDIT\\_LOG\\_ENCRYPTION\\_PASSWORD\\_CANNOT\\_BE\\_FETCHED](#); SQLSTATE: [HY000](#)

Message: Audit log encryption password cannot be fetched from the keyring. Password used so far is used for encryption.

- Error number: [MY-013164](#); Symbol: [ER\\_COULD\\_NOT\\_REINITIALIZE\\_AUDIT\\_LOG\\_FILTERS](#); SQLSTATE: [HY000](#)

Message: Could not reinitialize audit log filters.

- Error number: [MY-013165](#); Symbol: [ER\\_AUDIT\\_LOG\\_JSON\\_USER\\_NAME\\_CANNOT\\_BE\\_EMPTY](#); SQLSTATE: [HY000](#)

Message: User cannot be empty.

- 
- Error number: [MY-013166](#); Symbol: [ER\\_AUDIT\\_LOG\\_USER\\_FIRST\\_CHARACTER\\_MUST\\_BE\\_ALPHANUMERIC](#); SQLSTATE: [HY000](#)  
Message: First character of the user name must be alphanumeric.
  - Error number: [MY-013167](#); Symbol: [ER\\_AUDIT\\_LOG\\_JSON\\_FILTER\\_DOES\\_NOT\\_EXIST](#); SQLSTATE: [HY000](#)  
Message: Specified filter has not been found.
  - Error number: [MY-013168](#); Symbol: [ER\\_IB\\_MSG\\_1271](#); SQLSTATE: [HY000](#)  
Message: Cannot upgrade server earlier than 5.7 to 8.0
  - Error number: [MY-013169](#); Symbol: [ER\\_STARTING\\_INIT](#); SQLSTATE: [HY000](#)  
Message: %s (mysqld %s) initializing of server in progress as process %lu
  - Error number: [MY-013170](#); Symbol: [ER\\_ENDING\\_INIT](#); SQLSTATE: [HY000](#)  
Message: %s (mysqld %s) initializing of server has completed
  - Error number: [MY-013171](#); Symbol: [ER\\_IB\\_MSG\\_1272](#); SQLSTATE: [HY000](#)  
Message: Cannot boot server version %lu on data directory built by version %llu. Downgrade is not supported
  - Error number: [MY-013172](#); Symbol: [ER\\_SERVER\\_SHUTDOWN\\_INFO](#); SQLSTATE: [HY000](#)  
Message: Received SHUTDOWN from user %s. Shutting down mysqld (Version: %s).
  - Error number: [MY-013173](#); Symbol: [ER\\_GRP\\_RPL\\_PLUGIN\\_ABORT](#); SQLSTATE: [HY000](#)  
Message: The plugin encountered a critical error and will abort: %s
  - Error number: [MY-013177](#); Symbol: [ER\\_AUDIT\\_LOG\\_TABLE\\_DEFINITION\\_NOT\\_UPDATED](#); SQLSTATE: [HY000](#)  
Message: '%s.%s' table definition has not been upgraded; Please perform the MySQL upgrade procedure.
  - Error number: [MY-013178](#); Symbol: [ER\\_DD\\_INITIALIZE\\_SQL\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Execution of server-side SQL statement '%s' failed with error code = %d, error message = '%s'.
  - Error number: [MY-013179](#); Symbol: [ER\\_NO\\_PATH\\_FOR\\_SHARED\\_LIBRARY](#); SQLSTATE: [HY000](#)  
Message: No paths allowed for shared library.
  - Error number: [MY-013180](#); Symbol: [ER\\_UDF\\_ALREADY\\_EXISTS](#); SQLSTATE: [HY000](#)  
Message: Function '%s' already exists.
  - Error number: [MY-013181](#); Symbol: [ER\\_SET\\_EVENT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Got Error: %ld from SetEvent.
  - Error number: [MY-013182](#); Symbol: [ER\\_FAILED\\_TO\\_ALLOCATE\\_SSL\\_BIO](#); SQLSTATE: [HY000](#)  
Message: Error allocating SSL BIO.
  - Error number: [MY-013183](#); Symbol: [ER\\_IB\\_MSG\\_1273](#); SQLSTATE: [HY000](#)  
Message: %s

- 
- Error number: [MY-013184](#); Symbol: [ER\\_PID\\_FILEPATH\\_LOCATIONS\\_INACCESSIBLE](#); SQLSTATE: [HY000](#)  
Message: One or several locations were inaccessible while checking PID filepath.
  - Error number: [MY-013185](#); Symbol: [ER\\_UNKNOWN\\_VARIABLE\\_IN\\_PERSISTED\\_CONFIG\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Currently unknown variable '%s' was read from the persisted config file.
  - Error number: [MY-013186](#); Symbol: [ER\\_FAILED\\_TO\\_HANDLE\\_DEFAULTS\\_FILE](#); SQLSTATE: [HY000](#)  
Message: Fatal error in defaults handling. Program aborted!
  - Error number: [MY-013187](#); Symbol: [ER\\_DUPLICATE\\_SYS\\_VAR](#); SQLSTATE: [HY000](#)  
Message: Duplicate variable name '%s'.
  - Error number: [MY-013188](#); Symbol: [ER\\_FAILED\\_TO\\_INIT\\_SYS\\_VAR](#); SQLSTATE: [HY000](#)  
Message: Failed to initialize system variables.
  - Error number: [MY-013189](#); Symbol: [ER\\_SYS\\_VAR\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)  
Message: Variable name '%s' not found.
  - Error number: [MY-013190](#); Symbol: [ER\\_IB\\_MSG\\_1274](#); SQLSTATE: [HY000](#)  
Message: Some (%d) threads are still active
  - Error number: [MY-013191](#); Symbol: [ER\\_IB\\_MSG\\_1275](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013193](#); Symbol: [ER\\_IB\\_MSG\\_WAIT\\_FOR\\_ENCRYPT\\_THREAD](#); SQLSTATE: [HY000](#)  
Message: Waiting for tablespace\_alter\_encrypt\_thread to exit
  - Error number: [MY-013194](#); Symbol: [ER\\_IB\\_MSG\\_1277](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013195](#); Symbol: [ER\\_IB\\_MSG\\_NO\\_ENCRYPT\\_PROGRESS\\_FOUND](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013196](#); Symbol: [ER\\_IB\\_MSG\\_RESUME\\_OP\\_FOR\\_SPACE](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013197](#); Symbol: [ER\\_IB\\_MSG\\_1280](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013198](#); Symbol: [ER\\_IB\\_MSG\\_1281](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013199](#); Symbol: [ER\\_IB\\_MSG\\_1282](#); SQLSTATE: [HY000](#)  
Message: %s

- 
- Error number: `MY-013200`; Symbol: `ER_IB_MSG_1283`; SQLSTATE: `HY000`  
Message: %s
  - Error number: `MY-013201`; Symbol: `ER_IB_MSG_1284`; SQLSTATE: `HY000`  
Message: %s
  - Error number: `MY-013202`; Symbol: `ER_CANT_SET_ERROR_SUPPRESSION_LIST_FROM_COMMAND_LINE`; SQLSTATE: `HY000`  
Message: %s: Could not add suppression rule for code "%s". Rule-set may be full, or code may not correspond to an error-log message.
  - Error number: `MY-013203`; Symbol: `ER_INVALID_VALUE_OF_BIND_ADDRESSES`; SQLSTATE: `HY000`  
Message: Invalid value for command line option bind-addresses: '%s'
  - Error number: `MY-013204`; Symbol: `ER_RELAY_LOG_SPACE_LIMIT_DISABLED`; SQLSTATE: `HY000`  
Message: Ignoring the @@global.relay\_log\_space\_limit option because @@global.relay\_log\_purge is disabled.
  - Error number: `MY-013205`; Symbol: `ER_GRP_RPL_ERROR_GTID_SET_EXTRACTION`; SQLSTATE: `HY000`  
Message: Error when extracting GTID execution information: %s
  - Error number: `MY-013206`; Symbol: `ER_GRP_RPL_MISSING_GRP_RPL_ACTION_COORDINATOR`; SQLSTATE: `HY000`  
Message: Message received without a proper group coordinator module.
  - Error number: `MY-013207`; Symbol: `ER_GRP_RPL_JOIN_WHEN_GROUP_ACTION_RUNNING`; SQLSTATE: `HY000`  
Message: A member cannot join the group while a group configuration operation '%s' is running initiated by '%s'.
  - Error number: `MY-013208`; Symbol: `ER_GRP_RPL_JOINER_EXIT_WHEN_GROUP_ACTION_RUNNING`; SQLSTATE: `HY000`  
Message: A member is joining the group while a group configuration operation '%s' is running initiated by '%s'. The member will now leave the group.
  - Error number: `MY-013209`; Symbol: `ER_GRP_RPL_CHANNEL_THREAD_WHEN_GROUP_ACTION_RUNNING`; SQLSTATE: `HY000`  
Message: Can't start %s for channel '%s' when group replication is running a group configuration operation '%s' initiated by '%s'.
  - Error number: `MY-013210`; Symbol: `ER_GRP_RPL_APPOINTED_PRIMARY_NOT_PRESENT`; SQLSTATE: `HY000`  
Message: A primary election was invoked but the requested primary member is not in the group. Request ignored.
  - Error number: `MY-013211`; Symbol: `ER_GRP_RPL_ERROR_ON_MESSAGE_SENDING`; SQLSTATE: `HY000`  
Message: Error while sending message. Context: %s



- 
- Error number: [MY-013212](#); Symbol: [ER\\_GRP\\_RPL\\_CONFIGURATION\\_ACTION\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Error while executing a group configuration operation: %s
  - Error number: [MY-013213](#); Symbol: [ER\\_GRP\\_RPL\\_CONFIGURATION\\_ACTION\\_LOCAL\\_TERMINATION](#); SQLSTATE: [HY000](#)  
Message: Configuration operation '%s' terminated. %s
  - Error number: [MY-013214](#); Symbol: [ER\\_GRP\\_RPL\\_CONFIGURATION\\_ACTION\\_START](#); SQLSTATE: [HY000](#)  
Message: Starting group operation local execution: %s
  - Error number: [MY-013215](#); Symbol: [ER\\_GRP\\_RPL\\_CONFIGURATION\\_ACTION\\_END](#); SQLSTATE: [HY000](#)  
Message: Termination of group operation local execution: %s
  - Error number: [MY-013216](#); Symbol: [ER\\_GRP\\_RPL\\_CONFIGURATION\\_ACTION\\_KILLED\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: A configuration change was killed in this member. The member will now leave the group as its configuration may have diverged.
  - Error number: [MY-013217](#); Symbol: [ER\\_GRP\\_RPL\\_PRIMARY\\_ELECTION\\_PROCESS\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: There was an issue on the primary election process: %s The member will now leave the group.
  - Error number: [MY-013218](#); Symbol: [ER\\_GRP\\_RPL\\_PRIMARY\\_ELECTION\\_STOP\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: There was an issue when stopping a previous election process: %s
  - Error number: [MY-013219](#); Symbol: [ER\\_GRP\\_RPL\\_NO\\_STAGE\\_SERVICE](#); SQLSTATE: [HY000](#)  
Message: It was not possible to initialize stage logging for this task. The operation will still run without stage tracking.
  - Error number: [MY-013220](#); Symbol: [ER\\_GRP\\_RPL\\_UDF\\_REGISTER\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Could not execute the installation of Group Replication UDF function: %s. Check if the function is already present, if so, try to remove it
  - Error number: [MY-013221](#); Symbol: [ER\\_GRP\\_RPL\\_UDF\\_UNREGISTER\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Could not uninstall Group Replication UDF functions. Try to remove them manually if present.
  - Error number: [MY-013222](#); Symbol: [ER\\_GRP\\_RPL\\_UDF\\_REGISTER\\_SERVICE\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Could not execute the installation of Group Replication UDF functions. Check for other errors in the log and try to reinstall the plugin
  - Error number: [MY-013223](#); Symbol: [ER\\_GRP\\_RPL\\_SERVER\\_UDF\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: The function '%s' failed. %s
  - Error number: [MY-013227](#); Symbol: [ER\\_SERVER\\_WRONG\\_VALUE\\_FOR\\_VAR](#); SQLSTATE: [HY000](#)
-

---

Message: Variable '%s' can't be set to the value of '%s'

- Error number: [MY-013228](#); Symbol: [ER\\_COULD\\_NOT\\_CREATE\\_WINDOWS\\_REGISTRY\\_KEY](#); SQLSTATE: [HY000](#)

Message: %s was unable to create a new Windows registry key %s for %s; continuing to use the previous ident.

- Error number: [MY-013229](#); Symbol: [ER\\_SERVER\\_GTID\\_UNSAFE\\_CREATE\\_DROP\\_TEMP\\_TABLE\\_IN\\_TRX\\_IN\\_SBR](#); SQLSTATE: [HY000](#)

Message: Statement violates GTID consistency: CREATE TEMPORARY TABLE and DROP TEMPORARY TABLE are not allowed inside a transaction or inside a procedure in a transactional context when @@session.binlog\_format=STATEMENT.

- Error number: [MY-013233](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_SWITCH\\_SECURITY\\_CTX](#); SQLSTATE: [HY000](#)

Message: Unable to switch security context to user: %s

- Error number: [MY-013234](#); Symbol: [ER\\_RPL\\_GTID\\_UNSAFE\\_ALTER\\_ADD\\_COL\\_WITH\\_DEFAULT\\_EXPRESSION](#); SQLSTATE: [HY000](#)

Message: Statement violates GTID consistency: ALTER TABLE ... ADD COLUMN .. with expression as DEFAULT.

- Error number: [MY-013235](#); Symbol: [ER\\_UPGRADE\\_PARSE\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Error in parsing %s '%s'. '%s' during upgrade. %s

- Error number: [MY-013236](#); Symbol: [ER\\_DATA\\_DIRECTORY\\_UNUSABLE](#); SQLSTATE: [HY000](#)

Message: The designated data directory %s is unusable. You can remove all files that the server added to it.

- Error number: [MY-013237](#); Symbol: [ER\\_LDAP\\_AUTH\\_USER\\_GROUP\\_SEARCH\\_ROOT\\_BIND](#); SQLSTATE: [HY000](#)

Message: Group search rebinding via root DN: %s

- Error number: [MY-013238](#); Symbol: [ER\\_PLUGIN\\_INSTALL\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Error installing plugin '%s': %s

- Error number: [MY-013239](#); Symbol: [ER\\_PLUGIN\\_UNINSTALL\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Error uninstalling plugin '%s': %s

- Error number: [MY-013240](#); Symbol: [ER\\_SHARED\\_TABLESPACE\\_USED\\_BY\\_PARTITIONED\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Partitioned table '%s' is not allowed to use shared tablespace '%s'. Please move all partitions to file-per-table tablespaces before upgrade.

- Error number: [MY-013241](#); Symbol: [ER\\_UNKNOWN\\_TABLESPACE\\_TYPE](#); SQLSTATE: [HY000](#)

Message: Cannot determine the type of the tablespace named '%s'.

- Error number: [MY-013242](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_UTF8\\_ALIAS\\_OPTION](#); SQLSTATE: [HY000](#)

Message: %s: 'utf8' is currently an alias for the character set UTF8MB3, but will be an alias for UTF8MB4 in a future release. Please consider using UTF8MB4 in order to be unambiguous.

- 
- Error number: [MY-013243](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_UTF8MB3\\_CHARSET\\_OPTION](#); SQLSTATE: [HY000](#)  
  
Message: %s: The character set UTF8MB3 is deprecated and will be removed in a future release. Please consider using UTF8MB4 instead.
  - Error number: [MY-013244](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_UTF8MB3\\_COLLATION\\_OPTION](#); SQLSTATE: [HY000](#)  
  
Message: %s: '%s' is a collation of the deprecated character set UTF8MB3. Please consider using UTF8MB4 with an appropriate collation instead.
  - Error number: [MY-013245](#); Symbol: [ER\\_SSL\\_MEMORY\\_INSTRUMENTATION\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: The SSL library function %s failed. This is typically caused by the SSL library already being used. As a result the SSL memory allocation will not be instrumented.
  - Error number: [MY-013246](#); Symbol: [ER\\_IB\\_MSG\\_MADV\\_DONTDUMP\\_UNSUPPORTED](#); SQLSTATE: [HY000](#)  
  
Message: Disabling @@core\_file because @@innodb\_buffer\_pool\_in\_core\_file is disabled, yet MADV\_DONTDUMP is not supported on this platform
  - Error number: [MY-013247](#); Symbol: [ER\\_IB\\_MSG\\_MADVISE\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Disabling @@core\_file because @@innodb\_buffer\_pool\_in\_core\_file is disabled, yet madvise(%p,%zu,%s) failed with %s
  - Error number: [MY-013249](#); Symbol: [ER\\_WARN\\_REMOVED\\_SQL\\_MODE](#); SQLSTATE: [HY000](#)  
  
Message: sql\_mode=0x%08x has been removed and will be ignored
  - Error number: [MY-013250](#); Symbol: [ER\\_IB\\_MSG\\_FAILED\\_TO\\_ALLOCATE\\_WAIT](#); SQLSTATE: [HY000](#)  
  
Message: Failed to allocate memory for a pool of size %zu bytes. Will wait for %zu seconds for a thread to free a resource.
  - Error number: [MY-013252](#); Symbol: [ER\\_IB\\_MSG\\_USING\\_UNDO\\_SPACE](#); SQLSTATE: [HY000](#)  
  
Message: Using undo tablespace '%s'.
  - Error number: [MY-013253](#); Symbol: [ER\\_IB\\_MSG\\_FAIL\\_TO\\_SAVE\\_SPACE\\_STATE](#); SQLSTATE: [HY000](#)  
  
Message: %s Unable to save the current state of tablespace '%s' to the data dictionary
  - Error number: [MY-013254](#); Symbol: [ER\\_IB\\_MSG\\_MAX\\_UNDO\\_SPACES\\_REACHED](#); SQLSTATE: [HY000](#)  
  
Message: Cannot create undo tablespace %s at %s because %d undo tablespaces already exist.
  - Error number: [MY-013255](#); Symbol: [ER\\_IB\\_MSG\\_ERROR\\_OPENING\\_NEW\\_UNDO\\_SPACE](#); SQLSTATE: [HY000](#)  
  
Message: Error %d opening newly created undo tablespace %s.
  - Error number: [MY-013256](#); Symbol: [ER\\_IB\\_MSG\\_FAILED\\_SDI\\_Z\\_BUF\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: SDI Compression failed, Z\_BUF\_ERROR
-

- 
- Error number: [MY-013257](#); Symbol: [ER\\_IB\\_MSG\\_FAILED\\_SDI\\_Z\\_MEM\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: SDI Compression failed, Z\_MEM\_ERROR
  - Error number: [MY-013258](#); Symbol: [ER\\_IB\\_MSG\\_SDI\\_Z\\_STREAM\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: SDI Compression failed, Z\_STREAM\_ERROR
  - Error number: [MY-013259](#); Symbol: [ER\\_IB\\_MSG\\_SDI\\_Z\\_UNKNOWN\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013260](#); Symbol: [ER\\_IB\\_MSG\\_FOUND\\_WRONG\\_UNDO\\_SPACE](#); SQLSTATE: [HY000](#)  
Message: Expected to find undo tablespace '%s' for Space ID=%lu, but found '%s' instead! Did you change innodb\_undo\_directory?
  - Error number: [MY-013261](#); Symbol: [ER\\_IB\\_MSG\\_NOT\\_END\\_WITH\\_IBU](#); SQLSTATE: [HY000](#)  
Message: Cannot use %s as an undo tablespace because it does not end with '.ibu'.
  - Error number: [MY-013266](#); Symbol: [ER\\_IB\\_MSG\\_FAILED\\_TO\\_FINISH\\_TRUNCATE](#); SQLSTATE: [HY000](#)  
Message: %s Failed to finish truncating Undo Tablespace '%s'
  - Error number: [MY-013267](#); Symbol: [ER\\_IB\\_MSG\\_DEPRECATED\\_INNODB\\_UNDO\\_TABLESPACES](#); SQLSTATE: [HY000](#)  
Message: The setting INNODB\_UNDO\_TABLESPACES is deprecated and is no longer used. InnoDB always creates 2 undo tablespaces to start with. If you need more, please use CREATE UNDO TABLESPACE.
  - Error number: [MY-013268](#); Symbol: [ER\\_IB\\_MSG\\_WRONG\\_TABLESPACE\\_DIR](#); SQLSTATE: [HY000](#)  
Message: The directory for tablespace %s does not exist or is incorrect.
  - Error number: [MY-013269](#); Symbol: [ER\\_IB\\_MSG\\_LOCK\\_FREE\\_HASH\\_USAGE\\_STATS](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013270](#); Symbol: [ER\\_CLONE\\_DONOR\\_TRACE](#); SQLSTATE: [HY000](#)  
Message: Clone donor reported : %s.
  - Error number: [MY-013271](#); Symbol: [ER\\_CLONE\\_PROTOCOL\\_TRACE](#); SQLSTATE: [HY000](#)  
Message: Clone received unexpected response from donor : %s.
  - Error number: [MY-013272](#); Symbol: [ER\\_CLONE\\_CLIENT\\_TRACE](#); SQLSTATE: [HY000](#)  
Message: Client: %s.
  - Error number: [MY-013273](#); Symbol: [ER\\_CLONE\\_SERVER\\_TRACE](#); SQLSTATE: [HY000](#)  
Message: Server: %s.
  - Error number: [MY-013274](#); Symbol: [ER\\_THREAD\\_POOL\\_PFS\\_TABLES\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to initialize the performance schema tables service.

- 
- Error number: [MY-013275](#); Symbol: [ER\\_THREAD\\_POOL\\_PFS\\_TABLES\\_ADD\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to add thread pool performance schema tables.
  - Error number: [MY-013276](#); Symbol: [ER\\_CANT\\_SET\\_DATA\\_DIR](#); SQLSTATE: [HY000](#)  
Message: Failed to set datadir to '%s' (OS errno: %d - %s)
  - Error number: [MY-013277](#); Symbol: [ER\\_INNODB\\_INVALID\\_INNODB\\_UNDO\\_DIRECTORY\\_LOCATION](#); SQLSTATE: [HY000](#)  
Message: The innodb\_undo\_directory is not allowed to be an ancestor of the datadir.
  - Error number: [MY-013278](#); Symbol: [ER\\_SERVER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_FETCH\\_KEY](#); SQLSTATE: [HY000](#)  
Message: Failed to fetch key from keyring, please check if keyring is loaded.
  - Error number: [MY-013279](#); Symbol: [ER\\_SERVER\\_RPL\\_ENCRYPTION\\_KEY\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)  
Message: Can't find key from keyring, please check in the server log if a keyring is loaded and initialized successfully.
  - Error number: [MY-013280](#); Symbol: [ER\\_SERVER\\_RPL\\_ENCRYPTION\\_KEYRING\\_INVALID\\_KEY](#); SQLSTATE: [HY000](#)  
Message: Fetched an invalid key from keyring.
  - Error number: [MY-013281](#); Symbol: [ER\\_SERVER\\_RPL\\_ENCRYPTION\\_HEADER\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Error reading a replication log encryption header: %s.
  - Error number: [MY-013282](#); Symbol: [ER\\_SERVER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_ROTATE\\_LOGS](#); SQLSTATE: [HY000](#)  
Message: Failed to rotate some logs after changing binlog encryption settings. Please fix the problem and rotate the logs manually.
  - Error number: [MY-013283](#); Symbol: [ER\\_SERVER\\_RPL\\_ENCRYPTION\\_KEY\\_EXISTS\\_UNEXPECTED](#); SQLSTATE: [HY000](#)  
Message: Key %s exists unexpected.
  - Error number: [MY-013284](#); Symbol: [ER\\_SERVER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_GENERATE\\_KEY](#); SQLSTATE: [HY000](#)  
Message: Failed to generate key, please check if keyring is loaded.
  - Error number: [MY-013285](#); Symbol: [ER\\_SERVER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_STORE\\_KEY](#); SQLSTATE: [HY000](#)  
Message: Failed to store key, please check if keyring is loaded.
  - Error number: [MY-013286](#); Symbol: [ER\\_SERVER\\_RPL\\_ENCRYPTION\\_FAILED\\_TO\\_REMOVE\\_KEY](#); SQLSTATE: [HY000](#)  
Message: Failed to remove key, please check if keyring is loaded.
  - Error number: [MY-013287](#); Symbol: [ER\\_SERVER\\_RPL\\_ENCRYPTION\\_MASTER\\_KEY\\_RECOVERY\\_FAILED](#); SQLSTATE: [HY000](#)

---

Message: Unable to recover binlog encryption master key, please check if keyring is loaded.

- Error number: MY-013288; Symbol: ER\_SERVER\_RPL\_ENCRYPTION\_UNABLE\_TO\_INITIALIZE; SQLSTATE: HY000

Message: Failed to initialize binlog encryption, please check if keyring is loaded.

- Error number: MY-013289; Symbol: ER\_SERVER\_RPL\_ENCRYPTION\_UNABLE\_TO\_ROTATE\_MASTER\_KEY\_AT\_STARTUP; SQLSTATE: HY000

Message: Failed to rotate binlog encryption master key at startup, please check if keyring is loaded.

- Error number: MY-013290; Symbol: ER\_SERVER\_RPL\_ENCRYPTION\_IGNORE\_ROTATE\_MASTER\_KEY\_AT\_STARTUP; SQLSTATE: HY000

Message: Ignoring binlog\_rotate\_encryption\_master\_key\_at\_startup because binlog\_encryption option is disabled.

- Error number: MY-013291; Symbol: ER\_INVALID\_ADMIN\_ADDRESS; SQLSTATE: HY000

Message: Invalid value for command line option admin-address: '%s'

- Error number: MY-013292; Symbol: ER\_SERVER\_STARTUP\_ADMIN\_INTERFACE; SQLSTATE: HY000

Message: Admin interface ready for connections, address: '%s' port: %d

- Error number: MY-013293; Symbol: ER\_CANT\_CREATE\_ADMIN\_THREAD; SQLSTATE: HY000

Message: Can't create thread to handle admin connections (errno= %d)

- Error number: MY-013294; Symbol: ER\_WARNING\_RETAIN\_CURRENT\_PASSWORD\_CLAUSE\_VOID; SQLSTATE: HY000

Message: RETAIN CURRENT PASSWORD ignored for user '%s'@'%s' as its authentication plugin %s does not support multiple passwords.

- Error number: MY-013295; Symbol: ER\_WARNING\_DISCARD\_OLD\_PASSWORD\_CLAUSE\_VOID; SQLSTATE: HY000

Message: DISCARD OLD PASSWORD ignored for user '%s'@'%s' as its authentication plugin %s does not support multiple passwords.

- Error number: MY-013299; Symbol: ER\_WARNING\_AUTHCACHE\_INVALID\_USER\_ATTRIBUTES; SQLSTATE: HY000

Message: Can not read and process value of User\_attributes column from mysql.user table for user: '%s'@'%s'; Ignoring user.

- Error number: MY-013300; Symbol: ER\_MYSQL\_NATIVE\_PASSWORD\_SECOND\_PASSWORD\_USED\_INFORMATION; SQLSTATE: HY000

Message: Second password was used for login by user: '%s'@'%s'.

- Error number: MY-013301; Symbol: ER\_SHA256\_PASSWORD\_SECOND\_PASSWORD\_USED\_INFORMATION; SQLSTATE: HY000

Message: Second password was used for login by user: '%s'@'%s'.

- Error number: MY-013302; Symbol: ER\_CACHING\_SHA2\_PASSWORD\_SECOND\_PASSWORD\_USED\_INFORMATION; SQLSTATE: HY000

---

Message: Second password was used for login by user: '%s'@'%s'.

- Error number: [MY-013303](#); Symbol: [ER\\_GRP\\_RPL\\_SEND\\_TRX\\_PREPARED\\_MESSAGE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Error sending transaction '%d:%lld' prepared message from session '%u'.

- Error number: [MY-013304](#); Symbol: [ER\\_GRP\\_RPL\\_RELEASE\\_COMMIT\\_AFTER\\_GROUP\\_PREPARE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Error releasing transaction '%d:%lld' for commit on session '%u' after being prepared on all group members.

- Error number: [MY-013305](#); Symbol: [ER\\_GRP\\_RPL\\_TRX\\_ALREADY\\_EXISTS\\_ON\\_TCM\\_ON\\_AFTER\\_CERTIFICATION](#); SQLSTATE: [HY000](#)

Message: Transaction '%d:%lld' already exists on Group Replication consistency manager while being registered after conflict detection.

- Error number: [MY-013306](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_INSERT\\_TRX\\_ON\\_TCM\\_ON\\_AFTER\\_CERTIFICATION](#); SQLSTATE: [HY000](#)

Message: Error registering transaction '%d:%lld' on Group Replication consistency manager after conflict detection.

- Error number: [MY-013307](#); Symbol: [ER\\_GRP\\_RPL\\_REGISTER\\_TRX\\_TO\\_WAIT\\_FOR\\_GROUP\\_PREPARE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Error registering transaction '%d:%lld' from session '%u' to wait for being prepared on all group members.

- Error number: [MY-013308](#); Symbol: [ER\\_GRP\\_RPL\\_TRX\\_WAIT\\_FOR\\_GROUP\\_PREPARE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Error on transaction '%d:%lld' from session '%u' while waiting for being prepared on all group members.

- Error number: [MY-013309](#); Symbol: [ER\\_GRP\\_RPL\\_TRX\\_DOES\\_NOT\\_EXIST\\_ON\\_TCM\\_ON\\_HANDLE\\_REMOTE\\_PREPARE](#); SQLSTATE: [HY000](#)

Message: Transaction '%d:%lld' does not exist on Group Replication consistency manager while receiving remote transaction prepare.

- Error number: [MY-013310](#); Symbol: [ER\\_GRP\\_RPL\\_RELEASE\\_BEGIN\\_TRX\\_AFTER\\_DEPENDENCIES\\_COMMIT\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Error releasing transaction '%d:%lld' for execution on session '%u' after its dependencies did complete commit.

- Error number: [MY-013311](#); Symbol: [ER\\_GRP\\_RPL\\_REGISTER\\_TRX\\_TO\\_WAIT\\_FOR\\_DEPENDENCIES\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Error registering transaction from session '%u' to wait for its dependencies to complete commit.

- Error number: [MY-013312](#); Symbol: [ER\\_GRP\\_RPL\\_WAIT\\_FOR\\_DEPENDENCIES\\_FAILED](#); SQLSTATE: [HY000](#)

---

Message: Error on session '%u' while waiting for its dependencies to complete commit.

- Error number: MY-013313; Symbol: ER\_GRP\_RPL\_REGISTER\_TRX\_TO\_WAIT\_FOR\_SYNC\_BEFORE\_EXECUTION\_FAILED; SQLSTATE: HY000

Message: Error registering transaction from session '%u' to wait for sync before execution.

- Error number: MY-013314; Symbol: ER\_GRP\_RPL\_SEND\_TRX\_SYNC\_BEFORE\_EXECUTION\_FAILED; SQLSTATE: HY000

Message: Error sending sync before execution message from session '%u'.

- Error number: MY-013315; Symbol: ER\_GRP\_RPL\_TRX\_WAIT\_FOR\_SYNC\_BEFORE\_EXECUTION\_FAILED; SQLSTATE: HY000

Message: Error on transaction from session '%u' while waiting for sync before execution.

- Error number: MY-013316; Symbol: ER\_GRP\_RPL\_RELEASE\_BEGIN\_TRX\_AFTER\_WAIT\_FOR\_SYNC\_BEFORE\_EXEC; SQLSTATE: HY000

Message: Error releasing transaction for execution on session '%u' after wait for sync before execution.

- Error number: MY-013317; Symbol: ER\_GRP\_RPL\_TRX\_WAIT\_FOR\_GROUP\_GTID\_EXECUTED; SQLSTATE: HY000

Message: Error waiting for group executed transactions commit on session '%u'.

- Error number: MY-013320; Symbol: ER\_WARN\_PROPERTY\_STRING\_PARSE\_FAILED; SQLSTATE: HY000

Message: Could not parse key-value pairs in property string '%s'

- Error number: MY-013321; Symbol: ER\_INVALID\_PROPERTY\_KEY; SQLSTATE: HY000

Message: Property key '%s' is invalid.

- Error number: MY-013322; Symbol: ER\_GRP\_RPL\_GTID\_SET\_EXTRACT\_ERROR\_DURING\_RECOVERY; SQLSTATE: HY000

Message: Error when extracting the group\_replication\_applier channel received transactions set. Unable to ensure the execution of group transactions received during recovery.

- Error number: MY-013323; Symbol: ER\_SERVER\_RPL\_ENCRYPTION\_FAILED\_TO\_ENCRYPT; SQLSTATE: HY000

Message: Failed to encrypt content to write into binlog file: %s.

- Error number: MY-013324; Symbol: ER\_CANNOT\_GET\_SERVER\_VERSION\_FROM\_TABLESPACE\_HEADER; SQLSTATE: HY000

Message: Cannot get the server version number from the dictionary tablespace header.

- Error number: MY-013325; Symbol: ER\_CANNOT\_SET\_SERVER\_VERSION\_IN\_TABLESPACE\_HEADER; SQLSTATE: HY000

Message: Cannot set the server version number in the dictionary tablespace header.

- Error number: MY-013326; Symbol: ER\_SERVER\_UPGRADE\_VERSION\_NOT\_SUPPORTED; SQLSTATE: HY000



---

Message: Upgrading the server from server version '%u' is not supported.

- Error number: [MY-013327](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_FROM\\_VERSION](#); SQLSTATE: [HY000](#)

Message: MySQL server upgrading from version '%u' to '%u'.

- Error number: [MY-013328](#); Symbol: [ER\\_GRP\\_RPL\\_ERROR\\_ON\\_CERT\\_DB\\_INSTALL](#); SQLSTATE: [HY000](#)

Message: The certification information could not be set in this server: '%s'

- Error number: [MY-013329](#); Symbol: [ER\\_GRP\\_RPL\\_FORCE\\_MEMBERS\\_WHEN\\_LEAVING](#); SQLSTATE: [HY000](#)

Message: A request to force a new group membership was issued when the member is leaving the group.

- Error number: [MY-013330](#); Symbol: [ER\\_TRG\\_WRONG\\_ORDER](#); SQLSTATE: [HY000](#)

Message: Trigger %s.%s for table %s.%s is listed in wrong order. Please drop and recreate all triggers for the table.

- Error number: [MY-013332](#); Symbol: [ER\\_LDAP\\_AUTH\\_GRP\\_SEARCH\\_NOT\\_SPECIAL\\_HDL](#); SQLSTATE: [HY000](#)

Message: Special handling for group search, {GA} not found

- Error number: [MY-013333](#); Symbol: [ER\\_LDAP\\_AUTH\\_GRP\\_USER\\_OBJECT\\_HAS\\_GROUP\\_INFO](#); SQLSTATE: [HY000](#)

Message: User group retrieval: User object has group information

- Error number: [MY-013334](#); Symbol: [ER\\_LDAP\\_AUTH\\_GRP\\_INFO\\_FOUND\\_IN\\_MANY\\_OBJECTS](#); SQLSTATE: [HY000](#)

Message: Group information found in multiple user objects. Search filter configuration is incorrect.

- Error number: [MY-013335](#); Symbol: [ER\\_LDAP\\_AUTH\\_GRP\\_INCORRECT\\_ATTRIBUTE](#); SQLSTATE: [HY000](#)

Message: User group retrieval: no group attribute found. Incorrect group search attribute.

- Error number: [MY-013336](#); Symbol: [ER\\_LDAP\\_AUTH\\_GRP\\_NULL\\_ATTRIBUTE\\_VALUE](#); SQLSTATE: [HY000](#)

Message: User group retrieval: Group attribute values is NULL.

- Error number: [MY-013337](#); Symbol: [ER\\_LDAP\\_AUTH\\_GRP\\_DN\\_PARSING\\_FAILED](#); SQLSTATE: [HY000](#)

Message: User group retrieval: parsing DN failed.

- Error number: [MY-013338](#); Symbol: [ER\\_LDAP\\_AUTH\\_GRP\\_OBJECT\\_HAS\\_USER\\_INFO](#); SQLSTATE: [HY000](#)

Message: User group retrieval: Group object has user information

- Error number: [MY-013339](#); Symbol: [ER\\_LDAP\\_AUTH\\_LDAPS](#); SQLSTATE: [HY000](#)

Message: Reserved port for ldaps using ldaps

- Error number: [MY-013340](#); Symbol: [ER\\_LDAP\\_MAPPING\\_GET\\_USER\\_PROXY](#); SQLSTATE: [HY000](#)

---

Message: Get user proxy

- Error number: MY-013341; Symbol: ER\_LDAP\_MAPPING\_USER\_DONT\_BELONG\_GROUP; SQLSTATE: HY000

Message: Get user proxy: User doesn't belongs to any group, user name will be treated as authenticated user.

- Error number: MY-013342; Symbol: ER\_LDAP\_MAPPING\_INFO; SQLSTATE: HY000

Message: Get user proxy: configured mapping info: %s

- Error number: MY-013343; Symbol: ER\_LDAP\_MAPPING\_EMPTY\_MAPPING; SQLSTATE: HY000

Message: Get user proxy: User doesn't have group mapping information, First LDAP group will be treated as authenticated user.

- Error number: MY-013344; Symbol: ER\_LDAP\_MAPPING\_PROCESS\_MAPPING; SQLSTATE: HY000

Message: Process group proxy mapping

- Error number: MY-013345; Symbol: ER\_LDAP\_MAPPING\_CHECK\_DELIMI\_QUOTE; SQLSTATE: HY000

Message: Check delimiter after quote

- Error number: MY-013346; Symbol: ER\_LDAP\_MAPPING\_PROCESS\_DELIMITER; SQLSTATE: HY000

Message: Processing delimiter

- Error number: MY-013347; Symbol: ER\_LDAP\_MAPPING\_PROCESS\_DELIMITER\_EQUAL\_NOT\_FOUND; SQLSTATE: HY000

Message: Processing delimiter, separator = not found, resetting position

- Error number: MY-013348; Symbol: ER\_LDAP\_MAPPING\_PROCESS\_DELIMITER\_TRY\_COMMA; SQLSTATE: HY000

Message: Processing delimiter, failed to get data for = separator try for separator ,

- Error number: MY-013349; Symbol: ER\_LDAP\_MAPPING\_PROCESS\_DELIMITER\_COMMA\_NOT\_FOUND; SQLSTATE: HY000

Message: Processing delimiter, separator , not found, resetting position

- Error number: MY-013350; Symbol: ER\_LDAP\_MAPPING\_NO\_SEPEARATOR\_END\_OF\_GROUP; SQLSTATE: HY000

Message: Processing delimiter: No mapping separator is found, end of group information

- Error number: MY-013351; Symbol: ER\_LDAP\_MAPPING\_GETTING\_NEXT\_MAPPING; SQLSTATE: HY000

Message: Getting next mapping information

- Error number: MY-013352; Symbol: ER\_LDAP\_MAPPING\_PARSING\_CURRENT\_STATE; SQLSTATE: HY000

Message: Parsing mapping, current state: %d delimiter char: %c

- Error number: MY-013353; Symbol: ER\_LDAP\_MAPPING\_PARSING\_MAPPING\_INFO; SQLSTATE: HY000

---

Message: Parsing mapping info, LDAP group: %s MySQL proxy: %s

- Error number: [MY-013354](#); Symbol: [ER\\_LDAP\\_MAPPING\\_PARSING\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Mapping parsing error

- Error number: [MY-013355](#); Symbol: [ER\\_LDAP\\_MAPPING\\_TRIMMING\\_SPACES](#); SQLSTATE: [HY000](#)

Message: Trimming left spaces

- Error number: [MY-013356](#); Symbol: [ER\\_LDAP\\_MAPPING\\_IS\\_QUOTE](#); SQLSTATE: [HY000](#)

Message: Checking if current characters is quote

- Error number: [MY-013357](#); Symbol: [ER\\_LDAP\\_MAPPING\\_NON\\_DESIRED\\_STATE](#); SQLSTATE: [HY000](#)

Message: Not desired state or un-defined states.

- Error number: [MY-013358](#); Symbol: [ER\\_INVALID\\_NAMED\\_PIPE\\_FULL\\_ACCESS\\_GROUP](#); SQLSTATE: [HY000](#)

Message: Invalid value for named\_pipe\_full\_access\_group.

- Error number: [MY-013359](#); Symbol: [ER\\_PREPARE\\_FOR\\_SECONDARY\\_ENGINE](#); SQLSTATE: [HY000](#)

Message: Retry the statement using a secondary storage engine.

- Error number: [MY-013360](#); Symbol: [ER\\_SERVER\\_WARN\\_DEPRECATED](#); SQLSTATE: [HY000](#)

Message: '%s' is deprecated and will be removed in a future release. Please use %s instead

- Error number: [MY-013361](#); Symbol: [ER\\_AUTH\\_ID\\_WITH\\_SYSTEM\\_USER\\_PRIV\\_IN\\_MANDATORY\\_ROLES](#); SQLSTATE: [HY000](#)

Message: Cannot set mandatory\_roles: AuthId `%s`@`%s` has '%s' privilege.

- Error number: [MY-013362](#); Symbol: [ER\\_SERVER\\_BINLOG\\_MASTER\\_KEY\\_RECOVERY\\_OUT\\_OF\\_COMBINATION](#); SQLSTATE: [HY000](#)

Message: Unable to recover binary log master key, the combination of new\_master\_key\_seqno=%u, master\_key\_seqno=%u and old\_master\_key\_seqno=%u are wrong.

- Error number: [MY-013363](#); Symbol: [ER\\_SERVER\\_BINLOG\\_MASTER\\_KEY\\_ROTATION\\_FAIL\\_TO\\_CLEANUP\\_AUX\\_KEY](#); SQLSTATE: [HY000](#)

Message: Failed to remove auxiliary binary log encryption key from keyring, please check if keyring is loaded. The cleanup of the binary log master key rotation process did not finish as expected and the cleanup will take place upon server restart or next 'ALTER INSTANCE ROTATE BINLOG MASTER KEY' execution.

- Error number: [MY-013368](#); Symbol: [ER\\_TURNING\\_ON\\_PARTIAL\\_REVOKES](#); SQLSTATE: [HY000](#)

Message: At least one partial revoke exists on a database. Turning ON the system variable '@@partial\_revokes'.

- Error number: [MY-013369](#); Symbol: [ER\\_WARN\\_PARTIAL\\_REVOKE\\_AND\\_DB\\_GRANT](#); SQLSTATE: [HY000](#)

Message: For user '%s'@'%s', one or more privileges granted through mysql.db for database '%s', conflict with partial revoke. It could mean 'mysql' schema is corrupted.

- 
- Error number: [MY-013370](#); Symbol: [ER\\_WARN\\_INCORRECT\\_PRIVILEGE\\_FOR\\_DB\\_RESTRICTIONS](#); SQLSTATE: [HY000](#)  
Message: For user %s, ignored restrictions for privilege(s) '%s' for database '%s' as these are not valid database privileges.
  - Error number: [MY-013371](#); Symbol: [ER\\_WARN\\_INVALID\\_DB\\_RESTRICTIONS](#); SQLSTATE: [HY000](#)  
Message: For user %s, ignored restrictions for privilege(s) '%s' for database '%s' as corresponding global privilege(s) are not granted.
  - Error number: [MY-013372](#); Symbol: [ER\\_GRP\\_RPL\\_INVALID\\_COMMUNICATION\\_PROTOCOL](#); SQLSTATE: [HY000](#)  
Message: '%s' is an invalid value for group\_replication\_communication\_protocol\_join, please use a MySQL version between 5.7.14 and this server's version
  - Error number: [MY-013373](#); Symbol: [ER\\_GRP\\_RPL\\_STARTED\\_AUTO\\_REJOIN](#); SQLSTATE: [HY000](#)  
Message: Started auto-rejoin procedure attempt %lu of %lu
  - Error number: [MY-013374](#); Symbol: [ER\\_GRP\\_RPL\\_TIMEOUT\\_RECEIVED\\_VC\\_ON\\_REJOIN](#); SQLSTATE: [HY000](#)  
Message: Timeout while waiting for a view change event during the auto-rejoin procedure
  - Error number: [MY-013375](#); Symbol: [ER\\_GRP\\_RPL\\_FINISHED\\_AUTO\\_REJOIN](#); SQLSTATE: [HY000](#)  
Message: Auto-rejoin procedure attempt %lu of %lu finished. Member was%s able to join the group.
  - Error number: [MY-013376](#); Symbol: [ER\\_GRP\\_RPL\\_DEFAULT\\_TABLE\\_ENCRYPTION\\_DIFF\\_FROM\\_GRP](#); SQLSTATE: [HY000](#)  
Message: The member is configured with a default\_table\_encryption option value '%d' different from the group '%d'. The member will now exit the group.
  - Error number: [MY-013377](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_OFF](#); SQLSTATE: [HY000](#)  
Message: Server shutting down because upgrade is required, yet prohibited by the command line option '--upgrade=NONE'.
  - Error number: [MY-013378](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_SKIP](#); SQLSTATE: [HY000](#)  
Message: Server upgrade is required, but skipped by command line option '--upgrade=MINIMAL'.
  - Error number: [MY-013379](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_PENDING](#); SQLSTATE: [HY000](#)  
Message: Server upgrade started with version %d, but server upgrade of version %d is still pending.
  - Error number: [MY-013380](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to upgrade server.
  - Error number: [MY-013381](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_STATUS](#); SQLSTATE: [HY000](#)  
Message: Server upgrade from '%d' to '%d' %s.
  - Error number: [MY-013382](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_REPAIR\\_REQUIRED](#); SQLSTATE: [HY000](#)  
Message: Table '%s' requires repair.
  - Error number: [MY-013383](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_REPAIR\\_STATUS](#); SQLSTATE: [HY000](#)

---

Message: Table '%s' repair %s.

- Error number: [MY-013384](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_INFO\\_FILE](#); SQLSTATE: [HY000](#)

Message: Could not open server upgrade info file '%s' for writing. Please make sure the file is writable.

- Error number: [MY-013385](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_SYS\\_SCHEMA](#); SQLSTATE: [HY000](#)

Message: Upgrading the sys schema.

- Error number: [MY-013386](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_MYSQL\\_TABLES](#); SQLSTATE: [HY000](#)

Message: Running queries to upgrade MySQL server.

- Error number: [MY-013387](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_SYSTEM\\_TABLES](#); SQLSTATE: [HY000](#)

Message: Upgrading system table data.

- Error number: [MY-013388](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_EMPTY\\_SYS](#); SQLSTATE: [HY000](#)

Message: Found empty sys database. Installing the sys schema.

- Error number: [MY-013389](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_NO\\_SYS\\_VERSION](#); SQLSTATE: [HY000](#)

Message: A sys schema exists with no sys.version view. If you have a user created sys schema, this must be renamed for the upgrade to succeed.

- Error number: [MY-013390](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_SYS\\_VERSION\\_EMPTY](#); SQLSTATE: [HY000](#)

Message: A sys schema exists with a sys.version view, but it returns no results.

- Error number: [MY-013391](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_SYS\\_SCHEMA\\_OUTDATED](#); SQLSTATE: [HY000](#)

Message: Found outdated sys schema version %s.

- Error number: [MY-013392](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_SYS\\_SCHEMA\\_UP\\_TO\\_DATE](#); SQLSTATE: [HY000](#)

Message: The sys schema is already up to date (version %s).

- Error number: [MY-013393](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_SYS\\_SCHEMA\\_OBJECT\\_COUNT](#); SQLSTATE: [HY000](#)

Message: Found %d sys %s, but expected %d. Re-installing the sys schema.

- Error number: [MY-013394](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_CHECKING\\_DB](#); SQLSTATE: [HY000](#)

Message: Checking '%s' schema.

- Error number: [MY-013395](#); Symbol: [ER\\_IB\\_MSG\\_DDL\\_LOG\\_DELETE\\_BY\\_ID\\_TMCT](#); SQLSTATE: [HY000](#)

Message: Too many concurrent transactions while clearing the DDL Log. Please increase the number of Rollback Segments.

- Error number: [MY-013396](#); Symbol: [ER\\_IB\\_MSG\\_POST\\_RECOVER\\_DDL\\_LOG\\_RECOVER](#); SQLSTATE: [HY000](#)

Message: Error in DDL Log recovery during Post-Recovery processing.

- 
- Error number: [MY-013397](#); Symbol: [ER\\_IB\\_MSG\\_POST\\_RECOVER\\_POST\\_TS\\_ENCRYPT](#); SQLSTATE: [HY000](#)  
Message: Error in Post-Tablespace-Encryption during Post-Recovery processing.
  - Error number: [MY-013398](#); Symbol: [ER\\_IB\\_MSG\\_DDL\\_LOG\\_FAIL\\_POST\\_DDL](#); SQLSTATE: [HY000](#)  
Message: Error in DLL Log cleanup during Post-DDL processing.
  - Error number: [MY-013399](#); Symbol: [ER\\_SERVER\\_BINLOG\\_UNSAFE\\_SYSTEM\\_FUNCTION](#); SQLSTATE: [HY000](#)  
Message: '%s' statement is unsafe because it uses a system function that may return a different value on the replica.
  - Error number: [MY-013400](#); Symbol: [ER\\_SERVER\\_UPGRADE\\_HELP\\_TABLE\\_STATUS](#); SQLSTATE: [HY000](#)  
Message: Upgrade of help tables %s.
  - Error number: [MY-013404](#); Symbol: [ER\\_BINLOG\\_UNABLE\\_TO\\_ROTATE\\_GTID\\_TABLE\\_READONLY](#); SQLSTATE: [HY000](#)  
Message: Unable to create a new binlog file: Table `mysql.gtid\_executed` couldn't be opened. %s
  - Error number: [MY-013405](#); Symbol: [ER\\_NETWORK\\_NAMESPACES\\_NOT\\_SUPPORTED](#); SQLSTATE: [HY000](#)  
Message: Network Namespaces is not supported on this platform
  - Error number: [MY-013406](#); Symbol: [ER\\_UNKNOWN\\_NETWORK\\_NAMESPACE](#); SQLSTATE: [HY000](#)  
Message: Unknown network namespace '%s'
  - Error number: [MY-013407](#); Symbol: [ER\\_NETWORK\\_NAMESPACE\\_NOT\\_ALLOWED\\_FOR\\_WILDCARD\\_ADDRESS](#); SQLSTATE: [HY000](#)  
Message: Network namespace not allowed for wildcard interface address
  - Error number: [MY-013408](#); Symbol: [ER\\_SETNS\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: setns() failed with error '%s'
  - Error number: [MY-013409](#); Symbol: [ER\\_WILDCARD\\_NOT\\_ALLOWED\\_FOR\\_MULTIADDRESS\\_BIND](#); SQLSTATE: [HY000](#)  
Message: Wildcard address value not allowed for multivalued bind address
  - Error number: [MY-013410](#); Symbol: [ER\\_NETWORK\\_NAMESPACE\\_FILE\\_PATH\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)  
Message: The path to a special network namespace file is too long. (got %u > max %u)
  - Error number: [MY-013411](#); Symbol: [ER\\_IB\\_MSG\\_TOO\\_LONG\\_PATH](#); SQLSTATE: [HY000](#)  
Message: Cannot create tablespace '%s'. The filepath is too long for this OS.
  - Error number: [MY-013412](#); Symbol: [ER\\_IB\\_RECV\\_FIRST\\_REC\\_GROUP\\_INVALID](#); SQLSTATE: [HY000](#)  
Message: The last block of redo had corrupted first\_rec\_group and became fixed (%u -> %u).
  - Error number: [MY-013413](#); Symbol: [ER\\_DD\\_UPGRADE\\_COMPLETED](#); SQLSTATE: [HY000](#)

---

Message: Data dictionary upgrade from version '%u' to '%u' completed.

- Error number: [MY-013415](#); Symbol: [ER\\_PERSIST\\_OPTION\\_USER\\_TRUNCATED](#); SQLSTATE: [HY000](#)

Message: Truncated a user name for %s that was too long while reading the persisted variables file

- Error number: [MY-013416](#); Symbol: [ER\\_PERSIST\\_OPTION\\_HOST\\_TRUNCATED](#); SQLSTATE: [HY000](#)

Message: Truncated a host name for %s that was too long while reading the persisted variables file

- Error number: [MY-013417](#); Symbol: [ER\\_NET\\_WAIT\\_ERROR](#); SQLSTATE: [HY000](#)

Message: The wait\_timeout period was exceeded, the idle time since last command was too long.

- Error number: [MY-013418](#); Symbol: [ER\\_IB\\_MSG\\_1285](#); SQLSTATE: [HY000](#)

Message: '%s' found not encrypted while '%s' is ON. Trying to encrypt it now.

- Error number: [MY-013419](#); Symbol: [ER\\_IB\\_MSG\\_CLOCK\\_MONOTONIC\\_UNSUPPORTED](#); SQLSTATE: [HY000](#)

Message: CLOCK\_MONOTONIC is unsupported, so do not change the system time when MySQL is running !

- Error number: [MY-013420](#); Symbol: [ER\\_IB\\_MSG\\_CLOCK\\_GETTIME\\_FAILED](#); SQLSTATE: [HY000](#)

Message: clock\_gettime() failed: %s

- Error number: [MY-013421](#); Symbol: [ER\\_PLUGIN\\_NOT\\_EARLY\\_DUP](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' is not to be used as an "early" plugin. Don't add it to --early-plugin-load, keyring migration etc.

- Error number: [MY-013422](#); Symbol: [ER\\_PLUGIN\\_NO\\_INSTALL\\_DUP](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' is marked as not dynamically installable. You have to stop the server to install it.

- Error number: [MY-013425](#); Symbol: [ER\\_BINLOG\\_UNSAFE\\_DEFAULT\\_EXPRESSION\\_IN\\_SUBSTATEMENT](#); SQLSTATE: [HY000](#)

Message: The statement is unsafe because it invokes a trigger or a stored function that modifies a table that has a column with a DEFAULT expression that may return a different value on the replica.

- Error number: [MY-013426](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_VER\\_READ\\_COMPATIBLE](#); SQLSTATE: [HY000](#)

Message: Member version is read compatible with the group.

- Error number: [MY-013427](#); Symbol: [ER\\_LOCK\\_ORDER\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Lock order disabled (reason: init failed).

- Error number: [MY-013428](#); Symbol: [ER\\_AUDIT\\_LOG\\_KEYRING\\_ID\\_TIMESTAMP\\_VALUE\\_IS\\_INVALID](#); SQLSTATE: [HY000](#)

Message: Keyring ID timestamp value is invalid: '%s'

- Error number: [MY-013429](#); Symbol: [ER\\_AUDIT\\_LOG\\_FILE\\_NAME\\_TIMESTAMP\\_VALUE\\_IS\\_MISSING\\_OR\\_INVALID](#); SQLSTATE: [HY000](#)

---

Message: Cannot process audit log file. File name timestamp value is missing or invalid: '%s'

- Error number: MY-013430; Symbol: ER\_AUDIT\_LOG\_FILE\_NAME\_DOES\_NOT\_HAVE\_REQUIRED\_FORMAT; SQLSTATE: HY000

Message: Cannot process audit log file. File name does not have required format: '%s'

- Error number: MY-013431; Symbol: ER\_AUDIT\_LOG\_FILE\_NAME\_KEYRING\_ID\_VALUE\_IS\_MISSING; SQLSTATE: HY000

Message: Cannot process audit log file. File name keyring ID value is missing: '%s'

- Error number: MY-013432; Symbol: ER\_AUDIT\_LOG\_FILE\_HAS\_BEEN\_SUCCESSFULLY\_PROCESSED; SQLSTATE: HY000

Message: Audit log file has been successfully processed: '%s'

- Error number: MY-013433; Symbol: ER\_AUDIT\_LOG\_COULD\_NOT\_OPEN\_FILE\_FOR\_READING; SQLSTATE: HY000

Message: Could not open audit log file for reading: '%s'

- Error number: MY-013434; Symbol: ER\_AUDIT\_LOG\_INVALID\_FILE\_CONTENT; SQLSTATE: HY000

Message: Invalid audit log file content: '%s'

- Error number: MY-013435; Symbol: ER\_AUDIT\_LOG\_CANNOT\_READ\_PASSWORD; SQLSTATE: HY000

Message: Cannot read password: '%s'.

- Error number: MY-013436; Symbol: ER\_AUDIT\_LOG\_CANNOT\_STORE\_PASSWORD; SQLSTATE: HY000

Message: Cannot store password: '%s'.

- Error number: MY-013437; Symbol: ER\_AUDIT\_LOG\_CANNOT\_REMOVE\_PASSWORD; SQLSTATE: HY000

Message: Cannot remove password: '%s'.

- Error number: MY-013438; Symbol: ER\_AUDIT\_LOG\_PASSWORD\_HAS\_BEEN\_COPIED; SQLSTATE: HY000

Message: 'audit\_log' password has been copied into '%s' and will be removed with first purged password.

- Error number: MY-013447; Symbol: ER\_LDAP\_EMPTY\_USERDN\_PASSWORD; SQLSTATE: HY000

Message: Empty user dn or password is not allowed, not attempting LDAP bind.

- Error number: MY-013449; Symbol: ER\_ACL\_WRONG\_OR\_MISSING\_ACL\_TABLES\_LOG; SQLSTATE: HY000

Message: The current layout of the ACL tables does not conform to the server's expected layout. They're either altered, missing or not upgraded from a previous version. However a best effort attempt to read data from these tables will still be made.

- Error number: MY-013450; Symbol: ER\_LOCK\_ORDER\_FAILED\_WRITE\_FILE; SQLSTATE: HY000

Message: LOCK\_ORDER: Failed to write to file <%s>.



- 
- Error number: [MY-013451](#); Symbol: [ER\\_LOCK\\_ORDER\\_FAILED\\_READ\\_FILE](#); SQLSTATE: [HY000](#)  
Message: LOCK\_ORDER: Failed to read from file <%s>.
  - Error number: [MY-013452](#); Symbol: [ER\\_LOCK\\_ORDER\\_MESSAGE](#); SQLSTATE: [HY000](#)  
Message: LOCK\_ORDER message: %s
  - Error number: [MY-013453](#); Symbol: [ER\\_LOCK\\_ORDER\\_DEPENDENCIES\\_SYNTAX](#); SQLSTATE: [HY000](#)  
Message: Lock order dependencies file <%s> (%d:%d) - (%d:%d) : %s
  - Error number: [MY-013454](#); Symbol: [ER\\_LOCK\\_ORDER\\_SCANNER\\_SYNTAX](#); SQLSTATE: [HY000](#)  
Message: Lock order scanner: (%d:%d) - (%d:%d) : %s
  - Error number: [MY-013455](#); Symbol: [ER\\_DATA\\_DIRECTORY\\_UNUSABLE\\_DELETABLE](#); SQLSTATE: [HY000](#)  
Message: The newly created data directory %s by --initialize is unusable. You can remove it.
  - Error number: [MY-013456](#); Symbol: [ER\\_IB\\_MSG\\_BTREE\\_LEVEL\\_LIMIT\\_EXCEEDED](#); SQLSTATE: [HY000](#)  
Message: No. of B-tree level created for index %s has crossed the permissible limit. If debug option innodb\_limit\_optimistic\_insert\_debug is being used try tweaking it to include more records in a page.
  - Error number: [MY-013457](#); Symbol: [ER\\_IB\\_CLONE\\_START\\_STOP](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013458](#); Symbol: [ER\\_IB\\_CLONE\\_OPERATION](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013459](#); Symbol: [ER\\_IB\\_CLONE\\_RESTART](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013460](#); Symbol: [ER\\_IB\\_CLONE\\_USER\\_DATA](#); SQLSTATE: [HY000](#)  
Message: Clone removing all user data for provisioning: %s
  - Error number: [MY-013461](#); Symbol: [ER\\_IB\\_CLONE\\_NON\\_INNO\\_DB\\_TABLE](#); SQLSTATE: [HY000](#)  
Message: Non innodb table: %s.%s is not cloned and is empty.
  - Error number: [MY-013462](#); Symbol: [ER\\_CLONE\\_SHUTDOWN\\_TRACE](#); SQLSTATE: [HY000](#)  
Message: Clone shutting down server as RESTART failed. Please start server to complete clone operation.
  - Error number: [MY-013463](#); Symbol: [ER\\_GRP\\_RPL\\_GTID\\_PURGED\\_EXTRACT\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Error when extracting this member GTID purged set. Operations and checks made to group joiners may be incomplete.
  - Error number: [MY-013464](#); Symbol: [ER\\_GRP\\_RPL\\_CLONE\\_PROCESS\\_PREPARE\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: There was an issue when configuring the remote cloning process: %s
-

- 
- Error number: `MY-013465`; Symbol: `ER_GRP_RPL_CLONE_PROCESS_EXEC_ERROR`; SQLSTATE: `HY000`  
Message: There was an issue when cloning from another server: %s
  - Error number: `MY-013466`; Symbol: `ER_GRP_RPL_RECOVERY_EVAL_ERROR`; SQLSTATE: `HY000`  
Message: There was an issue when trying to evaluate the best distributed recovery strategy while joining.%s
  - Error number: `MY-013467`; Symbol: `ER_GRP_RPL_NO_POSSIBLE_RECOVERY`; SQLSTATE: `HY000`  
Message: No valid or ONLINE members exist to get the missing data from the group. For cloning check if donors of the same version and with clone plugin installed exist. For incremental recovery check if you have donors where the required data was not purged from the binary logs.
  - Error number: `MY-013468`; Symbol: `ER_GRP_RPL_CANT_KILL_THREAD`; SQLSTATE: `HY000`  
Message: The group replication plugin could not kill the plugin routine for %s. %s
  - Error number: `MY-013469`; Symbol: `ER_GRP_RPL_RECOVERY_STRAT_CLONE_THRESHOLD`; SQLSTATE: `HY000`  
Message: This member will start distributed recovery using clone. It is due to the number of missing transactions being higher than the configured threshold of %llu.
  - Error number: `MY-013470`; Symbol: `ER_GRP_RPL_RECOVERY_STRAT_CLONE_PURGED`; SQLSTATE: `HY000`  
Message: This member will start distributed recovery using clone. It is due to no ONLINE member has the missing data for recovering in its binary logs.
  - Error number: `MY-013471`; Symbol: `ER_GRP_RPL_RECOVERY_STRAT_CHOICE`; SQLSTATE: `HY000`  
Message: Distributed recovery will transfer data using: %s
  - Error number: `MY-013472`; Symbol: `ER_GRP_RPL_RECOVERY_STRAT_FALLBACK`; SQLSTATE: `HY000`  
Message: Due to some issue on the previous step distributed recovery is now executing: %s
  - Error number: `MY-013473`; Symbol: `ER_GRP_RPL_RECOVERY_STRAT_NO_FALLBACK`; SQLSTATE: `HY000`  
Message: Due to a critical cloning error or lack of donors, distributed recovery cannot be executed. The member will now leave the group.
  - Error number: `MY-013474`; Symbol: `ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_CLONE`; SQLSTATE: `HY000`  
Message: The '%s' thread of channel '%s' will error out as the server will attempt to clone another server
  - Error number: `MY-013475`; Symbol: `ER_UNKNOWN_TABLE_IN_UPGRADE`; SQLSTATE: `HY000`  
Message: Unknown table '%s'
  - Error number: `MY-013476`; Symbol: `ER_IDENT_CAUSES_TOO_LONG_PATH_IN_UPGRADE`; SQLSTATE: `HY000`  
Message: Long database name and identifier for object resulted in path length exceeding %d characters. Path: '%s'.

- 
- Error number: [MY-013477](#); Symbol: [ER\\_XA\\_CANT\\_CREATE\\_MDL\\_BACKUP](#); SQLSTATE: [HY000](#)

Message: XA: Failed to take MDL Lock backup of PREPARED XA transaction during client disconnect.
  - Error number: [MY-013478](#); Symbol: [ER\\_AUDIT\\_LOG\\_SUPER\\_PRIVILEGE\\_REQUIRED](#); SQLSTATE: [HY000](#)

Message: SUPER privilege or AUDIT\_ADMIN role required for '%s'@'%s' user.
  - Error number: [MY-013479](#); Symbol: [ER\\_AUDIT\\_LOG\\_UDF\\_INVALID\\_ARGUMENT\\_TYPE](#); SQLSTATE: [HY000](#)

Message: Invalid argument type
  - Error number: [MY-013480](#); Symbol: [ER\\_AUDIT\\_LOG\\_UDF\\_INVALID\\_ARGUMENT\\_COUNT](#); SQLSTATE: [HY000](#)

Message: Invalid argument count
  - Error number: [MY-013481](#); Symbol: [ER\\_AUDIT\\_LOG\\_HAS\\_NOT\\_BEEN\\_INSTALLED](#); SQLSTATE: [HY000](#)

Message: audit\_log plugin has not been installed using INSTALL PLUGIN syntax.
  - Error number: [MY-013482](#); Symbol: [ER\\_AUDIT\\_LOG\\_UDF\\_READ\\_INVALID\\_MAX\\_ARRAY\\_LENGTH\\_ARG\\_TYPE](#); SQLSTATE: [HY000](#)

Message: Invalid "max\_array\_length" argument type.
  - Error number: [MY-013483](#); Symbol: [ER\\_LOG\\_CANNOT\\_WRITE\\_EXTENDED](#); SQLSTATE: [HY000](#)

Message: Failed to write to %s: %s (%s)
  - Error number: [MY-013485](#); Symbol: [ER\\_KEYRING\\_AWS\\_INCORRECT\\_PROXY](#); SQLSTATE: [HY000](#)

Message: Incorrect environment variable %s, invalid port: %s
  - Error number: [MY-013486](#); Symbol: [ER\\_GRP\\_RPL\\_SERVER\\_SET\\_TO\\_OFFLINE\\_MODE\\_DUE\\_TO\\_ERRORS](#); SQLSTATE: [HY000](#)

Message: The server was automatically set into offline mode after an error was detected.
  - Error number: [MY-013487](#); Symbol: [ER\\_GRP\\_RPL\\_MESSAGE\\_SERVICE\\_FATAL\\_ERROR](#); SQLSTATE: [HY000](#)

Message: A message sent through the Group Replication message deliver service was not delivered successfully. The server will now leave the group. Try to add the server back to the group and check if the problem persists, or check previous messages in the log for hints of what could be the problem.
  - Error number: [MY-013488](#); Symbol: [ER\\_WARN\\_WRONG\\_COMPRESSION\\_ALGORITHM\\_LOG](#); SQLSTATE: [HY000](#)

Message: Invalid SOURCE\_COMPRESSION\_ALGORITHMS '%s' found in repository for channel '%s'. Resetting to 'uncompressed' (no compression).
  - Error number: [MY-013489](#); Symbol: [ER\\_WARN\\_WRONG\\_COMPRESSION\\_LEVEL\\_LOG](#); SQLSTATE: [HY000](#)

Message: Invalid SOURCE\_ZSTD\_COMPRESSION\_LEVEL found in repository for channel '%s'. Resetting to %u.
  - Error number: [MY-013490](#); Symbol: [ER\\_PROTOCOL\\_COMPRESSION\\_RESET\\_LOG](#); SQLSTATE: [HY000](#)
-

---

Message: Option --protocol-compression-algorithms is reset to default value.

- Error number: [MY-013491](#); Symbol: [ER\\_XPLUGIN\\_COMPRESSION\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Fatal error while compressing outgoing data - %s

- Error number: [MY-013492](#); Symbol: [ER\\_MYSQLBACKUP\\_MSG](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013493](#); Symbol: [ER\\_WARN\\_UNKNOWN\\_KEYRING\\_AWS\\_REGION](#); SQLSTATE: [HY000](#)

Message: Unknown keyring\_aws\_region '%s'. Connection to AWS KMS may fail.

- Error number: [MY-013494](#); Symbol: [ER\\_WARN\\_LOG\\_PRIVILEGE\\_CHECKS\\_USER\\_DOES\\_NOT\\_EXIST](#); SQLSTATE: [HY000](#)

Message: PRIVILEGE\_CHECKS\_USER for replication channel '%s' was set to '%s`@`%s`', but this is not an existing user. Correct this before starting replication threads.

- Error number: [MY-013495](#); Symbol: [ER\\_WARN\\_LOG\\_PRIVILEGE\\_CHECKS\\_USER\\_CORRUPT](#); SQLSTATE: [HY000](#)

Message: Invalid, corrupted PRIVILEGE\_CHECKS\_USER was found in the replication configuration repository for channel '%s'. Use CHANGE REPLICATION SOURCE TO PRIVILEGE\_CHECKS\_USER to correct the configuration.

- Error number: [MY-013496](#); Symbol: [ER\\_WARN\\_LOG\\_PRIVILEGE\\_CHECKS\\_USER\\_NEEDS\\_RPL\\_APPLIER\\_PRIV](#); SQLSTATE: [HY000](#)

Message: PRIVILEGE\_CHECKS\_USER for replication channel '%s' was set to '%s`@`%s`', but this user does not have REPLICATION\_APPLIER privilege. Correct this before starting the replication threads.

- Error number: [MY-013497](#); Symbol: [ER\\_OBSOLETE\\_FILE\\_PRIVILEGE\\_FOR\\_REPLICATION\\_CHECKS](#); SQLSTATE: [HY000](#)

Message: The PRIVILEGE\_CHECKS\_USER for channel '%s' would need FILE privilege to execute a LOAD DATA INFILE statement replicated in statement format. Consider using binlog\_format=ROW on source. If the replicated events are trusted, recover from the failure by temporarily granting FILE to the PRIVILEGE\_CHECKS\_USER.

- Error number: [MY-013498](#); Symbol: [ER\\_RPL\\_REPLICA\\_SQL\\_THREAD\\_STARTING\\_WITH\\_PRIVILEGE\\_CHECKS](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread%s initialized, starting replication in log '%s' at position %s, relay log '%s' position: %s, user: '%s`@`%s`, roles: %s

- Error number: [MY-013499](#); Symbol: [ER\\_AUDIT\\_LOG\\_CANNOT\\_GENERATE\\_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Cannot generate password: '%s'

- Error number: [MY-013500](#); Symbol: [ER\\_INIT\\_FAILED\\_TO\\_GENERATE\\_ROOT\\_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Failed to generate a random password for root. Probably not enough entropy.

- Error number: [MY-013501](#); Symbol: [ER\\_PLUGIN\\_LOAD\\_OPTIONS\\_IGNORED](#); SQLSTATE: [HY000](#)

Message: Ignoring --plugin-load[\_add] list as the server is running with --initialize(-insecure).

- Error number: [MY-013502](#); Symbol: [ER\\_WARN\\_AUTH\\_ID\\_WITH\\_SYSTEM\\_USER\\_PRIV\\_IN\\_MANDATORY\\_ROLES](#); SQLSTATE: HY000

Message: Cannot set mandatory\_roles: AuthId `'%s`@`'%s`' has '%s' privilege. AuthId(s) set in the mandatory\_roles are ignored.
- Error number: [MY-013503](#); Symbol: [ER\\_IB\\_MSG\\_SKIP\\_HIDDEN\\_DIR](#); SQLSTATE: HY000

Message: Directory '%s' will not be scanned because it is a hidden directory.
- Error number: [MY-013504](#); Symbol: [ER\\_WARN\\_RPL\\_RECOVERY\\_NO\\_ROTATE\\_EVENT\\_FROM\\_SOURCE\\_EOF](#); SQLSTATE: HY000

Message: Server was not able to find a rotate event from source server to initialize relay log recovery for channel '%s'. Skipping relay log recovery for the channel.
- Error number: [MY-013505](#); Symbol: [ER\\_IB\\_LOB\\_ROLLBACK\\_INDEX\\_LEN](#); SQLSTATE: HY000

Message: Rolling back LOB for transaction %llu undo number %llu : current index length %llu. (iteration %llu)
- Error number: [MY-013506](#); Symbol: [ER\\_CANT\\_PROCESS\\_EXPRESSION\\_FOR\\_GENERATED\\_COLUMN\\_TO\\_DD](#); SQLSTATE: HY000

Message: Error in processing (possibly deprecated) expression or function '%s' for generated column %s.%s.%s
- Error number: [MY-013507](#); Symbol: [ER\\_RPL\\_REPLICA\\_QUEUE\\_EVENT\\_FAILED\\_INVALID\\_NON\\_ROW\\_FORMAT](#); SQLSTATE: HY000

Message: The queue event failed for channel '%s' as an invalid event according to REQUIRE\_ROW\_FORMAT was found.
- Error number: [MY-013508](#); Symbol: [ER\\_OBSOLETE\\_REQUIRE\\_ROW\\_FORMAT\\_VIOLATION](#); SQLSTATE: HY000

Message: The application of relay events failed for channel '%s' as an invalid event according to REQUIRE\_ROW\_FORMAT was found.
- Error number: [MY-013509](#); Symbol: [ER\\_LOG\\_PRIV\\_CHECKS\\_REQUIRE\\_ROW\\_FORMAT\\_NOT\\_SET](#); SQLSTATE: HY000

Message: PRIVILEGE\_CHECKS\_USER for replication channel '%s' can't be set to `'%s`@`'%s`' unless REQUIRE\_ROW\_FORMAT is also set to %d.
- Error number: [MY-013510](#); Symbol: [ER\\_RPL\\_REPLICA\\_SQL\\_THREAD\\_DETECTED\\_UNEXPECTED\\_EVENT\\_SEQUENCE](#); SQLSTATE: HY000

Message: An unexpected event sequence was detected by the SQL thread while applying an event.
- Error number: [MY-013511](#); Symbol: [ER\\_IB\\_MSG\\_UPGRADE\\_PARTITION\\_FILE](#); SQLSTATE: HY000

Message: Updating partition file name '%s' to '%s' and all other partition files during upgrade
- Error number: [MY-013512](#); Symbol: [ER\\_IB\\_MSG\\_DOWNGRADE\\_PARTITION\\_FILE](#); SQLSTATE: HY000

Message: Updating partition file name '%s' to '%s' and all other partition files during downgrade
- Error number: [MY-013513](#); Symbol: [ER\\_IB\\_MSG\\_UPGRADE\\_PARTITION\\_FILE\\_IMPORT](#); SQLSTATE: HY000

---

Message: Updating partition file name '%s' to '%s' for import

- Error number: [MY-013514](#); Symbol: [ER\\_IB\\_WARN\\_OPEN\\_PARTITION\\_FILE](#); SQLSTATE: [HY000](#)

Message: Unable to open partition file with new name '%s'. Please check if innodb\_directories is set to include all external file paths

- Error number: [MY-013515](#); Symbol: [ER\\_IB\\_MSG\\_FIL\\_STATE\\_MOVED\\_CORRECTED](#); SQLSTATE: [HY000](#)

Message: %s DD ID: %llu - Partition tablespace %u, name '%s' is corrected to '%s'

- Error number: [MY-013516](#); Symbol: [ER\\_IB\\_MSG\\_FIL\\_STATE\\_MOVED\\_CHANGED\\_PATH](#); SQLSTATE: [HY000](#)

Message: %s DD ID: %llu - Tablespace %u, name '%s', '%s' is moved to '%s'

- Error number: [MY-013517](#); Symbol: [ER\\_IB\\_MSG\\_FIL\\_STATE\\_MOVED\\_CHANGED\\_NAME](#); SQLSTATE: [HY000](#)

Message: %s DD ID: %llu - Partition tablespace %u, name '%s', '%s' is updated to '%s'

- Error number: [MY-013518](#); Symbol: [ER\\_IB\\_MSG\\_FIL\\_STATE\\_MOVED\\_TOO\\_MANY](#); SQLSTATE: [HY000](#)

Message: %s Too many files have been moved, disabling logging of detailed messages

- Error number: [MY-013519](#); Symbol: [ER\\_GR\\_ELECTED\\_PRIMARY\\_GTID\\_INFORMATION](#); SQLSTATE: [HY000](#)

Message: Elected primary member %s: %s

- Error number: [MY-013520](#); Symbol: [ER\\_SCHEMA\\_NAME\\_IN\\_UPPER\\_CASE\\_NOT\\_ALLOWED](#); SQLSTATE: [HY000](#)

Message: Schema name '%s' containing upper case characters is not allowed with lower\_case\_table\_names = 1.

- Error number: [MY-013521](#); Symbol: [ER\\_TABLE\\_NAME\\_IN\\_UPPER\\_CASE\\_NOT\\_ALLOWED](#); SQLSTATE: [HY000](#)

Message: Table name '%s.%s' containing upper case characters is not allowed with lower\_case\_table\_names = 1.

- Error number: [MY-013522](#); Symbol: [ER\\_SCHEMA\\_NAME\\_IN\\_UPPER\\_CASE\\_NOT\\_ALLOWED\\_FOR\\_FK](#); SQLSTATE: [HY000](#)

Message: Schema name '%s' containing upper case characters, used by foreign key '%s' in table '%s.%s', is not allowed with lower\_case\_table\_names = 1.

- Error number: [MY-013523](#); Symbol: [ER\\_TABLE\\_NAME\\_IN\\_UPPER\\_CASE\\_NOT\\_ALLOWED\\_FOR\\_FK](#); SQLSTATE: [HY000](#)

Message: Table name '%s.%s' containing upper case characters, used by foreign key '%s' in table '%s.%s', is not allowed with lower\_case\_table\_names = 1.

- Error number: [MY-013524](#); Symbol: [ER\\_IB\\_MSG\\_DICT\\_PARTITION\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)

Message: Table Partition: %s is not found in InnoDB dictionary

- Error number: [MY-013525](#); Symbol: [ER\\_ACCESS\\_DENIED\\_FOR\\_USER\\_ACCOUNT\\_BLOCKED\\_BY\\_PASSWORD\\_LOCK](#); SQLSTATE: [HY000](#)

---

Message: Access denied for user '%s'@'%s'. Account is blocked for %s day(s) (%s day(s) remaining) due to %u consecutive failed logins. Use FLUSH PRIVILEGES or ALTER USER to reset.

- Error number: [MY-013526](#); Symbol: [ER\\_INNODB\\_OUT\\_OF\\_RESOURCES](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013527](#); Symbol: [ER\\_DD\\_UPGRADE\\_FOUND\\_PREPARED\\_XA\\_TRANSACTION](#); SQLSTATE: [HY000](#)

Message: Upgrade cannot proceed due to an existing prepared XA transaction.

- Error number: [MY-013528](#); Symbol: [ER\\_MIGRATE\\_TABLE\\_TO\\_DD\\_OOM](#); SQLSTATE: [HY000](#)

Message: Could not allocate memory for key\_info when migrating table %s.%s

- Error number: [MY-013529](#); Symbol: [ER\\_RPL\\_RELAY\\_LOG\\_RECOVERY\\_INFO\\_AFTER\\_CLONE](#); SQLSTATE: [HY000](#)

Message: Applier metadata information for channel '%s' was found after a clone operation. Relay log recovery will be executed to adjust positions and file information for this new server. Should that automatic procedure fail please adjust the positions through 'CHANGE REPLICATION SOURCE TO'

- Error number: [MY-013530](#); Symbol: [ER\\_IB\\_MSG\\_57\\_UNDO\\_SPACE\\_DELETE\\_FAIL](#); SQLSTATE: [HY000](#)

Message: Failed to delete 5.7 undo tablespace: %s during upgrade

- Error number: [MY-013531](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1285](#); SQLSTATE: [HY000](#)

Message: Empty doublewrite file: %s

- Error number: [MY-013532](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1286](#); SQLSTATE: [HY000](#)

Message: Using '%s' for doublewrite

- Error number: [MY-013533](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1287](#); SQLSTATE: [HY000](#)

Message: Error reading doublewrite buffer from the system tablespace

- Error number: [MY-013534](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1288](#); SQLSTATE: [HY000](#)

Message: Cannot create doublewrite buffer: you must increase your buffer pool size. Cannot continue operation.

- Error number: [MY-013535](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1290](#); SQLSTATE: [HY000](#)

Message: The page in the doublewrite file is corrupt. Cannot continue operation. You can try to recover the database with innodb\_force\_recovery=6

- Error number: [MY-013536](#); Symbol: [ER\\_IB\\_MSG\\_BAD\\_DBLWR\\_FILE\\_NAME](#); SQLSTATE: [HY000](#)

Message: The doublewrite filename '%s' is incorrect.

- Error number: [MY-013538](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1293](#); SQLSTATE: [HY000](#)

Message: Doublewrite file create failed: %s

- Error number: [MY-013539](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1294](#); SQLSTATE: [HY000](#)

Message: DBLWRThread: pthread\_setaffinity() failed!

- Error number: [MY-013540](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1295](#); SQLSTATE: [HY000](#)

---

Message: %s

- Error number: MY-013541; Symbol: ER\_IB\_MSG\_DBLWR\_1296; SQLSTATE: HY000

Message: %s

- Error number: MY-013542; Symbol: ER\_IB\_MSG\_DBLWR\_1297; SQLSTATE: HY000

Message: Doublewrite file read failed: %s

- Error number: MY-013543; Symbol: ER\_IB\_MSG\_DBLWR\_1298; SQLSTATE: HY000

Message: Dump of the data file page:

- Error number: MY-013544; Symbol: ER\_IB\_MSG\_DBLWR\_1300; SQLSTATE: HY000

Message: %s

- Error number: MY-013545; Symbol: ER\_IB\_MSG\_DBLWR\_1301; SQLSTATE: HY000

Message: %s

- Error number: MY-013546; Symbol: ER\_IB\_MSG\_DBLWR\_1304; SQLSTATE: HY000

Message: %s

- Error number: MY-013547; Symbol: ER\_IB\_MSG\_DBLWR\_1305; SQLSTATE: HY000

Message: %s

- Error number: MY-013548; Symbol: ER\_IB\_MSG\_DBLWR\_1306; SQLSTATE: HY000

Message: %s

- Error number: MY-013549; Symbol: ER\_IB\_MSG\_DBLWR\_1307; SQLSTATE: HY000

Message: %s

- Error number: MY-013550; Symbol: ER\_IB\_MSG\_DBLWR\_1308; SQLSTATE: HY000

Message: %s

- Error number: MY-013551; Symbol: ER\_IB\_MSG\_DBLWR\_1309; SQLSTATE: HY000

Message: %s

- Error number: MY-013552; Symbol: ER\_IB\_MSG\_DBLWR\_1310; SQLSTATE: HY000

Message: %s

- Error number: MY-013553; Symbol: ER\_IB\_MSG\_DBLWR\_1311; SQLSTATE: HY000

Message: %s

- Error number: MY-013554; Symbol: ER\_IB\_MSG\_DBLWR\_1312; SQLSTATE: HY000

Message: %s

- Error number: MY-013555; Symbol: ER\_IB\_MSG\_DBLWR\_1313; SQLSTATE: HY000

Message: %s

- Error number: MY-013556; Symbol: ER\_IB\_MSG\_DBLWR\_1314; SQLSTATE: HY000



---

Message: %s

- Error number: [MY-013557](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1315](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013558](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1316](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013559](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1317](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013560](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1318](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013561](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_LOAD\\_WRONG\\_SIZE](#); SQLSTATE: [HY000](#)

Message: Doublewrite load file %s size %llu is not a multiple of the configured page size %zu

- Error number: [MY-013562](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1320](#); SQLSTATE: [HY000](#)

Message: Doublewrite file %s truncate failed

- Error number: [MY-013563](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1321](#); SQLSTATE: [HY000](#)

Message: Doublewrite file %s failed to writ zeros

- Error number: [MY-013564](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_OPEN\\_OR\\_CREATE\\_WRONG\\_SIZE](#); SQLSTATE: [HY000](#)

Message: Doublewrite open or create file %s size %llu is not a multiple of the configured page size %zu

- Error number: [MY-013565](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1323](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013566](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1324](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013567](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1325](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013568](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1326](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013569](#); Symbol: [ER\\_IB\\_MSG\\_DBLWR\\_1327](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013570](#); Symbol: [ER\\_IB\\_MSG\\_GTID\\_FLUSH\\_AT\\_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: Could not flush all GTIDs during slow shutdown. Will recover GTIDs when server restarts.

- Error number: [MY-013571](#); Symbol: [ER\\_IB\\_MSG\\_57\\_STAT\\_SPACE\\_DELETE\\_FAIL](#); SQLSTATE: [HY000](#)

---

Message: Failed to delete 5.7 stat tablespace: %s during upgrade

- Error number: [MY-013572](#); Symbol: [ER\\_NDBINFO\\_UPGRADING\\_SCHEMA](#); SQLSTATE: [HY000](#)

Message: Installing ndbinfo schema version %s

- Error number: [MY-013573](#); Symbol: [ER\\_NDBINFO\\_NOT\\_UPGRADING\\_SCHEMA](#); SQLSTATE: [HY000](#)

Message: Installed ndbinfo schema is current. Not upgrading.

- Error number: [MY-013574](#); Symbol: [ER\\_NDBINFO\\_UPGRADING\\_SCHEMA\\_FAIL](#); SQLSTATE: [HY000](#)

Message: Failed to upgrade ndbinfo schema.

- Error number: [MY-013576](#); Symbol: [ER\\_IB\\_MSG\\_INNODB\\_START\\_INITIALIZE](#); SQLSTATE: [HY000](#)

Message: InnoDB initialization has started.

- Error number: [MY-013577](#); Symbol: [ER\\_IB\\_MSG\\_INNODB\\_END\\_INITIALIZE](#); SQLSTATE: [HY000](#)

Message: InnoDB initialization has ended.

- Error number: [MY-013578](#); Symbol: [ER\\_IB\\_MSG\\_PAGE\\_ARCH\\_NO\\_RESET\\_POINTS](#); SQLSTATE: [HY000](#)

Message: Could not find appropriate reset points.

- Error number: [MY-013579](#); Symbol: [ER\\_IB\\_WRN\\_PAGE\\_ARCH\\_FLUSH\\_DATA](#); SQLSTATE: [HY000](#)

Message: Unable to flush. Page archiving data may be corrupt in case of a crash.

- Error number: [MY-013580](#); Symbol: [ER\\_IB\\_ERR\\_PAGE\\_ARCH\\_INVALID\\_DOUBLE\\_WRITE\\_BUF](#); SQLSTATE: [HY000](#)

Message: Page archiver's doublewrite buffer for %ld is not valid.

- Error number: [MY-013581](#); Symbol: [ER\\_IB\\_ERR\\_PAGE\\_ARCH\\_RECOVERY\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Page archiver system's recovery failed.

- Error number: [MY-013582](#); Symbol: [ER\\_IB\\_ERR\\_PAGE\\_ARCH\\_INVALID\\_FORMAT](#); SQLSTATE: [HY000](#)

Message: Invalid archived file name format. The archived file is supposed to have the format %s + [0-9]\*.

- Error number: [MY-013583](#); Symbol: [ER\\_INVALID\\_XPLUGIN\\_SOCKET\\_SAME\\_AS\\_SERVER](#); SQLSTATE: [HY000](#)

Message: X Plugins UNIX socket must use different file than MySQL server. X Plugin won't be accessible through UNIX socket

- Error number: [MY-013584](#); Symbol: [ER\\_INNODB\\_UNABLE\\_TO\\_ACQUIRE\\_DD\\_OBJECT](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013585](#); Symbol: [ER\\_WARN\\_LOG\\_DEPRECATED\\_PARTITION\\_PREFIX\\_KEY](#); SQLSTATE: [HY000](#)

---

Message: Column '%s.%s.%s' having prefix key part '%s(%u)' is ignored by the partitioning function. Use of prefixed columns in the PARTITION BY KEY() clause is deprecated and will be removed in a future release.

- Error number: [MY-013586](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_TOO\\_OFTEN](#); SQLSTATE: [HY000](#)

Message: Undo Truncation is occurring too often. Consider increasing --innodb-max-undo-log-size.

- Error number: [MY-013587](#); Symbol: [ER\\_GRP\\_RPL\\_IS\\_STARTING](#); SQLSTATE: [HY000](#)

Message: Plugin 'group\_replication' is starting.

- Error number: [MY-013588](#); Symbol: [ER\\_IB\\_MSG\\_INVALID\\_LOCATION\\_FOR\\_TABLESPACE](#); SQLSTATE: [HY000](#)

Message: Cannot create tablespace %s because the directory is not a valid location. %s

- Error number: [MY-013589](#); Symbol: [ER\\_IB\\_MSG\\_INVALID\\_LOCATION\\_WRONG\\_DB](#); SQLSTATE: [HY000](#)

Message: Scanned file '%s' for tablespace %s cannot be opened because it is not in a sub-directory named for the schema.

- Error number: [MY-013590](#); Symbol: [ER\\_IB\\_MSG\\_CANNOT\\_FIND\\_DD\\_UNDO\\_SPACE](#); SQLSTATE: [HY000](#)

Message: Cannot find undo tablespace %s with filename '%s' as indicated by the Data Dictionary. Did you move or delete this tablespace? Any undo logs in it cannot be used.

- Error number: [MY-013591](#); Symbol: [ER\\_GRP\\_RPL\\_RECOVERY\\_ENDPOINT\\_FORMAT](#); SQLSTATE: [HY000](#)

Message: Invalid input value for recovery socket endpoints '%s'. Please, provide a valid, comma separated, list of endpoints (IP:port).

- Error number: [MY-013592](#); Symbol: [ER\\_GRP\\_RPL\\_RECOVERY\\_ENDPOINT\\_INVALID](#); SQLSTATE: [HY000](#)

Message: The server is not listening on endpoint '%s'. Only endpoints that the server is listening on are valid recovery endpoints.

- Error number: [MY-013593](#); Symbol: [ER\\_GRP\\_RPL\\_RECOVERY\\_ENDPOINT\\_INVALID\\_DONOR\\_ENDPOINT](#); SQLSTATE: [HY000](#)

Message: Received invalid recovery endpoints configuration from donor. This member is not a valid donor for recovery, so it will be skipped.

- Error number: [MY-013594](#); Symbol: [ER\\_GRP\\_RPL\\_RECOVERY\\_ENDPOINT\\_INTERFACES\\_IPS](#); SQLSTATE: [HY000](#)

Message: Failed to retrieve IP addresses from enabled host network interfaces.

- Error number: [MY-013595](#); Symbol: [ER\\_WARN\\_TLS\\_CHANNEL\\_INITIALIZATION\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Failed to initialize TLS for channel: %s. See below for the description of exact issue.

- Error number: [MY-013596](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_VALIDATE\\_ADDRESS](#); SQLSTATE: [HY000](#)

Message: Validation of value '%s' set to `Mysqlx\_bind\_address` failed: %s. Skipping this value.

- 
- Error number: [MY-013597](#); Symbol: [ER\\_XPLUGIN\\_FAILED\\_TO\\_BIND\\_INTERFACE\\_ADDRESS](#); SQLSTATE: [HY000](#)  
Message: Value '%s' set to `MysqIx\_bind\_address`, X Plugin can't bind to it. Skipping this value.
  - Error number: [MY-013598](#); Symbol: [ER\\_IB\\_ERR\\_RECOVERY\\_REDO\\_DISABLED](#); SQLSTATE: [HY000](#)  
Message: Server was killed when InnoDB redo logging was disabled. Data files could be corrupt. You can try to restart the database with `innodb_force_recovery=6`
  - Error number: [MY-013599](#); Symbol: [ER\\_IB\\_WRN\\_FAST\\_SHUTDOWN\\_REDO\\_DISABLED](#); SQLSTATE: [HY000](#)  
Message: InnoDB cannot do cold shutdown 'innodb\_fast\_shutdown = 2' and is forcing 'innodb\_fast\_shutdown = 1' as redo logging is disabled. InnoDB would flush all dirty pages to ensure physical data consistency.
  - Error number: [MY-013600](#); Symbol: [ER\\_IB\\_WRN\\_REDO\\_DISABLED](#); SQLSTATE: [HY000](#)  
Message: InnoDB redo logging is disabled. All data could be lost in case of a server crash.
  - Error number: [MY-013601](#); Symbol: [ER\\_IB\\_WRN\\_REDO\\_ENABLED](#); SQLSTATE: [HY000](#)  
Message: InnoDB redo logging is enabled. Data is now safe and can be recovered in case of a server crash.
  - Error number: [MY-013602](#); Symbol: [ER\\_TLS\\_CONFIGURED\\_FOR\\_CHANNEL](#); SQLSTATE: [HY000](#)  
Message: Channel %s configured to support TLS. Encrypted connections are now supported for this channel.
  - Error number: [MY-013603](#); Symbol: [ER\\_TLS\\_CONFIGURATION\\_REUSED](#); SQLSTATE: [HY000](#)  
Message: No TLS configuration was given for channel %s; re-using TLS configuration of channel %s.
  - Error number: [MY-013604](#); Symbol: [ER\\_IB\\_TABLESPACE\\_PATH\\_VALIDATION\\_SKIPPED](#); SQLSTATE: [HY000](#)  
Message: Skipping InnoDB tablespace path validation. Manually moved tablespace files will not be detected!
  - Error number: [MY-013605](#); Symbol: [ER\\_IB\\_CANNOT\\_UPGRADE\\_WITH\\_DISCARDED\\_TABLESPACES](#); SQLSTATE: [HY000](#)  
Message: Upgrade failed because database contains discarded tablespaces.
  - Error number: [MY-013606](#); Symbol: [ER\\_USERNAME\\_TRUNCATED](#); SQLSTATE: [HY000](#)  
Message: The user name '%s' exceeds the maximum number of allowed characters %d and is truncated.
  - Error number: [MY-013607](#); Symbol: [ER\\_HOSTNAME\\_TRUNCATED](#); SQLSTATE: [HY000](#)  
Message: The host name '%s' exceeds the maximum number of allowed characters %d and is truncated.
  - Error number: [MY-013608](#); Symbol: [ER\\_IB\\_MSG\\_TRX\\_RECOVERY\\_ROLLBACK\\_NOT\\_COMPLETED](#); SQLSTATE: [HY000](#)  
Message: Rollback of non-prepared transactions not completed, due to fast shutdown

- 
- Error number: MY-013609; Symbol: ER\_AUTHCACHE\_ROLE\_EDGES\_IGNORED\_EMPTY\_NAME; SQLSTATE: HY000  
Message: Found an entry in the 'role\_edges' table with empty authorization ID; Skipped
  - Error number: MY-013610; Symbol: ER\_AUTHCACHE\_ROLE\_EDGES\_UNKNOWN\_AUTHORIZATION\_ID; SQLSTATE: HY000  
Message: Found an entry in the 'role\_edges' table with unknown authorization ID '%s'; Skipped
  - Error number: MY-013611; Symbol: ER\_AUTHCACHE\_DEFAULT\_ROLES\_IGNORED\_EMPTY\_NAME; SQLSTATE: HY000  
Message: Found an entry in the 'default\_roles' table with empty authorization ID; Skipped
  - Error number: MY-013612; Symbol: ER\_AUTHCACHE\_DEFAULT\_ROLES\_UNKNOWN\_AUTHORIZATION\_ID; SQLSTATE: HY000  
Message: Found an entry in the 'default\_roles' table with unknown authorization ID '%s'; Skipped
  - Error number: MY-013613; Symbol: ER\_IB\_ERR\_DDL\_LOG\_INSERT\_FAILURE; SQLSTATE: HY000  
Message: Couldn't insert entry in ddl log for ddl.
  - Error number: MY-013614; Symbol: ER\_IB\_LOCK\_VALIDATE\_LATCH\_ORDER\_VIOLATION; SQLSTATE: HY000  
Message: %s
  - Error number: MY-013615; Symbol: ER\_IB\_RELOCK\_LATCH\_ORDER\_VIOLATION; SQLSTATE: HY000  
Message: %s
  - Error number: MY-013621; Symbol: ER\_IB\_MSG\_1357; SQLSTATE: HY000  
Message: %s
  - Error number: MY-013622; Symbol: ER\_IB\_MSG\_1358; SQLSTATE: HY000  
Message: %s
  - Error number: MY-013623; Symbol: ER\_IB\_MSG\_1359; SQLSTATE: HY000  
Message: %s
  - Error number: MY-013624; Symbol: ER\_IB\_FAILED\_TO\_DELETE\_TABLESPACE\_FILE; SQLSTATE: HY000  
Message: %s
  - Error number: MY-013625; Symbol: ER\_IB\_UNABLE\_TO\_EXPAND\_TEMPORARY\_TABLESPACE\_POOL; SQLSTATE: HY000  
Message: %s
  - Error number: MY-013626; Symbol: ER\_IB\_TMP\_TABLESPACE\_CANNOT\_CREATE\_DIRECTORY; SQLSTATE: HY000  
Message: %s
  - Error number: MY-013627; Symbol: ER\_IB\_MSG\_SCANNING\_TEMP\_TABLESPACE\_DIR; SQLSTATE: HY000

---

Message: %s

- Error number: MY-013628; Symbol: ER\_IB\_ERR\_TEMP\_TABLESPACE\_DIR\_DOESNT\_EXIST; SQLSTATE: HY000

Message: %s

- Error number: MY-013629; Symbol: ER\_IB\_ERR\_TEMP\_TABLESPACE\_DIR\_EMPTY; SQLSTATE: HY000

Message: %s

- Error number: MY-013630; Symbol: ER\_IB\_ERR\_TEMP\_TABLESPACE\_DIR\_CONTAINS\_SEMICOLON; SQLSTATE: HY000

Message: %s

- Error number: MY-013631; Symbol: ER\_IB\_ERR\_TEMP\_TABLESPACE\_DIR\_SUBDIR\_OF\_DATADIR; SQLSTATE: HY000

Message: %s

- Error number: MY-013632; Symbol: ER\_IB\_ERR\_SCHED\_SETAFFINITY\_FAILED; SQLSTATE: HY000

Message: %s

- Error number: MY-013633; Symbol: ER\_IB\_ERR\_UNKNOWN\_PAGE\_FETCH\_MODE; SQLSTATE: HY000

Message: %s

- Error number: MY-013634; Symbol: ER\_IB\_ERR\_LOG\_PARSING\_BUFFER\_OVERFLOW; SQLSTATE: HY000

Message: %s

- Error number: MY-013635; Symbol: ER\_IB\_ERR\_NOT\_ENOUGH\_MEMORY\_FOR\_PARSE\_BUFFER; SQLSTATE: HY000

Message: %s

- Error number: MY-013636; Symbol: ER\_IB\_MSG\_1372; SQLSTATE: HY000

Message: %s

- Error number: MY-013637; Symbol: ER\_IB\_MSG\_1373; SQLSTATE: HY000

Message: %s

- Error number: MY-013638; Symbol: ER\_IB\_MSG\_1374; SQLSTATE: HY000

Message: %s

- Error number: MY-013639; Symbol: ER\_IB\_MSG\_1375; SQLSTATE: HY000

Message: %s

- Error number: MY-013640; Symbol: ER\_IB\_ERR\_ZLIB\_UNCOMPRESS\_FAILED; SQLSTATE: HY000

Message: %s

- 
- Error number: [MY-013641](#); Symbol: [ER\\_IB\\_ERR\\_ZLIB\\_BUF\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013642](#); Symbol: [ER\\_IB\\_ERR\\_ZLIB\\_MEM\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013643](#); Symbol: [ER\\_IB\\_ERR\\_ZLIB\\_DATA\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013644](#); Symbol: [ER\\_IB\\_ERR\\_ZLIB\\_UNKNOWN\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013645](#); Symbol: [ER\\_IB\\_MSG\\_1381](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013646](#); Symbol: [ER\\_IB\\_ERR\\_INDEX\\_RECORDS\\_WRONG\\_ORDER](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013647](#); Symbol: [ER\\_IB\\_ERR\\_INDEX\\_DUPLICATE\\_KEY](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013648](#); Symbol: [ER\\_IB\\_ERR\\_FOUND\\_N\\_DUPLICATE\\_KEYS](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013649](#); Symbol: [ER\\_IB\\_ERR\\_FOUND\\_N\\_RECORDS\\_WRONG\\_ORDER](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013650](#); Symbol: [ER\\_IB\\_ERR\\_PARALLEL\\_READ\\_OOM](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013651](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_MARKED\\_ACTIVE](#); SQLSTATE: [HY000](#)  
Message: The state of undo tablespace %s is set to active implicitly.
  - Error number: [MY-013652](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_ALTERED\\_ACTIVE](#); SQLSTATE: [HY000](#)  
Message: The state of undo tablespace %s is set to 'active' by ALTER TABLESPACE.
  - Error number: [MY-013653](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_ALTERED\\_INACTIVE](#); SQLSTATE: [HY000](#)  
Message: The state of undo tablespace %s is set to 'inactive' by ALTER TABLESPACE.
  - Error number: [MY-013654](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_MARKED\\_EMPTY](#); SQLSTATE: [HY000](#)  
Message: The state of undo tablespace %s is set to 'empty'.
  - Error number: [MY-013655](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_DELAY\\_BY\\_CLONE](#); SQLSTATE: [HY000](#)  
Message: Delaying truncate of undo tablespace %s due to clone activity.
-

- 
- Error number: [MY-013656](#); Symbol: [ER\\_IB\\_MSG\\_UNDO\\_TRUNCATE\\_DELAY\\_BY\\_MDL](#); SQLSTATE: [HY000](#)  
 Message: Delaying truncate of undo tablespace %s due to a metadata lock.
  - Error number: [MY-013657](#); Symbol: [ER\\_IB\\_MSG\\_INJECT\\_CRASH](#); SQLSTATE: [HY000](#)  
 Message: Injected debug crash point: %s
  - Error number: [MY-013658](#); Symbol: [ER\\_IB\\_MSG\\_INJECT\\_FAILURE](#); SQLSTATE: [HY000](#)  
 Message: Injected debug failure point: %s
  - Error number: [MY-013659](#); Symbol: [ER\\_GRP\\_RPL\\_TIMEOUT\\_RECEIVED\\_VC\\_LEAVE\\_ON\\_REJOIN](#); SQLSTATE: [HY000](#)  
 Message: Timeout while waiting for a view change event during the leave step before a auto-rejoin attempt.
  - Error number: [MY-013660](#); Symbol: [ER\\_RPL\\_ASYNC\\_RECONNECT\\_FAIL\\_NO\\_SOURCE](#); SQLSTATE: [HY000](#)  
 Message: Failed to automatically re-connect to a different source, for channel '%s', because %s. To fix this %s.
  - Error number: [MY-013661](#); Symbol: [ER\\_UDF\\_REGISTER\\_SERVICE\\_ERROR](#); SQLSTATE: [HY000](#)  
 Message: Could not execute the installation of UDF functions. Check for other errors in the log
  - Error number: [MY-013662](#); Symbol: [ER\\_UDF\\_REGISTER\\_ERROR](#); SQLSTATE: [HY000](#)  
 Message: Could not execute the installation of UDF function: %s. Check if the function is already present, if so, try to remove it.
  - Error number: [MY-013663](#); Symbol: [ER\\_UDF\\_UNREGISTER\\_ERROR](#); SQLSTATE: [HY000](#)  
 Message: Could not uninstall UDF functions. Try to remove them manually if present.
  - Error number: [MY-013664](#); Symbol: [ER\\_EMPTY\\_PRIVILEGE\\_NAME\\_IGNORED](#); SQLSTATE: [HY000](#)  
 Message: An empty or illegal privilege identifier was ignored when global privileges were read from disk.
  - Error number: [MY-013665](#); Symbol: [ER\\_IB\\_MSG\\_INCORRECT\\_SIZE](#); SQLSTATE: [HY000](#)  
 Message: %s
  - Error number: [MY-013666](#); Symbol: [ER\\_TMPDIR\\_PATH\\_TOO\\_LONG](#); SQLSTATE: [HY000](#)  
 Message: A tmpdir temporary path "%s" is too long (> %zu) for this OS. This would not leave enough space for a temporary filename of length %zu within it.
  - Error number: [MY-013667](#); Symbol: [ER\\_ERROR\\_LOG\\_DESTINATION\\_NOT\\_A\\_FILE](#); SQLSTATE: [HY000](#)  
 Message: Error-log destination "%s" is not a file. Can not restore error log messages from previous run.
  - Error number: [MY-013668](#); Symbol: [ER\\_NO\\_ERROR\\_LOG\\_PARSER\\_CONFIGURED](#); SQLSTATE: [HY000](#)  
 Message: None of the log-sinks selected with --log-error-services=... provides a log-parser. The server will not be able to make the previous runs' error-logs available in performance\_schema.error\_log.



- 
- Error number: [MY-013669](#); Symbol: [ER\\_UPGRADE\\_NONEXISTENT\\_SCHEMA](#); SQLSTATE: [HY000](#)  
Message: The schema "%s" referenced by %s "%s" does not exist. Please clean up any orphan %s before upgrading.
  - Error number: [MY-013670](#); Symbol: [ER\\_IB\\_MSG\\_CREATED\\_UNDO\\_SPACE](#); SQLSTATE: [HY000](#)  
Message: Created undo tablespace '%s'.
  - Error number: [MY-013671](#); Symbol: [ER\\_IB\\_MSG\\_DROPPED\\_UNDO\\_SPACE](#); SQLSTATE: [HY000](#)  
Message: Dropped undo tablespace '%s'.
  - Error number: [MY-013672](#); Symbol: [ER\\_IB\\_MSG\\_MASTER\\_KEY\\_ROTATED](#); SQLSTATE: [HY000](#)  
Message: The InnoDB Encryption Master Key has been rotated in %d tablespaces.
  - Error number: [MY-013673](#); Symbol: [ER\\_IB\\_DBLWR\\_DECOMPRESS\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to decompress a DBLWR page (err=%d). The original size is %d. Reporting the dblwr page as corrupted.
  - Error number: [MY-013674](#); Symbol: [ER\\_IB\\_DBLWR\\_DECRYPT\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Decrypting a page in doublewrite file failed: %s.
  - Error number: [MY-013675](#); Symbol: [ER\\_IB\\_DBLWR\\_KEY\\_MISSING](#); SQLSTATE: [HY000](#)  
Message: Encryption key missing: %s.
  - Error number: [MY-013676](#); Symbol: [ER\\_INNODB\\_IO\\_WRITE\\_ERROR\\_RETRYING](#); SQLSTATE: [HY000](#)  
Message: I/O error while writing to file: %s. Retrying ...
  - Error number: [MY-013677](#); Symbol: [ER\\_INNODB\\_IO\\_WRITE\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to write data to file: %s
  - Error number: [MY-013678](#); Symbol: [ER\\_LOG\\_COMPONENT\\_CANNOT\\_INIT](#); SQLSTATE: [HY000](#)  
Message: Log component %s failed to initialize.
  - Error number: [MY-013679](#); Symbol: [ER\\_RPL\\_ASYNC\\_CHANNEL\\_CANT\\_CONNECT](#); SQLSTATE: [HY000](#)  
Message: The Monitor IO thread failed to connect to the source (host:%s port:%u network\_namespace:%s) for channel '%s', thence it will try to connect to another source.
  - Error number: [MY-013680](#); Symbol: [ER\\_RPL\\_ASYNC\\_SENDER\\_ADDED](#); SQLSTATE: [HY000](#)  
Message: The source (host:%s port:%u network\_namespace:%s) for channel '%s' has joined the group (group\_name: %s), and so added its entry into replication\_asynchronous\_connection\_failover table.
  - Error number: [MY-013681](#); Symbol: [ER\\_RPL\\_ASYNC\\_SENDER\\_REMOVED](#); SQLSTATE: [HY000](#)  
Message: The source (host:%s port:%u network\_namespace:%s) for channel '%s' has left the group (group\_name: %s), and so removed its entry from replication\_asynchronous\_connection\_failover table.
  - Error number: [MY-013682](#); Symbol: [ER\\_RPL\\_ASYNC\\_CHANNEL\\_STOPPED\\_QUORUM\\_LOST](#); SQLSTATE: [HY000](#)
-

---

Message: The Monitor IO thread detected that the source (host:%s port:%u network\_namespace:%s) does not belong to the group majority, thence the channel '%s' will try to connect to another source.

- Error number: [MY-013683](#); Symbol: [ER\\_RPL\\_ASYNC\\_CHANNEL\\_CANT\\_CONNECT\\_NO\\_QUORUM](#); SQLSTATE: [HY000](#)

Message: The IO thread detected that the source (host:%s port:%u network\_namespace:%s) does not belong to the group majority, thence the channel '%s' will try to connect to another source.

- Error number: [MY-013685](#); Symbol: [ER\\_RPL\\_REPLICA\\_MONITOR\\_IO\\_THREAD\\_EXITING](#); SQLSTATE: [HY000](#)

Message: Replica Monitor IO thread exiting.

- Error number: [MY-013686](#); Symbol: [ER\\_RPL\\_ASYNC\\_MANAGED\\_NAME\\_REMOVED](#); SQLSTATE: [HY000](#)

Message: The group (group\_name: %s) for the channel '%s' has been removed, and so removed its entry from replication\_asynchronous\_connection\_failover\_managed and all the group members from replication\_asynchronous\_connection\_failover table.

- Error number: [MY-013687](#); Symbol: [ER\\_RPL\\_ASYNC\\_MANAGED\\_NAME\\_ADDED](#); SQLSTATE: [HY000](#)

Message: The group (group\_name: %s) for the channel '%s' has been added, and so added its entry in replication\_asynchronous\_connection\_failover\_managed and source to replication\_asynchronous\_connection\_failover table.

- Error number: [MY-013688](#); Symbol: [ER\\_RPL\\_ASYNC\\_READ\\_FAILOVER\\_TABLE](#); SQLSTATE: [HY000](#)

Message: Error reading failover sources for channel '%s' from replication\_asynchronous\_connection\_failover table.

- Error number: [MY-013689](#); Symbol: [ER\\_RPL\\_REPLICA\\_MONITOR\\_IO\\_THREAD\\_RECONNECT\\_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Error %s the channel '%s', the operation will be automatically retried.

- Error number: [MY-013690](#); Symbol: [ER\\_REPLICA\\_ANON\\_TO\\_GTID\\_IS\\_LOCAL\\_OR\\_UUID\\_AND\\_GTID\\_MODE\\_NOT\\_ON](#); SQLSTATE: [HY000](#)

Message: Replication channel '%s' is configured with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS='%s'`, which is invalid when `GTID_MODE <> ON`. If you intend to use `GTID_MODE = ON` everywhere, change to `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = OFF` and use the procedure for enabling GTIDs online (see the documentation). If you intend to use GTIDs on this replica and cannot enable GTIDs on the source, enable `GTID_MODE = ON` and leave `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>`. If you intend to not use GTIDs at all in the replication topology, change to `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS=OFF` and leave `GTID_MODE = '%s'`.

- Error number: [MY-013691](#); Symbol: [ER\\_REPLICA\\_ANONYMOUS\\_TO\\_GTID\\_UUID\\_SAME\\_AS\\_GROUP\\_NAME](#); SQLSTATE: [HY000](#)

Message: Replication channel '%s' is configured with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS='%s'` which is equal to `group_replication_group_name`. To fix this issue, either change the `group_replication_group_name` or use a different value for `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS`.

- 
- Error number: [MY-013692](#); Symbol: [ER\\_GRP\\_RPL\\_GRP\\_NAME\\_IS\\_SAME\\_AS\\_ANONYMOUS\\_TO\\_GTID\\_UUID](#); SQLSTATE: [HY000](#)

Message: The group\_replication\_group\_name '%s' is the same as the UUID value for ASSIGN\_GTIDS\_TO\_ANONYMOUS\_TRANSACTIONS in a server channel
  - Error number: [MY-013693](#); Symbol: [ER\\_WARN\\_GTID\\_THRESHOLD\\_BREACH](#); SQLSTATE: [HY000](#)

Message: The integer component of the GTID number is high. Suggest restarting the server with a new server\_uuid to prevent it from reaching the maximum number 2<sup>63</sup>-1, which will make it impossible to write the binary log and invoke the behavior specified by binlog\_error\_action.
  - Error number: [MY-013694](#); Symbol: [ER\\_HEALTH\\_INFO](#); SQLSTATE: [HY000](#)

Message: %s
  - Error number: [MY-013695](#); Symbol: [ER\\_HEALTH\\_WARNING](#); SQLSTATE: [HY000](#)

Message: %s
  - Error number: [MY-013696](#); Symbol: [ER\\_HEALTH\\_ERROR](#); SQLSTATE: [HY000](#)

Message: %s
  - Error number: [MY-013697](#); Symbol: [ER\\_HEALTH\\_WARNING\\_DISK\\_USAGE\\_LEVEL\\_1](#); SQLSTATE: [HY000](#)

Message: %s: Warning Level 1 (%llu MiB): mount point = '%s', available = %llu MiB, total = %llu MiB, used = %.2f%%, low limit = %llu MiB, critical level = %llu MiB
  - Error number: [MY-013698](#); Symbol: [ER\\_HEALTH\\_WARNING\\_DISK\\_USAGE\\_LEVEL\\_2](#); SQLSTATE: [HY000](#)

Message: %s: Warning Level 2 (%llu MiB): mount point = '%s', available = %llu MiB, total = %llu MiB, used = %.2f%%, low limit = %llu MiB, critical level = %llu MiB
  - Error number: [MY-013699](#); Symbol: [ER\\_HEALTH\\_WARNING\\_DISK\\_USAGE\\_LEVEL\\_3](#); SQLSTATE: [HY000](#)

Message: %s: Warning Level 3 (%llu MiB): mount point = '%s', available = %llu MiB, total = %llu MiB, used = %.2f%%, low limit = %llu MiB, critical level = %llu MiB
  - Error number: [MY-013700](#); Symbol: [ER\\_IB\\_INNO\\_DB\\_TBSP\\_OUT\\_OF\\_SPACE](#); SQLSTATE: [HY000](#)

Message: InnoDB: Size of tablespace %s is more than the maximum size allowed.
  - Error number: [MY-013701](#); Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_CHANNEL\\_STILL\\_RUNNING](#); SQLSTATE: [HY000](#)

Message: The group\_replication\_applier channel is still running, most likely it is waiting for a database/table lock, which is preventing the channel from stopping. Please check database/table locks, including the ones created by backup tools.
  - Error number: [MY-013702](#); Symbol: [ER\\_RPL\\_ASYNC\\_RECONNECT\\_GTID\\_MODE\\_OFF\\_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Detected misconfiguration: replication channel '%s' was configured with SOURCE\_CONNECTION\_AUTO\_FAILOVER = 1, but the server was started with a value other than --gtid-mode = ON. Either reconfigure replication using CHANGE REPLICATION SOURCE TO SOURCE\_CONNECTION\_AUTO\_FAILOVER = 0 FOR CHANNEL '%s', or change GTID\_MODE to value ON, before starting the replica receiver thread.
-

- 
- Error number: `MY-013703`; Symbol: `ER_FIREWALL_SERVICES_NOT_ACQUIRED`; SQLSTATE: `HY000`  
Message: Could not acquire required component services.
  - Error number: `MY-013704`; Symbol: `ER_FIREWALL_UDF_REGISTER_FAILED`; SQLSTATE: `HY000`  
Message: Automatic registration of function(s) failed.
  - Error number: `MY-013705`; Symbol: `ER_FIREWALL_PFS_TABLE_REGISTER_FAILED`; SQLSTATE: `HY000`  
Message: Automatic registration of Performance schema table(s) failed.
  - Error number: `MY-013706`; Symbol: `ER_IB_MSG_STATS_SAMPLING_TOO_LARGE`; SQLSTATE: `HY000`  
Message: %s
  - Error number: `MY-013707`; Symbol: `ER_AUDIT_LOG_FILE_PRUNE_FAILED`; SQLSTATE: `HY000`  
Message: Failed to auto-prune file '%s', Error (%d): %s
  - Error number: `MY-013708`; Symbol: `ER_AUDIT_LOG_FILE_AUTO_PRUNED`; SQLSTATE: `HY000`  
Message: File '%s' auto-pruned
  - Error number: `MY-013709`; Symbol: `ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_INIT`; SQLSTATE: `HY000`  
Message: Received an error while processing components from manifest file: %s
  - Error number: `MY-013710`; Symbol: `ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_DEINIT`; SQLSTATE: `HY000`  
Message: Received an error while unloading components read from manifest file: %s
  - Error number: `MY-013711`; Symbol: `ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFEST_NOT_RO`; SQLSTATE: `HY000`  
Message: Manifest file '%s' is not read-only. For better security, please make sure that the file is read-only.
  - Error number: `MY-013712`; Symbol: `ER_WARN_NO_KEYRING_COMPONENT_SERVICE_FOUND`; SQLSTATE: `HY000`  
Message: No suitable '%s' service implementation found to fulfill the request.
  - Error number: `MY-013713`; Symbol: `ER_NOTE_KEYRING_COMPONENT_INITIALIZED`; SQLSTATE: `HY000`  
Message: Keyring component initialized successfully.
  - Error number: `MY-013714`; Symbol: `ER_KEYRING_COMPONENT_NOT_INITIALIZED`; SQLSTATE: `HY000`  
Message: The component is not initialized properly. Make sure that configuration is proper and use `ALTER INSTANCE RELOAD KEYRING` to reinitialize the component.
  - Error number: `MY-013715`; Symbol: `ER_KEYRING_COMPONENT_EXCEPTION`; SQLSTATE: `HY000`  
Message: Keyring component encountered an exception while executing : '%s' API of service: '%s'

- 
- Error number: `MY-013716`; Symbol: `ER_KEYRING_COMPONENT_MEMORY_ALLOCATION_ERROR`; SQLSTATE: `HY000`  
Message: Failed to allocated memory for '%s' while executing: '%s' API of service: '%s'
  - Error number: `MY-013717`; Symbol: `ER_NOTE_KEYRING_COMPONENT_AES_INVALID_MODE_BLOCK_SIZE`; SQLSTATE: `HY000`  
Message: Empty or 0 values for AES encryption mode and/or block size are not permitted.
  - Error number: `MY-013718`; Symbol: `ER_NOTE_KEYRING_COMPONENT_AES_DATA_IDENTIFIER_EMPTY`; SQLSTATE: `HY000`  
Message: A valid data identifier is required in order to fetch the key required for the AES operation.
  - Error number: `MY-013719`; Symbol: `ER_NOTE_KEYRING_COMPONENT_AES_INVALID_KEY`; SQLSTATE: `HY000`  
Message: Key identified by Data ID: '%s' and Auth ID: '%s' is not of type AES.
  - Error number: `MY-013720`; Symbol: `ER_NOTE_KEYRING_COMPONENT_AES_OPERATION_ERROR`; SQLSTATE: `HY000`  
Message: Encountered error: '%s' while executing '%s' API of keyring\_aes service. Key details are Data ID: '%s' and Auth ID: '%s'.
  - Error number: `MY-013721`; Symbol: `ER_NOTE_KEYRING_COMPONENT_READ_DATA_NOT_FOUND`; SQLSTATE: `HY000`  
Message: Could not find the data corresponding to Data ID: '%s', Auth ID: '%s'.
  - Error number: `MY-013722`; Symbol: `ER_NOTE_KEYRING_COMPONENT_WRITE_MAXIMUM_DATA_LENGTH`; SQLSTATE: `HY000`  
Message: Maximum permissible size of data is '%zu' bits
  - Error number: `MY-013723`; Symbol: `ER_NOTE_KEYRING_COMPONENT_STORE_FAILED`; SQLSTATE: `HY000`  
Message: Error writing data for Data ID: '%s', Auth ID: '%s'. Either data already exists with same identifier or keyring backend encountered an error.
  - Error number: `MY-013724`; Symbol: `ER_NOTE_KEYRING_COMPONENT_REMOVE_FAILED`; SQLSTATE: `HY000`  
Message: Error removing data for Data ID: '%s', Auth ID: '%s'. Either data does not exists with same identifier or keyring backend encountered an error.
  - Error number: `MY-013725`; Symbol: `ER_NOTE_KEYRING_COMPONENT_GENERATE_FAILED`; SQLSTATE: `HY000`  
Message: Error generating data for Data ID: '%s', Auth ID: '%s'. Either data already exists with same identifier or keyring backend encountered an error.
  - Error number: `MY-013726`; Symbol: `ER_NOTE_KEYRING_COMPONENT_KEYS_METADATA_ITERATOR_FETCH_FAILED`; SQLSTATE: `HY000`  
Message: Failed to get metadata from current keys metadata iterator position.
  - Error number: `MY-013727`; Symbol: `ER_NOTE_KEYRING_COMPONENT_METADATA_ITERATOR_INVALID_OUT_PARAM`; SQLSTATE: `HY000`

---

Message: Key and value length parameters must not be null.

- Error number: [MY-013728](#); Symbol: [ER\\_IB\\_WRN\\_FAILED\\_TO\\_ACQUIRE\\_SERVICE](#); SQLSTATE: [HY000](#)

Message: Innodb could not acquire service : %s

- Error number: [MY-013729](#); Symbol: [ER\\_IB\\_WRN\\_OLD\\_GEOMETRY\\_TYPE](#); SQLSTATE: [HY000](#)

Message: Column %s of type GEOMETRY is in old (5.6) format which could be deprecated in the future. To change the format to latest, please consider rebuilding the table after the upgrade.

- Error number: [MY-013730](#); Symbol: [ER\\_NET\\_WAIT\\_ERROR2](#); SQLSTATE: [HY000](#)

Message: 'wait\_timeout' period of %s seconds was exceeded for %s. The idle time since last command was too long.

- Error number: [MY-013731](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_TRIGGERED](#); SQLSTATE: [HY000](#)

Message: The member action "%s" for event "%s" with priority "%u" will be run.

- Error number: [MY-013732](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_FAILURE\\_IGNORE](#); SQLSTATE: [HY000](#)

Message: The member action "%s" for event "%s" with priority "%u" failed, this error is ignored as instructed. Please check previous messages in the error log for hints about what could have caused this failure.

- Error number: [MY-013733](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: The member action "%s" for event "%s" with priority "%u" failed. Please check previous messages in the error log for hints about what could have caused this failure.

- Error number: [MY-013734](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_PARSE\\_ON\\_RECEIVE](#); SQLSTATE: [HY000](#)

Message: Unable to parse the member actions configuration sent by the primary.

- Error number: [MY-013735](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_UPDATE\\_ACTIONS](#); SQLSTATE: [HY000](#)

Message: Unable to update the member actions configuration with the one sent by the primary. Please check the tables 'mysql.replication\_group\_member\_actions' and 'mysql.replication\_group\_configuration\_version'.

- Error number: [MY-013736](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_GET\\_EXCHANGEABLE\\_DATA](#); SQLSTATE: [HY000](#)

Message: Unable to read the member actions configuration during group membership change. Please check the tables 'mysql.replication\_group\_member\_actions' and 'mysql.replication\_group\_configuration\_version'.

- Error number: [MY-013737](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_DEFAULT\\_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: This member joined a group on which all members do not support member actions, as such it did reset its member configuration to the default one.

- 
- Error number: [MY-013738](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_UNABLE\\_TO\\_SET\\_DEFAULT\\_CONFIGURATION](#); SQLSTATE: [HY000](#)  
  
Message: Unable to reset to member actions default configuration on member join. Please check the tables 'mysql.replication\_group\_member\_actions' and 'mysql.replication\_group\_configuration\_version'.
  - Error number: [MY-013739](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_PARSE\\_ON\\_MEMBER\\_JOIN](#); SQLSTATE: [HY000](#)  
  
Message: Unable to parse the member actions configuration sent by the group on member join.
  - Error number: [MY-013740](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_UPDATE\\_ACTIONS\\_ON\\_MEMBER\\_JOIN](#); SQLSTATE: [HY000](#)  
  
Message: Unable to update the member actions configuration on member join. Please check the tables 'mysql.replication\_group\_member\_actions' and 'mysql.replication\_group\_configuration\_version'.
  - Error number: [MY-013741](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_INVALID\\_ACTIONS\\_ON\\_MEMBER\\_JOIN](#); SQLSTATE: [HY000](#)  
  
Message: The group members were unable to send their member actions configuration. Please check the tables 'mysql.replication\_group\_member\_actions' and 'mysql.replication\_group\_configuration\_version' on all members.
  - Error number: [MY-013742](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_ENABLED](#); SQLSTATE: [HY000](#)  
  
Message: Member action enabled: "%s", type: "%s", event: "%s", priority: "%u", error\_handling: "%s".
  - Error number: [MY-013743](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTION\\_DISABLED](#); SQLSTATE: [HY000](#)  
  
Message: Member action disabled: "%s", type: "%s", event: "%s", priority: "%u", error\_handling: "%s".
  - Error number: [MY-013744](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_ACTIONS\\_RESET](#); SQLSTATE: [HY000](#)  
  
Message: Member actions configuration was reset.
  - Error number: [MY-013747](#); Symbol: [ER\\_FIREWALL\\_DEPRECATED\\_USER\\_PROFILE](#); SQLSTATE: [HY000](#)  
  
Message: User profile '%s' loaded. Firewall user profiles are deprecated, consider migrating to group profiles.
  - Error number: [MY-013748](#); Symbol: [ER\\_GRP\\_RPL\\_VIEW\\_CHANGE\\_UUID\\_INVALID](#); SQLSTATE: [HY000](#)  
  
Message: Invalid input value for group\_replication\_view\_change\_uuid '%s'. Please, provide a valid UUID.
  - Error number: [MY-013749](#); Symbol: [ER\\_GRP\\_RPL\\_VIEW\\_CHANGE\\_UUID\\_SAME\\_AS\\_GROUP\\_NAME](#); SQLSTATE: [HY000](#)  
  
Message: Variable 'group\_replication\_view\_change\_uuid' cannot be set to the value of '%s'. If you want to use the UUID of 'group\_replication\_group\_name' for the UUID of View\_change\_log\_events, please set 'group\_replication\_view\_change\_uuid' to AUTOMATIC.
  - Error number: [MY-013750](#); Symbol: [ER\\_GRP\\_RPL\\_GROUP\\_NAME\\_SAME\\_AS\\_VIEW\\_CHANGE\\_UUID](#); SQLSTATE: [HY000](#)
-

---

Message: group\_replication\_group\_name '%s', which is the same as group\_replication\_view\_change\_uuid. Please change group\_replication\_view\_change\_uuid to AUTOMATIC

- Error number: MY-013751; Symbol: ER\_GRP\_RPL\_VIEW\_CHANGE\_UUID\_IS\_SAME\_AS\_ANONYMOUS\_TO\_GTID\_UUID; SQLSTATE: HY000

Message: The group\_replication\_view\_change\_uuid '%s' is the same as the UUID value for ASSIGN\_GTIDS\_TO\_ANONYMOUS\_TRANSACTIONS in a server channel

- Error number: MY-013752; Symbol: ER\_GRP\_RPL\_GRP\_VIEW\_CHANGE\_UUID\_IS\_INCOMPATIBLE\_WITH\_SERVER\_UUID; SQLSTATE: HY000

Message: group\_replication\_view\_change\_uuid is incompatible with group.  
group\_replication\_view\_change\_uuid %s matches server\_uuid %s.

- Error number: MY-013753; Symbol: ER\_GRP\_RPL\_VIEW\_CHANGE\_UUID\_DIFF\_FROM\_GRP; SQLSTATE: HY000

Message: The member is configured with a group\_replication\_view\_change\_uuid option value '%s' different from the group '%s'. The member will now exit the group.

- Error number: MY-013754; Symbol: ER\_WARN\_REPLICA\_ANONYMOUS\_TO\_GTID\_UUID\_SAME\_AS\_VIEW\_CHANGE\_UUID; SQLSTATE: HY000

Message: Replication channel '%s' is configured with ASSIGN\_GTIDS\_TO\_ANONYMOUS\_TRANSACTIONS='%s' which is equal to group\_replication\_view\_change\_uuid. To fix this issue, either change the group\_replication\_view\_change\_uuid or use a different value for ASSIGN\_GTIDS\_TO\_ANONYMOUS\_TRANSACTIONS.

- Error number: MY-013755; Symbol: ER\_GRP\_RPL\_FAILED\_TO\_PARSE\_THE\_VIEW\_CHANGE\_UUID; SQLSTATE: HY000

Message: Unable to parse the group\_replication\_view\_change\_uuid.

- Error number: MY-013756; Symbol: ER\_GRP\_RPL\_FAILED\_TO\_GENERATE\_SIDNO\_FOR\_VIEW\_CHANGE\_UUID; SQLSTATE: HY000

Message: Unable to generate sidno for group\_replication\_view\_change\_uuid.

- Error number: MY-013757; Symbol: ER\_GRP\_RPL\_VIEW\_CHANGE\_UUID\_PARSE\_ERROR; SQLSTATE: HY000

Message: Unable to parse the group\_replication\_view\_change\_uuid during the Certification module initialization.

- Error number: MY-013758; Symbol: ER\_GRP\_RPL\_UPDATE\_GRPGTID\_VIEW\_CHANGE\_UUID\_EXECUTED\_ERROR; SQLSTATE: HY000

Message: Error updating group\_gtid\_executed GTID set with view change uuid during the Certification module initialization.

- Error number: MY-013759; Symbol: ER\_GRP\_RPL\_ADD\_VIEW\_CHANGE\_UUID\_TO\_GRP\_SID\_MAP\_ERROR; SQLSTATE: HY000

Message: Unable to add the group\_replication\_view\_change\_uuid sidno in the group\_gtid\_sid\_map during the Certification module initialization.



- 
- Error number: [MY-013760](#); Symbol: [ER\\_GRP\\_RPL\\_DONOR\\_VIEW\\_CHANGE\\_UUID\\_TRANS\\_INFO\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Unable to handle the donor's view change uuid transaction information when initializing the conflict detection component. Possible out of memory error.
  - Error number: [MY-013761](#); Symbol: [ER\\_WARN\\_GRP\\_RPL\\_VIEW\\_CHANGE\\_UUID\\_FAIL\\_GET\\_VARIABLE](#); SQLSTATE: [HY000](#)  
Message: Unable to retrieve group\_replication\_view\_change\_uuid during server checks on replication operations.
  - Error number: [MY-013762](#); Symbol: [ER\\_WARN\\_ADUIT\\_LOG\\_MAX\\_SIZE\\_AND\\_PRUNE\\_SECONDS\\_LOG](#); SQLSTATE: [HY000](#)  
Message: Both audit\_log\_max\_size and audit\_log\_prune\_seconds are set to non-zero. audit\_log\_max\_size takes precedence and audit\_log\_prune\_seconds is ignored
  - Error number: [MY-013763](#); Symbol: [ER\\_WARN\\_ADUIT\\_LOG\\_MAX\\_SIZE\\_CLOSE\\_TO\\_ROTATE\\_ON\\_SIZE\\_LOG](#); SQLSTATE: [HY000](#)  
Message: audit\_log\_rotate\_on\_size is not granular enough for the value of audit\_log\_max\_size supplied. Should be at least %d times smaller.
  - Error number: [MY-013764](#); Symbol: [ER\\_PLUGIN\\_INVALID\\_TABLE\\_DEFINITION](#); SQLSTATE: [HY000](#)  
Message: Invalid table definition for '%s.%s'.
  - Error number: [MY-013765](#); Symbol: [ER\\_AUTH\\_KERBEROS\\_LOGGER\\_GENERIC\\_MSG](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-013766](#); Symbol: [ER\\_INSTALL\\_PLUGIN\\_CONFLICT\\_LOG](#); SQLSTATE: [HY000](#)  
Message: Cannot install the %s plugin when the %s plugin is installed.
  - Error number: [MY-013767](#); Symbol: [ER\\_DEPRECATED\\_PERSISTED\\_VARIABLE\\_WITH\\_ALIAS](#); SQLSTATE: [HY000](#)  
Message: The variable %s has been renamed to %s, and the old name deprecated. Only the old name was found in the persisted variable file. Next time the file is saved, both names will be stored. Issue any SET PERSIST command to save the file, get rid of this warning, and prepare the persisted configuration for when the variable is removed in a future version.
  - Error number: [MY-013768](#); Symbol: [ER\\_LOG\\_COMPONENT\\_FLUSH\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: %d error logging component(s) failed to flush. For file-based logs this can happen when the path or permissions of the log-file have changed. Failure to flush file-based logs may affect log-rotation.
  - Error number: [MY-013769](#); Symbol: [ER\\_IB\\_MSG\\_REENCRYPTED\\_TABLESPACE\\_KEY](#); SQLSTATE: [HY000](#)  
Message: Tablespace key for %s has been re-encrypted using the latest InnoDB master key. However, we recommend that you rebuild the table for better security.
  - Error number: [MY-013770](#); Symbol: [ER\\_IB\\_MSG\\_REENCRYPTED\\_GENERAL\\_TABLESPACE\\_KEY](#); SQLSTATE: [HY000](#)  
Message: Tablespace key for %s has been re-encrypted using the latest InnoDB master key. However, we recommend that you reencrypt the tablespace for better security.

- 
- Error number: [MY-013771](#); Symbol: [ER\\_IB\\_ERR\\_PAGE\\_ARCH\\_DBLWR\\_INIT\\_FAILED](#); SQLSTATE: [HY000](#)  
  
Message: Page Archiver's doublewrite buffer initialisation failed. Page tracking is at risk of losing tracked information.
  - Error number: [MY-013772](#); Symbol: [ER\\_IB\\_MSG\\_RECOVERY\\_NO\\_SPACE\\_IN\\_REDO\\_LOG\\_\\_SKIP\\_IBUF\\_MERGES](#); SQLSTATE: [HY000](#)  
  
Message: There is not enough free space in the redo log during recovery to perform pending ibuf merges. Please retry starting MySQL with --innodb-force-recovery=4.
  - Error number: [MY-013773](#); Symbol: [ER\\_IB\\_MSG\\_RECOVERY\\_NO\\_SPACE\\_IN\\_REDO\\_LOG\\_\\_UNEXPECTED](#); SQLSTATE: [HY000](#)  
  
Message: There is not enough free space in the redo log during recovery, restore from backup (or retry with --innodb-force-recovery=6).
  - Error number: [MY-013774](#); Symbol: [ER\\_WARN\\_AUDIT\\_LOG\\_FORMAT\\_UNIX\\_TIMESTAMP\\_ONLY\\_WHEN\\_JSON\\_LOG](#); SQLSTATE: [HY000](#)  
  
Message: audit\_log\_format\_unix\_timestamp is applicable only when audit\_log\_format = JSON.
  - Error number: [MY-013775](#); Symbol: [ER\\_PREPARE\\_FOR\\_PRIMARY\\_ENGINE](#); SQLSTATE: [HY000](#)  
  
Message: Retry the statement using the primary storage engine.
  - Error number: [MY-013776](#); Symbol: [ER\\_IB\\_MSG\\_PAR\\_RSEG\\_INIT\\_COMPLETE\\_MSG](#); SQLSTATE: [HY000](#)  
  
Message: Parallel initialization of rseg complete
  - Error number: [MY-013777](#); Symbol: [ER\\_IB\\_MSG\\_PAR\\_RSEG\\_INIT\\_TIME\\_MSG](#); SQLSTATE: [HY000](#)  
  
Message: Time taken to initialize rseg using %u thread: %u ms.
  - Error number: [MY-013778](#); Symbol: [ER\\_DDL\\_MSG\\_1](#); SQLSTATE: [HY000](#)  
  
Message: DDL failed to create a thread to load an index, fall back to single thread
  - Error number: [MY-013779](#); Symbol: [ER\\_MTR\\_MSG\\_1](#); SQLSTATE: [HY000](#)  
  
Message: Debug\_check\_no\_latching failed, slot->type=%d
  - Error number: [MY-013780](#); Symbol: [ER\\_GRP\\_RPL\\_MYSQL\\_NETWORK\\_PROVIDER\\_CLIENT\\_ERROR\\_CONN\\_ERR](#); SQLSTATE: [HY000](#)  
  
Message: Failed to establish MySQL client connection in Group Replication. Error establishing connection. Please refer to the manual to make sure that you configured Group Replication properly to work with MySQL Protocol connections.
  - Error number: [MY-013781](#); Symbol: [ER\\_GRP\\_RPL\\_MYSQL\\_NETWORK\\_PROVIDER\\_CLIENT\\_ERROR\\_COMMAND\\_ERR](#); SQLSTATE: [HY000](#)  
  
Message: Failed to establish MySQL client connection in Group Replication. Error sending connection delegation command. Please refer to the manual to make sure that you configured Group Replication properly to work with MySQL Protocol connections.

- 
- Error number: [MY-013782](#); Symbol: [ER\\_GRP\\_RPL\\_FAILOVER\\_CONF\\_GET\\_EXCHANGEABLE\\_DATA](#); SQLSTATE: [HY000](#)

Message: Unable to read the replication failover channels configuration during group membership change. Please check the tables 'mysql.replication\_asynchronous\_connection\_failover', 'mysql.replication\_asynchronous\_connection\_failover\_managed' and 'mysql.replication\_group\_configuration\_version'.

- Error number: [MY-013783](#); Symbol: [ER\\_GRP\\_RPL\\_FAILOVER\\_CONF\\_DEFAULT\\_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: This member joined a group on which all members do not support replication failover channels integration on Group Replication, as such it did reset its replication failover channels configuration to the default one.

- Error number: [MY-013784](#); Symbol: [ER\\_GRP\\_RPL\\_FAILOVER\\_CONF\\_UNABLE\\_TO\\_SET\\_DEFAULT\\_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: Unable to reset to replication failover channels default configuration on member join. Please check the tables 'mysql.replication\_asynchronous\_connection\_failover', 'mysql.replication\_asynchronous\_connection\_failover\_managed' and 'mysql.replication\_group\_configuration\_version'.

- Error number: [MY-013785](#); Symbol: [ER\\_GRP\\_RPL\\_FAILOVER\\_CONF\\_PARSE\\_ON\\_MEMBER\\_JOIN](#); SQLSTATE: [HY000](#)

Message: Unable to parse the replication failover channels configuration sent by the group on member join.

- Error number: [MY-013786](#); Symbol: [ER\\_GRP\\_RPL\\_FAILOVER\\_CONF\\_CHANNEL\\_DOES\\_NOT\\_EXIST](#); SQLSTATE: [HY000](#)

Message: Unable to set SOURCE\_CONNECTION\_AUTO\_FAILOVER on a non-existent or misconfigured replication channel '%s', please create the channel and rejoin the server to the group.

- Error number: [MY-013787](#); Symbol: [ER\\_GRP\\_RPL\\_FAILOVER\\_REGISTER\\_MESSAGE\\_LISTENER\\_SERVICE](#); SQLSTATE: [HY000](#)

Message: Unable to register the listener 'replication\_asynchronous\_connection\_failover\_configuration' to the service 'group\_replication\_message\_service\_recv'.

- Error number: [MY-013788](#); Symbol: [ER\\_GRP\\_RPL\\_FAILOVER\\_PRIMARY\\_WITHOUT\\_MAJORITY](#); SQLSTATE: [HY000](#)

Message: This server is not able to reach a majority of members in the group. This server will skip the replication failover channels handling until this server is back to the group majority.

- Error number: [MY-013789](#); Symbol: [ER\\_GRP\\_RPL\\_FAILOVER\\_PRIMARY\\_BACK\\_TO\\_MAJORITY](#); SQLSTATE: [HY000](#)

Message: This server is back to the group majority. Replication failover channels handling is resumed.

- Error number: [MY-013790](#); Symbol: [ER\\_RPL\\_INCREMENTING\\_MEMBER\\_ACTION\\_VERSION](#); SQLSTATE: [HY000](#)

Message: Error incrementing member action configuration version for %s.%s table.

- Error number: [MY-013791](#); Symbol: [ER\\_GRP\\_RPL\\_REPLICA\\_THREAD\\_ERROR\\_ON\\_SECONDARY\\_MEMBER](#); SQLSTATE: [HY000](#)

---

Message: The '%s' thread of channel '%s' will error out as this server is a group secondary.

- Error number: MY-013792; Symbol: ER\_IB\_MSG\_CLONE\_DDL\_NTFN; SQLSTATE: HY000

Message: Clone DDL Notification: %s

- Error number: MY-013793; Symbol: ER\_IB\_MSG\_CLONE\_DDL\_APPLY; SQLSTATE: HY000

Message: Clone DDL APPLY: %s

- Error number: MY-013794; Symbol: ER\_IB\_MSG\_CLONE\_DDL\_INVALIDATE; SQLSTATE: HY000

Message: Clone DDL Invalidate : %s

- Error number: MY-013795; Symbol: ER\_IB\_MSG\_UNDO\_ENCRYPTION\_INFO\_LOADED; SQLSTATE: HY000

Message: Encryption key is loaded for undo tablespace '%s'.

- Error number: MY-013796; Symbol: ER\_IB\_WRN\_ENCRYPTION\_INFO\_SIZE\_MISMATCH; SQLSTATE: HY000

Message: Ignoring encryption INFO size in redo log: %zu, expected: %zu

- Error number: MY-013797; Symbol: ER\_INVALID\_AUTHENTICATION\_POLICY; SQLSTATE: HY000

Message: Option --authentication-policy is set to an invalid value. Please check if the specified authentication plugins are valid.

- Error number: MY-013798; Symbol: ER\_AUTHENTICATION\_PLUGIN\_REGISTRATION\_FAILED; SQLSTATE: HY000

Message: Signature verification failed during registration.

- Error number: MY-013799; Symbol: ER\_AUTHENTICATION\_PLUGIN\_REGISTRATION\_INSUFFICIENT\_BUFFER; SQLSTATE: HY000

Message: Buffer too small to hold registration challenge response.

- Error number: MY-013800; Symbol: ER\_AUTHENTICATION\_PLUGIN\_AUTH\_DATA\_CORRUPT; SQLSTATE: HY000

Message: FIDO device authenticator data corrupt.

- Error number: MY-013801; Symbol: ER\_AUTHENTICATION\_PLUGIN\_SIGNATURE\_CORRUPT; SQLSTATE: HY000

Message: FIDO device signature corrupt.

- Error number: MY-013802; Symbol: ER\_AUTHENTICATION\_PLUGIN\_VERIFY\_SIGNATURE\_FAILED; SQLSTATE: HY000

Message: Signature verification failed during authentication.

- Error number: MY-013803; Symbol: ER\_AUTHENTICATION\_PLUGIN\_OOM; SQLSTATE: HY000

Message: Out of memory.

- Error number: MY-013804; Symbol: ER\_AUTHENTICATION\_PLUGIN\_LOG; SQLSTATE: HY000

Message: Can't initialize logging service.

- 
- Error number: [MY-013805](#); Symbol: [ER\\_WARN\\_REPLICA\\_GTID\\_ONLY\\_AND\\_GTID\\_MODE\\_NOT\\_ON](#); SQLSTATE: [HY000](#)  
  
Message: Replication channel '%s' is configured with GTID\_ONLY=1, which is invalid when GTID\_MODE <> ON. If you intend to disable GTIDs in the replication topology, change GTID\_ONLY to 0.
  - Error number: [MY-013806](#); Symbol: [ER\\_WARN\\_L\\_DISABLE\\_GTID\\_ONLY\\_WITH\\_SOURCE\\_AUTO\\_POS\\_INVALID\\_POS](#); SQLSTATE: [HY000](#)  
  
Message: The replication positions relative to the source may be out-of-date on channel '%s', due to the use of GTID\_ONLY=1. The out-of-date positions can still be used in some cases so, in order to update them, we suggest that you start the replication to receive and apply at least one transaction, which will set the positions to valid values.
  - Error number: [MY-013807](#); Symbol: [ER\\_RPL\\_CANNOT\\_OPEN\\_RELAY\\_LOG](#); SQLSTATE: [HY000](#)  
  
Message: Could not open relay log: %s
  - Error number: [MY-013808](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_PLUGIN\\_NOT\\_INITIALIZED](#); SQLSTATE: [HY000](#)  
  
Message: Authentication plugin not initialized.
  - Error number: [MY-013809](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_PRIVATE\\_KEY\\_ERROR](#); SQLSTATE: [HY000](#)  
  
Message: Cannot use the generated private key file.
  - Error number: [MY-013810](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_DOWNLOAD\\_PUBLIC\\_KEY](#); SQLSTATE: [HY000](#)  
  
Message: Unavailable public key with fingerprint %s for user %s in tenancy %s .
  - Error number: [MY-013811](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_IMDS](#); SQLSTATE: [HY000](#)  
  
Message: Cannot obtain the OCI configuration from the IMDS service.
  - Error number: [MY-013812](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_IAM](#); SQLSTATE: [HY000](#)  
  
Message: Cannot initialize the IAM service.
  - Error number: [MY-013813](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_INVALID\\_AUTHENTICATION\\_STRING](#); SQLSTATE: [HY000](#)  
  
Message: Invalid authentication string details for user: `%s`@`%s`.
  - Error number: [MY-013814](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_NO\\_MATCHING\\_GROUPS](#); SQLSTATE: [HY000](#)  
  
Message: None of the groups returned by IAM matches any of the entries from authentication string.
  - Error number: [MY-013815](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_NO\\_GROUPS\\_FOUND](#); SQLSTATE: [HY000](#)  
  
Message: User is not part of any groups. However, account is configured to use group mapping.
  - Error number: [MY-013816](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_NONCE](#); SQLSTATE: [HY000](#)  
  
Message: Received OpenSSL error: %s while authenticating user %s with fingerprint %s in tenancy %s .
-

- 
- Error number: `MY-013817`; Symbol: `ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_1`;  
SQLSTATE: `HY000`  
  
Message: %s: Warning Level 1 (%llu MiB): available=%llu MiB, total=%llu MiB, used=%.2f%%, mysqlid=%llu MiB
  - Error number: `MY-013818`; Symbol: `ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_2`;  
SQLSTATE: `HY000`  
  
Message: %s: Warning Level 2 (%llu MiB): available=%llu MiB, total=%llu MiB, used=%.2f%%, mysqlid=%llu MiB
  - Error number: `MY-013819`; Symbol: `ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_3`;  
SQLSTATE: `HY000`  
  
Message: %s: Warning Level 3 (%llu MiB): available=%llu MiB, total=%llu MiB, used=%.2f%%, mysqlid=%llu MiB
  - Error number: `MY-013820`; Symbol: `ER_GRP_RPL_SET_SINGLE_CONSENSUS_LEADER`;  
SQLSTATE: `HY000`  
  
Message: The member %s:%u, with UUID: %s, was set as the single preferred consensus leader.
  - Error number: `MY-013821`; Symbol: `ER_GRP_RPL_ERROR_SET_SINGLE_CONSENSUS_LEADER`;  
SQLSTATE: `HY000`  
  
Message: Something went wrong trying to set the member %s:%u, with UUID: %s, as the single preferred consensus leader. Please query the `performance_schema.replication_group_communication_information` table to see whether the operation took effect, i.e. whether the preferred consensus leader matches the current primary. If not, consider electing a different primary to try again. Please check the error log and `GCS_DEBUG_TRACE` for more information that may help understanding what went wrong.
  - Error number: `MY-013822`; Symbol: `ER_GRP_RPL_SET_MULTI_CONSENSUS_LEADER`; SQLSTATE: `HY000`  
  
Message: All members were set as consensus leaders.
  - Error number: `MY-013823`; Symbol: `ER_GRP_RPL_ERROR_SET_MULTI_CONSENSUS_LEADER`;  
SQLSTATE: `HY000`  
  
Message: Something went wrong trying to set all members as consensus leaders. Please query the `performance_schema.replication_group_communication_information` table to see whether the operation took effect, i.e. whether the consensus leaders match all members. If not, consider resetting the group communication protocol to a version < 8.0.22, or switch to single-primary mode and back again to multi-primary mode, to try again. Please check the error log and `GCS_DEBUG_TRACE` for more information that may help understanding what went wrong.
  - Error number: `MY-013824`; Symbol: `ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_GRP`;  
SQLSTATE: `HY000`  
  
Message: This member is configured with a `group_replication_paxos_single_leader` option value of '%d' that is different from the group's value ('%d'). This member will now exit the group.
  - Error number: `MY-013825`; Symbol: `ER_MFA_USER_ATTRIBUTES_CORRUPT`; SQLSTATE: `HY000`  
  
Message: Invalid and/or corrupted multi factor authentication methods in `User_attributes` column in `mysql.user` table. "%s".
  - Error number: `MY-013826`; Symbol: `ER_MFA_PLUGIN_NOT_LOADED`; SQLSTATE: `HY000`  
  
Message: Plugin '%s' is not loaded; Ignoring user

- 
- Error number: [MY-013827](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_CHARSET\\_OPTION](#); SQLSTATE: [HY000](#)  
  
Message: %s: The character set %s is deprecated and will be removed in a future release. Please consider using %s instead.
  - Error number: [MY-013828](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_COLLATION\\_OPTION](#); SQLSTATE: [HY000](#)  
  
Message: %s: '%s' is a collation of the deprecated character set %s. Please consider using %s with an appropriate collation instead.
  - Error number: [MY-013829](#); Symbol: [ER\\_REGEX\\_MISSING\\_ICU\\_DATADIR](#); SQLSTATE: [HY000](#)  
  
Message: Missing data directory for ICU regular expressions: %s.
  - Error number: [MY-013830](#); Symbol: [ER\\_IB\\_WARN\\_MANY\\_NON\\_LRU\\_FILES\\_OPENED](#); SQLSTATE: [HY000](#)  
  
Message: More than 90%% of files opened out of the innodb\_open\_files limit are files that are not easy to close. The performance of system may degrade. Consider increasing value of the innodb\_open\_files system variable. There are %zu such files opened out of the total limit for all files opened of %zu.
  - Error number: [MY-013831](#); Symbol: [ER\\_IB\\_MSG\\_TRYING\\_TO\\_OPEN\\_FILE\\_FOR\\_LONG\\_TIME](#); SQLSTATE: [HY000](#)  
  
Message: Trying to open a file for %lld seconds. Configuration only allows for %zu open files. Consider setting innobase\_open\_files higher.
  - Error number: [MY-013832](#); Symbol: [ER\\_GLOBAL\\_CONN\\_LIMIT](#); SQLSTATE: [HY000](#)  
  
Message: Connection closed. Global connection memory limit %llu bytes exceeded. Consumed %llu bytes.
  - Error number: [MY-013833](#); Symbol: [ER\\_CONN\\_LIMIT](#); SQLSTATE: [HY000](#)  
  
Message: Connection closed. Connection memory limit %llu bytes exceeded. Consumed %llu bytes.
  - Error number: [MY-013834](#); Symbol: [ER\\_WARN\\_AUDIT\\_LOG\\_DISABLED](#); SQLSTATE: [HY000](#)  
  
Message: Audit Log is disabled. Enable it with audit\_log\_disable = false.
  - Error number: [MY-013835](#); Symbol: [ER\\_INVALID\\_TLS\\_VERSION](#); SQLSTATE: [HY000](#)  
  
Message: Option --tls-version or --admin-tls-version is set to an invalid value %s.
  - Error number: [MY-013836](#); Symbol: [ER\\_RPL\\_RELAY\\_LOG\\_RECOVERY\\_GTID\\_ONLY](#); SQLSTATE: [HY000](#)  
  
Message: Relay log recovery on channel with GTID\_ONLY=1. The channel will switch to a new relay log and the GTID protocol will be used to replicate unapplied transactions.
  - Error number: [MY-013837](#); Symbol: [ER\\_KEYRING\\_OKV\\_STANDBY\\_SERVER\\_COUNT\\_EXCEEDED](#); SQLSTATE: [HY000](#)  
  
Message: Number of STANDBY\_SERVER values exceeded maximum limit of 64.
  - Error number: [MY-013838](#); Symbol: [ER\\_WARN\\_MIGRATION\\_EMPTY\\_SOURCE\\_KEYRING](#); SQLSTATE: [HY000](#)  
  
Message: Source keyring does not have any keys to migrate.
-

- 
- Error number: `MY-013839`; Symbol: `ER_WARN_CANNOT_PERSIST_SENSITIVE_VARIABLES`; SQLSTATE: `HY000`

Message: Cannot persist SENSITIVE system variables because keyring component support is unavailable and `persist_sensitive_variables_in_plaintext` is set to OFF. Please make sure that keyring services are active and required keys are available.

- Error number: `MY-013840`; Symbol: `ER_CANNOT_INTERPRET_PERSISTED_SENSITIVE_VARIABLES`; SQLSTATE: `HY000`

Message: Cannot interpret persisted SENSITIVE system variables. Please make sure that keyring services are active and required keys are available.

- Error number: `MY-013841`; Symbol: `ER_PERSISTED_VARIABLES_KEYRING_SUPPORT_REQUIRED`; SQLSTATE: `HY000`

Message: Keyring has to be loaded through manifest file in order to support secure storage for persisted variables

- Error number: `MY-013842`; Symbol: `ER_PERSISTED_VARIABLES_MASTER_KEY_NOT_FOUND`; SQLSTATE: `HY000`

Message: Could not find master key %s in keyring

- Error number: `MY-013843`; Symbol: `ER_PERSISTED_VARIABLES_MASTER_KEY_CANNOT_BE_GENERATED`; SQLSTATE: `HY000`

Message: A new master key %s could not be generated

- Error number: `MY-013844`; Symbol: `ER_PERSISTED_VARIABLES_ENCRYPTION_FAILED`; SQLSTATE: `HY000`

Message: Failed to encrypt %s using %s

- Error number: `MY-013845`; Symbol: `ER_PERSISTED_VARIABLES_DECRYPTION_FAILED`; SQLSTATE: `HY000`

Message: Failed to decrypt %s using %s

- Error number: `MY-013846`; Symbol: `ER_PERSISTED_VARIABLES_LACK_KEYRING_SUPPORT`; SQLSTATE: `HY000`

Message: Persisting SENSITIVE variables in encrypted form requires keyring component loaded through manifest file.

- Error number: `MY-013847`; Symbol: `ER_MY_MALLOC_USING_JEMALLOC`; SQLSTATE: `HY000`

Message: Using jemalloc.dll for my\_malloc and ut::malloc etc.

- Error number: `MY-013848`; Symbol: `ER_MY_MALLOC_USING_STD_MALLOC`; SQLSTATE: `HY000`

Message: %s.

- Error number: `MY-013849`; Symbol: `ER_MY_MALLOC_LOADLIBRARY_FAILED`; SQLSTATE: `HY000`

Message: %s.

- Error number: `MY-013850`; Symbol: `ER_MY_MALLOC_GETPROCADDRESS_FAILED`; SQLSTATE: `HY000`

Message: %s.

- Error number: `MY-013851`; Symbol: `ER_ACCOUNT_WITH_EXPIRED_PASSWORD`; SQLSTATE: `HY000`



---

Message: Password for the account '%s'@'%s' has expired. To log in, either change it using a client that supports expired passwords or send the change request to an administrator.

- Error number: [MY-013852](#); Symbol: [ER\\_THREAD\\_POOL\\_PLUGIN\\_STARTED](#); SQLSTATE: [HY000](#)

Message: Thread pool plugin started successfully with parameters: %s

- Error number: [MY-013853](#); Symbol: [ER\\_THREAD\\_POOL\\_DEDICATED\\_LISTENERS\\_INVALID](#); SQLSTATE: [HY000](#)

Message: thread\_pool\_dedicated\_listeners cannot be set unless thread\_pool\_max\_transactions\_limit > 0

- Error number: [MY-013854](#); Symbol: [ER\\_IB\\_DBLWR\\_BYTES\\_INFO](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013855](#); Symbol: [ER\\_IB\\_RDBLWR\\_BYTES\\_INFO](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013856](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_IS\\_EMPTY](#); SQLSTATE: [HY000](#)

Message: The redo log file %s is empty, which indicates it was not generated by InnoDB or become corrupted. Please restore the correct file or try recovering without the redo files, in read-only mode, by providing --innodb-force-recovery=6.

- Error number: [MY-013857](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_TOO\\_SMALL](#); SQLSTATE: [HY000](#)

Message: The redo log file %s is smaller than %llu bytes, which indicates it was not generated by InnoDB or become corrupted. Please restore the correct file.

- Error number: [MY-013858](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_TOO\\_BIG](#); SQLSTATE: [HY000](#)

Message: The redo log file %s is larger than %llu bytes, which indicates it was not generated by InnoDB or become corrupted. Please restore the correct file.

- Error number: [MY-013859](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_HEADER\\_READ\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to read header of the redo log file %s

- Error number: [MY-013860](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_INIT\\_DIR\\_NOT\\_EMPTY\\_WONT\\_INITIALIZE](#); SQLSTATE: [HY000](#)

Message: --initialize specified but the redo log directory %s has redo log files inside. Aborting.

- Error number: [MY-013861](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_INIT\\_DIR\\_LIST\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to list redo log files in the redo log directory %s

- Error number: [MY-013862](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_INIT\\_DIR\\_MISSING\\_SUBDIR](#); SQLSTATE: [HY000](#)

Message: Neither found %s subdirectory, nor %s\* files in %s

- Error number: [MY-013863](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILES\\_CREATED\\_BY\\_CLONE\\_AND\\_READ\\_ONLY\\_MODE](#); SQLSTATE: [HY000](#)

Message: Cannot restore cloned data directory, InnoDB running in read-only mode!

- 
- Error number: `MY-013864`; Symbol: `ER_IB_MSG_LOG_WRITER_WRITE_FAILED`; SQLSTATE: `HY000`  
Message: Error %d encountered when writing to the redo log file: %s.
  - Error number: `MY-013865`; Symbol: `ER_IB_MSG_LOG_WRITER_WAIT_ON_NEW_LOG_FILE`; SQLSTATE: `HY000`  
Message: Redo log writer is waiting for a new redo log file. Consider increasing `innodb_redo_log_capacity`.
  - Error number: `MY-013866`; Symbol: `ER_IB_MSG_RECOVERY_CHECKPOINT_OUTSIDE_LOG_FILE`; SQLSTATE: `HY000`  
Message: Found checkpoint LSN %llu in a redo log file %s, but the file represents range of LSN values [%llu, %llu), so the file is corrupted.
  - Error number: `MY-013867`; Symbol: `ER_IB_MSG_LOG_WRITER_ENTERED_EXTRA_MARGIN`; SQLSTATE: `HY000`  
Message: Redo log is running out of free space, pausing user threads... Consider increasing `innodb_redo_log_capacity`.
  - Error number: `MY-013868`; Symbol: `ER_IB_MSG_LOG_WRITER_EXITED_EXTRA_MARGIN`; SQLSTATE: `HY000`  
Message: Redo log reclaimed some free space, resuming user threads.
  - Error number: `MY-013869`; Symbol: `ER_IB_MSG_LOG_PARAMS_FILE_SIZE_UNUSED`; SQLSTATE: `HY000`  
Message: Ignored deprecated configuration parameter `innodb_log_file_size`. Used `innodb_redo_log_capacity` instead.
  - Error number: `MY-013870`; Symbol: `ER_IB_MSG_LOG_PARAMS_N_FILES_UNUSED`; SQLSTATE: `HY000`  
Message: Ignored deprecated configuration parameter `innodb_log_files_in_group`. Used `innodb_redo_log_capacity` instead.
  - Error number: `MY-013871`; Symbol: `ER_IB_MSG_LOG_UPGRADE_FORCED_RECV`; SQLSTATE: `HY000`  
Message: Cannot upgrade format (v%lu) of redo log files when `innodb-force-recovery > 0`.
  - Error number: `MY-013872`; Symbol: `ER_IB_MSG_LOG_UPGRADE_IN_READ_ONLY_MODE`; SQLSTATE: `HY000`  
Message: Cannot upgrade format (v%lu) of redo log files in read-only mode (`--innodb-read-only`).
  - Error number: `MY-013873`; Symbol: `ER_IB_MSG_LOG_UPGRADE_CLONED_DB`; SQLSTATE: `HY000`  
Message: Cannot upgrade format (v%lu) of redo log files on cloned data directory. Please use an older version of MySQL - recover and shutdown (with `innodb-fast-shutdown < 2`).
  - Error number: `MY-013874`; Symbol: `ER_IB_MSG_LOG_UPGRADE_UNINITIALIZED_FILES`; SQLSTATE: `HY000`  
Message: Cannot upgrade format (v%lu) of redo log files because they are marked as uninitialized. Please use an older version of MySQL - recover and shutdown (with `innodb-fast-shutdown < 2`).
  - Error number: `MY-013875`; Symbol: `ER_IB_MSG_LOG_UPGRADE_CORRUPTION__UNEXPECTED`; SQLSTATE: `HY000`

---

Message: Cannot upgrade format (v%lu) of redo log files when the redo log is corrupted. Please use an older version of MySQL - recover and shutdown (with innodb-fast-shutdown < 2).

- Error number: `MY-013879`; Symbol: `ER_IB_MSG_LOG_FILE_FOREIGN_UUID`; SQLSTATE: `HY000`

Message: The redo log file %s comes from other data directory than redo log file %s.

- Error number: `MY-013880`; Symbol: `ER_IB_MSG_LOG_FILE_INVALID_START_LSN`; SQLSTATE: `HY000`

Message: The redo log file %s has invalid start\_lsn %llu.

- Error number: `MY-013881`; Symbol: `ER_IB_MSG_LOG_FILE_INVALID_LSN_RANGES`; SQLSTATE: `HY000`

Message: The redo log file %s has start\_lsn %llu but expected %llu (end\_lsn of the previous redo log file).

- Error number: `MY-013882`; Symbol: `ER_IB_MSG_LOG_FILE_MISSING_FOR_ID`; SQLSTATE: `HY000`

Message: Missing redo log file %s (with start\_lsn = %llu).

- Error number: `MY-013883`; Symbol: `ER_IB_MSG_LOG_CHECKPOINT_FOUND`; SQLSTATE: `HY000`

Message: The latest found checkpoint is at lsn = %llu in redo log file %s.

- Error number: `MY-013884`; Symbol: `ER_IB_MSG_LOG_FILES_CAPACITY_CHANGED`; SQLSTATE: `HY000`

Message: User has set innodb\_redo\_log\_capacity to %lluM.

- Error number: `MY-013885`; Symbol: `ER_IB_MSG_LOG_FILES_RESIZE_REQUESTED`; SQLSTATE: `HY000`

Message: Redo log has been requested to resize from %lluM to %lluM.

- Error number: `MY-013886`; Symbol: `ER_IB_MSG_LOG_FILES_RESIZE_CANCELLED`; SQLSTATE: `HY000`

Message: Redo log resize has been cancelled.

- Error number: `MY-013887`; Symbol: `ER_IB_MSG_LOG_FILES_RESIZE_FINISHED`; SQLSTATE: `HY000`

Message: Redo log has been resized to %lluM.

- Error number: `MY-013888`; Symbol: `ER_IB_MSG_LOG_FILES_UPGRADE`; SQLSTATE: `HY000`

Message: Upgrading redo log: %lluM, LSN=%llu.

- Error number: `MY-013889`; Symbol: `ER_IB_MSG_LOG_FILE_MARK_CURRENT_AS_INCOMPLETE`; SQLSTATE: `HY000`

Message: Marked the current redo log file %s as incomplete.

- Error number: `MY-013890`; Symbol: `ER_IB_MSG_LOG_FILE_REMOVE_FAILED`; SQLSTATE: `HY000`

Message: Failed to remove redo log file %s.

- Error number: `MY-013891`; Symbol: `ER_IB_MSG_LOG_FILE_RENAME_ON_CREATE_FAILED`; SQLSTATE: `HY000`

---

Message: Failed to rename %s when creating redo log file %s (error: %d)

- Error number: MY-013892; Symbol: ER\_IB\_MSG\_LOG\_FILES\_CREATED\_BY\_UNKNOWN\_CREATOR; SQLSTATE: HY000

Message: Redo log files created by unknown creator %s.

- Error number: MY-013893; Symbol: ER\_IB\_MSG\_LOG\_FILES\_FOUND\_MISSING; SQLSTATE: HY000

Message: Found existing redo log files, but at least one is missing. It is unknown if recovery could reach physically consistent state. Please consider restoring from backup or providing --innodb-force-recovery > 0.

- Error number: MY-013894; Symbol: ER\_IB\_MSG\_LOG\_FILE\_FORMAT\_TOO\_NEW; SQLSTATE: HY000

Message: Found redo log file %s which has format (v%lu) and is stored outside #innodb\_redo.

- Error number: MY-013895; Symbol: ER\_IB\_MSG\_LOG\_FILE\_FORMAT\_TOO\_OLD; SQLSTATE: HY000

Message: Found redo log file %s which has format (v%lu) and is stored inside #innodb\_redo.

- Error number: MY-013896; Symbol: ER\_IB\_MSG\_LOG\_FILE\_DIFFERENT\_FORMATS; SQLSTATE: HY000

Message: Found redo log files with different formats: %s has format v%lu, %s has format v%lu.

- Error number: MY-013897; Symbol: ER\_IB\_MSG\_LOG\_PRE\_8\_0\_30\_MISSING\_FILE0; SQLSTATE: HY000

Message: Missing ib\_logfile0 in the directory %s.

- Error number: MY-013898; Symbol: ER\_IB\_MSG\_LOG\_PFS\_ACQUIRE\_SERVICES\_FAILED; SQLSTATE: HY000

Message: Failed to initialize services required to handle redo log PFS tables.

- Error number: MY-013899; Symbol: ER\_IB\_MSG\_LOG\_PFS\_CREATE\_TABLES\_FAILED; SQLSTATE: HY000

Message: Failed to create redo log PFS tables.

- Error number: MY-013900; Symbol: ER\_IB\_MSG\_LOG\_FILE\_TRUNCATE; SQLSTATE: HY000

Message: Truncating redo log file %s...

- Error number: MY-013901; Symbol: ER\_IB\_MSG\_LOG\_FILE\_UNUSED\_RESIZE\_FAILED; SQLSTATE: HY000

Message: Failed to resize unused redo log file %s to %llu MB (%s).

- Error number: MY-013902; Symbol: ER\_IB\_MSG\_LOG\_FILE\_UNUSED\_REMOVE\_FAILED; SQLSTATE: HY000

Message: Failed to remove unused redo log file %s.

- Error number: MY-013903; Symbol: ER\_IB\_MSG\_LOG\_FILE\_UNUSED\_RENAME\_FAILED; SQLSTATE: HY000

Message: Failed to rename unused redo log file %s to %s.

- 
- Error number: [MY-013904](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_UNUSED\\_MARK\\_AS\\_IN\\_USE\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to mark unused redo log file %s as in use (by renaming to %s).
  - Error number: [MY-013905](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_FILE\\_MARK\\_AS\\_UNUSED\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to mark redo log file %s as unused (by renaming to %s).
  - Error number: [MY-013906](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_PARAMS\\_DEDICATED\\_SERVER\\_IGNORED](#); SQLSTATE: [HY000](#)  
Message: Option `innodb_dedicated_server` is ignored for `innodb_redo_log_capacity`, because `innodb_redo_log_capacity`, `innodb_log_file_size` or `innodb_log_files_in_group` is specified explicitly. Redo log capacity: %lluM.
  - Error number: [MY-013907](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_PARAMS\\_LEGACY\\_USAGE](#); SQLSTATE: [HY000](#)  
Message: Deprecated configuration parameters `innodb_log_file_size` and/or `innodb_log_files_in_group` have been used to compute `innodb_redo_log_capacity=%llu`. Please use `innodb_redo_log_capacity` instead.
  - Error number: [MY-013908](#); Symbol: [ER\\_GRP\\_RPL\\_FAILED\\_TO\\_LOG\\_VIEW\\_CHANGE](#); SQLSTATE: [HY000](#)  
Message: This member was unable to log the `View_change_log_event` into the binary log, hence it will leave the group. Please check that there is available disk space and add the member back to the group.
  - Error number: [MY-013909](#); Symbol: [ER\\_BINLOG\\_CRASH\\_RECOVERY\\_MALFORMED\\_LOG](#); SQLSTATE: [HY000](#)  
Message: Found invalid event sequence while recovering from binary log file '%s', between positions %llu and %llu: %s. The recovery process was stopped early and no transaction was recovered. Side effects may be transactions in an inconsistent state between the binary log and the storage engines, or transactions kept by storage engines in a prepared state (possibly holding locks). Either fix the issues with the binary log or, to release possibly acquired locks, disable the binary log during server recovery. Note that disabling the binary log may lead to loss of transactions that were already acknowledged as successful to client connections and may have been replicated to other servers in the topology.
  - Error number: [MY-013910](#); Symbol: [ER\\_BINLOG\\_CRASH\\_RECOVERY\\_ERROR\\_RETURNED\\_SE](#); SQLSTATE: [HY000](#)  
Message: Storage engines failed to recover one or more transactions. The recovery process was stopped early, check previous messages for the details on failed transactions. Side effects may be transactions in an inconsistent state between the binary log and the storage engines, or transactions kept by storage engines in a prepared state (possibly holding locks). Either fix the issues with the storage engine (out-of-memory, no disk space, etc) or, to release possibly acquired locks held by XA transactions, disable the binary log during server recovery and check consistency between storage engines and binary log files.
  - Error number: [MY-013911](#); Symbol: [ER\\_BINLOG\\_CRASH\\_RECOVERY\\_ENGINE\\_RESULTS](#); SQLSTATE: [HY000](#)  
Message: Crash recovery finished in %s engine. %s
  - Error number: [MY-013912](#); Symbol: [ER\\_BINLOG\\_CRASH\\_RECOVERY\\_COMMIT\\_FAILED](#); SQLSTATE: [HY000](#)
-

---

Message: Failed to commit %s in %s, with failure code %s.

- Error number: [MY-013913](#); Symbol: [ER\\_BINLOG\\_CRASH\\_RECOVERY\\_ROLLBACK\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to rollback %s in %s, with failure code %s.

- Error number: [MY-013914](#); Symbol: [ER\\_BINLOG\\_CRASH\\_RECOVERY\\_PREPARE\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to prepare %s in %s, with failure code %s.

- Error number: [MY-013915](#); Symbol: [ER\\_COMPONENT\\_EE\\_SYS\\_VAR\\_REGISTRATION\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Cannot register variable '%s'. Please check if it is not already registered by another component.

- Error number: [MY-013916](#); Symbol: [ER\\_COMPONENT\\_EE\\_SYS\\_VAR\\_DEREGISTRATION\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Cannot unregister variable '%s'. Please check if it was registered properly in the first place.

- Error number: [MY-013917](#); Symbol: [ER\\_COMPONENT\\_EE\\_FUNCTION\\_REGISTRATION\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Cannot register function '%s'. Please check if it is not already registered.

- Error number: [MY-013918](#); Symbol: [ER\\_COMPONENT\\_EE\\_FUNCTION\\_DEREGISTRATION\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Cannot unregister function '%s'. Please check if it was registered properly in the first place.

- Error number: [MY-013919](#); Symbol: [ER\\_COMPONENT\\_EE\\_FUNCTION\\_INVALID\\_ARGUMENTS](#); SQLSTATE: [HY000](#)

Message: Invalid arguments to function '%s'. Expected values: %s.

- Error number: [MY-013920](#); Symbol: [ER\\_COMPONENT\\_EE\\_FUNCTION\\_INVALID\\_ALGORITHM](#); SQLSTATE: [HY000](#)

Message: Invalid algorithm value '%s' in function %s.

- Error number: [MY-013921](#); Symbol: [ER\\_COMPONENT\\_EE\\_FUNCTION\\_KEY\\_LENGTH\\_OUT\\_OF\\_RANGE](#); SQLSTATE: [HY000](#)

Message: Invalid key length '%d' for function '%s' with algorithm '%s'. Please provide a value between [%d, %d].

- Error number: [MY-013922](#); Symbol: [ER\\_COMPONENT\\_EE\\_FUNCTION\\_PRIVATE\\_KEY\\_GENERATION\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Failed to generate private key of length '%d' with algorithm '%s' in function '%s'. More details about the error would have been logged before this message.

- Error number: [MY-013923](#); Symbol: [ER\\_COMPONENT\\_EE\\_FUNCTION\\_PUBLIC\\_KEY\\_GENERATION\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Failed to generate public key with algorithm '%s' for given private key in function '%s'. More details about the error would have been logged before this message.

- Error number: [MY-013924](#); Symbol: [ER\\_COMPONENT\\_EE\\_DATA\\_LENGTH\\_OUT\\_OF\\_RANGE](#); SQLSTATE: [HY000](#)

---

Message: Invalid data length '%d' (in bytes) for function '%s' with algorithm '%s'. The maximum support data length for given private key is %d (in bytes).

- Error number: [MY-013925](#); Symbol: [ER\\_COMPONENT\\_EE\\_DATA\\_ENCRYPTION\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Could not encrypt data in function '%s' using algorithm '%s'. Data length was '%d' bytes. More details about the error would have been logged before this message.

- Error number: [MY-013926](#); Symbol: [ER\\_COMPONENT\\_EE\\_DATA\\_DECRYPTION\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Could not decrypt data in function '%s' using algorithm '%s'. Data length was '%d' bytes. More details about the error would have been logged before this message.

- Error number: [MY-013927](#); Symbol: [ER\\_COMPONENT\\_EE\\_DATA\\_SIGN\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Could not sign data in function '%s' using algorithm '%s' and digest type '%s'. More details about the error would have been logged before this message.

- Error number: [MY-013928](#); Symbol: [ER\\_COMPONENT\\_EE\\_OPENSSL\\_ERROR](#); SQLSTATE: [HY000](#)

Message: Received OpenSSL error in function '%s' for algorithm '%s': '%s'

- Error number: [MY-013929](#); Symbol: [ER\\_COMPONENT\\_EE\\_INSUFFICIENT\\_LENGTH](#); SQLSTATE: [HY000](#)

Message: In function '%s' with algorithm '%s': insufficient output buffer length '%zu'. Required length '%zu'.

- Error number: [MY-013930](#); Symbol: [ER\\_SYSTEMD\\_NOTIFY\\_DEBUG](#); SQLSTATE: [HY000](#)

Message: %s%s

- Error number: [MY-013931](#); Symbol: [ER\\_TMP\\_SESSION\\_FOR\\_VAR](#); SQLSTATE: [HY000](#)

Message: Setting session values for system variables only makes sense in a user session (failed to set '%s').

- Error number: [MY-013932](#); Symbol: [ER\\_BUILD\\_ID](#); SQLSTATE: [HY000](#)

Message: BuildID[sha1]=%s

- Error number: [MY-013933](#); Symbol: [ER\\_THREAD\\_POOL\\_CANNOT\\_REGISTER\\_DYNAMIC\\_PRIVILEGE](#); SQLSTATE: [HY000](#)

Message: Failed to register dynamic privilege %s.

- Error number: [MY-013934](#); Symbol: [ER\\_IB\\_MSG\\_LOG\\_WRITER\\_WAIT\\_ON\\_CONSUMER](#); SQLSTATE: [HY000](#)

Message: Redo log writer is waiting for %s redo log consumer which is currently reading LSN=%llu preventing reclamation of subsequent portion of the redo log. Consider increasing innodb\_redo\_log\_capacity.

- Error number: [MY-013935](#); Symbol: [ER\\_CONDITIONAL\\_DEBUG](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013936](#); Symbol: [ER\\_IB\\_MSG\\_PARSE\\_OLD\\_REDO\\_INDEX\\_VERSION](#); SQLSTATE: [HY000](#)

Message: Recovery: Generating index information for INSTANT DDL Table in 8.0.29 format

- 
- Error number: `MY-013941`; Symbol: `ER_IB_MSG_CLEAR_INSTANT_DROP_COLUMN_METADATA`; SQLSTATE: `HY000`  
Message: Failed to clear instant drop column metadata for table %s
  - Error number: `MY-013942`; Symbol: `ER_COMPONENT_KEYRING_OCI_OPEN_KEY_FILE`; SQLSTATE: `HY000`  
Message: Cannot open signing key file %s.
  - Error number: `MY-013943`; Symbol: `ER_COMPONENT_KEYRING_OCI_CREATE_PRIVATE_KEY`; SQLSTATE: `HY000`  
Message: Out of memory! Cannot create private key.
  - Error number: `MY-013944`; Symbol: `ER_COMPONENT_KEYRING_OCI_READ_KEY_FILE`; SQLSTATE: `HY000`  
Message: Cannot read signing key file %s.
  - Error number: `MY-013945`; Symbol: `ER_NOTE_COMPONENT_KEYRING_OCI_MISSING_NAME_OR_TYPE`; SQLSTATE: `HY000`  
Message: Incomplete key: missing Name/Type for the Key: %s.
  - Error number: `MY-013946`; Symbol: `ER_WARN_COMPONENT_KEYRING_OCI_DUPLICATE_KEY`; SQLSTATE: `HY000`  
Message: Duplicate key found in keyring with Name: %s and Owner: %s.
  - Error number: `MY-013947`; Symbol: `ER_KEYRING_OCI_PARSE_JSON`; SQLSTATE: `HY000`  
Message: Error parsing JSON response %s.
  - Error number: `MY-013948`; Symbol: `ER_KEYRING_OCI_INVALID_JSON`; SQLSTATE: `HY000`  
Message: Invalid JSON response!
  - Error number: `MY-013949`; Symbol: `ER_KEYRING_OCI_HTTP_REQUEST`; SQLSTATE: `HY000`  
Message: HTTP request failed with error: '%s'
  - Error number: `MY-013950`; Symbol: `ER_THREAD_POOL_SYSVAR_CHANGE`; SQLSTATE: `HY000`  
Message: Variable thread\_pool.%s was updated: %s
  - Error number: `MY-013951`; Symbol: `ER_STACK_BACKTRACE`; SQLSTATE: `HY000`  
Message: %s
  - Error number: `MY-013952`; Symbol: `ER_IB_MSG_BUF_POOL_RESIZE_COMPLETE_CUR_CODE`; SQLSTATE: `HY000`  
Message: Status code %u: Completed
  - Error number: `MY-013953`; Symbol: `ER_IB_MSG_BUF_POOL_RESIZE_PROGRESS_UPDATE`; SQLSTATE: `HY000`  
Message: Status code %u: %u%% complete
  - Error number: `MY-013954`; Symbol: `ER_IB_MSG_BUF_POOL_RESIZE_CODE_STATUS`; SQLSTATE: `HY000`  
Message: Status code %u: %s



- 
- Error number: [MY-013955](#); Symbol: [ER\\_THREAD\\_POOL\\_QUERY\\_THREADS\\_PER\\_GROUP\\_INVALID](#); SQLSTATE: [HY000](#)

Message: Invalid value set to thread\_pool\_query\_threads\_per\_group. Valid value range is %u - %u.
  - Error number: [MY-013956](#); Symbol: [ER\\_THREAD\\_POOL\\_QUERY\\_THRS\\_PER\\_GRP\\_EXCEEDS\\_TXN\\_THR\\_LIMIT](#); SQLSTATE: [HY000](#)

Message: Query threads count(%u) exceeds transaction threads limit(%u) per group. Please use query threads count per group smaller or equal to max transaction threads limit per group
  - Error number: [MY-013957](#); Symbol: [ER\\_IB\\_MSG\\_INVALID\\_PAGE\\_TYPE](#); SQLSTATE: [HY000](#)

Message: Found page type mismatch. Expected %u, found %u, in page: space\_id=%lu page\_no=%lu
  - Error number: [MY-013958](#); Symbol: [ER\\_IB\\_PARALLEL\\_READER\\_WORKER\\_INFO](#); SQLSTATE: [HY000](#)

Message: preader: thread\_id=%zu, n\_threads=%zu, n\_ctx=%zu, one\_range\_per\_thread=%s, n\_index=%zu, index\_list=%s, err=%zu
  - Error number: [MY-013959](#); Symbol: [ER\\_IB\\_BULK\\_LOAD\\_SUBTREE\\_INFO](#); SQLSTATE: [HY000](#)

Message: bulkload: space\_id=%zu, table=%s, index=%s, height=%zu, n\_extents=%zu, n\_pages=%zu
  - Error number: [MY-013960](#); Symbol: [ER\\_IB\\_BULK\\_FLUSHER\\_INFO](#); SQLSTATE: [HY000](#)

Message: bulkflusher: sleep\_count=%zu, sleep\_duration=%zu milliseconds, total\_sleep=%zu milliseconds, pages\_flushed=%zu
  - Error number: [MY-013961](#); Symbol: [ER\\_IB\\_BUFFER\\_POOL\\_OVERUSE](#); SQLSTATE: [HY000](#)

Message: %s: Over 67 percent of the buffer pool (curr\_size=%zu MB) is occupied by lock heaps or the adaptive hash index or BUF\_BLOCK\_MEMORY pages. Check that your transactions do not set too many row locks. Maybe you should make the buffer pool bigger?. Starting the InnoDB Monitor to print diagnostics.
  - Error number: [MY-013962](#); Symbol: [ER\\_IB\\_BUFFER\\_POOL\\_FULL](#); SQLSTATE: [HY000](#)

Message: %s: Over 95 percent of the buffer pool (curr\_size=%zu MB) is occupied by lock heaps or the adaptive hash index or BUF\_BLOCK\_MEMORY pages. Check that your transactions do not set too many row locks. Maybe you should make the buffer pool bigger?. We intentionally generate a seg fault to print a stack trace on Linux!
  - Error number: [MY-013963](#); Symbol: [ER\\_IB\\_DUPLICATE\\_KEY](#); SQLSTATE: [HY000](#)

Message: %s: table=%s, index=%s, n\_uniq=%zu, n\_fields=%zu, lhs=(%s), rhs=(%s)
  - Error number: [MY-013964](#); Symbol: [ER\\_REPLICATION\\_INCOMPATIBLE\\_TABLE\\_WITH\\_GIPK](#); SQLSTATE: [HY000](#)

Message: Failed to apply row event with %d columns, originating from a server of version %s on table '%s.%s', which has %d columns, one of which is a generated implicit primary key. Replication is unsupported when the source server is older than 8.0.30, the replica table has a generated implicit primary key, and there is a difference in column count, not counting the replica's generated implicit primary key. Align the table schemas on source and replica, and restart replication.
  - Error number: [MY-013965](#); Symbol: [ER\\_BULK\\_EXECUTOR\\_INFO](#); SQLSTATE: [HY000](#)

Message: Bulk executor: %s
-

- 
- Error number: [MY-013966](#); Symbol: [ER\\_BULK\\_LOADER\\_INFO](#); SQLSTATE: [HY000](#)  
Message: Bulk loader: %s
  - Error number: [MY-013967](#); Symbol: [ER\\_BULK\\_LOADER\\_FILE\\_CONTAINS\\_LESS\\_LINES\\_THAN\\_IGNORE\\_CLAUSE\\_LOG](#); SQLSTATE: [HY000](#)  
Message: The first file being loaded contained less lines than the ignore clause
  - Error number: [MY-013968](#); Symbol: [ER\\_BULK\\_READER\\_INFO](#); SQLSTATE: [HY000](#)  
Message: Bulk reader: %s
  - Error number: [MY-013969](#); Symbol: [ER\\_BULK\\_READER\\_LIBCURL\\_INIT\\_FAILED\\_LOG](#); SQLSTATE: [HY000](#)  
Message: Bulk reader failed to initialize libcurl
  - Error number: [MY-013970](#); Symbol: [ER\\_BULK\\_READER\\_LIBCURL\\_ERROR\\_LOG](#); SQLSTATE: [HY000](#)  
Message: Bulk reader got libcurl error: %s
  - Error number: [MY-013971](#); Symbol: [ER\\_BULK\\_READER\\_SERVER\\_ERROR\\_LOG](#); SQLSTATE: [HY000](#)  
Message: Bulk reader got error response from server: %ld
  - Error number: [MY-013972](#); Symbol: [ER\\_BULK\\_READER\\_COMMUNICATION\\_ERROR\\_LOG](#); SQLSTATE: [HY000](#)  
Message: Bulk reader got error in communication with source server, check the error log for additional details
  - Error number: [MY-013973](#); Symbol: [ER\\_BULK\\_PARSER\\_MISSING\\_ENCLOSED\\_BY\\_LOG](#); SQLSTATE: [HY000](#)  
Message: Missing ENCLOSED BY character at row %ld in file %s. Add OPTIONALLY to the ENCLOSED BY clause to allow this input.
  - Error number: [MY-013974](#); Symbol: [ER\\_BULK\\_PARSER\\_ROW\\_BUFFER\\_MAX\\_TOTAL\\_COLS\\_EXCEEDED\\_LOG](#); SQLSTATE: [HY000](#)  
Message: The number of input columns that need to be buffered for parsing exceeded predefined buffer max size for file '%s'.
  - Error number: [MY-013975](#); Symbol: [ER\\_BULK\\_PARSER\\_COPY\\_BUFFER\\_SIZE\\_EXCEEDED\\_LOG](#); SQLSTATE: [HY000](#)  
Message: The column data that needed to be copied due to escaped characters exceeded the size of the internal copy buffer for file '%s'.
  - Error number: [MY-013976](#); Symbol: [ER\\_BULK\\_PARSER\\_UNEXPECTED\\_END\\_OF\\_INPUT\\_LOG](#); SQLSTATE: [HY000](#)  
Message: Unexpected end of input found at row %ld in file '%s'. Data for some columns is missing.
  - Error number: [MY-013977](#); Symbol: [ER\\_BULK\\_PARSER\\_UNEXPECTED\\_ROW\\_TERMINATOR\\_LOG](#); SQLSTATE: [HY000](#)  
Message: Unexpected row terminator found at row %ld in file '%s'. Data for some columns is missing.

- 
- Error number: [MY-013978](#); Symbol: [ER\\_BULK\\_PARSER\\_UNEXPECTED\\_CHAR\\_AFTER\\_ENDING\\_ENCLOSED\\_BY\\_LOG](#); SQLSTATE: [HY000](#)  
Message: Unexpected characters after ending ENCLOSED BY character found at row %ld in file '%s'.
  - Error number: [MY-013979](#); Symbol: [ER\\_BULK\\_PARSER\\_UNEXPECTED\\_CHAR\\_AFTER\\_NULL\\_ESCAPE\\_LOG](#); SQLSTATE: [HY000](#)  
Message: Unexpected characters after NULL escape (\N) found at row %ld in file '%s'.
  - Error number: [MY-013980](#); Symbol: [ER\\_BULK\\_PARSER\\_UNEXPECTED\\_CHAR\\_AFTER\\_COLUMN\\_TERMINATOR\\_LOG](#); SQLSTATE: [HY000](#)  
Message: Unexpected characters after column terminator found at row %ld in file '%s'.
  - Error number: [MY-013981](#); Symbol: [ER\\_BULK\\_PARSER\\_INCOMPLETE\\_ESCAPE\\_SEQUENCE\\_LOG](#); SQLSTATE: [HY000](#)  
Message: Unexpected end of input found at row %ld in file '%s' resulting in incomplete escape sequence.
  - Error number: [MY-013982](#); Symbol: [ER\\_LOAD\\_BULK\\_DATA\\_WRONG\\_VALUE\\_FOR\\_FIELD\\_LOG](#); SQLSTATE: [HY000](#)  
Message: Incorrect %s value: '%s' for column '%s' at row %ld in file '%s'
  - Error number: [MY-013983](#); Symbol: [ER\\_LOAD\\_BULK\\_DATA\\_WARN\\_NULL\\_TO\\_NOTNULL\\_LOG](#); SQLSTATE: [HY000](#)  
Message: NULL supplied to NOT NULL column '%s' at row %ld in file '%s'
  - Error number: [MY-013984](#); Symbol: [ER\\_IB\\_BULK\\_LOAD\\_THREAD\\_FAIL](#); SQLSTATE: [HY000](#)  
Message: %s: LOAD BULK DATA thread failure (err=%lu), table=%s, index=%s
  - Error number: [MY-013985](#); Symbol: [ER\\_IB\\_BULK\\_LOAD\\_MERGE\\_FAIL](#); SQLSTATE: [HY000](#)  
Message: %s: Failed to merge sub-trees in LOAD BULK DATA, table=%s, index=%s, details=%s
  - Error number: [MY-013986](#); Symbol: [ER\\_IB\\_LOAD\\_BULK\\_CONCURRENCY\\_REDUCED](#); SQLSTATE: [HY000](#)  
Message: LOAD BULK DATA: Buffer pool size is %zu. Reducing concurrency from %zu to %zu. table=%s.
  - Error number: [MY-013987](#); Symbol: [ER\\_PLUGIN\\_EXCEPTION\\_OPERATION\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: C++ Exception caught while %s the %s plugin: [%s]
  - Error number: [MY-013988](#); Symbol: [ER\\_REQUIRE\\_TABLE\\_PRIMARY\\_KEY\\_CHECK\\_GENERATE\\_WITH\\_GR\\_IN\\_REPO](#); SQLSTATE: [HY000](#)  
Message: Replication configuration appears to be corrupted. On Group Replication channel '%s', setting REQUIRE\_TABLE\_PRIMARY\_KEY\_CHECK to 'GENERATE' is not allowed. Run RESET REPLICA ALL to reset it.
  - Error number: [MY-013989](#); Symbol: [ER\\_CHECK\\_TABLE\\_INSTANT\\_VERSION\\_BIT\\_SET](#); SQLSTATE: [HY000](#)
-

---

Message: Record has both instant and version bit set.

- Error number: `MY-013990`; Symbol: `ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_OLD_GRP`; SQLSTATE: `HY000`

Message: This member is configured with a `group_replication_paxos_single_leader` option value of 1 and it is trying to join a group with Communication Protocol Version below 8.0.27. In order to join this group, `group_replication_paxos_single_leader` value must be configured to the value 0. This member will now exit the group.

- Error number: `MY-013991`; Symbol: `ER_IB_WRN_IGNORE_REDO_LOG_CAPACITY`; SQLSTATE: `HY000`

Message: Ignored the `innodb-redo-log-capacity` option in the InnoDB read-only mode. Server is using active redo log files.

- Error number: `MY-013992`; Symbol: `ER_IB_PRIMARY_KEY_IS_INSTANT`; SQLSTATE: `HY000`

Message: Unexpected INSTANTLY Added / Dropped column: '%s' at position %lu for Table '%s', Index '%s' while getting Primary Key for row logging

- Error number: `MY-013993`; Symbol: `ER_THREAD_POOL_IDLE_CONNECTION_CLOSED`; SQLSTATE: `HY000`

Message: %s

- Error number: `MY-013994`; Symbol: `ER_IB_HIDDEN_NAME_CONFLICT`; SQLSTATE: `HY000`

Message: Column name %s and internally generated INSTANT DROP column name %s is causing a conflict.

- Error number: `MY-013995`; Symbol: `ER_IB_DICT_INVALID_COLUMN_POSITION`; SQLSTATE: `HY000`

Message: Field number: %llu too large, Total fields in Record: %zu.

- Error number: `MY-013996`; Symbol: `ER_IB_DICT_LOG_TABLE_INFO`; SQLSTATE: `HY000`

Message: %s

- Error number: `MY-013997`; Symbol: `ER_RPL_ASYNC_NEXT_FAILOVER_CHANNEL_SELECTED`; SQLSTATE: `HY000`

Message: The connection has timed out after %lu retries connecting to '%s@%s:%d'%s, and therefore the MySQL server is going to attempt an asynchronous replication connection failover, to '%s@%s:%d'

- Error number: `MY-013998`; Symbol: `ER_RPL_REPLICA_SOURCE_UUID_HAS_NOT_CHANGED`; SQLSTATE: `HY000`

Message: The Replica which was connected to source '%s:%d', is now connected to new source '%s:%d', but still has the same server\_uuid %s.

- Error number: `MY-013999`; Symbol: `ER_RPL_REPLICA_SOURCE_UUID_HAS_CHANGED_HOST_PORT_UNCHANGED`; SQLSTATE: `HY000`

Message: The server\_uuid for source server '%s:%d' has changed from %s to %s. This should not happen unless you have changed it manually.

- Error number: `MY-014000`; Symbol: `ER_RPL_REPLICA_SOURCE_UUID_HOST_PORT_HAS_CHANGED`; SQLSTATE: `HY000`

---

Message: The source server has changed from '\%s:%d\' with server\_uuid %s, to '\%s:%d\' with server\_uuid %s.

- Error number: [MY-014001](#); Symbol: [ER\\_RPL\\_REPLICA\\_CONNECTED\\_TO\\_SOURCE\\_RPL\\_STARTED\\_FILE\\_BASED](#); SQLSTATE: [HY000](#)

Message: Replica receiver thread%s: connected to source '\%s@%s:%d\' with server\_uuid=%s, server\_id=%d. Starting replication from file '%s', position '%s'.

- Error number: [MY-014002](#); Symbol: [ER\\_RPL\\_REPLICA\\_CONNECTED\\_TO\\_SOURCE\\_RPL\\_STARTED\\_GTID\\_BASED](#); SQLSTATE: [HY000](#)

Message: Replica receiver thread%s: connected to source '\%s@%s:%d\' with server\_uuid=%s, server\_id=%d. Starting GTID-based replication.

- Error number: [MY-014003](#); Symbol: [ER\\_IB\\_INDEX\\_LOADER\\_DONE](#); SQLSTATE: [HY000](#)

Message: Loader::build\_all(): Completed building %zu indexes for old\_table=%s, new\_table=%s, err=%zu.

- Error number: [MY-014004](#); Symbol: [ER\\_IB\\_INDEX\\_BUILDER\\_DONE](#); SQLSTATE: [HY000](#)

Message: Builder::finish(): Completed building index=%s of table=%s, err=%zu.

- Error number: [MY-014005](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_USER\\_DEFINED\\_COLLATIONS\\_OPTION](#); SQLSTATE: [HY000](#)

Message: %s: '%s' is a user defined collation. User defined collations are deprecated and will be removed in a future release. Consider using a compiled collation instead.

- Error number: [MY-014006](#); Symbol: [ER\\_IB\\_INDEX\\_BUILDER\\_INIT](#); SQLSTATE: [HY000](#)

Message: Builder::init(): Initialize for building index=%s of table=%s, n\_threads=%zu, sort buffer size=%zu bytes, i/o buffer size=%zu bytes.

- Error number: [MY-014007](#); Symbol: [ER\\_IB\\_SELECT\\_COUNT\\_STAR](#); SQLSTATE: [HY000](#)

Message: SELECT COUNT(\*) FROM table=%s, n\_threads=%zu, n\_partitions=%zu.

- Error number: [MY-014008](#); Symbol: [ER\\_IB\\_INDEX\\_LOG\\_VERSION\\_MISMATCH](#); SQLSTATE: [HY000](#)

Message: Index log version %u did not match. Max index version is %u. Recovery can't continue. Please make sure server is not starting up with the datadir generated in future version.

- Error number: [MY-014009](#); Symbol: [ER\\_WARN\\_COMPONENTS\\_INFRASTRUCTURE\\_MANIFEST\\_MULTIPLE\\_KEYRING](#); SQLSTATE: [HY000](#)

Message: Multiple keyring component URNs '%s' found in manifest file '%s'. Only one keyring component can be loaded at a time.

- Error number: [MY-014010](#); Symbol: [ER\\_GRP\\_RPL\\_HAS\\_STARTED](#); SQLSTATE: [HY000](#)

Message: Plugin 'group\_replication' has been started.

- Error number: [MY-014011](#); Symbol: [ER\\_CHECK\\_TABLE\\_MIN\\_REC\\_FLAG\\_SET](#); SQLSTATE: [HY000](#)

Message: Minimum record flag is wrongly set to rec on page '%lu' at level '%lu' for index '%s' of table '%s'.

- Error number: [MY-014012](#); Symbol: [ER\\_CHECK\\_TABLE\\_MIN\\_REC\\_FLAG\\_NOT\\_SET](#); SQLSTATE: [HY000](#)

---

Message: Minimum record flag is not set to first rec on page '%lu' at level '%lu' for index '%s' of table '%s'.

- Error number: MY-014013; Symbol: ER\_NOTE\_COMPONENT\_SLOT\_REGISTRATION\_SUCCESS; SQLSTATE: HY000

Message: Successfully registered slot '%d' for component '%s'.

- Error number: MY-014014; Symbol: ER\_NOTE\_COMPONENT\_SLOT\_DEREGISTRATION\_SUCCESS; SQLSTATE: HY000

Message: Successfully de-registered slot '%d' from component '%s'.

- Error number: MY-014015; Symbol: ER\_WARN\_CANNOT\_FREE\_COMPONENT\_DATA\_DEALLOCATION\_FAILED; SQLSTATE: HY000

Message: Cannot free resources stored by component '%s' in thread with ID: '%d'. Component failed to free required resources.

- Error number: MY-014016; Symbol: ER\_IB\_RESURRECT\_TRX\_INSERT; SQLSTATE: HY000

Message: Transaction ID: %lu found for resurrecting inserts

- Error number: MY-014017; Symbol: ER\_IB\_RESURRECT\_TRX\_UPDATE; SQLSTATE: HY000

Message: Transaction ID: %lu found for resurrecting updates

- Error number: MY-014018; Symbol: ER\_IB\_RESURRECT\_IDENTIFY\_TABLE\_TO\_LOCK; SQLSTATE: HY000

Message: Identified table ID: %lu to acquire lock

- Error number: MY-014019; Symbol: ER\_IB\_RESURRECT\_ACQUIRE\_TABLE\_LOCK; SQLSTATE: HY000

Message: Acquired lock on table ID: %lu, name: %s

- Error number: MY-014020; Symbol: ER\_IB\_RESURRECT\_RECORD\_PROGRESS; SQLSTATE: HY000

Message: Records read: %lu - Pages read: %lu

- Error number: MY-014021; Symbol: ER\_IB\_RESURRECT\_RECORD\_COMPLETE; SQLSTATE: HY000

Message: Total records resurrected: %lu - Total pages read: %lu - Total tables acquired: %lu

- Error number: MY-014022; Symbol: ER\_IB\_RESURRECT\_TRX\_INSERT\_COMPLETE; SQLSTATE: HY000

Message: Resurrected %lu transactions doing inserts.

- Error number: MY-014023; Symbol: ER\_IB\_RESURRECT\_TRX\_UPDATE\_COMPLETE; SQLSTATE: HY000

Message: Resurrected %lu transactions doing updates.

- Error number: MY-014024; Symbol: ER\_AUTHENTICATION\_OCI\_INVALID\_TOKEN; SQLSTATE: HY000

Message: Invalid security token provided by '%s' for '%s'@'%s': %s.

- Error number: MY-014025; Symbol: ER\_AUTHENTICATION\_OCI\_TOKEN\_DETAILS\_MISMATCH; SQLSTATE: HY000

---

Message: Unknown user/tenancy (user: %s tenancy: %s) found in security token provided by '%s' for '%s'@'%s'.

- Error number: [MY-014026](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_TOKEN\\_NOT\\_VERIFIED](#); SQLSTATE: [HY000](#)

Message: Verification failed for security token provided by '%s' for '%s'@'%s': %s.

- Error number: [MY-014027](#); Symbol: [ER\\_AUTHENTICATION\\_OCI\\_DOWNLOAD\\_IDDP\\_PUBLIC\\_KEY](#); SQLSTATE: [HY000](#)

Message: Could not download IDDP Public key. Please check if security token provided by '%s' for '%s'@'%s' is valid.

- Error number: [MY-014029](#); Symbol: [ER\\_SYS\\_VAR\\_REGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot register variable '%s'. Please check if it is not already registered by another component.

- Error number: [MY-014030](#); Symbol: [ER\\_SYS\\_VAR\\_DEREGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot unregister variable '%s'. Please check if it was registered properly in the first place.

- Error number: [MY-014031](#); Symbol: [ER\\_UDF\\_REGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot register function '%s'. Please check if it is not already registered by another component.

- Error number: [MY-014032](#); Symbol: [ER\\_UDF\\_DEREGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot unregister function '%s'. Please check if it was registered properly in the first place.

- Error number: [MY-014033](#); Symbol: [ER\\_PRIVILEGE\\_REGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot register privilege '%s'. Please check if it is not already registered.

- Error number: [MY-014034](#); Symbol: [ER\\_PRIVILEGE\\_DEREGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot unregister privilege '%s'. Please check if it was registered properly in the first place.

- Error number: [MY-014035](#); Symbol: [ER\\_UDF\\_EXEC\\_FAILURE](#); SQLSTATE: [HY000](#)

Message: Error while executing UDF %s.

- Error number: [MY-014036](#); Symbol: [ER\\_UDF\\_EXEC\\_FAILURE\\_REASON](#); SQLSTATE: [HY000](#)

Message: Error while executing UDF %s: %s.

- Error number: [MY-014037](#); Symbol: [ER\\_COMPONENT\\_SERVICE\\_CALL](#); SQLSTATE: [HY000](#)

Message: %s failed.

- Error number: [MY-014038](#); Symbol: [ER\\_COMPONENT\\_SERVICE\\_CALL\\_RESULT](#); SQLSTATE: [HY000](#)

Message: %s failed with %u.

- Error number: [MY-014039](#); Symbol: [ER\\_COMPONENT\\_LOCK](#); SQLSTATE: [HY000](#)

Message: Lock failed at %s : %u.

- Error number: [MY-014040](#); Symbol: [ER\\_COMPONENT\\_UNLOCK](#); SQLSTATE: [HY000](#)

---

Message: Lock from %s : %u failed to unlock.

- Error number: MY-014041; Symbol: ER\_COMPONENT\_MASKING\_OTHER\_ERROR; SQLSTATE: HY000

Message: Masking component error: '%s'.

- Error number: MY-014042; Symbol: ER\_COMPONENT\_MASKING\_ABI; SQLSTATE: HY000

Message: %s failed.

- Error number: MY-014043; Symbol: ER\_COMPONENT\_MASKING\_ABI\_REASON; SQLSTATE: HY000

Message: %s failed because %s.

- Error number: MY-014044; Symbol: ER\_COMPONENT\_MASKING\_RANDOM\_CREATE; SQLSTATE: HY000

Message: Creation of random context failed.

- Error number: MY-014045; Symbol: ER\_COMPONENT\_MASKING\_RANDOM\_CREATE\_REASON; SQLSTATE: HY000

Message: Creation of random context failed because %s.

- Error number: MY-014046; Symbol: ER\_COMPONENT\_MASKING\_CANNOT\_ACCESS\_TABLE; SQLSTATE: HY000

Message: Cannot access %s.%s table.

- Error number: MY-014047; Symbol: ER\_REDUCED\_DBLWR\_FILE\_CORRUPTED; SQLSTATE: HY000

Message: Cannot recover from detect\_only doublewrite buffer as page %u from batch doublewrite file is corrupted.

- Error number: MY-014048; Symbol: ER\_REDUCED\_DBLWR\_PAGE\_FOUND; SQLSTATE: HY000

Message: Database page corruption of tablespace %s space\_id: %u page\_num: %u. Cannot recover it from the doublewrite buffer because it was written in detect\_only-doublewrite mode.

- Error number: MY-014049; Symbol: ER\_CONN\_INIT\_CONNECT\_IGNORED\_MFA; SQLSTATE: HY000

Message: init\_connect variable is ignored for user: %s host: %s due to multi-factor registration required sandboxing

- Error number: MY-014050; Symbol: ER\_SECONDARY\_ENGINE\_DDL\_FAILED; SQLSTATE: HY000

Message: Execution of alter table %s %s failed because %s.

- Error number: MY-014051; Symbol: ER\_THREAD\_POOL\_CONNECTION\_REPORT; SQLSTATE: HY000

Message: TP conn (port: managed(delta), active, opened, closed, added, dropped): %s

- Error number: MY-014052; Symbol: ER\_WARN\_SCHEDULED\_TASK\_RUN\_FAILED; SQLSTATE: HY000

Message: Scheduled run of task %s failed

- Error number: MY-014053; Symbol: ER\_AUDIT\_LOG\_INVALID\_FLUSH\_INTERVAL\_VALUE; SQLSTATE: HY000



---

Message: Invalid flush interval specified: %u. Valid values are 0 (off) or greater than or equal to %d.  
Adjusting to %d

- Error number: [MY-014054](#); Symbol: [ER\\_LOG\\_CANNOT\\_PURGE\\_BINLOG\\_WITH\\_BACKUP\\_LOCK](#); SQLSTATE: [HY000](#)

Message: Could not purge binary logs since another session is executing LOCK INSTANCE FOR BACKUP. Wait for that session to release the lock.

- Error number: [MY-014055](#); Symbol: [ER\\_CONVERT\\_MULTI\\_VALUE](#); SQLSTATE: [HY000](#)

Message: Multi-values cannot be converted to MySQL format: %s

- Error number: [MY-014056](#); Symbol: [ER\\_IB\\_DDL\\_CONVERT\\_HEAP\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)

Message: Heap required to convert columns is not present.

- Error number: [MY-014057](#); Symbol: [ER\\_SERVER\\_DOWNGRADE\\_FROM\\_VERSION](#); SQLSTATE: [HY000](#)

Message: MySQL server downgrading from version '%u' to '%u'.

- Error number: [MY-014058](#); Symbol: [ER\\_BEYOND\\_SERVER\\_DOWNGRADE\\_THRESHOLD](#); SQLSTATE: [HY000](#)

Message: Invalid MySQL server downgrade: Cannot downgrade from %u to %u. Target MySQL server version is lower than the server downgrade threshold %u.

- Error number: [MY-014059](#); Symbol: [ER\\_BEYOND\\_SERVER\\_UPGRADE\\_THRESHOLD](#); SQLSTATE: [HY000](#)

Message: Invalid MySQL server upgrade: Cannot upgrade from %u to %u. Target MySQL server version is lower than the server upgrade threshold %u.

- Error number: [MY-014060](#); Symbol: [ER\\_INVALID\\_SERVER\\_UPGRADE\\_NOT\\_LTS](#); SQLSTATE: [HY000](#)

Message: Invalid MySQL server upgrade: Cannot upgrade from %u to %u. Upgrade to next major version is only allowed from the last LTS release, which version %u is not.

- Error number: [MY-014061](#); Symbol: [ER\\_INVALID\\_SERVER\\_DOWNGRADE\\_NOT\\_PATCH](#); SQLSTATE: [HY000](#)

Message: Invalid MySQL server downgrade: Cannot downgrade from %u to %u. Downgrade is only permitted between patch releases.

- Error number: [MY-014062](#); Symbol: [ER\\_FAILED\\_GET\\_DD\\_PROPERTY](#); SQLSTATE: [HY000](#)

Message: Failed to get the data dictionary property %s.

- Error number: [MY-014063](#); Symbol: [ER\\_FAILED\\_SET\\_DD\\_PROPERTY](#); SQLSTATE: [HY000](#)

Message: Failed to set the data dictionary property %s.

- Error number: [MY-014064](#); Symbol: [ER\\_SERVER\\_DOWNGRADE\\_STATUS](#); SQLSTATE: [HY000](#)

Message: Server downgrade from '%d' to '%d' %s.

- Error number: [MY-014065](#); Symbol: [ER\\_INFORMATION\\_SCHEMA\\_VERSION\\_CHANGE](#); SQLSTATE: [HY000](#)

Message: %s information schema from version %u to %u.

- 
- Error number: [MY-014066](#); Symbol: [ER\\_PERFORMANCE\\_SCHEMA\\_VERSION\\_CHANGE](#); SQLSTATE: [HY000](#)  
Message: %s performance schema from version %u to %u.
  - Error number: [MY-014067](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_OR\\_BLOCKED\\_CIPHER](#); SQLSTATE: [HY000](#)  
Message: Value for option '%s' contains cipher '%s' that is either blocked or deprecated (and will be removed in a future release). Please refer to the documentation for more details.
  - Error number: [MY-014068](#); Symbol: [ER\\_IB\\_MSG\\_DDL\\_FAIL\\_NO\\_BUILDER](#); SQLSTATE: [HY000](#)  
Message: DDL failed as Builder is already freed. Builder: state=%u, error\_state=%u. Index: id=%zu, name='%s', space\_id=%u, page=%u. Table: old\_name='%s', new\_name='%s'.
  - Error number: [MY-014069](#); Symbol: [ER\\_GRP\\_RPL\\_MEMBER\\_INFO\\_DOES\\_NOT\\_EXIST](#); SQLSTATE: [HY000](#)  
Message: Member identified %s: '%s' does not exist on Group Replication membership during %s.
  - Error number: [MY-014070](#); Symbol: [ER\\_USAGE\\_DEPRECATION\\_COUNTER](#); SQLSTATE: [HY000](#)  
Message: Deprecated '%s' used %s times, last time used '%s'.
  - Error number: [MY-015000](#); Symbol: [ER\\_LANGUAGE\\_COMPONENT\\_INFO](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-015001](#); Symbol: [ER\\_LANGUAGE\\_COMPONENT\\_WARNING](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-015002](#); Symbol: [ER\\_LANGUAGE\\_COMPONENT\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-015003](#); Symbol: [ER\\_IB\\_BULK\\_FLUSHER\\_PUNCH\\_HOLE](#); SQLSTATE: [HY000](#)  
Message: bulkflusher: Failed to punch hole: table=%s, index=%s, space\_id=%zu, page\_no=%zu, disk\_page\_size=%zu, hole\_size=%zu, file=%s, err=%zu
  - Error number: [MY-015004](#); Symbol: [ER\\_GRP\\_RPL\\_CONN\\_KILLED](#); SQLSTATE: [HY000](#)  
Message: %s as the client session was killed.
  - Error number: [MY-015005](#); Symbol: [ER\\_WARN\\_CANT\\_OPEN\\_CERTIFICATE](#); SQLSTATE: [HY000](#)  
Message: Cannot open certificate %s. Please check the certificate
  - Error number: [MY-015006](#); Symbol: [ER\\_FAILED\\_TO\\_VALIDATE\\_CERTIFICATES\\_SERVER\\_EXIT](#); SQLSTATE: [HY000](#)  
Message: Certificate validation has failed. Stopping the server as tls-certificates-enforced-validation is enabled
  - Error number: [MY-015007](#); Symbol: [ER\\_WARN\\_CA\\_CERT\\_VERIFY\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: CA certificate/certificates is invalid. Please check logs for more details.
  - Error number: [MY-015008](#); Symbol: [ER\\_WARN\\_FAILED\\_TO\\_SETUP\\_TLS](#); SQLSTATE: [HY000](#)  
Message: Internal TLS error %s:%s:%d:%s

- 
- Error number: [MY-015009](#); Symbol: [ER\\_TLS\\_LIBRARY\\_ERROR\\_INTERNAL](#); SQLSTATE: [HY000](#)  
Message: Failed to set up TLS. Check logs for details
  - Error number: [MY-015010](#); Symbol: [ER\\_SERVER\\_CERT\\_VERIFY\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Server certificate %s verification has failed. Check logs for more details
  - Error number: [MY-015011](#); Symbol: [ER\\_WARN\\_CERTIFICATE\\_ERROR\\_STRING](#); SQLSTATE: [HY000](#)  
Message: Failed to validate certificate %s because %s
  - Error number: [MY-015012](#); Symbol: [ER\\_TELEMETRY\\_INFO](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-015013](#); Symbol: [ER\\_TELEMETRY\\_WARNING](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-015014](#); Symbol: [ER\\_TELEMETRY\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: %s
  - Error number: [MY-015015](#); Symbol: [ER\\_SRV\\_START](#); SQLSTATE: [HY000](#)  
Message: MySQL Server - start.
  - Error number: [MY-015016](#); Symbol: [ER\\_SRV\\_END](#); SQLSTATE: [HY000](#)  
Message: MySQL Server - end.
  - Error number: [MY-015017](#); Symbol: [ER\\_SRV\\_INIT\\_START](#); SQLSTATE: [HY000](#)  
Message: MySQL Server Initialization - start.
  - Error number: [MY-015018](#); Symbol: [ER\\_SRV\\_INIT\\_END](#); SQLSTATE: [HY000](#)  
Message: MySQL Server Initialization - end.
  - Error number: [MY-015019](#); Symbol: [ER\\_PLUGINS\\_SHUTDOWN\\_START](#); SQLSTATE: [HY000](#)  
Message: MySQL Server: Plugins Shutdown - start.
  - Error number: [MY-015020](#); Symbol: [ER\\_PLUGINS\\_SHUTDOWN\\_END](#); SQLSTATE: [HY000](#)  
Message: MySQL Server: Plugins Shutdown - end.
  - Error number: [MY-015021](#); Symbol: [ER\\_COMPONENTS\\_INFRASTRUCTURE\\_SHUTDOWN\\_START](#); SQLSTATE: [HY000](#)  
Message: MySQL Server: Components Shutdown - start.
  - Error number: [MY-015022](#); Symbol: [ER\\_COMPONENTS\\_INFRASTRUCTURE\\_SHUTDOWN\\_END](#); SQLSTATE: [HY000](#)  
Message: MySQL Server: Components Shutdown - end (with return value = %d).
  - Error number: [MY-015023](#); Symbol: [ER\\_CONNECTIONS\\_SHUTDOWN\\_START](#); SQLSTATE: [HY000](#)  
Message: MySQL Server: Closing Connections - start.
  - Error number: [MY-015024](#); Symbol: [ER\\_CONNECTIONS\\_SHUTDOWN\\_END](#); SQLSTATE: [HY000](#)

---

Message: MySQL Server: Closing Connections - end.

- Error number: [MY-015025](#); Symbol: [ER\\_THREAD\\_STILL\\_ALIVE](#); SQLSTATE: [HY000](#)

Message: Waiting for forceful disconnection of Thread (ID %ld) to end.

- Error number: [MY-015026](#); Symbol: [ER\\_NUM\\_THREADS\\_STILL\\_ALIVE](#); SQLSTATE: [HY000](#)

Message: Waiting for forceful disconnection of %ld thread(s) to end.

- Error number: [MY-015027](#); Symbol: [ER\\_GRP\\_RPL\\_MYSQL\\_NETWORK\\_PROVIDER\\_SERVER\\_ERROR\\_COMMAND\\_ERR](#); SQLSTATE: [HY000](#)

Message: Failed to accept a MySQL connection for Group Replication. %s. Please retry.

- Error number: [MY-015028](#); Symbol: [ER\\_COMPONENT\\_KEYRING\\_OCI\\_INVALID\\_CONFIG\\_VAR](#); SQLSTATE: [HY000](#)

Message: Invalid value of argument %s (%s).

- Error number: [MY-015029](#); Symbol: [ER\\_WARN\\_OPTION\\_RESET\\_AND\\_IGNORED\\_DURING\\_INITIALIZE](#); SQLSTATE: [HY000](#)

Message: Ignoring a non-default value for %s during --initialize.

- Error number: [MY-015030](#); Symbol: [ER\\_FIREWALL\\_SCHEDULER\\_REGISTER\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Automatic registration of the scheduler failed.

- Error number: [MY-015031](#); Symbol: [ER\\_FIREWALL\\_INVALID\\_RELOAD\\_INTERVAL\\_VALUE](#); SQLSTATE: [HY000](#)

Message: Invalid reload interval specified: %lu. Valid values are 0 (off) or greater than or equal to %d. Adjusting to %d.

- Error number: [MY-015032](#); Symbol: [ER\\_WARN\\_DEPRECATED\\_DYNAMIC\\_PRIV\\_FOR\\_USER](#); SQLSTATE: [HY000](#)

Message: '%s' (granted to '%s@%s') is deprecated and will be removed in a future release.

- Error number: [MY-015033](#); Symbol: [ER\\_BULK\\_MULTI\\_READER\\_INFO](#); SQLSTATE: [HY000](#)

Message: Bulk Multi Reader: %s

- Error number: [MY-015034](#); Symbol: [ER\\_BULK\\_MERGE\\_LOADER\\_INFO](#); SQLSTATE: [HY000](#)

Message: Bulk Merge Loader: %s

- Error number: [MY-015035](#); Symbol: [ER\\_BULK\\_SORTING\\_LOADER\\_INFO](#); SQLSTATE: [HY000](#)

Message: Bulk Sorting Loader: %s

- Error number: [MY-015036](#); Symbol: [ER\\_BULK\\_WRITER\\_INFO](#); SQLSTATE: [HY000](#)

Message: Bulk Writer: %s

- Error number: [MY-015037](#); Symbol: [ER\\_BULK\\_WRITER\\_LIBCURL\\_INIT\\_FAILED\\_LOG](#); SQLSTATE: [HY000](#)

Message: Bulk writer failed to initialize libcurl

- Error number: [MY-015038](#); Symbol: [ER\\_BULK\\_WRITER\\_LIBCURL\\_ERROR\\_LOG](#); SQLSTATE: [HY000](#)

---

Message: Bulk writer got libcurl error: %s

- Error number: [MY-015039](#); Symbol: [ER\\_IB\\_WRONG\\_PAGE\\_ID](#); SQLSTATE: [HY000](#)

Message: Detected wrong page\_id: buf\_block\_t[space\_id=%zu, page\_no=%zu],  
buf\_frame\_t[space\_id=%zu, page\_no=%zu], file=%s

- Error number: [MY-015040](#); Symbol: [ER\\_IB\\_FIXED\\_PAGE\\_ID](#); SQLSTATE: [HY000](#)

Message: Fixed wrong page\_id with sync read: buf\_block\_t[space\_id=%zu, page\_no=%zu],  
buf\_frame\_t[space\_id=%zu, page\_no=%zu], file=%s, retry=%zu

- Error number: [MY-015041](#); Symbol: [ER\\_IB\\_WRONG\\_PAGEID\\_AFTER\\_SYNC\\_READ](#); SQLSTATE: [HY000](#)

Message: Wrong page\_id after sync read: buf\_block\_t[space\_id=%zu, page\_no=%zu],  
buf\_frame\_t[space\_id=%zu, page\_no=%zu], file=%s, retry=%zu

- Error number: [MY-015042](#); Symbol: [ER\\_IB\\_SYNC\\_READ\\_FAILED](#); SQLSTATE: [HY000](#)

Message: Sync read to fix wrong page\_id failed: buf\_block\_t[space\_id=%zu, page\_no=%zu], file=  
%s, err=%zu, retry=%zu

- Error number: [MY-015043](#); Symbol: [ER\\_START\\_REPLICA\\_CHANNEL\\_INVALID\\_CONFIGURATION\\_LOG](#); SQLSTATE: [HY000](#)

Message: Cannot start replication channel '%s' because %s.

- Error number: [MY-015044](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_CERTIFIER\\_MESSAGE\\_LARGE](#); SQLSTATE: [HY000](#)

Message: The certification information, part of the required information to the new member join the group, is too big and cannot be send. Please wait until the value of the column COUNT\_TRANSACTIONS\_ROWS\_VALIDATING of the table performance\_schema.replication\_group\_member\_stats decreases and try to join the new member again.

- Error number: [MY-015045](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_METADATA\\_SENDER\\_IS\\_REMOTE](#); SQLSTATE: [HY000](#)

Message: The member %s:%u will be the one sending the recovery metadata message.

- Error number: [MY-015046](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_METADATA\\_SENDER](#); SQLSTATE: [HY000](#)

Message: This member %s:%u will be the one sending the recovery metadata message.

- Error number: [MY-015047](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_ERROR\\_COMPRESS\\_INITIALIZE](#); SQLSTATE: [HY000](#)

Message: Error initializing the %s compression context. Data cannot be compressed.

- Error number: [MY-015048](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_COMPRESS\\_PROCESS](#); SQLSTATE: [HY000](#)

Message: Error while compressing data using %s compression. Data cannot be decompressed.

- Error number: [MY-015049](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_UNKNOWN\\_COMPRESSION\\_TYPE](#); SQLSTATE: [HY000](#)

Message: Error unknown Compression Library requested.

- 
- Error number: [MY-015050](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_COMPRESS\\_EXCEEDS\\_MAX\\_SIZE](#); SQLSTATE: [HY000](#)

Message: Error while compressing data using %s compression. The operation could not be performed as buffer size exceeded configured maximum size. Please wait until the value of the column `COUNT_TRANSACTIONS_ROWS_VALIDATING` of the table `performance_schema.replication_group_member_stats` decreases and try to join the new member again.

- Error number: [MY-015051](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_COMPRESS\\_OUT\\_OF\\_MEMORY](#); SQLSTATE: [HY000](#)

Message: Error while compressing data using %s compression. The operation could not be performed as memory allocation failed.

- Error number: [MY-015052](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_ERROR\\_DECOMPRESS\\_INITIALIZE](#); SQLSTATE: [HY000](#)

Message: Error initializing the %s decompression context. Data cannot be decompressed.

- Error number: [MY-015053](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_DECOMPRESS\\_EXCEEDS\\_MAX\\_SIZE](#); SQLSTATE: [HY000](#)

Message: Error while decompressing data using %s compression. The operation could not be performed as buffer size exceeded configured maximum size. Please wait until the value of the column `COUNT_TRANSACTIONS_ROWS_VALIDATING` of the table `performance_schema.replication_group_member_stats` decreases and try to join the new member again.

- Error number: [MY-015054](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_DECOMPRESS\\_OUT\\_OF\\_MEMORY](#); SQLSTATE: [HY000](#)

Message: Error while decompressing data using %s compression. The operation could not be performed as memory allocation failed.

- Error number: [MY-015055](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_DECOMPRESS\\_TRUNCATED](#); SQLSTATE: [HY000](#)

Message: Error while decompressing data using %s compression. The operation could not be performed as all the input provided to decompress is consumed, but the decompressed output produced is less than required.

- Error number: [MY-015056](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_DECOMPRESS\\_CORRUPTED](#); SQLSTATE: [HY000](#)

Message: Error while decompressing data using %s compression. The operation could not be performed as the compression library reported an error.

- Error number: [MY-015057](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_DECOMPRESS\\_END](#); SQLSTATE: [HY000](#)

Message: Error while decompressing data using %s compression. The operation could not be performed as no more input bytes remaining to decompress. The decompressed output has not been changed.

- Error number: [MY-015058](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_DECOMPRESS\\_PROCESS](#); SQLSTATE: [HY000](#)

Message: Error while decompressing data using %s compression. Data cannot be decompressed.

- Error number: [MY-015059](#); Symbol: [ER\\_GRP\\_RPL\\_VCLE\\_NOT\\_BEING\\_LOGGED](#); SQLSTATE: [HY000](#)

---

Message: View\_change\_log\_event will not be logged further on the binary log, as all members of the group are 8.3.0 or greater.

- Error number: `MY-015060`; Symbol: `ER_GROUP_REPLICATION_METADATA_PROTOBUF_PARSING`; SQLSTATE: `HY000`

Message: Error while parsing serialized Certification\_info from received Recovery Metadata to Protobuf format using Protobuf library.

- Error number: `MY-015061`; Symbol: `ER_GROUP_REPLICATION_PROTOBUF_SERIALIZING_ERROR`; SQLSTATE: `HY000`

Message: Error while serializing % data using Protobuf library.

- Error number: `MY-015062`; Symbol: `ER_GROUP_REPLICATION_ERROR_RECEIVED_WAITING_METADATA`; SQLSTATE: `HY000`

Message: Error received while the Recovery thread was waiting for the Recovery Metadata. The Recovery will be terminated.

- Error number: `MY-015063`; Symbol: `ER_GROUP_REPLICATION_TIMEOUT_ERROR_FETCHING_METADATA`; SQLSTATE: `HY000`

Message: Error fetching AFTER\_GTIDS from Recovery Metadata by Recovery thread. The Recovery thread timeout after waiting for %d seconds. The Recovery will be terminated.

- Error number: `MY-015064`; Symbol: `ER_GROUP_REPLICATION_METADATA_PAYLOAD_EMPTY`; SQLSTATE: `HY000`

Message: Error while decoding the received Recovery Metadata Message. The received payload is empty which could be due to error in decoding of received Recovery Metadata Message. The joining member will leave the group.

- Error number: `MY-015065`; Symbol: `ER_GROUP_REPLICATION_METADATA_MESSAGE_PAYLOAD_EMPTY`; SQLSTATE: `HY000`

Message: The %s payload type of the received Recovery Metadata Message is empty.

- Error number: `MY-015066`; Symbol: `ER_GROUP_REPLICATION_METADATA_READ_GTID_EXECUTED`; SQLSTATE: `HY000`

Message: Error reading gtid\_executed from the received Recovery Metadata Message.

- Error number: `MY-015067`; Symbol: `ER_GROUP_REPLICATION_METADATA_PAYLOAD_DECODING`; SQLSTATE: `HY000`

Message: Error while decoding the received Recovery Metadata Message.

- Error number: `MY-015068`; Symbol: `ER_GROUP_REPLICATION_METADATA_SEND_ERROR`; SQLSTATE: `HY000`

Message: The group was unable to send the Recovery Metadata to a joining member.

- Error number: `MY-015069`; Symbol: `ER_GROUP_REPLICATION_METADATA_SAVE_RECOVERY_COPY`; SQLSTATE: `HY000`

Message: Error while saving copy of Recovery Metadata Message.

- 
- Error number: [MY-015070](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_METADATA\\_CERT\\_INFO\\_ERROR\\_PROCESSING](#); SQLSTATE: [HY000](#)  
Message: Error while processing received Certification Information from the Recovery Metadata Message.
  - Error number: [MY-015071](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_METADATA\\_CERT\\_INFO\\_PACKET\\_EMPTY](#); SQLSTATE: [HY000](#)  
Message: Error Certification Information packet from the received Recovery Metadata Message is empty.
  - Error number: [MY-015072](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_METADATA\\_ERROR\\_ON\\_SEND\\_ERROR\\_MESSAGE](#); SQLSTATE: [HY000](#)  
Message: Error while sending Recovery metadata error message. If this is a temporary failure of send message and member itself hasn't left the group, then joiner will timeout waiting for Recovery metadata message. If this is a permanent failure, the member will leave the group and another member will send the Recovery metadata message.
  - Error number: [MY-015073](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_METADATA\\_SET\\_IN\\_RECOVERY\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Error when transferring Recovery Metadata Message to Recovery. The joining member will leave the group.
  - Error number: [MY-015074](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_CERTIFICATION\\_MODULE\\_FAILURE](#); SQLSTATE: [HY000](#)  
Message: Error Certification module wasn't properly initialized.
  - Error number: [MY-015075](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_METADATA\\_INITIALIZATION\\_FAILURE](#); SQLSTATE: [HY000](#)  
Message: Error Recovery Metadata Message module wasn't properly initialized.
  - Error number: [MY-015076](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_METADATA\\_MEMORY\\_ALLOC](#); SQLSTATE: [HY000](#)  
Message: Error while %s. The operation could not be performed as memory allocation failed.
  - Error number: [MY-015077](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_RECOVERY\\_SKIPPED\\_GTID\\_PRESENT](#); SQLSTATE: [HY000](#)  
Message: The group replication recovery is skipped as the joiner's gtid executed set %s already has all the transactions of the donor's gtid set %s.
  - Error number: [MY-015078](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_RECOVERY\\_FETCHING\\_GTID\\_EXECUTED\\_SET](#); SQLSTATE: [HY000](#)  
Message: Error in Group Replication Recovery while getting member's global GTID executed set.
  - Error number: [MY-015079](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_RECOVERY\\_ERROR\\_ADD\\_GTID\\_EXECUTED](#); SQLSTATE: [HY000](#)  
Message: Error in Group Replication Recovery while adding GTIDs in string format to Gtid\_set.
  - Error number: [MY-015080](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_RECOVERY\\_METADATA\\_SENDER\\_NOT\\_FOUND](#); SQLSTATE: [HY000](#)  
Message: Error computing the current Recovery metadata sender. Check if this MEMBER is not leaving the group and the joiner is able to successfully fetch the recovery metadata or not.



- 
- Error number: [MY-015081](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_METADATA\\_CERT\\_INFO\\_PACKET\\_COUNT\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Error in the received Recovery Metadata Message the number of compressed Certification Information packet count mismatch with the number of sent compressed Certification Information packets.
  - Error number: [MY-015082](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_METADATA\\_CERT\\_INFO\\_ENCODING\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: Error while encoding Certification Information for the Recovery Metadata Message.
  - Error number: [MY-015083](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_METADATA\\_NO\\_VALID\\_DONOR](#); SQLSTATE: [HY000](#)  
Message: There are no valid recovery metadata donors. The joining member will leave the group.
  - Error number: [MY-015084](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_NO\\_CERTIFICATION\\_DONOR\\_AVAILABLE](#); SQLSTATE: [HY000](#)  
Message: No donor available to provide the certification information, part of the required information to the new member join the group. Please wait until there are ONLINE members on the group and try to join the new member again.
  - Error number: [MY-015085](#); Symbol: [ER\\_GROUP\\_REPLICATION\\_RECOVERY\\_STOPPED\\_GTID\\_PRESENT](#); SQLSTATE: [HY000](#)  
Message: The group replication recovery is complete, joiner gtid executed set has all the transactions of the donor's gtid set %s.
  - Error number: [MY-015086](#); Symbol: [ER\\_RPL\\_ASYNC\\_CHECK\\_CONNECTION\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: The Monitor IO thread encountered an error while executing the query to check connection to the source server. Error: %s. The query failed to execute on the source (host:%s port:%u network\_namespace:%s) for channel '%s'.
  - Error number: [MY-015087](#); Symbol: [ER\\_RPL\\_ASYNC\\_MONITOR\\_IO\\_THD\\_FETCH\\_GROUP\\_MAJORITY\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: The Monitor IO thread failed to detect if the source belongs to the group majority. Error: %s. The query failed to execute on the source (host:%s port:%u network\_namespace:%s) for channel '%s'.
  - Error number: [MY-015088](#); Symbol: [ER\\_RPL\\_ASYNC\\_REPLICA\\_IO\\_THD\\_FETCH\\_GROUP\\_MAJORITY\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: The replica IO thread failed to detect if the source belongs to the group majority. Error: %s. The query failed to execute on the source (host:%s port:%u network\_namespace:%s) for channel '%s'.
  - Error number: [MY-015089](#); Symbol: [ER\\_RPL\\_ASYNC\\_GET\\_GROUP\\_MEMBERSHIP\\_DETAILS\\_ERROR](#); SQLSTATE: [HY000](#)  
Message: The Monitor IO thread failed to get group membership details. Error: %s. The query failed to execute on the source (host:%s port:%u network\_namespace:%s) for channel '%s'.
  - Error number: [MY-015090](#); Symbol: [ER\\_IB\\_ERR\\_CORRUPT\\_TABLESPACE\\_UNRECOVERABLE](#); SQLSTATE: [HY000](#)  
Message: Tablespace '%u' mentioned in the redo log is corrupted in a way it is unrecoverable by double-write buffer, so further redo log recovery is not possible!
-

- 
- Error number: [MY-015091](#); Symbol: [ER\\_IB\\_BULK\\_LOAD\\_STATS\\_WARN](#); SQLSTATE: [HY000](#)  
Message: %s: Failed to save statistics for table=%s err=%zu
  - Error number: [MY-015092](#); Symbol: [ER\\_COMPONENT\\_MASKING\\_INVALID\\_FLUSH\\_INTERVAL\\_VALUE](#); SQLSTATE: [HY000](#)  
Message: Invalid flush interval specified: %lu. Valid values are 0 (off) or greater than or equal to %d. Adjusting to %d.
  - Error number: [MY-015093](#); Symbol: [ER\\_COMPONENT\\_MASKING\\_VAR\\_REGISTRATION\\_FAILURE](#); SQLSTATE: [HY000](#)  
Message: Cannot register variable '%s'. '%s'.
  - Error number: [MY-015094](#); Symbol: [ER\\_COMPONENT\\_MASKING\\_NOTIFICATION\\_REGISTRATION\\_FAILURE](#); SQLSTATE: [HY000](#)  
Message: Masking component failed to register notification service. Periodical masking dictionaries flush will not work.
  - Error number: [MY-015095](#); Symbol: [ER\\_GRP\\_RPL\\_MSG\\_DECODING\\_FAILED](#); SQLSTATE: [HY000](#)  
Message: Failed to decode Group Replication message: %s. Reason : %s
  - Error number: [MY-015096](#); Symbol: [ER\\_GRP\\_RPL\\_APPLIER\\_ERROR\\_PACKET\\_RECEIVED](#); SQLSTATE: [HY000](#)  
Message: The Applier process of Group Replication found an error and was requested to stop: %s

---

## Chapter 3 Client Error Message Reference

Client error messages originate from within the MySQL client library. Here is an example client error message, as displayed by the `mysql` client:

```
$> mysql -h no-such-host
ERROR 2005 (HY000): Unknown MySQL server host 'no-such-host' (0)
```

Each client error message includes an error code, SQLSTATE value, and message string, as described in [Error Message Sources and Elements](#). These elements are available as described in [Error Information Interfaces](#). For client errors, the SQLSTATE value is always 'HY000' (general error), so it is not meaningful for distinguishing one client error from another.

The client library also makes available to host client programs any errors that originate on the server side and are received by the client from the server. For a list of server-side errors, see [Chapter 2, Server Error Message Reference](#).

In addition to the errors in the following list, the client library can also produce error messages that have error codes in the range from 1 to 999. See [Chapter 4, Global Error Message Reference](#)

- Error number: 2000; Symbol: `CR_UNKNOWN_ERROR`;  
Message: Unknown MySQL error
- Error number: 2001; Symbol: `CR_SOCKET_CREATE_ERROR`;  
Message: Can't create UNIX socket (%d)
- Error number: 2002; Symbol: `CR_CONNECTION_ERROR`;  
Message: Can't connect to local MySQL server through socket '%s' (%d)
- Error number: 2003; Symbol: `CR_CONN_HOST_ERROR`;  
Message: Can't connect to MySQL server on '%s:%u' (%d)
- Error number: 2004; Symbol: `CR_IPSOCK_ERROR`;  
Message: Can't create TCP/IP socket (%d)
- Error number: 2005; Symbol: `CR_UNKNOWN_HOST`;  
Message: Unknown MySQL server host '%s' (%d)
- Error number: 2006; Symbol: `CR_SERVER_GONE_ERROR`;  
Message: MySQL server has gone away
- Error number: 2007; Symbol: `CR_VERSION_ERROR`;  
Message: Protocol mismatch; server version = %d, client version = %d
- Error number: 2008; Symbol: `CR_OUT_OF_MEMORY`;  
Message: MySQL client ran out of memory
- Error number: 2009; Symbol: `CR_WRONG_HOST_INFO`;  
Message: Wrong host info
- Error number: 2010; Symbol: `CR_LOCALHOST_CONNECTION`;  
Message: Localhost via UNIX socket

- 
- Error number: [2011](#); Symbol: [CR\\_TCP\\_CONNECTION](#);  
Message: %s via TCP/IP
  - Error number: [2012](#); Symbol: [CR\\_SERVER\\_HANDSHAKE\\_ERR](#);  
Message: Error in server handshake
  - Error number: [2013](#); Symbol: [CR\\_SERVER\\_LOST](#);  
Message: Lost connection to MySQL server during query
  - Error number: [2014](#); Symbol: [CR\\_COMMANDS\\_OUT\\_OF\\_SYNC](#);  
Message: Commands out of sync; you can't run this command now  
  
Commands were executed in an improper order. This error occurs when a function is called that is not appropriate for the current state of the connection. For example, if `mysql_stmt_fetch()` is not called enough times to read an entire result set (that is, enough times to return `MYSQL_NO_DATA`), this error may occur for the following C API call.
  - Error number: [2015](#); Symbol: [CR\\_NAMEDPIPE\\_CONNECTION](#);  
Message: Named pipe: %s
  - Error number: [2016](#); Symbol: [CR\\_NAMEDPIPEWAIT\\_ERROR](#);  
Message: Can't wait for named pipe to host: %s pipe: %s (%lu)
  - Error number: [2017](#); Symbol: [CR\\_NAMEDPIPEOPEN\\_ERROR](#);  
Message: Can't open named pipe to host: %s pipe: %s (%lu)
  - Error number: [2018](#); Symbol: [CR\\_NAMEDPIPESETSTATE\\_ERROR](#);  
Message: Can't set state of named pipe to host: %s pipe: %s (%lu)
  - Error number: [2019](#); Symbol: [CR\\_CANT\\_READ\\_CHARSET](#);  
Message: Can't initialize character set %s (path: %s)
  - Error number: [2020](#); Symbol: [CR\\_NET\\_PACKET\\_TOO\\_LARGE](#);  
Message: Got packet bigger than 'max\_allowed\_packet' bytes
  - Error number: [2021](#); Symbol: [CR\\_EMBEDDED\\_CONNECTION](#);  
Message: Embedded server
  - Error number: [2022](#); Symbol: [CR\\_PROBE\\_REPLICA\\_STATUS](#);  
Message: Error on SHOW REPLICA STATUS:
  - Error number: [2023](#); Symbol: [CR\\_PROBE\\_REPLICA\\_HOSTS](#);  
Message: Error on SHOW REPLICA HOSTS:
  - Error number: [2024](#); Symbol: [CR\\_PROBE\\_REPLICA\\_CONNECT](#);  
Message: Error connecting to replica:
  - Error number: [2025](#); Symbol: [CR\\_PROBE\\_SOURCE\\_CONNECT](#);  
Message: Error connecting to source:

- 
- Error number: 2026; Symbol: `CR_SSL_CONNECTION_ERROR`;  
Message: SSL connection error: %s
  - Error number: 2027; Symbol: `CR_MALFORMED_PACKET`;  
Message: Malformed packet
  - Error number: 2028; Symbol: `CR_WRONG_LICENSE`;  
Message: This client library is licensed only for use with MySQL servers having '%s' license
  - Error number: 2029; Symbol: `CR_NULL_POINTER`;  
Message: Invalid use of null pointer
  - Error number: 2030; Symbol: `CR_NO_PREPARE_STMT`;  
Message: Statement not prepared
  - Error number: 2031; Symbol: `CR_PARAMS_NOT_BOUND`;  
Message: No data supplied for parameters in prepared statement
  - Error number: 2032; Symbol: `CR_DATA_TRUNCATED`;  
Message: Data truncated
  - Error number: 2033; Symbol: `CR_NO_PARAMETERS_EXISTS`;  
Message: No parameters exist in the statement
  - Error number: 2034; Symbol: `CR_INVALID_PARAMETER_NO`;  
Message: Invalid parameter number  
  
The column number for `mysql_stmt_fetch_column()` was invalid.  
  
The parameter number for `mysql_stmt_send_long_data()` was invalid.  
  
A key name was empty or the amount of connection attribute data for `mysql_options4()` exceeds the 64KB limit.
  - Error number: 2035; Symbol: `CR_INVALID_BUFFER_USE`;  
Message: Can't send long data for non-string/non-binary data types (parameter: %d)
  - Error number: 2036; Symbol: `CR_UNSUPPORTED_PARAM_TYPE`;  
Message: Using unsupported buffer type: %d (parameter: %d)
  - Error number: 2037; Symbol: `CR_SHARED_MEMORY_CONNECTION`;  
Message: Shared memory: %s
  - Error number: 2038; Symbol: `CR_SHARED_MEMORY_CONNECT_REQUEST_ERROR`;  
Message: Can't open shared memory; client could not create request event (%lu)
  - Error number: 2039; Symbol: `CR_SHARED_MEMORY_CONNECT_ANSWER_ERROR`;  
Message: Can't open shared memory; no answer event received from server (%lu)
  - Error number: 2040; Symbol: `CR_SHARED_MEMORY_CONNECT_FILE_MAP_ERROR`;

- 
- Message: Can't open shared memory; server could not allocate file mapping (%lu)
  - Error number: 2041; Symbol: [CR\\_SHARED\\_MEMORY\\_CONNECT\\_MAP\\_ERROR](#);
  - Message: Can't open shared memory; server could not get pointer to file mapping (%lu)
  - Error number: 2042; Symbol: [CR\\_SHARED\\_MEMORY\\_FILE\\_MAP\\_ERROR](#);
  - Message: Can't open shared memory; client could not allocate file mapping (%lu)
  - Error number: 2043; Symbol: [CR\\_SHARED\\_MEMORY\\_MAP\\_ERROR](#);
  - Message: Can't open shared memory; client could not get pointer to file mapping (%lu)
  - Error number: 2044; Symbol: [CR\\_SHARED\\_MEMORY\\_EVENT\\_ERROR](#);
  - Message: Can't open shared memory; client could not create %s event (%lu)
  - Error number: 2045; Symbol: [CR\\_SHARED\\_MEMORY\\_CONNECT\\_ABANDONED\\_ERROR](#);
  - Message: Can't open shared memory; no answer from server (%lu)
  - Error number: 2046; Symbol: [CR\\_SHARED\\_MEMORY\\_CONNECT\\_SET\\_ERROR](#);
  - Message: Can't open shared memory; cannot send request event to server (%lu)
  - Error number: 2047; Symbol: [CR\\_CONN\\_UNKNOW\\_PROTOCOL](#);
  - Message: Wrong or unknown protocol
  - Error number: 2048; Symbol: [CR\\_INVALID\\_CONN\\_HANDLE](#);
  - Message: Invalid connection handle
  - Error number: 2049; Symbol: [CR\\_UNUSED\\_1](#);
  - Message: Connection using old (pre-4.1.1) authentication protocol refused (client option 'secure\_auth' enabled)
  - Error number: 2050; Symbol: [CR\\_FETCH\\_CANCELED](#);
  - Message: Row retrieval was canceled by mysql\_stmt\_close() call
  - Error number: 2051; Symbol: [CR\\_NO\\_DATA](#);
  - Message: Attempt to read column without prior row fetch
  - Error number: 2052; Symbol: [CR\\_NO\\_STMT\\_METADATA](#);
  - Message: Prepared statement contains no metadata
  - Error number: 2053; Symbol: [CR\\_NO\\_RESULT\\_SET](#);
  - Message: Attempt to read a row while there is no result set associated with the statement
  - Error number: 2054; Symbol: [CR\\_NOT\\_IMPLEMENTED](#);
  - Message: This feature is not implemented yet
  - Error number: 2055; Symbol: [CR\\_SERVER\\_LOST\\_EXTENDED](#);
  - Message: Lost connection to MySQL server at '%s', system error: %d
  - Error number: 2056; Symbol: [CR\\_STMT\\_CLOSED](#);

---

Message: Statement closed indirectly because of a preceding %s() call

- Error number: 2057; Symbol: `CR_NEW_STMT_METADATA`;

Message: The number of columns in the result set differs from the number of bound buffers. You must reset the statement, rebind the result set columns, and execute the statement again

- Error number: 2058; Symbol: `CR_ALREADY_CONNECTED`;

Message: This handle is already connected. Use a separate handle for each connection.

- Error number: 2059; Symbol: `CR_AUTH_PLUGIN_CANNOT_LOAD`;

Message: Authentication plugin '%s' cannot be loaded: %s

- Error number: 2060; Symbol: `CR_DUPLICATE_CONNECTION_ATTR`;

Message: There is an attribute with the same name already

A duplicate connection attribute name was specified for `mysql_options4()`.

- Error number: 2061; Symbol: `CR_AUTH_PLUGIN_ERR`;

Message: Authentication plugin '%s' reported error: %s

- Error number: 2062; Symbol: `CR_INSECURE_API_ERR`;

Message: Insecure API function call: '%s' Use instead: '%s'

An insecure function call was detected. Modify the application to use the suggested alternative function instead.

- Error number: 2063; Symbol: `CR_FILE_NAME_TOO_LONG`;

Message: File name is too long

- Error number: 2064; Symbol: `CR_SSL_FIPS_MODE_ERR`;

Message: Set FIPS mode ON/STRICT failed

- Error number: 2065; Symbol: `CR_DEPRECATED_COMPRESSION_NOT_SUPPORTED`;

Message: Compression protocol not supported with asynchronous protocol

- Error number: 2066; Symbol: `CR_COMPRESSION_WRONGLY_CONFIGURED`;

Message: Connection failed due to wrongly configured compression algorithm

- Error number: 2067; Symbol: `CR_KERBEROS_USER_NOT_FOUND`;

Message: SSO user not found, Please perform SSO authentication using kerberos.

- Error number: 2068; Symbol: `CR_LOAD_DATA_LOCAL_INFILE_REJECTED`;

Message: LOAD DATA LOCAL INFILE file request rejected due to restrictions on access.

- Error number: 2069; Symbol: `CR_LOAD_DATA_LOCAL_INFILE_REALPATH_FAIL`;

Message: Determining the real path for '%s' failed with error (%d): %s

- Error number: 2070; Symbol: `CR_DNS_SRV_LOOKUP_FAILED`;

Message: DNS SRV lookup failed with error : %d

- 
- Error number: 2071; Symbol: CR\_MANDATORY\_TRACKER\_NOT\_FOUND;  
Message: Client does not recognise tracker type %d marked as mandatory by server.
  - Error number: 2072; Symbol: CR\_INVALID\_FACTOR\_NO;  
Message: Invalid first argument for MYSQL\_OPT\_USER\_PASSWORD option. Valid value should be between 1 and 3 inclusive.
  - Error number: 2073; Symbol: CR\_CANT\_GET\_SESSION\_DATA;  
Message: Can't get session data: %s
  - Error number: 2074; Symbol: CR\_INVALID\_CLIENT\_CHARSET;  
Message: '%s' character set is having more than 1 byte minimum character length, which cannot be used as a client character set. Please use any of the single byte minimum ones, e.g. utf8mb4, latin1 etc.
  - Error number: 2075; Symbol: CR\_TLS\_SERVER\_NOT\_FOUND;  
Message: Server rejected the ssl handshake for specified sni servername, sslerror: %s



---

## Chapter 4 Global Error Message Reference

This document lists “global” error messages that are shared in the sense that they can be produced by the MySQL server or by MySQL client programs. These errors have error codes in the range from 1 to 999.

Each global error message includes an error code, SQLSTATE value, and message string, as described in [Error Message Sources and Elements](#). These elements are available as described in [Error Information Interfaces](#). For global errors, the SQLSTATE value is always 'HY000' (general error), so it is not meaningful for distinguishing one client error from another.

If the server writes a message to the error log that has a global error code, it pads the error code with leading zeros to six digits and adds a prefix of `MY-` (example: `MY-000022`). The following list displays error codes in that format.

If a client returns a message with a global error code, it adds no zero-padding or prefix to the error code.

- Error number: 1; Symbol: `EE_CANTCREATEFILE`;  
Message: Can't create/write to file '%s' (OS errno %d - %s)
- Error number: 2; Symbol: `EE_READ`;  
Message: Error reading file '%s' (OS errno %d - %s)
- Error number: 3; Symbol: `EE_WRITE`;  
Message: Error writing file '%s' (OS errno %d - %s)
- Error number: 4; Symbol: `EE_BADCLOSE`;  
Message: Error on close of '%s' (OS errno %d - %s)
- Error number: 5; Symbol: `EE_OUTOFMEMORY`;  
Message: Out of memory (Needed %u bytes)
- Error number: 6; Symbol: `EE_DELETE`;  
Message: Error on delete of '%s' (OS errno %d - %s)
- Error number: 7; Symbol: `EE_LINK`;  
Message: Error on rename of '%s' to '%s' (OS errno %d - %s)
- Error number: 9; Symbol: `EE_EOFERR`;  
Message: Unexpected EOF found when reading file '%s' (OS errno %d - %s)
- Error number: 10; Symbol: `EE_CANTLOCK`;  
Message: Can't lock file (OS errno %d - %s)
- Error number: 11; Symbol: `EE_CANTUNLOCK`;  
Message: Can't unlock file (OS errno %d - %s)
- Error number: 12; Symbol: `EE_DIR`;  
Message: Can't read dir of '%s' (OS errno %d - %s)
- Error number: 13; Symbol: `EE_STAT`;

- 
- Message: Can't get stat of '%s' (OS errno %d - %s)
  - Error number: 14; Symbol: `EE_CANT_CHSIZE`;  
Message: Can't change size of file (OS errno %d - %s)
  - Error number: 15; Symbol: `EE_CANT_OPEN_STREAM`;  
Message: Can't open stream from handle (OS errno %d - %s)
  - Error number: 16; Symbol: `EE_GETWD`;  
Message: Can't get working directory (OS errno %d - %s)
  - Error number: 17; Symbol: `EE_SETWD`;  
Message: Can't change dir to '%s' (OS errno %d - %s)
  - Error number: 18; Symbol: `EE_LINK_WARNING`;  
Message: Warning: '%s' had %d links
  - Error number: 19; Symbol: `EE_OPEN_WARNING`;  
Message: Warning: %d files and %d streams are left open
  - Error number: 20; Symbol: `EE_DISK_FULL`;  
Message: Disk is full writing '%s' (OS errno %d - %s). Waiting for someone to free space...
  - Error number: 21; Symbol: `EE_CANT_MKDIR`;  
Message: Can't create directory '%s' (OS errno %d - %s)
  - Error number: 22; Symbol: `EE_UNKNOWN_CHARSET`;  
Message: Character set '%s' is not a compiled character set and is not specified in the '%s' file
  - Error number: 23; Symbol: `EE_OUT_OF_FILERESOURCES`;  
Message: Out of resources when opening file '%s' (OS errno %d - %s)
  - Error number: 24; Symbol: `EE_CANT_READLINK`;  
Message: Can't read value for symlink '%s' (Error %d - %s)
  - Error number: 25; Symbol: `EE_CANT_SYMLINK`;  
Message: Can't create symlink '%s' pointing at '%s' (Error %d - %s)
  - Error number: 26; Symbol: `EE_REALPATH`;  
Message: Error on realpath() on '%s' (Error %d - %s)
  - Error number: 27; Symbol: `EE_SYNC`;  
Message: Can't sync file '%s' to disk (OS errno %d - %s)
  - Error number: 28; Symbol: `EE_UNKNOWN_COLLATION`;  
Message: Collation '%s' is not a compiled collation and is not specified in the '%s' file
  - Error number: 29; Symbol: `EE_FILENOTFOUND`;

- 
- Message: File '%s' not found (OS errno %d - %s)
  - Error number: 30; Symbol: `EE_FILE_NOT_CLOSED`;  
Message: File '%s' (fileno: %d) was not closed
  - Error number: 31; Symbol: `EE_CHANGE_OWNERSHIP`;  
Message: Cannot change ownership of the file '%s' (OS errno %d - %s)
  - Error number: 32; Symbol: `EE_CHANGE_PERMISSIONS`;  
Message: Cannot change permissions of the file '%s' (OS errno %d - %s)
  - Error number: 33; Symbol: `EE_CANT_SEEK`;  
Message: Cannot seek in file '%s' (OS errno %d - %s)
  - Error number: 34; Symbol: `EE_CAPACITY_EXCEEDED`;  
Message: Memory capacity exceeded (capacity %llu bytes)
  - Error number: 35; Symbol: `EE_DISK_FULL_WITH_RETRY_MSG`;  
Message: Disk is full writing '%s' (OS errno %d - %s). Waiting for someone to free space... Retry in %d secs. Message reprinted in %d secs.
  - Error number: 36; Symbol: `EE_FAILED_TO_CREATE_TIMER`;  
Message: Failed to create timer (OS errno %d).
  - Error number: 37; Symbol: `EE_FAILED_TO_DELETE_TIMER`;  
Message: Failed to delete timer (OS errno %d).
  - Error number: 38; Symbol: `EE_FAILED_TO_CREATE_TIMER_QUEUE`;  
Message: Failed to create timer queue (OS errno %d).
  - Error number: 39; Symbol: `EE_FAILED_TO_START_TIMER_NOTIFY_THREAD`;  
Message: Failed to start timer notify thread.
  - Error number: 40; Symbol: `EE_FAILED_TO_CREATE_TIMER_NOTIFY_THREAD_INTERRUPT_EVENT`;  
Message: Failed to create event to interrupt timer notifier thread (OS errno %d).
  - Error number: 41; Symbol: `EE_EXITING_TIMER_NOTIFY_THREAD`;  
Message: Failed to register timer event with queue (OS errno %d), exiting timer notifier thread.
  - Error number: 42; Symbol: `EE_WIN_LIBRARY_LOAD_FAILED`;  
Message: LoadLibrary("kernel32.dll") failed: GetLastError returns %lu.
  - Error number: 43; Symbol: `EE_WIN_RUN_TIME_ERROR_CHECK`;  
Message: %s.
  - Error number: 44; Symbol: `EE_FAILED_TO_DETERMINE_LARGE_PAGE_SIZE`;  
Message: Failed to determine large page size.
-

- 
- Error number: 45; Symbol: `EE_FAILED_TO_KILL_ALL_THREADS`;  
Message: Error in my\_thread\_global\_end(): %d thread(s) did not exit.
  - Error number: 46; Symbol: `EE_FAILED_TO_CREATE_IO_COMPLETION_PORT`;  
Message: Failed to create IO completion port (OS errno %d).
  - Error number: 47; Symbol: `EE_FAILED_TO_OPEN_DEFAULTS_FILE`;  
Message: Failed to open required defaults file: %s
  - Error number: 48; Symbol: `EE_FAILED_TO_HANDLE_DEFAULTS_FILE`;  
Message: Fatal error in defaults handling. Program aborted!
  - Error number: 49; Symbol: `EE_WRONG_DIRECTIVE_IN_CONFIG_FILE`;  
Message: Wrong '!%s' directive in config file %s at line %d.
  - Error number: 50; Symbol: `EE_SKIPPING_DIRECTIVE_DUE_TO_MAX_INCLUDE_RECURSION`;  
Message: Skipping '%s' directive as maximum include recursion level was reached in file %s at line %d.
  - Error number: 51; Symbol: `EE_INCORRECT_GRP_DEFINITION_IN_CONFIG_FILE`;  
Message: Wrong group definition in config file %s at line %d.
  - Error number: 52; Symbol: `EE_OPTION_WITHOUT_GRP_IN_CONFIG_FILE`;  
Message: Found option without preceding group in config file %s at line %d.
  - Error number: 53; Symbol: `EE_CONFIG_FILE_PERMISSION_ERROR`;  
Message: %s should be readable/writable only by current user.
  - Error number: 54; Symbol: `EE_IGNORE_WORLD_WRITABLE_CONFIG_FILE`;  
Message: World-writable config file '%s' is ignored.
  - Error number: 55; Symbol: `EE_USING_DISABLED_OPTION`;  
Message: %s: Option '%s' was used, but is disabled.
  - Error number: 56; Symbol: `EE_USING_DISABLED_SHORT_OPTION`;  
Message: %s: Option '-%c' was used, but is disabled.
  - Error number: 57; Symbol: `EE_USING_PASSWORD_ON_CLI_IS_INSECURE`;  
Message: Using a password on the command line interface can be insecure.
  - Error number: 58; Symbol: `EE_UNKNOWN_SUFFIX_FOR_VARIABLE`;  
Message: Unknown suffix '%c' used for variable '%s' (value '%s').
  - Error number: 59; Symbol: `EE_SSL_ERROR_FROM_FILE`;  
Message: SSL error: %s from '%s'.
  - Error number: 60; Symbol: `EE_SSL_ERROR`;  
Message: SSL error: %s.

- 
- Error number: 61; Symbol: `EE_NET_SEND_ERROR_IN_BOOTSTRAP`;  
Message: %d %s.
  - Error number: 62; Symbol: `EE_PACKETS_OUT_OF_ORDER`;  
Message: Packets out of order (found %u, expected %u).
  - Error number: 63; Symbol: `EE_UNKNOWN_PROTOCOL_OPTION`;  
Message: Unknown option to protocol: %s.
  - Error number: 64; Symbol: `EE_FAILED_TO_LOCATE_SERVER_PUBLIC_KEY`;  
Message: Failed to locate server public key '%s'.
  - Error number: 65; Symbol: `EE_PUBLIC_KEY_NOT_IN_PEM_FORMAT`;  
Message: Public key is not in Privacy Enhanced Mail format: '%s'.
  - Error number: 66; Symbol: `EE_DEBUG_INFO`;  
Message: %s.
  - Error number: 67; Symbol: `EE_UNKNOWN_VARIABLE`;  
Message: unknown variable '%s'.
  - Error number: 68; Symbol: `EE_UNKNOWN_OPTION`;  
Message: unknown option '--%s'.
  - Error number: 69; Symbol: `EE_UNKNOWN_SHORT_OPTION`;  
Message: %s: unknown option '-%c'.
  - Error number: 70; Symbol: `EE_OPTION_WITHOUT_ARGUMENT`;  
Message: %s: option '--%s' cannot take an argument.
  - Error number: 71; Symbol: `EE_OPTION_REQUIRES_ARGUMENT`;  
Message: %s: option '--%s' requires an argument.
  - Error number: 72; Symbol: `EE_SHORT_OPTION_REQUIRES_ARGUMENT`;  
Message: %s: option '-%c' requires an argument.
  - Error number: 73; Symbol: `EE_OPTION_IGNORED_DUE_TO_INVALID_VALUE`;  
Message: %s: ignoring option '--%s' due to invalid value '%s'.
  - Error number: 74; Symbol: `EE_OPTION_WITH_EMPTY_VALUE`;  
Message: %s: Empty value for '%s' specified.
  - Error number: 75; Symbol: `EE_FAILED_TO_ASSIGN_MAX_VALUE_TO_OPTION`;  
Message: %s: Maximum value of '%s' cannot be set.
  - Error number: 76; Symbol: `EE_INCORRECT_BOOLEAN_VALUE_FOR_OPTION`;  
Message: option '%s': boolean value '%s' was not recognized. Set to OFF.
  - Error number: 77; Symbol: `EE_FAILED_TO_SET_OPTION_VALUE`;

---

Message: %s: Error while setting value '%s' to '%s'.

- Error number: 78; Symbol: `EE_INCORRECT_INT_VALUE_FOR_OPTION`;  
Message: Incorrect integer value: '%s'.
- Error number: 79; Symbol: `EE_INCORRECT_UINT_VALUE_FOR_OPTION`;  
Message: Incorrect unsigned integer value: '%s'.
- Error number: 80; Symbol: `EE_ADJUSTED_SIGNED_VALUE_FOR_OPTION`;  
Message: option '%s': signed value %s adjusted to %s.
- Error number: 81; Symbol: `EE_ADJUSTED_UNSIGNED_VALUE_FOR_OPTION`;  
Message: option '%s': unsigned value %s adjusted to %s.
- Error number: 82; Symbol: `EE_ADJUSTED_ULONGLONG_VALUE_FOR_OPTION`;  
Message: option '%s': value %s adjusted to %s.
- Error number: 83; Symbol: `EE_ADJUSTED_DOUBLE_VALUE_FOR_OPTION`;  
Message: option '%s': value %g adjusted to %g.
- Error number: 84; Symbol: `EE_INVALID_DECIMAL_VALUE_FOR_OPTION`;  
Message: Invalid decimal value for option '%s'.
- Error number: 85; Symbol: `EE_COLLATION_PARSER_ERROR`;  
Message: %s.
- Error number: 86; Symbol: `EE_FAILED_TO_RESET_BEFORE_PRIMARY_IGNOREABLE_CHAR`;  
Message: Failed to reset before a primary ignorable character %s.
- Error number: 87; Symbol: `EE_FAILED_TO_RESET_BEFORE_TERTIARY_IGNOREABLE_CHAR`;  
Message: Failed to reset before a tertiary ignorable character %s.
- Error number: 88; Symbol: `EE_SHIFT_CHAR_OUT_OF_RANGE`;  
Message: Shift character out of range: %s.
- Error number: 89; Symbol: `EE_RESET_CHAR_OUT_OF_RANGE`;  
Message: Reset character out of range: %s.
- Error number: 90; Symbol: `EE_UNKNOWN_LDML_TAG`;  
Message: Unknown LDML tag: '%.\*s'.
- Error number: 91; Symbol: `EE_FAILED_TO_RESET_BEFORE_SECONDARY_IGNOREABLE_CHAR`;  
Message: Failed to reset before a secondary ignorable character %s.
- Error number: 92; Symbol: `EE_FAILED_PROCESSING_DIRECTIVE`;  
Message: Stopped processing the '%s' directive in file %s at line %d.
- Error number: 93; Symbol: `EE_PTHREAD_KILL_FAILED`;

---

Message: pthread\_kill(thread\_id:%lu, signal:%s) returned '%s'.





---

# Index

## C

- CR\_ALREADY\_CONNECTED error code, 409
- CR\_AUTH\_PLUGIN\_CANNOT\_LOAD error code, 409
- CR\_AUTH\_PLUGIN\_ERR error code, 409
- CR\_CANT\_GET\_SESSION\_DATA error code, 410
- CR\_CANT\_READ\_CHARSET error code, 406
- CR\_COMMANDS\_OUT\_OF\_SYNC error code, 406
- CR\_COMPRESSION\_WRONGLY\_CONFIGURED error code, 409
- CR\_CONNECTION\_ERROR error code, 405
- CR\_CONN\_HOST\_ERROR error code, 405
- CR\_CONN\_UNKNOW\_PROTOCOL error code, 408
- CR\_DATA\_TRUNCATED error code, 407
- CR\_DEPRECATED\_COMPRESSION\_NOT\_SUPPORTED error code, 409
- CR\_DNS\_SRV\_LOOKUP\_FAILED error code, 409
- CR\_DUPLICATE\_CONNECTION\_ATTR error code, 409
- CR\_EMBEDDED\_CONNECTION error code, 406
- CR\_FETCH\_CANCELED error code, 408
- CR\_FILE\_NAME\_TOO\_LONG error code, 409
- CR\_INSECURE\_API\_ERR error code, 409
- CR\_INVALID\_BUFFER\_USE error code, 407
- CR\_INVALID\_CLIENT\_CHARSET error code, 410
- CR\_INVALID\_CONN\_HANDLE error code, 408
- CR\_INVALID\_FACTOR\_NO error code, 410
- CR\_INVALID\_PARAMETER\_NO error code, 407
- CR\_IPSOCK\_ERROR error code, 405
- CR\_KERBEROS\_USER\_NOT\_FOUND error code, 409
- CR\_LOAD\_DATA\_LOCAL\_INFILE\_REALPATH\_FAIL error code, 409
- CR\_LOAD\_DATA\_LOCAL\_INFILE\_REJECTED error code, 409
- CR\_LOCALHOST\_CONNECTION error code, 405
- CR\_MALFORMED\_PACKET error code, 407
- CR\_MANDATORY\_TRACKER\_NOT\_FOUND error code, 410
- CR\_NAMEDPIPEOPEN\_ERROR error code, 406
- CR\_NAMEDPIPESETSTATE\_ERROR error code, 406
- CR\_NAMEDPIPEWAIT\_ERROR error code, 406
- CR\_NAMEDPIPE\_CONNECTION error code, 406
- CR\_NET\_PACKET\_TOO\_LARGE error code, 406
- CR\_NEW\_STMT\_METADATA error code, 409
- CR\_NOT\_IMPLEMENTED error code, 408
- CR\_NO\_DATA error code, 408
- CR\_NO\_PARAMETERS\_EXISTS error code, 407
- CR\_NO\_PREPARE\_STMT error code, 407
- CR\_NO\_RESULT\_SET error code, 408
- CR\_NO\_STMT\_METADATA error code, 408
- CR\_NULL\_POINTER error code, 407
- CR\_OUT\_OF\_MEMORY error code, 405
- CR\_PARAMS\_NOT\_BOUND error code, 407
- CR\_PROBE\_REPLICA\_CONNECT error code, 406
- CR\_PROBE\_REPLICA\_HOSTS error code, 406
- CR\_PROBE\_REPLICA\_STATUS error code, 406
- CR\_PROBE\_SOURCE\_CONNECT error code, 406
- CR\_SERVER\_GONE\_ERROR error code, 405
- CR\_SERVER\_HANDSHAKE\_ERR error code, 406
- CR\_SERVER\_LOST error code, 406
- CR\_SERVER\_LOST\_EXTENDED error code, 408
- CR\_SHARED\_MEMORY\_CONNECTION error code, 407
- CR\_SHARED\_MEMORY\_CONNECT\_ABANDONED\_ERROR error code, 408
- CR\_SHARED\_MEMORY\_CONNECT\_ANSWER\_ERROR error code, 407
- CR\_SHARED\_MEMORY\_CONNECT\_FILE\_MAP\_ERROR error code, 408
- CR\_SHARED\_MEMORY\_CONNECT\_MAP\_ERROR error code, 408
- CR\_SHARED\_MEMORY\_CONNECT\_REQUEST\_ERROR error code, 407
- CR\_SHARED\_MEMORY\_CONNECT\_SET\_ERROR error code, 408
- CR\_SHARED\_MEMORY\_EVENT\_ERROR error code, 408
- CR\_SHARED\_MEMORY\_FILE\_MAP\_ERROR error code, 408
- CR\_SHARED\_MEMORY\_MAP\_ERROR error code, 408
- CR\_SOCKET\_CREATE\_ERROR error code, 405
- CR\_SSL\_CONNECTION\_ERROR error code, 407
- CR\_SSL\_FIPS\_MODE\_ERR error code, 409
- CR\_STMT\_CLOSED error code, 409
- CR\_TCP\_CONNECTION error code, 406
- CR\_TLS\_SERVER\_NOT\_FOUND error code, 410
- CR\_UNKNOWN\_ERROR error code, 405
- CR\_UNKNOWN\_HOST error code, 405
- CR\_UNSUPPORTED\_PARAM\_TYPE error code, 407
- CR\_UNUSED\_1 error code, 408
- CR\_VERSION\_ERROR error code, 405
- CR\_WRONG\_HOST\_INFO error code, 405
- CR\_WRONG\_LICENSE error code, 407

## E

- EE\_ADJUSTED\_DOUBLE\_VALUE\_FOR\_OPTION error code, 416
- EE\_ADJUSTED\_SIGNED\_VALUE\_FOR\_OPTION error code, 416
- EE\_ADJUSTED\_ULONGLONG\_VALUE\_FOR\_OPTION error code, 416
- EE\_ADJUSTED\_UNSIGNED\_VALUE\_FOR\_OPTION error code, 416
- EE\_BADCLOSE error code, 411
- EE\_CANTCREATEFILE error code, 411
- EE\_CANTLOCK error code, 411
- EE\_CANTUNLOCK error code, 411
- EE\_CANT\_CHSIZE error code, 412
- EE\_CANT\_MKDIR error code, 412
- EE\_CANT\_OPEN\_STREAM error code, 412
- EE\_CANT\_READLINK error code, 412
- EE\_CANT\_SEEK error code, 413

---

EE\_CANT\_SYMLINK error code, 412  
 EE\_CAPACITY\_EXCEEDED error code, 413  
 EE\_CHANGE\_OWNERSHIP error code, 413  
 EE\_CHANGE\_PERMISSIONS error code, 413  
 EE\_COLLATION\_PARSER\_ERROR error code, 416  
 EE\_CONFIG\_FILE\_PERMISSION\_ERROR error code, 414  
 EE\_DEBUG\_INFO error code, 415  
 EE\_DELETE error code, 411  
 EE\_DIR error code, 411  
 EE\_DISK\_FULL error code, 412  
 EE\_DISK\_FULL\_WITH\_RETRY\_MSG error code, 413  
 EE\_EOFERR error code, 411  
 EE\_EXITING\_TIMER\_NOTIFY\_THREAD error code, 413  
 EE\_FAILED\_PROCESSING\_DIRECTIVE error code, 416  
 EE\_FAILED\_TO\_ASSIGN\_MAX\_VALUE\_TO\_OPTION error code, 415  
 EE\_FAILED\_TO\_CREATE\_IO\_COMPLETION\_PORT error code, 414  
 EE\_FAILED\_TO\_CREATE\_TIMER error code, 413  
 EE\_FAILED\_TO\_CREATE\_TIMER\_NOTIFY\_THREAD error code, 413  
 EE\_FAILED\_TO\_CREATE\_TIMER\_QUEUE error code, 413  
 EE\_FAILED\_TO\_DELETE\_TIMER error code, 413  
 EE\_FAILED\_TO\_DETERMINE\_LARGE\_PAGE\_SIZE error code, 413  
 EE\_FAILED\_TO\_HANDLE\_DEFAULTS\_FILE error code, 414  
 EE\_FAILED\_TO\_KILL\_ALL\_THREADS error code, 414  
 EE\_FAILED\_TO\_LOCATE\_SERVER\_PUBLIC\_KEY error code, 415  
 EE\_FAILED\_TO\_OPEN\_DEFAULTS\_FILE error code, 414  
 EE\_FAILED\_TO\_RESET\_BEFORE\_PRIMARY\_IGNOREABLE\_CHAR error code, 416  
 EE\_FAILED\_TO\_RESET\_BEFORE\_SECONDARY\_IGNOREABLE\_CHAR error code, 416  
 EE\_FAILED\_TO\_RESET\_BEFORE\_TERTIARY\_IGNOREABLE\_CHAR error code, 416  
 EE\_FAILED\_TO\_SET\_OPTION\_VALUE error code, 416  
 EE\_FAILED\_TO\_START\_TIMER\_NOTIFY\_THREAD error code, 413  
 EE\_FILENOTFOUND error code, 413  
 EE\_FILE\_NOT\_CLOSED error code, 413  
 EE\_GETWD error code, 412  
 EE\_IGNORE\_WORLD\_WRITABLE\_CONFIG\_FILE error code, 414  
 EE\_INCORRECT\_BOOLEAN\_VALUE\_FOR\_OPTION error code, 415  
 EE\_INCORRECT\_GRP\_DEFINITION\_IN\_CONFIG\_FILE error code, 414  
 EE\_INCORRECT\_INT\_VALUE\_FOR\_OPTION error code, 416  
 EE\_INCORRECT\_UINT\_VALUE\_FOR\_OPTION error code, 416  
 EE\_INVALID\_DECIMAL\_VALUE\_FOR\_OPTION error code, 416  
 EE\_LINK error code, 411  
 EE\_LINK\_WARNING error code, 412  
 EE\_NET\_SEND\_ERROR\_IN\_BOOTSTRAP error code, 415  
 EE\_OPEN\_WARNING error code, 412  
 EE\_OPTION\_IGNORED\_DUE\_TO\_INVALID\_VALUE error code, 415  
 EE\_OPTION\_REQUIRES\_ARGUMENT error code, 415  
 EE\_OPTION\_WITHOUT\_ARGUMENT error code, 415  
 EE\_OPTION\_WITHOUT\_GRP\_IN\_CONFIG\_FILE error code, 414  
 EE\_OPTION\_WITH\_EMPTY\_VALUE error code, 415  
 EE\_OUTOFMEMORY error code, 411  
 EE\_OUT\_OF\_FILERESOURCES error code, 412  
 EE\_PACKETS\_OUT\_OF\_ORDER error code, 415  
 EE\_PTHREAD\_KILL\_FAILED error code, 417  
 EE\_PUBLIC\_KEY\_NOT\_IN\_PEM\_FORMAT error code, 415  
 EE\_READ error code, 411  
 EE\_REALPATH error code, 412  
 EE\_RESET\_CHAR\_OUT\_OF\_RANGE error code, 416  
 EE\_SETWD error code, 412  
 EE\_SHIFT\_CHAR\_OUT\_OF\_RANGE error code, 416  
 EE\_SHORT\_OPTION\_REQUIRES\_ARGUMENT error code, 415  
 EE\_SKIPPING\_DIRECTIVE\_DUE\_TO\_MAX\_INCLUDE\_RECURSION error code, 414  
 EE\_SSL\_ERROR error code, 414  
 EE\_SSL\_ERROR\_FROM\_FILE error code, 414  
 EE\_STAT error code, 412  
 EE\_SYNC error code, 412  
 EE\_UNKNOWN\_CHARSET error code, 412  
 EE\_UNKNOWN\_COLLATION error code, 412  
 EE\_UNKNOWN\_LDML\_TAG error code, 416  
 EE\_UNKNOWN\_OPTION error code, 415  
 EE\_UNKNOWN\_PROTOCOL\_OPTION error code, 415  
 EE\_UNKNOWN\_SHORT\_OPTION error code, 415  
 EE\_UNKNOWN\_SUFFIX\_FOR\_VARIABLE error code, 414  
 EE\_UNKNOWN\_VARIABLE error code, 415  
 EE\_USING\_DISABLED\_OPTION error code, 414  
 EE\_USING\_DISABLED\_SHORT\_OPTION error code, 414  
 EE\_USING\_PASSWORD\_ON\_CLI\_IS\_INSECURE error code, 414  
 EE\_WIN\_LIBRARY\_LOAD\_FAILED error code, 413  
 EE\_WIN\_RUN\_TIME\_ERROR\_CHECK error code, 413  
 EE\_WRITE error code, 411  
 EE\_WRONG\_DIRECTIVE\_IN\_CONFIG\_FILE error code, 414

---

CR\_ALREADY\_CONNECTED, 409  
 CR\_AUTH\_PLUGIN\_CANNOT\_LOAD, 409  
 CR\_AUTH\_PLUGIN\_ERR, 409  
 CR\_CANT\_GET\_SESSION\_DATA, 410  
 CR\_CANT\_READ\_CHARSET, 406  
 CR\_COMMANDS\_OUT\_OF\_SYNC, 406  
 CR\_COMPRESSION\_WRONGLY\_CONFIGURED, 409  
 CR\_CONNECTION\_ERROR, 405  
 CR\_CONN\_HOST\_ERROR, 405  
 CR\_CONN\_UNKNOW\_PROTOCOL, 408  
 CR\_DATA\_TRUNCATED, 407  
 CR\_DEPRECATED\_COMPRESSION\_NOT\_SUPPORTED, 409  
 CR\_DNS\_SRV\_LOOKUP\_FAILED, 409  
 CR\_DUPLICATE\_CONNECTION\_ATTR, 409  
 CR\_EMBEDDED\_CONNECTION, 406  
 CR\_FETCH\_CANCELED, 408  
 CR\_FILE\_NAME\_TOO\_LONG, 409  
 CR\_INSECURE\_API\_ERR, 409  
 CR\_INVALID\_BUFFER\_USE, 407  
 CR\_INVALID\_CLIENT\_CHARSET, 410  
 CR\_INVALID\_CONN\_HANDLE, 408  
 CR\_INVALID\_FACTOR\_NO, 410  
 CR\_INVALID\_PARAMETER\_NO, 407  
 CR\_IPSOCK\_ERROR, 405  
 CR\_KERBEROS\_USER\_NOT\_FOUND, 409  
 CR\_LOAD\_DATA\_LOCAL\_INFILE\_REALPATH\_FAIL, 409  
 CR\_LOAD\_DATA\_LOCAL\_INFILE\_REJECTED, 409  
 CR\_LOCALHOST\_CONNECTION, 405  
 CR\_MALFORMED\_PACKET, 407  
 CR\_MANDATORY\_TRACKER\_NOT\_FOUND, 410  
 CR\_NAMEDPIPEOPEN\_ERROR, 406  
 CR\_NAMEDPIPESETSTATE\_ERROR, 406  
 CR\_NAMEDPIPEWAIT\_ERROR, 406  
 CR\_NAMEDPIPE\_CONNECTION, 406  
 CR\_NET\_PACKET\_TOO\_LARGE, 406  
 CR\_NEW\_STMT\_METADATA, 409  
 CR\_NOT\_IMPLEMENTED, 408  
 CR\_NO\_DATA, 408  
 CR\_NO\_PARAMETERS\_EXISTS, 407  
 CR\_NO\_PREPARE\_STMT, 407  
 CR\_NO\_RESULT\_SET, 408  
 CR\_NO\_STMT\_METADATA, 408  
 CR\_NULL\_POINTER, 407  
 CR\_OUT\_OF\_MEMORY, 405  
 CR\_PARAMS\_NOT\_BOUND, 407  
 CR\_PROBE\_REPLICA\_CONNECT, 406  
 CR\_PROBE\_REPLICA\_HOSTS, 406  
 CR\_PROBE\_REPLICA\_STATUS, 406  
 CR\_PROBE\_SOURCE\_CONNECT, 406  
 CR\_SERVER\_GONE\_ERROR, 405  
 CR\_SERVER\_HANDSHAKE\_ERR, 406  
 CR\_SERVER\_LOST, 406  
 CR\_SERVER\_LOST\_EXTENDED, 408  
 CR\_SHARED\_MEMORY\_CONNECTION, 407  
 CR\_SHARED\_MEMORY\_CONNECT\_ABANDONED\_ERROR, 408  
 CR\_SHARED\_MEMORY\_CONNECT\_ANSWER\_ERROR, 407  
 CR\_SHARED\_MEMORY\_CONNECT\_FILE\_MAP\_ERROR, 408  
 CR\_SHARED\_MEMORY\_CONNECT\_MAP\_ERROR, 408  
 CR\_SHARED\_MEMORY\_CONNECT\_REQUEST\_ERROR, 407  
 CR\_SHARED\_MEMORY\_CONNECT\_SET\_ERROR, 408  
 CR\_SHARED\_MEMORY\_EVENT\_ERROR, 408  
 CR\_SHARED\_MEMORY\_FILE\_MAP\_ERROR, 408  
 CR\_SHARED\_MEMORY\_MAP\_ERROR, 408  
 CR\_SOCKET\_CREATE\_ERROR, 405  
 CR\_SSL\_CONNECTION\_ERROR, 407  
 CR\_SSL\_FIPS\_MODE\_ERR, 409  
 CR\_STMT\_CLOSED, 409  
 CR\_TCP\_CONNECTION, 406  
 CR\_TLS\_SERVER\_NOT\_FOUND, 410  
 CR\_UNKNOWN\_ERROR, 405  
 CR\_UNKNOWN\_HOST, 405  
 CR\_UNSUPPORTED\_PARAM\_TYPE, 407  
 CR\_UNUSED\_1, 408  
 CR\_VERSION\_ERROR, 405  
 CR\_WRONG\_HOST\_INFO, 405  
 CR\_WRONG\_LICENSE, 407  
 EE\_ADJUSTED\_DOUBLE\_VALUE\_FOR\_OPTION, 416  
 EE\_ADJUSTED\_SIGNED\_VALUE\_FOR\_OPTION, 416  
 EE\_ADJUSTED\_ULONGLONG\_VALUE\_FOR\_OPTION, 416  
 EE\_ADJUSTED\_UNSIGNED\_VALUE\_FOR\_OPTION, 416  
 EE\_BADCLOSE, 411  
 EE\_CANTCREATEFILE, 411  
 EE\_CANTLOCK, 411  
 EE\_CANTUNLOCK, 411  
 EE\_CANT\_CHSIZE, 412  
 EE\_CANT\_MKDIR, 412  
 EE\_CANT\_OPEN\_STREAM, 412  
 EE\_CANT\_READLINK, 412  
 EE\_CANT\_SEEK, 413  
 EE\_CANT\_SYMLINK, 412  
 EE\_CAPACITY\_EXCEEDED, 413  
 EE\_CHANGE\_OWNERSHIP, 413  
 EE\_CHANGE\_PERMISSIONS, 413  
 EE\_COLLATION\_PARSER\_ERROR, 416  
 EE\_CONFIG\_FILE\_PERMISSION\_ERROR, 414  
 EE\_DEBUG\_INFO, 415  
 EE\_DELETE, 411  
 EE\_DIR, 411  
 EE\_DISK\_FULL, 412  
 EE\_DISK\_FULL\_WITH\_RETRY\_MSG, 413  
 EE\_EOFERR, 411  
 EE\_EXITING\_TIMER\_NOTIFY\_THREAD, 413

---

---

EE\_FAILED\_PROCESSING\_DIRECTIVE, 416  
 EE\_FAILED\_TO\_ASSIGN\_MAX\_VALUE\_TO\_OPTION, 415  
 EE\_FAILED\_TO\_CREATE\_IO\_COMPLETION\_PORT, 414  
 EE\_FAILED\_TO\_CREATE\_TIMER, 413  
 EE\_FAILED\_TO\_CREATE\_TIMER\_NOTIFY\_THREAD\_INTERRUPT\_EVENT, 413  
 EE\_FAILED\_TO\_CREATE\_TIMER\_QUEUE, 413  
 EE\_FAILED\_TO\_DELETE\_TIMER, 413  
 EE\_FAILED\_TO\_DETERMINE\_LARGE\_PAGE\_SIZE, 413  
 EE\_FAILED\_TO\_HANDLE\_DEFAULTS\_FILE, 414  
 EE\_FAILED\_TO\_KILL\_ALL\_THREADS, 414  
 EE\_FAILED\_TO\_LOCATE\_SERVER\_PUBLIC\_KEY, 415  
 EE\_FAILED\_TO\_OPEN\_DEFAULTS\_FILE, 414  
 EE\_FAILED\_TO\_RESET\_BEFORE\_PRIMARY\_IGNOREABLE\_CHARACTER, 416  
 EE\_FAILED\_TO\_RESET\_BEFORE\_SECONDARY\_IGNOREABLE\_CHARACTER, 416  
 EE\_FAILED\_TO\_RESET\_BEFORE\_TERTIARY\_IGNOREABLE\_CHARACTER, 416  
 EE\_FAILED\_TO\_SET\_OPTION\_VALUE, 416  
 EE\_FAILED\_TO\_START\_TIMER\_NOTIFY\_THREAD, 413  
 EE\_FILENOTFOUND, 413  
 EE\_FILE\_NOT\_CLOSED, 413  
 EE\_GETWD, 412  
 EE\_IGNORE\_WORLD\_WRITABLE\_CONFIG\_FILE, 414  
 EE\_INCORRECT\_BOOLEAN\_VALUE\_FOR\_OPTION, 415  
 EE\_INCORRECT\_GRP\_DEFINITION\_IN\_CONFIG\_FILE, 414  
 EE\_INCORRECT\_INT\_VALUE\_FOR\_OPTION, 416  
 EE\_INCORRECT\_UINT\_VALUE\_FOR\_OPTION, 416  
 EE\_INVALID\_DECIMAL\_VALUE\_FOR\_OPTION, 416  
 EE\_LINK, 411  
 EE\_LINK\_WARNING, 412  
 EE\_NET\_SEND\_ERROR\_IN\_BOOTSTRAP, 415  
 EE\_OPEN\_WARNING, 412  
 EE\_OPTION\_IGNORED\_DUE\_TO\_INVALID\_VALUE, 415  
 EE\_OPTION\_REQUIRES\_ARGUMENT, 415  
 EE\_OPTION\_WITHOUT\_ARGUMENT, 415  
 EE\_OPTION\_WITHOUT\_GRP\_IN\_CONFIG\_FILE, 414  
 EE\_OPTION\_WITH\_EMPTY\_VALUE, 415  
 EE\_OUTOFMEMORY, 411  
 EE\_OUT\_OF\_FILERESOURCES, 412  
 EE\_PACKETS\_OUT\_OF\_ORDER, 415  
 EE\_PTHREAD\_KILL\_FAILED, 417  
 EE\_PUBLIC\_KEY\_NOT\_IN\_PEM\_FORMAT, 415  
 EE\_READ, 411  
 EE\_REALPATH, 412  
 EE\_RESET\_CHAR\_OUT\_OF\_RANGE, 416  
 EE\_SETWD, 412  
 EE\_SHIFT\_CHAR\_OUT\_OF\_RANGE, 416  
 EE\_SHORT\_OPTION\_REQUIRES\_ARGUMENT, 415  
 EE\_SKIPPING\_DIRECTIVE\_DUE\_TO\_MAX\_INCLUDE\_RECURSION\_DEPTH, 415  
 EE\_SSL\_ERROR, 414  
 EE\_SSL\_ERROR\_FROM\_FILE, 414  
 EE\_STAT, 412  
 EE\_SYNC, 412  
 EE\_UNKNOWN\_CHARSET, 412  
 EE\_UNKNOWN\_COLLATION, 412  
 EE\_UNKNOWN\_LDML\_TAG, 416  
 EE\_UNKNOWN\_OPTION, 415  
 EE\_UNKNOWN\_PROTOCOL\_OPTION, 415  
 EE\_UNKNOWN\_SHORT\_OPTION, 415  
 EE\_UNKNOWN\_SUFFIX\_FOR\_VARIABLE, 414  
 EE\_UNKNOWN\_VARIABLE, 415  
 EE\_USING\_DISABLED\_OPTION, 414  
 EE\_USING\_DISABLED\_SHORT\_OPTION, 414  
 EE\_USING\_PASSWORD\_ON\_CLI\_IS\_INSECURE, 414  
 EE\_WIN\_LIBRARY\_LOAD\_FAILED, 413  
 EE\_WIN\_RUN\_TIME\_ERROR\_CHECK, 413  
 EE\_WRITE, 411  
 EE\_WRONG\_DIRECTIVE\_IN\_CONFIG\_FILE, 414  
 ER\_ABORTING, 136  
 ER\_ABORTING\_CONNECTION, 13  
 ER\_ABORTING\_USER\_CONNECTION, 181  
 ER\_ACCESS\_DENIED\_CHANGE\_USER\_ERROR, 56  
 ER\_ACCESS\_DENIED\_ERROR, 6  
 ER\_ACCESS\_DENIED\_ERROR\_WITHOUT\_PASSWORD, 182  
 ER\_ACCESS\_DENIED\_ERROR\_WITH\_PASSWORD, 182  
 ER\_ACCESS\_DENIED\_FOR\_USER\_ACCOUNT\_BLOCKED\_BY\_PASSWORD, 353  
 ER\_ACCESS\_DENIED\_FOR\_USER\_ACCOUNT\_LOCKED, 182  
 ER\_ACCESS\_DENIED\_NO\_PASSWORD\_ERROR, 44  
 ER\_ACCOUNT\_HAS\_BEEN\_LOCKED, 66  
 ER\_ACCOUNT\_WITH\_EXPIRED\_PASSWORD, 379  
 ER\_ACL\_OPERATION\_FAILED, 72  
 ER\_ACL\_WRONG\_OR\_MISSING\_ACL\_TABLES\_LOG, 346  
 ER\_ADDRESSES\_FOR\_HOSTNAME\_HEADER, 132  
 ER\_ADDRESSES\_FOR\_HOSTNAME\_LIST\_ITEM, 132  
 ER\_ADD\_PARTITION\_NO\_NEW\_PARTITION, 34  
 ER\_ADD\_PARTITION\_SUBPART\_ERROR, 34  
 ER\_ADMIN\_WRONG\_MRG\_TABLE, 31  
 ER\_AES\_INVALID\_IV, 56  
 ER\_AES\_INVALID\_KDF\_ITERATIONS, 72

ER_AES_INVALID_KDF_NAME, 72	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD,
ER_AES_INVALID_KDF_OPTION_SIZE, 72	346
ER_AGGREGATE_IN_ORDER_NOT_SELECT, 62	ER_AUDIT_LOG_CANNOT_SET_LOG_POLICY_WITH_OT
ER_AGGREGATE_ORDER_FOR_UNION, 59	202
ER_AGGREGATE_ORDER_NON_AGG_QUERY,	ER_AUDIT_LOG_CANNOT_STORE_PASSWORD,
59	346
ER_ALTER_CONSTRAINT_ENFORCEMENT_NOT_SUPPORTED,	ER_AUDIT_LOG_COULD_NOT_CREATE_AES_KEY,
103	327
ER_ALTER_FILEGROUP_FAILED, 35	ER_AUDIT_LOG_COULD_NOT_OPEN_FILE_FOR_READING
ER_ALTER_INFO, 8	346
ER_ALTER_OPERATION_NOT_SUPPORTED, 54	ER_AUDIT_LOG_EC_WRITER_FAILED_TO_CREATE_FILE
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON,	202
54	ER_AUDIT_LOG_EC_WRITER_FAILED_TO_INIT_COMPRE
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON,	202
54	ER_AUDIT_LOG_EC_WRITER_FAILED_TO_INIT_ENCRYPT
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON,	202
55	CHANGE_FTS,
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON,	327
54	ER_AUDIT_LOG_ENCRYPTION_PASSWORD_CANNOT_B
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON,	327
115	ER_AUDIT_LOG_ENCRYPTION_PASSWORD_HAS_NOT_I
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON,	327
54	ER_AUDIT_LOG_FILE_AUTO_PRUNED, 366
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON,	327
54	ER_AUDIT_LOG_FILE_HAS_BEEN_SUCCESSFULLY_PRO
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON,	346
54	ER_AUDIT_LOG_FILE_NAME_DOES_NOT_HAVE_REQUIRE
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON,	346
54	ER_AUDIT_LOG_FILE_NAME_KEYRING_ID_VALUE_IS_M
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON,	346
55	ER_AUDIT_LOG_FILE_NAME_TIMESTAMP_VALUE_IS_M
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON,	346
61	ER_AUDIT_LOG_FILE_PRUNE_FAILED, 366
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON,	202
55	ER_AUDIT_LOG_FILTER_FAILED_TO_CLOSE_TABLE_AF
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON,	202
54	ER_AUDIT_LOG_FILTER_FAILED_TO_DELETE_FROM_TA
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON,	202
55	ER_AUDIT_LOG_FILTER_FAILED_TO_INIT_TABLE_FOR
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON,	202
55	ER_AUDIT_LOG_FILTER_FAILED_TO_INSERT_INTO_TAE
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON,	202
54	ER_AUDIT_LOG_FILTER_FAILED_TO_READ_TABLE,
ER_AMBIGUOUS_FIELD_TERM, 31	203
ER_ANONYMOUS_AUTH_ID_NOT_ALLOWED_IN_MANAGED	ER_AUDIT_LOG_FILTER_FAILED_TO_STORE_TABLE_FL
184	203
ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_GROUP	ER_AUDIT_LOG_FILTER_FAILED_TO_UPDATE_TABLE,
110	203
ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_VIEW	CHANGE_UUID,
111	204
ER_APPLIER_LOG_EVENT_VALIDATION_ERROR,	ER_AUDIT_LOG_FILTER_FLD_FILTERNAME_CANNOT_B
81	201
ER_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTION	ER_AUDIT_LOG_FILTER_IS_NOT_INSTALLED,
109	201
ER_ATTRIBUTE_IGNORED, 83	ER_AUDIT_LOG_FILTER_REQUIRED_RESULT_MSG, 203
ER_AUDIT_API_ABORT, 69	ER_AUDIT_LOG_FILTER_USER_AND_HOST_CANNOT_B
ER_AUDIT_CANT_ABORT_COMMAND, 180	203
ER_AUDIT_CANT_ABORT_EVENT, 180	ER_AUDIT_LOG_HAS_NOT_BEEN_INSTALLED,
ER_AUDIT_LOG_CANNOT_GENERATE_PASSWORD,	349
350	ER_AUDIT_LOG_HOST_NAME_INVALID_CHARACTER,
ER_AUDIT_LOG_CANNOT_READ_PASSWORD,	327
346	ER_AUDIT_LOG_INDEX_MAP_CANNOT_ACCESS_DIR,
	202
	ER_AUDIT_LOG_INSUFFICIENT_PRIVILEGE, 101

ER_AUDIT_LOG_INVALID_FILE_CONTENT, 346	ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED,
ER_AUDIT_LOG_INVALID_FLUSH_INTERVAL_VALUE,	202
395	ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED_REMOVE,
ER_AUDIT_LOG_JSON_FILTERING_NOT_ENABLED,	202
327	ER_AUDIT_PLUGIN_DOES_NOT_SUPPORT_AUDIT_AUTH_E
ER_AUDIT_LOG_JSON_FILTER_DOES_NOT_EXIST,	152
328	ER_AUDIT_PLUGIN_HAS_INVALID_DATA, 152
ER_AUDIT_LOG_JSON_FILTER_NAME_CANNOT_BE_EMPTY,	180
327	ER_AUDIT_WARNING, 180
ER_AUDIT_LOG_JSON_FILTER_PARSING_ERROR,	150
326	ER_AUTHCACHE_CANT_INIT_GRANT_SUBSYSTEM,
ER_AUDIT_LOG_JSON_READER_BUF_TOO_SMALL,	150
203	ER_AUTHCACHE_CANT_OPEN_AND_LOCK_PRIVILEGE_TAE
ER_AUDIT_LOG_JSON_READER_FAILED_TO_OPEN_FILE,	150
203	ER_AUTHCACHE_DB_ENTRY_LOWERCASED_REVOKE_WIL
ER_AUDIT_LOG_JSON_READER_FAILED_TO_PARSE,	150
203	ER_AUTHCACHE_DB_IGNORED_EMPTY_NAME,
ER_AUDIT_LOG_JSON_READER_FILE_PARSING_ERROR,	150
203	ER_AUTHCACHE_DB_SKIPPED_NEEDS_RESOLVE,
ER_AUDIT_LOG_JSON_USER_NAME_CANNOT_BE_EMPTY,	150
327	ER_AUTHCACHE_DEFAULT_ROLES_IGNORED_EMPTY_NAM
ER_AUDIT_LOG_KEYRING_ID_TIMESTAMP_VALUE_INVALID,	349
345	ER_AUTHCACHE_DEFAULT_ROLES_UNKNOWN_AUTHORIZ
ER_AUDIT_LOG_NO_KEYRING_PLUGIN_INSTALLED,	149
327	ER_AUTHCACHE_EXPIRED_PASSWORD_UNSUPPORTED,
ER_AUDIT_LOG_ONLY_INCLUDE_LIST_USED,	149
202	ER_AUTHCACHE_PLUGIN_CONFIG, 149
ER_AUDIT_LOG_PASSWORD_HAS_BEEN_COPIED,	150
346	ER_AUTHCACHE_PLUGIN_MISSING, 149
ER_AUDIT_LOG_RENAME_LOG_FILE_BEFORE_FLUSH,	150
202	ER_AUTHCACHE_PROCS_PRIV_ENTRY_IGNORED_BAD_RO
ER_AUDIT_LOG_SUPER_PRIVILEGE_REQUIRED,	149
349	ER_AUTHCACHE_PROCS_PRIV_SKIPPED_NEEDS_RESOLV
ER_AUDIT_LOG_SWITCHING_TO_INCLUDE_LIST,	359
201	ER_AUTHCACHE_PROXIES_PRIV_SKIPPED_NEEDS_RESOL
ER_AUDIT_LOG_TABLE_DEFINITION_NOT_UPDATED,	359
328	ER_AUTHCACHE_ROLE_EDGES_IGNORED_EMPTY_NAME,
ER_AUDIT_LOG_UDF_INSUFFICIENT_PRIVILEGE,	150
327	ER_AUTHCACHE_ROLE_EDGES_UNKNOWN_AUTHORIZATIO
ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_COUNT,	150
349	ER_AUTHCACHE_ROLE_EDGES_UNKNOWN_AUTHORIZATIO
ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_TYPE,	149
349	ER_AUTHCACHE_TABLES_PRIV_SKIPPED_NEEDS_RESOLV
ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH,	149
349	ER_AUTHCACHE_TABLE_PROXIES_PRIV_MISSING,
ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH,	72
72	ER_AUTHCACHE_USER_IGNORED_DEPRECATED_PASSWO
ER_AUDIT_LOG_USER_FIRST_CHARACTER_MUST_BE_ALPHANUMERIC,	149
328	ER_AUTHCACHE_USER_IGNORED_INVALID_PASSWORD,
ER_AUDIT_LOG_USER_NAME_INVALID_CHARACTER,	393
327	ER_AUTHCACHE_USER_IGNORED_NEEDS_PLUGIN,
ER_AUDIT_LOG_WRITER_DEST_FILE_ALREADY_EXISTS,	375
202	ER_AUTHCACHE_USER_SKIPPED_NEEDS_RESOLVE,
ER_AUDIT_LOG_WRITER_FAILED_TO_WRITE_TO_FILE,	149
202	ER_AUTHCACHE_USER_TABLE_DODGY, 149
ER_AUDIT_LOG_WRITER_INCOMPLETE_FILE_RENAME,	375
202	ER_AUTHENTICATION_OCI_DOWNLOAD_IDDP_PUBLIC_KEY
	393
	ER_AUTHENTICATION_OCI_DOWNLOAD_PUBLIC_KEY,
	375
	ER_AUTHENTICATION_OCI_IAM, 375
	ER_AUTHENTICATION_OCI_IMDS, 375
	ER_AUTHENTICATION_OCI_INVALID_AUTHENTICATION_ST
	375

---

ER_AUTHENTICATION_OCI_INVALID_TOKEN, 392	ER_AUTO_POSITION_REQUIRES_GTID_MODE_NOT_OF 49
ER_AUTHENTICATION_OCI_NONCE, 375	ER_BACK_IN_TIME, 136
ER_AUTHENTICATION_OCI_NO_GROUPS_FOUND, 375	ER_BAD_DB_ERROR, 6
ER_AUTHENTICATION_OCI_NO_MATCHING_GROUPS 375	ER_BAD_FIELD_ERROR, 6
ER_AUTHENTICATION_OCI_PLUGIN_NOT_INITIALIZED, 375	ER_BAD_FT_COLUMN, 20
ER_AUTHENTICATION_OCI_PRIVATE_KEY_ERROR, 375	ER_BAD_HOST_ERROR, 5
ER_AUTHENTICATION_OCI_TOKEN_DETAILS_MISMATCH, 393	ER_BAD_LOG_STATEMENT, 37
ER_AUTHENTICATION_OCI_TOKEN_NOT_VERIFIED, 393	ER_BAD_NULL_ERROR, 6
ER_AUTHENTICATION_PLUGIN_AUTH_DATA_CORRUPT, 374	ER_BAD_NULL_ERROR_NOT_IGNORED, 84
ER_AUTHENTICATION_PLUGIN_LOG, 374	ER_BAD_REPLICA, 15
ER_AUTHENTICATION_PLUGIN_OOM, 374	ER_BAD_REPLICA_AUTO_POSITION, 49
ER_AUTHENTICATION_PLUGIN_REGISTRATION_FAILED, 374	ER_BAD_REPLICA_UNTIL_COND, 20
ER_AUTHENTICATION_PLUGIN_REGISTRATION_INSUFFICIENT_RESOURCES, 374	ER_BAD_TABLE_ERROR, 6
ER_AUTHENTICATION_PLUGIN_SIGNATURE_CORRUPT, 374	ER_BAD_TIMESTAMP_FORMAT, 118
ER_AUTHENTICATION_PLUGIN_VERIFY_SIGNATURE_FAILED, 374	ER_BASE64_DECODE_ERROR, 37
ER_AUTHENTICATION_POLICY_MISMATCH, 113	ER_BASEDIR_SET_TO, 183
ER_AUTH_CANT_ACTIVATE_ROLE, 148	ER_BEFORE_DML_VALIDATION_ERROR, 64
ER_AUTH_CANT_CREATE_RSA_PAIR, 148	ER_BEG_INITFILE, 137
ER_AUTH_CANT_SET_DEFAULT_PLUGIN, 140	ER_BEYOND_SERVER_DOWNGRADE_THRESHOLD, 395
ER_AUTH_CANT_WRITE_PRIVKEY, 148	ER_CANNOT_REMOVE_SERVER_UPGRADE_THRESHOLD, 395
ER_AUTH_CANT_WRITE_PUBKEY, 148	ER_BINLOG_CACHE_SIZE_GREATER_THAN_MAX, 47
ER_AUTH_CERTS_SAVED_TO_DATADIR, 148	ER_BINLOG_CACHE_SIZE_TOO_LARGE, 180
ER_AUTH_CERT_GENERATION_DISABLED, 148	ER_BINLOG_CANT_APPEND_LOG_TO_TMP_INDEX, 175
ER_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_PRIVILEGES, 341	ER_BINLOG_CANT_CLEAR_IN_USE_FLAG_FOR_CRASH, 177
ER_AUTH_KERBEROS_LOGGER_GENERIC_MSG, 371	ER_BINLOG_CANT_CLOSE_TMP_INDEX, 176
ER_AUTH_KEYS_SAVED_TO_DATADIR, 149	ER_BINLOG_CANT_COPY_INDEX_TO_TMP, 176
ER_AUTH_KEY_GENERATION_DISABLED, 149	ER_BINLOG_CANT_DELETE_FILE, 175
ER_AUTH_KEY_GENERATION_SKIPPED_PAIR_PRESENT, 149	ER_BINLOG_CANT_DELETE_FILE_AND_READ_BINLOG, 177
ER_AUTH_LDAP_ERROR_LOGGER_ERROR_MSG, 205	ER_BINLOG_CANT_DELETE_LOG_FILE_DOES_INDEX_M 177
ER_AUTH_RSA_CANT_FIND, 147	ER_BINLOG_CANT_FIND_LOG_IN_INDEX, 177
ER_AUTH_RSA_CANT_PARSE, 147	ER_BINLOG_CANT_GENERATE_NEW_FILE_NAME, 175
ER_AUTH_RSA_CANT_READ, 147	ER_BINLOG_CANT_LOCATE_OLD_BINLOG_OR_RELAY_ 175
ER_AUTH_RSA_CONF_PREVENTS_KEY_GENERATION, 149	ER_BINLOG_CANT_MOVE_TMP_TO_INDEX, 176
ER_AUTH_RSA_FILES_NOT_FOUND, 147	ER_BINLOG_CANT_OPEN_CRASHED_BINLOG, 177
ER_AUTH_SSL_CONF_PREVENTS_CERT_GENERATION, 148	ER_BINLOG_CANT_OPEN_FOR_LOGGING, 174
ER_AUTH_USING_EXISTING_CERTS, 148	ER_BINLOG_CANT_OPEN_TMP_INDEX, 175
ER_AUTOINC_READ_FAILED, 31	ER_BINLOG_CANT_RESIZE_CACHE, 174
ER_AUTO_CONVERT, 18	ER_BINLOG_CANT_SET_TMP_INDEX_NAME, 175
ER_AUTO_INCREMENT_CONFLICT, 55	ER_BINLOG_CANT_TRIM_CRASHED_BINLOG, 177
ER_AUTO_OPTIONS_FAILED, 140	ER_BINLOG_CANT_USE_FOR_LOGGING, 175
	ER_BINLOG_CRASHED_BINLOG_TRIMMED, 177
	ER_BINLOG_CRASH_RECOVERY_COMMIT_FAILED, 384
	ER_BINLOG_CRASH_RECOVERY_ENGINE_RESULTS, 383

---

ER_BINLOG_CRASH_RECOVERY_ERROR_RETURNED, 383	ER_BINLOG_FILE_NAME_TOO_LONG, 174
ER_BINLOG_CRASH_RECOVERY_MALFORMED_LOG, 383	ER_BINLOG_FILE_OPEN_FAILED, 184
ER_BINLOG_CRASH_RECOVERY_PREPARE_FAILED, 384	ER_BINLOG_IO_ERROR_READING_HEADER, 174
ER_BINLOG_CRASH_RECOVERY_ROLLBACK_FAILED, 384	ER_BINLOG_LOGGING_IMPOSSIBLE, 38
ER_BINLOG_CREATE_ROUTINE_NEED_SUPER, 28	ER_BINLOG_LOGGING_INCIDENT_TO_STOP_REPLICAS, 177
ER_BINLOG_END, 136	ER_BINLOG_LOGGING_NOT_POSSIBLE, 192
ER_BINLOG_ERROR_READING_GTIDS_FROM_BINARY_LOG, 174	ER_BINLOG_LOGICAL_CORRUPTION, 55
ER_BINLOG_ERROR_READING_GTIDS_FROM_RELAY_LOG, 174	ER_BINLOG_MALFORMED_OR_OLD_RELAY_LOG, 193
ER_BINLOG_EVENTS_READ_FROM_APPLIER_METADATA, 174	ER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATION, 93
ER_BINLOG_EVENTS_READ_FROM_BINLOG_INFO, 174	ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP, 94
ER_BINLOG_EVENT_WRITE_TO_STMT_CACHE_FAILED, 184	ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP, 94
ER_BINLOG_FAILED_TO_CLOSE_INDEX_FILE_WHILE_REBUILDING, 175	ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_OPERATE, 94
ER_BINLOG_FAILED_TO_DELETE_INDEX_FILE_WHILE_REBUILDING, 175	ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_REENCRYPT, 94
ER_BINLOG_FAILED_TO_DELETE_LOG_FILE, 177	ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_ROTATE_L, 94
ER_BINLOG_FAILED_TO_OPEN_INDEX_FILE_AFTER_REBUILDING, 175	ER_BINLOG_MULTIPLE_ENGINES_AND_SELF_LOGGING_EN, 42
ER_BINLOG_FAILED_TO_OPEN_REGISTER_FILE, 176	ER_BINLOG_NEEDS_SERVERID, 139
ER_BINLOG_FAILED_TO_OPEN_TEMPORARY_INDEX_FILE, 175	ER_BINLOG_OOM_WRITING_DELETE_WHILE_OPENING_HE, 94
ER_BINLOG_FAILED_TO_READ_REGISTER_FILE, 176	ER_BINLOG_PURGE_EMFILE, 37
ER_BINLOG_FAILED_TO_REINIT_REGISTER_FILE, 176	ER_BINLOG_PURGE_FATAL_ERR, 26
ER_BINLOG_FAILED_TO_RENAME_INDEX_FILE_WHILE_REBUILDING, 175	ER_BINLOG_PURGE_LOGS_CALLED_WITH_FILE_NOT_IN_IN, 176
ER_BINLOG_FAILED_TO_RUN_AFTER_FLUSH_HOOK, 178	ER_BINLOG_PURGE_LOGS_CANT_COPY_TO_REGISTER_FI, 176
ER_BINLOG_FAILED_TO_RUN_AFTER_SYNC_HOOK, 177	ER_BINLOG_PURGE_LOGS_CANT_FLUSH_REGISTER_FILE, 176
ER_BINLOG_FAILED_TO_SET_PURGE_INDEX_FILE_NAME, 176	ER_BINLOG_PURGE_LOGS_CANT_SYNC_INDEX_FILE, 176
ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE, 174	ER_BINLOG_REBUILDING, 176
ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE_IN_OPENING, 175	ER_BINLOG_PURGE_LOGS_CANT_UPDATE_INDEX_FILE, 176
ER_BINLOG_FAILED_TO_WRITE_DROP_FOR_TEMP_TABLES, 168	ER_BINLOG_PURGE_LOGS_FAILED_TO_PURGE_LOG, 176
ER_BINLOG_FATAL_ERROR, 38	ER_BINLOG_PURGE_PROHIBITED, 26
ER_BINLOG_FILE_BEING_READ_NOT_PURGED, 174	ER_BINLOG_RECOVERING_AFTER_CRASH_USING, 177
ER_BINLOG_FILE_EXTENSION_NUMBER_EXHAUSTED, 174	ER_BINLOG_ROW_ENGINE_AND_STMT_ENGINE, 41
ER_BINLOG_FILE_EXTENSION_NUMBER_RUNNING_LOW, 174	ER_BINLOG_ROW_INJECTION_AND_STMT_ENGINE, 42
	ER_BINLOG_ROW_INJECTION_AND_STMT_MODE, 42
	ER_BINLOG_ROW_LOGGING_FAILED, 35
	ER_BINLOG_ROW_MODE_AND_STMT_ENGINE, 41
	ER_BINLOG_ROW_VALUE_OPTION_IGNORED, 323
	ER_BINLOG_ROW_VALUE_OPTION_USED_ONLY_FOR_AFT, 323



---

ER_BINLOG_STMT_CACHE_SIZE_GREATER_THAN_MAX,	ER_BOOST_GEOMETRY_EMPTY_INPUT_EXCEPTION,
47	60
ER_BINLOG_STMT_CACHE_SIZE_TOO_LARGE,	ER_BOOST_GEOMETRY_INCONSISTENT_TURNS_EXCE
180	66
ER_BINLOG_STMT_MODE_AND_NO_REPL_TABLES,	ER_BOOST_GEOMETRY_OVERLAY_INVALID_INPUT_EX
54	60
ER_BINLOG_STMT_MODE_AND_ROW_ENGINE,	ER_BOOST_GEOMETRY_SELF_INTERSECTION_POINT
42	60
ER_BINLOG_UNABLE_TO_ROTATE_GTID_TABLE_READ	ER_BOOST_GEOMETRY_TURN_INFO_EXCEPTION,
344	60
ER_BINLOG_UNSAFE_ACL_TABLE_READ_IN_DML_D	ER_BOOST_GEOMETRY_UNKNOWN_EXCEPTION,
109	60
ER_BINLOG_UNSAFE_AND_STMT_ENGINE,	ER_BOOTSTRAP_CANT_THREAD,
41	128
ER_BINLOG_UNSAFE_AUTOINC_COLUMNS,	ER_BUFPOOL_RESIZE_INPROGRESS,
42	69
ER_BINLOG_UNSAFE_AUTOINC_NOT_FIRST,	ER_BUILD_ID,
46	385
ER_BINLOG_UNSAFE_CREATE_IGNORE_SELECT,	ER_BULK_EXECUTOR_ERROR,
45	119
ER_BINLOG_UNSAFE_CREATE_REPLACE_SELECT,	ER_BULK_EXECUTOR_INFO,
45	387
ER_BINLOG_UNSAFE_CREATE_SELECT_AUTOINC,	ER_BULK_LOADER_COLUMN_TOO_BIG_FOR_LEFTOVER
46	119
ER_BINLOG_UNSAFE_DEFAULT_EXPRESSION_IN_SUB	ER_BULK_LOADER_COMPONENT_ERROR,
345	119
ER_BINLOG_UNSAFE_FULLTEXT_PLUGIN,	ER_BULK_LOADER_FILE_CONTAINS_LESS_LINES_THAN
57	388
ER_BINLOG_UNSAFE_INSERT_IGNORE_SELECT,	ER_BULK_LOADER_FILE_CONTAINS_LESS_LINES_THAN
45	388
ER_BINLOG_UNSAFE_INSERT_SELECT_UPDATE,	ER_BULK_LOADER_INFO,
45	388
ER_BINLOG_UNSAFE_INSERT_TWO_KEYS,	ER_BULK_LOAD_DATA_FAILED,
46	119
ER_BINLOG_UNSAFE_LIMIT,	ER_BULK_LOAD_RESOURCE,
42	123
ER_BINLOG_UNSAFE_MESSAGE_AND_STATEMENT,	ER_BULK_LOAD_SECONDARY_ENGINE,
181	123
ER_BINLOG_UNSAFE_MIXED_STATEMENT,	ER_BULK_LOAD_TABLE_HAS_INSTANT_COLS,
44	123
ER_BINLOG_UNSAFE_MULTIPLE_ENGINES_AND_SEL	ER_BULK_MERGE_INVALID_CHUNK,
43	123
ER_BINLOG_UNSAFE_NONTRANS_AFTER_TRANS,	ER_BULK_MERGE_LOADER_INFO,
42	398
ER_BINLOG_UNSAFE_NOWAIT,	ER_BULK_MERGE_NOT_ALL_CHUNKS_CONSUMED,
77	123
ER_BINLOG_UNSAFE_REPLACE_SELECT,	ER_BULK_MERGE_LOADING_ENGINE,
45	123
ER_BINLOG_UNSAFE_ROUTINE,	ER_BULK_MULTI_READER_INFO,
28	398
ER_BINLOG_UNSAFE_SKIP_LOCKED,	ER_BULK_MULTI_READER_OPEN_FILE_FAILED,
77	123
ER_BINLOG_UNSAFE_STATEMENT,	ER_BULK_MULTI_READER_READ_FILE_FAILED,
38	123
ER_BINLOG_UNSAFE_SYSTEM_FUNCTION,	ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED,
42	119
ER_BINLOG_UNSAFE_SYSTEM_TABLE,	ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED_L
42	388
ER_BINLOG_UNSAFE_SYSTEM_VARIABLE,	ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE
42	120
ER_BINLOG_UNSAFE_UDF,	ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE
42	389
ER_BINLOG_UNSAFE_UPDATE_IGNORE,	ER_BULK_PARSER_MISSING_ENCLOSED_BY,
45	119
ER_BINLOG_UNSAFE_WRITE_AUTOINC_SELECT,	ER_BULK_PARSER_MISSING_ENCLOSED_BY_LOG,
46	388
ER_BINLOG_UNSAFE_XA,	ER_BULK_PARSER_ROW_BUFFER_MAX_TOTAL_COLS
71	119
ER_BINLOG_WARNING_SUPPRESSED,	ER_BULK_PARSER_ROW_BUFFER_MAX_TOTAL_COLS
178	388
ER_BLOBS_AND_NO_TERMINATED,	ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COLU
8	120
ER_BLOB_CANT_HAVE_DEFAULT,	
9	
ER_BLOB_FIELD_IN_PART_FUNC_ERROR,	
33	
ER_BLOB_KEY_WITHOUT_LENGTH,	
14	
ER_BLOB_USED_AS_KEY,	
8	
ER_BOOST_GEOMETRY_CENTROID_EXCEPTION,	
60	

---

ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COLUMN_IDENTIFIER, 389	ER_CANNOT_INSERT_INTO_TEMPORARY_TABLE, 57
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_END_OF_ROW, 120	ER_CANNOT_OPEN_FILE_BY_COLUMN_FUNCTIONAL_INDEX, 90
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_END_OF_ROW_BYTE, 389	ER_CANNOT_OPEN_FILE_ON_PRIMARY, 124
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPE, 120	ER_CANNOT_FIND_KEY_IN_KEYRING, 71
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPE, 389	ER_CANNOT_GET_SERVER_VERSION_FROM_TABLESPACE, 338
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPE, 119	ER_CANNOT_GRANT_ROLES_TO_ANONYMOUS_USER, 99
ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT, 388	ER_CANNOT_GRANT_SYSTEM_PRIV_TO_MANDATORY_ROLE, 100
ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT_LOG, 120	ER_CANNOT_INTERPRET_PERSISTED_SENSITIVE_VARIABLE, 378
ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR, 388	ER_CANNOT_LOAD_FROM_TABLE_V2, 46
ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR_LOG, 119	ER_CANNOT_LOCK_USER_MANAGEMENT_CACHES, 75
ER_BULK_READER_COMMUNICATION_ERROR, 119	ER_CANNOT_LOG, 63
ER_BULK_READER_COMMUNICATION_ERROR_LOG, 388	ER_CANNOT_LOG_PARTIAL_DROP_DATABASE_WITH_GTIID, 116
ER_BULK_READER_COULDNT_RESOLVE_HOST, 123	ER_CANNOT_PERSIST_SENSITIVE_VARIABLES, 115
ER_BULK_READER_ERROR, 123	ER_CANNOT_PURGE_BINLOG_WITH_BACKUP_LOCK, 95
ER_BULK_READER_FILE_DOESNT_EXIST, 123	ER_CANNOT_SET_DATABASE_ENCRYPTION, 184
ER_BULK_READER_INFO, 388	ER_CANNOT_SET_LOG_ERROR_SERVICES, 338
ER_BULK_READER_LIBCURL_ERROR, 119	ER_CANNOT_SET_SERVER_VERSION_IN_TABLESPACE_HEADER, 95
ER_BULK_READER_LIBCURL_ERROR_LOG, 388	ER_CANNOT_SET_TABLESPACE_ENCRYPTION, 95
ER_BULK_READER_LIBCURL_INIT_FAILED, 119	ER_CANNOT_SET_TABLE_ENCRYPTION, 27
ER_BULK_READER_LIBCURL_INIT_FAILED_LOG, 388	ER_CANNOT_USER, 109
ER_BULK_READER_OPEN_FILE_FAILED, 123	ER_CANNOT_USER_REFERENCED_AS_DEFINER, 110
ER_BULK_READER_SERVER_ERROR, 119	ER_CANNOT_USE_AUTOEXTEND_SIZE_CLAUSE, 96
ER_BULK_READER_SERVER_ERROR_LOG, 388	ER_CANNOT_USE_ENCRYPTION_CLAUSE, 140
ER_BULK_SORTING_LOADER_INFO, 398	ER_CANT_ACCESS_CAPATH, 19
ER_BULK_SORTING_LOADER_WAIT, 123	ER_CANT_AGGREGATE_2COLLATIONS, 20
ER_BULK_SORTING_LOADER_WRITE, 123	ER_CANT_AGGREGATE_3COLLATIONS, 20
ER_BULK_WRITER_INFO, 398	ER_CANT_AGGREGATE_NCOLLATIONS, 171
ER_BULK_WRITER_LIBCURL_ERROR, 123	ER_CANT_ALLOC_TABLE_OBJECT, 120
ER_BULK_WRITER_LIBCURL_ERROR_LOG, 399	ER_CANT_CHANGE_SYS_VAR_IN_READ_ONLY_MODE, 36
ER_BULK_WRITER_LIBCURL_INIT_FAILED, 123	ER_CANT_CHANGE_TX_CHARACTERISTICS, 246
ER_BULK_WRITER_LIBCURL_INIT_FAILED_LOG, 398	ER_CANT_CHANGE_VARIABLE_PATH, 140
ER_CACHING_SHA2_PASSWORD_SECOND_PASSWORD_USED_INFORMATION, 337	ER_CANT_CHOWN_DATADIR, 109
ER_CALL_ME_LOCALHOST, 136	ER_CANT_COMBINE_ANONYMOUS_TO_GTIID_AND_AUTOPOPC, 336
ER_CANNOT_ADD_FOREIGN, 16	ER_CANT_CREATE_ADMIN_THREAD, 172
ER_CANNOT_ADD_FOREIGN_BASE_COL_STORED, 71	ER_CANT_CREATE_CACHE_FOR_DB_OPT, 3
ER_CANNOT_ADD_FOREIGN_BASE_COL_VIRTUAL, 70	ER_CANT_CREATE_DB, 3
ER_CANNOT_ALTER_SRID_DUE_TO_INDEX, 82	ER_CANT_CREATE_FILE, 28
ER_CANNOT_CHANGE_TO_ROOT_DIR, 183	ER_CANT_CREATE_GEOMETRY_OBJECT, 33
ER_CANNOT_CONVERT_STRING, 97	ER_CANT_CREATE_HANDLER_FILE, 71
ER_CANNOT_CREATE_VIRTUAL_INDEX_CONSTRAINT, 70	ER_CANT_CREATE_HANDLER_OBJECT_FOR_TABLE, 130
	ER_CANT_CREATE_HANDLE_MGR_THREAD, 130

---

ER\_CANT\_CREATE\_INTERRUPT\_THREAD, 135  
ER\_CANT\_CREATE\_NAMED\_PIPES\_THREAD,  
135  
ER\_CANT\_CREATE\_PID\_FILE, 134  
ER\_CANT\_CREATE\_SCHEDULER\_THREAD, 131  
ER\_CANT\_CREATE\_SHM\_THREAD, 135  
ER\_CANT\_CREATE\_SHUTDOWN\_THREAD, 134  
ER\_CANT\_CREATE\_TABLE, 3  
ER\_CANT\_CREATE\_TABLE\_SHARE\_FROM\_FRM,  
171  
ER\_CANT\_CREATE\_TCPIP\_THREAD, 135  
ER\_CANT\_CREATE\_TEST\_FILE, 134  
ER\_CANT\_CREATE\_THREAD, 12  
ER\_CANT\_CREATE\_USER\_WITH\_GRANT, 27  
ER\_CANT\_CREATE\_UUID, 133  
ER\_CANT\_DETACH\_SESSION\_LEFT\_BY\_PLUGIN,  
160  
ER\_CANT\_DO\_IMPLICIT\_COMMIT\_IN\_TRX\_WHEN\_GTID  
49  
ER\_CANT\_DO\_THIS\_DURING\_AN\_TRANSACTION,  
14  
ER\_CANT\_DROP\_FIELD\_OR\_KEY, 9  
ER\_CANT\_ENFORCE\_GTID\_CONSISTENCY\_WITH\_ONE  
65  
ER\_CANT\_EXECUTE\_COMMAND\_WITH\_ASSIGNED\_GTID  
115  
ER\_CANT\_EXECUTE\_IN\_READ\_ONLY\_TRANSACTION  
50  
ER\_CANT\_FIND\_DL\_ENTRY, 11  
ER\_CANT\_FIND\_SYSTEM\_REC, 4  
ER\_CANT\_FIND\_UDF, 11  
ER\_CANT\_GET\_STAT, 4  
ER\_CANT\_HASH\_DO\_AND\_IGNORE\_RULES, 140  
ER\_CANT\_IDENTIFY\_CHARSET\_USING\_DEFAULT,  
172  
ER\_CANT\_INCREASE\_MAX\_OPEN\_FILES, 138  
ER\_CANT\_INITIALIZE\_BUILTIN\_PLUGINS, 140  
ER\_CANT\_INITIALIZE\_DYNAMIC\_PLUGINS, 140  
ER\_CANT\_INITIALIZE\_EARLY\_PLUGINS, 139  
ER\_CANT\_INITIALIZE\_GTID, 139  
ER\_CANT\_INITIALIZE\_UDF, 11  
ER\_CANT\_INIT\_DBS, 138  
ER\_CANT\_INIT\_SCHEDULER\_THREAD, 131  
ER\_CANT\_INIT\_TC\_LOG, 131  
ER\_CANT\_INIT\_TIMER, 141  
ER\_CANT\_JOIN\_SHUTDOWN\_THREAD, 140  
ER\_CANT\_LOCK, 4  
ER\_CANT\_LOCK\_LOG\_TABLE, 36  
ER\_CANT\_LOCK\_TABLE, 171  
ER\_CANT\_LOCK\_TABLESPACE, 171  
ER\_CANT\_MODIFY\_SRID\_0, 86  
ER\_CANT\_MODIFY\_SRS\_USED\_BY\_COLUMN,  
87  
ER\_CANT\_OPEN\_AND\_LOCK\_PRIVILEGE\_TABLES,  
152  
ER\_CANT\_OPEN\_CA, 140  
ER\_CANT\_OPEN\_DATADIR\_AFTER\_UPGRADE\_FAILURE  
173  
ER\_CANT\_OPEN\_DB\_OPT\_USING\_DEFAULT\_CHARSET,  
172  
ER\_CANT\_OPEN\_DIR, 173  
ER\_CANT\_OPEN\_ERROR\_LOG, 141  
ER\_CANT\_OPEN\_FILE, 4  
ER\_CANT\_OPEN\_FRM\_FILE, 152  
ER\_CANT\_OPEN\_LIBRARY, 11  
ER\_CANT\_OPEN\_TABLE\_MYSQL\_PROC, 173  
ER\_CANT\_PARSE\_STORED\_ROUTINE\_BODY,  
173  
ER\_CANT\_PROCESS\_EXPRESSION\_FOR\_GENERATED  
351  
ER\_CANT\_READ\_DIR, 4  
ER\_CANT\_READ\_ERRMSG, 138  
ER\_CANT\_READ\_FRM\_FILE, 152  
ER\_CANT\_READ\_TABLE\_MYSQL\_PROC, 173  
ER\_CANT\_REMOVE\_ALL\_FIELDS, 9  
ER\_CANT\_REMOVE\_PID\_FILE, 134  
ER\_CANT\_RENAME\_LOG\_TABLE, 37  
ER\_CANT\_REOPEN\_TABLE, 12  
ER\_CANT\_REPLICATE\_ANONYMOUS\_WITH\_AUTO\_POS  
326  
ER\_CANT\_REPLICATE\_ANONYMOUS\_WITH\_GTID\_MODE  
326  
ER\_CANT\_RESET\_SOURCE, 71  
ER\_CANT\_SAVE\_GTIDS, 140  
ER\_CANT\_SET\_DATA\_DIR, 335  
ER\_CANT\_SET\_ERROR\_LOG\_SERVICE, 86  
ER\_CANT\_SET\_ERROR\_SUPPRESSION\_LIST, 88  
ER\_CANT\_SET\_ERROR\_SUPPRESSION\_LIST\_FROM\_CC  
330  
ER\_CANT\_SET\_GTID\_MODE, 65  
ER\_CANT\_SET\_GTID\_NEXT\_LIST\_TO\_NON\_NULL\_WHEN  
50  
ER\_CANT\_SET\_GTID\_NEXT\_TO\_ANONYMOUS\_WHEN\_G  
50  
ER\_CANT\_SET\_GTID\_NEXT\_TO\_AUTOMATIC\_TAGGED  
124  
ER\_CANT\_SET\_GTID\_NEXT\_TO\_GTID\_WHEN\_GTID\_MO  
50  
ER\_CANT\_SET\_GTID\_NEXT\_WHEN\_OWNING\_GTID,  
50  
ER\_CANT\_SET\_GTID\_PURGED\_DUE\_SETS\_CONSTRAIN  
75  
ER\_CANT\_SET\_GTID\_PURGED\_WHEN\_GTID\_EXECUTED  
53  
ER\_CANT\_SET\_GTID\_PURGED\_WHEN\_OWNED\_GTIDS  
54  
ER\_CANT\_SET\_HANDLER\_REFERENCE\_FOR\_TABLE,  
171  
ER\_CANT\_SET\_PATH\_FOR, 173  
ER\_CANT\_SET\_PERSISTED, 121  
ER\_CANT\_SET\_SQL\_AFTER\_OR\_BEFORE\_GTIDS\_WITH  
110  
ER\_CANT\_SET\_UP\_PERSISTED\_VALUES, 140

---

ER_CANT_SET_VARIABLE_WHEN_OWNING_GTID, 67	ER_CHANGE_SOURCE_WRONG_COMPRESSION_LEVEL_CL 102
ER_CANT_START_ERROR_LOG_SERVICE, 182	ER_CHARACTER_SET_MISMATCH, 108
ER_CANT_STAT_DATADIR, 140	ER_CHECKING_TABLE, 171
ER_CANT_STAT_FILE, 177	ER_CHECKREAD, 4
ER_CANT_UPDATE_TABLE_IN_CREATE_TABLE_SELECT, 47	ER_CHECK_CONSTRAINT_CLAUSE_USING_FK_REFER_ACT 95
ER_CANT_UPDATE_USED_TABLE_IN_SF_OR_TRG, 29	ER_CHECK_CONSTRAINT_DUP_NAME, 95
ER_CANT_UPDATE_WITH_READLOCK, 17	ER_CHECK_CONSTRAINT_FUNCTION_IS_NOT_ALLOWED, 94
ER_CANT_UPGRADE_GENERATED_COLUMNS_TO_D 171	ER_CHECK_CONSTRAINT_NAMED_FUNCTION_IS_NOT_ALL 94
ER_CANT_USE_ANONYMOUS_TO_GTID_WITH_GTID, 109	ER_CHECK_CONSTRAINT_NOT_FOUND, 95
ER_CANT_USE_AUTO_POSITION_WITH_GTID_MODE 65	ER_CHECK_CONSTRAINT_REFERS_AUTO_INCREMENT_CO 95
ER_CANT_USE_GTID_ONLY_WITH_GTID_MODE_NOT 114	ER_CHECK_CONSTRAINT_REFERS_UNKNOWN_COLUMN, 95
ER_CANT_USE_OPTION_HERE, 18	ER_CHECK_CONSTRAINT_ROW_VALUE, 95
ER_CANT_USE_SAME_UUID_AS_GROUP_NAME, 110	ER_CHECK_CONSTRAINT_VARIABLES, 94
ER_CANT_USE_SAME_UUID_AS_VIEW_CHANGE_UUID 111	ER_CHECK_CONSTRAINT_VIOLATED, 95
ER_CANT_WAIT_FOR_EXECUTED_GTID_SET_WHILE 70	ER_CHECK_NOT_IMPLEMENTED, 14
ER_CAPACITY_EXCEEDED, 70	ER_CHECK_NO_SUCH_TABLE, 14
ER_CAPACITY_EXCEEDED_IN_PARSER, 71	ER_CHECK_TABLE_INSTANT_VERSION_BIT_SET, 390
ER_CAPACITY_EXCEEDED_IN_RANGE_OPTIMIZER, 70	ER_CHECK_TABLE_MIN_REC_FLAG_NOT_SET, 392
ER_CA_SELF_SIGNED, 133	ER_CHECK_TABLE_MIN_REC_FLAG_SET, 391
ER_CHANGED_ENFORCE_GTID_CONSISTENCY, 131	ER_CLIENT_DOES_NOT_SUPPORT, 82
ER_CHANGED_GTID_MODE, 131	ER_CLIENT_FILE_PRIVILEGE_FOR_REPLICATION_CHECKS, 117
ER_CHANGED_MAX_CONNECTIONS, 138	ER_CLIENT_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE_ 89
ER_CHANGED_MAX_OPEN_FILES, 137	ER_CLIENT_INTERACTION_TIMEOUT, 111
ER_CHANGED_TABLE_OPEN_CACHE, 138	ER_CLIENT_KEYRING_UDF_KEY_INVALID, 102
ER_CHANGE_REPLICATION_SOURCE_NO_OPTIONS 113	ER_CLIENT_KEYRING_UDF_KEY_TOO_LONG, 103
ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO 114	ER_CLIENT_KEYRING_UDF_KEY_TYPE_INVALID, 102
ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO 114	ER_CLIENT_KEYRING_ONLY, 103
ER_CHANGE_REP_SOURCE_CANT_DISABLE_GTID_O 114	ER_CLIENT_KEYRING_ONLY, 103
ER_CHANGE_REP_SOURCE_CANT_DISABLE_REQ 113	ER_CLIENT_KEYRING_ONLY, 103
ER_CHANGE_REP_SOURCE_GR_CHANNEL_WITH_G 114	ER_CLIENT_KEYRING_ONLY, 103
ER_CHANGE_RPL_INFO_REPOSITORY_FAILURE, 47	ER_CLIENT_KEYRING_ONLY, 103
ER_CHANGE_RPL_SRC_WRONG_COMPRESSION_AL 111	ER_CLIENT_KEYRING_ONLY, 103
ER_CHANGE_SOURCE_PASSWORD_LENGTH, 61	ER_CLIENT_KEYRING_ONLY, 103
ER_CHANGE_SOURCE_WRONG_COMPRESSION_AL 102	ER_CLIENT_KEYRING_ONLY, 103
ER_CHANGE_SOURCE_WRONG_COMPRESSION_AL 102	ER_CLIENT_KEYRING_ONLY, 103

---

ER\_CLONE\_DISK\_SPACE, 98  
 ER\_CLONE\_DONOR, 98  
 ER\_CLONE\_DONOR\_TRACE, 334  
 ER\_CLONE\_DONOR\_VERSION, 98  
 ER\_CLONE\_ENCRYPTION, 98  
 ER\_CLONE\_HANDLER\_EXIST\_TRACE, 190  
 ER\_CLONE\_IN\_PROGRESS, 98  
 ER\_CLONE\_LOOPBACK, 98  
 ER\_CLONE\_NETWORK\_PACKET, 105  
 ER\_CLONE\_OS, 98  
 ER\_CLONE\_PLATFORM, 98  
 ER\_CLONE\_PLUGIN\_MATCH, 98  
 ER\_CLONE\_PLUGIN\_NOT\_LOADED\_TRACE, 190  
 ER\_CLONE\_PROTOCOL, 98  
 ER\_CLONE\_PROTOCOL\_TRACE, 334  
 ER\_CLONE\_SERVER\_TRACE, 334  
 ER\_CLONE\_SHUTDOWN\_TRACE, 347  
 ER\_CLONE\_SYS\_CONFIG, 98  
 ER\_CLONE\_TOO\_MANY\_CONCURRENT\_CLONES,  
 81  
 ER\_CMD\_NEED\_SUPER, 81  
 ER\_COALESCE\_ONLY\_ON\_HASH\_PARTITION,  
 33  
 ER\_COALESCE\_PARTITION\_NO\_PARTITION, 34  
 ER\_COLLATION\_CHARSET\_MISMATCH, 19  
 ER\_COLUMNACCESS\_DENIED\_ERROR, 12  
 ER\_COLUMN\_CHANGE\_SIZE, 99  
 ER\_COLUMN\_CHECK\_CONSTRAINT\_REFERENCES\_OUTSIDE\_COLUMN,  
 94  
 ER\_COL\_COUNT\_DOESNT\_MATCH\_CORRUPTED\_V2,  
 51  
 ER\_COL\_COUNT\_DOESNT\_MATCH\_PLEASE\_UPDATE,  
 36  
 ER\_COL\_COUNT\_DOESNT\_MATCH\_PLEASE\_UPDATE\_V2,  
 58  
 ER\_COMMAND\_BACKEND\_FAILED\_TO\_FETCH\_SECURITY\_CONTEXT,  
 117  
 ER\_COMMAND\_SERVICE\_BACKEND\_FAILED,  
 117  
 ER\_COMMENT\_CONTAINS\_INVALID\_STRING,  
 115  
 ER\_COMMIT\_NOT\_ALLOWED\_IN\_SF\_OR\_TRG,  
 28  
 ER\_COMPONENTS\_CANT\_ACQUIRE\_SERVICE\_IMPLEMENTATION,  
 74  
 ER\_COMPONENTS\_CANT\_LOAD, 74  
 ER\_COMPONENTS\_CANT\_RELEASE\_SERVICE,  
 75  
 ER\_COMPONENTS\_CANT\_SATISFY\_DEPENDENCY,  
 74  
 ER\_COMPONENTS\_CANT\_UNLOAD, 75  
 ER\_COMPONENTS\_FAILED\_TO\_ACQUIRE\_SERVICE\_IMPLEMENTATION,  
 193  
 ER\_COMPONENTS\_INFRASTRUCTURE\_BOOTSTRAP,  
 133  
 ER\_COMPONENTS\_INFRASTRUCTURE\_MANIFEST\_DENIED,  
 366  
 ER\_COMPONENTS\_INFRASTRUCTURE\_MANIFEST\_INIT,  
 366  
 ER\_COMPONENTS\_INFRASTRUCTURE\_SHUTDOWN,  
 133  
 ER\_COMPONENTS\_INFRASTRUCTURE\_SHUTDOWN\_ENDED,  
 397  
 ER\_COMPONENTS\_INFRASTRUCTURE\_SHUTDOWN\_STARTED,  
 397  
 ER\_COMPONENTS\_LOAD\_CANT\_INITIALIZE, 75  
 ER\_COMPONENTS\_LOAD\_CANT\_REGISTER\_SERVICE\_IMPL,  
 74  
 ER\_COMPONENTS\_NO\_SCHEME, 74  
 ER\_COMPONENTS\_NO\_SCHEME\_SERVICE, 74  
 ER\_COMPONENTS\_PERSIST\_LOADER\_BOOTSTRAP,  
 133  
 ER\_COMPONENTS\_UNLOAD\_CANT\_DEINITIALIZE,  
 75  
 ER\_COMPONENTS\_UNLOAD\_CANT\_UNREGISTER\_SERVICE\_IMPL,  
 75  
 ER\_COMPONENTS\_UNLOAD\_DUPLICATE\_IN\_GROUP,  
 75  
 ER\_COMPONENTS\_UNLOAD\_NOT\_LOADED, 75  
 ER\_COMPONENT\_EE\_DATA\_DECRYPTION\_ERROR,  
 385  
 ER\_COMPONENT\_EE\_DATA\_ENCRYPTION\_ERROR,  
 385  
 ER\_COMPONENT\_EE\_DATA\_LENGTH\_OUT\_OF\_RANGE,  
 385  
 ER\_COMPONENT\_EE\_DATA\_SIGN\_ERROR, 385  
 ER\_COMPONENT\_EE\_FUNCTION\_DEREGISTRATION\_FAILED,  
 384  
 ER\_COMPONENT\_EE\_FUNCTION\_INVALID\_ALGORITHM,  
 384  
 ER\_COMPONENT\_EE\_FUNCTION\_INVALID\_ARGUMENTS,  
 384  
 ER\_COMPONENT\_EE\_FUNCTION\_INVALID\_KEY,  
 384  
 ER\_COMPONENT\_EE\_FUNCTION\_KEY\_LENGTH\_OUT\_OF\_RANGE,  
 384  
 ER\_COMPONENT\_EE\_FUNCTION\_PRIVATE\_KEY\_GENERATION\_FAILED,  
 384  
 ER\_COMPONENT\_EE\_FUNCTION\_PUBLIC\_KEY\_GENERATION\_FAILED,  
 384  
 ER\_COMPONENT\_EE\_FUNCTION\_REGISTRATION\_FAILED,  
 384  
 ER\_COMPONENT\_EE\_INSUFFICIENT\_LENGTH,  
 385  
 ER\_COMPONENT\_EE\_OPENSSL\_ERROR, 385  
 ER\_COMPONENT\_EE\_SYS\_VAR\_DEREGISTRATION\_FAILED,  
 384  
 ER\_COMPONENT\_EE\_SYS\_VAR\_REGISTRATION\_FAILED,  
 384  
 ER\_COMPONENT\_FILTER\_CONFUSED, 206  
 ER\_COMPONENT\_FILTER\_DIAGNOSTICS, 86  
 ER\_COMPONENT\_FILTER\_FLABBERGASTED, 80  
 ER\_COMPONENT\_FILTER\_WRONG\_VALUE, 324  
 ER\_COMPONENT\_KEYRING\_OCI\_CREATE\_PRIVATE\_KEY\_FAILED,  
 398  
 ER\_COMPONENT\_KEYRING\_OCI\_INVALID\_CONFIG\_VARIABLE,  
 398

---

ER\_COMPONENT\_KEYRING\_OCI\_OPEN\_KEY\_FILE, 386  
 ER\_COMPONENT\_KEYRING\_OCI\_READ\_KEY\_FILE, 386  
 ER\_COMPONENT\_LOCK, 393  
 ER\_COMPONENT\_MANIPULATE\_ROW\_FAILED, 75  
 ER\_COMPONENT\_MASKING\_ABI, 394  
 ER\_COMPONENT\_MASKING\_ABI\_REASON, 394  
 ER\_COMPONENT\_MASKING\_CANNOT\_ACCESS\_TABLE, 394  
 ER\_COMPONENT\_MASKING\_INVALID\_FLUSH\_INTERVAL, 404  
 ER\_COMPONENT\_MASKING\_NOTIFICATION\_REGISTER\_FAILED, 404  
 ER\_COMPONENT\_MASKING\_OTHER\_ERROR, 394  
 ER\_COMPONENT\_MASKING\_RANDOM\_CREATE, 394  
 ER\_COMPONENT\_MASKING\_RANDOM\_CREATE\_REASON, 394  
 ER\_COMPONENT\_MASKING\_VAR\_REGISTRATION\_FAILED, 404  
 ER\_COMPONENT\_SERVICE\_CALL, 393  
 ER\_COMPONENT\_SERVICE\_CALL\_RESULT, 393  
 ER\_COMPONENT\_TABLE\_INCORRECT, 75  
 ER\_COMPONENT\_UNLOCK, 394  
 ER\_CONCURRENT\_PROCEDURE\_USAGE, 115  
 ER\_CONDITIONAL\_DEBUG, 385  
 ER\_COND\_ITEM\_TOO\_LONG, 41  
 ER\_CONFIG\_OPTION\_WITHOUT\_GROUP, 142  
 ER\_CONFIRMING\_THE\_FUTURE, 136  
 ER\_CONFLICTING\_DECLARATIONS, 21  
 ER\_CONFLICT\_FN\_PARSE\_ERROR, 39  
 ER\_CONNECTIONS\_SHUTDOWN\_END, 398  
 ER\_CONNECTIONS\_SHUTDOWN\_START, 397  
 ER\_CONNECTION\_ABORTED, 323  
 ER\_CONNECTION\_HANDLING\_OOM, 134  
 ER\_CONNECTION\_METADATA, 15  
 ER\_CONNECT\_TO\_FOREIGN\_DATA\_SOURCE, 29  
 ER\_CONNECT\_TO\_SOURCE, 17  
 ER\_CONN\_ATTR\_TRUNCATED, 147  
 ER\_CONN\_CONTROL\_DELAY\_ACTION\_INIT\_FAILED, 207  
 ER\_CONN\_CONTROL\_ERROR\_MSG, 205  
 ER\_CONN\_CONTROL\_EVENT\_COORDINATOR\_INIT\_FAILED, 207  
 ER\_CONN\_CONTROL\_FAILED\_TO\_SET\_CONN\_DELAY, 207  
 ER\_CONN\_CONTROL\_FAILED\_TO\_UPDATE\_CONN\_DELAY, 207  
 ER\_CONN\_CONTROL\_INVALID\_CONN\_DELAY\_TYPE, 207  
 ER\_CONN\_CONTROL\_STAT\_CONN\_DELAY\_TRIGGERED, 207  
 ER\_CONN\_CONTROL\_STAT\_CONN\_DELAY\_TRIGGERED\_ONCE, 207  
 ER\_CONN\_INIT\_CONNECT\_IGNORED, 206  
 ER\_CONN\_INIT\_CONNECT\_IGNORED\_MFA, 394  
 ER\_CONN\_LIMIT, 377  
 ER\_CONN\_PER\_THREAD\_NO\_THREAD, 145  
 ER\_CONN\_PIP\_CANT\_CREATE\_EVENT, 145  
 ER\_CONN\_PIP\_CANT\_CREATE\_PIPE, 145  
 ER\_CONN\_SHM\_CANT\_CREATE\_CONNECTION, 144  
 ER\_CONN\_SHM\_CANT\_CREATE\_SERVICE, 144  
 ER\_CONN\_SHM\_LISTENER, 144  
 ER\_CONN\_SOCKET\_ACCEPT\_FAILED, 147  
 ER\_CONN\_SOCKET\_SELECT\_FAILED, 147  
 ER\_CONN\_TCP\_ADDRESS, 145  
 ER\_CONN\_TCP\_BIND\_FAIL, 146  
 ER\_CONN\_TCP\_BIND\_RETRY, 145  
 ER\_CONN\_TCP\_CANT\_RESET\_V6ONLY, 145  
 ER\_CONN\_TCP\_CANT\_RESOLVE\_HOSTNAME, 145  
 ER\_CONN\_TCP\_CREATED, 145  
 ER\_CONN\_TCP\_ERROR\_WITH\_STRERROR, 145  
 ER\_CONN\_TCP\_IPV6\_AVAILABLE, 145  
 ER\_CONN\_TCP\_IPV6\_UNAVAILABLE, 145  
 ER\_CONN\_TCP\_IP\_NOT\_LOGGED, 146  
 ER\_CONN\_TCP\_IS\_THERE\_ANOTHER\_USING\_PORT, 145  
 ER\_CONN\_TCP\_LISTEN\_FAIL, 146  
 ER\_CONN\_TCP\_NO\_SOCKET, 145  
 ER\_CONN\_TCP\_RESOLVE\_INFO, 146  
 ER\_CONN\_TCP\_START\_FAIL, 146  
 ER\_CONN\_UNIX\_IS\_THERE\_ANOTHER\_USING\_SOCKET, 145  
 ER\_CONN\_UNIX\_LISTEN\_FAILED, 146  
 ER\_CONN\_UNIX\_LOCK\_FILE\_CANT\_CLOSE, 147  
 ER\_CONN\_UNIX\_LOCK\_FILE\_CANT\_CREATE, 146  
 ER\_CONN\_UNIX\_LOCK\_FILE\_CANT\_DELETE, 147  
 ER\_CONN\_UNIX\_LOCK\_FILE\_CANT\_OPEN, 146  
 ER\_CONN\_UNIX\_LOCK\_FILE\_CANT\_READ, 146  
 ER\_CONN\_UNIX\_LOCK\_FILE\_CANT\_SYNC, 147  
 ER\_CONN\_UNIX\_LOCK\_FILE\_CANT\_WRITE, 147  
 ER\_CONN\_UNIX\_LOCK\_FILE\_EMPTY, 146  
 ER\_CONN\_UNIX\_LOCK\_FILE\_FAIL, 146  
 ER\_CONN\_UNIX\_LOCK\_FILE\_GIVING\_UP, 146  
 ER\_CONN\_UNIX\_LOCK\_FILE\_PIDLESS, 147  
 ER\_CONN\_UNIX\_NO\_BIND\_NO\_START, 146  
 ER\_CONN\_UNIX\_NO\_FD, 146  
 ER\_CONN\_UNIX\_PATH\_TOO\_LONG, 146  
 ER\_CONN\_UNIX\_PID\_CLAIMED\_SOCKET\_FILE, 145  
 ER\_CONSECUTIVE\_REORG\_PARTITIONS, 34  
 ER\_CONSTRAINT\_NOT\_FOUND, 103  
 ER\_CONVERT\_MULTI\_VALUE, 395  
 ER\_CON\_COUNT\_ERROR, 5  
 ER\_CORRUPTED\_VALUES, 135  
 ER\_CORRUPTED\_JSON\_DIFF, 82  
 ER\_COURTNEY\_FEED\_DB, 18  
 ER\_COULD\_NOT\_APPLY\_JSON\_DIFF, 82

---

ER\_COULD\_NOT\_CREATE\_WINDOWS\_REGISTRY\_KEYS, 332  
ER\_COULD\_NOT\_REINITIALIZE\_AUDIT\_LOG\_FILTERS, 327  
ER\_CRASHED\_ON\_REPAIR, 15  
ER\_CRASHED\_ON\_USAGE, 15  
ER\_CREATED\_SYSTEM\_WITH\_VERSION, 188  
ER\_CREATE\_FILEGROUP\_FAILED, 35  
ER\_CREATE\_SELECT\_WITH\_GIPK\_DISALLOWED\_IN\_SBR, 117  
ER\_CREATING\_NEW\_UUID, 133  
ER\_CREATING\_NEW\_UUID\_FIRST\_START, 182  
ER\_CREDENTIALLESS\_AUTO\_USER\_BAD, 134  
ER\_CREDENTIALS\_CONTRADICT\_TO\_HISTORY, 81  
ER\_CTE\_MAX\_RECURSION\_DEPTH, 81  
ER\_CTE\_RECURSIVE\_FORBIDDEN\_JOIN\_ORDER, 77  
ER\_CTE\_RECURSIVE\_FORBIDS\_AGGREGATION, 77  
ER\_CTE\_RECURSIVE\_NOT\_UNION, 117  
ER\_CTE\_RECURSIVE\_REQUIRES\_NONRECURSIVE\_FIRST, 77  
ER\_CTE\_RECURSIVE\_REQUIRES\_SINGLE\_REFERENCE, 77  
ER\_CTE\_RECURSIVE\_REQUIRES\_UNION, 77  
ER\_CURRENT\_PASSWORD\_CANNOT\_BE\_RETAINED, 100  
ER\_CURRENT\_PASSWORD\_NOT\_REQUIRED, 100  
ER\_CUT\_VALUE\_GROUP\_CONCAT, 19  
ER\_CYCLE\_TIMER\_IS\_NOT\_AVAILABLE, 190  
ER\_DATABASE\_NAME, 39  
ER\_DATA\_DIRECTORY\_UNUSABLE, 332  
ER\_DATA\_DIRECTORY\_UNUSABLE\_DELETABLE, 347  
ER\_DATA\_OUT\_OF\_RANGE, 43  
ER\_DATA\_TOO\_LONG, 27  
ER\_DATETIME\_FUNCTION\_OVERFLOW, 29  
ER\_DA\_AUTH\_ID\_WITH\_SYSTEM\_USER\_PRIV\_IN\_MASTER, 99  
ER\_DA\_CANT\_OPEN\_ERROR\_LOG, 108  
ER\_DA\_CONN\_LIMIT, 115  
ER\_DA\_ERROR\_LOG\_COMPONENT\_FLUSH\_FAILED, 112  
ER\_DA\_ERROR\_LOG\_MULTIPLE\_FILTERS, 108  
ER\_DA\_ERROR\_LOG\_TABLE\_DISABLED, 108  
ER\_DA\_GLOBAL\_CONN\_LIMIT, 115  
ER\_DA\_GRP\_RPL\_RECOVERY\_ENDPOINT\_FORMAT, 106  
ER\_DA\_GRP\_RPL\_RECOVERY\_ENDPOINT\_INVALID, 106  
ER\_DA\_GRP\_RPL\_STARTED\_AUTO\_REJOIN, 101  
ER\_DA\_INVALID\_CONDITION\_NUMBER, 48  
ER\_DA\_NO\_ERROR\_LOG\_PARSER\_CONFIGURED, 108  
ER\_DA\_OOM, 104  
ER\_DA\_PLUGIN\_INSTALL\_ERROR, 99  
ER\_DA\_RPL\_GTID\_TABLE\_CANNOT\_OPEN, 99  
ER\_DA\_SSL\_FIPS\_MODE\_ERROR, 114  
ER\_DA\_SSL\_LIBRARY\_ERROR, 99  
ER\_DA\_UDF\_INVALID\_ARGUMENT\_TO\_SET\_CHARSET, 104  
ER\_DA\_UDF\_INVALID\_CHARSET, 103  
ER\_DA\_UDF\_INVALID\_CHARSET\_SPECIFIED, 103  
ER\_DA\_UDF\_INVALID\_COLLATION, 103  
ER\_DA\_UDF\_INVALID\_EXTENSION\_ARGUMENT\_TYPE, 103  
ER\_DA\_UDF\_INVALID\_RETURN\_TYPE\_TO\_SET\_CHARSET, 104  
ER\_DA\_UNKNOWN\_ERROR\_NUMBER, 99  
ER\_DBACCESS\_DENIED\_ERROR, 5  
ER\_DEBUG\_CHECK\_SHARES\_DROPPED, 160  
ER\_DEBUG\_CHECK\_SHARES\_INFO, 160  
ER\_DEBUG\_CHECK\_SHARES\_OPEN, 160  
ER\_DB\_ACCESS\_DENIED, 99  
ER\_DB\_CREATE\_EXISTS, 4  
ER\_DB\_DROP\_EXISTS, 4  
ER\_DB\_DROP\_RMDIR, 4  
ER\_DB\_DROP\_RMDIR2, 79  
ER\_DB\_OPT\_NOT\_FOUND\_USING\_DEFAULT\_CHARSET, 172  
ER\_DDL\_MSG\_1, 372  
ER\_DD\_ABORTING\_PARTIAL\_UPGRADE, 151  
ER\_DD\_CACHE\_NOT\_EMPTY\_AT\_SHUTDOWN, 130  
ER\_DD\_CANT\_CREATE\_OBJECT\_KEY, 130  
ER\_DD\_CANT\_CREATE\_SP, 171  
ER\_DD\_CANT\_FETCH\_TABLE\_DATA, 171  
ER\_DD\_CANT\_FIX\_SE\_DATA, 171  
ER\_DD\_CANT\_GET\_OBJECT\_KEY, 130  
ER\_DD\_CANT\_RESOLVE\_VIEW, 142  
ER\_DD\_CREATED\_FOR\_UPGRADE, 151  
ER\_DD\_ERROR\_CREATING\_ENTRY, 171  
ER\_DD\_FAILSAFE, 129  
ER\_DD\_FOREIGN\_KEYS\_FOR\_TABLE, 151  
ER\_DD\_INITIALIZE, 193  
ER\_DD\_INITIALIZE\_SQL\_ERROR, 328  
ER\_DD\_INIT\_FAILED, 130  
ER\_DD\_INIT\_UPGRADE\_FAILED, 129  
ER\_DD\_METADATA\_NOT\_FOUND, 130  
ER\_DD\_MINOR\_DOWNGRADE, 194  
ER\_DD\_MINOR\_DOWNGRADE\_VERSION\_NOT\_SUPPORTED, 194  
ER\_DD\_NO\_VERSION\_FOUND, 194  
ER\_DD\_NO\_WRITES\_NO\_REPOPULATION, 129  
ER\_DD\_OBJECT\_RELEASER\_REMAINS, 130  
ER\_DD\_OBJECT\_REMAINS, 130  
ER\_DD\_OBJECT\_REMAINS\_IN\_RELEASER, 130  
ER\_DD\_POPULATING\_TABLES\_FAILED, 130  
ER\_DD\_RESTART, 193  
ER\_DD\_SCHEMA\_NOT\_FOUND, 151  
ER\_DD\_SE\_INIT\_FAILED, 151  
ER\_DD\_TABLESPACE\_NOT\_FOUND, 141

---

ER\_DD\_TABLE\_NOT\_FOUND, 151  
 ER\_DD\_TRG\_CANT\_ADD, 141  
 ER\_DD\_TRG\_CONNECTION\_COLLATION\_MISSING,  
 141  
 ER\_DD\_TRG\_DB\_COLLATION\_MISSING, 141  
 ER\_DD\_TRG\_DEFINER\_OOM, 141  
 ER\_DD\_TRG\_FILE\_UNREADABLE, 141  
 ER\_DD\_UPDATING\_PLUGIN\_MD\_FAILED, 130  
 ER\_DD\_UPGRADE, 194  
 ER\_DD\_UPGRADE\_COMPLETED, 345  
 ER\_DD\_UPGRADE\_DD\_OPEN\_FAILED, 187  
 ER\_DD\_UPGRADE\_DD\_POPULATED, 187  
 ER\_DD\_UPGRADE\_FAILED\_FIND\_VALID\_DATA\_DIR,  
 188  
 ER\_DD\_UPGRADE\_FAILED\_INIT\_DD\_SE, 188  
 ER\_DD\_UPGRADE\_FAILED\_TO\_ACQUIRE\_TABLESPACE,  
 187  
 ER\_DD\_UPGRADE\_FAILED\_TO\_CREATE\_INDEX\_STATS,  
 188  
 ER\_DD\_UPGRADE\_FAILED\_TO\_CREATE\_TABLE\_STATS,  
 187  
 ER\_DD\_UPGRADE\_FAILED\_TO\_FETCH\_TABLES,  
 187  
 ER\_DD\_UPGRADE\_FAILED\_TO\_FETCH\_TABLESPACES,  
 187  
 ER\_DD\_UPGRADE\_FAILED\_TO\_RESOLVE\_TABLESPACE,  
 187  
 ER\_DD\_UPGRADE\_FAILED\_TO\_UPDATE\_VER\_NO\_IN\_TABLESPACE,  
 193  
 ER\_DD\_UPGRADE\_FOUND\_PARTIALLY\_UPGRADED\_DD\_ABORT,  
 188  
 ER\_DD\_UPGRADE\_FOUND\_PARTIALLY\_UPGRADED\_DD\_CONTINUE,  
 188  
 ER\_DD\_UPGRADE\_FOUND\_PREPARED\_XA\_TRANSACTION,  
 353  
 ER\_DD\_UPGRADE\_INDEX\_STATS\_MIGRATE\_COMPLETED,  
 188  
 ER\_DD\_UPGRADE\_INFO\_FILE\_CLOSE\_FAILED,  
 187  
 ER\_DD\_UPGRADE\_INFO\_FILE\_OPEN\_FAILED,  
 187  
 ER\_DD\_UPGRADE\_OFF, 194  
 ER\_DD\_UPGRADE\_RENAME\_IDX\_STATS\_FILE\_FAILED,  
 187  
 ER\_DD\_UPGRADE\_SCHEMA\_UNAVAILABLE, 194  
 ER\_DD\_UPGRADE\_SDI\_INFO\_UPDATE\_FAILED,  
 188  
 ER\_DD\_UPGRADE\_SE\_LOGS\_FAILED, 188  
 ER\_DD\_UPGRADE\_START, 188  
 ER\_DD\_UPGRADE\_TABLESPACE\_MIGRATION\_FAILED,  
 187  
 ER\_DD\_UPGRADE\_TABLE\_INTACT\_ERROR, 192  
 ER\_DD\_UPGRADE\_TABLE\_STATS\_MIGRATE\_COMPLETED,  
 188  
 ER\_DD\_UPGRADE\_VERSION\_NOT\_SUPPORTED,  
 194  
 ER\_DD\_UPGRADE\_VIEW\_COLUMN\_NAME\_TOO\_LONG,  
 193  
 ER\_DD\_VERSION\_FOUND, 129  
 ER\_DD\_VERSION\_INSTALLED, 129  
 ER\_DD\_VERSION\_UNSUPPORTED, 129  
 ER\_DD\_VIEW\_CANT\_ALLOC\_CHARSET, 129  
 ER\_DD\_VIEW\_CANT\_CREATE, 130  
 ER\_DD\_VIEW\_WITHOUT\_DEFINER, 142  
 ER\_DEBUG\_SYNC\_EXECUTED, 131  
 ER\_DEBUG\_SYNC\_HIT, 131  
 ER\_DEBUG\_SYNC\_HIT\_LIMIT, 40  
 ER\_DEBUG\_SYNC\_OOM, 131  
 ER\_DEBUG\_SYNC\_THREAD\_MAX, 131  
 ER\_DEBUG\_SYNC\_TIMEOUT, 40  
 ER\_DEFAULT\_AS\_VAL\_GENERATED, 91  
 ER\_DEFAULT\_SE\_UNAVAILABLE, 141  
 ER\_DEFAULT\_VAL\_GENERATED\_FUNCTION\_IS\_NOT\_ALLOWED,  
 ER\_DEFAULT\_VAL\_GENERATED\_NAMED\_FUNCTION\_IS\_NOT\_ALLOWED,  
 ER\_DEFAULT\_VAL\_GENERATED\_NON\_PRIOR,  
 ER\_DEFAULT\_VAL\_GENERATED\_REF\_AUTO\_INC,  
 91  
 ER\_DEFAULT\_VAL\_GENERATED\_ROW\_VALUE,  
 ER\_DEFAULT\_VAL\_GENERATED\_VARIABLES,  
 ER\_DEFAULT\_VAL\_GENERATED\_VARIABLES\_ENGINE,  
 ER\_DEFINITION\_CONTAINS\_INVALID\_STRING,  
 ER\_DEPART\_WITH\_GRACE, 133  
 ER\_DEPENDENT\_BY\_CHECK\_CONSTRAINT, 105  
 ER\_DEPENDENT\_BY\_DEFAULT\_GENERATED\_VALUE,  
 ER\_DEPENDENT\_BY\_FUNCTIONAL\_INDEX, 96  
 ER\_DEPENDENT\_BY\_GENERATED\_COLUMN, 65  
 ER\_DEPENDENT\_BY\_PARTITION\_FUNC, 97  
 ER\_DEPRECATED\_NATIONAL, 87  
 ER\_DEPRECATED\_PERSISTED\_VARIABLE\_WITH\_ALIAS,  
 371  
 ER\_DEPRECATED\_SYNTAX\_NO\_REPLACEMENT,  
 192  
 ER\_DEPRECATED\_SYNTAX\_WITH\_REPLACEMENT,  
 192  
 ER\_DEPRECATED\_TIMESTAMP\_IMPLICIT\_DEFAULTS,  
 134  
 ER\_DEPRECATED\_UTF8\_ALIAS, 87  
 ER\_DEPRECATED\_MSG\_NO\_REPLACEMENT, 192  
 ER\_DEPRECATED\_MSG\_WITH\_REPLACEMENT,  
 181  
 ER\_DERIVED\_MUST\_HAVE\_ALIAS, 18  
 ER\_DES\_FILE\_WRONG\_KEY, 142  
 ER\_DETACHED\_SESSIONS\_LEFT\_BY\_PLUGIN,  
 160  
 ER\_DETACHING\_SESSION\_LEFT\_BY\_PLUGIN,  
 160  
 ER\_DIMENSION\_UNSUPPORTED, 62  
 ER\_DISABLED\_STORAGE\_ENGINE, 69  
 ER\_DISABLED\_STORAGE\_ENGINE\_AS\_DEFAULT,  
 131



---

ER\_DISABLE\_AUTO\_POSITION\_REQUIRES\_ASYNC\_REPLICATIONS, 151  
 108  
 ER\_DISABLE\_GTID\_MODE\_REQUIRES\_ASYNC\_REPLICATIONS, 151  
 107  
 ER\_DISALLOWED\_OPERATION, 83  
 ER\_DISCARD\_FK\_CHECKS\_RUNNING, 51  
 ER\_DISCONNECTING\_REMAINING\_CLIENTS, 136  
 ER\_DISK\_FULL\_NOWAIT, 84  
 ER\_DIVISION\_BY\_ZERO, 25  
 ER\_DONT\_SUPPORT\_REPLICA\_PRESERVE\_COMMIT\_ORDER, 59  
 ER\_DROP\_DATABASE\_FAILED\_RMDIR\_MANUALLY, 193  
 ER\_DROP\_FILEGROUP\_FAILED, 35  
 ER\_DROP\_INDEX\_FK, 35  
 ER\_DROP\_LAST\_PARTITION, 33  
 ER\_DROP\_PARTITION\_NON\_EXISTENT, 33  
 ER\_DROP\_PK\_COLUMN\_TO\_DROP\_GIPK, 117  
 ER\_DUPLICATED\_VALUE\_IN\_TYPE, 21  
 ER\_DUPLICATE\_OPTION\_KEY, 76  
 ER\_DUPLICATE\_SYS\_VAR, 329  
 ER\_DUPLICATE\_TABLE\_LOCK, 77  
 ER\_DUP\_ARGUMENT, 17  
 ER\_DUP\_ENTRY, 7  
 ER\_DUP\_ENTRY\_AUTOINCREMENT\_CASE, 36  
 ER\_DUP\_ENTRY\_WITH\_KEY\_NAME, 37  
 ER\_DUP\_FD\_OPEN\_FAILED, 183  
 ER\_DUP\_FIELDNAME, 7  
 ER\_DUP\_INDEX, 53  
 ER\_DUP\_KEY, 4  
 ER\_DUP\_KEYNAME, 7  
 ER\_DUP\_LIST\_ENTRY, 59  
 ER\_DUP\_SIGNAL\_SET, 40  
 ER\_DUP\_UNIQUE, 14  
 ER\_DUP\_UNKNOWN\_IN\_INDEX, 55  
 ER\_EMPTY\_PIPELINE\_FOR\_ERROR\_LOG\_SERVICE, 86  
 ER\_EMPTY\_PRIVILEGE\_NAME\_IGNORED, 362  
 ER\_EMPTY\_QUERY, 7  
 ER\_ENDING\_INIT, 328  
 ER\_END\_INITFILE, 137  
 ER\_ENFORCE\_GTID\_CONSISTENCY\_WARN\_WITH\_ONE\_TRANSACTION\_BEFORE\_STARTS, 65  
 ER\_ENGINE\_ATTRIBUTE\_NOT\_SUPPORTED, 107  
 ER\_ENGINE\_CANT\_DROP\_MISSING\_TABLE, 79  
 ER\_ENGINE\_CANT\_DROP\_TABLE, 79  
 ER\_ENGINE\_COST\_FAILED\_TO\_READ, 157  
 ER\_ENGINE\_COST\_INVALID\_CONST\_CONSTANT\_FOR\_SE, 157  
 ER\_ENGINE\_COST\_INVALID\_DEVICE\_TYPE\_FOR\_SE, 157  
 ER\_ENGINE\_COST\_UNKNOWN\_COST\_CONSTANT, 157  
 ER\_ENGINE\_COST\_UNKNOWN\_STORAGE\_ENGINE, 157  
 ER\_ENGINE\_OUT\_OF\_MEMORY, 58  
 ER\_ERRMSG\_CANT\_FIND\_FILE, 151  
 ER\_ERRMSG\_CANT\_READ, 151  
 ER\_ERRMSG\_LOADING\_55\_STYLE, 151  
 ER\_ERRMSG\_MISSING\_IN\_FILE, 151  
 ER\_ERRMSG\_OOM, 151  
 ER\_ERRMSG\_REPLACEMENTS\_FAILED, 179  
 ER\_ERRMSG\_REPLACEMENT\_DODGY, 179  
 ER\_ERROR\_DURING\_COMMIT, 14  
 ER\_ERROR\_DURING\_FLUSH\_LOGS, 14  
 ER\_ERROR\_DURING\_FLUSH\_LOG\_COMMIT\_PHASE, 14  
 ER\_ERROR\_DURING\_OPTIMIZE\_TABLE, 171  
 ER\_ERROR\_DURING\_ROLLBACK, 14  
 ER\_ERROR\_ENABLING\_KEYS, 171  
 ER\_ERROR\_INFO\_FROM\_DA, 325  
 ER\_ERROR\_IN\_TRIGGER\_BODY, 45  
 ER\_ERROR\_IN\_UNKNOWN\_TRIGGER\_BODY, 45  
 ER\_ERROR\_LOG\_DESTINATION\_NOT\_A\_FILE, 362  
 ER\_ERROR\_ON\_MODIFYING\_GTID\_EXECUTED\_TABLE, 70  
 ER\_ERROR\_ON\_READ, 4  
 ER\_ERROR\_ON\_RENAME, 4  
 ER\_ERROR\_ON\_SOURCE, 57  
 ER\_ERROR\_ON\_WRITE, 4  
 ER\_ERROR\_WHEN\_EXECUTING\_COMMAND, 17  
 ER\_EVENT\_ALREADY\_EXISTS, 35  
 ER\_EVENT\_CANNOT ALTER IN THE PAST, 37  
 ER\_EVENT\_CANNOT\_CREATE\_IN\_THE\_PAST, 37  
 ER\_EVENT\_CANT\_FIND\_TIMEZONE, 172  
 ER\_EVENT\_CANT\_GET\_CHARSET, 172  
 ER\_EVENT\_CANT\_GET\_COLLATION, 172  
 ER\_EVENT\_CANT\_GET\_LOCK\_FOR\_DROPPING\_EVENT, 173  
 ER\_EVENT\_CANT\_GET\_TIMEZONE\_FROM\_FIELD, 172  
 ER\_EVENT\_CANT\_INIT\_QUEUE, 131  
 ER\_EVENT\_CANT\_OPEN\_TABLE\_MYSQL\_EVENT, 172  
 ER\_EVENT\_DOES\_NOT\_EXIST, 35  
 ER\_EVENT\_DROPPING, 158  
 ER\_EVENT\_INTERVAL\_BEFORE\_STARTS, 35  
 ER\_EVENT\_ERROR\_CREATING\_QUERY\_TO\_WRITE\_TO, 173  
 ER\_EVENT\_ERROR\_DURING\_COMPILATION, 158  
 ER\_EVENT\_EXECUTION\_FAILED, 131  
 ER\_EVENT\_EXECUTION\_FAILED\_CANT\_AUTHENTICATE\_USER\_AND\_DEVICE, 158  
 ER\_EVENT\_EXECUTION\_FAILED\_USER\_LOST\_EVEN\_PASSWORD, 158  
 ER\_EVENT\_EXEC\_TIME\_IN\_THE\_PAST, 35  
 ER\_EVENT\_INTERVAL\_NOT\_POSITIVE\_OR\_TOO\_BIG, 35  
 ER\_EVENT\_INVALID\_CREATION\_CTX, 38  
 ER\_EVENT\_LAST\_EXECUTION, 131  
 ER\_EVENT\_MESSAGE\_STACK, 131

---

---

ER\_EVENT\_PURGING\_QUEUE, 131  
ER\_EVENT\_RECURSION\_FORBIDDEN, 37  
ER\_EVENT\_SAME\_NAME, 35  
ER\_EVENT\_SCHEDULER\_ERROR\_GETTING\_EVENT\_OBJECT, 173  
ER\_EVENT\_SCHEDULER\_ERROR\_LOADING\_FROM\_DATABASE, 173  
ER\_EVENT\_SCHEDULER\_GOT\_BAD\_DATA\_FROM\_TABLE, 173  
ER\_EVENT\_SET\_VAR\_ERROR, 36  
ER\_EVENT\_UNABLE\_TO\_DROP\_EVENT, 174  
ER\_EXCEEDED\_MV\_KEYS\_NUM, 101  
ER\_EXCEEDED\_MV\_KEYS\_SPACE, 101  
ER\_EXCEPTIONS\_WRITE\_ERROR, 39  
ER\_EXCESS\_ARGUMENTS, 138  
ER\_EXPLAIN\_INTO\_ANALYZE\_NOT\_SUPPORTED, 122  
ER\_EXPLAIN\_INTO\_FORMAT\_NOT\_SUPPORTED, 122  
ER\_EXPLAIN\_INTO\_FOR\_CONNECTION\_NOT\_SUPPORTED, 122  
ER\_EXPLAIN\_INTO\_IMPLICIT\_FORMAT\_NOT\_SUPPORTED, 122  
ER\_EXPLAIN\_NOT\_SUPPORTED, 58  
ER\_FAILED\_DEFAULT\_ROLES, 74  
ER\_FAILED\_GET\_DD\_PROPERTY, 395  
ER\_FAILED\_READ\_FROM\_PAR\_FILE, 44  
ER\_FAILED\_REVOKE\_ROLE, 74  
ER\_FAILED\_ROLE\_GRANT, 74  
ER\_FAILED\_SET\_DD\_PROPERTY, 395  
ER\_FAILED\_START\_MYSQLD\_DAEMON, 183  
ER\_FAILED\_TO\_ACQUIRE\_LOCK\_ON\_RESOURCE\_GROUP, 185  
ER\_FAILED\_TO\_ADD\_RESOURCE\_GROUP\_TO\_MAP, 185  
ER\_FAILED\_TO\_ADD\_RPL\_FILTER, 189  
ER\_FAILED\_TO\_ALLOCATE\_MEMORY\_FOR\_RESOURCE\_GROUP, 185  
ER\_FAILED\_TO\_ALLOCATE\_MEMORY\_FOR\_RESOURCE\_GROUP\_HASWRITE, 185  
ER\_FAILED\_TO\_ALLOCATE\_SSL\_BIO, 328  
ER\_FAILED\_TO\_APPLY\_RESOURCE\_GROUP\_CONTROL, 185  
ER\_FAILED\_TO\_BINLOG\_DROP\_EVENT, 189  
ER\_FAILED\_TO\_BUILD\_DO\_AND\_IGNORE\_TABLE\_HASH, 189  
ER\_FAILED\_TO\_COMPRESS\_GTID\_EXECUTED\_TABLE, 154  
ER\_FAILED\_TO\_COMPRESS\_GTID\_EXECUTED\_TABLE\_FROM\_OLD, 155  
ER\_FAILED\_TO\_CONSTRUCT\_DROP\_EVENT\_QUERY, 189  
ER\_FAILED\_TO\_CREATE\_GTID\_TABLE\_COMPRESSION\_THREAD, 155  
ER\_FAILED\_TO\_CREATE\_SDI\_FOR\_TABLESPACE, 187  
ER\_FAILED\_TO\_DECREMENT\_NUMBER\_OF\_THREADS, 160  
ER\_FAILED\_TO\_DELETE\_FROM\_GTID\_EXECUTED\_TABLE, 154  
ER\_FAILED\_TO\_DESERIALIZE\_RESOURCE\_GROUP, OBJECT,  
ER\_FAILED\_TO\_DETERMINE\_IF\_ROLE\_IS\_MANDATORY, 184  
ER\_FAILED\_TO\_FETCH\_MANDATORY\_ROLE\_LIST, TABLE,  
ER\_FAILED\_TO\_FIND\_COLLATION\_NAME, 182  
ER\_FAILED\_TO\_FIND\_DL\_ENTRY, 180  
ER\_FAILED\_TO\_FIND\_LOCALE\_NAME, 182  
ER\_FAILED\_TO\_FIND\_MYSQLD\_STATUS, 192  
ER\_FAILED\_TO\_GENERATE\_UNIQUE\_LOGFILE, 180  
ER\_FAILED\_TO\_GET\_ABSOLUTE\_PATH, 183  
ER\_FAILED\_TO\_HANDLE\_DEFAULTS\_FILE, 329  
ER\_FAILED\_TO\_INIT\_SYS\_VAR, 329  
ER\_FAILED\_TO\_INIT\_THREAD\_ATTR\_FOR\_GTID\_TABLE\_COMPRESSION\_THREAD, 155  
ER\_FAILED\_TO\_JOIN\_GTID\_TABLE\_COMPRESSION\_THREADS, 155  
ER\_FAILED\_TO\_LOCK\_MEM, 137  
ER\_FAILED\_TO\_OPEN\_COST\_CONSTANT\_TABLES, 158  
ER\_FAILED\_TO\_OPEN\_SHARED\_LIBRARY, 180  
ER\_FAILED\_TO\_PERSIST\_RESOURCE\_GROUP\_METADATA, 185  
ER\_FAILED\_TO\_READ\_FILE, 180  
ER\_FAILED\_TO\_REMOVE\_TEMP\_TABLE, 168  
ER\_FAILED\_TO\_REPAIR\_TABLE, 168  
ER\_FAILED\_TO\_SET\_PERSISTED\_OPTIONS, 192  
ER\_FAILED\_TO\_START\_REPLICA\_THREAD, 189  
ER\_FAILED\_TO\_STORE\_SDI\_FOR\_TABLESPACE, GROUP,  
ER\_FAILED\_TO\_UPDATE\_RESOURCE\_GROUP, 185  
ER\_FAILED\_TO\_VALIDATE\_CERTIFICATES\_SERVER\_EXIT, 396  
ER\_FAIL\_HASWRITE\_TO\_FILE, 180  
ER\_FAIL\_CHROOT, 137  
ER\_FAIL\_SETGID, 137  
ER\_FAIL\_SETREGID, 137  
ER\_FAIL\_SETREUID, 137  
ER\_FAIL\_SETTUID, 137  
ER\_FAIL\_FEATURE\_DISABLED, 21  
ER\_FAIL\_FEATURE\_DISABLED\_SEE\_DOC, 69  
ER\_FAIL\_FEATURE\_NOT\_AVAILABLE, 65  
ER\_FAIL\_FEATURE\_UNSUPPORTED, 83  
ER\_FAIL\_WOULD\_IN\_GROUPING\_NOT\_GROUP\_BY, 79  
ER\_FAIL\_FIELD\_IN\_ORDER\_NOT\_SELECT, 61  
ER\_FAIL\_FIELD\_NOT\_FOUND\_PART\_ERROR, 32  
ER\_FAIL\_FIELD\_SPECIFIED\_TWICE, 10  
ER\_FAIL\_INTEGER\_TYPE\_NOT\_ALLOWED\_AS\_PARTITION\_FIELD, 41  
ER\_FAIL\_FILEGROUP\_OPTION\_ONLY\_ONCE, 34  
ER\_FAIL\_FILE\_CORRUPT, 57  
ER\_FAIL\_FILE\_EXISTS\_DURING\_UPGRADE, 173  
ER\_FAIL\_FILE\_EXISTS\_ERROR, 8

---

ER\_FILE\_HAS\_OLD\_FORMAT, 181  
 ER\_FILE\_NOT\_FOUND, 4  
 ER\_FILE\_TYPE\_UNKNOWN, 152  
 ER\_FILE\_USED, 5  
 ER\_FIREWALL\_ACCESS\_DENIED, 201  
 ER\_FIREWALL\_DEPRECATED\_USER\_PROFILE, 369  
 ER\_FIREWALL\_FAILED\_TO\_READ\_FIREWALL\_TABLES, 201  
 ER\_FIREWALL\_FAILED\_TO\_REG\_DYNAMIC\_PRIVILEGES, 201  
 ER\_FIREWALL\_INVALID\_RELOAD\_INTERVAL\_VALUE, 398  
 ER\_FIREWALL\_PFS\_TABLE\_REGISTER\_FAILED, 366  
 ER\_FIREWALL\_RECORDING\_STMT\_WAS\_TRUNCATED, 201  
 ER\_FIREWALL\_RECORDING\_STMT\_WITHOUT\_TEXT, 201  
 ER\_FIREWALL\_RELOADING\_CACHE, 201  
 ER\_FIREWALL\_RESET\_FOR\_USER, 201  
 ER\_FIREWALL\_SCHEDULER\_REGISTER\_FAILED, 398  
 ER\_FIREWALL\_SERVICES\_NOT\_ACQUIRED, 366  
 ER\_FIREWALL\_SKIPPED\_UNKNOWN\_USER\_MODE, 201  
 ER\_FIREWALL\_STATUS\_FLUSHED, 201  
 ER\_FIREWALL\_SUSPICIOUS\_STMT, 201  
 ER\_FIREWALL\_UDF\_REGISTER\_FAILED, 366  
 ER\_FIXING\_CLIENT\_CHARSET, 137  
 ER\_FK\_CANNOT\_CHANGE\_ENGINE, 91  
 ER\_FK\_CANNOT\_DROP\_PARENT, 88  
 ER\_FK\_CANNOT\_OPEN\_PARENT, 53  
 ER\_FK\_CANNOT\_USE\_VIRTUAL\_COLUMN, 88  
 ER\_FK\_COLUMN\_CANNOT\_CHANGE, 53  
 ER\_FK\_COLUMN\_CANNOT\_CHANGE\_CHILD, 53  
 ER\_FK\_COLUMN\_CANNOT\_DROP, 53  
 ER\_FK\_COLUMN\_CANNOT\_DROP\_CHILD, 53  
 ER\_FK\_COLUMN\_NOT\_NULL, 53  
 ER\_FK\_DEPTH\_EXCEEDED, 57  
 ER\_FK\_DUP\_NAME, 53  
 ER\_FK\_FAIL\_ADD\_SYSTEM, 52  
 ER\_FK\_INCOMPATIBLE\_COLUMNS, 91  
 ER\_FK\_INCORRECT\_OPTION, 53  
 ER\_FK\_NO\_COLUMN\_PARENT, 88  
 ER\_FK\_NO\_INDEX\_CHILD, 52  
 ER\_FK\_NO\_INDEX\_PARENT, 52  
 ER\_FORBID\_SCHEMA\_CHANGE, 30  
 ER\_FORCE\_CLOSE\_THREAD, 181  
 ER\_FORCING\_CLOSE, 8  
 ER\_FOREIGN\_DATA\_SOURCE\_DOESNT\_EXIST, 29  
 ER\_FOREIGN\_DATA\_STRING\_INVALID, 29  
 ER\_FOREIGN\_DATA\_STRING\_INVALID\_CANT\_CREATE, 29  
 ER\_FOREIGN\_DUPLICATE\_KEY\_OLD\_UNUSED, 36  
 ER\_FOREIGN\_DUPLICATE\_KEY\_WITHOUT\_CHILD\_INFO, 48  
 ER\_FOREIGN\_DUPLICATE\_KEY\_WITH\_CHILD\_INFO, 48  
 ER\_FOREIGN\_KEY\_ON\_PARTITIONED, 33  
 ER\_FOREIGN\_KEY\_WITH\_ATOMIC\_CREATE\_SELECT, 106  
 ER\_FOREIGN\_SERVER\_DOESNT\_EXIST, 32  
 ER\_FOREIGN\_SERVER\_EXISTS, 32  
 ER\_FOUND\_MISSING\_GTIDS, 246  
 ER\_FOUND\_ROWS\_WHILE\_REPAIRING, 170  
 ER\_FPARSER\_BAD\_HEADER, 24  
 ER\_FPARSER\_EOF\_IN\_COMMENT, 24  
 ER\_FPARSER\_EOF\_IN\_UNKNOWN\_PARAMETER, 24  
 ER\_FPARSER\_ERROR\_IN\_PARAMETER, 24  
 ER\_FPARSER\_TOO\_BIG\_FILE, 24  
 ER\_FSEEK\_FAIL, 26  
 ER\_FT\_BOOL\_SYNTAX\_INVALID, 134  
 ER\_FT\_MATCHING\_KEY\_NOT\_FOUND, 15  
 ER\_FULLTEXT\_FUNCTIONAL\_INDEX, 90  
 ER\_FULLTEXT\_NOT\_SUPPORTED\_WITH\_PARTITIONING, 48  
 ER\_FULLTEXT\_WITH\_ROLLUP, 114  
 ER\_FUNCTIONAL\_INDEX\_DATA\_IS\_TOO\_LONG, 101  
 ER\_FUNCTIONAL\_INDEX\_FUNCTION\_IS\_NOT\_ALLOWED, 90  
 ER\_FUNCTIONAL\_INDEX\_ON\_FIELD, 90  
 ER\_FUNCTIONAL\_INDEX\_ON\_JSON\_OR\_GEOMETRY\_FUNCTIONS, 89  
 ER\_FUNCTIONAL\_INDEX\_ON\_LOB, 90  
 ER\_FUNCTIONAL\_INDEX\_PRIMARY\_KEY, 90  
 ER\_FUNCTIONAL\_INDEX\_REF\_AUTO\_INCREMENT, 90  
 ER\_FUNCTIONAL\_INDEX\_ROW\_VALUE\_IS\_NOT\_ALLOWED, 93  
 ER\_FUNCTION\_DOES\_NOT\_SUPPORT\_CHARACTER\_SET, 107  
 ER\_FUNCTION\_NOT\_DEFINED, 11  
 ER\_FUNC\_INEXISTENT\_NAME\_COLLISION, 39  
 ER\_FUTURE\_DATE, 136  
 ER\_GENERATED\_COLUMN\_FUNCTION\_IS\_NOT\_ALLOWED, 64  
 ER\_GENERATED\_COLUMN\_NAMED\_FUNCTION\_IS\_NOT\_ALLOWED, 90  
 ER\_GENERATED\_COLUMN\_NON\_PRIOR, 65  
 ER\_GENERATED\_COLUMN\_REF\_AUTO\_INC, 65  
 ER\_GENERATED\_COLUMN\_ROW\_VALUE, 90  
 ER\_GENERATED\_COLUMN\_VARIABLES, 90  
 ER\_GEOMETRY\_IN\_UNKNOWN\_LENGTH\_UNIT, 99  
 ER\_GEOMETRY\_PARAM\_LATITUDE\_OUT\_OF\_RANGE, 88  
 ER\_GEOMETRY\_PARAM\_LONGITUDE\_OUT\_OF\_RANGE, 88  
 ER\_GET\_ERRMSG, 21  
 ER\_GET\_ERRNO, 5

---

ER_GET_ERRNO_FROM_STORAGE_ENGINE, 182	ER_GROUP_REPLICATION_ERROR_DECOMPRESS_INITIALI 400
ER_GET_STACKED_DA_WITHOUT_ACTIVE_HANDLER, 57	ER_GROUP_REPLICATION_ERROR_RECEIVED_WAITING_M 401
ER_GET_TEMPORARY_ERRMSG, 21	ER_GROUP_REPLICATION_FORCE_MEMBERS_COMMAND_ 117
ER_GIPK_COLUMN_ALTER_NOT_ALLOWED, 117	ER_GROUP_REPLICATION_MAX_GROUP_SIZE, 71
ER_GIPK_COLUMN_EXISTS, 117	ER_GROUP_REPLICATION_METADATA_CERT_INFO_ENCODE 403
ER_GIPK_FAILED_AUTOINC_COLUMN_EXISTS, 117	ER_GROUP_REPLICATION_METADATA_CERT_INFO_ERROR 402
ER_GIS_DATA_WRONG_ENDIANNESS, 61	ER_GROUP_REPLICATION_METADATA_CERT_INFO_PACKE 403
ER_GIS_DIFFERENT_SRIDS, 59	ER_GROUP_REPLICATION_METADATA_CERT_INFO_PACKE 402
ER_GIS_DIFFERENT_SRIDS_AGGREGATION, 111	ER_GROUP_REPLICATION_METADATA_ERROR_ON_SEND_ 402
ER_GIS_INVALID_DATA, 60	ER_GROUP_REPLICATION_METADATA_INITIALIZATION_FAI 402
ER_GIS_MAX_POINTS_IN_GEOMETRY_OVERFLOWED, 67	ER_GROUP_REPLICATION_METADATA_MEMORY_ALLOC, 402
ER_GIS_UNKNOWN_ERROR, 59	ER_GROUP_REPLICATION_METADATA_MESSAGE_PAYLOAD 401
ER_GIS_UNKNOWN_EXCEPTION, 60	ER_GROUP_REPLICATION_METADATA_NO_VALID_DONOR, 403
ER_GIS_UNSUPPORTED_ARGUMENT, 59	ER_GROUP_REPLICATION_METADATA_PAYLOAD_DECODIN 402
ER_GLOBAL_CONN_LIMIT, 377	ER_GROUP_REPLICATION_METADATA_PAYLOAD_EMPTY, 403
ER_GLOBAL_VARIABLE, 17	ER_GROUP_REPLICATION_METADATA_PAYLOAD_PARSE 401
ER_GLOBSTAT_CHANGE_DURING_QUERY, 101	ER_GROUP_REPLICATION_METADATA_PROTOBUF_PARSIN 400
ER_GNO_EXHAUSTED, 49	ER_GROUP_REPLICATION_METADATA_READ_GTID_EXECU 400
ER_GRANT_WRONG_HOST_OR_USER, 12	ER_GROUP_REPLICATION_METADATA_SAVE_RECOVERY_ 403
ER_GROUPING_ON_TIMESTAMP_IN_DST, 101	ER_GROUP_REPLICATION_METADATA_SESSION_ERROR, 400
ER_GROUP_REPLICATION_APPLIER_INIT_ERROR, 64	ER_GROUP_REPLICATION_METADATA_SENDER, 400
ER_GROUP_REPLICATION_CERTIFICATION_MODULE_ 402	ER_GROUP_REPLICATION_METADATA_SENDER_IS_REMO 400
ER_GROUP_REPLICATION_CERTIFIER_MESSAGE_LA 399	ER_GROUP_REPLICATION_METADATA_SEND_ERROR, 401
ER_GROUP_REPLICATION_COMMAND_FAILURE, 83	ER_GROUP_REPLICATION_METADATA_SET_IN_RECOVERY 402
ER_GROUP_REPLICATION_COMMUNICATION_LAYER_ 64	ER_GROUP_REPLICATION_NO_CERTIFICATION_DONOR_AV 403
ER_GROUP_REPLICATION_COMMUNICATION_LAYER_ 64	ER_GROUP_REPLICATION_PASSWORD_LENGTH, 106
ER_GROUP_REPLICATION_COMPRESS_EXCEEDS_M 400	ER_GROUP_REPLICATION_PLUGIN_NOT_INSTALLED, 154
ER_GROUP_REPLICATION_COMPRESS_OUT_OF_MEMO 400	ER_GROUP_REPLICATION_PROTOBUF_SERIALIZING_ERR 401
ER_GROUP_REPLICATION_COMPRESS_PROCESS, 399	ER_GROUP_REPLICATION_RECOVERY_ERROR_ADD_GTID 402
ER_GROUP_REPLICATION_CONFIGURATION, 63	ER_GROUP_REPLICATION_RECOVERY_FETCHING_GTID_E 402
ER_GROUP_REPLICATION_DECOMPRESS_CORRUPTED, 400	ER_GROUP_REPLICATION_RECOVERY_METADATA_SENDE 402
ER_GROUP_REPLICATION_DECOMPRESS_END, 400	
ER_GROUP_REPLICATION_DECOMPRESS_EXCEEDS_M 400	
ER_GROUP_REPLICATION_DECOMPRESS_OUT_OF_M 400	
ER_GROUP_REPLICATION_DECOMPRESS_PROCESS, 400	
ER_GROUP_REPLICATION_DECOMPRESS_TRUNCATED, 400	
ER_GROUP_REPLICATION_ERROR_COMPRESS_INITI 399	

ER_GROUP_REPLICATION_RECOVERY_SKIPPED_GTID_PRESENT,	ER_GRP_RPL_APPLIER_TERMINATION_TIMED_OUT_ON
402	234
ER_GROUP_REPLICATION_RECOVERY_STOPPED_GTID_PRESENT,	ER_GRP_RPL_APPLIER_THD_EXECUTION_ABORTED,
403	219
ER_GROUP_REPLICATION_RUNNING, 63	ER_GRP_RPL_APPLIER_THD_KILLED, 218
ER_GROUP_REPLICATION_STOP_APPLIER_THREAD_INTERRUPT,	ER_GRP_RPL_APPLIER_THD_SETUP_ERROR,
64	225
ER_GROUP_REPLICATION_TIMEOUT_ERROR_FETCHING_METADATA,	ER_GRP_RPL_APPLIER_THD_START_ERROR,
401	225
ER_GROUP_REPLICATION_UNKOWN_COMPRESSION_ERROR,	ER_GRP_RPL_APPLIER_THD_STOP_ERROR,
399	225
ER_GROUP_REPLICATION_USER_EMPTY_MSG,	ER_GRP_RPL_APPOINTED_PRIMARY_NOT_PRESENT,
106	330
ER_GROUP_REPLICATION_USER_MANDATORY_MSG,	ER_GRP_RPL_AUTO_INC_OFFSET_RESET, 226
106	ER_GRP_RPL_AUTO_INC_OFFSET_SET, 226
ER_GRP_OPERATION_NOT_ALLOWED_GRP_MUST_STOP,	ER_GRP_RPL_AUTO_INC_RESET, 226
105	ER_GRP_RPL_AUTO_INC_SET, 226
ER_GRP_RPL_ABORTS_AS_SSL_NOT_SUPPORTED_ERROR,	ER_GRP_RPL_BINLOG_DISABLED, 236
236	ER_GRP_RPL_BLOCK_SIZE_DIFF_FROM_GRP,
ER_GRP_RPL_ADD_GRP_SID_TO_GRP_GTIDS_MAP_ERROR,	225,
219	ER_GRP_RPL_BROADCASTING_TRANS_TO_GRP_FAILED,
ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_LOCAL_GTID,	221 FAILED,
227	ER_GRP_RPL_BROADCAST_COMMIT_MSSG_TOO_BIG,
ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_REMOTE_GTID,	240D FAILED,
227	ER_GRP_RPL_BROADCAST_COMMIT_TRANS_MSSG_FAILED,
ER_GRP_RPL_ADD_GTID_INFO_WITH_LOCAL_GTID,	241D,
227	ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_ERROR,
ER_GRP_RPL_ADD_GTID_INFO_WITH_REMOTE_GTID,	230A FAILED,
227	ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_OFFLINE,
ER_GRP_RPL_ADD_GTID_TO_GRP_GTID_EXECUTED_ERROR,	230B,
220	ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_RECORDING,
ER_GRP_RPL_ADD_RETRIEVED_SET_TO_GRP_GTID_EXECUTED,	230C,
220	ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_STOPPING,
ER_GRP_RPL_ADD_VIEW_CHANGE_UUID_TO_GRP_SID_MAP,	230D MAP_ERROR,
370	ER_GRP_RPL_CANT_GENERATE_GTID, 220
ER_GRP_RPL_ALL_DONORS_LEFT_ABORT_RECOVERY,	ER_GRP_RPL_CANT_KILL_THREAD, 348
228	ER_GRP_RPL_CANT_READ_GRP_GTID_EXTRACTED,
ER_GRP_RPL_ALL_OBSERVERS_UNREGISTERED,	221
235	ER_GRP_RPL_CANT_READ_GTID, 221
ER_GRP_RPL_APPLIER_CHANNEL_STILL_RUNNING,	ER_GRP_RPL_CANT_READ_WRITE_SET_ITEM,
365	221
ER_GRP_RPL_APPLIER_ERROR_PACKET_RECEIVED,	ER_GRP_RPL_CERTIFICATE_SIZE_ERROR, 218
404	ER_GRP_RPL_CERTIFICATION_INITIALIZATION_FAILURE,
ER_GRP_RPL_APPLIER_EXECUTION_FATAL_ERROR,	220
219	ER_GRP_RPL_CERTIFICATION_REC_PROCESS,
ER_GRP_RPL_APPLIER_HANDLER_IS_IN_USE,	232
238	ER_GRP_RPL_CERTIFIER_MSSG_PROCESS_ERROR,
ER_GRP_RPL_APPLIER_HANDLER_NOT_INITIALIZED,	221
238	ER_GRP_RPL_CHANGE_GRP_MEM_NOT_PROCESSED,
ER_GRP_RPL_APPLIER_HANDLER_ROLE_IS_IN_USE,	222
238	ER_GRP_RPL_CHANNEL_THREAD_WHEN_GROUP_ACTIVE,
ER_GRP_RPL_APPLIER_INITIALIZED,	235
235	ER_GRP_RPL_CHECK_STATUS_TABLE, 229
ER_GRP_RPL_APPLIER_METADATA_REPO_MUST_BE_AVAILABLE,	ER_GRP_RPL_CLONE_PROCESS_EXEC_ERROR,
236	235,
ER_GRP_RPL_APPLIER_NOT_STARTED_DUE_TO_RUNNING_PREV_SHUTDOWN,	235,
235	ER_GRP_RPL_CLONE_PROCESS_PREPARE_ERROR,
ER_GRP_RPL_APPLIER_PIPELINE_NOT_DISPOSED,	347
219	

ER_GRP_RPL_COMMUNICATION_SSL_CONF_INFO, 236	ER_GRP_RPL_ERROR_SENDING_SINGLE_PRIMARY_MSSG, 219
ER_GRP_RPL_CONFIGURATION_ACTION_END, 331	ER_GRP_RPL_ERROR_SET_MULTI_CONSENSUS_LEADER, 376
ER_GRP_RPL_CONFIGURATION_ACTION_ERROR, 331	ER_GRP_RPL_ERROR_SET_SINGLE_CONSENSUS_LEADER, 376
ER_GRP_RPL_CONFIGURATION_ACTION_KILLED, 331	ER_GRP_RPL_ERROR_STOPPING_CHANNELS, 219
ER_GRP_RPL_CONFIGURATION_ACTION_LOCAL_TERMINATION, 331	ER_GRP_RPL_ERROR_WHILE_WAITING_FOR_CONFLICT_D 232
ER_GRP_RPL_CONFIGURATION_ACTION_START, 331	ER_GRP_RPL_ESTABLISHING_CONN_GRP_REC_DONOR, 229
ER_GRP_RPL_CONFIG_RECOVERY, 229	ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_ANOTHER_D 229
ER_GRP_RPL_CONFLICT_DETECTION_DISABLED, 221	ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_DONOR, 229
ER_GRP_RPL_CONNECTION_METADATA_REPO_MUST_BE_TABLE, 236	ER_GRP_RPL_EVENT_HANDLING_ERROR, 218
ER_GRP_RPL_CONN_INTERNAL_PLUGIN_FAIL, 228	ER_GRP_RPL_EXCEEDS_AUTO_INC_VALUE, 223
ER_GRP_RPL_CONN_KILLED, 396	ER_GRP_RPL_EXIT_GRP_GCS_ERROR, 239
ER_GRP_RPL_COPY_FROM_EMPTY_STRING, 228	ER_GRP_RPL_FAILED_TO_BOOTSTRAP_EVENT_HANDLING 238
ER_GRP_RPL_CREATE_APPLIER_CACHE_ERROR, 219	ER_GRP_RPL_FAILED_TO_BROADCAST_GRP_MEMBERSHIP 230
ER_GRP_RPL_CREATE_GRP_RPL_REC_CHANNEL, 229	ER_GRP_RPL_FAILED_TO_BROADCAST_MEMBER_STATUS 230
ER_GRP_RPL_CREATE_SESSION_UNABLE, 228	ER_GRP_RPL_FAILED_TO_CALL_GRP_COMMUNICATION_IN 233
ER_GRP_RPL_DATA_NOT_PROVIDED_BY_MEM, 224	ER_GRP_RPL_FAILED_TO_CONFIRM_IF_SERVER_LEFT_GRP 233
ER_GRP_RPL_DEBUG_OPTIONS, 239	ER_GRP_RPL_FAILED_TO_CREATE_TRANS_CONTEXT, 231
ER_GRP_RPL_DEFAULT_TABLE_ENCRYPTION_DIFFERENTIAL, 342	ER_GRP_RPL_FAILED_TO_ENABLE_READ_ONLY_MODE_ON 234
ER_GRP_RPL_DISABLE_READ_ONLY_FAILED, 223	ER_GRP_RPL_FAILED_TO_ENABLE_SUPER_READ_ONLY_M 233
ER_GRP_RPL_DISABLE_SRV_READ_MODE_RESTRICTIONS, 222	ER_GRP_RPL_FAILED_TO_EXTRACT_TRANS_WRITE_SET, 231
ER_GRP_RPL_DONOR_CONN_TERMINATION, 229	ER_GRP_RPL_FAILED_TO_GATHER_TRANS_WRITE_SET, 231
ER_GRP_RPL_DONOR_SERVER_CONN, 229	ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_GRP, 231
ER_GRP_RPL_DONOR_TRANS_INFO_ERROR, 220	ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_VIEW_C 237
ER_GRP_RPL_DONOR_VIEW_CHANGE_UUID_TRANS_INFO, 371	ER_GRP_RPL_FAILED_TO_INIT_APPLIER_HANDLER, 370
ER_GRP_RPL_ENABLE_READ_ONLY_FAILED, 223	ER_GRP_RPL_FAILED_TO_INIT_APPLIER_MODULE, 337
ER_GRP_RPL_ERROR_FETCHING_GTID_EXECUTED, 220	ER_GRP_RPL_FAILED_TO_INIT_COMMUNICATION_ENGINE, 233
ER_GRP_RPL_ERROR_FETCHING_GTID_SET, 220	ER_GRP_RPL_FAILED_TO_INIT_HANDLER, 234
ER_GRP_RPL_ERROR_GTID_EXECUTION_INFO, 218	ER_GRP_RPL_FAILED_TO_INSERT_TRX_ON_TCM_ON_AFT 337
ER_GRP_RPL_ERROR_GTID_SET_EXTRACTION, 330	ER_GRP_RPL_FAILED_TO_LOG_VIEW_CHANGE, 383
ER_GRP_RPL_ERROR_MSG, 205	ER_GRP_RPL_FAILED_TO_NOTIFY_GRP_MEMBERSHIP_EV 230
ER_GRP_RPL_ERROR_ON_CERT_DB_INSTALL, 339	
ER_GRP_RPL_ERROR_ON_MESSAGE_SENDING, 330	

ER_GRP_RPL_FAILED_TO_PARSE_THE_GRP_NAME,	ER_GRP_RPL_FETCH_TRANS_CONTEXT_FAILED,
235	226
ER_GRP_RPL_FAILED_TO_PARSE_THE_VIEW_CHANGE_LOG_EVENT_ID,	ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_ID,
370	227
ER_GRP_RPL_FAILED_TO_REGISTER_BINLOG_STATE_ON_SERVER,	ER_GRP_RPL_FETCH_TRANS_DATA_FAILED,
235	225
ER_GRP_RPL_FAILED_TO_REGISTER_SERVER_STATE_ON_SERVER,	ER_GRP_RPL_FETCH_VIEW_CHANGE_LOG_EVENT_FAILED,
234	227
ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_OUTCOME_ON_SERVER,	ENGINE_NOT_FINISHED_AUTO_REJOIN, 342
231	ER_GRP_RPL_FK_WITH_CASCADE_UNSUPPORTED,
ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_STATE_ON_SERVER,	220
234	ER_GRP_RPL_FLOW_CONTROL_STATS, 240
ER_GRP_RPL_FAILED_TO_REINIT_BINLOG_CACHE_FOR_GRP,	ER_GRP_RPL_FLOW_CTRL_MAX_QUOTA_SMALLER_THAN_MIN,
231	237
ER_GRP_RPL_FAILED_TO_SHUTDOWN_REGISTRY_FOR_GRP,	ER_GRP_RPL_FLOW_CTRL_MIN_QUOTA_GREATER_THAN_MAX,
234	237
ER_GRP_RPL_FAILED_TO_START_COMMUNICATION_ENGINE,	ER_GRP_RPL_FLOW_CTRL_MIN_RECOVERY_QUOTA_GREATER_THAN_MAX,
233	237
ER_GRP_RPL_FAILED_TO_START_ON_BOOT,	ER_GRP_RPL_FORCE_MEMBERS_MUST_BE_EMPTY,
235	233
ER_GRP_RPL_FAILED_TO_START_ON_SECONDARY_MEMBER,	ER_GRP_RPL_FORCE_MEMBERS_WHEN_LEAVING,
233	339
ER_GRP_RPL_FAILED_TO_START_WITH_INVALID_SERVER_ID,	ER_GRP_RPL_FORCE_MEMBER_VALUE_SET,
232	240
ER_GRP_RPL_FAILED_TO_STOP_ON_PLUGIN_UNINSTALL,	ER_GRP_RPL_FORCE_MEMBER_VALUE_SET_ERROR,
235	240
ER_GRP_RPL_FAILED_TO_UNREGISTER_BINLOG_STATE_ON_SERVER,	ER_GRP_RPL_FORCE_MEMBER_VALUE_TIME_OUT,
235	240
ER_GRP_RPL_FAILED_TO_UNREGISTER_SERVER_STATE_ON_SERVER,	ER_GRP_RPL_GCS_GR_ERROR_MSG, 241
235	ER_GRP_RPL_GCS_INTERFACE_ERROR, 240
ER_GRP_RPL_FAILED_TO_UNREGISTER_TRANS_STATE_ON_SERVER,	ER_GRP_RPL_GMS_LISTENER_FAILED_TO_LOG_NOTIFICATION,
235	239
ER_GRP_RPL_FAILOVER_CHANNEL_STATUS_PROPAGATION_FAILED,	ER_GRP_RPL_GROUP_NAME_PARSE_ERROR,
112	219
ER_GRP_RPL_FAILOVER_CONF_CHANNEL_DOES_NOT_EXIST,	ER_GRP_RPL_GROUP_NAME_SAME_AS_VIEW_CHANGE_LOG_EVENT_ID,
373	370
ER_GRP_RPL_FAILOVER_CONF_DEFAULT_CONFIGURATION_INVALID,	ER_GRP_RPL_GRP_COMMUNICATION_ENG_INIT_FAILED,
373	239
ER_GRP_RPL_FAILOVER_CONF_GET_EXCHANGEABLE_DATA_FAILED,	ER_GRP_RPL_GRP_COMMUNICATION_INIT_WITH_CONFIG_FAILED,
373	237
ER_GRP_RPL_FAILOVER_CONF_PARSE_ON_MEMBER_FAILED,	ER_GRP_RPL_GRP_MEMBER_OFFLINE, 239
373	ER_GRP_RPL_GRP_NAME_IS_NOT_VALID_UUID,
ER_GRP_RPL_FAILOVER_CONF_UNABLE_TO_SET_DEFAULT_CONFIGURATION,	237
373	ER_GRP_RPL_GRP_NAME_IS_SAME_AS_ANONYMOUS_MEMBER,
ER_GRP_RPL_FAILOVER_PRIMARY_BACK_TO_MAJORITY,	365,
373	ER_GRP_RPL_GRP_NAME_IS_TOO_LONG, 237
ER_GRP_RPL_FAILOVER_PRIMARY_WITHOUT_MAJORITY,	ER_GRP_RPL_GRP_NAME_OPTION_MANDATORY,
373	237
ER_GRP_RPL_FAILOVER_REGISTER_MESSAGE_LISTENER_FAILED,	ER_GRP_RPL_GRP_VIEW_CHANGE_UUID_IS_INCOMPATIBLE,
373	370
ER_GRP_RPL_FATAL_REC_PROCESS, 232	ER_GRP_RPL_GTID_ALREADY_USED, 218
ER_GRP_RPL_FETCH_FORMAT_DESC_LOG_EVENT_FAILED,	ER_GRP_RPL_GTID_EXECUTED_EXTRACT_ERROR,
226	224
ER_GRP_RPL_FETCH_GTID_LOG_EVENT_FAILED,	ER_GRP_RPL_GTID_MODE_OFF, 236
227	ER_GRP_RPL_GTID_PURGED_EXTRACT_ERROR,
ER_GRP_RPL_FETCH_LOG_EVENT_FAILED, 227	347
ER_GRP_RPL_FETCH_SNAPSHOT_VERSION_FAILED,	ER_GRP_RPL_GTID_SET_EXTRACT_ERROR,
227	224

ER_GRP_RPL_GTID_SET_EXTRACT_ERROR_DURING_RECOVERY,	ER_GRP_RPL_MEMBER_ALREADY_EXISTS, 224
338	ER_GRP_RPL_MEMBER_CFG_INCOMPATIBLE_WITH_GRP_C
ER_GRP_RPL_HAS_STARTED, 391	225
ER_GRP_RPL_INCORRECT_TYPE_SET_FOR_PARALLEL_APPLIER,	ER_GRP_RPL_MEMBER_CHANGE, 223
236	ER_GRP_RPL_MEMBER_CONF_INFO, 233
ER_GRP_RPL_INIT_CERTIFICATION_INFO_FAILURE,	ER_GRP_RPL_MEMBER_CONTACT_RESTORED,
221	222
ER_GRP_RPL_INTERNAL_QUERY, 228	ER_GRP_RPL_MEMBER_EXIT_PLUGIN_ERROR,
ER_GRP_RPL_INVALID_BINLOG_FORMAT, 230	223
ER_GRP_RPL_INVALID_COMMUNICATION_PROTOCOL,	ER_GRP_RPL_MEMBER_EXPELLED, 223
342	ER_GRP_RPL_MEMBER_INFO_DOES_NOT_EXIST,
ER_GRP_RPL_INVALID_DEBUG_OPTIONS, 239	396
ER_GRP_RPL_INVALID_GTID_SET, 220	ER_GRP_RPL_MEMBER_LEFT_GRP, 223
ER_GRP_RPL_INVALID_SSL_RECOVERY_STRING,	ER_GRP_RPL_MEMBER_NOT_FOUND, 228
237	ER_GRP_RPL_MEMBER_REMOVED, 222
ER_GRP_RPL_IS_STARTING, 357	ER_GRP_RPL_MEMBER_SERVER_UUID_IS_INCOMPATIBLE,
ER_GRP_RPL_IS_STOPPED, 234	233
ER_GRP_RPL_IS_STOPPING, 234	ER_GRP_RPL_MEMBER_STATS_INFO, 240
ER_GRP_RPL_JOINER_EXIT_WHEN_GROUP_ACTION_RUNNING,	ER_GRP_RPL_MEMBER_STOP_RPL_CHANNELS_ERROR,
330	225
ER_GRP_RPL_JOIN_WHEN_GROUP_ACTION_RUNNING,	ER_GRP_RPL_MEMBER_TRANS_GREATER_THAN_GRP,
330	224
ER_GRP_RPL_KILLED_FAILED_ID, 228	ER_GRP_RPL_MEMBER_VERSION_LOWER_THAN_GRP,
ER_GRP_RPL_KILLED_SESSION_ID, 228	224
ER_GRP_RPL_LOCAL_GTID_SETS_PROCESS_ERROR,	ER_GRP_RPL_MEMBER_VER_INCOMPATIBLE,
224	224
ER_GRP_RPL_LOG_REPLICA_UPDATES_NOT_SET,	ER_GRP_RPL_MEMBER_VER_READ_COMPATIBLE,
236	345
ER_GRP_RPL_LOWER_CASE_TABLE_NAMES_DIFF_FROM_GRP,	ER_GRP_RPL_MEM_ONLINE, 222
323	ER_GRP_RPL_MEM_REACHABLE, 222
ER_GRP_RPL_MAXIMUM_CONNECTION_RETRIES_REACHED,	ER_GRP_RPL_MEM_UNREACHABLE, 222
228	ER_GRP_RPL_MESSAGE_SERVICE_FATAL_ERROR,
ER_GRP_RPL_MEMBER_ACTIONS_RESET, 369	349
ER_GRP_RPL_MEMBER_ACTION_DEFAULT_CONFIGURATION,	ER_GRP_RPL_MESSAGE_SERVICE_INIT_FAILURE,
368	101
ER_GRP_RPL_MEMBER_ACTION_DISABLED,	ER_GRP_RPL_MISSING_GRP_RPL_ACTION_COORDINATOR,
369	330
ER_GRP_RPL_MEMBER_ACTION_ENABLED, 369	ER_GRP_RPL_MISSING_GRP_RPL_APPLIER,
ER_GRP_RPL_MEMBER_ACTION_FAILURE, 368	221
ER_GRP_RPL_MEMBER_ACTION_FAILURE_IGNORE,	ER_GRP_RPL_MODULE_TERMINATE_ERROR,
368	237
ER_GRP_RPL_MEMBER_ACTION_GET_EXCHANGEABLE_DATA,	ER_GRP_RPL_MSG_DECODING_FAILED, 404
368	ER_GRP_RPL_MSG_DISCARDED, 221
ER_GRP_RPL_MEMBER_ACTION_INVALID_ACTIONS_ON_MEMBER_JOIN,	ER_GRP_RPL_MSG_TOO_LONG_BROADCASTING_TRANS_F
369	231
ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_MEMBER_JOIN,	ER_GRP_RPL_MULTIPLE_CACHE_TYPE_NOT_SUPPORTED,
369	231
ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_RECEIVE,	ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_CLIENT_ERR
368	372
ER_GRP_RPL_MEMBER_ACTION_TRIGGERED,	ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_CLIENT_ERR
368	372
ER_GRP_RPL_MEMBER_ACTION_UNABLE_TO_SET_DEFAULT_CONFIGURATION,	ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_SERVER_ERR
369	398
ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS,	ER_GRP_RPL_NEEDS_INNODB_TABLE, 226
368	ER_GRP_RPL_NEW_PRIMARY_ELECTED, 223
ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS_ON_MEMBER_NOTIFY,	ER_GRP_RPL_NOTIFY_CERTIFICATION_OUTCOME_FAILED
369	227
ER_GRP_RPL_MEMBER_ADDED, 222	ER_GRP_RPL_NO_POSSIBLE_RECOVERY, 348



ER_GRP_RPL_NO_STAGE_SERVICE, 331	ER_GRP_RPL_RECOVERY_STRAT_FALLBACK,
ER_GRP_RPL_NO_SUITABLE_PRIMARY_MEM,	348
223	ER_GRP_RPL_RECOVERY_STRAT_NO_FALLBACK,
ER_GRP_RPL_NO_VALID_DONOR, 229	348
ER_GRP_RPL_NULL_PACKET, 221	ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_DEPEND
ER_GRP_RPL_ONLY_ONE_SERVER_ALIVE, 232	337
ER_GRP_RPL_OOM_FAILED_TO_GENERATE_IDENTIFICATION_HASH,	ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_GROUP
230	337
ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_PRIMARY,	ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_SYNC_B
376	338
ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_SECONDARY,	ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_DEPEND
390	337
ER_GRP_RPL_PIPELINE_CREATE_FAILED, 240	ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_WAIT_FOR
ER_GRP_RPL_PIPELINE_FLUSH_FAIL, 240	338
ER_GRP_RPL_PIPELINE_REINIT_FAILED_READ,	ER_GRP_RPL_RELEASE_COMMIT_AFTER_GROUP_PRE
241	337
ER_GRP_RPL_PIPELINE_REINIT_FAILED_WRITE,	ER_GRP_RPL_REPLICA_APPLIER_THREAD_ERROR_OUT
240	241
ER_GRP_RPL_PLUGIN_ABORT, 328	ER_GRP_RPL_REPLICA_APPLIER_THREAD_UNBLOCKED
ER_GRP_RPL_PLUGIN_STRUCT_INIT_NOT_POSSIBLE,	ON_SERVER_START,
233	ER_GRP_RPL_REPLICA_IO_THD_PRIMARY_UNKNOWN,
ER_GRP_RPL_PRIMARY_ELECTION_PROCESS_ERROR,	225
331	ER_GRP_RPL_REPLICA_IO_THREAD_ERROR_OUT,
ER_GRP_RPL_PRIMARY_ELECTION_STOP_ERROR,	241
331	ER_GRP_RPL_REPLICA_IO_THREAD_UNBLOCKED,
ER_GRP_RPL_PRIMARY_KEY_NOT_DEFINED,	241
226	ER_GRP_RPL_REPLICA_PRESERVE_COMMIT_ORDER_M
ER_GRP_RPL_PRIMARY_MEMBER_LEFT_GRP,	236
222	ER_GRP_RPL_REPLICA_SQL_THD_ON_SECONDARY_M
ER_GRP_RPL_PROCESS_GTID_SET_ERROR,	226
221	ER_GRP_RPL_REPLICA_SQL_THD_PRIMARY_UNKNOWN
ER_GRP_RPL_PROCESS_INTERSECTION_GTID_SET_ERROR,	226
221	ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_CLONE,
ER_GRP_RPL_PURGE_APPLIER_LOGS, 225	348
ER_GRP_RPL_PURGE_REC, 229	ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_SECOND
ER_GRP_RPL_QUERY_FAIL, 228	374
ER_GRP_RPL_READ_UNABLE_FOR_READ_ONLY_SERVER,	ER_GRP_RPL_READ_ONLY_REQUESTING_NON_MEMBER_SERVER_T
232	234
ER_GRP_RPL_RECEIVED_SET_MISSING_GTIDS,	ER_GRP_RPL_RESET_APPLIER_MODULE_LOGS_ERROR
221	225
ER_GRP_RPL_RECOVERY_CHANNEL_STILL_RUNNING,	ER_GRP_RPL_SALVE_IO_THD_ON_SECONDARY_MEMB
110	226
ER_GRP_RPL_RECOVERY_ENDPOINT_FORMAT,	ER_GRP_RPL_SEND_STATS_ERROR, 240
357	ER_GRP_RPL_SEND_TRX_PREPARED_MESSAGE_FAILED
ER_GRP_RPL_RECOVERY_ENDPOINT_INTERFACES,	335,
357	ER_GRP_RPL_SEND_TRX_SYNC_BEFORE_EXECUTION,
ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID,	338
357	ER_GRP_RPL_SERVER_ALREADY_LEFT, 234
ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID_DONOR_ENDPOINT,	ER_GRP_RPL_SERVER_CONN_ERROR, 220
357	ER_GRP_RPL_SERVER_IS_ALREADY_LEAVING,
ER_GRP_RPL_RECOVERY_EVAL_ERROR, 348	233
ER_GRP_RPL_RECOVERY_MODULE_TERMINATION_TIMEOUT,	ER_GRP_RPL_SERVER_SHUTDOWN,
234	349
ER_GRP_RPL_RECOVERY_STRAT_CHOICE, 348	ER_GRP_RPL_SERVER_SET_TO_READ_ONLY_DUE_TO
ER_GRP_RPL_RECOVERY_STRAT_CLONE_PURGED,	239
348	ER_GRP_RPL_SERVER_UDF_ERROR, 331
ER_GRP_RPL_RECOVERY_STRAT_CLONE_THRESHOLD,	ER_GRP_RPL_SESSION_OPEN_FAILED, 223
348	

ER_GRP_RPL_SET_GRP_COMMUNICATION_ENG_LOGGING_DISABLED, 239	ER_GRP_RPL_TRANS_SIZE_EXCEEDS_LIMIT, 231
ER_GRP_RPL_SET_MULTI_CONSENSUS_LEADER, 376	ER_GRP_RPL_TRANS_WRITE_SET_EXTRACT_DIFF_FROM, 225
ER_GRP_RPL_SET_SINGLE_CONSENSUS_LEADER, 376	ER_GRP_RPL_TRX_ALREADY_EXISTS_ON_TCM_ON_AFTER, 337
ER_GRP_RPL_SET_STABLE_TRANS_ERROR, 221	ER_GRP_RPL_TRX_DOES_NOT_EXIST_ON_TCM_ON_HAND, 337
ER_GRP_RPL_SINGLE_PRIM_MODE_NOT_ALLOWED, 236	ER_GRP_RPL_UPDATE_EXISTS_WITHOUT_GROUP_GTID_EXECUTED, 338
ER_GRP_RPL_SQL_SERVICE_COMM_SESSION_NOT_INITIALIZED, 238	ER_GRP_RPL_TRX_WAIT_FOR_GROUP_PREPARE_FAILED, 337
ER_GRP_RPL_SQL_SERVICE_FAILED_TO_FETCH_SECONDARY_GRP, 238	ER_GRP_RPL_TRX_WAIT_FOR_SYNC_BEFORE_EXECUTION, 338
ER_GRP_RPL_SQL_SERVICE_FAILED_TO_INIT_SESSION_ON_GRP, 238	ER_GRP_RPL_UDF_ERROR, 101
ER_GRP_RPL_SQL_SERVICE_FAILED_TO_RUN_SQL_QUERY, 238	ER_GRP_RPL_UDF_REGISTER_ERROR, 331
ER_GRP_RPL_SQL_SERVICE_MAX_CONN_ERROR_FROM_SERVER, 239	ER_GRP_RPL_UDF_REGISTER_SERVICE_ERROR, 331
ER_GRP_RPL_SQL_SERVICE_RETRIES_EXCEEDED_ON_SESSION_STATE, 238	ER_GRP_RPL_UDF_UNREGISTER_ERROR, 331
ER_GRP_RPL_SQL_SERVICE_SERVER_ACCESS_DENIED, 239	ER_GRP_RPL_UNABLE_TO_CERTIFY_PLUGIN_TRANS, 238
ER_GRP_RPL_SQL_SERVICE_SERVER_ERROR_ON_CONN, 239	ER_GRP_RPL_UNABLE_TO_CONVERT_EVENT_TO_PACKET_ID_FOR_USER, 238
ER_GRP_RPL_SQL_SERVICE_SERVER_INTERNAL_FAILURE, 238	ER_GRP_RPL_UNABLE_TO_CONVERT_PACKET_TO_EVENT_ID, 238
ER_GRP_RPL_SQL_SERVICE_SERVER_SESSION_KILLED, 238	ER_GRP_RPL_UNABLE_TO_ENSURE_EXECUTION_REC, 236
ER_GRP_RPL_SRV_BLOCKED, 222	ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_APPLI, 229
ER_GRP_RPL_SRV_BLOCKED_FOR_SECS, 222	ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_FAIL, 230
ER_GRP_RPL_SRV_NOT_ONLINE, 221	ER_GRP_RPL_UNABLE_TO_RESET_SERVER_READ_MODE, 232
ER_GRP_RPL_SRV_ONLINE, 222	ER_GRP_RPL_UNBLOCK_CERTIFIED_TRANS, 232
ER_GRP_RPL_SRV_PRIMARY_MEM, 223	ER_GRP_RPL_UNBLOCK_WAITING_THD, 219
ER_GRP_RPL_SRV_SECONDARY_MEM, 223	ER_GRP_RPL_UNKNOWN_GRP_RPL_APPLIER_PIPELINE_R, 237
ER_GRP_RPL_SSL_DISABLED, 236	ER_GRP_RPL_UNREACHABLE_MAJORITY_TIMEOUT_FOR_M, 239
ER_GRP_RPL_STARTED_AUTO_REJOIN, 342	ER_GRP_RPL_UNSUPPORTED_TRANS_ISOLATION, 230
ER_GRP_RPL_STARTING_GRP_REC, 229	ER_GRP_RPL_UPDATE_GRP GTID_EXECUTED_ERROR, 219
ER_GRP_RPL_START_FAILED, 224	ER_GRP_RPL_UPDATE_GRP GTID_VIEW_CHANGE_UUID_EX, 370
ER_GRP_RPL_START_GRP_RPL_FAILED, 228	ER_GRP_RPL_UPDATE_GTID_SET_ERROR, 220
ER_GRP_RPL_STOPPING_GRP_REC, 229	ER_GRP_RPL_UPDATE_LAST_CONFLICT_FREE_TRANS_ER, 238
ER_GRP_RPL_SUPER_READ_OFF, 228	ON SHUTDOWN, 234
ER_GRP_RPL_SUPER_READ_ON, 228	ER_GRP_RPL_UPDATE_SERV_CERTIFICATE_FAILED, 227
ER_GRP_RPL_SUPER_READ_ONLY_ACTIVATE_ERROR, 223	ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_REF_VER_ERR, 220
ER_GRP_RPL_TIMEOUT_ON_VIEW_AFTER_JOINING_GRP, 233	ER_GRP_RPL_VCLE_NOT_BEING_LOGGED, 401
ER_GRP_RPL_TIMEOUT_RECEIVED_VC_LEAVE_ON_REJOIN, 362	
ER_GRP_RPL_TIMEOUT_RECEIVED_VC_ON_REJOIN, 342	
ER_GRP_RPL_TIMEOUT_RECEIVING_VIEW_CHANGE_ON, 234	
ER_GRP_RPL_TRANS_GREATER_THAN_GRP, 224	
ER_GRP_RPL_TRANS_NOT_PRESENT_IN_GRP, 224	

ER_GRP_RPL_VIEW_CHANGE_UUID_DIFF_FROM_GRP	ER_HEALTH_WARNING, 365
370	ER_HEALTH_WARNING_DISK_USAGE_LEVEL_1,
ER_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIABLE,	365,
111	ER_HEALTH_WARNING_DISK_USAGE_LEVEL_2,
ER_GRP_RPL_VIEW_CHANGE_UUID_INVALID,	365
369	ER_HEALTH_WARNING_DISK_USAGE_LEVEL_3,
ER_GRP_RPL_VIEW_CHANGE_UUID_IS_SAME_AS_ANONYMOUS_TO_GTID_UUID,	365
370	ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_1,
ER_GRP_RPL_VIEW_CHANGE_UUID_PARSE_ERROR,	376
370	ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_2,
ER_GRP_RPL_VIEW_CHANGE_UUID_SAME_AS_GROUPNAME,	369
369	ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_3,
ER_GRP_RPL_WAITING_FOR_VIEW_UPDATE,	376
234	ER_HOSTNAME, 31
ER_GRP_RPL_WAIT_FOR_DEPENDENCIES_FAILED,	ER_HOSTNAME_DOESNT_RESOLVE_TO, 132
338	ER_HOSTNAME_RESEMBLES_IPV4, 132
ER_GRP_RPL_WHILE_SENDING_MSG_REC,	232
ER_GRP_RPL_WRITE_IDENT_HASH_BASE64_ENCODING_FAILED,	358
230	ER_HOST_IS_BLOCKED, 11
ER_GRP_RPL_WRITE_TO_TRANSACTION_MESSAGE_FAILED,	11
231	ER_HOST_NOT_PRIVILEGED, 11
ER_GRP_TRX_CONSISTENCY_AFTER_ON_TRX_BEGIN,	ER_HYPERGRAPH_NOT_SUPPORTED_YET, 108
93	ER_IB_BUFFER_POOL_FULL, 387
ER_GRP_TRX_CONSISTENCY_BEFORE,	93
ER_GRP_TRX_CONSISTENCY_BEGIN_NOT_ALLOWED,	ER_IB_BUFFER_POOL_OVERUSE, 387
93	ER_IB_BULK_FLUSHER_INFO, 387
ER_GRP_TRX_CONSISTENCY_NOT_ALLOWED,	ER_IB_BULK_FLUSHER_PUNCH_HOLE, 396
93	ER_IB_BULK_LOAD_MERGE_FAIL, 389
ER_GR_ELECTED_PRIMARY_GTID_INFORMATION,	ER_IB_BULK_LOAD_STATS_WARN, 404
352	ER_IB_BULK_LOAD_SUBTREE_INFO, 387
ER_GR_HOLD_KILLED,	92
ER_GR_HOLD_MEMBER_STATUS_ERROR,	92
ER_GR_HOLD_WAIT_TIMEOUT,	92
ER_GTID_ALREADY_ADDED_BY_USER,	154
ER_GTID_EXECUTED_WAS_CHANGED,	54
ER_GTID_EXECUTED_WAS_UPDATED,	181
ER_GTID_MODE_CAN_ONLY_CHANGE_ONE_STEP_ATIME,	50
50	ER_IB_CLONE_ONE_RESTART, 347
ER_GTID_MODE_OFF,	61
ER_GTID_MODE_ON_REQUIRES_ENFORCE_GTID_CONSISTENCY,	49
49	ER_IB_CLONE_SQL, 256
ER_GTID_NEXT_CANT_BE_AUTOMATIC_IF_GTID_NEXT_IS_CURRENT_USER,	49
49	ER_IB_CLONE_START_STOP, 347
ER_GTID_NEXT_TAG_GTID_MODE_OFF,	124
ER_GTID_NEXT_TYPE_UNDEFINED_GTID,	53
ER_GTID_PURGED_WAS_CHANGED,	54
ER_GTID_PURGED_WAS_UPDATED,	181
ER_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION,	91
91	ER_IB_CLONE_STATUS_FILE, 256
ER_GTID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AND_ASSIGNED_TABLE,	57
57	ER_IB_CLONE_TIMEOUT, 256
ER_GTID_UNSAFE_CREATE_SELECT,	50
ER_GTID_UNSAFE_NON_TRANSACTIONAL_TABLE,	50
50	ER_IB_CLONE_VALIDATE, 256
ER_HANDLERTON_OOM,	144
ER_HANDSHAKE_ERROR,	5
ER_HEALTH_ERROR,	365
ER_HEALTH_INFO,	365
	ER_IB_CLONE_USER_DATA, 347
	ER_IB_CLONE_VALIDATE, 256
	ER_IB_DBLWR_BYTES_INFO, 379
	ER_IB_DBLWR_DECOMPRESS_FAILED, 363
	ER_IB_DBLWR_DECRYPT_FAILED, 363
	ER_IB_DBLWR_KEY_MISSING, 363
	ER_IB_DBLWR_CONVERT_HEAP_NOT_FOUND, 395
	ER_IB_DICT_INVALID_COLUMN_POSITION, 390
	ER_IB_DICT_INVALID_COLUMN_POSITION, 390
	ER_IB_DUPLICATE_KEY, 387
	ER_IB_ERR_CORRUPT_TABLESPACE_UNRECOVERABLE,
	403
	ER_IB_ERR_DDL_LOG_INSERT_FAILURE, 359
	ER_IB_ERR_FOUND_N_DUPLICATE_KEYS, 361
	ER_IB_ERR_FOUND_N_RECORDS_WRONG_ORDER,
	361
	ER_IB_ERR_INDEX_DUPLICATE_KEY, 361

ER_IB_ERR_INDEX_RECORDS_WRONG_ORDER, 361	ER_IB_MSG_1003, 306
ER_IB_ERR_LOG_PARSING_BUFFER_OVERFLOW, 360	ER_IB_MSG_1004, 306
ER_IB_ERR_NOT_ENOUGH_MEMORY_FOR_PARSE_BUFFER, 360	ER_IB_MSG_1005, 306
ER_IB_ERR_PAGE_ARCH_DBLWR_INIT_FAILED, 372	ER_IB_MSG_1006, 306
ER_IB_ERR_PAGE_ARCH_INVALID_DOUBLE_WRITE, 356	ER_IB_MSG_1007, 306
ER_IB_ERR_PAGE_ARCH_INVALID_FORMAT, 356	ER_IB_MSG_1008, 306
ER_IB_ERR_PAGE_ARCH_RECOVERY_FAILED, 356	ER_IB_MSG_1009, 306
ER_IB_ERR_PARALLEL_READ_OOM, 361	ER_IB_MSG_101, 253
ER_IB_ERR_RECOVERY_REDO_DISABLED, 358	ER_IB_MSG_1010, 306
ER_IB_ERR_SCHED_SETAFFINITY_FAILED, 360	ER_IB_MSG_1011, 306
ER_IB_ERR_TEMP_TABLESPACE_DIR_CONTAINS_SYMBOLS, 360	ER_IB_MSG_1012, 306
ER_IB_ERR_TEMP_TABLESPACE_DIR_DOESNT_EXIST, 360	ER_IB_MSG_1013, 306
ER_IB_ERR_TEMP_TABLESPACE_DIR_EMPTY, 360	ER_IB_MSG_1015, 307
ER_IB_ERR_TEMP_TABLESPACE_DIR_SUBDIR_OF_DATA_DIR, 360	ER_IB_MSG_1016, 307
ER_IB_ERR_UNKNOWN_PAGE_FETCH_MODE, 360	ER_IB_MSG_1017, 307
ER_IB_ERR_ZLIB_BUF_ERROR, 361	ER_IB_MSG_1018, 307
ER_IB_ERR_ZLIB_DATA_ERROR, 361	ER_IB_MSG_1019, 307
ER_IB_ERR_ZLIB_MEM_ERROR, 361	ER_IB_MSG_102, 253
ER_IB_ERR_ZLIB_UNCOMPRESS_FAILED, 360	ER_IB_MSG_1020, 307
ER_IB_ERR_ZLIB_UNKNOWN_ERROR, 361	ER_IB_MSG_1021, 307
ER_IB_FAILED_TO_DELETE_TABLESPACE_FILE, 359	ER_IB_MSG_1022, 307
ER_IB_FIXED_PAGE_ID, 399	ER_IB_MSG_1023, 307
ER_IB_HIDDEN_NAME_CONFLICT, 390	ER_IB_MSG_1024, 307
ER_IB_IMPORT_INDEX_METADATA_READ_FAILED, 302	ER_IB_MSG_1025, 307
ER_IB_IMPORT_START_CFG_NAME, 307	ER_IB_MSG_1026, 307
ER_IB_INDEX_BUILDER_DONE, 391	ER_IB_MSG_1027, 307
ER_IB_INDEX_BUILDER_INIT, 391	ER_IB_MSG_1028, 307
ER_IB_INDEX_LOADER_DONE, 391	ER_IB_MSG_1029, 307
ER_IB_INDEX_LOG_VERSION_MISMATCH, 391	ER_IB_MSG_103, 253
ER_IB_INNO_DB_TBSP_OUT_OF_SPACE, 365	ER_IB_MSG_1030, 308
ER_IB_LOAD_BULK_CONCURRENCY_REDUCED, 389	ER_IB_MSG_1031, 308
ER_IB_LOB_ROLLBACK_INDEX_LEN, 351	ER_IB_MSG_1032, 308
ER_IB_LOCK_VALIDATE_LATCH_ORDER_VIOLATION, 359	ER_IB_MSG_1033, 308
ER_IB_LONG_AHI_DISABLE_WAIT, 258	ER_IB_MSG_1034, 308
ER_IB_MSG_0, 247	ER_IB_MSG_1035, 308
ER_IB_MSG_1, 247	ER_IB_MSG_1036, 308
ER_IB_MSG_10, 248	ER_IB_MSG_1037, 308
ER_IB_MSG_100, 253	ER_IB_MSG_1038, 308
ER_IB_MSG_1000, 306	ER_IB_MSG_1039, 308
ER_IB_MSG_1001, 306	ER_IB_MSG_104, 253
ER_IB_MSG_1002, 306	ER_IB_MSG_1040, 308
	ER_IB_MSG_1041, 308
	ER_IB_MSG_1042, 308
	ER_IB_MSG_1043, 308
	ER_IB_MSG_1044, 308
	ER_IB_MSG_1045, 308
	ER_IB_MSG_1046, 309
	ER_IB_MSG_1047, 309
	ER_IB_MSG_1048, 309
	ER_IB_MSG_1049, 309
	ER_IB_MSG_105, 253
	ER_IB_MSG_1051, 309
	ER_IB_MSG_1052, 309
	ER_IB_MSG_1053, 309
	ER_IB_MSG_1054, 309
	ER_IB_MSG_1055, 309
	ER_IB_MSG_1056, 309
	ER_IB_MSG_1057, 309

---

ER_IB_MSG_1058, 309	ER_IB_MSG_112, 254
ER_IB_MSG_1059, 309	ER_IB_MSG_1120, 313
ER_IB_MSG_106, 254	ER_IB_MSG_1121, 313
ER_IB_MSG_1060, 309	ER_IB_MSG_1122, 313
ER_IB_MSG_1065, 310	ER_IB_MSG_1123, 313
ER_IB_MSG_107, 254	ER_IB_MSG_1124, 313
ER_IB_MSG_1070, 310	ER_IB_MSG_1125, 313
ER_IB_MSG_1071, 310	ER_IB_MSG_1126, 314
ER_IB_MSG_1072, 310	ER_IB_MSG_1127, 314
ER_IB_MSG_1073, 310	ER_IB_MSG_1128, 314
ER_IB_MSG_1074, 310	ER_IB_MSG_1129, 314
ER_IB_MSG_1075, 310	ER_IB_MSG_1130, 314
ER_IB_MSG_1076, 310	ER_IB_MSG_1131, 314
ER_IB_MSG_1077, 310	ER_IB_MSG_1132, 314
ER_IB_MSG_1078, 310	ER_IB_MSG_1133, 314
ER_IB_MSG_1079, 311	ER_IB_MSG_1134, 314
ER_IB_MSG_108, 254	ER_IB_MSG_1139, 314
ER_IB_MSG_1080, 311	ER_IB_MSG_1142, 315
ER_IB_MSG_1081, 311	ER_IB_MSG_1144, 315
ER_IB_MSG_1082, 311	ER_IB_MSG_1145, 315
ER_IB_MSG_1083, 311	ER_IB_MSG_1146, 315
ER_IB_MSG_1085, 311	ER_IB_MSG_1147, 315
ER_IB_MSG_1086, 311	ER_IB_MSG_1148, 315
ER_IB_MSG_1087, 311	ER_IB_MSG_1149, 315
ER_IB_MSG_1088, 311	ER_IB_MSG_1150, 315
ER_IB_MSG_1089, 311	ER_IB_MSG_1151, 315
ER_IB_MSG_109, 254	ER_IB_MSG_1152, 315
ER_IB_MSG_1090, 311	ER_IB_MSG_1154, 315
ER_IB_MSG_1091, 311	ER_IB_MSG_1155, 315
ER_IB_MSG_1092, 311	ER_IB_MSG_1156, 316
ER_IB_MSG_1093, 311	ER_IB_MSG_1157, 316
ER_IB_MSG_1094, 312	ER_IB_MSG_1158, 316
ER_IB_MSG_1095, 312	ER_IB_MSG_1159, 316
ER_IB_MSG_1096, 312	ER_IB_MSG_1160, 316
ER_IB_MSG_1097, 312	ER_IB_MSG_1161, 316
ER_IB_MSG_1098, 312	ER_IB_MSG_1162, 316
ER_IB_MSG_1099, 312	ER_IB_MSG_1163, 316
ER_IB_MSG_11, 248	ER_IB_MSG_1164, 316
ER_IB_MSG_110, 254	ER_IB_MSG_1165, 316
ER_IB_MSG_1100, 312	ER_IB_MSG_1177, 317
ER_IB_MSG_1101, 312	ER_IB_MSG_1178, 317
ER_IB_MSG_1102, 312	ER_IB_MSG_1179, 317
ER_IB_MSG_1103, 312	ER_IB_MSG_1180, 317
ER_IB_MSG_1104, 312	ER_IB_MSG_1181, 317
ER_IB_MSG_1105, 312	ER_IB_MSG_1182, 317
ER_IB_MSG_1107, 312	ER_IB_MSG_1183, 317
ER_IB_MSG_1108, 312	ER_IB_MSG_1184, 317
ER_IB_MSG_1109, 313	ER_IB_MSG_1185, 317
ER_IB_MSG_111, 254	ER_IB_MSG_1186, 317
ER_IB_MSG_1110, 313	ER_IB_MSG_1187, 317
ER_IB_MSG_1111, 313	ER_IB_MSG_1188, 317
ER_IB_MSG_1112, 313	ER_IB_MSG_1189, 317
ER_IB_MSG_1113, 313	ER_IB_MSG_119, 254
ER_IB_MSG_1114, 313	ER_IB_MSG_1191, 317
ER_IB_MSG_1115, 313	ER_IB_MSG_1192, 318
ER_IB_MSG_1116, 313	ER_IB_MSG_1193, 318
ER_IB_MSG_1117, 313	ER_IB_MSG_1194, 318
ER_IB_MSG_1119, 313	ER_IB_MSG_1195, 318

---

ER\_IB\_MSG\_1196, 318  
ER\_IB\_MSG\_1197, 318  
ER\_IB\_MSG\_1198, 318  
ER\_IB\_MSG\_1199, 318  
ER\_IB\_MSG\_12, 248  
ER\_IB\_MSG\_120, 254  
ER\_IB\_MSG\_1200, 318  
ER\_IB\_MSG\_1201, 318  
ER\_IB\_MSG\_1202, 318  
ER\_IB\_MSG\_1203, 318  
ER\_IB\_MSG\_1204, 318  
ER\_IB\_MSG\_1205, 318  
ER\_IB\_MSG\_1206, 318  
ER\_IB\_MSG\_1207, 318  
ER\_IB\_MSG\_1208, 319  
ER\_IB\_MSG\_1209, 319  
ER\_IB\_MSG\_121, 254  
ER\_IB\_MSG\_1210, 319  
ER\_IB\_MSG\_1211, 319  
ER\_IB\_MSG\_1212, 319  
ER\_IB\_MSG\_1213, 319  
ER\_IB\_MSG\_1214, 319  
ER\_IB\_MSG\_1215, 319  
ER\_IB\_MSG\_1217, 319  
ER\_IB\_MSG\_1218, 319  
ER\_IB\_MSG\_1219, 319  
ER\_IB\_MSG\_122, 254  
ER\_IB\_MSG\_1220, 319  
ER\_IB\_MSG\_1221, 319  
ER\_IB\_MSG\_1222, 319  
ER\_IB\_MSG\_1223, 320  
ER\_IB\_MSG\_1224, 320  
ER\_IB\_MSG\_1225, 320  
ER\_IB\_MSG\_1226, 320  
ER\_IB\_MSG\_1227, 320  
ER\_IB\_MSG\_1228, 320  
ER\_IB\_MSG\_1229, 320  
ER\_IB\_MSG\_123, 254  
ER\_IB\_MSG\_1231, 320  
ER\_IB\_MSG\_1233, 320  
ER\_IB\_MSG\_1235, 320  
ER\_IB\_MSG\_1238, 320  
ER\_IB\_MSG\_1239, 320  
ER\_IB\_MSG\_124, 254  
ER\_IB\_MSG\_1241, 321  
ER\_IB\_MSG\_1245, 321  
ER\_IB\_MSG\_1246, 321  
ER\_IB\_MSG\_1247, 321  
ER\_IB\_MSG\_1248, 321  
ER\_IB\_MSG\_1249, 321  
ER\_IB\_MSG\_125, 254  
ER\_IB\_MSG\_1250, 321  
ER\_IB\_MSG\_1251, 321  
ER\_IB\_MSG\_1253, 321  
ER\_IB\_MSG\_1255, 321  
ER\_IB\_MSG\_1256, 321  
ER\_IB\_MSG\_1257, 321  
ER\_IB\_MSG\_1258, 322

ER\_IB\_MSG\_1259, 322  
ER\_IB\_MSG\_126, 254  
ER\_IB\_MSG\_1260, 322  
ER\_IB\_MSG\_1261, 322  
ER\_IB\_MSG\_1262, 322  
ER\_IB\_MSG\_1263, 322  
ER\_IB\_MSG\_1266, 322  
ER\_IB\_MSG\_1268, 322  
ER\_IB\_MSG\_1269, 322  
ER\_IB\_MSG\_127, 254  
ER\_IB\_MSG\_1271, 328  
ER\_IB\_MSG\_1272, 328  
ER\_IB\_MSG\_1273, 328  
ER\_IB\_MSG\_1274, 329  
ER\_IB\_MSG\_1275, 329  
ER\_IB\_MSG\_1277, 329  
ER\_IB\_MSG\_128, 255  
ER\_IB\_MSG\_1280, 329  
ER\_IB\_MSG\_1281, 329  
ER\_IB\_MSG\_1282, 329  
ER\_IB\_MSG\_1283, 330  
ER\_IB\_MSG\_1284, 330  
ER\_IB\_MSG\_1285, 345  
ER\_IB\_MSG\_129, 255  
ER\_IB\_MSG\_13, 248  
ER\_IB\_MSG\_130, 255  
ER\_IB\_MSG\_131, 255  
ER\_IB\_MSG\_132, 255  
ER\_IB\_MSG\_133, 255  
ER\_IB\_MSG\_134, 255  
ER\_IB\_MSG\_135, 255  
ER\_IB\_MSG\_1357, 359  
ER\_IB\_MSG\_1358, 359  
ER\_IB\_MSG\_1359, 359  
ER\_IB\_MSG\_136, 255  
ER\_IB\_MSG\_137, 255  
ER\_IB\_MSG\_1372, 360  
ER\_IB\_MSG\_1373, 360  
ER\_IB\_MSG\_1374, 360  
ER\_IB\_MSG\_1375, 360  
ER\_IB\_MSG\_138, 255  
ER\_IB\_MSG\_1381, 361  
ER\_IB\_MSG\_139, 255  
ER\_IB\_MSG\_14, 248  
ER\_IB\_MSG\_140, 255  
ER\_IB\_MSG\_141, 255  
ER\_IB\_MSG\_142, 255  
ER\_IB\_MSG\_143, 255  
ER\_IB\_MSG\_144, 256  
ER\_IB\_MSG\_145, 256  
ER\_IB\_MSG\_146, 256  
ER\_IB\_MSG\_147, 256  
ER\_IB\_MSG\_148, 256  
ER\_IB\_MSG\_15, 248  
ER\_IB\_MSG\_156, 256  
ER\_IB\_MSG\_157, 256  
ER\_IB\_MSG\_158, 256  
ER\_IB\_MSG\_159, 256

---

ER\_IB\_MSG\_16, 248  
ER\_IB\_MSG\_160, 257  
ER\_IB\_MSG\_161, 257  
ER\_IB\_MSG\_162, 257  
ER\_IB\_MSG\_163, 257  
ER\_IB\_MSG\_164, 257  
ER\_IB\_MSG\_165, 257  
ER\_IB\_MSG\_166, 257  
ER\_IB\_MSG\_167, 257  
ER\_IB\_MSG\_168, 257  
ER\_IB\_MSG\_169, 257  
ER\_IB\_MSG\_17, 248  
ER\_IB\_MSG\_170, 257  
ER\_IB\_MSG\_171, 257  
ER\_IB\_MSG\_172, 257  
ER\_IB\_MSG\_173, 257  
ER\_IB\_MSG\_174, 257  
ER\_IB\_MSG\_175, 257  
ER\_IB\_MSG\_176, 258  
ER\_IB\_MSG\_177, 258  
ER\_IB\_MSG\_178, 258  
ER\_IB\_MSG\_179, 258  
ER\_IB\_MSG\_18, 249  
ER\_IB\_MSG\_180, 258  
ER\_IB\_MSG\_182, 258  
ER\_IB\_MSG\_183, 258  
ER\_IB\_MSG\_184, 258  
ER\_IB\_MSG\_185, 258  
ER\_IB\_MSG\_186, 258  
ER\_IB\_MSG\_187, 258  
ER\_IB\_MSG\_188, 258  
ER\_IB\_MSG\_189, 258  
ER\_IB\_MSG\_19, 249  
ER\_IB\_MSG\_190, 258  
ER\_IB\_MSG\_191, 258  
ER\_IB\_MSG\_192, 259  
ER\_IB\_MSG\_193, 259  
ER\_IB\_MSG\_194, 259  
ER\_IB\_MSG\_195, 259  
ER\_IB\_MSG\_196, 259  
ER\_IB\_MSG\_197, 259  
ER\_IB\_MSG\_198, 259  
ER\_IB\_MSG\_199, 259  
ER\_IB\_MSG\_2, 248  
ER\_IB\_MSG\_20, 249  
ER\_IB\_MSG\_200, 259  
ER\_IB\_MSG\_201, 259  
ER\_IB\_MSG\_202, 259  
ER\_IB\_MSG\_203, 259  
ER\_IB\_MSG\_204, 259  
ER\_IB\_MSG\_205, 259  
ER\_IB\_MSG\_206, 259  
ER\_IB\_MSG\_207, 259  
ER\_IB\_MSG\_208, 260  
ER\_IB\_MSG\_209, 260  
ER\_IB\_MSG\_21, 249  
ER\_IB\_MSG\_210, 260  
ER\_IB\_MSG\_211, 260  
ER\_IB\_MSG\_212, 260  
ER\_IB\_MSG\_213, 260  
ER\_IB\_MSG\_214, 260  
ER\_IB\_MSG\_215, 260  
ER\_IB\_MSG\_216, 260  
ER\_IB\_MSG\_217, 260  
ER\_IB\_MSG\_218, 260  
ER\_IB\_MSG\_219, 260  
ER\_IB\_MSG\_22, 249  
ER\_IB\_MSG\_220, 260  
ER\_IB\_MSG\_221, 260  
ER\_IB\_MSG\_222, 260  
ER\_IB\_MSG\_223, 260  
ER\_IB\_MSG\_224, 261  
ER\_IB\_MSG\_225, 261  
ER\_IB\_MSG\_226, 261  
ER\_IB\_MSG\_227, 261  
ER\_IB\_MSG\_228, 261  
ER\_IB\_MSG\_229, 261  
ER\_IB\_MSG\_23, 249  
ER\_IB\_MSG\_230, 261  
ER\_IB\_MSG\_231, 261  
ER\_IB\_MSG\_232, 261  
ER\_IB\_MSG\_233, 261  
ER\_IB\_MSG\_234, 261  
ER\_IB\_MSG\_235, 261  
ER\_IB\_MSG\_236, 261  
ER\_IB\_MSG\_237, 261  
ER\_IB\_MSG\_238, 261  
ER\_IB\_MSG\_239, 261  
ER\_IB\_MSG\_24, 249  
ER\_IB\_MSG\_240, 262  
ER\_IB\_MSG\_241, 262  
ER\_IB\_MSG\_242, 262  
ER\_IB\_MSG\_243, 262  
ER\_IB\_MSG\_244, 262  
ER\_IB\_MSG\_245, 262  
ER\_IB\_MSG\_246, 262  
ER\_IB\_MSG\_247, 262  
ER\_IB\_MSG\_248, 262  
ER\_IB\_MSG\_249, 262  
ER\_IB\_MSG\_25, 249  
ER\_IB\_MSG\_250, 262  
ER\_IB\_MSG\_251, 262  
ER\_IB\_MSG\_252, 262  
ER\_IB\_MSG\_253, 262  
ER\_IB\_MSG\_254, 262  
ER\_IB\_MSG\_255, 262  
ER\_IB\_MSG\_256, 263  
ER\_IB\_MSG\_257, 263  
ER\_IB\_MSG\_258, 263  
ER\_IB\_MSG\_259, 263  
ER\_IB\_MSG\_26, 249  
ER\_IB\_MSG\_260, 263  
ER\_IB\_MSG\_261, 263  
ER\_IB\_MSG\_262, 263  
ER\_IB\_MSG\_263, 263  
ER\_IB\_MSG\_264, 263

ER\_IB\_MSG\_265, 263  
ER\_IB\_MSG\_266, 263  
ER\_IB\_MSG\_267, 263  
ER\_IB\_MSG\_268, 263  
ER\_IB\_MSG\_269, 263  
ER\_IB\_MSG\_27, 249  
ER\_IB\_MSG\_270, 263  
ER\_IB\_MSG\_271, 263  
ER\_IB\_MSG\_272, 264  
ER\_IB\_MSG\_273, 264  
ER\_IB\_MSG\_278, 264  
ER\_IB\_MSG\_28, 249  
ER\_IB\_MSG\_280, 264  
ER\_IB\_MSG\_281, 264  
ER\_IB\_MSG\_282, 264  
ER\_IB\_MSG\_283, 264  
ER\_IB\_MSG\_284, 264  
ER\_IB\_MSG\_285, 264  
ER\_IB\_MSG\_287, 264  
ER\_IB\_MSG\_288, 264  
ER\_IB\_MSG\_289, 264  
ER\_IB\_MSG\_29, 249  
ER\_IB\_MSG\_291, 264  
ER\_IB\_MSG\_292, 264  
ER\_IB\_MSG\_293, 265  
ER\_IB\_MSG\_294, 265  
ER\_IB\_MSG\_295, 265  
ER\_IB\_MSG\_296, 265  
ER\_IB\_MSG\_297, 265  
ER\_IB\_MSG\_298, 265  
ER\_IB\_MSG\_299, 265  
ER\_IB\_MSG\_3, 248  
ER\_IB\_MSG\_30, 249  
ER\_IB\_MSG\_300, 265  
ER\_IB\_MSG\_301, 265  
ER\_IB\_MSG\_303, 265  
ER\_IB\_MSG\_304, 265  
ER\_IB\_MSG\_305, 265  
ER\_IB\_MSG\_306, 265  
ER\_IB\_MSG\_307, 266  
ER\_IB\_MSG\_308, 266  
ER\_IB\_MSG\_309, 266  
ER\_IB\_MSG\_31, 249  
ER\_IB\_MSG\_310, 266  
ER\_IB\_MSG\_311, 266  
ER\_IB\_MSG\_312, 266  
ER\_IB\_MSG\_313, 266  
ER\_IB\_MSG\_314, 266  
ER\_IB\_MSG\_315, 266  
ER\_IB\_MSG\_316, 266  
ER\_IB\_MSG\_317, 266  
ER\_IB\_MSG\_318, 266  
ER\_IB\_MSG\_319, 266  
ER\_IB\_MSG\_32, 249  
ER\_IB\_MSG\_320, 266  
ER\_IB\_MSG\_321, 266  
ER\_IB\_MSG\_322, 266  
ER\_IB\_MSG\_323, 267

ER\_IB\_MSG\_324, 267  
ER\_IB\_MSG\_325, 267  
ER\_IB\_MSG\_326, 267  
ER\_IB\_MSG\_328, 267  
ER\_IB\_MSG\_329, 267  
ER\_IB\_MSG\_33, 249  
ER\_IB\_MSG\_330, 267  
ER\_IB\_MSG\_331, 267  
ER\_IB\_MSG\_332, 267  
ER\_IB\_MSG\_333, 267  
ER\_IB\_MSG\_334, 267  
ER\_IB\_MSG\_335, 267  
ER\_IB\_MSG\_336, 267  
ER\_IB\_MSG\_337, 267  
ER\_IB\_MSG\_338, 267  
ER\_IB\_MSG\_339, 267  
ER\_IB\_MSG\_34, 250  
ER\_IB\_MSG\_340, 268  
ER\_IB\_MSG\_341, 268  
ER\_IB\_MSG\_342, 268  
ER\_IB\_MSG\_343, 268  
ER\_IB\_MSG\_344, 268  
ER\_IB\_MSG\_345, 268  
ER\_IB\_MSG\_346, 268  
ER\_IB\_MSG\_347, 268  
ER\_IB\_MSG\_348, 268  
ER\_IB\_MSG\_349, 268  
ER\_IB\_MSG\_35, 250  
ER\_IB\_MSG\_350, 268  
ER\_IB\_MSG\_354, 268  
ER\_IB\_MSG\_355, 268  
ER\_IB\_MSG\_356, 268  
ER\_IB\_MSG\_357, 268  
ER\_IB\_MSG\_358, 269  
ER\_IB\_MSG\_359, 269  
ER\_IB\_MSG\_36, 250  
ER\_IB\_MSG\_360, 269  
ER\_IB\_MSG\_361, 269  
ER\_IB\_MSG\_362, 269  
ER\_IB\_MSG\_364, 269  
ER\_IB\_MSG\_365, 269  
ER\_IB\_MSG\_367, 269  
ER\_IB\_MSG\_368, 269  
ER\_IB\_MSG\_369, 269  
ER\_IB\_MSG\_37, 250  
ER\_IB\_MSG\_370, 269  
ER\_IB\_MSG\_371, 269  
ER\_IB\_MSG\_372, 269  
ER\_IB\_MSG\_373, 269  
ER\_IB\_MSG\_374, 269  
ER\_IB\_MSG\_375, 270  
ER\_IB\_MSG\_376, 270  
ER\_IB\_MSG\_377, 270  
ER\_IB\_MSG\_378, 270  
ER\_IB\_MSG\_379, 270  
ER\_IB\_MSG\_38, 250  
ER\_IB\_MSG\_380, 270  
ER\_IB\_MSG\_381, 270



---

ER\_IB\_MSG\_382, 270  
ER\_IB\_MSG\_383, 270  
ER\_IB\_MSG\_384, 270  
ER\_IB\_MSG\_385, 270  
ER\_IB\_MSG\_386, 270  
ER\_IB\_MSG\_387, 270  
ER\_IB\_MSG\_39, 250  
ER\_IB\_MSG\_390, 270  
ER\_IB\_MSG\_391, 271  
ER\_IB\_MSG\_392, 271  
ER\_IB\_MSG\_393, 271  
ER\_IB\_MSG\_394, 271  
ER\_IB\_MSG\_395, 271  
ER\_IB\_MSG\_396, 271  
ER\_IB\_MSG\_397, 271  
ER\_IB\_MSG\_398, 271  
ER\_IB\_MSG\_399, 271  
ER\_IB\_MSG\_4, 248  
ER\_IB\_MSG\_40, 250  
ER\_IB\_MSG\_401, 271  
ER\_IB\_MSG\_402, 271  
ER\_IB\_MSG\_403, 271  
ER\_IB\_MSG\_404, 271  
ER\_IB\_MSG\_405, 271  
ER\_IB\_MSG\_406, 271  
ER\_IB\_MSG\_407, 271  
ER\_IB\_MSG\_408, 272  
ER\_IB\_MSG\_409, 272  
ER\_IB\_MSG\_41, 250  
ER\_IB\_MSG\_410, 272  
ER\_IB\_MSG\_411, 272  
ER\_IB\_MSG\_412, 272  
ER\_IB\_MSG\_413, 272  
ER\_IB\_MSG\_414, 272  
ER\_IB\_MSG\_415, 272  
ER\_IB\_MSG\_416, 272  
ER\_IB\_MSG\_417, 272  
ER\_IB\_MSG\_418, 272  
ER\_IB\_MSG\_419, 272  
ER\_IB\_MSG\_42, 250  
ER\_IB\_MSG\_420, 272  
ER\_IB\_MSG\_421, 272  
ER\_IB\_MSG\_422, 272  
ER\_IB\_MSG\_423, 272  
ER\_IB\_MSG\_424, 273  
ER\_IB\_MSG\_425, 273  
ER\_IB\_MSG\_426, 273  
ER\_IB\_MSG\_427, 273  
ER\_IB\_MSG\_428, 273  
ER\_IB\_MSG\_429, 273  
ER\_IB\_MSG\_43, 250  
ER\_IB\_MSG\_430, 273  
ER\_IB\_MSG\_431, 273  
ER\_IB\_MSG\_432, 273  
ER\_IB\_MSG\_433, 273  
ER\_IB\_MSG\_434, 273  
ER\_IB\_MSG\_435, 273  
ER\_IB\_MSG\_436, 273  
ER\_IB\_MSG\_437, 273  
ER\_IB\_MSG\_438, 273  
ER\_IB\_MSG\_439, 273  
ER\_IB\_MSG\_44, 250  
ER\_IB\_MSG\_440, 274  
ER\_IB\_MSG\_441, 274  
ER\_IB\_MSG\_442, 274  
ER\_IB\_MSG\_443, 274  
ER\_IB\_MSG\_444, 274  
ER\_IB\_MSG\_445, 274  
ER\_IB\_MSG\_446, 274  
ER\_IB\_MSG\_447, 274  
ER\_IB\_MSG\_448, 274  
ER\_IB\_MSG\_449, 274  
ER\_IB\_MSG\_45, 250  
ER\_IB\_MSG\_450, 274  
ER\_IB\_MSG\_451, 274  
ER\_IB\_MSG\_452, 274  
ER\_IB\_MSG\_453, 274  
ER\_IB\_MSG\_454, 274  
ER\_IB\_MSG\_455, 274  
ER\_IB\_MSG\_456, 274  
ER\_IB\_MSG\_457, 275  
ER\_IB\_MSG\_458, 275  
ER\_IB\_MSG\_459, 275  
ER\_IB\_MSG\_46, 250  
ER\_IB\_MSG\_460, 275  
ER\_IB\_MSG\_461, 275  
ER\_IB\_MSG\_462, 275  
ER\_IB\_MSG\_463, 275  
ER\_IB\_MSG\_464, 275  
ER\_IB\_MSG\_465, 275  
ER\_IB\_MSG\_466, 275  
ER\_IB\_MSG\_467, 275  
ER\_IB\_MSG\_468, 275  
ER\_IB\_MSG\_469, 275  
ER\_IB\_MSG\_47, 250  
ER\_IB\_MSG\_470, 275  
ER\_IB\_MSG\_471, 275  
ER\_IB\_MSG\_472, 275  
ER\_IB\_MSG\_473, 276  
ER\_IB\_MSG\_474, 276  
ER\_IB\_MSG\_475, 276  
ER\_IB\_MSG\_476, 276  
ER\_IB\_MSG\_477, 276  
ER\_IB\_MSG\_478, 276  
ER\_IB\_MSG\_479, 276  
ER\_IB\_MSG\_48, 250  
ER\_IB\_MSG\_480, 276  
ER\_IB\_MSG\_481, 276  
ER\_IB\_MSG\_482, 276  
ER\_IB\_MSG\_483, 276  
ER\_IB\_MSG\_484, 276  
ER\_IB\_MSG\_485, 276  
ER\_IB\_MSG\_486, 276  
ER\_IB\_MSG\_487, 276  
ER\_IB\_MSG\_488, 276  
ER\_IB\_MSG\_489, 276

---

ER\_IB\_MSG\_49, 250  
ER\_IB\_MSG\_490, 277  
ER\_IB\_MSG\_491, 277  
ER\_IB\_MSG\_492, 277  
ER\_IB\_MSG\_493, 277  
ER\_IB\_MSG\_494, 277  
ER\_IB\_MSG\_495, 277  
ER\_IB\_MSG\_496, 277  
ER\_IB\_MSG\_497, 277  
ER\_IB\_MSG\_498, 277  
ER\_IB\_MSG\_499, 277  
ER\_IB\_MSG\_5, 248  
ER\_IB\_MSG\_50, 251  
ER\_IB\_MSG\_500, 277  
ER\_IB\_MSG\_501, 277  
ER\_IB\_MSG\_502, 277  
ER\_IB\_MSG\_503, 277  
ER\_IB\_MSG\_504, 277  
ER\_IB\_MSG\_505, 277  
ER\_IB\_MSG\_506, 278  
ER\_IB\_MSG\_507, 278  
ER\_IB\_MSG\_508, 278  
ER\_IB\_MSG\_509, 278  
ER\_IB\_MSG\_51, 251  
ER\_IB\_MSG\_510, 278  
ER\_IB\_MSG\_511, 278  
ER\_IB\_MSG\_512, 278  
ER\_IB\_MSG\_513, 278  
ER\_IB\_MSG\_514, 278  
ER\_IB\_MSG\_515, 278  
ER\_IB\_MSG\_516, 278  
ER\_IB\_MSG\_517, 278  
ER\_IB\_MSG\_518, 278  
ER\_IB\_MSG\_519, 278  
ER\_IB\_MSG\_52, 251  
ER\_IB\_MSG\_520, 278  
ER\_IB\_MSG\_521, 278  
ER\_IB\_MSG\_522, 278  
ER\_IB\_MSG\_523, 279  
ER\_IB\_MSG\_524, 279  
ER\_IB\_MSG\_525, 279  
ER\_IB\_MSG\_526, 279  
ER\_IB\_MSG\_527, 279  
ER\_IB\_MSG\_53, 251  
ER\_IB\_MSG\_530, 279  
ER\_IB\_MSG\_531, 279  
ER\_IB\_MSG\_532, 279  
ER\_IB\_MSG\_533, 279  
ER\_IB\_MSG\_534, 279  
ER\_IB\_MSG\_537, 279  
ER\_IB\_MSG\_538, 279  
ER\_IB\_MSG\_539, 279  
ER\_IB\_MSG\_54, 251  
ER\_IB\_MSG\_540, 279  
ER\_IB\_MSG\_541, 279  
ER\_IB\_MSG\_542, 279  
ER\_IB\_MSG\_543, 280  
ER\_IB\_MSG\_544, 280  
ER\_IB\_MSG\_545, 280  
ER\_IB\_MSG\_546, 280  
ER\_IB\_MSG\_547, 280  
ER\_IB\_MSG\_548, 280  
ER\_IB\_MSG\_549, 280  
ER\_IB\_MSG\_55, 251  
ER\_IB\_MSG\_550, 280  
ER\_IB\_MSG\_551, 280  
ER\_IB\_MSG\_552, 280  
ER\_IB\_MSG\_553, 280  
ER\_IB\_MSG\_554, 280  
ER\_IB\_MSG\_555, 280  
ER\_IB\_MSG\_556, 280  
ER\_IB\_MSG\_557, 280  
ER\_IB\_MSG\_558, 280  
ER\_IB\_MSG\_559, 280  
ER\_IB\_MSG\_56, 251  
ER\_IB\_MSG\_560, 281  
ER\_IB\_MSG\_561, 281  
ER\_IB\_MSG\_562, 281  
ER\_IB\_MSG\_563, 281  
ER\_IB\_MSG\_564, 281  
ER\_IB\_MSG\_566, 281  
ER\_IB\_MSG\_567, 281  
ER\_IB\_MSG\_568, 281  
ER\_IB\_MSG\_569, 281  
ER\_IB\_MSG\_57, 251  
ER\_IB\_MSG\_570, 281  
ER\_IB\_MSG\_571, 281  
ER\_IB\_MSG\_573, 281  
ER\_IB\_MSG\_574, 281  
ER\_IB\_MSG\_578, 281  
ER\_IB\_MSG\_579, 281  
ER\_IB\_MSG\_57\_STAT\_SPACE\_DELETE\_FAIL,  
356  
ER\_IB\_MSG\_57\_UNDO\_SPACE\_DELETE\_FAIL,  
353  
ER\_IB\_MSG\_58, 251  
ER\_IB\_MSG\_580, 282  
ER\_IB\_MSG\_581, 282  
ER\_IB\_MSG\_582, 282  
ER\_IB\_MSG\_583, 282  
ER\_IB\_MSG\_584, 282  
ER\_IB\_MSG\_585, 282  
ER\_IB\_MSG\_586, 282  
ER\_IB\_MSG\_587, 282  
ER\_IB\_MSG\_588, 282  
ER\_IB\_MSG\_589, 282  
ER\_IB\_MSG\_59, 251  
ER\_IB\_MSG\_590, 282  
ER\_IB\_MSG\_591, 282  
ER\_IB\_MSG\_592, 282  
ER\_IB\_MSG\_593, 282  
ER\_IB\_MSG\_594, 282  
ER\_IB\_MSG\_595, 282  
ER\_IB\_MSG\_596, 283  
ER\_IB\_MSG\_597, 283  
ER\_IB\_MSG\_598, 283

---

ER\_IB\_MSG\_599, 283  
ER\_IB\_MSG\_6, 248  
ER\_IB\_MSG\_60, 251  
ER\_IB\_MSG\_600, 283  
ER\_IB\_MSG\_601, 283  
ER\_IB\_MSG\_602, 283  
ER\_IB\_MSG\_603, 283  
ER\_IB\_MSG\_604, 283  
ER\_IB\_MSG\_605, 283  
ER\_IB\_MSG\_606, 283  
ER\_IB\_MSG\_607, 283  
ER\_IB\_MSG\_608, 283  
ER\_IB\_MSG\_609, 283  
ER\_IB\_MSG\_61, 251  
ER\_IB\_MSG\_610, 283  
ER\_IB\_MSG\_611, 283  
ER\_IB\_MSG\_612, 283  
ER\_IB\_MSG\_613, 284  
ER\_IB\_MSG\_614, 284  
ER\_IB\_MSG\_615, 284  
ER\_IB\_MSG\_616, 284  
ER\_IB\_MSG\_617, 284  
ER\_IB\_MSG\_618, 284  
ER\_IB\_MSG\_619, 284  
ER\_IB\_MSG\_62, 251  
ER\_IB\_MSG\_620, 284  
ER\_IB\_MSG\_621, 284  
ER\_IB\_MSG\_622, 284  
ER\_IB\_MSG\_623, 284  
ER\_IB\_MSG\_624, 284  
ER\_IB\_MSG\_625, 284  
ER\_IB\_MSG\_626, 284  
ER\_IB\_MSG\_627, 284  
ER\_IB\_MSG\_628, 284  
ER\_IB\_MSG\_629, 285  
ER\_IB\_MSG\_63, 251  
ER\_IB\_MSG\_630, 285  
ER\_IB\_MSG\_631, 285  
ER\_IB\_MSG\_632, 285  
ER\_IB\_MSG\_633, 285  
ER\_IB\_MSG\_634, 285  
ER\_IB\_MSG\_635, 285  
ER\_IB\_MSG\_636, 285  
ER\_IB\_MSG\_637, 285  
ER\_IB\_MSG\_638, 285  
ER\_IB\_MSG\_639, 285  
ER\_IB\_MSG\_64, 251  
ER\_IB\_MSG\_642, 285  
ER\_IB\_MSG\_643, 285  
ER\_IB\_MSG\_644, 285  
ER\_IB\_MSG\_645, 285  
ER\_IB\_MSG\_646, 285  
ER\_IB\_MSG\_647, 286  
ER\_IB\_MSG\_648, 286  
ER\_IB\_MSG\_649, 286  
ER\_IB\_MSG\_65, 251  
ER\_IB\_MSG\_650, 286  
ER\_IB\_MSG\_651, 286  
ER\_IB\_MSG\_652, 286  
ER\_IB\_MSG\_654, 286  
ER\_IB\_MSG\_655, 286  
ER\_IB\_MSG\_656, 286  
ER\_IB\_MSG\_657, 286  
ER\_IB\_MSG\_658, 286  
ER\_IB\_MSG\_659, 286  
ER\_IB\_MSG\_66, 252  
ER\_IB\_MSG\_660, 286  
ER\_IB\_MSG\_661, 286  
ER\_IB\_MSG\_662, 286  
ER\_IB\_MSG\_663, 287  
ER\_IB\_MSG\_67, 252  
ER\_IB\_MSG\_68, 252  
ER\_IB\_MSG\_69, 252  
ER\_IB\_MSG\_694, 287  
ER\_IB\_MSG\_695, 287  
ER\_IB\_MSG\_696, 287  
ER\_IB\_MSG\_697, 287  
ER\_IB\_MSG\_699, 287  
ER\_IB\_MSG\_7, 248  
ER\_IB\_MSG\_70, 252  
ER\_IB\_MSG\_707, 287  
ER\_IB\_MSG\_708, 288  
ER\_IB\_MSG\_709, 288  
ER\_IB\_MSG\_71, 252  
ER\_IB\_MSG\_710, 288  
ER\_IB\_MSG\_711, 288  
ER\_IB\_MSG\_712, 288  
ER\_IB\_MSG\_713, 288  
ER\_IB\_MSG\_714, 288  
ER\_IB\_MSG\_715, 288  
ER\_IB\_MSG\_716, 288  
ER\_IB\_MSG\_718, 288  
ER\_IB\_MSG\_719, 288  
ER\_IB\_MSG\_72, 252  
ER\_IB\_MSG\_720, 288  
ER\_IB\_MSG\_722, 288  
ER\_IB\_MSG\_723, 288  
ER\_IB\_MSG\_724, 289  
ER\_IB\_MSG\_725, 289  
ER\_IB\_MSG\_726, 289  
ER\_IB\_MSG\_727, 289  
ER\_IB\_MSG\_728, 289  
ER\_IB\_MSG\_73, 252  
ER\_IB\_MSG\_737, 289  
ER\_IB\_MSG\_738, 289  
ER\_IB\_MSG\_739, 290  
ER\_IB\_MSG\_74, 252  
ER\_IB\_MSG\_740, 290  
ER\_IB\_MSG\_741, 290  
ER\_IB\_MSG\_742, 290  
ER\_IB\_MSG\_743, 290  
ER\_IB\_MSG\_744, 290  
ER\_IB\_MSG\_745, 290  
ER\_IB\_MSG\_746, 290  
ER\_IB\_MSG\_747, 290  
ER\_IB\_MSG\_748, 290

ER\_IB\_MSG\_749, 290  
ER\_IB\_MSG\_75, 252  
ER\_IB\_MSG\_750, 290  
ER\_IB\_MSG\_751, 290  
ER\_IB\_MSG\_752, 290  
ER\_IB\_MSG\_753, 290  
ER\_IB\_MSG\_754, 290  
ER\_IB\_MSG\_755, 291  
ER\_IB\_MSG\_756, 291  
ER\_IB\_MSG\_757, 291  
ER\_IB\_MSG\_758, 291  
ER\_IB\_MSG\_759, 291  
ER\_IB\_MSG\_76, 252  
ER\_IB\_MSG\_760, 291  
ER\_IB\_MSG\_761, 291  
ER\_IB\_MSG\_762, 291  
ER\_IB\_MSG\_763, 291  
ER\_IB\_MSG\_764, 291  
ER\_IB\_MSG\_765, 291  
ER\_IB\_MSG\_766, 291  
ER\_IB\_MSG\_767, 291  
ER\_IB\_MSG\_768, 291  
ER\_IB\_MSG\_769, 291  
ER\_IB\_MSG\_77, 252  
ER\_IB\_MSG\_770, 291  
ER\_IB\_MSG\_771, 292  
ER\_IB\_MSG\_772, 292  
ER\_IB\_MSG\_773, 292  
ER\_IB\_MSG\_774, 292  
ER\_IB\_MSG\_775, 292  
ER\_IB\_MSG\_776, 292  
ER\_IB\_MSG\_777, 292  
ER\_IB\_MSG\_778, 292  
ER\_IB\_MSG\_779, 292  
ER\_IB\_MSG\_78, 252  
ER\_IB\_MSG\_780, 292  
ER\_IB\_MSG\_781, 292  
ER\_IB\_MSG\_782, 292  
ER\_IB\_MSG\_783, 292  
ER\_IB\_MSG\_784, 292  
ER\_IB\_MSG\_785, 292  
ER\_IB\_MSG\_786, 292  
ER\_IB\_MSG\_787, 293  
ER\_IB\_MSG\_788, 293  
ER\_IB\_MSG\_789, 293  
ER\_IB\_MSG\_79, 252  
ER\_IB\_MSG\_790, 293  
ER\_IB\_MSG\_791, 293  
ER\_IB\_MSG\_792, 293  
ER\_IB\_MSG\_793, 293  
ER\_IB\_MSG\_794, 293  
ER\_IB\_MSG\_795, 293  
ER\_IB\_MSG\_796, 293  
ER\_IB\_MSG\_797, 293  
ER\_IB\_MSG\_798, 293  
ER\_IB\_MSG\_799, 293  
ER\_IB\_MSG\_8, 248  
ER\_IB\_MSG\_80, 252

ER\_IB\_MSG\_800, 293  
ER\_IB\_MSG\_801, 293  
ER\_IB\_MSG\_802, 293  
ER\_IB\_MSG\_803, 294  
ER\_IB\_MSG\_804, 294  
ER\_IB\_MSG\_805, 294  
ER\_IB\_MSG\_806, 294  
ER\_IB\_MSG\_807, 294  
ER\_IB\_MSG\_808, 294  
ER\_IB\_MSG\_809, 294  
ER\_IB\_MSG\_81, 252  
ER\_IB\_MSG\_810, 294  
ER\_IB\_MSG\_811, 294  
ER\_IB\_MSG\_812, 294  
ER\_IB\_MSG\_813, 294  
ER\_IB\_MSG\_814, 294  
ER\_IB\_MSG\_815, 294  
ER\_IB\_MSG\_816, 294  
ER\_IB\_MSG\_817, 294  
ER\_IB\_MSG\_818, 294  
ER\_IB\_MSG\_819, 295  
ER\_IB\_MSG\_82, 253  
ER\_IB\_MSG\_820, 295  
ER\_IB\_MSG\_821, 295  
ER\_IB\_MSG\_822, 295  
ER\_IB\_MSG\_823, 295  
ER\_IB\_MSG\_824, 295  
ER\_IB\_MSG\_825, 295  
ER\_IB\_MSG\_826, 295  
ER\_IB\_MSG\_827, 295  
ER\_IB\_MSG\_828, 295  
ER\_IB\_MSG\_829, 295  
ER\_IB\_MSG\_83, 253  
ER\_IB\_MSG\_830, 295  
ER\_IB\_MSG\_831, 295  
ER\_IB\_MSG\_832, 295  
ER\_IB\_MSG\_833, 295  
ER\_IB\_MSG\_834, 295  
ER\_IB\_MSG\_835, 295  
ER\_IB\_MSG\_836, 296  
ER\_IB\_MSG\_837, 296  
ER\_IB\_MSG\_838, 296  
ER\_IB\_MSG\_839, 296  
ER\_IB\_MSG\_84, 253  
ER\_IB\_MSG\_840, 296  
ER\_IB\_MSG\_841, 296  
ER\_IB\_MSG\_842, 296  
ER\_IB\_MSG\_844, 296  
ER\_IB\_MSG\_845, 296  
ER\_IB\_MSG\_846, 296  
ER\_IB\_MSG\_847, 296  
ER\_IB\_MSG\_848, 296  
ER\_IB\_MSG\_849, 296  
ER\_IB\_MSG\_85, 253  
ER\_IB\_MSG\_850, 296  
ER\_IB\_MSG\_851, 296  
ER\_IB\_MSG\_852, 297  
ER\_IB\_MSG\_853, 297

---

ER\_IB\_MSG\_854, 297  
ER\_IB\_MSG\_855, 297  
ER\_IB\_MSG\_856, 297  
ER\_IB\_MSG\_857, 297  
ER\_IB\_MSG\_858, 297  
ER\_IB\_MSG\_859, 297  
ER\_IB\_MSG\_86, 253  
ER\_IB\_MSG\_860, 297  
ER\_IB\_MSG\_861, 297  
ER\_IB\_MSG\_862, 297  
ER\_IB\_MSG\_863, 297  
ER\_IB\_MSG\_864, 297  
ER\_IB\_MSG\_865, 297  
ER\_IB\_MSG\_866, 297  
ER\_IB\_MSG\_867, 297  
ER\_IB\_MSG\_868, 298  
ER\_IB\_MSG\_869, 298  
ER\_IB\_MSG\_870, 298  
ER\_IB\_MSG\_871, 298  
ER\_IB\_MSG\_872, 298  
ER\_IB\_MSG\_873, 298  
ER\_IB\_MSG\_874, 298  
ER\_IB\_MSG\_875, 298  
ER\_IB\_MSG\_876, 298  
ER\_IB\_MSG\_877, 298  
ER\_IB\_MSG\_878, 298  
ER\_IB\_MSG\_879, 298  
ER\_IB\_MSG\_880, 298  
ER\_IB\_MSG\_881, 298  
ER\_IB\_MSG\_882, 298  
ER\_IB\_MSG\_883, 298  
ER\_IB\_MSG\_884, 299  
ER\_IB\_MSG\_885, 299  
ER\_IB\_MSG\_886, 299  
ER\_IB\_MSG\_887, 299  
ER\_IB\_MSG\_888, 299  
ER\_IB\_MSG\_889, 299  
ER\_IB\_MSG\_890, 299  
ER\_IB\_MSG\_891, 299  
ER\_IB\_MSG\_892, 299  
ER\_IB\_MSG\_893, 299  
ER\_IB\_MSG\_894, 299  
ER\_IB\_MSG\_895, 299  
ER\_IB\_MSG\_896, 299  
ER\_IB\_MSG\_897, 299  
ER\_IB\_MSG\_898, 299  
ER\_IB\_MSG\_899, 299  
ER\_IB\_MSG\_9, 248  
ER\_IB\_MSG\_900, 300  
ER\_IB\_MSG\_901, 300  
ER\_IB\_MSG\_902, 300  
ER\_IB\_MSG\_903, 300  
ER\_IB\_MSG\_904, 300  
ER\_IB\_MSG\_905, 300  
ER\_IB\_MSG\_906, 300  
ER\_IB\_MSG\_907, 300  
ER\_IB\_MSG\_908, 300  
ER\_IB\_MSG\_909, 300  
ER\_IB\_MSG\_910, 300  
ER\_IB\_MSG\_911, 300  
ER\_IB\_MSG\_912, 300  
ER\_IB\_MSG\_913, 300  
ER\_IB\_MSG\_914, 300  
ER\_IB\_MSG\_915, 300  
ER\_IB\_MSG\_916, 301  
ER\_IB\_MSG\_917, 301  
ER\_IB\_MSG\_918, 301  
ER\_IB\_MSG\_919, 301  
ER\_IB\_MSG\_920, 301  
ER\_IB\_MSG\_921, 301  
ER\_IB\_MSG\_922, 301  
ER\_IB\_MSG\_923, 301  
ER\_IB\_MSG\_924, 301  
ER\_IB\_MSG\_925, 301  
ER\_IB\_MSG\_926, 301  
ER\_IB\_MSG\_927, 301  
ER\_IB\_MSG\_928, 301  
ER\_IB\_MSG\_929, 301  
ER\_IB\_MSG\_930, 301  
ER\_IB\_MSG\_931, 301  
ER\_IB\_MSG\_932, 301  
ER\_IB\_MSG\_933, 302  
ER\_IB\_MSG\_934, 302  
ER\_IB\_MSG\_935, 302  
ER\_IB\_MSG\_936, 302  
ER\_IB\_MSG\_937, 302  
ER\_IB\_MSG\_938, 302  
ER\_IB\_MSG\_939, 302  
ER\_IB\_MSG\_940, 302  
ER\_IB\_MSG\_941, 302  
ER\_IB\_MSG\_942, 302  
ER\_IB\_MSG\_943, 302  
ER\_IB\_MSG\_944, 302  
ER\_IB\_MSG\_945, 302  
ER\_IB\_MSG\_946, 302  
ER\_IB\_MSG\_948, 302  
ER\_IB\_MSG\_949, 303  
ER\_IB\_MSG\_95, 253  
ER\_IB\_MSG\_950, 303  
ER\_IB\_MSG\_951, 303  
ER\_IB\_MSG\_952, 303  
ER\_IB\_MSG\_953, 303  
ER\_IB\_MSG\_954, 303  
ER\_IB\_MSG\_955, 303  
ER\_IB\_MSG\_956, 303  
ER\_IB\_MSG\_957, 303  
ER\_IB\_MSG\_958, 303  
ER\_IB\_MSG\_959, 303  
ER\_IB\_MSG\_96, 253  
ER\_IB\_MSG\_960, 303  
ER\_IB\_MSG\_961, 303  
ER\_IB\_MSG\_962, 303  
ER\_IB\_MSG\_963, 303  
ER\_IB\_MSG\_964, 303  
ER\_IB\_MSG\_965, 304  
ER\_IB\_MSG\_966, 304

---

ER\_IB\_MSG\_967, 304  
ER\_IB\_MSG\_968, 304  
ER\_IB\_MSG\_969, 304  
ER\_IB\_MSG\_97, 253  
ER\_IB\_MSG\_970, 304  
ER\_IB\_MSG\_971, 304  
ER\_IB\_MSG\_972, 304  
ER\_IB\_MSG\_973, 304  
ER\_IB\_MSG\_974, 304  
ER\_IB\_MSG\_975, 304  
ER\_IB\_MSG\_976, 304  
ER\_IB\_MSG\_977, 304  
ER\_IB\_MSG\_978, 304  
ER\_IB\_MSG\_979, 304  
ER\_IB\_MSG\_98, 253  
ER\_IB\_MSG\_980, 304  
ER\_IB\_MSG\_981, 305  
ER\_IB\_MSG\_982, 305  
ER\_IB\_MSG\_983, 305  
ER\_IB\_MSG\_984, 305  
ER\_IB\_MSG\_985, 305  
ER\_IB\_MSG\_986, 305  
ER\_IB\_MSG\_987, 305  
ER\_IB\_MSG\_988, 305  
ER\_IB\_MSG\_989, 305  
ER\_IB\_MSG\_99, 253  
ER\_IB\_MSG\_990, 305  
ER\_IB\_MSG\_991, 305  
ER\_IB\_MSG\_992, 305  
ER\_IB\_MSG\_993, 305  
ER\_IB\_MSG\_994, 305  
ER\_IB\_MSG\_995, 305  
ER\_IB\_MSG\_996, 305  
ER\_IB\_MSG\_997, 306  
ER\_IB\_MSG\_998, 306  
ER\_IB\_MSG\_999, 306  
ER\_IB\_MSG\_BAD\_DBLWR\_FILE\_NAME, 353  
ER\_IB\_MSG\_BTREE\_LEVEL\_LIMIT\_EXCEEDED,  
347  
ER\_IB\_MSG\_BUF\_PENDING\_IO, 312  
ER\_IB\_MSG\_BUF\_PENDING\_IO\_ON\_SHUTDOWN,  
321  
ER\_IB\_MSG\_BUF\_POOL\_RESIZE\_CODE\_STATUS,  
386  
ER\_IB\_MSG\_BUF\_POOL\_RESIZE\_COMPLETE\_CUR\_CORRUPT,  
386  
ER\_IB\_MSG\_BUF\_POOL\_RESIZE\_PROGRESS\_UPDATED,  
386  
ER\_IB\_MSG\_CANNOT\_FIND\_DD\_UNDO\_SPACE,  
357  
ER\_IB\_MSG\_CANNOT\_OPEN\_57\_UNDO, 311  
ER\_IB\_MSG\_CANT\_ENCRYPT\_REDO\_LOG\_DATA,  
296  
ER\_IB\_MSG\_CLEAR\_INSTANT\_DROP\_COLUMN\_METADATA,  
386  
ER\_IB\_MSG\_CLOCK\_GETTIME\_FAILED, 345  
ER\_IB\_MSG\_CLOCK\_MONOTONIC\_UNSUPPORTED,  
345  
ER\_IB\_MSG\_CLONE\_DDL\_APPLY, 374  
ER\_IB\_MSG\_CLONE\_DDL\_INVALIDATE, 374  
ER\_IB\_MSG\_CLONE\_DDL\_NTFN, 374  
ER\_IB\_MSG\_CREATED\_UNDO\_SPACE, 363  
ER\_IB\_MSG\_DATA\_DIRECTORY\_NOT\_INITIALIZED\_OR\_CORRUPT,  
314  
ER\_IB\_MSG\_DBLWR\_1285, 353  
ER\_IB\_MSG\_DBLWR\_1286, 353  
ER\_IB\_MSG\_DBLWR\_1287, 353  
ER\_IB\_MSG\_DBLWR\_1288, 353  
ER\_IB\_MSG\_DBLWR\_1290, 353  
ER\_IB\_MSG\_DBLWR\_1293, 353  
ER\_IB\_MSG\_DBLWR\_1294, 353  
ER\_IB\_MSG\_DBLWR\_1295, 354  
ER\_IB\_MSG\_DBLWR\_1296, 354  
ER\_IB\_MSG\_DBLWR\_1297, 354  
ER\_IB\_MSG\_DBLWR\_1298, 354  
ER\_IB\_MSG\_DBLWR\_1300, 354  
ER\_IB\_MSG\_DBLWR\_1301, 354  
ER\_IB\_MSG\_DBLWR\_1304, 354  
ER\_IB\_MSG\_DBLWR\_1305, 354  
ER\_IB\_MSG\_DBLWR\_1306, 354  
ER\_IB\_MSG\_DBLWR\_1307, 354  
ER\_IB\_MSG\_DBLWR\_1308, 354  
ER\_IB\_MSG\_DBLWR\_1309, 354  
ER\_IB\_MSG\_DBLWR\_1310, 354  
ER\_IB\_MSG\_DBLWR\_1311, 354  
ER\_IB\_MSG\_DBLWR\_1312, 354  
ER\_IB\_MSG\_DBLWR\_1313, 354  
ER\_IB\_MSG\_DBLWR\_1314, 355  
ER\_IB\_MSG\_DBLWR\_1315, 355  
ER\_IB\_MSG\_DBLWR\_1316, 355  
ER\_IB\_MSG\_DBLWR\_1317, 355  
ER\_IB\_MSG\_DBLWR\_1318, 355  
ER\_IB\_MSG\_DBLWR\_1320, 355  
ER\_IB\_MSG\_DBLWR\_1321, 355  
ER\_IB\_MSG\_DBLWR\_1323, 355  
ER\_IB\_MSG\_DBLWR\_1324, 355  
ER\_IB\_MSG\_DBLWR\_1325, 355  
ER\_IB\_MSG\_DBLWR\_1326, 355  
ER\_IB\_MSG\_DBLWR\_1327, 355  
ER\_IB\_MSG\_DBLWR\_LOAD\_WRONG\_SIZE, 355  
ER\_IB\_MSG\_DBLWR\_OPEN\_OR\_CREATE\_WRONG\_SIZE,  
355  
ER\_IB\_MSG\_DDL\_FAIL\_NO\_BUILDER, 396  
ER\_IB\_MSG\_DDL\_LOG\_DELETE\_BY\_ID\_OK, 286  
ER\_IB\_MSG\_DDL\_LOG\_DELETE\_BY\_ID\_TMCT,  
343  
ER\_IB\_MSG\_DDL\_LOG\_FAIL\_POST\_DDL, 344  
ER\_IB\_MSG\_DEPRECATED\_INNOODB\_UNDO\_TABLESPACES,  
334  
ER\_IB\_MSG\_DICT\_PARTITION\_NOT\_FOUND,  
352  
ER\_IB\_MSG\_DOWNGRADE\_PARTITION\_FILE,  
351  
ER\_IB\_MSG\_DROPPED\_UNDO\_SPACE, 363  
ER\_IB\_MSG\_ERROR\_OPENING\_NEW\_UNDO\_SPACE,  
333

---

ER\_IB\_MSG\_FAILED\_SDI\_Z\_BUF\_ERROR, 333  
 ER\_IB\_MSG\_FAILED\_SDI\_Z\_MEM\_ERROR, 334  
 ER\_IB\_MSG\_FAILED\_TO\_ALLOCATE\_WAIT, 333  
 ER\_IB\_MSG\_FAILED\_TO\_FINISH\_TRUNCATE,  
 334  
 ER\_IB\_MSG\_FAIL\_TO\_SAVE\_SPACE\_STATE,  
 333  
 ER\_IB\_MSG\_FILE\_RESIZE, 310  
 ER\_IB\_MSG\_FIL\_STATE\_MOVED\_CHANGED\_NAME,  
 352  
 ER\_IB\_MSG\_FIL\_STATE\_MOVED\_CHANGED\_PATH,  
 352  
 ER\_IB\_MSG\_FIL\_STATE\_MOVED\_CORRECTED,  
 352  
 ER\_IB\_MSG\_FIL\_STATE\_MOVED\_TOO\_MANY,  
 352  
 ER\_IB\_MSG\_FOUND\_WRONG\_UNDO\_SPACE,  
 334  
 ER\_IB\_MSG\_GENERAL\_TABLESPACE\_UNDER\_DATA,  
 270  
 ER\_IB\_MSG\_GTID\_FLUSH\_AT\_SHUTDOWN, 355  
 ER\_IB\_MSG\_IGNORE\_SCAN\_PATH, 269  
 ER\_IB\_MSG\_IMPLICIT\_TABLESPACE\_IN\_DATADIR,  
 270  
 ER\_IB\_MSG\_INCORRECT\_SIZE, 362  
 ER\_IB\_MSG\_INJECT\_CRASH, 362  
 ER\_IB\_MSG\_INJECT\_FAILURE, 362  
 ER\_IB\_MSG\_INNODB\_END\_INITIALIZE, 356  
 ER\_IB\_MSG\_INNODB\_START\_INITIALIZE, 356  
 ER\_IB\_MSG\_INVALID\_LOCATION\_FOR\_TABLE,  
 281  
 ER\_IB\_MSG\_INVALID\_LOCATION\_FOR\_TABLESPACE,  
 357  
 ER\_IB\_MSG\_INVALID\_LOCATION\_WRONG\_DB,  
 357  
 ER\_IB\_MSG\_INVALID\_PAGE\_TYPE, 387  
 ER\_IB\_MSG\_LOCK\_FREE\_HASH\_USAGE\_STATS,  
 334  
 ER\_IB\_MSG\_LOG\_CHECKPOINT\_FOUND, 381  
 ER\_IB\_MSG\_LOG\_CORRUPT, 287  
 ER\_IB\_MSG\_LOG\_FILES\_CANNOT\_ENCRYPT\_IN\_READ\_ONLY,  
 321  
 ER\_IB\_MSG\_LOG\_FILES\_CAPACITY\_CHANGED,  
 381  
 ER\_IB\_MSG\_LOG\_FILES\_CREATED\_BY\_CLONE,  
 289  
 ER\_IB\_MSG\_LOG\_FILES\_CREATED\_BY\_CLONE\_AND\_READ\_ONLY\_MODE,  
 379  
 ER\_IB\_MSG\_LOG\_FILES\_CREATED\_BY\_MEB,  
 289  
 ER\_IB\_MSG\_LOG\_FILES\_CREATED\_BY\_MEB\_AND\_READ\_ONLY\_MODE,  
 289  
 ER\_IB\_MSG\_LOG\_FILES\_CREATED\_BY\_UNKNOWN\_CREATOR,  
 382  
 ER\_IB\_MSG\_LOG\_FILES\_CREATE\_AND\_READ\_ONLY\_MODE,  
 310  
 ER\_IB\_MSG\_LOG\_FILES\_DIFFERENT\_SIZES,  
 314  
 ER\_IB\_MSG\_LOG\_FILES\_ENCRYPTION\_INIT\_FAILED,  
 321  
 ER\_IB\_MSG\_LOG\_FILES\_FOUND\_MISSING, 382  
 ER\_IB\_MSG\_LOG\_FILES\_INITIALIZED, 310  
 ER\_IB\_MSG\_LOG\_FILES\_INVALID\_SET, 314  
 ER\_IB\_MSG\_LOG\_FILES\_RESIZE\_CANCELLED,  
 381  
 ER\_IB\_MSG\_LOG\_FILES\_RESIZE\_FINISHED, 381  
 ER\_IB\_MSG\_LOG\_FILES\_RESIZE\_ON\_START,  
 319  
 ER\_IB\_MSG\_LOG\_FILES\_RESIZE\_REQUESTED,  
 381  
 ER\_IB\_MSG\_LOG\_FILES\_REWRITING, 315  
 ER\_IB\_MSG\_LOG\_FILES\_UPGRADE, 381  
 ER\_IB\_MSG\_LOG\_FILE\_DIFFERENT\_FORMATS,  
 382  
 ER\_IB\_MSG\_LOG\_FILE\_FOREIGN\_UUID, 381  
 ER\_IB\_MSG\_LOG\_FILE\_FORMAT\_TOO\_NEW,  
 382  
 ER\_IB\_MSG\_LOG\_FILE\_FORMAT\_TOO\_OLD, 382  
 ER\_IB\_MSG\_LOG\_FILE\_FORMAT\_UNKNOWN,  
 287  
 ER\_IB\_MSG\_LOG\_FILE\_HEADER\_INVALID\_CHECKSUM,  
 322  
 ER\_IB\_MSG\_LOG\_FILE\_HEADER\_READ\_FAILED,  
 379  
 ER\_IB\_MSG\_LOG\_FILE\_INVALID\_LSN\_RANGES,  
 381  
 ER\_IB\_MSG\_LOG\_FILE\_INVALID\_START\_LSN,  
 381  
 ER\_IB\_MSG\_LOG\_FILE\_IS\_EMPTY, 379  
 ER\_IB\_MSG\_LOG\_FILE\_MARK\_AS\_UNUSED\_FAILED,  
 383  
 ER\_IB\_MSG\_LOG\_FILE\_MARK\_CURRENT\_AS\_INCOMPLETE,  
 381  
 ER\_IB\_MSG\_LOG\_FILE\_MISSING\_FOR\_ID, 381  
 ER\_IB\_MSG\_LOG\_FILE\_OPEN\_FAILED, 310  
 ER\_IB\_MSG\_LOG\_FILE\_OS\_CREATE\_FAILED,  
 309  
 ER\_IB\_MSG\_LOG\_FILE\_PREPARE\_ON\_CREATE\_FAILED,  
 310  
 ER\_IB\_MSG\_LOG\_FILE\_REMOVE\_FAILED, 381  
 ER\_IB\_MSG\_LOG\_FILE\_RENAME\_ON\_CREATE\_FAILED,  
 382  
 ER\_IB\_MSG\_LOG\_FILE\_RESIZE\_FAILED, 310  
 ER\_IB\_MSG\_LOG\_FILE\_SIZE\_INVALID, 314  
 ER\_IB\_MSG\_LOG\_FILE\_TOO\_BIG, 379  
 ER\_IB\_MSG\_LOG\_FILE\_TOO\_SMALL, 379  
 ER\_IB\_MSG\_LOG\_FILE\_TRUNCATE, 382  
 ER\_IB\_MSG\_LOG\_FILE\_UNUSED\_MARK\_AS\_IN\_USE\_FAILED,  
 382  
 ER\_IB\_MSG\_LOG\_FILE\_UNUSED\_REMOVE\_FAILED,  
 382  
 ER\_IB\_MSG\_LOG\_FILE\_UNUSED\_RENAME\_FAILED,  
 310  
 ER\_IB\_MSG\_LOG\_FILE\_UNUSED\_RESIZE\_FAILED,  
 382  
 ER\_IB\_MSG\_LOG\_FORMAT\_BEFORE\_5\_7\_9, 322

---

---

ER_IB_MSG_LOG_FORMAT_BEFORE_8_0_30, 287	ER_IB_MSG_NOT_END_WITH_IBU, 334
ER_IB_MSG_LOG_FORMAT_OLD, 289	ER_IB_MSG_NO_ENCRYPT_PROGRESS_FOUND, 329
ER_IB_MSG_LOG_FORMAT_OLD_AND_LOG_CORRUPTED, 287	ER_IB_MSG_PAGE_ARCH_NO_RESET_POINTS, 356
ER_IB_MSG_LOG_FORMAT_OLD_AND_NO_CLEAN_SHUTDOWN, 287	ER_IB_MSG_PARSE_OLD_REDO_INDEX_VERSION, 385
ER_IB_MSG_LOG_INIT_DIR_LIST_FAILED, 379	ER_IB_MSG_PAR_RSEG_INIT_COMPLETE_MSG, 372
ER_IB_MSG_LOG_INIT_DIR_MISSING_SUBDIR, 379	ER_IB_MSG_PAR_RSEG_INIT_TIME_MSG, 372
ER_IB_MSG_LOG_INIT_DIR_NOT_EMPTY_WONT_INITIALIZE, 379	ER_IB_MSG_POST_RECOVER_DDL_LOG_RECOVER, 343
ER_IB_MSG_LOG_PARAMS_CONCURRENCY_MARGIN_RUNNING, 322	ER_IB_MSG_POST_RECOVER_POST_TS_ENCRYPT, 344
ER_IB_MSG_LOG_PARAMS_DEDICATED_SERVER_IGNORED, 383	ER_IB_MSG_RECOVERY_CHECKPOINT_FROM_BEFORE_CLONE, 289
ER_IB_MSG_LOG_PARAMS_FILE_SIZE_UNUSED, 380	ER_IB_MSG_RECOVERY_CHECKPOINT_NOT_FOUND, 287
ER_IB_MSG_LOG_PARAMS_LEGACY_USAGE, 383	ER_IB_MSG_RECOVERY_CHECKPOINT_OUTSIDE_LOG_FILES, 380
ER_IB_MSG_LOG_PARAMS_N_FILES_UNUSED, 380	ER_IB_MSG_RECOVERY_CORRUPT, 315
ER_IB_MSG_LOG_PFS_ACQUIRE_SERVICES_FAILED, 382	ER_IB_MSG_RECOVERY_IN_READ_ONLY, 289
ER_IB_MSG_LOG_PFS_CREATE_TABLES_FAILED, 382	ER_IB_MSG_RECOVERY_IS_NEEDED, 289
ER_IB_MSG_LOG_PFS_CREATE_TABLES_FAILED, 382	ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG__SKIP, 372
ER_IB_MSG_LOG_PRE_8_0_30_MISSING_FILE0, 382	ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG__UNE, 372
ER_IB_MSG_LOG_UPGRADE_CLONED_DB, 380	ER_IB_MSG_RECOVERY_SKIPPED_IN_READ_ONLY_MODE, 288
ER_IB_MSG_LOG_UPGRADE_CORRUPTION__UNEXPECTED, 381	ER_IB_MSG_REENCRYPTED_GENERAL_TABLESPACE_KEY, 371
ER_IB_MSG_LOG_UPGRADE_FORCED_RECV, 380	ER_IB_MSG_REENCRYPTED_TABLESPACE_KEY, 371
ER_IB_MSG_LOG_UPGRADE_IN_READ_ONLY_MODE, 380	ER_IB_MSG_RESUME_OP_FOR_SPACE, 329
ER_IB_MSG_LOG_UPGRADE_UNINITIALIZED_FILES, 380	ER_IB_MSG_SCANNING_TEMP_TABLESPACE_DIR, 360
ER_IB_MSG_LOG_WRITER_ABORTS_LOG_ARCHIVER, 320	ER_IB_MSG_SDI_Z_STREAM_ERROR, 334
ER_IB_MSG_LOG_WRITER_ENTERED_EXTRA_MARGIN, 380	ER_IB_MSG_SDI_Z_UNKNOWN_ERROR, 334
ER_IB_MSG_LOG_WRITER_EXITED_EXTRA_MARGIN, 380	ER_IB_MSG_SKIP_HIDDEN_DIR, 351
ER_IB_MSG_LOG_WRITER_OUT_OF_SPACE, 320	ER_IB_MSG_STATS_SAMPLING_TOO_LARGE, 366
ER_IB_MSG_LOG_WRITER_WAITING_FOR_ARCHIVER, 320	ER_IB_MSG_THREAD_CONCURRENCY_CHANGED, 322
ER_IB_MSG_LOG_WRITER_WAIT_ON_CONSUMER, 385	ER_IB_MSG_TOO_LONG_PATH, 344
ER_IB_MSG_LOG_WRITER_WAIT_ON_NEW_LOG_FILES, 380	ER_IB_MSG_TRX_RECOVERY_ROLLBACK_COMPLETED, 317
ER_IB_MSG_LOG_WRITER_WRITE_FAILED, 380	ER_IB_MSG_TRX_RECOVERY_ROLLBACK_NOT_COMPLETED, 358
ER_IB_MSG_MADVISE_FAILED, 333	ER_IB_MSG_TRYING_TO_OPEN_FILE_FOR_LONG_TIME, 377
ER_IB_MSG_MADV_DONTDUMP_UNSUPPORTED, 333	ER_IB_MSG_UNDO_ALTERED_ACTIVE, 361
ER_IB_MSG_MASTER_KEY_ROTATED, 363	ER_IB_MSG_UNDO_ALTERED_INACTIVE, 361
ER_IB_MSG_MAX_UNDO_SPACES_REACHED, 333	ER_IB_MSG_UNDO_ENCRYPTION_INFO_LOADED, 374
	ER_IB_MSG_UNDO_MARKED_ACTIVE, 361
	ER_IB_MSG_UNDO_MARKED_EMPTY, 361
	ER_IB_MSG_UNDO_MARKED_FOR_TRUNCATE, 316



---

ER\_IB\_MSG\_UNDO\_TRUNCATE\_COMPLETE, 317  
ER\_IB\_MSG\_UNDO\_TRUNCATE\_DELAY\_BY\_CLONE, 361  
ER\_IB\_MSG\_UNDO\_TRUNCATE\_DELAY\_BY\_FAILURE, 316  
ER\_IB\_MSG\_UNDO\_TRUNCATE\_DELAY\_BY\_LOG\_CREATE, 316  
ER\_IB\_MSG\_UNDO\_TRUNCATE\_DELAY\_BY\_MDL, 362  
ER\_IB\_MSG\_UNDO\_TRUNCATE\_FAIL\_TO\_READ\_LOGFILE, 316  
ER\_IB\_MSG\_UNDO\_TRUNCATE\_START, 316  
ER\_IB\_MSG\_UNDO\_TRUNCATE\_TOO\_OFTEN, 357  
ER\_IB\_MSG\_UNEXPECTED\_FILE\_EXISTS, 265  
ER\_IB\_MSG\_UNPROTECTED\_LOCATION\_ALLOWED, 268  
ER\_IB\_MSG\_UPGRADE\_PARTITION\_FILE, 351  
ER\_IB\_MSG\_UPGRADE\_PARTITION\_FILE\_IMPORT, 352  
ER\_IB\_MSG\_USING\_UNDO\_SPACE, 333  
ER\_IB\_MSG\_WAIT\_FOR\_ENCRYPT\_THREAD, 329  
ER\_IB\_MSG\_WRONG\_TABLESPACE\_DIR, 334  
ER\_IB\_PARALLEL\_READER\_WORKER\_INFO, 387  
ER\_IB\_PRIMARY\_KEY\_IS\_INSTANT, 390  
ER\_IB\_RDBLWR\_BYTES\_INFO, 379  
ER\_IB\_RECV\_FIRST\_REC\_GROUP\_INVALID, 344  
ER\_IB\_RELOCK\_LATCH\_ORDER\_VIOLATION, 359  
ER\_IB\_RESURRECT\_ACQUIRE\_TABLE\_LOCK, 392  
ER\_IB\_RESURRECT\_IDENTIFY\_TABLE\_TO\_LOCK, 392  
ER\_IB\_RESURRECT\_RECORD\_COMPLETE, 392  
ER\_IB\_RESURRECT\_RECORD\_PROGRESS, 392  
ER\_IB\_RESURRECT\_TRX\_INSERT, 392  
ER\_IB\_RESURRECT\_TRX\_INSERT\_COMPLETE, 392  
ER\_IB\_RESURRECT\_TRX\_UPDATE, 392  
ER\_IB\_RESURRECT\_TRX\_UPDATE\_COMPLETE, 392  
ER\_IB\_SELECT\_COUNT\_STAR, 391  
ER\_IB\_SYNC\_READ\_FAILED, 399  
ER\_IB\_TABLESPACE\_PATH\_VALIDATION\_SKIPPED, 358  
ER\_IB\_TMP\_TABLESPACE\_CANNOT\_CREATE\_DIRECTORY, 359  
ER\_IB\_UNABLE\_TO\_EXPAND\_TEMPORARY\_TABLESPACE, 359  
ER\_IB\_WARN\_ACCESSING\_NONEXISTING\_SPACE, 264  
ER\_IB\_WARN\_MANY\_NON\_LRU\_FILES\_OPENED, 377  
ER\_IB\_WARN\_OPEN\_PARTITION\_FILE, 352  
ER\_IB\_WRN\_ENCRYPTION\_INFO\_SIZE\_MISMATCH, 374  
ER\_IB\_WRN\_FAILED\_TO\_ACQUIRE\_SERVICE, 368  
ER\_IB\_WRN\_FAST\_SHUTDOWN\_REDO\_DISABLED, 358  
ER\_IB\_WRN\_IGNORE\_REDO\_LOG\_CAPACITY, 390  
ER\_IB\_WRN\_OLD\_GEOMETRY\_TYPE, 368  
ER\_IB\_WRN\_PAGE\_ARCH\_FLUSH\_DATA, 356  
ER\_IB\_WRN\_REDO\_DISABLED, 358  
ER\_IB\_WRN\_REDO\_ENABLED, 358  
ER\_IB\_WRONG\_PAGEID\_AFTER\_SYNC\_READ, 399  
ER\_IB\_WRONG\_PAGE\_ID, 399  
ER\_IDENTIFIED\_BY\_UNSUPPORTED, 112  
ER\_IDENT\_CAUSES\_TOO\_LONG\_PATH, 55  
ER\_IDENT\_CAUSES\_TOO\_LONG\_PATH\_IN\_UPGRADE, 348  
ER\_IF\_NOT\_EXISTS\_UNSUPPORTED\_TRG\_EXISTS\_ON, 116  
ER\_IF\_NOT\_EXISTS\_UNSUPPORTED\_UDF\_NATIVE\_FCT, 116  
ER\_ILLEGAL\_GRANT\_FOR\_TABLE, 12  
ER\_ILLEGAL\_HA, 5  
ER\_ILLEGAL\_HA\_CREATE\_OPTION, 32  
ER\_ILLEGAL\_PRIVILEGE\_LEVEL, 80  
ER\_ILLEGAL\_REFERENCE, 18  
ER\_ILLEGAL\_USER\_VAR, 61  
ER\_ILLEGAL\_VALUE\_FOR\_TYPE, 25  
ER\_IMPLICIT\_COMPARISON\_FOR\_JSON, 107  
ER\_IMPOSSIBLE\_STRING\_CONVERSION, 107  
ER\_IMP\_INCOMPATIBLE\_CFG\_VERSION, 104  
ER\_IMP\_INCOMPATIBLE\_DD\_VERSION, 80  
ER\_IMP\_INCOMPATIBLE\_MYSQLD\_VERSION, 80  
ER\_IMP\_INCOMPATIBLE\_SDI\_VERSION, 80  
ER\_IMP\_NO\_FILES\_MATCHED, 80  
ER\_IMP\_SCHEMA\_DOES\_NOT\_EXIST, 80  
ER\_IMP\_TABLE\_ALREADY\_EXISTS, 80  
ER\_INCONSISTENT\_ERROR, 324  
ER\_INCONSISTENT\_PARTITION\_INFO\_ERROR, 32  
ER\_INCONSISTENT\_TYPE\_OF\_FUNCTIONS\_ERROR, 32  
ER\_INCORRECT\_CURRENT\_PASSWORD, 100  
ER\_INCORRECT\_GLOBAL\_LOCAL\_VAR, 18  
ER\_INCORRECT\_TYPE, 61  
ER\_INDEX\_COLUMN\_TOO\_LONG, 45  
ER\_INDEX\_CORRUPT, 45  
ER\_INDEX\_OTHER\_THAN\_PK, 118  
ER\_INDEX\_TYPE\_NOT\_SUPPORTED\_FOR\_SPATIAL\_INDEX, 38  
ER\_INFORMATION\_SCHEMA\_VERSION\_CHANGE, 395  
ER\_INIT\_BOOTSTRAP\_COMPLETE, 159  
ER\_INIT\_CANT\_OPEN\_BOOTSTRAP\_FILE, 159  
ER\_INIT\_CREATING\_DD, 159  
ER\_INIT\_DATADIR\_EXISTS\_AND\_NOT\_WRITABLE\_WRONG, 159

---

ER_INIT_DATADIR_EXISTS_AND_PATH_TOO_LONG, 159	ER_INNODB_ILLEGAL_COMPATIBLE_WITH_TABLESPACE, 110
ER_INIT_DATADIR_EXISTS_WONT_INITIALIZE, 159	ER_INNODB_INDEX_COLUMN_INFO_UNLIKE_MYSQLS, 179
ER_INIT_DATADIR_NOT_EMPTY_WONT_INITIALIZE, 159	ER_INNODB_INDEX_CORRUPT, 52
ER_INIT_FAILED_TO_GENERATE_ROOT_PASSWORD, 350	ER_INNODB_INSTANT_ADD_DROP_NOT_SUPPORTED_MAX, 120
ER_INIT_GENERATING_TEMP_PASSWORD_FOR_ROOT, 159	ER_INNODB_INSTANT_ADD_NOT_SUPPORTED_MAX_FIELD, 121
ER_INIT_ROOT_WITHOUT_PASSWORD, 158	ER_INNODB_INTERNAL_INDEX, 191
ER_INNODB_ACTIVE_INDEX_CHANGE_FAILED, 190	ER_INNODB_INVALID_AUTOEXTEND_SIZE_VALUE, 110
ER_INNODB_AUTOEXTEND_SIZE_OUT_OF_RANGE, 110	ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY, 178
ER_INNODB_CANNOT_CREATE_TABLE, 191	ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY_LOCATION, 335
ER_INNODB_CANT_BUILD_INDEX_XLATION_TABLE_FOR, 179	ER_INNODB_INVALID_LOG_GROUP_HOME_DIR, 178
ER_INNODB_CANT_FIND_INDEX_IN_INNODB_DD, 179	ER_INNODB_INVALID_MONITOR_COUNTER_NAME, 191
ER_INNODB_CLOSING_CONNECTION_ROLLS_BACK, 179	ER_INNODB_INVALID_PAGE_SIZE, 178
ER_INNODB_CLUSTERED_INDEX_PRIVATE, 179	ER_INNODB_IO_CAPACITY_EXCEEDS_MAX, 178
ER_INNODB_COMPRESSION_FAILURE, 111	ER_INNODB_IO_WRITE_ERROR_RETRYING, 363
ER_INNODB_DIFF_IN_REF_LEN, 190	ER_INNODB_IO_WRITE_FAILED, 363
ER_INNODB_DIRTY_WATER_MARK_NOT_LOW, 178	ER_INNODB_MANDATORY, 134
ER_INNODB_ERROR_LOGGER_FATAL_MSG, 192	ER_INNODB_MAX_ROW_VERSION, 116
ER_INNODB_ERROR_LOGGER_MSG, 192	ER_INNODB_MONITOR_DEFAULT_VALUE_NOT_DEFINED, 191
ER_INNODB_FAILED_TO_FIND_IDX, 190	ER_INNODB_MONITOR_IS_ENABLED, 191
ER_INNODB_FAILED_TO_FIND_IDX_FROM_DICT_CACHE, 190	ER_INNODB_NO_FT_TEMP_TABLE, 51
ER_INNODB_FAILED_TO_FIND_IDX_WITH_KEY_NO, 190	ER_INNODB_ONLINE_LOG_TOO_BIG, 51
ER_INNODB_FILES_SAME, 178	ER_INNODB_OUT_OF_RESOURCES, 353
ER_INNODB_FORCED_RECOVERY, 56	ER_INNODB_PK_NOT_IN_MYSQL, 179
ER_INNODB_FT_AUX_NOT_HEX_ID, 56	ER_INNODB_PK_ONLY_IN_MYSQL, 179
ER_INNODB_FT_LIMIT, 51	ER_INNODB_READ_ONLY, 56
ER_INNODB_FT_WRONG_DOCID_COLUMN, 51	ER_INNODB_REDO_ARCHIVING_ENABLED, 107
ER_INNODB_FT_WRONG_DOCID_INDEX, 51	ER_INNODB_REDO_DISABLED, 107
ER_INNODB_IDX_CNT_FEWER_THAN_DEFINED_IN_MYSQL, 191	ER_INNODB_REDO_LOG_ARCHIVE_ACTIVE, 97
ER_INNODB_IDX_CNT_MORE_THAN_DEFINED_IN_MYSQL, 191	ER_INNODB_REDO_LOG_ARCHIVE_DIRS_INVALID, 96
ER_INNODB_IDX_COLUMN_CNT_DIFF, 191	ER_INNODB_REDO_LOG_ARCHIVE_DIR_CLASH, 97
ER_INNODB_ILLEGAL_COLON_IN_POOL, 178	ER_INNODB_REDO_LOG_ARCHIVE_DIR_EMPTY, 97
ER_INNODB_IMPORT_DROP_COL_METADATA_MISMATCH, 122	ER_INNODB_REDO_LOG_ARCHIVE_DIR_PERMISSIONS, 97
ER_INNODB_IMPORT_ENUM_NULL_TERMINATOR_MISSING, 122	ER_INNODB_REDO_LOG_ARCHIVE_FAILED, 97
ER_INNODB_IMPORT_ERROR, 52	ER_INNODB_REDO_LOG_ARCHIVE_FILE_CREATE, 97
ER_INNODB_IMPORT_WRONG_DROPPED_ENUM_LENGTH, 122	ER_INNODB_REDO_LOG_ARCHIVE_INACTIVE, 97
ER_INNODB_IMPORT_WRONG_NUMBER_OF_INDEXES, 122	ER_INNODB_REDO_LOG_ARCHIVE_LABEL_NOT_FOUND, 96
ER_INNODB_IMPORT_WRONG_NUMBER_OF_INDEXES, 122	ER_INNODB_REDO_LOG_ARCHIVE_NO_SUCH_DIR, 96
	ER_INNODB_REDO_LOG_ARCHIVE_SESSION, 97
	ER_INNODB_REDO_LOG_ARCHIVE_ZERO, 97

---

ER\_INNODB\_REDO\_LOG\_ARCHIVE\_START\_SUBDIR\_PATH, 96  
ER\_INNODB\_REDO\_LOG\_ARCHIVE\_START\_TIMEOUT, 96  
ER\_INNODB\_TRX\_XLATION\_TABLE\_OOM, 179  
ER\_INNODB\_UNABLE\_TO\_ACQUIRE\_DD\_OBJECT, 356  
ER\_INNODB\_UNDO\_LOG\_FULL, 58  
ER\_INNODB\_UNKNOWN\_COLLATION, 178  
ER\_INNODB\_UNREGISTERED\_TRX\_ACTIVE, 178  
ER\_INNODB\_USE\_MONITOR\_GROUP\_NAME, 191  
ER\_INSECURE\_CHANGE\_SOURCE, 48  
ER\_INSECURE\_PLAIN\_TEXT, 48  
ER\_INSERT\_INFO, 9  
ER\_INSIDE\_TRANSACTION\_PREVENTS\_SWITCH\_BINLOG\_FORMAT, 43  
ER\_INSIDE\_TRANSACTION\_PREVENTS\_SWITCH\_BINLOG\_FORMAT, 43  
ER\_INSIDE\_TRANSACTION\_PREVENTS\_SWITCH\_SQL\_LOG\_BIN, 44  
ER\_INSTALL\_COMPONENT\_SET\_NULL\_VALUE, 121  
ER\_INSTALL\_COMPONENT\_SET\_UNUSED\_VALUE, 121  
ER\_INSTALL\_PLUGIN\_CONFLICT\_CLIENT, 112  
ER\_INSTALL\_PLUGIN\_CONFLICT\_LOG, 371  
ER\_INTERNAL\_ERROR, 52  
ER\_INTERSECT\_ALL\_MAX\_DUPLICATES\_EXCEEDED, 118  
ER\_INVALID\_ADMIN\_ADDRESS, 336  
ER\_INVALID\_ARGUMENT\_FOR\_LOGARITHM, 58  
ER\_INVALID\_ASSIGNMENT\_TARGET, 112  
ER\_INVALID\_AUTHENTICATION\_POLICY, 374  
ER\_INVALID\_BITWISE\_AGGREGATE\_OPERANDS\_SIZE, 73  
ER\_INVALID\_BITWISE\_OPERANDS\_SIZE, 73  
ER\_INVALID\_CAST, 108  
ER\_INVALID\_CAST\_POLYGON\_RING\_DIRECTION, 111  
ER\_INVALID\_CAST\_TO\_GEOMETRY, 111  
ER\_INVALID\_CAST\_TO\_JSON, 68  
ER\_INVALID\_CHARACTER\_STRING, 21  
ER\_INVALID\_CHARSET\_AND\_DEFAULT\_IS\_MB, 151  
ER\_INVALID\_COLLATION\_FOR\_CHARSET, 182  
ER\_INVALID\_DD\_OBJECT, 73  
ER\_INVALID\_DD\_OBJECT\_ID, 73  
ER\_INVALID\_DD\_OBJECT\_NAME, 73  
ER\_INVALID\_DEFAULT, 7  
ER\_INVALID\_DEFAULT\_UTF8MB4\_COLLATION, 87  
ER\_INVALID\_ENCRYPTION\_OPTION, 70  
ER\_INVALID\_ENCRYPTION\_REQUEST, 95  
ER\_INVALID\_ERROR\_LOG\_NAME, 141  
ER\_INVALID\_FIELD\_SIZE, 58  
ER\_INVALID\_GEOJSON\_CRS\_NOT\_TOP\_LEVEL, 84  
ER\_INVALID\_GEOJSON\_MISSING\_MEMBER, 62  
ER\_INVALID\_GEOJSON\_UNSPECIFIED, 62  
ER\_INVALID\_GEOJSON\_WRONG\_TYPE, 62  
ER\_INVALID\_GROUP\_FUNC\_USE, 10  
ER\_INVALID\_INFO\_IN\_FRM, 152  
ER\_INVALID\_INSTRUMENT, 134  
ER\_INVALID\_JSON\_ATTRIBUTE, 107  
ER\_INVALID\_JSON\_BINARY\_DATA, 67  
ER\_INVALID\_JSON\_CHARSET, 68  
ER\_INVALID\_JSON\_CHARSET\_IN\_FUNCTION, 68  
ER\_INVALID\_JSON\_DATA, 62  
ER\_INVALID\_JSON\_PATH, 68  
ER\_INVALID\_JSON\_PATH\_ARRAY\_CELL, 69  
ER\_INVALID\_JSON\_PATH\_CHARSET, 68  
ER\_INVALID\_JSON\_PATH\_WILDCARD, 68  
ER\_INVALID\_JSON\_TEXT, 67  
ER\_INVALID\_JSON\_TEXT\_IN\_PARAM, 67  
ER\_INVALID\_JSON\_TYPE, 97  
ER\_INVALID\_JSON\_VALUE\_FOR\_CAST, 68  
ER\_INVALID\_JSON\_VALUE\_FOR\_FUNC\_INDEX, 100  
ER\_INVALID\_MFA\_OPERATIONS\_FOR\_PASSWORDLESS, 113  
ER\_INVALID\_MFA\_PLUGIN\_SPECIFIED, 112  
ER\_INVALID\_MULTIPLE\_CLAUSES, 96  
ER\_INVALID\_NAMED\_PIPE\_FULL\_ACCESS\_GROUP, 341  
ER\_INVALID\_NO\_OF\_ARGS, 79  
ER\_INVALID\_ON\_UPDATE, 21  
ER\_INVALID\_OPTION\_CHARACTERS, 76  
ER\_INVALID\_OPTION\_END\_CHARACTER, 76  
ER\_INVALID\_OPTION\_KEY, 76  
ER\_INVALID\_OPTION\_KEY\_VALUE\_PAIR, 76  
ER\_INVALID\_OPTION\_START\_CHARACTER, 76  
ER\_INVALID\_OPTION\_VALUE, 76  
ER\_INVALID\_OR\_OLD\_TABLE\_OR\_DB\_NAME, 160  
ER\_INVALID\_PARAMETER\_USE, 108  
ER\_INVALID\_PLUGIN\_FOR\_REGISTRATION, 113  
ER\_INVALID\_PROPERTY\_KEY, 338  
ER\_INVALID\_RPL\_WILD\_TABLE\_FILTER\_PATTERN, 62  
ER\_INVALID\_SERVER\_DOWNGRADE\_NOT\_PATCH, 395  
ER\_INVALID\_SERVER\_UPGRADE\_NOT\_LTS, 395  
ER\_INVALID\_THREAD\_ID, 83  
ER\_INVALID\_THREAD\_PRIORITY, 83  
ER\_INVALID\_TIME\_ZONE\_INTERVAL, 108  
ER\_INVALID\_TLS\_VERSION, 377  
ER\_INVALID\_TYPE\_FOR\_JSON, 68  
ER\_INVALID\_USER\_ATTRIBUTE\_JSON, 107  
ER\_INVALID\_USER\_FOR\_REGISTRATION, 113  
ER\_INVALID\_USE\_OF\_FORCE\_OPTION, 83  
ER\_INVALID\_USE\_OF\_NULL, 12  
ER\_INVALID\_VALUE\_FOR\_ENFORCE\_GTID\_CONSISTENCY, 130  
ER\_INVALID\_VALUE\_OF\_BIND\_ADDRESSES, 330

---

ER_INVALID_VCPU_ID, 82	ER_KEYRING_AWS_FAILED_TO_OPEN_CONF_FILE, 216
ER_INVALID_VCPU_RANGE, 83	ER_KEYRING_AWS_FAILED_TO_RESTORE_FROM_BACKUP, 217
ER_INVALID_XPLUGIN_SOCKET_SAME_AS_SERVER, 356	ER_KEYRING_AWS_FAILED_TO_RE_ENCRYPT_KEY, 218
ER_INVALID_YEAR_COLUMN_LENGTH, 52	ER_KEYRING_AWS_FAILED_TO_ROTATE_CMK, 218
ER_IO_ERR_LOG_INDEX_READ, 26	ER_KEYRING_AWS_FAILED_TO_SET_CMK_ID, 216
ER_IO_READ_ERROR, 52	ER_KEYRING_AWS_FAILED_TO_SET_REGION, 216
ER_IO_WRITE_ERROR, 52	ER_KEYRING_AWS_FOUND_MALFORMED_BACKUP_FILE, 217
ER_IPSOCK_ERROR, 8	ER_KEYRING_AWS_INCORRECT_FILE, 217
ER_IS_QUERY_INVALID_CLAUSE, 76	ER_KEYRING_AWS_INCORRECT_PROXY, 349
ER_I_S_SKIPPED_TABLESPACE, 82	ER_KEYRING_AWS_INCORRECT_REGION, 218
ER_JSON_BAD_ONE_OR_ALL_ARG, 68	ER_KEYRING_AWS_INIT_FAILURE, 217
ER_JSON_DOCUMENT_NULL_KEY, 69	ER_KEYRING_AWS_INVALID_CONF_FILE_PATH, 216
ER_JSON_DOCUMENT_TOO_DEEP, 68	ER_KEYRING_AWS_INVALID_DATA_FILE_PATH, 216
ER_JSON_KEY_TOO_BIG, 68	ER_KEYRING_AWS_INVALID_KEY_LENGTH_FOR_CIPHER, 217
ER_JSON_PARSE_ERROR, 142	ER_KEYRING_AWS_UDF_AWS_KMS_ERROR, 71
ER_JSON_SCHEMA_VALIDATION_ERROR_WITH_DETAILS, 103	ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_EMPTY_KEY, 211
ER_JSON_USED_AS_KEY, 68	ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_INVALID_KEY, 211
ER_JSON_VACUOUS_PATH, 68	ER_KEYRING_COMPONENT_EXCEPTION, 366
ER_JSON_VALUE_OUT_OF_RANGE_FOR_FUNC_INDEX, 101	ER_KEYRING_COMPONENT_MEMORY_ALLOCATION_ERROR, 367
ER_JSON_VALUE_TOO_BIG, 68	ER_KEYRING_COMPONENT_NOT_INITIALIZED, 367
ER_JT_MAX_NESTED_PATH, 84	ER_KEYRING_COMPONENT_CONF_FILE, 367
ER_JT_VALUE_OUT_OF_RANGE, 84	ER_KEYRING_ENCRYPTED_FILE_DECRYPTION_FAILED, 215
ER_KERBEROS_CREATE_USER, 112	ER_KEYRING_DATA_FILE, 215
ER_KEYCACHE_OOM, 136	ER_KEYRING_ENCRYPTED_FILE_ENCRYPTION_FAILED, 215
ER_KEYRING_ACCESS_DENIED_ERROR, 72	ER_KEYRING_DIR, 215
ER_KEYRING_AWS_CMK_ID_NOT_SET, 217	ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_CREATE_KEYRING, 215
ER_KEYRING_AWS_FAILED_TO_ACCESS_DATA_FILE, 217	ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_FLUSH_KEYRING, 215
ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_FROM_CONF_FILE, 216	ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_RESTORE_KEYRING, 215
ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_ID_FROM_CONF_FILE, 216	ER_KEYRING_ENCRYPTED_FILE_FOUND_MALFORMED_BACKUP_FILE, 215
ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING, 217	ER_KEYRING_ENCRYPTED_FILE_GEN_KEY_FAILED_DUE_TO_INTERNAL_ERROR, 216
ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING, 216	ER_KEYRING_ENCRYPTED_FILE_INCORRECT_KEYRING_FILE, 215
ER_KEYRING_AWS_FAILED_TO_CONNECT_KMS, 218	ER_KEYRING_ENCRYPTED_FILE_INIT_FAILED_DUE_TO_INTERNAL_ERROR, 216
ER_KEYRING_AWS_FAILED_TO_DECRYPT_KEY, 218	ER_KEYRING_ENCRYPTED_FILE_INIT_FAILURE, 216
ER_KEYRING_AWS_FAILED_TO_ENCRYPT_KEY, 218	ER_KEYRING_ENCRYPTED_FILE_INVALID_KEYRING_DIR, 215
ER_KEYRING_AWS_FAILED_TO_FLUSH_KEYRING_TO_FILE, 218	ER_KEYRING_ENCRYPTED_FILE_INTERNAL_ERROR, 215
ER_KEYRING_AWS_FAILED_TO_GENERATE_KEY_DUE_TO_INTERNAL_ERROR, 217	ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_INVALID, 215
ER_KEYRING_AWS_FAILED_TO_GENERATE_NEW_KEYRING, 218	
ER_KEYRING_AWS_FAILED_TO_GET_KMS_CREDENTIALS, 217	
ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_INTERNAL_ERROR, 217	
ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_PLUGIN, 217	

ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_TOO_LONG, 215	ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY_DUE_TO_ERROR, 213
ER_KEYRING_FAILED_TO_CREATE_KEYRING_DIR, 211	ER_KEYRING_OKV_FAILED_TO_INIT_CLIENT, 213
ER_KEYRING_FAILED_TO_FLUSH_KEYRING_TO_FILE, 212	ER_KEYRING_OKV_FAILED_TO_INIT_SSL_LAYER, 213
ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING, 212	ER_KEYRING_OKV_FAILED_TO_LOAD_KEY_UID, 213
ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING_BACKUP, 212	ER_KEYRING_OKV_FAILED_TO_LOAD_SSL_TRUST_STORE, 214
ER_KEYRING_FAILED_TO_GENERATE_KEY, 211	ER_KEYRING_OKV_FAILED_TO_PARSE_CONF_FILE, 213
ER_KEYRING_FAILED_TO_GET_FILE_STAT, 212	ER_KEYRING_OKV_FAILED_TO_REMOVE_KEY, 214
ER_KEYRING_FAILED_TO_LOAD_KEYRING_CONTENT, 212	ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY, 214
ER_KEYRING_FAILED_TO_REMOVE_FILE, 212	ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY_SIGNATURE, 214
ER_KEYRING_FAILED_TO_REMOVE_KEY_DUE_TO_EMPTY_ID, 212	ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY_SIGNATURE_FILE, 214
ER_KEYRING_FAILED_TO_RESTORE_FROM_BACKUP_FILE, 212	ER_KEYRING_OKV_FAILED_TO_SET_CERTIFICATE_FILE, 214
ER_KEYRING_FAILED_TO_SET_KEYRING_FILE_DATA, 212	ER_KEYRING_OKV_FAILED_TO_SET_KEY_FILE, 214
ER_KEYRING_FAILED_TO_TRUNCATE_FILE, 212	ER_KEYRING_OKV_FAILED_TO_STORE_KEY, 214
ER_KEYRING_FILE_INIT_FAILED, 211	ER_KEYRING_OKV_FAILED_TO_STORE_OR_GENERATE_KEY, 214
ER_KEYRING_FILE_IO_ERROR, 212	ER_KEYRING_OKV_INCORRECT_KEY_VAULT_CONFIGURATION, 213
ER_KEYRING_FOUND_MALFORMED_BACKUP_FILE, 211	ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INCORRECT_CONFIGURATION, 213
ER_KEYRING_INCORRECT_FILE, 211	ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INTERNAL_ERROR, 213
ER_KEYRING_INTERNAL_EXCEPTION_FAILED_FILE_INIT, 211	ER_KEYRING_OKV_INVALID_KEY_LENGTH_FOR_CIPHER, 213
ER_KEYRING_INVALID_KEY_LENGTH, 211	ER_KEYRING_OKV_INVALID_KEY_TYPE, 213
ER_KEYRING_INVALID_KEY_TYPE, 211	ER_KEYRING_OKV_KEY_MISMATCH, 215
ER_KEYRING_KEY_FETCH_FAILED_DUE_TO_EMPTY_ID, 212	ER_KEYRING_OKV_STANDBY_SERVER_COUNT_EXCEEDED, 377
ER_KEYRING_LOGGER_ERROR_MSG, 201	ER_KEYRING_OPERATION_FAILED_DUE_TO_INTERNAL_ERROR, 211
ER_KEYRING_MIGRATE_FAILED, 323	ER_KEYRING_UDF_KEYRING_SERVICE_ERROR, 71
ER_KEYRING_MIGRATION_EXTRA_OPTIONS, 247	ER_KEYRING_UNKNOWN_ERROR, 212
ER_KEYRING_MIGRATION_FAILED, 193	ER_KEY_COLUMN_DOES_NOT_EXIST, 8
ER_KEYRING_MIGRATION_FAILURE, 71	ER_KEY_DOES_NOT_EXIST, 14
ER_KEYRING_MIGRATION_STATUS, 72	ER_KEY_NOT_FOUND, 5
ER_KEYRING_MIGRATION_SUCCESSFUL, 193	ER_KEY_PART_0, 26
ER_KEYRING_OCI_HTTP_REQUEST, 386	ER_KEY_REF_DO_NOT_MATCH_TABLE_REF, 18
ER_KEYRING_OCI_INVALID_JSON, 386	ER_KILLED_THREADS_OF_PLUGIN, 160
ER_KEYRING_OCI_PARSE_JSON, 386	ER_KILLING_THREAD, 159
ER_KEYRING_OKV_CONNECTION_TO_SERVER_FAILED, 214	ER_KILL_DENIED_ERROR, 9
ER_KEYRING_OKV_FAILED_TO_ACTIVATE_KEYS, 214	ER_LANGUAGE_COMPONENT, 121
ER_KEYRING_OKV_FAILED_TO_ADD_ATTRIBUTE, 214	ER_LANGUAGE_COMPONENT_CANNOT_UNINSTALL, 121
ER_KEYRING_OKV_FAILED_TO_FETCH_KEY, 214	ER_LANGUAGE_COMPONENT_ERROR, 396
ER_KEYRING_OKV_FAILED_TO_FIND_SERVER_ENTRY, 213	ER_LANGUAGE_COMPONENT_INFO, 396
ER_KEYRING_OKV_FAILED_TO_FIND_STANDBY_SERVER_ENTRY, 213	ER_LANGUAGE_COMPONENT_NOT_AVAILABLE, 121
ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY, 214	

---

ER_LANGUAGE_COMPONENT_UNSUPPORTED_LANGUAGE,	ER_LDAP_AUTH_FAILED_TO_WRITE_PACKET,
121	242
ER_LANGUAGE_COMPONENT_WARNING, 396	ER_LDAP_AUTH_FREEING_CONNECTION, 244
ER_LATITUDE_OUT_OF_RANGE, 80	ER_LDAP_AUTH_GETTING_CONNECTION_FROM_POOL,
ER_LCTN_CHANGED, 193	244
ER_LCTN_NOT_FOUND, 323	ER_LDAP_AUTH_GRP_DN_PARSING_FAILED,
ER_LDAP_AUTH_CERTIFICATE_NAME, 243	339
ER_LDAP_AUTH_COMMUNICATION_HOST_INFO,	ER_LDAP_AUTH_GRP_INCORRECT_ATTRIBUTE,
245	339
ER_LDAP_AUTH_CONNECTION_CREATOR_ENTER,	ER_LDAP_AUTH_GRP_INFO_FOUND_IN_MANY_OBJECTS,
244	339
ER_LDAP_AUTH_CONNECTION_GET_LDAP_INFO_NULL,	ER_LDAP_AUTH_GRP_IS_FULL_DN, 242
245	ER_LDAP_AUTH_GRP_NULL_ATTRIBUTE_VALUE,
ER_LDAP_AUTH_CONNECTION_POOL_INIT_FAILED,	339
244	ER_LDAP_AUTH_GRP_OBJECT_HAS_USER_INFO,
ER_LDAP_AUTH_CONNECTION_POOL_REINIT_ENTER,	339
246	ER_LDAP_AUTH_GRP_SEARCH_NOT_SPECIAL_HDL,
ER_LDAP_AUTH_CONNECTION_PUSHED_TO_POOL,	339
244	ER_LDAP_AUTH_GRP_SEARCH_SPECIAL_HDL,
ER_LDAP_AUTH_CONN_POOL_DEINITIALIZING,	242
242	ER_LDAP_AUTH_GRP_USER_OBJECT_HAS_GROUP_INFO,
ER_LDAP_AUTH_CONN_POOL_INITIALIZING,	339
242	ER_LDAP_AUTH_INFO_FOR_USER, 242
ER_LDAP_AUTH_CONN_POOL_NOT_CREATED,	ER_LDAP_AUTH_INIT_FAILED, 245
242	ER_LDAP_AUTH_LDAPS, 339
ER_LDAP_AUTH_CREATE_CONNECTION_KEY,	ER_LDAP_AUTH_LDAP_INFO_NULL, 244
245	ER_LDAP_AUTH_MAX_ALLOWED_CONNECTION_LIMIT_HIT,
ER_LDAP_AUTH_CREATING_LDAP_CONNECTION,	244
244	ER_LDAP_AUTH_MAX_POOL_SIZE_SET_FAILED,
ER_LDAP_AUTH_DEINIT_FAILED, 241	244
ER_LDAP_AUTH_DELETING_CONNECTION_KEY,	ER_LDAP_AUTH_METHOD_TO_CLIENT, 245
245	ER_LDAP_AUTH_OBJECT_CREATE_TIMESTAMP,
ER_LDAP_AUTH_DISTINGUISHED_NAME, 245	243
ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_CONNECTION,	ER_LDAP_AUTH_OR_GROUP_RETRIEVAL_FAILED,
246	245
ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT,	ER_LDAP_AUTH_PLUGIN_FAILED_TO_READ_PACKET,
241	244
ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT_CREATOR,	ER_LDAP_AUTH_POOLED_CONNECTION_KEY,
241	245
ER_LDAP_AUTH_FAILED_TO_CREATE_OR_GET_CONNECTION,	ER_LDAP_AUTH_POOL_DISABLE_MAX_SIZE_ZERO,
241	241
ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_NOT_READY_POOL,	ER_LDAP_AUTH_POOL_GET_FAILED_TO_CREATE_CONNECTION,
243	246
ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_POOL_IN_RECONSTRUCT_BOOTSTRAP,	ER_LDAP_AUTH_POOL_REINITIALIZING, 242
243	ER_LDAP_AUTH_RETURNING_CONNECTION_TO_POOL,
ER_LDAP_AUTH_FAILED_TO_ESTABLISH_TLS_CONNECTION,	241
246	ER_LDAP_AUTH_SASL_BIND_SUCCESS_INFO,
ER_LDAP_AUTH_FAILED_TO_GET_CONNECTION_AS_PLUGIN,	245
243	ER_LDAP_AUTH_SASL_PROCESS_SASL, 245
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_DIRECTORY,	ER_LDAP_AUTH_SASL_REQUEST_FROM_CLIENT,
243	245
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_DIRECTORY,	ER_LDAP_AUTH_SEARCHED_USER_GRP_NAME,
243	243
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_DIRECTORY,	ER_LDAP_AUTH_SEARCH_USER_GROUP_ATTR_NOT_FOUND,
243	244
ER_LDAP_AUTH_FAILED_TO_POOL_DEINIT, 243	ER_LDAP_AUTH_SETTING_USERNAME, 242
ER_LDAP_AUTH_FAILED_TO_SEARCH_DN, 246	ER_LDAP_AUTH_SKIPPING_USER_GROUP_SEARCH,
	241

---

---

ER\_LDAP\_AUTH\_STARTED\_FOR\_USER, 245  
 ER\_LDAP\_AUTH\_STARTING\_TLS, 244  
 ER\_LDAP\_AUTH\_TLS\_CONF, 241  
 ER\_LDAP\_AUTH\_TLS\_CONNECTION, 242  
 ER\_LDAP\_AUTH\_USER\_AUTH\_DATA, 242  
 ER\_LDAP\_AUTH\_USER\_BIND\_FAILED, 246  
 ER\_LDAP\_AUTH\_USER\_FOUND\_IN\_MANY\_GRP,  
 243  
 ER\_LDAP\_AUTH\_USER\_GROUP\_SEARCH\_FAILED,  
 245  
 ER\_LDAP\_AUTH\_USER\_GROUP\_SEARCH\_INFO,  
 242  
 ER\_LDAP\_AUTH\_USER\_GROUP\_SEARCH\_ROOT\_BIND,  
 332  
 ER\_LDAP\_AUTH\_USER\_HAS\_MULTIPLE\_GRP\_NAMES,  
 243  
 ER\_LDAP\_AUTH\_USER\_NOT\_FOUND\_IN\_ANY\_GRP,  
 242  
 ER\_LDAP\_AUTH\_ZERO\_MAX\_POOL\_SIZE\_UNCHANGING,  
 242  
 ER\_LDAP\_EMPTY\_USERDN\_PASSWORD, 346  
 ER\_LDAP\_MAPPING\_CHECK\_DELIMI\_QUOTE,  
 340  
 ER\_LDAP\_MAPPING\_EMPTY\_MAPPING, 340  
 ER\_LDAP\_MAPPING\_GETTING\_NEXT\_MAPPING,  
 340  
 ER\_LDAP\_MAPPING\_GET\_USER\_PROXY, 340  
 ER\_LDAP\_MAPPING\_INFO, 340  
 ER\_LDAP\_MAPPING\_IS\_QUOTE, 341  
 ER\_LDAP\_MAPPING\_NON\_DESIRED\_STATE,  
 341  
 ER\_LDAP\_MAPPING\_NO\_SEPEARATOR\_END\_OF\_GROUP,  
 340  
 ER\_LDAP\_MAPPING\_PARSING\_CURRENT\_STATE,  
 340  
 ER\_LDAP\_MAPPING\_PARSING\_ERROR, 341  
 ER\_LDAP\_MAPPING\_PARSING\_MAPPING\_INFO,  
 341  
 ER\_LDAP\_MAPPING\_PROCESS\_DELIMITER, 340  
 ER\_LDAP\_MAPPING\_PROCESS\_DELIMITER\_COMMA\_NOT\_FOUND,  
 340  
 ER\_LDAP\_MAPPING\_PROCESS\_DELIMITER\_EQUAL\_NOT\_FOUND,  
 340  
 ER\_LDAP\_MAPPING\_PROCESS\_DELIMITER\_TRY\_COMMA,  
 340  
 ER\_LDAP\_MAPPING\_PROCESS\_MAPPING, 340  
 ER\_LDAP\_MAPPING\_TRIMMING\_SPACES, 341  
 ER\_LDAP\_MAPPING\_USER\_DONT\_BELONG\_GROUP,  
 340  
 ER\_LH\_AVRO\_CANNOT\_PARSE\_HEADER, 128  
 ER\_LH\_AVRO\_DECODING\_ERR, 127  
 ER\_LH\_AVRO\_ENUM\_CANNOT\_CONVERT\_CHARSET,  
 126  
 ER\_LH\_AVRO\_ENUM\_MISMATCH, 126  
 ER\_LH\_AVRO\_FILE\_DATA\_CORRUPT, 126  
 ER\_LH\_AVRO\_FILE\_ENDS\_UNEXPECTEDLY, 126  
 ER\_LH\_AVRO\_HEADER\_METADATA\_ERR, 127  
 ER\_LH\_AVRO\_HEADER\_MISMATCH, 126  
 ER\_LH\_AVRO\_HEADER\_NO\_SCHEMA, 127  
 ER\_LH\_AVRO\_INVALID\_BLOCK\_RECORD\_COUNT,  
 127  
 ER\_LH\_AVRO\_INVALID\_BLOCK\_SIZE, 127  
 ER\_LH\_AVRO\_INVALID\_NAME\_IN\_SCHEMA, 127  
 ER\_LH\_AVRO\_INVALID\_UNION, 127  
 ER\_LH\_AVRO\_NO\_CODEC\_IN\_HEADER, 127  
 ER\_LH\_AVRO\_SCHEMA\_DEPTH\_EXCEEDS\_MAX,  
 126  
 ER\_LH\_AVRO\_TYPE\_CANNOT\_CONVERT, 126  
 ER\_LH\_AWS\_AUTH\_ERR, 125  
 ER\_LH\_BAD\_VALUE, 124  
 ER\_LH\_CANNOT\_CONVERT\_STRING, 125  
 ER\_LH\_CHARSET\_UNSUPPORTED, 126  
 ER\_LH\_COLUMN\_MAX\_ERR, 126  
 ER\_LH\_COLUMN\_MISMATCH\_ERR, 126  
 ER\_LH\_COL\_IS\_EMPTY, 124  
 ER\_LH\_COL\_IS\_EMPTY\_WARN, 124  
 ER\_LH\_COL\_NOT\_NULLABLE, 124  
 ER\_LH\_CSV\_PARSING\_ERR, 125  
 ER\_LH\_DATETIME\_FORMAT, 125  
 ER\_LH\_DECIMAL\_OOM\_ERR, 125  
 ER\_LH\_DECIMAL\_PRECISION\_EXCEEDS\_SCHEMA,  
 125  
 ER\_LH\_DECIMAL\_UNKNOWN\_ERR, 125  
 ER\_LH\_DUPLICATE\_FILE, 126  
 ER\_LH\_EMPTY\_FILE, 126  
 ER\_LH\_EXCEEDS\_MAX, 125  
 ER\_LH\_EXCEEDS\_MIN, 125  
 ER\_LH\_FORMAT\_HEADER\_NO\_MAGIC\_BYTES,  
 127  
 ER\_LH\_INFER\_FILE\_HAS\_NO\_DATA, 128  
 ER\_LH\_INFER\_NO\_DATA, 128  
 ER\_LH\_INFER\_NO\_FILES, 128  
 ER\_LH\_INFER\_SCHEMA\_MISMATCH, 128  
 ER\_LH\_INFER\_WARN\_GOT\_EXCEPTION, 128  
 ER\_LH\_NO\_FILES\_FOUND, 126  
 ER\_LH\_OOM, 128  
 ER\_LH\_OUT\_OF\_RANGE, 125  
 ER\_LH\_PARQUET\_CANNOT\_LOCATE\_OFFSET,  
 127  
 ER\_LH\_PARQUET\_CANNOT\_LOCATE\_SCHEMA,  
 127  
 ER\_LH\_PARQUET\_CANNOT\_READ\_HEADER,  
 128  
 ER\_LH\_PARQUET\_CANT\_OPEN\_FILE, 128  
 ER\_LH\_PARQUET\_DECIMAL\_CONVERSION\_ERR,  
 126  
 ER\_LH\_PARQUET\_NON\_UTF8\_FILE\_ENC, 127  
 ER\_LH\_PARQUET\_ROW\_GROUP\_SIZE\_EXCEEDS\_MAX,  
 127  
 ER\_LH\_PARQUET\_SCHEMA\_MISMATCH, 127  
 ER\_LH\_PARQUET\_TYPE\_CANNOT\_CONVERT,  
 127  
 ER\_LH\_REAL\_IS\_NAN, 125  
 ER\_LH\_RESORCE\_PRINCIPAL\_BUCKET\_ERR,  
 126  
 ER\_LH\_RESORCE\_PRINCIPAL\_ERR, 125

---

---

ER\_LH\_STRING\_TOO\_LONG, 126  
 ER\_LH\_WARN\_COL\_MISSING\_NOT\_NULLABLE, 124  
 ER\_LH\_WARN\_DECIMAL\_ROUNDING, 125  
 ER\_LH\_WARN\_EXCEEDS\_MAX\_TRUNCATING, 125  
 ER\_LH\_WARN\_EXCEEDS\_MIN\_TRUNCATING, 125  
 ER\_LH\_WARN\_INFER\_SKIPPED\_FILES, 128  
 ER\_LH\_WARN\_INFER\_SKIPPED\_LINES, 128  
 ER\_LH\_WARN\_INFER\_USE\_DEFAULT\_COL\_NAMES, 128  
 ER\_LH\_WARN\_TRUNCATED, 125  
 ER\_LIMITED\_PART\_RANGE, 34  
 ER\_LOAD\_BULK\_DATA\_FAILED, 120  
 ER\_LOAD\_BULK\_DATA\_UNSORTED, 119  
 ER\_LOAD\_BULK\_DATA\_WARN\_NULL\_TO\_NOTNULL, 120  
 ER\_LOAD\_BULK\_DATA\_WARN\_NULL\_TO\_NOTNULL\_LOG, 389  
 ER\_LOAD\_BULK\_DATA\_WRONG\_VALUE\_FOR\_FIELD, 120  
 ER\_LOAD\_BULK\_DATA\_WRONG\_VALUE\_FOR\_FIELD\_LOG, 389  
 ER\_LOAD\_DATA\_INFILE\_FAILED\_IN\_UNEXPECTED\_WAY, 143  
 ER\_LOAD\_FROM\_FIXED\_SIZE\_ROWS\_TO\_VAR, 27  
 ER\_LOAD\_INFO, 8  
 ER\_LOCAL\_VARIABLE, 17  
 ER\_LOCKING\_SERVICE\_DEADLOCK, 67  
 ER\_LOCKING\_SERVICE\_TIMEOUT, 67  
 ER\_LOCKING\_SERVICE\_WRONG\_NAME, 67  
 ER\_LOCK\_ABORTED, 43  
 ER\_LOCK\_DEADLOCK, 16  
 ER\_LOCK\_NOWAIT, 77  
 ER\_LOCK\_ORDER\_DEPENDENCIES\_SYNTAX, 347  
 ER\_LOCK\_ORDER\_FAILED\_READ\_FILE, 347  
 ER\_LOCK\_ORDER\_FAILED\_WRITE\_FILE, 346  
 ER\_LOCK\_ORDER\_INIT\_FAILED, 345  
 ER\_LOCK\_ORDER\_MESSAGE, 347  
 ER\_LOCK\_ORDER\_SCANNER\_SYNTAX, 347  
 ER\_LOCK\_OR\_ACTIVE\_TRANSACTION, 15  
 ER\_LOCK\_REFUSED\_BY\_ENGINE, 70  
 ER\_LOCK\_TABLE\_FULL, 16  
 ER\_LOCK\_WAIT\_TIMEOUT, 16  
 ER\_LOG\_BIN\_BETTER\_WITH\_NAME, 139  
 ER\_LOG\_CANNOT\_PURGE\_BINLOG\_WITH\_BACKUP\_LOG, 395  
 ER\_LOG\_CANNOT\_WRITE, 129  
 ER\_LOG\_CANNOT\_WRITE\_EXTENDED, 349  
 ER\_LOG\_COMPONENT\_CANNOT\_INIT, 363  
 ER\_LOG\_COMPONENT\_FLUSH\_FAILED, 371  
 ER\_LOG\_FILES\_GIVEN\_LOG\_OUTPUT\_IS\_TABLE, 139  
 ER\_LOG\_FILE\_CANNOT\_OPEN, 206  
 ER\_LOG\_FILE\_INVALID, 139  
 ER\_LOG\_GENERAL\_CANNOT\_OPEN, 129  
 ER\_LOG\_IN\_USE, 26  
 ER\_LOG\_OUTPUT\_CONTRADICTORY, 138  
 ER\_LOG\_PRINTF\_MSG, 192  
 ER\_LOG\_PRIV\_CHECKS\_REQUIRE\_ROW\_FORMAT\_NOT\_SE, 351  
 ER\_LOG\_PURGE\_NO\_FILE, 38  
 ER\_LOG\_PURGE\_UNKNOWN\_ERR, 26  
 ER\_LOG\_SLOW\_CANNOT\_OPEN, 129  
 ER\_LOG\_SYSLOG\_CANNOT\_OPEN, 129  
 ER\_LONGITUDE\_OUT\_OF\_RANGE, 80  
 ER\_LOWER\_CASE\_TABLE\_NAMES\_CS\_DD\_ON\_CI\_FS\_UN, 139  
 ER\_LOWER\_CASE\_TABLE\_NAMES\_USING\_0, 139  
 ER\_LOWER\_CASE\_TABLE\_NAMES\_USING\_2, 139  
 ER\_MALFORMED\_GTID\_SET\_ENCODING, 49  
 ER\_MALFORMED\_GTID\_SET\_SPECIFICATION, 49  
 ER\_MALFORMED\_GTID\_SPECIFICATION, 49  
 ER\_MALFORMED\_PACKET, 53  
 ER\_MANDATORY\_ROLE, 81  
 ER\_MASTER\_KEY\_ROTATION\_BINLOG\_FAILED, 70  
 ER\_MASTER\_KEY\_ROTATION\_NOT\_SUPPORTED\_BY\_SE, 70  
 ER\_MASTER\_KEY\_ROTATION\_SE\_UNAVAILABLE, 70  
 ER\_MAXVALUE\_IN\_VALUES\_IN, 41  
 ER\_MAX\_PREPARED\_STMT\_COUNT\_REACHED, 31  
 ER\_MDL\_OUT\_OF\_RESOURCES, 107  
 ER\_MECAB\_CHARSET\_LOADED, 196  
 ER\_MECAB\_CREATE\_LATTICE\_FAILED, 196  
 ER\_MECAB\_CREATING\_MODEL, 196  
 ER\_MECAB\_FAILED\_TO\_CREATE\_MODEL, 196  
 ER\_MECAB\_FAILED\_TO\_CREATE\_TRIGGER, 196  
 ER\_MECAB\_NOT\_SUPPORTED, 195  
 ER\_MECAB\_NOT\_VERIFIED, 196  
 ER\_MECAB\_OOM\_WHILE\_PARSING\_TEXT, 196  
 ER\_MECAB\_PARSE\_FAILED, 196  
 ER\_MECAB\_UNSUPPORTED\_CHARSET, 196  
 ER\_MESSAGE\_AND\_STATEMENT, 42  
 ER\_MFA\_METHODS\_IDENTICAL, 113  
 ER\_MFA\_METHODS\_INVALID\_ORDER, 113  
 ER\_MFA\_METHOD\_EXISTS, 113  
 ER\_MFA\_METHOD\_NOT\_EXISTS, 113  
 ER\_MFA\_PLUGIN\_NOT\_LOADED, 376  
 ER\_MFA\_USER\_ATTRIBUTES\_CORRUPT, 376  
 ER\_MICROSECOND\_TIMER\_IS\_NOT\_AVAILABLE, 190  
 ER\_MIGRATE\_TABLE\_TO\_DD\_OOM, 353  
 ER\_MISPLACED\_INTO, 104  
 ER\_MISSING\_ACL\_SYSTEM\_TABLE, 184  
 ER\_MISSING\_CURRENT\_PASSWORD, 100  
 ER\_MISSING\_GRANT\_SYSTEM\_TABLE, 184  
 ER\_MISSING\_HA\_CREATE\_OPTION, 58



---

ER\_MISSING\_JSON\_TABLE\_VALUE, 83  
 ER\_MISSING\_JSON\_VALUE, 105  
 ER\_MISSING\_KEY, 57  
 ER\_MISSING\_SKIP\_REPLICA, 20  
 ER\_MISSING\_TABLESPACE\_FILE, 81  
 ER\_MIXING\_NOT\_ALLOWED, 17  
 ER\_MIX\_HANDLER\_ERROR, 33  
 ER\_MIX\_OF\_GROUP\_FUNC\_AND\_FIELDS, 12  
 ER\_MIX\_OF\_GROUP\_FUNC\_AND\_FIELDS\_V2, 63  
 ER\_MTA\_CANT\_PARALLEL, 48  
 ER\_MTA\_CHANGE\_SOURCE\_CANT\_RUN\_WITH\_GAPS, 51  
 ER\_MTA\_EVENT\_BIGGER\_PENDING\_JOBS\_SIZE\_MAX, 55  
 ER\_MTA\_FEATURE\_IS\_NOT\_SUPPORTED, 48  
 ER\_MTA\_INCONSISTENT\_DATA, 48  
 ER\_MTA\_RECOVERY\_FAILURE, 51  
 ER\_MTA\_RESET\_WORKERS, 51  
 ER\_MTA\_UPDATED\_DBS\_GREATER\_MAX, 48  
 ER\_MTR\_MSG\_1, 372  
 ER\_MULTIPLE\_CONSTRAINTS\_WITH\_SAME\_NAME, 103  
 ER\_MULTIPLE\_DEF\_CONST\_IN\_LIST\_PART\_ERROR, 33  
 ER\_MULTIPLE\_INTO\_CLAUSES, 104  
 ER\_MULTIPLE\_JSON\_VALUES, 105  
 ER\_MULTIPLE\_PRI\_KEY, 7  
 ER\_MULTI\_UPDATE\_KEY\_CONFLICT, 44  
 ER\_MUST\_CHANGE\_PASSWORD, 52  
 ER\_MUST\_CHANGE\_PASSWORD\_LOGIN, 55  
 ER\_MYINIT\_FAILED, 137  
 ER\_MYISAM\_CHECK\_METHOD\_ERROR, 192  
 ER\_MYISAM\_CRASHED\_ERROR, 192  
 ER\_MYISAM\_CRASHED\_ERROR\_IN, 144  
 ER\_MYISAM\_CRASHED\_ERROR\_IN\_THREAD, 144  
 ER\_MYSQLBACKUP\_CLIENT\_MSG, 115  
 ER\_MYSQLBACKUP\_MSG, 350  
 ER\_MYSQL\_NATIVE\_PASSWORD\_SECOND\_PASSWORD\_USED\_INFORM, 336  
 ER\_MY\_MALLOC\_GETPROCADDRESS\_FAILED, 378  
 ER\_MY\_MALLOC\_LOADLIBRARY\_FAILED, 378  
 ER\_MY\_MALLOC\_USING\_JEMALLOC, 378  
 ER\_MY\_MALLOC\_USING\_STD\_MALLOC, 378  
 ER\_MY\_NET\_WRITE\_FAILED\_FALLING\_BACK\_ON\_STREAM, 170  
 ER\_M\_BIGGER\_THAN\_D, 28  
 ER\_NAME\_BECOMES\_EMPTY, 31  
 ER\_NANOSECOND\_TIMER\_IS\_NOT\_AVAILABLE, 190  
 ER\_NATIVE\_FCT\_NAME\_COLLISION, 37  
 ER\_NDBINFO\_NOT\_UPGRADING\_SCHEMA, 356  
 ER\_NDBINFO\_UPGRADING\_SCHEMA, 356  
 ER\_NDBINFO\_UPGRADING\_SCHEMA\_FAIL, 356  
 ER\_NDB\_LOG\_ENTRY, 178  
 ER\_NDB\_LOG\_ENTRY\_WITH\_PREFIX, 178  
 ER\_NDB\_REPLICATION\_SCHEMA\_ERROR, 39  
 ER\_NEED\_FILE\_INSTEAD\_OF\_DIR, 139  
 ER\_NEED\_LOG\_BIN, 139  
 ER\_NEED\_REPREPARE, 39  
 ER\_NETWORK\_NAMESPACES\_NOT\_SUPPORTED, 344  
 ER\_NETWORK\_NAMESPACE\_FILE\_PATH\_TOO\_LONG, 344  
 ER\_NETWORK\_NAMESPACE\_NOT\_ALLOWED\_FOR\_WIL, 344  
 ER\_NETWORK\_READ\_EVENT\_CHECKSUM\_FAILURE, 324  
 ER\_NET\_ERROR\_ON\_WRITE, 13  
 ER\_NET\_FCNTL\_ERROR, 13  
 ER\_NET\_OK\_PACKET\_TOO\_LARGE, 62  
 ER\_NET\_PACKETS\_OUT\_OF\_ORDER, 13  
 ER\_NET\_PACKET\_TOO\_LARGE, 13  
 ER\_NET\_READ\_ERROR, 13  
 ER\_NET\_READ\_ERROR\_FROM\_PIPE, 13  
 ER\_NET\_READ\_INTERRUPTED, 13  
 ER\_NET\_UNCOMPRESS\_ERROR, 13  
 ER\_NET\_WAIT\_ERROR, 345  
 ER\_NET\_WAIT\_ERROR2, 368  
 ER\_NET\_WRITE\_INTERRUPTED, 13  
 ER\_NEW\_ABORTING\_CONNECTION, 14  
 ER\_NO, 3  
 ER\_NONEXISTING\_GRANT, 12  
 ER\_NONEXISTING\_PROC\_GRANT, 27  
 ER\_NONEXISTING\_TABLE\_GRANT, 12  
 ER\_NONPOSITIVE\_RADIUS, 86  
 ER\_NONUNIQ\_TABLE, 7  
 ER\_NONUPDATEABLE\_COLUMN, 24  
 ER\_NON\_BOOLEAN\_EXPR\_FOR\_CHECK\_CONSTRAINT, 94  
 ER\_NON\_DEFAULT\_VALUE\_FOR\_GENERATED\_COLUMN, 65  
 ER\_NON\_GROUPING\_FIELD\_USED, 31  
 ER\_NON\_INSERTABLE\_TABLE, 31  
 ER\_NON\_RO\_SELECT\_DISABLE\_TIMER, 59  
 ER\_NON\_UNIQUE\_INDEX, 6  
 ER\_NON\_UPDATABLE\_TABLE, 21  
 ER\_NORMAL\_SERVER\_SHUTDOWN, 323  
 ER\_NOTE\_COMPONENT\_KEYRING\_OCI\_MISSING\_NAME, 386  
 ER\_NOTE\_COMPONENT\_SLOT\_DEREGISTRATION\_SUCCESS, 392  
 ER\_NOTE\_COMPONENT\_SLOT\_REGISTRATION\_SUCCESS, 392  
 ER\_NOTE\_KEYRING\_COMPONENT\_AES\_DATA\_IDENTIFIER, 367  
 ER\_NOTE\_KEYRING\_COMPONENT\_AES\_INVALID\_KEY, 367  
 ER\_NOTE\_KEYRING\_COMPONENT\_AES\_INVALID\_MODE, 367  
 ER\_NOTE\_KEYRING\_COMPONENT\_AES\_OPERATION\_ERROR, 367  
 ER\_NOTE\_KEYRING\_COMPONENT\_GENERATE\_FAILED, 367

---

ER_NOTE_KEYRING_COMPONENT_INITIALIZED, 366	ER_NO_SUCH_TABLE, 12
ER_NOTE_KEYRING_COMPONENT_KEYS_METADATA_ITERATION_FAILED, 367	ER_NO_SUCH_THREAD, 9
ER_NOTE_KEYRING_COMPONENT_METADATA_ITERATION_FAILED, 368	ER_NO_SUPER_WITHOUT_USER_PLUGIN, 150
ER_NOTE_KEYRING_COMPONENT_READ_DATA_NOT_FOUND, 367	ER_NO_SYSTEM_TABLESPACE_ACCESS, 76
ER_NOTE_KEYRING_COMPONENT_REMOVE_FAILED, 367	ER_NO_SYSTEM_TABLESPACE_ACCESS, 76
ER_NOTE_KEYRING_COMPONENT_STORE_FAILED, 367	ER_NO_SYSTEM_TABLE_ACCESS, 76
ER_NOTE_KEYRING_COMPONENT_WRITE_MAXIMUM_DATA_LENGTH, 367	ER_NO_SYSTEM_TABLE_ACCESS_FOR_DICTIONARY_TABLES, 76
ER_NOT_ALLOWED_COMMAND, 12	ER_NO_SYSTEM_TABLE_ACCESS_FOR_SYSTEM_TABLE, 76
ER_NOT_ALLOWED_WITH_START_TRANSACTION, 106	ER_NO_SYSTEM_TABLE_ACCESS_FOR_TABLE, 76
ER_NOT_FORM_FILE, 5	ER_NO_SYSTEM_VIEW_ACCESS, 80
ER_NOT_HINT_UPDATABLE_VARIABLE, 81	ER_NO_TABLES_USED, 9
ER_NOT_IMPLEMENTED_FOR_CARTESIAN_SRS, 86	ER_NO_THD_NO_UUID, 133
ER_NOT_IMPLEMENTED_FOR_GEOGRAPHIC_SRS, 80	ER_NO_TRIGGERS_ON_SYSTEM_SCHEMA, 31
ER_NOT_IMPLEMENTED_FOR_PROJECTED_SRS, 86	ER_NO_UNIQUE_LOGFILE, 9
ER_NOT_IMPLEMENTED_GET_TABLESPACE_STATISTICS, 206	ER_NPIPE_CANT_CREATE, 179
ER_NOT_KEYFILE, 5	ER_NPIPE_FAILED_TO_INIT_SECURITY_DESCRIPTOR, 155
ER_NOT_RIGHT_NOW, 137	ER_NPIPE_FAILED_TO_SET_SECURITY_DESCRIPTOR, 155
ER_NOT_SUPPORTED_AUTH_MODE, 19	ER_NPIPE_PIPE_ALREADY_IN_USE, 155
ER_NOT_SUPPORTED_YET, 18	ER_NULL_CANT_BE_PERSISTED_FOR_READONLY, 125
ER_NOT_VALID_PASSWORD, 52	ER_NULL_COLUMN_IN_INDEX, 11
ER_NO_ACCESS_TO_NATIVE_FCT, 77	ER_NULL_IN_VALUES_LESS_THAN, 36
ER_NO_BINARY_LOGGING, 26	ER_NUMERIC_JSON_VALUE_OUT_OF_RANGE, 68
ER_NO_BINLOG_ERROR, 34	ER_NUM_THREADS_STILL_ALIVE, 398
ER_NO_CSV_NO_LOG_TABLES, 138	ER_OBSOLETE_FILE_PRIVILEGE_FOR_REPLICATION_CHECK, 350
ER_NO_DB_ERROR, 6	ER_OBSOLETE_REQUIRE_ROW_FORMAT_VIOLATION, 351
ER_NO_DEFAULT, 17	ER_OLD_FILE_FORMAT, 30
ER_NO_DEFAULT_FOR_FIELD, 25	ER_OLD_KEYFILE, 5
ER_NO_DEFAULT_FOR_VIEW_FIELD, 28	ER_OLD_TEMPORALS_UPGRADED, 56
ER_NO_ERROR_LOG_PARSER_CONFIGURED, 362	ER_ONLY_FD_AND_RBR_EVENTS_ALLOWED_IN_BINLOG_STATEMENT, 46
ER_NO_FORMAT_DESCRIPTION_EVENT_BEFORE_BINLOG_STATEMENT, 38	ER_ONLY_IMPLEMENTED_FOR_SRID_0_AND_4326, 84
ER_NO_FT_MATERIALIZED_SUBQUERY, 58	ER_ONLY_IN_MEMORY_ROWS_ALLOWED, 37
ER_NO_PARTITION_FOR_GIVEN_VALUE, 34	ER_ONLY_ON_RANGE_LIST_PARTITION, 34
ER_NO_PARTITION_FOR_GIVEN_VALUE_SILENT, 37	ER_OOM, 137
ER_NO_PARTS_ERROR, 33	ER_OOM_SAVE_GTIDS, 323
ER_NO_PATH_FOR_SHARED_LIBRARY, 328	ER_OPEN_AS_READONLY, 5
ER_NO_PERMISSION_TO_CREATE_USER, 16	ER_OPEN_ROLE_TABLES, 74
ER_NO_REFERENCED_ROW, 16	ER_OPERAND_COLUMNS, 18
ER_NO_REFERENCED_ROW_2, 30	ER_OPERATION_NOT_ALLOWED_ON_GR_SECONDARY, 112
ER_NO_SECURE_TRANSPORTS_CONFIGURED, 69	ER_OPERATION_NOT_ALLOWED_WHILE_PRIMARY_CHANGING, 116
ER_NO_SESSION_TEMP, 99	ER_OPTION_PREVENTS_STATEMENT, 21
ER_NO_SUCH_DB, 72	ER_OPT_WRONG_TREE, 128
ER_NO_SUCH_INDEX, 8	ER_OUTOFMEMORY, 5
	ER_OUT_OF_RESOURCES, 5
	ER_OUT_OF_SORTMEMORY, 5

---

ER\_PAGE\_TRACKING\_CANNOT\_PURGE, 93  
 ER\_PAGE\_TRACKING\_NOT\_STARTED, 93  
 ER\_PAGE\_TRACKING\_RANGE\_NOT\_TRACKED, 93  
 ER\_PARSER\_TRACE, 128  
 ER\_PARSE\_ERROR, 7  
 ER\_PARSE\_ERROR\_IN\_DIGEST\_FN, 84  
 ER\_PARSING\_VIEW, 132  
 ER\_PARTIAL\_REVOKES\_EXIST, 100  
 ER\_PARTIAL\_REVOKE\_AND\_DB\_GRANT\_BOTH\_EXIST, 100  
 ER\_PARTITIONS\_MUST\_BE\_DEFINED\_ERROR, 32  
 ER\_PARTITION\_CLAUSE\_ON\_NONPARTITIONED, 47  
 ER\_PARTITION\_COLUMN\_LIST\_ERROR, 41  
 ER\_PARTITION\_CONST\_DOMAIN\_ERROR, 36  
 ER\_PARTITION\_ENTRY\_ERROR, 33  
 ER\_PARTITION\_EXCHANGE\_DIFFERENT\_OPTION, 46  
 ER\_PARTITION\_EXCHANGE\_FOREIGN\_KEY, 47  
 ER\_PARTITION\_EXCHANGE\_PART\_TABLE, 46  
 ER\_PARTITION\_EXCHANGE\_TEMP\_TABLE, 46  
 ER\_PARTITION\_FIELDS\_TOO\_LONG, 41  
 ER\_PARTITION\_FUNCTION\_FAILURE, 34  
 ER\_PARTITION\_FUNCTION\_IS\_NOT\_ALLOWED, 36  
 ER\_PARTITION\_FUNC\_NOT\_ALLOWED\_ERROR, 32  
 ER\_PARTITION\_HANDLER\_ADMIN\_MSG, 191  
 ER\_PARTITION\_INSTEAD\_OF\_SUBPARTITION, 47  
 ER\_PARTITION\_MAXVALUE\_ERROR, 32  
 ER\_PARTITION\_MERGE\_ERROR, 36  
 ER\_PARTITION\_MGMT\_ON\_NONPARTITIONED, 33  
 ER\_PARTITION\_MOVE\_CREATED\_DUPLICATE\_ROW\_IDS, 179  
 ER\_PARTITION\_NAME, 40  
 ER\_PARTITION\_NOT\_DEFINED\_ERROR, 33  
 ER\_PARTITION\_NO\_TEMPORARY, 36  
 ER\_PARTITION\_REQUIRES\_VALUES\_ERROR, 32  
 ER\_PARTITION\_WRONG\_NO\_PART\_ERROR, 32  
 ER\_PARTITION\_WRONG\_NO\_SUBPART\_ERROR, 32  
 ER\_PARTITION\_WRONG\_VALUES\_ERROR, 32  
 ER\_PART\_EXPR\_TOO\_LONG, 80  
 ER\_PASSWORD\_ANONYMOUS\_USER, 11  
 ER\_PASSWORD\_CANNOT\_BE\_RETAINED\_ON\_PLUGIN\_CHANGE, 100  
 ER\_PASSWORD\_EXPIRATION\_NOT\_SUPPORTED\_BY\_PLUGIN, 84  
 ER\_PASSWORD\_EXPIRE\_ANONYMOUS\_USER, 58  
 ER\_PASSWORD\_FORMAT, 53  
 ER\_PASSWORD\_NOT\_ALLOWED, 11  
 ER\_PASSWORD\_NO\_MATCH, 11  
 ER\_PATH\_IN\_DATADIR, 81  
 ER\_PATH\_LENGTH, 43  
 ER\_PERFORMANCE\_SCHEMA\_VERSION\_CHANGE, 396  
 ER\_PERFSCHEMA\_COMPONENTS\_INFRASTRUCTURE\_LOAD\_FAILED, 183  
 ER\_PERFSCHEMA\_COMPONENTS\_INFRASTRUCTURE\_LOAD\_FAILED\_2, 183  
 ER\_PERFSCHEMA\_INIT\_FAILED, 140  
 ER\_PERFSCHEMA\_TABLES\_INIT\_FAILED, 184  
 ER\_PERSISTED\_VARIABLES\_DECRYPTION\_FAILED, 378  
 ER\_PERSISTED\_VARIABLES\_ENCRYPTION\_FAILED, 378  
 ER\_PERSISTED\_VARIABLES\_KEYRING\_SUPPORT\_REQUIRED, 378  
 ER\_PERSISTED\_VARIABLES\_LACK\_KEYRING\_SUPPORT, 378  
 ER\_PERSISTED\_VARIABLES\_MASTER\_KEY\_CANNOT\_BE\_LOADED, 378  
 ER\_PERSISTED\_VARIABLES\_MASTER\_KEY\_NOT\_FOUND, 378  
 ER\_PERSISTENT\_PRIVILEGES\_BOOTSTRAP, 183  
 ER\_PERSIST\_ONLY\_ACCESS\_DENIED\_ERROR, 81  
 ER\_PERSIST\_OPTION\_HOST\_TRUNCATED, 345  
 ER\_PERSIST\_OPTION\_STATUS, 206  
 ER\_PERSIST\_OPTION\_USER\_TRUNCATED, 345  
 ER\_PER\_CHANNEL\_RPL\_FILTER\_CONF\_FOR\_GRP\_RPL\_UNSUPPORTED, 189  
 ER\_PFS\_MALLOC\_ARRAY\_OOM, 190  
 ER\_PFS\_MALLOC\_ARRAY\_OVERFLOW, 190  
 ER\_PFS\_NOTIFICATION\_FUNCTION\_REGISTER\_FAILED, 185  
 ER\_PID\_FILEPATH\_LOCATIONS\_INACCESSIBLE, 329  
 ER\_PLUGIN\_CANNOT\_BE\_LOADED, 170  
 ER\_PLUGIN\_CANNOT\_BE\_PRIV\_DIRECTORY\_INSECURE, 246  
 ER\_PLUGIN\_CANNOT\_BE\_UNINSTALLED, 56  
 ER\_PLUGIN\_CANT\_LOAD, 169  
 ER\_PLUGIN\_CANT\_OPEN\_PLUGIN\_TABLE, 169  
 ER\_PLUGIN\_CANT\_SET\_PERSISTENT\_OPTIONS, 170  
 ER\_PLUGIN\_CHANGE, 170  
 ER\_PLUGIN\_COMMON\_FAILED\_TO\_OPEN\_FILTER\_TABLE, 205  
 ER\_PLUGIN\_COMMON\_FAILED\_TO\_OPEN\_TABLE, 205  
 ER\_PLUGIN\_DELETE\_BUILTIN, 39  
 ER\_PLUGIN\_DID\_NOT\_DEINITIALIZE\_THREADS, 160  
 ER\_PLUGIN\_DISABLED, 170

---

---

ER\_PLUGIN\_EXCEPTION\_OPERATION\_FAILED, 389  
 ER\_PLUGIN\_FAILED\_DEINITIALIZATION, 169  
 ER\_PLUGIN\_FAILED\_TO\_OPEN\_TABLE, 327  
 ER\_PLUGIN\_FAILED\_TO\_OPEN\_TABLES, 327  
 ER\_PLUGIN\_FORCING\_SHUTDOWN, 169  
 ER\_PLUGIN\_HAS\_CONFLICTING\_SYSTEM\_VARIABLES, 170  
 ER\_PLUGIN\_HAS\_NONZERO\_REFCOUNT\_AFTER\_DEINITIALIZATION, 169  
 ER\_PLUGIN\_HAS\_NONZERO\_REFCOUNT\_AFTER\_SHUTDOWN, 169  
 ER\_PLUGIN\_INIT\_FAILED, 142  
 ER\_PLUGIN\_INSTALL\_ERROR, 332  
 ER\_PLUGIN\_INVALID\_TABLE\_DEFINITION, 371  
 ER\_PLUGIN\_IS\_NOT\_LOADED, 34  
 ER\_PLUGIN\_IS\_PERMANENT, 44  
 ER\_PLUGIN\_LOAD\_OPTIONS\_IGNORED, 350  
 ER\_PLUGIN\_LOAD\_PARAMETER\_TOO\_LONG, 169  
 ER\_PLUGIN\_NOT\_EARLY, 96  
 ER\_PLUGIN\_NOT\_EARLY\_DUP, 345  
 ER\_PLUGIN\_NO\_INSTALL, 46  
 ER\_PLUGIN\_NO\_INSTALL\_DUP, 345  
 ER\_PLUGIN\_NO\_UNINSTALL, 45  
 ER\_PLUGIN\_OOM, 170  
 ER\_PLUGIN\_PARSING\_OPTIONS\_FAILED, 170  
 ER\_PLUGIN\_REGISTRATION\_DONE, 113  
 ER\_PLUGIN\_REGISTRATION\_FAILED, 169  
 ER\_PLUGIN\_REQUIRES\_REGISTRATION, 113  
 ER\_PLUGIN\_SHUTTING\_DOWN\_PLUGIN, 169  
 ER\_PLUGIN\_UNINSTALL\_ERROR, 332  
 ER\_PLUGIN\_UNKNOWN\_VARIABLE\_TYPE, 170  
 ER\_PLUGIN\_VARIABLE\_MISSING\_NAME, 170  
 ER\_PLUGIN\_VARIABLE\_NOT\_ALLOCATED\_THREAD\_LOCAL, 170  
 ER\_PLUGIN\_VARIABLE\_SET\_READ\_ONLY, 170  
 ER\_POINTLESS\_WITHOUT\_SLOWLOG, 134  
 ER\_POLYGON\_TOO\_LARGE, 87  
 ER\_PREPARE\_FOR\_PRIMARY\_ENGINE, 372  
 ER\_PREPARE\_FOR\_SECONDARY\_ENGINE, 341  
 ER\_PREVENTS\_VARIABLE\_WITHOUT\_RBR, 64  
 ER\_PRIMARY\_CANT\_HAVE\_NULL, 14  
 ER\_PRIVILEGE\_DEREGISTRATION, 393  
 ER\_PRIVILEGE\_REGISTRATION, 393  
 ER\_PRIVILEGE\_SYSTEM\_INIT\_FAILED, 183  
 ER\_PROCACCESS\_DENIED\_ERROR, 26  
 ER\_PROC\_AUTO\_GRANT\_FAIL, 27  
 ER\_PROC\_AUTO\_REVOKE\_FAIL, 27  
 ER\_PROTOCOL\_COMPRESSION\_RESET\_LOG, 350  
 ER\_PS\_MANY\_PARAM, 26  
 ER\_PS\_NO\_RECURSION, 30  
 ER\_QUALIFY\_WITHOUT\_WINDOW\_FUNCTION, 124  
 ER\_QUERY\_INTERRUPTED, 22  
 ER\_QUERY\_ON\_FOREIGN\_DATA\_SOURCE, 29  
 ER\_QUERY\_TIMEOUT, 59  
 ER\_RANGE\_NOT\_INCREASING\_ERROR, 32  
 ER\_READING\_TABLE\_FAILED, 142  
 ER\_READY, 8  
 ER\_READ\_LOG\_EVENT\_FAILED, 188  
 ER\_READ\_ONLY\_MODE, 53  
 ER\_READ\_ONLY\_TRANSACTION, 16  
 ER\_REALLY\_RUN\_AS\_ROOT, 136  
 ER\_RECORD\_FILE\_FULL, 10  
 ER\_RECOVERING\_TABLE, 171  
 ER\_REDUCED\_DBLWR\_FILE\_CORRUPTED, 394  
 ER\_REDUCED\_DBLWR\_PAGE\_FOUND, 394  
 ER\_REFERENCED\_TRG\_DOES\_NOT\_EXIST, 58  
 ER\_REGEXP\_BAD\_ESCAPE\_SEQUENCE, 85  
 ER\_REGEXP\_BAD\_INTERVAL, 85  
 ER\_REGEXP\_BUFFER\_OVERFLOW, 85  
 ER\_REGEXP\_ERROR, 12  
 ER\_REGEXP\_ILLEGAL\_ARGUMENT, 85  
 ER\_REGEXP\_INDEX\_OUTOFBOUNDS\_ERROR, 85  
 ER\_REGEXP\_INTERNAL\_ERROR, 85  
 ER\_REGEXP\_INVALID\_BACK\_REF, 85  
 ER\_REGEXP\_INVALID\_CAPTURE\_GROUP\_NAME, 99  
 ER\_REGEXP\_INVALID\_FLAG, 100  
 ER\_REGEXP\_INVALID\_RANGE, 85  
 ER\_REGEXP\_LOOK\_BEHIND\_LIMIT, 85  
 ER\_REGEXP\_MAX\_LT\_MIN, 85  
 ER\_REGEXP\_MISMATCHED\_PAREN, 85  
 ER\_REGEXP\_MISSING\_CLOSE\_BRACKET, 85  
 ER\_REGEXP\_MISSING\_FILE, 115  
 ER\_REGEXP\_MISSING\_ICU\_DATADIR, 377  
 ER\_REGEXP\_MISSING\_RESOURCE, 114  
 ER\_REGEXP\_PATTERN\_TOO\_BIG, 85  
 ER\_REGEXP\_RULE\_SYNTAX, 85  
 ER\_REGEXP\_STACK\_OVERFLOW, 85  
 ER\_REGEXP\_TIME\_OUT, 85  
 ER\_REGEXP\_UNIMPLEMENTED, 85  
 ER\_REGEX\_NUMBER\_TOO\_BIG, 109  
 ER\_RELAY\_LOG\_FAIL, 26  
 ER\_RELAY\_LOG\_INIT, 26  
 ER\_RELAY\_LOG\_SPACE\_LIMIT\_DISABLED, 330  
 ER\_RELOAD\_KEYRING\_FAILURE, 111  
 ER\_REMOVED\_SPACES, 31  
 ER\_RENAMED\_NAME, 40  
 ER\_RENAME\_ROLE, 74  
 ER\_REORG\_HASH\_ONLY\_ON\_SAME\_NO, 33  
 ER\_REORG\_NO\_PARAM\_ERROR, 34  
 ER\_REORG\_OUTSIDE\_RANGE, 34  
 ER\_REORG\_PARTITION\_NOT\_EXIST, 34  
 ER\_REPLACE\_INACCESSIBLE\_ROWS, 61  
 ER\_REPLICATION\_INCOMPATIBLE\_TABLE\_WITH\_GIPK, 387  
 ER\_REPLICA\_AM\_INIT\_REPOSITORY, 56  
 ER\_REPLICA\_ANONYMOUS\_TO\_GTID\_UUID\_SAME\_AS\_GRO, 364  
 ER\_REPLICA\_ANON\_TO\_GTID\_IS\_LOCAL\_OR\_UUID\_AND\_G, 364  
 ER\_REPLICA\_CANT\_CREATE\_CONVERSION, 43

---

ER_REPLICA_CANT_USE_TEMPDIR, 167	ER_REPLICA_SQL_THREAD_STOPPED_AFTER_GTIDS_F
ER_REPLICA_CHANGE_SOURCE_TO_EXECUTED, 166	154
ER_REPLICA_CHANNEL_DOES_NOT_EXIST, 62	ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTIDS
ER_REPLICA_CHANNEL_IO_THREAD_MUST_STOP, 58	154
ER_REPLICA_CHANNEL_MUST_STOP, 62	ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTIDS
ER_REPLICA_CHANNEL_NAME_INVALID_OR_TOO_LONG, 62	154
ER_REPLICA_CHANNEL_NOT_RUNNING, 63	ER_REPLICA_SQL_THREAD_STOPPED_GAP_TRX_PROG
ER_REPLICA_CHANNEL_OPERATION_NOT_ALLOWED, 67	ER_REPLICA_SQL_THREAD_STOPPED_UNTIL_CONDITIO
ER_REPLICA_CHANNEL_SQL_SKIP_COUNTER, 63	154
ER_REPLICA_CHANNEL_SQL_THREAD_MUST_STOP, 63	ER_REPLICA_SQL_THREAD_STOPPED_UNTIL_POSITION
ER_REPLICA_CHANNEL_WAS_NOT_RUNNING, 63	154
ER_REPLICA_CHANNEL_WAS_RUNNING, 63	ER_REPLICA_THREAD, 15
ER_REPLICA_CM_INIT_REPOSITORY, 56	ER_REPLICA_WORKER_STOPPED_PREVIOUS_THD_ER
ER_REPLICA_CONFIGURATION, 51	59
ER_REPLICA_CORRUPT_EVENT, 38	ER_REQUIRES_PRIMARY_KEY, 14
ER_REPLICA_CREATE_EVENT_FAILURE, 324	ER_REQUIRE_ROW_FORMAT_INVALID_VALUE,
ER_REPLICA_FATAL_ERROR, 324	104
ER_REPLICA_HAS_MORE_GTIDS_THAN_SOURCE, 57	ER_REQUIRE_TABLE_PRIMARY_KEY_CHECK_GENERAT
ER_REPLICA_HEARTBEAT_FAILURE, 324	120
ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE, 39	ER_REQUIRE_TABLE_PRIMARY_KEY_CHECK_GENERAT
ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE_MAX, 44	389
ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE_MIN, 44	ER_RESERVED_SYNTAX, 26
ER_REPLICA_IGNORED_SSL_PARAMS, 20	ER_RESERVED_TABLESPACE_NAME, 87
ER_REPLICA_IGNORED_TABLE, 18	ER_RESET_SOURCE_TO_VALUE_OUT_OF_RANGE,
ER_REPLICA_IGNORE_SERVER_IDS, 41	77
ER_REPLICA_INCIDENT, 324	ER_RESIGNAL_WITHOUT_ACTIVE_HANDLER, 40
ER_REPLICA_KILLED_AFTER_RECONNECT, 189	ER_RESOURCE_GROUP_BIND_FAILED, 83
ER_REPLICA_MAX_CHANNELS_EXCEEDED, 62	ER_RESOURCE_GROUP_BUSY, 83
ER_REPLICA_MULTIPLE_CHANNELS_CMD, 62	ER_RESOURCE_GROUP_DISABLED, 83
ER_REPLICA_NEW_CHANNEL_WRONG_REPOSITORY, 62	ER_RESOURCE_GROUP_EXISTS, 82
ER_REPLICA_NOT_RUNNING, 15	ER_RESOURCE_GROUP_IS_DISABLED, 185
ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS, 189	ER_RESOURCE_GROUP_METADATA_UPDATE_SKIPPED
ER_REPLICA_POSSIBLY_DIVERGED_AFTER_DDL, 87	185
ER_REPLICA_RECONNECT_FAILED, 189	ER_RESOURCE_GROUP_NOT_EXISTS, 82
ER_REPLICA_RELAY_LOG_PURGE_FAILED, 184	ER_RESOURCE_GROUP_POST_INIT_FAILED,
ER_REPLICA_RELAY_LOG_READ_FAILURE, 324	183
ER_REPLICA_RELAY_LOG_TRUNCATE_INFO, 184	ER_RESOURCE_GROUP_SUBSYSTEM_INIT_FAILED,
ER_REPLICA_RELAY_LOG_WRITE_FAILURE, 324	183
ER_REPLICA_SILENT_RETRY_TRANSACTION, 51	ER_RESOURCE_GROUP_VALIDATION_FAILED,
ER_REPLICA_SOURCE_COM_FAILURE, 324	185
ER_REPLICA_SQL_THREAD_MUST_STOP, 58	ER_RESTART_RECEIVED_INFO, 193
	ER_RESTART_SERVER_FAILED, 86
	ER_RES_GRP_FAILED_DETERMINE_CPU_COUNT,
	186
	ER_RES_GRP_FAILED_TO_DETERMINE_NICE_CAPABIL
	186
	ER_RES_GRP_FAILED_TO_GET_THREAD_HANDLE,
	186
	ER_RES_GRP_FEATURE_NOT_AVAILABLE, 186
	ER_RES_GRP_GET_THREAD_PRIO_NOT_SUPPORTED,
	186
	ER_RES_GRP_INVALID_THREAD_PRIORITY, 186
	ER_RES_GRP_INVALID_VCPU_ID, 193
	ER_RES_GRP_INVALID_VCPU_RANGE, 193
	ER_RES_GRP_SET_THREAD_PRIORITY_FAILED,
	186
	ER_RES_GRP_SET_THR_AFFINITY_FAILED, 186

---

ER_RES_GRP_SET_THR_AFFINITY_TO_CPUS_FAILED, 186	ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF, 107
ER_RES_GRP_SOLARIS_PROCESSOR_AFFINITY_FAILED, 186	ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF_CHANNEL, 365
ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_CPU_FAILED, 186	ER_RPL_ASYNC_REPLICA_IO_THD_FETCH_GROUP_MAJOR, 403
ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_THR_FAILED, 186	ER_RPL_ASYNC_SENDER_ADDED, 363
ER_RES_GRP_THD_UNBIND_FROM_CPU_FAILED, 186	ER_RPL_ASYNC_SENDER_REMOVED, 363
ER_RETRYING_REPAIR_WITHOUT_QUICK, 170	ER_RPL_BINLOG_FILTERS_OOM, 136
ER_RETRYING_REPAIR_WITH_KEYCACHE, 170	ER_RPL_BINLOG_RELAY_DELEGATES_INIT_FAILED, 142
ER_REVOKE_GRANTS, 20	ER_RPL_BINLOG_SKIPPING_REMAINING_HEARTBEAT_INFO, 159
ER_REWRITER_LOAD_FAILED, 207	ER_RPL_BINLOG_SOURCE_SENDS_HEARTBEAT, 159
ER_REWRITER_OOM, 206	ER_RPL_BINLOG_SOURCE_USES_CHECKSUM_AND_REPLI, 159
ER_REWRITER_QUERY_ERROR_MSG, 204	ER_RPL_BINLOG_STARTING_DUMP, 159
ER_REWRITER_QUERY_FAILED, 204	ER_RPL_BINLOG_STORAGE_DELEGATES_INIT_FAILED, 142
ER_REWRITER_READ_FAILED, 207	ER_RPL_BINLOG_TRANSMIT_DELEGATES_INIT_FAILED, 142
ER_REWRITER_TABLE_MALFORMED_ERROR, 207	ER_RPL_CANNOT_OPEN_RELAY_LOG, 375
ER_ROLE_GRANTED_TO_ITSELF, 110	ER_RPL_CANT_ADD_DO_TABLE, 138
ER_ROLE_NOT_GRANTED, 74	ER_RPL_CANT_ADD_IGNORE_TABLE, 138
ER_ROW_DATA_TOO_BIG_TO_WRITE_IN_BINLOG, 189	ER_RPL_CANT_CREATE_REPLICA_THREAD, 162
ER_ROW_DOES_NOT_MATCH_GIVEN_PARTITION_SIZE, 47	ER_RPL_CANT_FIND_FOLLOWUP_FILE, 165
ER_ROW_DOES_NOT_MATCH_PARTITION, 47	ER_RPL_CANT_HAVE_SAME_BASENAME, 181
ER_ROW_IN_WRONG_PARTITION, 55	ER_RPL_CANT_INITIALIZE_GTID_SETS_IN_AM_INIT_INFO, 167
ER_ROW_IN_WRONG_PARTITION_PLEASE_REPAIR, 144	ER_RPL_CANT_MAKE_PATHS, 139
ER_ROW_IS_REFERENCED, 17	ER_RPL_CANT_OPEN_INFO_TABLE, 155
ER_ROW_IS_REFERENCED_2, 30	ER_RPL_CANT_OPEN_LOG_IN_AM_INIT_INFO, 167
ER_ROW_SINGLE_PARTITION_FIELD_ERROR, 41	ER_RPL_CANT_SCAN_INFO_TABLE, 155
ER_RPL_AM_INIT_INFO_MSG, 191	ER_RPL_CANT_STOP_REPLICA_WHILE_LOCKED_BACKUP, 107
ER_RPL_ASYNC_CHANNEL_CANT_CONNECT, 363	ER_RPL_CHANNELS_REQUIRE_NON_ZERO_SERVER_ID, 156
ER_RPL_ASYNC_CHANNEL_CANT_CONNECT_NO_QUORUM, 364	ER_RPL_CORRUPTED_INFO_TABLE, 155
ER_RPL_ASYNC_CHANNEL_STOPPED_QUORUM_LOST, 364	ER_RPL_CORRUPTED_KEYS_IN_INFO_TABLE, 155
ER_RPL_ASYNC_CHECK_CONNECTION_ERROR, 403	ER_RPL_ENCRYPTION_CANNOT_ROTATE_BINLOG_MASTER, 93
ER_RPL_ASYNC_GET_GROUP_MEMBERSHIP_DETAILS_ERROR, 403	ER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT, 93
ER_RPL_ASYNC_MANAGED_NAME_ADDED, 364	ER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY, 92
ER_RPL_ASYNC_MANAGED_NAME_REMOVED, 364	ER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY, 92
ER_RPL_ASYNC_MONITOR_IO_THD_FETCH_GROUP_FAILED, 403	ER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY, 92
ER_RPL_ASYNC_NEXT_FAILOVER_CHANNEL_SELECTED, 390	ER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS, 92
ER_RPL_ASYNC_READ_FAILOVER_TABLE, 364	ER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY, 92
ER_RPL_ASYNC_RECONNECT_AUTO_POSITION_OFFER, 107	ER_RPL_ENCRYPTION_HEADER_ERROR, 92
ER_RPL_ASYNC_RECONNECT_FAIL_NO_SOURCE, 362	

ER_RPL_ENCRYPTION_KEYRING_INVALID_KEY, 92	ER_RPL_INFINITY_DENIED, 141
ER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED, 92	ER_RPL_INFINITY_IGNORED, 141
ER_RPL_ENCRYPTION_KEY_NOT_FOUND, 92	ER_RPL_INFO_DATA_TOO_LONG, 47
ER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED, 93	ER_RPL_IO_THREAD_KILLED, 189
ER_RPL_ENCRYPTION_UNABLE_TO_CHANGE_OPTIONS, 92	ER_RPL_LOG_ENTRY_EXCEEDS_REPLICA_MAX_ALLOWED, 167
ER_RPL_ERROR_CREATING_APPLIER_METADATA, 156	ER_RPL_LOG_NOT_FOUND_WHILE_COUNTING_RELAY_LOG, 167
ER_RPL_ERROR_CREATING_CONNECTION_METADATA, 156	ER_RPL_MTA_AUTOMATIC_RECOVERY_FAILED, 162
ER_RPL_ERROR_LOOKING_FOR_LOG, 164	ER_RPL_MTA_CHECKPOINT_PERIOD_DIFFERS_FROM_COORDINATOR, 165
ER_RPL_ERROR_READING_REPLICA_WORKER_CONFIGURATION, 168	ER_RPL_MTA_GROUP_RECOVERY_APPLIER_METADATA, 164
ER_RPL_ERROR_READING_SOURCE_CONFIGURATION, 169	ER_RPL_MTA_GROUP_RECOVERY_APPLIER_METADATA, 164
ER_RPL_ERROR_WRITING_RELAY_LOG_CONFIGURATION, 167	ER_RPL_MTA_RECOVERY_CANT_OPEN_RELAY_LOG, 162
ER_RPL_ERROR_WRITING_SOURCE_CONFIGURATION, 169	ER_RPL_MTA_RECOVERY_COMPLETE, 163
ER_RPL_FAILED_TO_CREATE_CACHE_FOR_INFO_FILE, 157	ER_RPL_MTA_RECOVERY_FAILED_TO_START_COORDINATOR, 162
ER_RPL_FAILED_TO_CREATE_NEW_INFO_FILE, 157	ER_RPL_MTA_RECOVERY_STARTING_COORDINATOR, 162
ER_RPL_FAILED_TO_DELETE_FROM_REPLICA_WORKER_INFO, 156	ER_RPL_MTA_RECOVERY_SUCCESSFUL, 162
ER_RPL_FAILED_TO_OPEN_INFO_FILE, 157	ER_RPL_MTA_REPLICA_COORDINATOR_HAS_WAITED, 168
ER_RPL_FAILED_TO_OPEN_RELAY_LOG, 168	ER_RPL_MTA_RESTARTING_COORDINATOR, 163
ER_RPL_FAILED_TO_RESET_STATE_IN_REPLICA_INDEX, 156	ER_RPL_MULTISOURCE_REQUIRES_TABLE_TYPE_REPLICATION, 156
ER_RPL_FAILED_TO_STAT_LOG_IN_INDEX, 167	ER_RPL_OPEN_INDEX_FILE_FAILED, 167
ER_RPL_FILTERS_NOT_ATTACHED_TO_CHANNEL, 189	ER_RPL_PLUGIN_FUNCTION_FAILED, 142
ER_RPL_FILTER_ADD_WILD_DO_TABLE_FAILED, 183	ER_RPL_RECOVERY_ERROR, 161
ER_RPL_FILTER_ADD_WILD_IGNORE_TABLE_FAILED, 183	ER_RPL_RECOVERY_ERROR_READ_RELAY_LOG, 161
ER_RPL_GTID_LOG_EVENT_IN_STREAM, 158	ER_RPL_RECOVERY_FILE_SOURCE_POS_INFO, 162
ER_RPL_GTID_MEMORY_FINALLY_AVAILABLE, 157	ER_RPL_RECOVERY_IO_ERROR_READING_RELAY_LOG, 162
ER_RPL_GTID_MODE_REQUIRES_ENFORCE_GTID_CONSISTENCY, 181	ER_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_SOURCE, 161
ER_RPL_GTID_TABLE_CANNOT_OPEN, 129	ER_RPL_RECOVERY_REPLICATE_SAME_SERVER_ID_REQUIRED, 162
ER_RPL_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT, 332	ER_RPL_RECOVERY_SKIPPED_GROUP_REPLICATION, 161
ER_RPL_GTID_UNSAFE_STMT_CREATE_SELECT, 323	ER_RPL_RELAY_LOG_INDEX_NEEDS_FILE_NOT_DIRECTORY, 167
ER_RPL_GTID_UNSAFE_STMT_ON_NON_TRANS_TABLE, 323	ER_RPL_RELAY_LOG_NEEDS_FILE_NOT_DIRECTORY, 167
ER_RPL_INCOMPATIBLE_DECIMAL_IN_RBR, 158	ER_RPL_RELAY_LOG_RECOVERY_GTID_ONLY, 377
ER_RPL_INCONSISTENT_SEQUENCE_NO_IN_TRX, 156	ER_RPL_RELAY_LOG_RECOVERY_INFO_AFTER_CLONE, 353
ER_RPL_INCONSISTENT_TIMESTAMPS_IN_TRX, 155	ER_RPL_REPLICA_ADDITIONAL_ERROR_INFO_FROM_DONOR, 165
ER_RPL_INCREMENTING_MEMBER_ACTION_VERSION, 373	ER_RPL_REPLICA_AUTO_POSITION_IS_1_AND_GTID_MODE, 161

ER_RPL_REPLICA_CANT_FLUSH_CONNECTION_METADATA, 163	ER_RPL_REPLICA_IO_THREAD_DETECTED_UNEXPECTED_EXIT, 166
ER_RPL_REPLICA_CANT_INITIALIZE_REPLICA_WORKER, 164	ER_RPL_REPLICA_IO_THREAD_EXITING, 164
	ER_RPL_REPLICA_IO_THREAD_KILLED, 164
ER_RPL_REPLICA_CANT_INIT_RELAY_LOG_POSITION, 163	ER_RPL_REPLICA_IO_THREAD_STOP_CMD_EXEC_TIMEOUT, 323
ER_RPL_REPLICA_CANT_START_REPLICA_FOR_CHANNEL, 161	ER_RPL_REPLICA_IO_THREAD_WAS_KILLED, 162
ER_RPL_REPLICA_CANT_STOP_REPLICA_FOR_CHANNEL, 161	ER_RPL_REPLICA_MONITOR_IO_THREAD_EXITING, 364
ER_RPL_REPLICA_CANT_USE_CHARSET, 166	ER_RPL_REPLICA_MONITOR_IO_THREAD_RECONNECT_CHANNEL, 364
ER_RPL_REPLICA_CONNECTED_TO_SOURCE_REPLICATION, 166	ER_RPL_REPLICA_NEW_C_M_NEEDS_REPOS_TYPE_OTHER, 364
ER_RPL_REPLICA_CONNECTED_TO_SOURCE_RPL_SLAVE, 391	ER_RPL_REPLICA_NEXT_LOG_IS_ACTIVE, 166
ER_RPL_REPLICA_CONNECTED_TO_SOURCE_RPL_SLAVE, 391	ER_RPL_REPLICA_NEXT_LOG_IS_INACTIVE, 166
ER_RPL_REPLICA_COULD_NOT_CREATE_CHANNEL, 156	ER_RPL_REPLICA_QUEUE_EVENT_FAILED_INVALID_CONFIG, 166
ER_RPL_REPLICA_DUMP_THREAD_KILLED_BY_SOURCE, 163	ER_RPL_REPLICA_QUEUE_EVENT_FAILED_INVALID_NON_F, 351
ER_RPL_REPLICA_ERROR_INFO_FROM_DAEMON, 165	ER_RPL_REPLICA_READ_INVALID_EVENT_FROM_SOURCE, 166
ER_RPL_REPLICA_ERROR_LOADING_USER_DEFINED_FILTER, 165	ER_RPL_REPLICA_REPORT_HOST_TOO_LONG, 163
ER_RPL_REPLICA_ERROR_READING_FROM_SERVER, 163	ER_RPL_REPLICA_REPORT_PASSWORD_TOO_LONG, 163
ER_RPL_REPLICA_ERROR_READING_RELAY_LOG_EVENTS, 166	ER_RPL_REPLICA_REPORT_USER_TOO_LONG, 163
ER_RPL_REPLICA_ERROR_REQUESTING_BINLOG_DUMP, 164	ER_RPL_REPLICA_RESET_FILTER_OPTIONS, 184
ER_RPL_REPLICA_ERROR_RETRYING, 163	ER_RPL_REPLICA_SECONDS_BEHIND_SOURCE_DUBIOUS, 163
ER_RPL_REPLICA_ERROR_RUNNING_QUERY, 165	ER_RPL_REPLICA_SKIP_COUNTER_EXECUTED, 364
ER_RPL_REPLICA_FAILED_TO_CREATE_CHANNEL_FROM, 157	ER_RPL_REPLICA_SOURCE_UUID_HAS_CHANGED_HOST_F, 364
ER_RPL_REPLICA_FAILED_TO_CREATE_OR_RECOVER, 161	ER_RPL_REPLICA_SOURCE_UUID_HAS_NOT_CHANGED, 364
ER_RPL_REPLICA_FAILED_TO_INIT_A_CONNECTION, 156	ER_RPL_REPLICA_SOURCE_UUID_HOST_PORT_HAS_CHANG, 364
ER_RPL_REPLICA_FAILED_TO_INIT_CONNECTION_METADATA, 156	ER_RPL_REPLICA_SQL_THREAD_DETECTED_UNEXPECTED_EXIT, 351
ER_RPL_REPLICA_FAILED_TO_INIT_PARTITIONS_HASH, 165	ER_RPL_REPLICA_SQL_THREAD_EXITING, 165
ER_RPL_REPLICA_FILTER_CREATE_FAILED, 184	ER_RPL_REPLICA_SQL_THREAD_IO_ERROR_READING_EV, 166
ER_RPL_REPLICA_FORCING_TO_RECONNECT_IO_THREAD, 164	ER_RPL_REPLICA_SQL_THREAD_STARTING, 165
ER_RPL_REPLICA_GENERIC_MESSAGE, 156	ER_RPL_REPLICA_SQL_THREAD_STARTING_WITH_PRIVILE, 350
ER_RPL_REPLICA_GLOBAL_FILTERS_COPY_FAILED, 184	ER_RPL_REPLICA_SQL_THREAD_STOP_CMD_EXEC_TIMEOUT, 322
ER_RPL_REPLICA_INCORRECT_CHANNEL, 180	ER_RPL_REPLICA_STOPPING_AS_SOURCE_OOM, 164
ER_RPL_REPLICA_INSECURE_CHANGE_SOURCE, 180	ER_RPL_REPLICA_STOPPING_AS_SOURCE_OOM, 164
ER_RPL_REPLICA_IO_THREAD_ABORTED_WAITING_FOR, 164	ER_RPL_REPLICA_STOPPING_AS_SOURCE_OOM, 164
ER_RPL_REPLICA_IO_THREAD_CANT_REGISTER_ON, 164	ER_RPL_REPLICA_STOPPING_AS_SOURCE_OOM, 164



---

ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAILED_WITH_ERROR, 165	ER_SEC_FILE_PRIV_NO_ARGUMENT_TOO_LONG, 135
ER_RPL_REPO_HAS_GAPS, 130	ER_SEC_FILE_PRIV_CANT_ACCESS_DIR, 135
ER_RPL_REWRITEDB_EMPTY_FROM, 138	ER_SEC_FILE_PRIV_CANT_STAT, 135
ER_RPL_REWRITEDB_EMPTY_TO, 138	ER_SEC_FILE_PRIV_DIRECTORY_INSECURE, 135
ER_RPL_REWRITEDB_MISSING_ARROW, 138	ER_SEC_FILE_PRIV_DIRECTORY_PERMISSIONS, 135
ER_RPL_SERVER_ID_MISSING, 162	ER_SEC_FILE_PRIV_EMPTY, 135
ER_RPL_SSL_INFO_IN_CONNECTION_METADATA_IGNORED, 169	ER_SEC_FILE_PRIV_IGNORED, 135
ER_RPL_TRX_DELEGATES_INIT_FAILED, 142	ER_SEC_FILE_PRIV_NULL, 135
ER_RPL_UNEXPECTED_BEGIN_IN_STREAM, 158	ER_SEC_FILE_PRIV_NULL, 135
ER_RPL_UNEXPECTED_COMMIT_ROLLBACK_OR_XID_ERROR_IN_STREAM, 158	ER_SEMISYNC_ADD_ACK_TO_SLOT, 199
ER_RPL_UNEXPECTED_XA_ROLLBACK_IN_STREAM, 158	ER_SEMISYNC_BINLOG_REPLY_IS_AHEAD, 198
ER_RPL_UNSUPPORTED_UNIGNORABLE_EVENT_IN_STREAM, 158	ER_SEMISYNC_BINLOG_WRITE_OUT_OF_ORDER, 197
ER_RPL_WORKER_CANT_FIND_NEXT_RELAY_LOG, 168	ER_SEMISYNC_CLEARED_ACTIVE_TRANSACTION_TILL, 197
ER_RPL_WORKER_CANT_READ_RELAY_LOG, 168	ER_SEMISYNC_CLEARED_ALL_ACTIVE_TRANSACTION, 197
ER_RPL_WORKER_ID_IS, 155	ER_SEMISYNC_DISABLED_ON_SOURCE, 197
ER_RPL_ZOMBIE_ENCOUNTERED, 129	ER_SEMISYNC_EXECUTION_FAILED_ON_SOURCE, 200
ER_RUNNING_APPLIER_PREVENTS_SWITCH_GLOBAL_BENCHMARKS_FORMAT, 89	ER_SEMISYNC_FAILED_REGISTER_REPLICA_TO_RECEIVE, 199
ER_RUN_HOOK_ERROR, 64	ER_SEMISYNC_FAILED_TO_ALLOCATE_TRX_NODE, 196
ER_SAME_NAME_PARTITION, 34	ER_SEMISYNC_FAILED_TO_INSERT_TRX_NODE, 198
ER_SAME_NAME_PARTITION_FIELD, 41	ER_SEMISYNC_FAILED_TO_START_ACK_RECEIVER_THREAD, 199
ER_SCHEDULER_KILLING, 132	ER_SEMISYNC_FAILED_TO_STOP_ACK_RECEIVER_THREAD, 201
ER_SCHEDULER_STARTED, 132	ER_SEMISYNC_FAILED_TO_WAIT_ON_DUMP_SOCKET, 199
ER_SCHEDULER_STOPPED, 131	ER_SEMISYNC_FORCED_SHUTDOWN, 197
ER_SCHEDULER_STOPPING_FAILED_TO_CREATE_WORKER, 132	ER_SEMISYNC_FUNCTION_CALLED_TWICE, 197
ER_SCHEDULER_STOPPING_FAILED_TO_GET_EVENT, 132	ER_SEMISYNC_INIT_WAIT_POS, 198
ER_SCHEDULER_WAITING, 132	ER_SEMISYNC_INSERT_LOG_INFO_IN_ENTRY, 197
ER_SCHEMA_DIR_CREATE_FAILED, 84	ER_SEMISYNC_MISSING_MAGIC_NO_FOR_SEMISYNC_FORMAT, 200
ER_SCHEMA_DIR_EXISTS, 84	ER_SEMISYNC_MOVE_BACK_WAIT_POS, 198
ER_SCHEMA_DIR_MISSING, 84	ER_SEMISYNC_NOT_SUPPORTED_BY_SOURCE, 200
ER_SCHEMA_DIR_UNKNOWN, 84	ER_SEMISYNC_NO_SPACE_IN_THE_PKT, 198
ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED, 352	ER_SEMISYNC_PROBE_LOG_INFO_IN_ENTRY, 197
ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED_FORMAT, 352	ER_SEMISYNC_RECEIVED_ACK_IS_SMALLER, 199
ER_SCHEMA_READ_ONLY, 107	ER_SEMISYNC_REPLICA_NET_FLUSH_REPLY_FAILED, 200
ER_SDI_GET_KEYS_INVALID_TABLESPACE, 111	ER_SEMISYNC_REPLICA_REPLY, 200
ER_SDI_OPERATION_FAILED, 83	ER_SEMISYNC_REPLICA_REPLY_WITH_BINLOG_INFO, 200
ER_SDI_OPERATION_FAILED_MISSING_RECORD, 105	ER_SEMISYNC_REPLICA_SEND_REPLY_FAILED, 200
ER_SECONDARY_ENGINE, 99	ER_SEMISYNC_REPLICA_SET_FAILED, 200
ER_SECONDARY_ENGINE_DDL, 100	
ER_SECONDARY_ENGINE_DDL_FAILED, 394	
ER_SECONDARY_ENGINE_PLUGIN, 99	
ER_SECOND_PASSWORD_CANNOT_BE_EMPTY, 99	
ER_SECURE_AUTH_VALUE_UNSUPPORTED, 134	
ER_SECURE_TRANSPORT_REQUIRED, 69	

---

---

ER\_SEMISYNC\_REPLICA\_START, 200  
ER\_SEMISYNC\_REPLY\_BINLOG\_FILE\_TOO\_LARGE, 197  
ER\_SEMISYNC\_REPLY\_MAGIC\_NO\_ERROR, 197  
ER\_SEMISYNC\_REPLY\_PKT\_LENGTH\_TOO\_SMALL, 197  
ER\_SEMISYNC\_RPL\_ENABLED\_ON\_SOURCE, 197  
ER\_SEMISYNC\_RPL\_INIT\_FOR\_TRX, 196  
ER\_SEMISYNC\_RPL\_SWITCHED\_OFF, 198  
ER\_SEMISYNC\_RPL\_SWITCHED\_ON, 198  
ER\_SEMISYNC\_SERVER\_REPLY, 197  
ER\_SEMISYNC\_SOCKET\_FD\_TOO\_LARGE, 200  
ER\_SEMISYNC\_SOURCE\_FAILED\_ON\_NET\_FLUSH, 199  
ER\_SEMISYNC\_SOURCE\_GOT\_REPLY\_AT\_POS, 198  
ER\_SEMISYNC\_SOURCE\_OOM, 197  
ER\_SEMISYNC\_SOURCE\_SIGNAL\_ALL\_WAITING\_THREADS, 198  
ER\_SEMISYNC\_SOURCE\_TRX\_WAIT\_POS, 198  
ER\_SEMISYNC\_STARTING\_ACK\_RECEIVER\_THD, 199  
ER\_SEMISYNC\_START\_BINLOG\_DUMP\_TO\_REPLICA, 199  
ER\_SEMISYNC\_STOPPING\_ACK\_RECEIVER\_THREAD, 199  
ER\_SEMISYNC\_STOP\_BINLOG\_DUMP\_TO\_REPLICA, 199  
ER\_SEMISYNC\_SYNC\_HEADER\_UPDATE\_INFO, 198  
ER\_SEMISYNC\_TRACE\_ENTER\_FUNC, 196  
ER\_SEMISYNC\_TRACE\_EXIT, 196  
ER\_SEMISYNC\_TRACE\_EXIT\_WITH\_BOOL\_EXIT\_CODE, 196  
ER\_SEMISYNC\_TRACE\_EXIT\_WITH\_INT\_EXIT\_CODE, 196  
ER\_SEMISYNC\_TRX\_SKIPPED\_AT\_POS, 199  
ER\_SEMISYNC\_UNREGISTERED\_REPLICATOR, 200  
ER\_SEMISYNC\_UNREGISTER\_BINLOG\_STORAGE\_OBSERVER\_FAILED, 200  
ER\_SEMISYNC\_UNREGISTER\_BINLOG\_TRANSMIT\_OBSERVER\_FAILED, 200  
ER\_SEMISYNC\_UNREGISTER\_TRX\_OBSERVER\_FAILED, 199  
ER\_SEMISYNC\_UPDATE\_EXISTING\_REPLICA\_ACK, 199  
ER\_SEMISYNC\_WAIT\_FOR\_BINLOG\_TIMEDOUT, 198  
ER\_SEMISYNC\_WAIT\_TIME\_ASSESSMENT\_FOR\_COMMIT, 198  
ER\_SEMISYNC\_WAIT\_TIME\_FOR\_BINLOG\_SENT, 198  
ER\_SERVERID\_TOO\_LARGE, 141  
ER\_SERVER\_ACL\_TABLE\_ERROR, 326  
ER\_SERVER\_BINLOG\_MASTER\_KEY\_RECOVERY\_OUT\_OF\_SEQUENCE, 341  
ER\_SERVER\_BINLOG\_MASTER\_KEY\_ROTATION\_FAIL\_TO\_COPY, 341  
ER\_SERVER\_BINLOG\_UNSAFE\_SYSTEM\_FUNCTION, 344  
ER\_SERVER\_CANNOT\_LOAD\_FROM\_TABLE\_V2, 325  
ER\_SERVER\_CANT\_OPEN\_FILE, 325  
ER\_SERVER\_CERT\_VERIFY\_FAILED, 397  
ER\_SERVER\_COL\_COUNT\_DOESNT\_MATCH\_CORRUPTED\_INDEX, 326  
ER\_SERVER\_COL\_COUNT\_DOESNT\_MATCH\_PLEASE\_UPDATE, 326  
ER\_SERVER\_COST\_FAILED\_TO\_READ, 157  
ER\_SERVER\_COST\_INVALID\_COST\_CONSTANT, 157  
ER\_SERVER\_COST\_UNKNOWN\_COST\_CONSTANT, 157  
ER\_SERVER\_DISK\_FULL\_NOWAIT, 325  
ER\_SERVER\_DOWNGRADE\_FROM\_VERSION, 395  
ER\_SERVER\_DOWNGRADE\_STATUS, 395  
ER\_SERVER\_FILE\_NOT\_FOUND, 325  
ER\_SERVER\_FILE\_USED, 325  
ER\_SERVER\_GTID\_UNSAFE\_CREATE\_DROP\_TEMP\_TABLE\_IN\_TRANSACTION, 332  
ER\_SERVER\_HANDLER\_ERROR, 325  
ER\_SERVER\_INIT\_COMPILED\_IN\_COMMANDS, 192  
ER\_SERVER\_ISNT\_AVAILABLE, 69  
ER\_SERVER\_NET\_PACKET\_TOO\_LARGE, 325  
ER\_SERVER\_NEW\_ABORTING\_CONNECTION, 325  
ER\_SERVER\_NOT\_FORM\_FILE, 325  
ER\_SERVER\_NO\_SESSION\_TO\_SEND\_TO, 325  
ER\_SERVER\_NO\_SYSTEM\_TABLE\_ACCESS, 325  
ER\_SERVER\_OFFLINE\_MODE, 59  
ER\_SERVER\_OUTOFMEMORY, 182  
ER\_SERVER\_OUT\_OF\_RESOURCES, 182  
ER\_SERVER\_OUT\_OF\_SORTMEMORY, 325  
ER\_SERVER\_RECORD\_FILE\_FULL, 325  
ER\_SERVER\_RECOVER\_FAILED, 324  
ER\_SERVER\_RECOVER\_FAILED\_REPLICA\_AM\_INIT\_REPOSITORY, 324  
ER\_SERVER\_RECOVER\_FAILED\_REPLICA\_CM\_INIT\_REPOSITORY, 324  
ER\_SERVER\_REPLICA\_CONVERSION\_FAILED, 326  
ER\_SERVER\_REPLICA\_IGNORED\_TABLE, 326  
ER\_SERVER\_REPLICA\_INIT\_QUERY\_FAILED, 326  
ER\_SERVER\_RPL\_ENCRYPTION\_FAILED\_TO\_ENCRYPT, 335  
ER\_SERVER\_RPL\_ENCRYPTION\_FAILED\_TO\_FETCH\_KEY, 335  
ER\_SERVER\_RPL\_ENCRYPTION\_FAILED\_TO\_GENERATE\_KEY, 335  
ER\_SERVER\_RPL\_ENCRYPTION\_FAILED\_TO\_REMOVE\_KEY, 335  
ER\_SERVER\_RPL\_ENCRYPTION\_FAILED\_TO\_REMOVE\_KEY\_OF\_COMBINATION, 335

---

ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ROTATE_KEYS, 335	ER_SERVER_UPGRADE_VERSION_NOT_SUPPORTED, 339
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_STORE_KEYS, 335	ER_SERVER_WARN_DEPRECATED, 341
ER_SERVER_RPL_ENCRYPTION_HEADER_ERROR, 335	ER_SERVER_WRONG_VALUE_FOR_VAR, 332
ER_SERVER_RPL_ENCRYPTION_IGNORE_ROTATE_MASTER_KEY, 336	ER_SESSION_WAS_KILLED, 69
ER_SERVER_RPL_ENCRYPTION_KEYRING_INVALID_KEY, 335	ER_SETNS_FAILED, 344
ER_SERVER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED, 335	ER_SET_CONSTANTS_GROUP, 16
ER_SERVER_RPL_ENCRYPTION_KEY_NOT_FOUND, 335	ER_SET_EVENT_FAILED, 328
ER_SERVER_RPL_ENCRYPTION_MASTER_KEY_RECOVERED, 336	ER_SET_PASSWORD_AUTH_PLUGIN_ERROR, 116
ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_INITIALIZE, 336	ER_SET_STATEMENT_CANNOT_INVOKE_FUNCTION, 49
ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_ROTATE_MASTER_KEY, 336	ER_SE_TYPECODE_CONFLICT, 144
ER_SERVER_SHUTDOWN, 6	ER_SHA256_PASSWORD_SECOND_PASSWORD_USED, 332
ER_SERVER_SHUTDOWN_COMPLETE, 181	ER_SHARED_TABLESPACE_USED_BY_PARTITIONED_T, 205
ER_SERVER_SHUTDOWN_INFO, 328	ER_SHARED_TABLESPACE_USED_BY_PARTITIONED_T, 205
ER_SERVER_SOURCE_FATAL_ERROR_READING_BINLOG, 324	ER_SHA_PWD_FAILED_TO_GENERATE_MULTI_ROUND, 205
ER_SERVER_STARTUP_ADMIN_INTERFACE, 336	ER_SHA_PWD_FAILED_TO_PARSE_AUTH_STRING, 206
ER_SERVER_STARTUP_MSG, 182	ER_SHA_PWD_RSA_KEY_TOO_LONG, 205
ER_SERVER_TABLE_CHECK_FAILED, 326	ER_SHA_PWD_SALT_FOR_USER_CORRUPT, 206
ER_SERVER_TEST_MESSAGE, 326	ER_SHUTDOWN_COMPLETE, 8
ER_SERVER_UNKNOWN_SYSTEM_VARIABLE, 325	ER_SHUTTING_DOWN_REPLICA_THREADS, 136
ER_SERVER_UPGRADE_CHECKING_DB, 343	ER_SIGNAL_BAD_CONDITION_TYPE, 40
ER_SERVER_UPGRADE_EMPTY_SYS, 343	ER_SIGNAL_EXCEPTION, 40
ER_SERVER_UPGRADE_FAILED, 342	ER_SIGNAL_NOT_FOUND, 40
ER_SERVER_UPGRADE_FROM_VERSION, 339	ER_SIGNAL_WARN, 40
ER_SERVER_UPGRADE_HELP_TABLE_STATUS, 344	ER_SIMULATED_INJECTION_ERROR, 122
ER_SERVER_UPGRADE_INFO_FILE, 343	ER_SIZE_OVERFLOW_ERROR, 35
ER_SERVER_UPGRADE_MYSQL_TABLES, 343	ER_SKIP_UPDATING_METADATA_IN_SE_RO_MODE, 188
ER_SERVER_UPGRADE_NO_SYS_VERSION, 343	ER_SLOW_LOG_MODE_IGNORED_WHEN_NOT_LOGGING, 93
ER_SERVER_UPGRADE_OFF, 342	ER_SOURCE, 15
ER_SERVER_UPGRADE_PENDING, 342	ER_SOURCE_DELAY_VALUE_OUT_OF_RANGE, 46
ER_SERVER_UPGRADE_REPAIR_REQUIRED, 342	ER_SOURCE_FATAL_ERROR_READING_BINLOG, 18
ER_SERVER_UPGRADE_REPAIR_STATUS, 343	ER_SOURCE_HAS_PURGED_REQUIRED_GTIDS, 50
ER_SERVER_UPGRADE_SKIP, 342	ER_SOURCE_NET_READ, 15
ER_SERVER_UPGRADE_STATUS, 342	ER_SOURCE_NET_WRITE, 15
ER_SERVER_UPGRADE_SYSTEM_TABLES, 343	ER_SPATIAL_CANT_HAVE_NULL, 19
ER_SERVER_UPGRADE_SYS_SCHEMA, 343	ER_SPATIAL_FUNCTIONAL_INDEX, 90
ER_SERVER_UPGRADE_SYS_SCHEMA_OBJECT_COUNT, 343	ER_SPATIAL_MUST_HAVE_GEOM_COL, 43
ER_SERVER_UPGRADE_SYS_SCHEMA_OUTDATED, 343	ER_SPATIAL_UNIQUE_INDEX, 87
ER_SERVER_UPGRADE_SYS_SCHEMA_UP_TO_DATE, 343	ER_SPECIFIC_ACCESS_DENIED, 124
ER_SERVER_UPGRADE_SYS_VERSION_EMPTY, 343	ER_SPECIFIC_ACCESS_DENIED_ERROR, 17
	ER_SPVAR_NONINTEGER_TYPE, 109
	ER_SP_ALREADY_EXISTS, 22
	ER_SP_BADRETURN, 22
	ER_SP_BADSELECT, 22

---

---

ER\_SP\_BADSTATEMENT, 22  
 ER\_SP\_BAD\_CURSOR\_QUERY, 23  
 ER\_SP\_BAD\_CURSOR\_SELECT, 23  
 ER\_SP\_BAD\_SQLSTATE, 27  
 ER\_SP\_BAD\_VAR\_SHADOW, 30  
 ER\_SP\_CANT\_ALTER, 23  
 ER\_SP\_CANT\_SET\_AUTOCOMMIT, 30  
 ER\_SP\_CASE\_NOT\_FOUND, 24  
 ER\_SP\_COND\_MISMATCH, 22  
 ER\_SP\_CURSOR\_AFTER\_HANDLER, 24  
 ER\_SP\_CURSOR\_ALREADY\_OPEN, 23  
 ER\_SP\_CURSOR\_MISMATCH, 23  
 ER\_SP\_CURSOR\_NOT\_OPEN, 23  
 ER\_SP\_DOES\_NOT\_EXIST, 22  
 ER\_SP\_DROP\_FAILED, 22  
 ER\_SP\_DUP\_COND, 23  
 ER\_SP\_DUP\_CURS, 23  
 ER\_SP\_DUP\_HANDLER, 28  
 ER\_SP\_DUP\_PARAM, 23  
 ER\_SP\_DUP\_VAR, 23  
 ER\_SP\_FETCH\_NO\_DATA, 23  
 ER\_SP\_LABEL\_MISMATCH, 22  
 ER\_SP\_LABEL\_REDEFINE, 22  
 ER\_SP\_LILABEL\_MISMATCH, 22  
 ER\_SP\_LOAD\_FAILED, 73  
 ER\_SP\_NORETURN, 23  
 ER\_SP\_NORETURNEND, 23  
 ER\_SP\_NOT\_VAR\_ARG, 28  
 ER\_SP\_NO\_AGGREGATE, 31  
 ER\_SP\_NO\_ALTER\_LANGUAGE, 122  
 ER\_SP\_NO\_DROP\_SP, 25  
 ER\_SP\_NO\_RECURSION, 28  
 ER\_SP\_NO\_RECURSIVE\_CREATE, 21  
 ER\_SP\_NO\_RESET, 28  
 ER\_SP\_RECURSION\_LIMIT, 30  
 ER\_SP\_STORE\_FAILED, 22  
 ER\_SP\_SUBSELECT\_NYI, 23  
 ER\_SP\_UNDECLARED\_VAR, 23  
 ER\_SP\_UNINIT\_VAR, 22  
 ER\_SP\_VARCOND\_AFTER\_CURSHNDLR, 24  
 ER\_SP\_WRONG\_NAME, 30  
 ER\_SP\_WRONG\_NO\_OF\_ARGS, 22  
 ER\_SP\_WRONG\_NO\_OF\_FETCH\_ARGS, 23  
 ER\_SQLTHREAD\_WITH\_SECURE\_REPLICA, 48  
 ER\_SQL\_AUTHOR\_DEFAULT\_ROLES\_FAIL, 144  
 ER\_SQL\_HA\_READ\_FAILED, 142  
 ER\_SQL\_MODE\_MERGED, 67  
 ER\_SQL\_MODE\_MERGED\_WITH\_STRICT\_MODE,  
 181  
 ER\_SQL\_REPLICA\_SKIP\_COUNTER\_USED\_WITH\_GTID,  
 109  
 ER\_SQL\_USER\_TABLE ALTER WARNING, 144  
 ER\_SQL\_USER\_TABLE\_CREATE WARNING, 144  
 ER\_SRS\_ATTRIBUTE\_STRING\_TOO\_LONG, 87  
 ER\_SRS\_GEOGCS\_INVALID\_AXES, 88  
 ER\_SRS\_ID\_ALREADY\_EXISTS, 86  
 ER\_SRS\_INVALID\_ANGULAR\_UNIT, 88  
 ER\_SRS\_INVALID\_CHARACTER\_IN\_ATTRIBUTE,  
 87  
 ER\_SRS\_INVALID\_HEIGHT, 118  
 ER\_SRS\_INVALID\_INVERSE\_FLATTENING, 88  
 ER\_SRS\_INVALID\_LATITUDE\_OF\_ORIGIN, 117  
 ER\_SRS\_INVALID\_LATITUDE\_POLAR\_STERE\_VAR\_A,  
 118  
 ER\_SRS\_INVALID\_LONGITUDE\_OF\_ORIGIN, 117  
 ER\_SRS\_INVALID\_PRIME\_MERIDIAN, 88  
 ER\_SRS\_INVALID\_SCALING, 118  
 ER\_SRS\_INVALID\_SEMI\_MAJOR\_AXIS, 88  
 ER\_SRS\_INVALID\_ZONE\_WIDTH, 118  
 ER\_SRS\_MISSING\_MANDATORY\_ATTRIBUTE,  
 86  
 ER\_SRS\_MULTIPLE\_ATTRIBUTE\_DEFINITIONS,  
 86  
 ER\_SRS\_NAME\_CANT\_BE\_EMPTY\_OR\_WHITESPACE,  
 86  
 ER\_SRS\_NOT\_CARTESIAN, 73  
 ER\_SRS\_NOT\_CARTESIAN\_UNDEFINED, 74  
 ER\_SRS\_NOT\_FOUND, 75  
 ER\_SRS\_NOT\_GEOGRAPHIC, 87  
 ER\_SRS\_ORGANIZATION\_CANT\_BE\_EMPTY\_OR\_WHITESPACE,  
 86  
 ER\_SRS\_PARSE\_ERROR, 73  
 ER\_SRS\_PROJ\_PARAMETER\_MISSING, 73  
 ER\_SRS\_UNUSED\_PROJ\_PARAMETER\_PRESENT,  
 117  
 ER\_SRV\_END, 397  
 ER\_SRV\_INIT\_END, 397  
 ER\_SRV\_INIT\_START, 397  
 ER\_SRV\_START, 397  
 ER\_SR\_BOGUS\_VALUE, 142  
 ER\_SR\_INVALID\_CONTEXT, 142  
 ER\_SSL\_FIPS\_MODE\_ERROR, 206  
 ER\_SSL\_LIBRARY\_ERROR, 133  
 ER\_SSL\_MEMORY\_INSTRUMENTATION\_INIT\_FAILED,  
 333  
 ER\_SSL\_TRYING\_DATADIR\_DEFAULTS, 140  
 ER\_STACKSIZE\_UNEXPECTED, 140  
 ER\_STACK\_BACKTRACE, 386  
 ER\_STACK\_OVERRUN, 11  
 ER\_STACK\_OVERRUN\_NEED\_MORE, 29  
 ER\_STARTING\_AS, 136  
 ER\_STARTING\_INIT, 328  
 ER\_STARTING\_REPLICA\_MONITOR\_IO\_THREAD,  
 109  
 ER\_STARTUP, 27  
 ER\_START\_REPLICA\_CHANNEL\_INVALID\_CONFIGURATION,  
 399  
 ER\_START\_REPLICA\_CHANNEL\_INVALID\_CONFIGURATION,  
 399  
 ER\_STATEMENT\_NOT\_ALLOWED\_AFTER\_START\_TRANSACTION,  
 106  
 ER\_STD\_BAD\_ALLOC\_ERROR, 60  
 ER\_STD\_DOMAIN\_ERROR, 60  
 ER\_STD\_INVALID\_ARGUMENT, 60  
 ER\_STD\_LENGTH\_ERROR, 60

---

ER\_STD\_LOGIC\_ERROR, 61  
 ER\_STD\_OUT\_OF\_RANGE\_ERROR, 60  
 ER\_STD\_OVERFLOW\_ERROR, 60  
 ER\_STD\_RANGE\_ERROR, 60  
 ER\_STD\_REGEX\_ERROR, 97  
 ER\_STD\_RUNTIME\_ERROR, 61  
 ER\_STD\_UNDERFLOW\_ERROR, 61  
 ER\_STD\_UNKNOWN\_EXCEPTION, 61  
 ER\_STMT\_CACHE\_FULL, 44  
 ER\_STMT\_HAS\_NO\_OPEN\_CURSOR, 28  
 ER\_STMT\_NOT\_ALLOWED\_IN\_SF\_OR\_TRG, 24  
 ER\_STOP\_REPLICA\_IO\_THREAD\_DISK\_SPACE, 206  
 ER\_STOP\_REPLICA\_IO\_THREAD\_TIMEOUT, 56  
 ER\_STOP\_REPLICA\_MONITOR\_IO\_THREAD\_TIMEOUT, 109  
 ER\_STOP\_REPLICA\_SQL\_THREAD\_TIMEOUT, 56  
 ER\_STORAGE\_ENGINE\_NOT\_LOADED, 57  
 ER\_STORED\_FUNCTION\_PREVENTS\_SWITCH\_BINLOG\_FORMAT, 43  
 ER\_STORED\_FUNCTION\_PREVENTS\_SWITCH\_BINLOG\_FORMAT, 36  
 ER\_STORED\_FUNCTION\_PREVENTS\_SWITCH\_SQL\_LOG\_BIN, 44  
 ER\_SUBPARTITION\_ERROR, 33  
 ER\_SUBPARTITION\_NAME, 40  
 ER\_SUBQUERY\_NO\_1\_ROW, 18  
 ER\_SUBQUERY\_TRANSFORM\_REJECTED, 106  
 ER\_SUPPORTED\_ONLY\_WITH\_HYPERGRAPH, 124  
 ER\_SWITCH\_TMP\_ENGINE, 77  
 ER\_SYNTAX\_ERROR, 13  
 ER\_SYSTEMD\_NOTIFY\_CONNECT\_FAILED, 246  
 ER\_SYSTEMD\_NOTIFY\_DEBUG, 385  
 ER\_SYSTEMD\_NOTIFY\_PATH\_TOO\_LONG, 246  
 ER\_SYSTEMD\_NOTIFY\_WRITE\_FAILED, 246  
 ER\_SYSTEM\_SCHEMA\_NOT\_FOUND, 129  
 ER\_SYSTEM\_TABLES\_NOT\_SUPPORTED\_BY\_STORAGE\_ENGINE, 182  
 ER\_SYSTEM\_TABLE\_NOT\_TRANSACTIONAL, 169  
 ER\_SYSTEM\_VIEW\_INIT\_FAILED, 183  
 ER\_SYSVAR\_CHANGE\_DURING\_QUERY, 101  
 ER\_SYS\_VAR\_COMPONENT\_FAILED\_TO\_MAKE\_VARIABLE\_DYNAMIC, 206  
 ER\_SYS\_VAR\_COMPONENT\_FAILED\_TO\_PARSE\_VARIABLE\_OPTION, 206  
 ER\_SYS\_VAR\_COMPONENT\_OOM, 206  
 ER\_SYS\_VAR\_COMPONENT\_UNKNOWN\_VARIABLE\_TYPE, 206  
 ER\_SYS\_VAR\_COMPONENT\_VARIABLE\_SET\_READ\_ONLY, 206  
 ER\_SYS\_VAR\_DEREGISTRATION, 393  
 ER\_SYS\_VAR\_NOT\_FOUND, 329  
 ER\_SYS\_VAR\_REGISTRATION, 393  
 ER\_TABLEACCESS\_DENIED\_ERROR, 12  
 ER\_TABLENAME\_NOT\_ALLOWED\_HERE, 18  
 ER\_TABLESPACE\_AUTO\_EXTEND\_ERROR, 35  
 ER\_TABLESPACE\_CANNOT\_BE\_DECRYPTED, 95  
 ER\_TABLESPACE\_CANNOT\_BE\_ENCRYPTED, 95  
 ER\_TABLESPACE\_CANNOT\_ENCRYPT, 70  
 ER\_TABLESPACE\_DISCARDED, 52  
 ER\_TABLESPACE\_DUP\_FILENAME, 79  
 ER\_TABLESPACE\_ENGINE\_MISMATCH, 82  
 ER\_TABLESPACE\_EXISTS, 52  
 ER\_TABLESPACE\_IS\_NOT\_EMPTY, 66  
 ER\_TABLESPACE\_MISSING, 52  
 ER\_TABLESPACE\_MISSING\_WITH\_NAME, 73  
 ER\_TABLESPACE\_TYPE\_UNKNOWN, 96  
 ER\_TABLES\_DIFFERENT\_METADATA, 47  
 ER\_TABLE\_CANT\_HANDLE\_AUTO\_INCREMENT, 13  
 ER\_TABLE\_CANT\_HANDLE\_BLOB, 13  
 ER\_TABLE\_CANT\_HANDLE\_FT, 16  
 ER\_TABLE\_CANT\_HANDLE\_SPKEYS, 31  
 ER\_TABLE\_CHECK\_INTACT, 141  
 ER\_TABLE\_CORRUPT, 56  
 ER\_TABLE\_CREATED\_WITH\_DIFFERENT\_VERSION, 102  
 ER\_TABLE\_DEF\_CHANGED, 28  
 ER\_TABLE\_EXISTS\_ERROR, 6  
 ER\_TABLE\_HAS\_NO\_FT, 48  
 ER\_TABLE\_INCOMPATIBLE\_DECIMAL\_FIELD, 151  
 ER\_TABLE\_INCOMPATIBLE\_YEAR\_FIELD, 151  
 ER\_TABLE\_IN\_FK\_CHECK, 46  
 ER\_TABLE\_IN\_SHARED\_TABLESPACE, 118  
 ER\_TABLE\_IN\_SYSTEM\_TABLESPACE, 52  
 ER\_TABLE\_MUST\_HAVE\_A\_VISIBLE\_COLUMN, 110  
 ER\_TABLE\_MUST\_HAVE\_COLUMNS, 10  
 ER\_TABLE\_NAME, 40  
 ER\_TABLE\_NAME\_CAUSES\_TOO\_LONG\_PATH, 61  
 ER\_TABLE\_NAME\_IN\_UPPER\_CASE\_NOT\_ALLOWED, 352  
 ER\_TABLE\_NAME\_IN\_UPPER\_CASE\_NOT\_ALLOWED\_FOR\_CHARSET, 352  
 ER\_TABLE\_NEEDS\_DUMP\_UPGRADE, 193  
 ER\_TABLE\_NEEDS\_REBUILD, 44  
 ER\_TABLE\_NEEDS\_UPGRADE, 30  
 ER\_TABLE\_OPTIONS\_EMPTY, 118  
 ER\_TABLE\_NOT\_LOCKED, 9  
 ER\_TABLE\_NOT\_LOCKED\_FOR\_WRITE, 9  
 ER\_TABLE\_NO\_PRIMARY\_KEY, 118  
 ER\_TABLE\_REFERENCED, 71  
 ER\_TABLE\_SCHEMA\_MISMATCH, 52  
 ER\_TABLE\_UPGRADE\_REQUIRED, 182  
 ER\_TABLE\_VALUE\_CONSTRUCTOR\_CANNOT\_HAVE\_DEFAULT, 103  
 ER\_TABLE\_VALUE\_CONSTRUCTOR\_MUST\_HAVE\_COLUMN, 103  
 ER\_TABLE\_WITHOUT\_PK, 89  
 ER\_TABLE\_WRONG\_KEY\_DEFINITION, 152

---

---

ER_TARGET_TABLESPACE_UNENCRYPTED, 96	ER_THREAD_POOL_NOT_SUPPORTED_ON_PLATFORM, 194
ER_TC_BAD_MAGIC_IN_TC_LOG, 160	ER_THREAD_POOL_PFS_TABLES_ADD_FAILED, 335
ER_TC_CANT_AUTO_RECOVER_WITH_TC_HEURISTIC_RECOVERY, 160	ER_THREAD_POOL_PFS_TABLES_INIT_FAILED, 334
ER_TC_HEURISTIC_RECOVERY_FAILED, 161	ER_THREAD_POOL_PLUGIN_STARTED, 379
ER_TC_HEURISTIC_RECOVERY_MODE, 161	ER_THREAD_POOL_QUERY_THREADS_PER_GROUP_INVALID, 387
ER_TC_NEED_N_SE_SUPPORTING_2PC_FOR_RECOVERY, 160	ER_THREAD_POOL_QUERY_THRS_PER_GRP_EXCEEDS_THREADS, 385
ER_TC_RECOVERING_AFTER_CRASH_USING, 160	ER_THREAD_POOL_RATE_LIMITED_ERROR_MSGS, 335
ER_TC_RECOVERY_FAILED_THese_Are_Your_Options, 161	ER_THREAD_POOL_SIZE_TOO_HIGH, 194
ER_TC_RESTART_WITHOUT_TC_HEURISTIC_RECOVERY, 161	ER_THREAD_POOL_SIZE_TOO_LOW, 194
ER_TELEMETRY_ERROR, 397	ER_THREAD_POOL_SYSVAR_CHANGE, 386
ER_TELEMETRY_INFO, 397	ER_THREAD_PRIORITY_IGNORED, 180
ER_TELEMETRY_WARNING, 397	ER_THREAD_STILL_ALIVE, 398
ER_TEMPORARY_NAME, 40	ER_TLS_CONFIGURATION_REUSED, 358
ER_TEMP_FILE_WRITE_FAILURE, 56	ER_TLS_CONFIGURATION_NOT_CONFIGURED_FOR_CHANNEL, 358
ER_TEMP_TABLE_PREVENTS_SWITCH_GLOBAL_BINLOG_FORMAT, 89	ER_TLS_LIBRARY_ERROR_INTERNAL, 397
ER_TEMP_TABLE_PREVENTS_SWITCH_SESSION_BINLOG_FORMAT, 89	ER_TLS_PATH_TOO_LONG, 362
ER_TEXTFILE_NOT_READABLE, 8	ER_TMP_SESSION_FOR_VAR, 385
ER_TF_FORBIDDEN_JOIN_TYPE, 83	ER_TOO_BIG_DISPLAYWIDTH, 29
ER_TF_MUST_HAVE_ALIAS, 83	ER_TOO_BIG_ENUM, 72
ER_THE_USER_ABIDES, 138	ER_TOO_BIG_FIELDLENGTH, 8
ER_THREAD_HANDLING_OOM, 134	ER_TOO_BIG_FOR_UNCOMPRESS, 19
ER_THREAD_POOL_ALGORITHM_INVALID, 194	ER_TOO_BIG_PRECISION, 28
ER_THREAD_POOL_BUFFER_TOO_SMALL, 195	ER_TOO_BIG_ROW_SIZE, 10
ER_THREAD_POOL_CANNOT_REGISTER_DYNAMIC_PLUGIN, 385	ER_TOO_BIG_SCALE, 28
ER_THREAD_POOL_CANNOT_SET_THREAD_SPECIFIC_DATA, 195	ER_TOO_BIG_SELECT, 10
ER_THREAD_POOL_CONNECTION_REPORT, 394	ER_TOO_BIG_SET, 9
ER_THREAD_POOL_CON_HANDLER_INIT_FAILED, 195	ER_TOO_HIGH_LEVEL_OF_NESTING_FOR_SELECT, 31
ER_THREAD_POOL_DEDICATED_LISTENERS_INVALID, 379	ER_TOO_LONG_BODY, 29
ER_THREAD_POOL_FAILED_PROCESS_CONNECT_EVENT, 195	ER_TOO_LONG_FIELD_COMMENT, 39
ER_THREAD_POOL_FAILED_TO_CREATE_CONNECT_HANDLER, 195	ER_TOO_LONG_IDENT, 7
ER_THREAD_POOL_FAILED_TO_CREATE_POOL, 195	ER_TOO_LONG_INDEX_COMMENT, 43
ER_THREAD_POOL_FAILED_TO_CREATE_THD_AND_ATTRIBUTES, 195	ER_TOO_LONG_KEY, 7
ER_THREAD_POOL_IDLE_CONNECTION_CLOSED, 390	ER_TOO_LONG_ROUTINE_COMMENT, 73
ER_THREAD_POOL_INIT_FAILED, 195	ER_TOO_LONG_SET_ENUM_VALUE, 72
ER_THREAD_POOL_INVALID_PRIO_KICKUP_TIMER, 194	ER_TOO_LONG_STRING, 13
ER_THREAD_POOL_INVALID_STALL_LIMIT, 194	ER_TOO_LONG_TABLESPACE_COMMENT, 79
ER_THREAD_POOL_LOW_LEVEL_REARM_FAILED, 195	ER_TOO_LONG_TABLE_COMMENT, 39
ER_THREAD_POOL_MAX_UNUSED_THREADS_INVALID, 195	ER_TOO_LONG_TABLE_PARTITION_COMMENT, 50
	ER_TOO_MANY_CONCURRENT_TRXS, 40
	ER_TOO_MANY_FIELDS, 10
	ER_TOO_MANY_GROUP_BY_MODIFIER_BRANCHES, 124
	ER_TOO_MANY_KEYS, 7
	ER_TOO_MANY_KEY_PARTS, 7
	ER_TOO_MANY_PARTITIONS_ERROR, 33
	ER_TOO_MANY_PARTITION_FUNC_FIELDS_ERROR, 41
	ER_TOO_MANY_ROWS, 14
	ER_TOO_MANY_STORAGE_ENGINES, 144
	ER_TOO_MANY_TABLES, 10

---

---

ER_TOO_MANY_USER_CONNECTIONS, 15	ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE_ID
ER_TOO_MANY_VALUES_ERROR, 41	153
ER_TOO_MANY_WINDOWS, 115	ER_TZ_CANT_OPEN_AND_LOCK_TIME_ZONE_TABLE,
ER_TP_QUERY_THRS_PER_GRP_EXCEEDS_TXN_THR	52
118	ER_TZ_ERROR_LOADING_LEAP_SECOND_TABLE,
ER_TRACK_VARIABLES_BOGUS, 138	153
ER_TRANSACTION_ROLLBACK_DURING_COMMIT,	ER_TZ_NO_TRANSITION_TYPES_IN_TIME_ZONE,
64	153
ER_TRANSFORM_SOURCE_SRS_MISSING_TOWGS84,	ER_TZ_OOM_INITIALIZING_TIME_ZONES, 152
89	ER_TZ_OOM_LOADING_LEAP_SECOND_TABLE,
ER_TRANSFORM_SOURCE_SRS_NOT_SUPPORTED,	152
88	ER_TZ_OOM_LOADING_TIME_ZONE_DESCRIPTION,
ER_TRANSFORM_TARGET_SRS_MISSING_TOWGS84,	153
89	ER_TZ_OOM_WHILE_LOADING_TIME_ZONE, 154
ER_TRANSFORM_TARGET_SRS_NOT_SUPPORTED,	ER_TZ_OOM_WHILE_SETTING_TIME_ZONE, 154
89	ER_TZ_TOO_MANY_LEAPS_IN_LEAP_SECOND_TABLE,
ER_TRANSPORTS_WHAT_TRANSPORTS, 137	152
ER_TRANS_CACHE_FULL, 15	ER_TZ_TRANSITION_TABLE_BAD_TRANSITION_TYPE,
ER_TREE_CORRUPT_2_CONSECUTIVE_REDS,	153
167	ER_TZ_TRANSITION_TABLE_LOAD_ERROR, 153
ER_TREE_CORRUPT_INCORRECT_BLACK_COUNT,	ER_TZ_TRANSITION_TABLE_TOO_MANY_TRANSITIONS,
168	153
ER_TREE_CORRUPT_PARENT_SHOULD_POINT_AT_PAREN	153
167	ER_TZ_TRANSITION_TYPE_TABLE_ABBREVIATIONS_EX
ER_TREE_CORRUPT_RIGHT_IS_LEFT, 168	153
ER_TREE_CORRUPT_ROOT_SHOULD_BE_BLACK,	153
167	ER_TZ_TRANSITION_TYPE_TABLE_TYPE_TOO_LARGE,
ER_TRG_ALREADY_EXISTS, 25	153
ER_TRG_CANT_CHANGE_ROW, 25	ER_TZ_UNKNOWN_OR_ILLEGAL_DEFAULT_TIME_ZONE
ER_TRG_CANT_OPEN_TABLE, 38	153
ER_TRG_CANT_PARSE, 141	ER_UDF_ALREADY_EXISTS, 328
ER_TRG_CORRUPTED_FILE, 38	ER_UDF_CANT_ALLOC_FOR_FUNCTION, 143
ER_TRG_CREATION_CTX_NOT_SET, 181	ER_UDF_CANT_ALLOC_FOR_STRUCTURES, 143
ER_TRG_DOES_NOT_EXIST, 25	ER_UDF_CANT_OPEN_FUNCTION_TABLE, 143
ER_TRG_INVALID_CREATION_CTX, 38	ER_UDF_DEREGISTRATION, 393
ER_TRG_IN_WRONG_SCHEMA, 29	ER_UDF_DROP_DYNAMICALLY_REGISTERED,
ER_TRG_NO_CLIENT_CHARSET, 132	80
ER_TRG_NO_CREATION_CTX, 38	ER_UDF_ERROR, 71
ER_TRG_NO_DEFINER, 30	ER_UDF_EXEC_FAILURE, 393
ER_TRG_NO_SUCH_ROW_IN_TRG, 25	ER_UDF_EXEC_FAILURE_REASON, 393
ER_TRG_ON_VIEW_OR_TEMP_TABLE, 25	ER_UDF_EXISTS, 11
ER_TRG_WITHOUT_DEFINER, 132	ER_UDF_INVALID_ROW_IN_FUNCTION_TABLE,
ER_TRG_WRONG_ORDER, 339	143
ER_TRHEAD_POOL_LOW_LEVEL_INIT_FAILED,	ER_UDF_NO_PATHS, 11
195	ER_UDF_REGISTER_ERROR, 362
ER_TRIGGER_INVALID_VALUE, 128	ER_UDF_REGISTER_SERVICE_ERROR, 362
ER_TRUNCATED_WRONG_VALUE, 21	ER_UDF_REGISTRATION, 393
ER_TRUNCATED_WRONG_VALUE_FOR_FIELD,	ER_UDF_UNREGISTER_ERROR, 362
25	ER_UNKNOWN_AUTH_ID_OR_ACCESS_DENIED_FOR_GR
ER_TRUNCATE_ILLEGAL_FK, 44	96
ER_TRX_GTID_COLLECT_REJECT, 144	ER_UNABLE_TO_BUILD_HISTOGRAM, 81
ER_TRX_WRITE_SET_OOM, 144	ER_UNABLE_TO_COLLECT_LOG_STATUS, 87
ER_TURNING_LOGGING_OFF_FOR_THE_DURATION,	ER_UNABLE_TO_DROP_COLUMN_STATISTICS,
178	81
ER_TURNING_ON_PARTIAL_REVOKES, 341	ER_UNABLE_TO_RESOLVE_HOSTNAME, 132
ER_TZ_CANT_BUILD_MKTIME_MAP, 154	ER_UNABLE_TO_RESOLVE_IP, 132
ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE,	ER_UNABLE_TO_SET_OPTION, 87
153	

---

---

ER\_UNABLE\_TO\_STORE\_COLUMN\_STATISTICS, 81  
ER\_UNABLE\_TO\_STORE\_STATISTICS, 76  
ER\_UNABLE\_TO\_UPDATE\_COLUMN\_STATISTICS, 81  
ER\_UNDISCLOSED\_PARSE\_ERROR\_IN\_DIGEST\_FN, 84  
ER\_UNDO\_RECORD\_TOO\_BIG, 45  
ER\_UNEXPECTED\_GEOMETRY\_TYPE, 73  
ER\_UNIQUE\_KEY\_NEED\_ALL\_FIELDS\_IN\_PF, 33  
ER\_UNIT\_NOT\_FOUND, 100  
ER\_UNKNOWN\_ALTER\_ALGORITHM, 51  
ER\_UNKNOWN\_ALTER\_LOCK, 51  
ER\_UNKNOWN\_AUTHID, 74  
ER\_UNKNOWN\_AUTH\_ID\_IN\_MANDATORY\_ROLE, 184  
ER\_UNKNOWN\_CHARACTER\_SET, 10  
ER\_UNKNOWN\_COLLATION, 20  
ER\_UNKNOWN\_COM\_ERROR, 6  
ER\_UNKNOWN\_ERROR, 10  
ER\_UNKNOWN\_ERROR\_DETECTED\_IN\_SE, 188  
ER\_UNKNOWN\_ERROR\_NUMBER, 143  
ER\_UNKNOWN\_EXPLAIN\_FORMAT, 50  
ER\_UNKNOWN\_KEY\_CACHE, 20  
ER\_UNKNOWN\_LOCALE, 41  
ER\_UNKNOWN\_NETWORK\_NAMESPACE, 344  
ER\_UNKNOWN\_PARTITION, 47  
ER\_UNKNOWN\_PROCEDURE, 10  
ER\_UNKNOWN\_STMT\_HANDLER, 18  
ER\_UNKNOWN\_STORAGE\_ENGINE, 21  
ER\_UNKNOWN\_SYSTEM\_VARIABLE, 15  
ER\_UNKNOWN\_TABLE, 10  
ER\_UNKNOWN\_TABLESPACE\_TYPE, 332  
ER\_UNKNOWN\_TABLE\_IN\_UPGRADE, 348  
ER\_UNKNOWN\_TARGET\_BINLOG, 26  
ER\_UNKNOWN\_TIME\_ZONE, 21  
ER\_UNKNOWN\_UNSUPPORTED\_STORAGE\_ENGINE, 133  
ER\_UNKNOWN\_VARIABLE\_IN\_PERSISTED\_CONFIG\_FILE, 329  
ER\_UNRESOLVED\_HINT\_NAME, 66  
ER\_UNRESOLVED\_TABLE\_LOCK, 77  
ER\_UNSUPPORTED\_LOG\_ENGINE, 37  
ER\_UNSUPPORTED\_ACTION\_ON\_DEFAULT\_VAL\_GENERATED, 91  
ER\_UNSUPPORTED\_ACTION\_ON\_GENERATED\_COLUMN, 65  
ER\_UNSUPPORTED\_ALTER\_ENCRYPTION\_INPLACE, 71  
ER\_UNSUPPORTED\_ALTER\_INPLACE\_ON\_VIRTUAL\_COLUMN, 64  
ER\_UNSUPPORTED\_ALTER\_ONLINE\_ON\_VIRTUAL\_COLUMN, 70  
ER\_UNSUPPORTED\_DATE, 136  
ER\_UNSUPPORTED\_ENGINE, 46  
ER\_UNSUPPORTED\_EXTENSION, 10  
ER\_UNSUPPORTED\_INDEX\_ALGORITHM, 72  
ER\_UNSUPPORTED\_PS, 21  
ER\_UNSUPPORTED\_SQL\_MODE, 100  
ER\_UNSUPPORTED\_USE\_OF\_GRANT\_AS, 96  
ER\_UNSUPPORTED\_COMPRESSED\_TEMPORARY\_TABLE, 72  
ER\_UNTIL\_COND\_IGNORED, 20  
ER\_UPDATE\_GTID\_PURGED\_WITH\_GR, 101  
ER\_UPDATE\_INFO, 12  
ER\_UPDATE\_LOG\_DEPRECATED\_IGNORED, 22  
ER\_UPDATE\_LOG\_DEPRECATED\_TRANSLATED, 22  
ER\_UPDATE\_TABLE\_USED, 9  
ER\_UPDATE\_WITHOUT\_KEY\_IN\_SAFE\_MODE, 14  
ER\_UPDATING\_DD\_TABLE, 73  
ER\_UPGRADE\_NONEXISTENT\_SCHEMA, 363  
ER\_UPGRADE\_PARSE\_ERROR, 332  
ER\_USAGE\_DEPRECATION\_COUNTER, 396  
ER\_USERNAME, 31  
ER\_USERNAME\_TRUNCATED, 358  
ER\_USER\_ACCESS\_DENIED\_FOR\_USER\_ACCOUNT\_BLOCK, 104  
ER\_USER\_ALREADY\_EXISTS, 69  
ER\_USER\_COLUMN\_OLD\_LENGTH, 71  
ER\_USER\_DOES\_NOT\_EXIST, 69  
ER\_USER\_LIMIT\_REACHED, 17  
ER\_USER\_LOCK\_DEADLOCK, 61  
ER\_USER\_LOCK\_OVERLONG\_NAME, 121  
ER\_USER\_LOCK\_WRONG\_NAME, 61  
ER\_USER\_NOT\_IN\_EXTRA\_USERS\_BINLOG\_POSSIBLY\_INC, 150  
ER\_USER\_REFERENCED\_AS\_DEFINER, 108  
ER\_USER\_REGISTRATION\_FAILED, 113  
ER\_USER\_REQUIRES\_ROOT, 136  
ER\_USER\_WHAT\_USER, 137  
ER\_USING\_ASSIGN\_GTIDS\_TO\_ANONYMOUS\_TRANSACTION, 110  
ER\_UUID\_INVALID, 133  
ER\_UUID\_IS, 133  
ER\_UUID\_SALT, 133  
ER\_UUID\_SCRUB, 133  
ER\_VALGRIND\_COUNT\_LEAKS, 143  
ER\_VALGRIND\_DO\_QUICK\_LEAK\_CHECK, 143  
ER\_VALIDATE\_PASSWORD\_INSUFFICIENT\_CHANGED\_CHARACTER, 204  
ER\_VALIDATE\_PWD\_CONVERT\_TO\_BUFFER\_FAILED, 204  
ER\_VALIDATE\_PWD\_COULD\_BE\_NULL, 247  
ER\_VALIDATE\_PWD\_DICT\_FILE\_NOT\_LOADED, 204  
ER\_VALIDATE\_PWD\_DICT\_FILE\_NOT\_SPECIFIED, 204  
ER\_VALIDATE\_PWD\_DICT\_FILE\_OPEN\_FAILED, 247  
ER\_VALIDATE\_PWD\_DICT\_FILE\_TOO\_BIG, 204  
ER\_VALIDATE\_PWD\_FAILED\_TO\_GET\_FLD\_FROM\_SECURITY\_CTX, 204  
ER\_VALIDATE\_PWD\_FAILED\_TO\_GET\_SECURITY\_CTX, 204

---



---

ER_VALIDATE_PWD_FAILED_TO_READ_DICT_FILE, 204	ER_WARNING_AUTHCACHE_INVALID_USER_ATTRIBUTES, 336
ER_VALIDATE_PWD_LENGTH_CHANGED, 204	ER_WARNING_DISCARD_OLD_PASSWORD_CLAUSE_VOID, 336
ER_VALIDATE_PWD_STATUS_VAR_REGISTRATION_FAILED, 246	ER_WARNING_NOT_COMPLETE_ROLLBACK, 15
ER_VALIDATE_PWD_STATUS_VAR_UNREGISTRATION_FAILED, 247	ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_CREATE, 47
ER_VALIDATE_PWD_STRING_CONV_TO_BUFFER_FAILED, 247	ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_DROP, 48
ER_VALIDATE_PWD_STRING_CONV_TO_LOWERCASE_FAILED, 247	ER_WARNING_PASSWORD_HISTORY_CLAUSES_VOID, 82
ER_VALIDATE_PWD_STRING_HANDLER_MEM_ALLOCATION_FAILED, 247	ER_WARNING_RETAIN_CURRENT_PASSWORD_CLAUSE_VOID, 336
ER_VALIDATE_PWD_STRONG_POLICY_DICT_FILE_UNSPECIFIED, 247	ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS, 112
ER_VALIDATE_PWD_VARIABLE_REGISTRATION_FAILED, 247	ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS, 371
ER_VALIDATE_PWD_VARIABLE_UNREGISTRATION_FAILED, 247	ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE, 112
ER_VALUES_IS_NOT_INT_TYPE_ERROR, 44	ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE, 371
ER_VALUE_OUT_OF_RANGE, 114	ER_WARN_ALLOWED_PACKET_OVERFLOWED, 21
ER_VARIABLE_IS_NOT_STRUCT, 20	ER_WARN_ASYNC_CONN_FAILOVER_NETWORK_NAME, 111
ER_VARIABLE_IS_READONLY, 39	ER_WARN_AUDIT_LOG_DISABLED, 377
ER_VARIABLE_NOT_PERSISTED, 75	ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP_ON, 112
ER_VARIABLE_NOT_SETTABLE_IN_SF_OR_TRIGGER, 49	ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP_ON, 372
ER_VARIABLE_NOT_SETTABLE_IN_SP, 53	ER_WARN_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_M, 351
ER_VARIABLE_NOT_SETTABLE_IN_TRANSACTION, 49	ER_WARN_BAD_MAX_EXECUTION_TIME, 66
ER_VAR_CANT_BE_READ, 18	ER_WARN_BINLOG_PARTIAL_UPDATES_DISABLED, 82
ER_VAR_DOES_NOT_EXIST, 80	ER_WARN_BINLOG_PARTIAL_UPDATES_SUGGESTS_PA, 82
ER_VERBOSE_HINT, 138	ER_WARN_CANNOT_FREE_COMPONENT_DATA_DEALL, 392
ER_VERBOSE_REQUIRES_HELP, 134	ER_WARN_CANNOT_PERSIST_SENSITIVE_VARIABLES, 378
ER_VIEW_CHECKSUM, 26	ER_WARN_CANNOT_SECURELY_PERSIST_SENSITIVE_V, 116
ER_VIEW_CHECK_FAILED, 25	ER_WARN_CANT_DROP_DEFAULT_KEYCACHE, 29
ER_VIEW_CREATION_CTX_NOT_SET, 181	ER_WARN_CANT_OPEN_CERTIFICATE, 396
ER_VIEW_DELETE_MERGE_VIEW, 27	ER_WARN_CA_CERT_VERIFY_FAILED, 396
ER_VIEW_FRM_NO_USER, 30	ER_WARN_CERTIFICATE_ERROR_STRING, 397
ER_VIEW_INVALID, 25	ER_WARN_CLIENT_DEPRECATED_PARTITION_PREFIX, 106
ER_VIEW_INVALID_CREATION_CTX, 38	ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFES, 391
ER_VIEW_MULTIUPDATE, 26	ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFES, 366
ER_VIEW_NONUPD_CHECK, 25	ER_WARN_COMPONENT_KEYRING_OCI_DUPLICATE_K, 386
ER_VIEW_NO_CREATION_CTX, 38	ER_WARN_CONFLICTING_HINT, 66
ER_VIEW_NO_EXPLAIN, 24	
ER_VIEW_NO_INSERT_FIELD_LIST, 26	
ER_VIEW_OTHER_USER, 30	
ER_VIEW_PREVENT_UPDATE, 29	
ER_VIEW_RECURSIVE, 31	
ER_VIEW_SELECT_CLAUSE, 24	
ER_VIEW_SELECT_TMPTABLE, 24	
ER_VIEW_SELECT_VARIABLE, 24	
ER_VIEW_UNKNOWN_CHARSET_OR_COLLATION, 129	
ER_VIEW_UNPARSABLE, 152	
ER_VIEW_WRONG_LIST, 25	
ER_VTOKEN_PLUGIN_TOKEN_MISMATCH, 67	
ER_VTOKEN_PLUGIN_TOKEN_NOT_FOUND, 67	
ER_WAITPID_FAILED, 192	

---

---

ER_WARN_C_DISABLE_GTID_ONLY_WITH_SOURCE_AUTO_POS_DISABLED, 114	ER_WARN_DEPRECATED_UTF8MB3_COLLATION, 91
ER_WARN_DATA_OUT_OF_RANGE, 19	ER_WARN_DEPRECATED_UTF8MB3_COLLATION_OPTION, 333
ER_WARN_DATA_OUT_OF_RANGE_FUNCTIONAL_INDEX, 89	ER_WARN_DEPRECATED_UTF8_ALIAS_OPTION, 332
ER_WARN_DATA_TRUNCATED_FUNCTIONAL_INDEX, 89	ER_WARN_DEPRECATED_VALUES_FUNCTION_ALWAYS_NULL, 105
ER_WARN_DA_PRIVILEGE_NOT_REGISTERED, 102	ER_WARN_DEPRECATED_WITH_NOTE, 121
ER_WARN_DEPRECATED_CHARSET_OPTION, 377	ER_WARN_DEPRECATED_YEAR_UNSIGNED, 104
ER_WARN_DEPRECATED_CLIENT_NO_SCHEMA_OPTION, 118	ER_WARN_DEPRECATED_ZEROFILL, 98
ER_WARN_DEPRECATED_COLLATION, 115	ER_WARN_ENGINE_TRANSACTION_ROLLBACK, 39
ER_WARN_DEPRECATED_COLLATION_OPTION, 377	ER_WARN_FAILED_TO_SETUP_TLS, 396
ER_WARN_DEPRECATED_DATETIME_DELIMITER, 116	ER_WARN_FIELD_RESOLVED, 20
ER_WARN_DEPRECATED_DYNAMIC_PRIV_FOR_USER, 398	ER_WARN_FUNC_INDEX_NOT_APPLICABLE, 101
ER_WARN_DEPRECATED_DYNAMIC_PRIV_IN_GRANTER, 122	ER_WARN_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIABLE, 371
ER_WARN_DEPRECATED_ENGINE_SYNTAX_NO_REPLACEMENT, 124	ER_WARN_GTID_THRESHOLD_BREACH, 365
ER_WARN_DEPRECATED_FLOAT_AUTO_INCREMENT, 97	ER_WARN_HOSTNAME_WONT_WORK, 20
ER_WARN_DEPRECATED_FLOAT_DIGITS, 97	ER_WARN_INCREMENTAL_HYPERGRAPH_EXPERIMENTAL, 108
ER_WARN_DEPRECATED_FLOAT_UNSIGNED, 98	ER_WARN_INCORRECT_PRIVILEGE_FOR_DB_RESTRICTION, 342
ER_WARN_DEPRECATED_FOUND_ROWS, 105	ER_WARN_INDEX_NOT_APPLICABLE, 47
ER_WARN_DEPRECATED_IDENT, 118	ER_WARN_INVALID_DB_RESTRICTIONS, 342
ER_WARN_DEPRECATED_INNER_INTO, 105	ER_WARN_INVALID_HINT, 80
ER_WARN_DEPRECATED_INTEGER_DISPLAY_WIDTH, 98	ER_WARN_INVALID_TIMESTAMP, 21
ER_WARN_DEPRECATED_JSON_TABLE_ON_ERROR, 105	ER_WARN_I_S_SKIPPED_TABLE, 43
ER_WARN_DEPRECATED_NESTED_COMMENT_SYNTAX, 91	ER_WARN_LEGACY_SYNTAX_CONVERTED, 57
ER_WARN_DEPRECATED_OR_BLOCKED_CIPHER, 396	ER_WARN_LOG_DEPRECATED_PARTITION_PREFIX_KEY, 357
ER_WARN_DEPRECATED_SQLMODE, 63	ER_WARN_LOG_PRIVILEGE_CHECKS_USER_CORRUPT, 301
ER_WARN_DEPRECATED_SQL_CALC_FOUND_ROWS, 105	ER_WARN_LOG_PRIVILEGE_CHECKS_USER_EMPTY, 301
ER_WARN_DEPRECATED_SUPERFLUOUS_DELIMITER, 116	ER_WARN_LOG_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST, 301
ER_WARN_DEPRECATED_SYNTAX, 21	ER_WARN_LOG_PRIVILEGE_CHECKS_USER_NEEDS_RPL_A, 350
ER_WARN_DEPRECATED_SYNTAX_NO_REPLACEMENT, 43	ER_WARN_LOG_PRIVILEGE_CHECKS_USER_NEEDS_RPL_A, 350
ER_WARN_DEPRECATED_SYNTAX_WITH_VER, 36	ER_WARN_L_DISABLE_GTID_ONLY_WITH_SOURCE_AUTO_POS_DISABLED, 375
ER_WARN_DEPRECATED_SYSVAR_UPDATE, 63	ER_WARN_MIGRATION_EMPTY_SOURCE_KEYRING, 377
ER_WARN_DEPRECATED_USER_DEFINED_COLLATION, 121	ER_WARN_NO_KEYRING_COMPONENT_SERVICE_FOUND, 366
ER_WARN_DEPRECATED_USER_DEFINED_COLLATION_OPTION, 391	ER_WARN_NO_SERVERID_SPECIFIED, 181
ER_WARN_DEPRECATED_USER_SET_EXPR, 91	ER_WARN_NO_SPACE_VERSION_COMMENT, 121
ER_WARN_DEPRECATED_UTF8MB3_CHARSET_OPTION, 333	ER_WARN_NULL_TO_NOTNULL, 19
	ER_WARN_ONLY_SOURCE_LOG_FILE_NO_POS, 59
	ER_WARN_ON_MODIFYING_GTID_EXECUTED_TABLE, 66
	ER_WARN_OPEN_TEMP_TABLES_MUST_BE_ZERO, 58
	ER_WARN_OPTIMIZER_HINT_SYNTAX_ERROR, 101

---

ER_WARN_OPTION_RESET_AND_IGNORED_DURING 398	ER_WARN_PARTITION_FUNCTION_IGNORES_FRAME, 79
ER_WARN_PARTIAL_REVOKE_AND_DB_GRANT, 341	ER_WINDOW_ILLEGAL_ORDER_BY, 78
ER_WARN_PROPERTY_STRING_PARSE_FAILED, 338	ER_WINDOW_INVALID_WINDOW_FUNC_ALIAS_USE, 79
ER_WARN_PURGE_LOG_IN_USE, 55	ER_WINDOW_INVALID_WINDOW_FUNC_USE, 78
ER_WARN_PURGE_LOG_IS_ACTIVE, 55	ER_WINDOW_NESTED_WINDOW_FUNC_USE_IN_WINDOW, 79
ER_WARN_REGEX_USING_DEFAULT, 114	ER_WINDOW_NO_CHILD_PARTITIONING, 78
ER_WARN_REMOVED_SQL_MODE, 333	ER_WINDOW_NO_GROUP_ORDER_UNUSED, 79
ER_WARN_REPLICA_ANONYMOUS_TO_GTID_UUID, 370	ER_WINDOW_NO_INHERIT_FRAME, 78
ER_WARN_REPLICA_GTID_ONLY_AND_GTID_MODE, 375	ER_WINDOW_NO_SAME_WINDOW_CHANGE_ID, 78
ER_WARN_RESERVED_SRID_RANGE, 87	ER_WINDOW_NO_SUCH_WINDOW, 78
ER_WARN_RPL_RECOVERY_NO_ROTATE_EVENT, 351	ER_WINDOW_RANGE_BOUND_NOT_CONSTANT, 78
ER_WARN_SCHEDULED_TASK_RUN_FAILED, 394	ER_WINDOW_RANGE_FRAME_NUMERIC_TYPE, FROM_SOURCE_EOF,
ER_WARN_SF_UDF_NAME_COLLISION, 115	ER_WINDOW_RANGE_FRAME_ORDER_TYPE, 78
ER_WARN_SQL_AFTER_MTS_GAPS_GAP_NOT_CALC, 112	ER_WINDOW_RANGE_FRAME_TEMPORAL_TYPE, 78
ER_WARN_SRS_ID_ALREADY_EXISTS, 86	ER_WINDOW_ROWS_INTERVAL_USE, 79
ER_WARN_SRS_NOT_FOUND, 73	ER_WIN_LISTEN_BUT_HOW, 137
ER_WARN_SRS_NOT_FOUND_AXIS_ORDER, 76	ER_WIN_LOAD_LIBRARY_FAILED, 191
ER_WARN_TLS_CHANNEL_INITIALIZATION_ERROR, 357	ER_WL9236_NOW_UNUSED, 79
ER_WARN_TOO_FEW_RECORDS, 19	ER_WRITABLE_CONFIG_REMOVED, 135
ER_WARN_TOO_MANY_RECORDS, 19	ER_WRITE_ROW_TO_PARTITION_FAILED, 185
ER_WARN_TRG_ALREADY_EXISTS, 116	ER_WRITE_SET_EXCEEDS_LIMIT, 72
ER_WARN_TRIGGER_DOESNT_HAVE_CREATED, 58	ER_WRONG_ARGUMENTS, 16
ER_WARN_UNKNOWN_KEYRING_AWS_REGION, 350	ER_WRONG_AUTO_KEY, 8
ER_WARN_UNKNOWN_QB_NAME, 66	ER_WRONG_COLUMN_NAME, 13
ER_WARN_UNLOAD_THE_NOT_PERSISTED, 75	ER_WRONG_COMPRESSION_ALGORITHM_CLIENT, 102
ER_WARN_UNSUPPORTED_HINT, 73	ER_WRONG_COMPRESSION_LEVEL_CLIENT, 102
ER_WARN_UNSUPPORTED_MAX_EXECUTION_TIME, 66	ER_WRONG_COUNT_FOR_KEY, 168
ER_WARN_USING_OTHER_HANDLER, 19	ER_WRONG_COUNT_FOR_ORIGIN, 168
ER_WARN_VAR_VALUE_CHANGE_NOT_SUPPORTED, 108	ER_WRONG_COUNT_OF_ELEMENTS, 168
ER_WARN_VIEW_MERGE, 25	ER_WRONG_DATETIME_SPEC, 136
ER_WARN_VIEW_WITHOUT_KEY, 25	ER_WRONG_DB_NAME, 9
ER_WARN_WRONG_COMPRESSION_ALGORITHM_LOG, 349	ER_WRONG_EXPR_IN_PARTITION_FUNC_ERROR, 32
ER_WARN_WRONG_COMPRESSION_LEVEL_LOG, 349	ER_WRONG_FIELD_SPEC, 7
ER_WASTEFUL_NET_BUFFER_SIZE, 134	ER_WRONG_FIELD_TERMINATORS, 8
ER_WILDCARD_NOT_ALLOWED_FOR_MULTIADDRESS, 344	ER_WRONG_FIELD_WITH_GROUP, 6
ER_WINDOW_CIRCULARITY_IN_WINDOW_GRAPH, 78	ER_WRONG_FIELD_WITH_GROUP_V2, 63
ER_WINDOW_DUPLICATE_NAME, 78	ER_WRONG_FILE_NAME, 66
ER_WINDOW_EXPLAIN_JSON, 79	ER_WRONG_FK_DEF, 18
ER_WINDOW_FRAME_END_ILLEGAL, 78	ER_WRONG_FK_OPTION_FOR_GENERATED_COLUMN, 64
ER_WINDOW_FRAME_ILLEGAL, 78	ER_WRONG_GROUP_FIELD, 7
ER_WINDOW_FRAME_START_ILLEGAL, 78	ER_WRONG_JSON_TABLE_VALUE, 83
	ER_WRONG_KEY_COLUMN, 13
	ER_WRONG_KEY_COLUMN_FUNCTIONAL_INDEX, 90
	ER_WRONG_LOCK_OF_SYSTEM_TABLE, 29
	ER_WRONG_MRG_TABLE, 14
	ER_WRONG_MVI_VALUE, 101
	ER_WRONG_NAME_FOR_CATALOG, 20

---

---

ER\_WRONG\_NAME\_FOR\_INDEX, 20  
 ER\_WRONG\_NATIVE\_TABLE\_STRUCTURE, 43  
 ER\_WRONG\_NUMBER\_OF\_COLUMNS\_IN\_SELECT, 17  
 ER\_WRONG\_OBJECT, 24  
 ER\_WRONG\_OUTER\_JOIN\_UNUSED, 11  
 ER\_WRONG\_PARAMCOUNT\_TO\_NATIVE\_FCT, 37  
 ER\_WRONG\_PARAMCOUNT\_TO\_PROCEDURE, 10  
 ER\_WRONG\_PARAMETERS\_TO\_NATIVE\_FCT, 37  
 ER\_WRONG\_PARAMETERS\_TO\_PROCEDURE, 10  
 ER\_WRONG\_PARAMETERS\_TO\_STORED\_FCT, 37  
 ER\_WRONG\_PARTITION\_NAME, 36  
 ER\_WRONG\_PERFSCHEMA\_USAGE, 43  
 ER\_WRONG\_SIZE\_NUMBER, 35  
 ER\_WRONG\_SRID\_FOR\_COLUMN, 82  
 ER\_WRONG\_STRING\_LENGTH, 31  
 ER\_WRONG\_SUB\_KEY, 8  
 ER\_WRONG\_SUM\_SELECT, 7  
 ER\_WRONG\_TABLESPACE\_NAME, 66  
 ER\_WRONG\_TABLE\_NAME, 9  
 ER\_WRONG\_TYPE\_COLUMN\_VALUE\_ERROR, 41  
 ER\_WRONG\_TYPE\_FOR\_COLUMN\_PREFIX\_IDX\_FLD, 191  
 ER\_WRONG\_TYPE\_FOR\_VAR, 17  
 ER\_WRONG\_USAGE, 17  
 ER\_WRONG\_VALUE, 34  
 ER\_WRONG\_VALUE\_COUNT, 7  
 ER\_WRONG\_VALUE\_COUNT\_ON\_ROW, 12  
 ER\_WRONG\_VALUE\_FOR\_TYPE, 28  
 ER\_WRONG\_VALUE\_FOR\_VAR, 17  
 ER\_WRONG\_VALUE\_FOR\_VAR\_PLUS\_ACTIONABLE\_PART, 106  
 ER\_X509\_CANT\_CHMOD\_KEY, 148  
 ER\_X509\_CANT\_CREATE\_CERT, 148  
 ER\_X509\_CANT\_READ\_CA\_CERT, 148  
 ER\_X509\_CANT\_READ\_CA\_KEY, 148  
 ER\_X509\_CANT\_WRITE\_CERT, 148  
 ER\_X509\_CANT\_WRITE\_KEY, 148  
 ER\_X509\_CIPHERS\_MISMATCH, 147  
 ER\_X509\_ISSUER\_MISMATCH, 147  
 ER\_X509\_NEEDS\_RSA\_PRIVKEY, 148  
 ER\_X509\_SUBJECT\_MISMATCH, 147  
 ER\_XAER\_DUPID, 29  
 ER\_XAER\_INVALID, 27  
 ER\_XAER\_NOTA, 27  
 ER\_XAER\_OUTSIDE, 27  
 ER\_XAER\_RMERR, 27  
 ER\_XAER\_RMFAIL, 27  
 ER\_XA\_CANT\_CREATE\_MDL\_BACKUP, 349  
 ER\_XA\_NO\_MULTI\_2PC\_HEURISTIC\_RECOVER, 143  
 ER\_XA\_RBDEADLOCK, 38  
 ER\_XA\_RBROLLBACK, 27  
 ER\_XA\_RBTIMEOUT, 38  
 ER\_XA\_RECOVERY\_DONE, 143  
 ER\_XA\_RECOVER\_EXPLANATION, 143  
 ER\_XA\_RECOVER\_FOUND\_TRX\_IN\_SE, 143  
 ER\_XA\_RECOVER\_FOUND\_XA\_TRX, 143  
 ER\_XA\_REPLICATION\_FILTERS, 100  
 ER\_XA\_RETRY, 71  
 ER\_XA\_STARTING\_RECOVERY, 143  
 ER\_XA\_TEMP\_TABLE, 116  
 ER\_XPLUGIN\_ALL\_IO\_INTERFACES\_DISABLED, 209  
 ER\_XPLUGIN\_BUFFER\_PAGE\_ALLOC\_FAILED, 207  
 ER\_XPLUGIN\_CLIENT\_KILL\_MSG, 210  
 ER\_XPLUGIN\_COMPRESSION\_ERROR, 350  
 ER\_XPLUGIN\_DETECTED\_HANGING\_CLIENTS, 208  
 ER\_XPLUGIN\_EMPTY\_ADMIN\_CMD, 210  
 ER\_XPLUGIN\_ERROR\_MSG, 205  
 ER\_XPLUGIN\_ERROR\_READING\_SOCKET, 209  
 ER\_XPLUGIN\_EXCEPTION\_IN\_EVENT\_LOOP, 208  
 ER\_XPLUGIN\_EXCEPTION\_IN\_TASK\_SCHEDULER, 208  
 ER\_XPLUGIN\_EXISTING\_USER\_ACCOUNT\_WITH\_INCOMPLETE, 210  
 ER\_XPLUGIN\_FAILED\_AT\_SSL\_CONF, 209  
 ER\_XPLUGIN\_FAILED\_TO\_ACCEPT\_CLIENT, 208  
 ER\_XPLUGIN\_FAILED\_TO\_BIND\_INTERFACE\_ADDRESS, 358  
 ER\_XPLUGIN\_FAILED\_TO\_CLOSE\_SQL\_SESSION, 210  
 ER\_XPLUGIN\_FAILED\_TO\_CREATE\_SESSION\_FOR\_CONN, 209  
 ER\_XPLUGIN\_FAILED\_TO\_EXECUTE\_ADMIN\_CMD, 210  
 ER\_XPLUGIN\_FAILED\_TO\_GET\_CREATION\_STMT, 210  
 ER\_XPLUGIN\_FAILED\_TO\_GET\_ENGINE\_INFO, 210  
 ER\_XPLUGIN\_FAILED\_TO\_GET\_SECURITY\_CTX, 210  
 ER\_XPLUGIN\_FAILED\_TO\_GET\_SYS\_VAR, 210  
 ER\_XPLUGIN\_FAILED\_TO\_INITIALIZE\_SESSION, 209  
 ER\_XPLUGIN\_FAILED\_TO\_OPEN\_INTERNAL\_SESSION, 210  
 ER\_XPLUGIN\_FAILED\_TO\_PREPARE\_IO\_INTERFACES, 208  
 ER\_XPLUGIN\_FAILED\_TO\_RESET\_IPV6\_V6ONLY\_FLAG, 211  
 ER\_XPLUGIN\_FAILED\_TO\_SCHEDULE\_CLIENT, 208  
 ER\_XPLUGIN\_FAILED\_TO\_SET\_MIN\_NUMBER\_OF\_WORKER, 209  
 ER\_XPLUGIN\_FAILED\_TO\_SET\_SO\_REUSEADDR\_FLAG, 210

---

ER\_XPLUGIN\_FAILED\_TO\_STOP\_SERVICES, 324  
 ER\_XPLUGIN\_FAILED\_TO\_SWITCH\_CONTEXT, 210  
 ER\_XPLUGIN\_FAILED\_TO\_SWITCH\_SECURITY\_CTX, 332  
 ER\_XPLUGIN\_FAILED\_TO\_UNREGISTER\_UDF, 211  
 ER\_XPLUGIN\_FAILED\_TO\_USE\_SSL\_CONF, 205  
 ER\_XPLUGIN\_FAILED\_TO\_VALIDATE\_ADDRESS, 357  
 ER\_XPLUGIN\_FORCE\_STOP\_CLIENT, 207  
 ER\_XPLUGIN\_IPv6\_AVAILABLE, 210  
 ER\_XPLUGIN\_LISTENER\_SETUP\_FAILED, 208  
 ER\_XPLUGIN\_LISTENER\_STATUS\_MSG, 209  
 ER\_XPLUGIN\_LISTENER\_SYS\_VARIABLE\_ERROR, 209  
 ER\_XPLUGIN\_MAX\_AUTH\_ATTEMPTS\_REACHED, 207  
 ER\_XPLUGIN\_MESSAGE\_TOO\_LONG, 209  
 ER\_XPLUGIN\_PEER\_DISCONNECTED\_WHILE\_READING, 209  
 ER\_XPLUGIN\_READ\_FAILED\_CLOSING\_CONNECTION, 209  
 ER\_XPLUGIN\_REFERENCE\_TO\_SECURE\_CONNECTION, 205  
 ER\_XPLUGIN\_REFERENCE\_TO\_USER\_ACCOUNT\_EXPIRED, 208  
 ER\_XPLUGIN\_RETRYING\_BIND\_ON\_PORT, 210  
 ER\_XPLUGIN\_SRV\_SESSION\_INIT\_THREAD\_FAILED, 208  
 ER\_XPLUGIN\_STARTUP\_FAILED, 204  
 ER\_XPLUGIN\_TASK\_SCHEDULING\_FAILED, 208  
 ER\_XPLUGIN\_UNABLE\_TO\_ACCEPT\_CONNECTION, 209  
 ER\_XPLUGIN\_UNABLE\_TO\_USE\_USER\_SESSION\_ACCOUNT, 208  
 ER\_XPLUGIN\_UNEXPECTED\_EXCEPTION\_DISPATCHED, 208  
 ER\_XPLUGIN\_UNINITIALIZED\_MESSAGE, 209  
 ER\_XPLUGIN\_USING\_SSL\_CONF\_FROM\_MYSQLX, 204  
 ER\_XPLUGIN\_USING\_SSL\_CONF\_FROM\_SERVER, 204  
 ER\_XPLUGIN\_USING\_SSL\_FOR\_TLS\_CONNECTION, 205  
 ER\_XPLUING\_NET\_STARTUP\_FAILED, 208  
 ER\_YES, 3  
 ER\_ZLIB\_Z\_BUF\_ERROR, 19  
 ER\_ZLIB\_Z\_DATA\_ERROR, 19  
 ER\_ZLIB\_Z\_MEM\_ERROR, 19  
 WARN\_AES\_KEY\_SIZE, 72  
 WARN\_COND\_ITEM\_TRUNCATED, 40  
 WARN\_DATA\_TRUNCATED, 19  
 WARN\_NAMED\_PIPE\_ACCESS\_EVERYONE, 57  
 WARN\_NON\_ASCII\_SEPARATOR\_NOT\_IMPLEMENTED, 40  
 WARN\_NO\_CONNECTION\_METADATA, 39  
 WARN\_ON\_BLOCKHOLE\_IN\_RBR, 56  
 WARN\_OPTION\_BELOW\_LIMIT, 44  
 WARN\_OPTION\_IGNORED, 39  
 WARN\_PLUGIN\_BUSY, 39  
 WARN\_UNENCRYPTED\_TABLE\_IN\_ENCRYPTED\_DB, 95  
 WARN\_UNSUPPORTED\_ACL\_TABLES\_READ, 109  
 WARN\_USELESS\_SPATIAL\_INDEX, 84  
 ER\_ABORTING error code, 136  
 ER\_ABORTING\_CONNECTION error code, 13  
 ER\_ABORTING\_USER\_CONNECTION error code, 181  
 ER\_ACCESS\_DENIED\_CHANGE\_USER\_ERROR error code, 56  
 ER\_ACCESS\_DENIED\_ERROR error code, 6  
 ER\_ACCESS\_DENIED\_ERROR\_WITHOUT\_PASSWORD error code, 182  
 ER\_ACCESS\_DENIED\_ERROR\_WITH\_PASSWORD error code, 182  
 ER\_ACCESS\_DENIED\_FOR\_USER\_ACCOUNT\_BLOCKED\_BY\_SECURITY error code, 353  
 ER\_ACCESS\_DENIED\_FOR\_USER\_ACCOUNT\_LOCKED error code, 182  
 ER\_ACCESS\_DENIED\_NO\_PASSWORD\_ERROR error code, 44  
 ER\_ACCOUNT\_HAS\_BEEN\_LOCKED error code, 66  
 ER\_ACCOUNT\_WITH\_EXPIRED\_PASSWORD error code, 379  
 ER\_ACL\_OPERATION\_FAILED error code, 72  
 ER\_ACL\_WRONG\_OR\_MISSING\_ACL\_TABLES\_LOG error code, 346  
 ER\_ADDRESSES\_FOR\_HOSTNAME\_HEADER error code, 132  
 ER\_ADDRESSES\_FOR\_HOSTNAME\_LIST\_ITEM error code, 132  
 ER\_ADD\_PARTITION\_NO\_NEW\_PARTITION error code, 34  
 ER\_ADD\_PARTITION\_SUBPART\_ERROR error code, 34  
 ER\_ADMIN\_WRONG\_MRG\_TABLE error code, 31  
 ER\_AES\_INVALID\_IV error code, 56  
 ER\_AES\_INVALID\_KDF\_ITERATIONS error code, 72  
 ER\_AES\_INVALID\_KDF\_NAME error code, 72  
 ER\_AES\_INVALID\_KDF\_OPTION\_SIZE error code, 72  
 ER\_AGGREGATE\_IN\_ORDER\_NOT\_SELECT error code, 62  
 ER\_AGGREGATE\_ORDER\_FOR\_UNION error code, 59  
 ER\_AGGREGATE\_ORDER\_NON\_AGG\_QUERY error code, 59  
 ER\_ALTER\_CONSTRAINT\_ENFORCEMENT\_NOT\_SUPPORTED error code, 103  
 ER\_ALTER\_FILEGROUP\_FAILED error code, 35  
 ER\_ALTER\_INFO error code, 8  
 ER\_ALTER\_OPERATION\_NOT\_SUPPORTED error code, 54  
 ER\_ALTER\_OPERATION\_NOT\_SUPPORTED\_REASON error code, 54

---

---

ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_AUTOMATIC error code, 54	ER_AUDIT_LOG_EC_WRITER_FAILED_TO_INIT_COMPRESSION error code, 202
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_CHANGE_LOG error code, 55	ER_AUDIT_LOG_EC_WRITER_FAILED_TO_INIT_ENCRYPTION error code, 202
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_COLUMN_TYPE error code, 54	ER_AUDIT_LOG_ENCRYPTION_PASSWORD_CANNOT_BE_FETCHED error code, 327
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_COLUMN_TYPE_ENCRYPTION error code, 115	ER_AUDIT_LOG_ENCRYPTION_PASSWORD_HAS_NOT_BEEN_SET error code, 327
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_COPY error code, 54	ER_AUDIT_LOG_FILE_AUTO_PRUNED error code, 366
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_CHECK error code, 54	ER_AUDIT_LOG_FILE_HAS_BEEN_SUCCESSFULLY_PROCESSED error code, 346
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_RENAME error code, 54	ER_AUDIT_LOG_FILE_NAME_DOES_NOT_HAVE_REQUIRED_FIELDS error code, 346
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_AUDIT_LOG_FILE_NAME_KEYRING_ID_VALUE_IS_MISSING error code, 55	ER_AUDIT_LOG_FILE_NAME_KEYRING_ID_VALUE_IS_MISSING error code, 346
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_AUDIT_LOG_FILE_NAME_TIMESTAMP_VALUE_IS_MISSING error code, 61	ER_AUDIT_LOG_FILE_NAME_TIMESTAMP_VALUE_IS_MISSING error code, 346
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_HIDDEN error code, 55	ER_AUDIT_LOG_FILE_PRUNE_FAILED error code, 366
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_READ error code, 54	ER_AUDIT_LOG_FILTER_FAILED_TO_CLOSE_TABLE_AFTER_FILTERING error code, 203
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_READ error code, 55	ER_AUDIT_LOG_FILTER_FAILED_TO_DELETE_FROM_TABLE error code, 203
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_READ error code, 54	ER_AUDIT_LOG_FILTER_FAILED_TO_INIT_TABLE_FOR_READ error code, 203
ER_AMBIGUOUS_FIELD_TERM error code, 31	ER_AUDIT_LOG_FILTER_FAILED_TO_INSERT_INTO_TABLE error code, 203
ER_ANONYMOUS_AUTH_ID_NOT_ALLOWED_IN_MANAGED_TRANSACTION error code, 184	ER_AUDIT_LOG_FILTER_FAILED_TO_READ_TABLE error code, 203
ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_GROUP_NAME error code, 110	ER_AUDIT_LOG_FILTER_FAILED_TO_STORE_TABLE_FLDS error code, 203
ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_VIEW_NAME error code, 111	ER_AUDIT_LOG_FILTER_FAILED_TO_UPDATE_TABLE error code, 203
ER_APPLIER_LOG_EVENT_VALIDATION_ERROR error code, 81	ER_AUDIT_LOG_FILTER_FLD_FILTERNAME_CANNOT_BE_EMPTY error code, 203
ER_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTION_REQUIRED error code, 109	ER_AUDIT_LOG_FILTER_GTID_MODE_ON error code, 203
ER_ATTRIBUTE_IGNORED error code, 83	ER_AUDIT_LOG_FILTER_IS_NOT_INSTALLED error code, 201
ER_AUDIT_API_ABORT error code, 69	ER_AUDIT_LOG_FILTER_RESULT_MSG error code, 203
ER_AUDIT_CANT_ABORT_COMMAND error code, 180	ER_AUDIT_LOG_FILTER_USER_AND_HOST_CANNOT_BE_EMPTY error code, 203
ER_AUDIT_CANT_ABORT_EVENT error code, 180	ER_AUDIT_LOG_HAS_NOT_BEEN_INSTALLED error code, 349
ER_AUDIT_LOG_CANNOT_GENERATE_PASSWORD error code, 350	ER_AUDIT_LOG_HOST_NAME_INVALID_CHARACTER error code, 327
ER_AUDIT_LOG_CANNOT_READ_PASSWORD error code, 346	ER_AUDIT_LOG_INDEX_MAP_CANNOT_ACCESS_DIRECTORY error code, 202
ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD error code, 346	ER_AUDIT_LOG_INDEX_MAP_INSUFFICIENT_PRIVILEGE error code, 101
ER_AUDIT_LOG_CANNOT_SET_LOG_POLICY_WITH_CURRENT_POLICY error code, 202	ER_AUDIT_LOG_INVALID_FILE_CONTENT error code, 346
ER_AUDIT_LOG_CANNOT_STORE_PASSWORD error code, 346	ER_AUDIT_LOG_INVALID_FLUSH_INTERVAL_VALUE error code, 395
ER_AUDIT_LOG_COULD_NOT_CREATE_AES_KEY error code, 327	ER_AUDIT_LOG_JSON_FILTERING_NOT_ENABLED error code, 327
ER_AUDIT_LOG_COULD_NOT_OPEN_FILE_FOR_READING error code, 346	ER_AUDIT_LOG_JSON_FILTER_DOES_NOT_EXIST error code, 328
ER_AUDIT_LOG_EC_WRITER_FAILED_TO_CREATE_FILTER error code, 202	

---

ER\_AUDIT\_LOG\_JSON\_FILTER\_NAME\_CANNOT\_BE\_EMPTY error code, 327  
 ER\_AUDIT\_LOG\_JSON\_FILTER\_PARSING\_ERROR error code, 326  
 ER\_AUDIT\_LOG\_JSON\_READER\_BUF\_TOO\_SMALL error code, 203  
 ER\_AUDIT\_LOG\_JSON\_READER\_FAILED\_TO\_OPEN\_FILTER error code, 203  
 ER\_AUDIT\_LOG\_JSON\_READER\_FAILED\_TO\_PARSE error code, 203  
 ER\_AUDIT\_LOG\_JSON\_READER\_FILE\_PARSING\_ERROR error code, 203  
 ER\_AUDIT\_LOG\_JSON\_USER\_NAME\_CANNOT\_BE\_EMPTY error code, 327  
 ER\_AUDIT\_LOG\_KEYRING\_ID\_TIMESTAMP\_VALUE\_IS\_INVALID error code, 345  
 ER\_AUDIT\_LOG\_NO\_KEYRING\_PLUGIN\_INSTALLED error code, 327  
 ER\_AUDIT\_LOG\_ONLY\_INCLUDE\_LIST\_USED error code, 202  
 ER\_AUDIT\_LOG\_PASSWORD\_HAS\_BEEN\_COPIED error code, 346  
 ER\_AUDIT\_LOG\_RENAME\_LOG\_FILE\_BEFORE\_FLUSH error code, 202  
 ER\_AUDIT\_LOG\_SUPER\_PRIVILEGE\_REQUIRED error code, 349  
 ER\_AUDIT\_LOG\_SWITCHING\_TO\_INCLUDE\_LIST error code, 201  
 ER\_AUDIT\_LOG\_TABLE\_DEFINITION\_NOT\_UPDATED error code, 328  
 ER\_AUDIT\_LOG\_UDF\_INSUFFICIENT\_PRIVILEGE error code, 327  
 ER\_AUDIT\_LOG\_UDF\_INVALID\_ARGUMENT\_COUNT error code, 349  
 ER\_AUDIT\_LOG\_UDF\_INVALID\_ARGUMENT\_TYPE error code, 349  
 ER\_AUDIT\_LOG\_UDF\_READ\_INVALID\_MAX\_ARRAY\_LENGTH error code, 349  
 ER\_AUDIT\_LOG\_UDF\_READ\_INVALID\_MAX\_ARRAY\_LENGTH error code, 72  
 ER\_AUDIT\_LOG\_USER\_FIRST\_CHARACTER\_MUST\_BE\_ALPHANUMERIC error code, 328  
 ER\_AUDIT\_LOG\_USER\_NAME\_INVALID\_CHARACTER error code, 327  
 ER\_AUDIT\_LOG\_WRITER\_DEST\_FILE\_ALREADY\_EXISTS error code, 202  
 ER\_AUDIT\_LOG\_WRITER\_FAILED\_TO\_WRITE\_TO\_FILE error code, 202  
 ER\_AUDIT\_LOG\_WRITER\_INCOMPLETE\_FILE\_RENAME error code, 202  
 ER\_AUDIT\_LOG\_WRITER\_RENAME\_FILE\_FAILED error code, 202  
 ER\_AUDIT\_LOG\_WRITER\_RENAME\_FILE\_FAILED\_REMOVED error code, 202  
 ER\_AUDIT\_PLUGIN\_DOES\_NOT\_SUPPORT\_AUDIT\_PLUGIN error code, 152  
 ER\_AUDIT\_PLUGIN\_HAS\_INVALID\_DATA error code, 152  
 ER\_AUDIT\_WARNING error code, 180  
 ER\_AUTHCACHE\_CANT\_INIT\_GRANT\_SUBSYSTEM error code, 150  
 ER\_AUTHCACHE\_CANT\_OPEN\_AND\_LOCK\_PRIVILEGE\_TABLE error code, 150  
 ER\_AUTHCACHE\_DB\_ENTRY\_LOWERCASED\_REVOKE\_WARNING error code, 150  
 ER\_AUTHCACHE\_DB\_IGNORED\_EMPTY\_NAME error code, 150  
 ER\_AUTHCACHE\_DB\_SKIPPED\_NEEDS\_RESOLVE error code, 150  
 ER\_AUTHCACHE\_DEFAULT\_ROLES\_IGNORED\_EMPTY\_NAME error code, 359  
 ER\_AUTHCACHE\_DEFAULT\_ROLES\_UNKNOWN\_AUTHORIZATIONS error code, 359  
 ER\_AUTHCACHE\_EXPIRED\_PASSWORD\_UNSUPPORTED error code, 149  
 ER\_AUTHCACHE\_PLUGIN\_CONFIG error code, 149  
 ER\_AUTHCACHE\_PLUGIN\_MISSING error code, 149  
 ER\_AUTHCACHE\_PROCS\_PRIV\_ENTRY\_IGNORED\_BAD\_ROLE error code, 150  
 ER\_AUTHCACHE\_PROCS\_PRIV\_SKIPPED\_NEEDS\_RESOLVE error code, 150  
 ER\_AUTHCACHE\_PROXIES\_PRIV\_SKIPPED\_NEEDS\_RESOLVE error code, 149  
 ER\_AUTHCACHE\_ROLE\_EDGES\_IGNORED\_EMPTY\_NAME error code, 359  
 ER\_AUTHCACHE\_ROLE\_EDGES\_UNKNOWN\_AUTHORIZATIONS error code, 359  
 ER\_AUTHCACHE\_TABLES\_PRIV\_SKIPPED\_NEEDS\_RESOLVE error code, 150  
 ER\_AUTHCACHE\_TABLE\_PROXIES\_PRIV\_MISSING error code, 150  
 ER\_AUTHCACHE\_USER\_IGNORED\_DEPRECATED\_PASSWORD error code, 149  
 ER\_AUTHCACHE\_USER\_IGNORED\_INVALID\_PASSWORD error code, 149  
 ER\_AUTHCACHE\_USER\_IGNORED\_NEEDS\_PLUGIN error code, 149  
 ER\_AUTHCACHE\_USER\_SKIPPED\_NEEDS\_RESOLVE error code, 149  
 ER\_AUTHCACHE\_USER\_TABLE\_DODGY error code, 149  
 ER\_AUTHENTICATION\_OCI\_DOWNLOAD\_IDDP\_PUBLIC\_KEY error code, 393  
 ER\_AUTHENTICATION\_OCI\_DOWNLOAD\_PUBLIC\_KEY error code, 375  
 ER\_AUTHENTICATION\_OCI\_IAM error code, 375  
 ER\_AUTHENTICATION\_OCI\_IMDS error code, 375  
 ER\_AUTHENTICATION\_OCI\_INVALID\_AUTHENTICATION\_STATE error code, 375  
 ER\_AUTHENTICATION\_OCI\_INVALID\_TOKEN error code, 375  
 ER\_AUTHENTICATION\_OCI\_INVALID\_TOKEN\_MANUALLY error code, 375  
 ER\_AUTHENTICATION\_OCI\_NONCE error code, 375  
 ER\_AUTHENTICATION\_OCI\_NO\_GROUPS\_FOUND error code, 375  
 ER\_AUTHENTICATION\_OCI\_NO\_MATCHING\_GROUPS error code, 375

---

---

ER\_AUTHENTICATION\_OCI\_PLUGIN\_NOT\_INITIALIZED error code, 375  
 ER\_AUTHENTICATION\_OCI\_PRIVATE\_KEY\_ERROR error code, 375  
 ER\_AUTHENTICATION\_OCI\_TOKEN\_DETAILS\_MISMATCH error code, 393  
 ER\_AUTHENTICATION\_OCI\_TOKEN\_NOT\_VERIFIED error code, 393  
 ER\_AUTHENTICATION\_PLUGIN\_AUTH\_DATA\_CORRUPT error code, 374  
 ER\_AUTHENTICATION\_PLUGIN\_LOG error code, 374  
 ER\_AUTHENTICATION\_PLUGIN\_OOM error code, 374  
 ER\_AUTHENTICATION\_PLUGIN\_REGISTRATION\_FAILED error code, 374  
 ER\_AUTHENTICATION\_PLUGIN\_REGISTRATION\_INSUFFICIENT\_PERMISSIONS error code, 374  
 ER\_AUTHENTICATION\_PLUGIN\_SIGNATURE\_CORRUPT error code, 374  
 ER\_AUTHENTICATION\_PLUGIN\_VERIFY\_SIGNATURE\_FAILED error code, 374  
 ER\_AUTHENTICATION\_POLICY\_MISMATCH error code, 113  
 ER\_AUTH\_CANT\_ACTIVATE\_ROLE error code, 148  
 ER\_AUTH\_CANT\_CREATE\_RSA\_PAIR error code, 148  
 ER\_AUTH\_CANT\_SET\_DEFAULT\_PLUGIN error code, 140  
 ER\_AUTH\_CANT\_WRITE\_PRIVKEY error code, 148  
 ER\_AUTH\_CANT\_WRITE\_PUBKEY error code, 148  
 ER\_AUTH\_CERTS\_SAVED\_TO\_DATADIR error code, 148  
 ER\_AUTH\_CERT\_GENERATION\_DISABLED error code, 148  
 ER\_AUTH\_ID\_WITH\_SYSTEM\_USER\_PRIV\_IN\_MANDATORY\_PROCESSES error code, 341  
 ER\_AUTH\_KERBEROS\_LOGGER\_GENERIC\_MSG error code, 371  
 ER\_AUTH\_KEYS\_SAVED\_TO\_DATADIR error code, 149  
 ER\_AUTH\_KEY\_GENERATION\_DISABLED error code, 149  
 ER\_AUTH\_KEY\_GENERATION\_SKIPPED\_PAIR\_PRESENT error code, 149  
 ER\_AUTH\_LDAP\_ERROR\_LOGGER\_ERROR\_MSG error code, 205  
 ER\_AUTH\_RSA\_CANT\_FIND error code, 147  
 ER\_AUTH\_RSA\_CANT\_PARSE error code, 147  
 ER\_AUTH\_RSA\_CANT\_READ error code, 147  
 ER\_AUTH\_RSA\_CONF\_PREVENTS\_KEY\_GENERATION error code, 149  
 ER\_AUTH\_RSA\_FILES\_NOT\_FOUND error code, 147  
 ER\_AUTH\_SSL\_CONF\_PREVENTS\_CERT\_GENERATION error code, 148  
 ER\_AUTH\_USING\_EXISTING\_CERTS error code, 148  
 ER\_AUTOINC\_READ\_FAILED error code, 31  
 ER\_AUTO\_CONVERT error code, 18  
 ER\_AUTO\_INCREMENT\_CONFLICT error code, 55  
 ER\_AUTO\_OPTIONS\_FAILED error code, 140  
 ER\_AUTO\_POSITION\_REQUIRES\_GTID\_MODE\_NOT\_OFF error code, 49  
 ER\_BACK\_IN\_TIME error code, 136  
 ER\_BAD\_DB\_ERROR error code, 6  
 ER\_BAD\_FIELD\_ERROR error code, 6  
 ER\_BAD\_FT\_COLUMN error code, 20  
 ER\_BAD\_HOST\_ERROR error code, 5  
 ER\_BAD\_LOG\_STATEMENT error code, 37  
 ER\_BAD\_NULL\_ERROR error code, 6  
 ER\_BAD\_NULL\_ERROR\_NOT\_IGNORED error code, 84  
 ER\_BAD\_REPLICA error code, 15  
 ER\_BAD\_REPLICA\_AUTO\_POSITION error code, 49  
 ER\_BAD\_REPLICA\_UNTIL\_COND error code, 20  
 ER\_BAD\_TIMESTAMP\_ERROR error code, 6  
 ER\_BAD\_TIMESTAMP\_FORMAT error code, 118  
 ER\_BASE64\_DECODE\_ERROR error code, 37  
 ER\_BASEDIR\_SET\_TO error code, 183  
 ER\_BEFORE\_DML\_VALIDATION\_ERROR error code, 64  
 ER\_BEG\_INITFILE error code, 137  
 ER\_BEYOND\_SERVER\_DOWNGRADE\_THRESHOLD error code, 395  
 ER\_BEYOND\_SERVER\_UPGRADE\_THRESHOLD error code, 395  
 ER\_BINLOG\_CACHE\_SIZE\_GREATER\_THAN\_MAX error code, 47  
 ER\_BINLOG\_CACHE\_SIZE\_TOO\_LARGE error code, 180  
 ER\_BINLOG\_CANT\_APPEND\_LOG\_TO\_TMP\_INDEX error code, 175  
 ER\_BINLOG\_CANT\_CLEAR\_IN\_USE\_FLAG\_FOR\_CRASHED\_BINLOG error code, 177  
 ER\_BINLOG\_CANT\_CLOSE\_TMP\_INDEX error code, 176  
 ER\_BINLOG\_CANT\_COPY\_INDEX\_TO\_TMP error code, 176  
 ER\_BINLOG\_CANT\_DELETE\_FILE error code, 175  
 ER\_BINLOG\_CANT\_DELETE\_FILE\_AND\_READ\_BINLOG\_INDEX error code, 177  
 ER\_BINLOG\_CANT\_DELETE\_LOG\_FILE\_DOES\_INDEX\_MATCH error code, 177  
 ER\_BINLOG\_CANT\_FIND\_LOG\_IN\_INDEX error code, 177  
 ER\_BINLOG\_CANT\_GENERATE\_NEW\_FILE\_NAME error code, 175  
 ER\_BINLOG\_CANT\_LOCATE\_OLD\_BINLOG\_OR\_RELAY\_LOG\_FILE error code, 175  
 ER\_BINLOG\_CANT\_MOVE\_TMP\_TO\_INDEX error code, 176  
 ER\_BINLOG\_CANT\_OPEN\_CRASHED\_BINLOG error code, 177  
 ER\_BINLOG\_CANT\_OPEN\_FOR\_LOGGING error code, 174  
 ER\_BINLOG\_CANT\_OPEN\_TMP\_INDEX error code, 175



---

ER\_BINLOG\_CANT\_RESIZE\_CACHE error code, 174  
 ER\_BINLOG\_CANT\_SET\_TMP\_INDEX\_NAME error code, 175  
 ER\_BINLOG\_CANT\_TRIM\_CRASHED\_BINLOG error code, 177  
 ER\_BINLOG\_CANT\_USE\_FOR\_LOGGING error code, 175  
 ER\_BINLOG\_CRASHED\_BINLOG\_TRIMMED error code, 177  
 ER\_BINLOG\_CRASH\_RECOVERY\_COMMIT\_FAILED error code, 384  
 ER\_BINLOG\_CRASH\_RECOVERY\_ENGINE\_RESULTS error code, 383  
 ER\_BINLOG\_CRASH\_RECOVERY\_ERROR\_RETURNED error code, 383  
 ER\_BINLOG\_CRASH\_RECOVERY\_MALFORMED\_LOG error code, 383  
 ER\_BINLOG\_CRASH\_RECOVERY\_PREPARE\_FAILED error code, 384  
 ER\_BINLOG\_CRASH\_RECOVERY\_ROLLBACK\_FAILED error code, 384  
 ER\_BINLOG\_CREATE\_ROUTINE\_NEED\_SUPER error code, 28  
 ER\_BINLOG\_END error code, 136  
 ER\_BINLOG\_ERROR\_READING\_GTIDS\_FROM\_BINARY\_LOG error code, 174  
 ER\_BINLOG\_ERROR\_READING\_GTIDS\_FROM\_RELAY\_LOG error code, 174  
 ER\_BINLOG\_EVENTS\_READ\_FROM\_APPLIER\_METADATA error code, 174  
 ER\_BINLOG\_EVENTS\_READ\_FROM\_BINLOG\_INFO error code, 174  
 ER\_BINLOG\_EVENT\_WRITE\_TO\_STMT\_CACHE\_FAILED error code, 184  
 ER\_BINLOG\_FAILED\_TO\_CLOSE\_INDEX\_FILE\_WHILE\_FLUSHING error code, 175  
 ER\_BINLOG\_FAILED\_TO\_DELETE\_INDEX\_FILE\_WHILE\_FLUSHING error code, 175  
 ER\_BINLOG\_FAILED\_TO\_DELETE\_LOG\_FILE error code, 177  
 ER\_BINLOG\_FAILED\_TO\_OPEN\_INDEX\_FILE\_AFTER\_FLUSHING error code, 175  
 ER\_BINLOG\_FAILED\_TO\_OPEN\_REGISTER\_FILE error code, 176  
 ER\_BINLOG\_FAILED\_TO\_OPEN\_TEMPORARY\_INDEX\_FILE error code, 175  
 ER\_BINLOG\_FAILED\_TO\_READ\_REGISTER\_FILE error code, 176  
 ER\_BINLOG\_FAILED\_TO\_REINIT\_REGISTER\_FILE error code, 176  
 ER\_BINLOG\_FAILED\_TO\_RENAME\_INDEX\_FILE\_WHILE\_FLUSHING error code, 175  
 ER\_BINLOG\_FAILED\_TO\_RUN\_AFTER\_FLUSH\_HOOK error code, 178  
 ER\_BINLOG\_FAILED\_TO\_RUN\_AFTER\_SYNC\_HOOK error code, 177  
 ER\_BINLOG\_FAILED\_TO\_SET\_PURGE\_INDEX\_FILE\_NAME error code, 176  
 ER\_BINLOG\_FAILED\_TO\_SYNC\_INDEX\_FILE error code, 174  
 ER\_BINLOG\_FAILED\_TO\_SYNC\_INDEX\_FILE\_IN\_OPEN error code, 175  
 ER\_BINLOG\_FAILED\_TO\_WRITE\_DROP\_FOR\_TEMP\_TABLE error code, 168  
 ER\_BINLOG\_FATAL\_ERROR error code, 38  
 ER\_BINLOG\_FILE\_BEING\_READ\_NOT\_PURGED error code, 174  
 ER\_BINLOG\_FILE\_EXTENSION\_NUMBER\_EXHAUSTED error code, 174  
 ER\_BINLOG\_FILE\_EXTENSION\_NUMBER\_RUNNING\_LOW error code, 174  
 ER\_BINLOG\_FILE\_NAME\_TOO\_LONG error code, 174  
 ER\_BINLOG\_FILE\_OPEN\_FAILED error code, 184  
 ER\_BINLOG\_IO\_ERROR\_READING\_HEADER error code, 174  
 ER\_BINLOG\_LOGGING\_IMPOSSIBLE error code, 38  
 ER\_BINLOG\_LOGGING\_INCIDENT\_TO\_STOP\_REPLICAS error code, 177  
 ER\_BINLOG\_LOGGING\_NOT\_POSSIBLE error code, 192  
 ER\_BINLOG\_LOGICAL\_CORRUPTION error code, 55  
 ER\_BINLOG\_MALFORMED\_OR\_OLD\_RELAY\_LOG error code, 193  
 ER\_BINLOG\_MASTER\_KEY\_RECOVERY\_OUT\_OF\_COMBINATION error code, 93  
 ER\_BINLOG\_MASTER\_KEY\_ROTATION\_FAIL\_TO\_CLEANUP error code, 94  
 ER\_BINLOG\_MASTER\_KEY\_ROTATION\_FAIL\_TO\_CLEANUP error code, 94  
 ER\_BINLOG\_MASTER\_KEY\_ROTATION\_FAIL\_TO\_OPERATE error code, 94  
 ER\_BINLOG\_MASTER\_KEY\_ROTATION\_FAIL\_TO\_REENCIPHER error code, 94  
 ER\_BINLOG\_MASTER\_KEY\_ROTATION\_FAIL\_TO\_ROTATE error code, 94  
 ER\_BINLOG\_MULTIPLE\_ENGINES\_AND\_SELF\_LOGGING\_ENABLED error code, 42  
 ER\_BINLOG\_NEEDS\_SERVERID error code, 139  
 ER\_BINLOG\_OOM\_WRITING\_DELETE\_WHILE\_OPENING\_HISTOGRAM error code, 168  
 ER\_BINLOG\_PURGE\_EMFILE error code, 37  
 ER\_BINLOG\_PURGE\_FATAL\_ERR error code, 26  
 ER\_BINLOG\_PURGE\_LOGS\_CALLED\_WITH\_FILE\_NOT\_IN\_INDEX error code, 176  
 ER\_BINLOG\_PURGE\_LOGS\_CANT\_COPY\_TO\_REGISTER\_FILE error code, 176  
 ER\_BINLOG\_PURGE\_LOGS\_CANT\_FLUSH\_REGISTER\_FILE error code, 176  
 ER\_BINLOG\_PURGE\_LOGS\_CANT\_SYNC\_INDEX\_FILE error code, 176  
 ER\_BINLOG\_PURGE\_LOGS\_CANT\_UPDATE\_INDEX\_FILE error code, 176  
 ER\_BINLOG\_PURGE\_LOGS\_FAILED\_TO\_PURGE\_LOG error code, 176  
 ER\_BINLOG\_PURGE\_PROHIBITED error code, 26

---

---

ER\_BINLOG\_RECOVERING\_AFTER\_CRASH\_USING error code, 177  
 ER\_BINLOG\_ROW\_ENGINE\_AND\_STMT\_ENGINE error code, 41  
 ER\_BINLOG\_ROW\_INJECTION\_AND\_STMT\_ENGINE error code, 42  
 ER\_BINLOG\_ROW\_INJECTION\_AND\_STMT\_MODE error code, 42  
 ER\_BINLOG\_ROW\_LOGGING\_FAILED error code, 35  
 ER\_BINLOG\_ROW\_MODE\_AND\_STMT\_ENGINE error code, 41  
 ER\_BINLOG\_ROW\_VALUE\_OPTION\_IGNORED error code, 323  
 ER\_BINLOG\_ROW\_VALUE\_OPTION\_USED\_ONLY\_FOR\_READ error code, 323  
 ER\_BINLOG\_STMT\_CACHE\_SIZE\_GREATER\_THAN\_MAX error code, 47  
 ER\_BINLOG\_STMT\_CACHE\_SIZE\_TOO\_LARGE error code, 180  
 ER\_BINLOG\_STMT\_MODE\_AND\_NO\_REPL\_TABLES error code, 54  
 ER\_BINLOG\_STMT\_MODE\_AND\_ROW\_ENGINE error code, 42  
 ER\_BINLOG\_UNABLE\_TO\_ROTATE\_GTID\_TABLE\_READ error code, 344  
 ER\_BINLOG\_UNSAFE\_ACL\_TABLE\_READ\_IN\_DML\_EXECUTION error code, 109  
 ER\_BINLOG\_UNSAFE\_AND\_STMT\_ENGINE error code, 41  
 ER\_BINLOG\_UNSAFE\_AUTOINC\_COLUMNS error code, 42  
 ER\_BINLOG\_UNSAFE\_AUTOINC\_NOT\_FIRST error code, 46  
 ER\_BINLOG\_UNSAFE\_CREATE\_IGNORE\_SELECT error code, 45  
 ER\_BINLOG\_UNSAFE\_CREATE\_REPLACE\_SELECT error code, 45  
 ER\_BINLOG\_UNSAFE\_CREATE\_SELECT\_AUTOINC error code, 46  
 ER\_BINLOG\_UNSAFE\_DEFAULT\_EXPRESSION\_IN\_SUBQUERY error code, 345  
 ER\_BINLOG\_UNSAFE\_FULLTEXT\_PLUGIN error code, 57  
 ER\_BINLOG\_UNSAFE\_INSERT\_IGNORE\_SELECT error code, 45  
 ER\_BINLOG\_UNSAFE\_INSERT\_SELECT\_UPDATE error code, 45  
 ER\_BINLOG\_UNSAFE\_INSERT\_TWO\_KEYS error code, 46  
 ER\_BINLOG\_UNSAFE\_LIMIT error code, 42  
 ER\_BINLOG\_UNSAFE\_MESSAGE\_AND\_STATEMENT error code, 181  
 ER\_BINLOG\_UNSAFE\_MIXED\_STATEMENT error code, 44  
 ER\_BINLOG\_UNSAFE\_MULTIPLE\_ENGINES\_AND\_SELF error code, 43  
 ER\_BINLOG\_UNSAFE\_NONTRANS\_AFTER\_TRANS error code, 42  
 ER\_BINLOG\_UNSAFE\_NOWAIT error code, 77  
 ER\_BINLOG\_UNSAFE\_REPLACE\_SELECT error code, 45  
 ER\_BINLOG\_UNSAFE\_ROUTINE error code, 28  
 ER\_BINLOG\_UNSAFE\_SKIP\_LOCKED error code, 77  
 ER\_BINLOG\_UNSAFE\_STATEMENT error code, 38  
 ER\_BINLOG\_UNSAFE\_SYSTEM\_FUNCTION error code, 42  
 ER\_BINLOG\_UNSAFE\_SYSTEM\_TABLE error code, 42  
 ER\_BINLOG\_UNSAFE\_SYSTEM\_VARIABLE error code, 42  
 ER\_BINLOG\_UNSAFE\_UDF error code, 42  
 ER\_BINLOG\_UNSAFE\_UPDATE\_IGNORE error code, 45  
 ER\_BINLOG\_UNSAFE\_WRITE\_AUTOINC\_SELECT error code, 46  
 ER\_BINLOG\_UNSAFE\_XA error code, 71  
 ER\_BINLOG\_WARNING\_SUPPRESSED error code, 178  
 ER\_BLOBS\_AND\_NO\_TERMINATED error code, 8  
 ER\_BLOB\_CANT\_HAVE\_DEFAULT error code, 9  
 ER\_BLOB\_FIELD\_IN\_PART\_FUNC\_ERROR error code, 138  
 ER\_BLOB\_KEY\_WITHOUT\_LENGTH error code, 14  
 ER\_BLOB\_USED\_AS\_KEY error code, 8  
 ER\_BOOST\_GEOMETRY\_CENTROID\_EXCEPTION error code, 60  
 ER\_BOOST\_GEOMETRY\_EMPTY\_INPUT\_EXCEPTION error code, 60  
 ER\_BOOST\_GEOMETRY\_INCONSISTENT\_TURNS\_EXCEPTION error code, 66  
 ER\_BOOST\_GEOMETRY\_OVERLAY\_INVALID\_INPUT\_EXCEPTION error code, 60  
 ER\_BOOST\_GEOMETRY\_SELF\_INTERSECTION\_POINT\_EXCEPTION error code, 60  
 ER\_BOOST\_GEOMETRY\_TURN\_INFO\_EXCEPTION error code, 60  
 ER\_BOOST\_GEOMETRY\_UNKNOWN\_EXCEPTION error code, 60  
 ER\_BOOTSTRAP\_CANT\_THREAD error code, 128  
 ER\_BUFPOOL\_RESIZE\_INPROGRESS error code, 69  
 ER\_BUILD\_ID error code, 385  
 ER\_BULK\_EXECUTOR\_ERROR error code, 119  
 ER\_BULK\_EXECUTOR\_INFO error code, 387  
 ER\_BULK\_LOADER\_COLUMN\_TOO\_BIG\_FOR\_LEFTOVER\_BUFFER error code, 119  
 ER\_BULK\_LOADER\_COMPONENT\_ERROR error code, 119  
 ER\_BULK\_LOADER\_FILE\_CONTAINS\_LESS\_LINES\_THAN\_IGNORED error code, 119  
 ER\_BULK\_LOADER\_FILE\_CONTAINS\_LESS\_LINES\_THAN\_IGNORED error code, 388  
 ER\_BULK\_LOADER\_INFO error code, 388  
 ER\_BULK\_LOAD\_INCOMPLETE\_FAILED error code, 119  
 ER\_BULK\_LOAD\_RESOURCE error code, 123  
 ER\_BULK\_LOAD\_SECONDARY\_ENGINE error code, 123

ER_BULK_LOAD_TABLE_HAS_INSTANT_COLS error code, 123	ER_BULK_READER_LIBCURL_ERROR error code, 119
ER_BULK_MERGE_INVALID_CHUNK error code, 123	ER_BULK_READER_LIBCURL_ERROR_LOG error code, 388
ER_BULK_MERGE_LOADER_INFO error code, 398	ER_BULK_READER_LIBCURL_INIT_FAILED error code, 119
ER_BULK_MERGE_NOT_ALL_CHUNKS_CONSUMED error code, 123	ER_BULK_READER_LIBCURL_INIT_FAILED_LOG error code, 388
ER_BULK_MULTI_READER_INFO error code, 398	ER_BULK_READER_OPEN_FILE_FAILED error code, 123
ER_BULK_MULTI_READER_OPEN_FILE_FAILED error code, 123	ER_BULK_READER_SERVER_ERROR error code, 119
ER_BULK_MULTI_READER_READ_FILE_FAILED error code, 123	ER_BULK_READER_SERVER_ERROR_LOG error code, 388
ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED error code, 119	ER_BULK_SORTING_LOADER_INFO error code, 398
ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED error code, 388	ER_BULK_SORTING_LOADER_WAIT error code, 123
ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE error code, 120	ER_BULK_SORTING_LOADER_WRITE error code, 119
ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE error code, 389	ER_BULK_WRITER_INFO error code, 398
ER_BULK_PARSER_MISSING_ENCLOSED_BY error code, 119	ER_BULK_WRITER_LIBCURL_ERROR error code, 123
ER_BULK_PARSER_MISSING_ENCLOSED_BY_LOG error code, 388	ER_BULK_WRITER_LIBCURL_ERROR_LOG error code, 399
ER_BULK_PARSER_ROW_BUFFER_MAX_TOTAL_COLS_EXCEEDED error code, 119	ER_BULK_WRITER_LIBCURL_INIT_FAILED error code, 123
ER_BULK_PARSER_ROW_BUFFER_MAX_TOTAL_COLS_EXCEEDED error code, 388	ER_BULK_WRITER_LIBCURL_INIT_FAILED_LOG error code, 398
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COMMA error code, 120	ER_CANNOT_ADD_FOREIGN_SECOND_PASSWORD error code, 337
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COMMA error code, 389	ER_CANNOT_ADD_FOREIGN_SECOND_PASSWORD error code, 136
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_ENCLOSED_BY error code, 120	ER_CANNOT_ADD_FOREIGN_BASE_COL_STORED error code, 71
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_ENCLOSED_BY error code, 389	ER_CANNOT_ADD_FOREIGN_BASE_COL_VIRTUAL error code, 70
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPE error code, 120	ER_CANNOT_ALTER_SRID_DUE_TO_INDEX error code, 82
ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPE error code, 389	ER_CANNOT_CHANGE_TO_ROOT_DIR error code, 183
ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT error code, 119	ER_CANNOT_CONVERT_STRING error code, 97
ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT error code, 388	ER_CANNOT_CREATE_VIRTUAL_INDEX_CONSTRAINT error code, 70
ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR error code, 120	ER_CANNOT_DISCARD_TEMPORARY_TABLE error code, 57
ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR error code, 388	ER_CANNOT_DROP_COLUMN_FUNCTIONAL_INDEX error code, 90
ER_BULK_READER_COMMUNICATION_ERROR error code, 119	ER_CANNOT_EXECUTE_IN_PRIMARY error code, 124
ER_BULK_READER_COMMUNICATION_ERROR_LOG error code, 388	ER_CANNOT_FIND_KEY_IN_KEYRING error code, 71
ER_BULK_READER_COULDNT_RESOLVE_HOST error code, 123	ER_CANNOT_GET_SERVER_VERSION_FROM_TABLESPACE error code, 338
ER_BULK_READER_ERROR error code, 123	ER_CANNOT_GRANT_ROLES_TO_ANONYMOUS_USER error code, 99
ER_BULK_READER_FILE_DOESNT_EXIST error code, 123	ER_CANNOT_GRANT_SYSTEM_PRIV_TO_MANDATORY_ROLE error code, 100
ER_BULK_READER_INFO error code, 388	ER_CANNOT_INTERPRET_PERSISTED_SENSITIVE_VARIABLE error code, 378

---

ER\_CANNOT\_LOAD\_FROM\_TABLE\_V2 error code, 46  
 ER\_CANNOT\_LOCK\_USER\_MANAGEMENT\_CACHES error code, 75  
 ER\_CANNOT\_LOG\_PARTIAL\_DROP\_DATABASE\_WITHOUT\_ID error code, 63  
 ER\_CANNOT\_PERSIST\_SENSITIVE\_VARIABLES error code, 116  
 ER\_CANNOT\_PURGE\_BINLOG\_WITH\_BACKUP\_LOCK error code, 115  
 ER\_CANNOT\_SET\_DATABASE\_ENCRYPTION error code, 95  
 ER\_CANNOT\_SET\_LOG\_ERROR\_SERVICES error code, 184  
 ER\_CANNOT\_SET\_SERVER\_VERSION\_IN\_TABLESPACE error code, 338  
 ER\_CANNOT\_SET\_TABLESPACE\_ENCRYPTION error code, 95  
 ER\_CANNOT\_SET\_TABLE\_ENCRYPTION error code, 95  
 ER\_CANNOT\_USER error code, 27  
 ER\_CANNOT\_USER\_REFERENCED\_AS\_DEFINER error code, 109  
 ER\_CANNOT\_USE\_AUTOEXTEND\_SIZE\_CLAUSE error code, 110  
 ER\_CANNOT\_USE\_ENCRYPTION\_CLAUSE error code, 96  
 ER\_CANT\_ACCESS\_CAPATH error code, 140  
 ER\_CANT\_AGGREGATE\_2COLLATIONS error code, 19  
 ER\_CANT\_AGGREGATE\_3COLLATIONS error code, 20  
 ER\_CANT\_AGGREGATE\_NCOLLATIONS error code, 20  
 ER\_CANT\_ALLOC\_TABLE\_OBJECT error code, 171  
 ER\_CANT\_CHANGE\_SYS\_VAR\_IN\_READ\_ONLY\_MODE error code, 120  
 ER\_CANT\_CHANGE\_TX\_CHARACTERISTICS error code, 36  
 ER\_CANT\_CHECK\_PID\_PATH error code, 246  
 ER\_CANT\_CHOWN\_DATADIR error code, 140  
 ER\_CANT\_COMBINE\_ANONYMOUS\_TO\_GTID\_AND\_AUTOCOMMIT error code, 109  
 ER\_CANT\_CREATE\_ADMIN\_THREAD error code, 336  
 ER\_CANT\_CREATE\_CACHE\_FOR\_DB\_OPT error code, 172  
 ER\_CANT\_CREATE\_DB error code, 3  
 ER\_CANT\_CREATE\_FILE error code, 3  
 ER\_CANT\_CREATE\_GEOMETRY\_OBJECT error code, 28  
 ER\_CANT\_CREATE\_HANDLER\_FILE error code, 33  
 ER\_CANT\_CREATE\_HANDLER\_OBJECT\_FOR\_TABLE error code, 171  
 ER\_CANT\_CREATE\_HANDLE\_MGR\_THREAD error code, 130  
 ER\_CANT\_CREATE\_INTERRUPT\_THREAD error code, 135  
 ER\_CANT\_CREATE\_NAMED\_PIPES\_THREAD error code, 135  
 ER\_CANT\_CREATE\_PID\_FILE error code, 134  
 ER\_CANT\_CREATE\_SCHEDULER\_THREAD error code, 131  
 ER\_CANT\_CREATE\_SHM\_THREAD error code, 135  
 ER\_CANT\_CREATE\_SHUTDOWN\_THREAD error code, 134  
 ER\_CANT\_CREATE\_TABLE error code, 3  
 ER\_CANT\_CREATE\_TABLE\_SHARE\_FROM\_FRM error code, 171  
 ER\_CANT\_CREATE\_TCPIP\_THREAD error code, 135  
 ER\_CANT\_CREATE\_TEST\_FILE error code, 134  
 ER\_CANT\_CREATE\_THREAD error code, 12  
 ER\_CANT\_CREATE\_USER\_WITH\_GRANT error code, 27  
 ER\_CANT\_CREATE\_UUID error code, 133  
 ER\_CANT\_DETACH\_SESSION\_LEFT\_BY\_PLUGIN error code, 160  
 ER\_CANT\_DO\_IMPLICIT\_COMMIT\_IN\_TRX\_WHEN\_GTID\_NEXT error code, 49  
 ER\_CANT\_DO\_THIS\_DURING\_AN\_TRANSACTION error code, 14  
 ER\_CANT\_DROP\_FIELD\_OR\_KEY error code, 9  
 ER\_CANT\_ENFORCE\_GTID\_CONSISTENCY\_WITH\_ONGOING\_C... error code, 65  
 ER\_CANT\_EXECUTE\_COMMAND\_WITH\_ASSIGNED\_GTID\_NEXT error code, 115  
 ER\_CANT\_EXECUTE\_IN\_READ\_ONLY\_TRANSACTION error code, 50  
 ER\_CANT\_FIND\_DL\_ENTRY error code, 11  
 ER\_CANT\_FIND\_SYSTEM\_REC error code, 4  
 ER\_CANT\_FIND\_UDF error code, 11  
 ER\_CANT\_GET\_STAT error code, 4  
 ER\_CANT\_HASH\_DO\_AND\_IGNORE\_RULES error code, 140  
 ER\_CANT\_IDENTIFY\_CHARSET\_USING\_DEFAULT error code, 172  
 ER\_CANT\_INCREASE\_MAX\_OPEN\_FILES error code, 138  
 ER\_CANT\_INITIALIZE\_BUILTIN\_PLUGINS error code, 140  
 ER\_CANT\_INITIALIZE\_DYNAMIC\_PLUGINS error code, 140  
 ER\_CANT\_INITIALIZE\_EARLY\_PLUGINS error code, 139  
 ER\_CANT\_INITIALIZE\_GTID error code, 139  
 ER\_CANT\_INITIALIZE\_UDF error code, 11  
 ER\_CANT\_INIT\_DBS error code, 138  
 ER\_CANT\_INIT\_SCHEDULER\_THREAD error code, 131  
 ER\_CANT\_INIT\_TC\_LOG error code, 131  
 ER\_CANT\_INIT\_TIMER error code, 141  
 ER\_CANT\_JOIN\_SHUTDOWN\_THREAD error code, 140  
 ER\_CANT\_LOCK error code, 4  
 ER\_CANT\_LOCK\_LOG\_TABLE error code, 36  
 ER\_CANT\_LOCK\_TABLE error code, 171

---

ER\_CANT\_LOCK\_TABLESPACE error code, 171  
ER\_CANT\_MODIFY\_SRID\_0 error code, 86  
ER\_CANT\_MODIFY\_SRS\_USED\_BY\_COLUMN error code, 87  
ER\_CANT\_OPEN\_AND\_LOCK\_PRIVILEGE\_TABLES error code, 152  
ER\_CANT\_OPEN\_CA error code, 140  
ER\_CANT\_OPEN\_DATADIR\_AFTER\_UPGRADE\_FAILURE error code, 173  
ER\_CANT\_OPEN\_DB\_OPT\_USING\_DEFAULT\_CHARS error code, 172  
ER\_CANT\_OPEN\_DIR error code, 173  
ER\_CANT\_OPEN\_ERROR\_LOG error code, 141  
ER\_CANT\_OPEN\_FILE error code, 4  
ER\_CANT\_OPEN\_FRM\_FILE error code, 152  
ER\_CANT\_OPEN\_LIBRARY error code, 11  
ER\_CANT\_OPEN\_TABLE\_MYSQL\_PROC error code, 173  
ER\_CANT\_PARSE\_STORED\_ROUTINE\_BODY error code, 173  
ER\_CANT\_PROCESS\_EXPRESSION\_FOR\_GENERATED\_COLUMNS error code, 351  
ER\_CANT\_READ\_DIR error code, 4  
ER\_CANT\_READ\_ERRMSG error code, 138  
ER\_CANT\_READ\_FRM\_FILE error code, 152  
ER\_CANT\_READ\_TABLE\_MYSQL\_PROC error code, 173  
ER\_CANT\_REMOVE\_ALL\_FIELDS error code, 9  
ER\_CANT\_REMOVE\_PID\_FILE error code, 134  
ER\_CANT\_RENAME\_LOG\_TABLE error code, 37  
ER\_CANT\_REOPEN\_TABLE error code, 12  
ER\_CANT\_REPLICATE\_ANONYMOUS\_WITH\_AUTO\_POSITION error code, 326  
ER\_CANT\_REPLICATE\_ANONYMOUS\_WITH\_GTID\_MODE\_OFF error code, 326  
ER\_CANT\_REPLICATE\_GTID\_WITH\_GTID\_MODE\_OFFER error code, 326  
ER\_CANT\_RESET\_SOURCE error code, 71  
ER\_CANT\_SAVE\_GTIDS error code, 140  
ER\_CANT\_SET\_DATA\_DIR error code, 335  
ER\_CANT\_SET\_ERROR\_LOG\_SERVICE error code, 86  
ER\_CANT\_SET\_ERROR\_SUPPRESSION\_LIST error code, 88  
ER\_CANT\_SET\_ERROR\_SUPPRESSION\_LIST\_FROM\_COMMAND\_LINE error code, 330  
ER\_CANT\_SET\_GTID\_MODE error code, 65  
ER\_CANT\_SET\_GTID\_NEXT\_LIST\_TO\_NON\_NULL\_WHEN\_GTID\_MODE\_IS\_ON error code, 50  
ER\_CANT\_SET\_GTID\_NEXT\_TO\_ANONYMOUS\_WHEN\_GTID\_MODE\_IS\_ON error code, 50  
ER\_CANT\_SET\_GTID\_NEXT\_TO\_AUTOMATIC\_TAGGED\_WHEN\_GTID\_MODE\_IS\_ON error code, 124  
ER\_CANT\_SET\_GTID\_NEXT\_TO\_GTID\_WHEN\_GTID\_MODE\_IS\_ON error code, 50  
ER\_CANT\_SET\_GTID\_NEXT\_WHEN\_OWNING\_GTID error code, 50  
ER\_CANT\_SET\_GTID\_PURGED\_DUE\_SETS\_CONSTRAINTS error code, 75  
ER\_CANT\_SET\_GTID\_PURGED\_WHEN\_GTID\_EXECUTED\_IN\_ERROR error code, 53  
ER\_CANT\_SET\_GTID\_PURGED\_WHEN\_OWNED\_GTIDS\_IS\_EMPTY error code, 54  
ER\_CANT\_SET\_HANDLER\_REFERENCE\_FOR\_TABLE error code, 171  
ER\_CANT\_SET\_PATH\_FOR error code, 173  
ER\_CANT\_SET\_PERSISTED error code, 121  
ER\_CANT\_SET\_SQL\_AFTER\_OR\_BEFORE\_GTIDS\_WITH\_A\_VALID\_ERROR error code, 110  
ER\_CANT\_SET\_UP\_PERSISTED\_VALUES error code, 140  
ER\_CANT\_SET\_VARIABLE\_WHEN\_OWNING\_GTID error code, 67  
ER\_CANT\_START\_ERROR\_LOG\_SERVICE error code, 182  
ER\_CANT\_STAT\_DATADIR error code, 140  
ER\_CANT\_STAT\_FILE error code, 177  
ER\_CANT\_UPDATE\_USED\_TABLE\_IN\_CREATE\_TABLE\_SELECT error code, 47  
ER\_CANT\_UPDATE\_USED\_TABLE\_IN\_SF\_OR\_TRG error code, 29  
ER\_CANT\_UPDATE\_WITH\_READLOCK error code, 17  
ER\_CANT\_UPGRADE\_GENERATED\_COLUMNS\_TO\_DD error code, 171  
ER\_CANT\_USE\_ANONYMOUS\_TO\_GTID\_WITH\_GTID\_MODE\_OFF error code, 109  
ER\_CANT\_USE\_AUTO\_POSITION\_WITH\_GTID\_MODE\_OFF error code, 65  
ER\_CANT\_USE\_GTID\_ONLY\_WITH\_GTID\_MODE\_NOT\_ON error code, 114  
ER\_CANT\_USE\_OPTION\_HERE error code, 18  
ER\_CANT\_USE\_SAME\_UUID\_AS\_GROUP\_NAME error code, 110  
ER\_CANT\_USE\_SAME\_UUID\_AS\_VIEW\_CHANGE\_UUID error code, 111  
ER\_CANT\_WAIT\_FOR\_EXECUTED\_GTID\_SET\_WHILE\_OWNING\_GTID error code, 70  
ER\_CAPACITY\_EXCEEDED error code, 70  
ER\_CAPACITY\_EXCEEDED\_IN\_PARSER error code, 71  
ER\_CAPACITY\_EXCEEDED\_IN\_RANGE\_OPTIMIZER error code, 70  
ER\_CA\_SELF\_SIGNED error code, 133  
ER\_CHANGE\_SOURCE error code, 131  
ER\_CHANGE\_SOURCE\_GTID\_CONSISTENCY error code, 131  
ER\_CHANGE\_SOURCE\_IS\_ON error code, 131  
ER\_CHANGED\_MAX\_CONNECTIONS error code, 137  
ER\_CHANGED\_MAX\_OPEN\_FILES error code, 137  
ER\_CHANGED\_TABLE\_OPEN\_CACHE error code, 138  
ER\_CHANGE\_REPLICATION\_SOURCE\_NO\_OPTIONS\_FOR\_SOURCE error code, 113

---

---

ER\_CHANGE\_REP\_SOURCE\_CANT\_DISABLE\_AUTO\_POSITION\_WITH\_GTID\_ONLY TIMEOUT error code, 111  
 error code, 114  
 ER\_CHANGE\_REP\_SOURCE\_CANT\_DISABLE\_AUTO\_POSITION\_WITH\_GTID\_ONLY KEY\_POSITIONS\_KEY\_INVALID error code, 114  
 error code, 102  
 ER\_CHANGE\_REP\_SOURCE\_CANT\_DISABLE\_GTID\_ONLY\_WITH\_GTID\_ONLY KEY\_POSITIONS\_KEY\_TOO\_LONG error code, 114  
 error code, 103  
 ER\_CHANGE\_REP\_SOURCE\_CANT\_DISABLE\_REQ\_ROW\_FORMAT\_WITH\_GTID\_ONLY KEY\_TYPE\_INVALID error code, 113  
 error code, 102  
 ER\_CHANGE\_REP\_SOURCE\_GR\_CHANNEL\_WITH\_GTID\_ONLY\_WITH\_GTID\_ONLY UDF\_KEY\_TYPE\_TOO\_LONG error code, 114  
 error code, 103  
 ER\_CHANGE\_RPL\_INFO\_REPOSITORY\_FAILURE ER\_CLIENT\_LOCAL\_FILES\_DISABLED error code, 47  
 error code, 104  
 ER\_CHANGE\_RPL\_SRC\_WRONG\_COMPRESSION\_ALGORITHM PRIVILEGE\_CHECKS\_USER\_CANNOT\_BE\_ANONYMOUS error code, 111  
 error code, 102  
 ER\_CHANGE\_SOURCE\_PASSWORD\_LENGTH error ER\_CLIENT\_PRIVILEGE\_CHECKS\_USER\_CORRUPT code, 61  
 error code, 102  
 ER\_CHANGE\_SOURCE\_WRONG\_COMPRESSION\_ALGORITHM PRIVILEGE\_CHECKS\_USER\_DOES\_NOT\_EXIST error code, 102  
 error code, 102  
 ER\_CHANGE\_SOURCE\_WRONG\_COMPRESSION\_ALGORITHM PRIVILEGE\_CHECKS\_USER\_NEEDS\_RPL\_APPLIED error code, 102  
 error code, 102  
 ER\_CHANGE\_SOURCE\_WRONG\_COMPRESSION\_LEVEL ER\_CLIENT\_QUERY\_FAILURE\_INVALID\_NON\_ROW\_FORMAT error code, 102  
 error code, 104  
 ER\_CHARACTER\_SET\_MISMATCH error code, 108  
 ER\_CHECKING\_TABLE error code, 171  
 ER\_CHECKREAD error code, 4  
 ER\_CHECK\_CONSTRAINT\_CLAUSE\_USING\_FK\_REFERENCES TO COLUMN error code, 95  
 error code, 190  
 ER\_CHECK\_CONSTRAINT\_DUP\_NAME error code, 95  
 ER\_CHECK\_CONSTRAINT\_FUNCTION\_IS\_NOT\_ALLOWED TO CLONE error code, 94  
 error code, 81  
 ER\_CHECK\_CONSTRAINT\_NAMED\_FUNCTION\_IS\_NOT\_ALLOWED TO CLONE error code, 94  
 error code, 99  
 ER\_CHECK\_CONSTRAINT\_NOT\_FOUND error code, 95  
 ER\_CHECK\_CONSTRAINT\_REFERS\_AUTO\_INCREMENT TO CLONE error code, 95  
 error code, 98  
 ER\_CHECK\_CONSTRAINT\_REFERS\_UNKNOWN\_COLUMN TO CLONE error code, 95  
 error code, 98  
 ER\_CHECK\_CONSTRAINT\_ROW\_VALUE error code, 95  
 ER\_CHECK\_CONSTRAINT\_VARIABLES error code, 94  
 ER\_CHECK\_CONSTRAINT\_PLUGIN\_MATCH error code, 94  
 ER\_CHECK\_CONSTRAINT\_PLUGIN\_NOT\_LOADED\_TRACE error code, 94  
 error code, 190  
 ER\_CHECK\_CONSTRAINT\_VIOLATED error code, 95  
 ER\_CHECK\_NOT\_IMPLEMENTED error code, 14  
 ER\_CHECK\_NO\_SUCH\_TABLE error code, 14  
 ER\_CHECK\_TABLE\_INSTANT\_VERSION\_BIT\_SET error code, 390  
 ER\_CHECK\_TABLE\_MIN\_REC\_FLAG\_NOT\_SET error code, 392  
 ER\_CHECK\_TABLE\_MIN\_REC\_FLAG\_SET error code, 391  
 ER\_CLIENT\_DOES\_NOT\_SUPPORT error code, 82  
 ER\_CLIENT\_FILE\_PRIVILEGE\_FOR\_REPLICATION\_CHECKS error code, 117  
 ER\_CLIENT\_GTID\_UNSAFE\_CREATE\_DROP\_TEMP\_TABLES error code, 89  
 ER\_CLIENT\_LOCAL\_FILES\_DISABLED error code, 104  
 ER\_CLIENT\_PRIVILEGE\_CHECKS\_USER\_CANNOT\_BE\_ANONYMOUS error code, 102  
 ER\_CLIENT\_PRIVILEGE\_CHECKS\_USER\_CORRUPT error code, 102  
 ER\_CLIENT\_PRIVILEGE\_CHECKS\_USER\_DOES\_NOT\_EXIST error code, 102  
 ER\_CLIENT\_PRIVILEGE\_CHECKS\_USER\_NEEDS\_RPL\_APPLIED error code, 102  
 ER\_CLIENT\_QUERY\_FAILURE\_INVALID\_NON\_ROW\_FORMAT error code, 104  
 ER\_CLONE\_CHARSET error code, 98  
 ER\_CLONE\_CLIENT\_TRACE error code, 334  
 ER\_CLONE\_CONFIG error code, 98  
 ER\_CLONE\_CREATE\_HANDLER\_FAIL\_TRACE error code, 190  
 ER\_CLONE\_DDL\_IN\_PROGRESS error code, 81  
 ER\_CLONE\_DISALLOWED error code, 99  
 ER\_CLONE\_DISK\_SPACE error code, 98  
 ER\_CLONE\_DONOR error code, 98  
 ER\_CLONE\_DONOR\_TRACE error code, 334  
 ER\_CLONE\_DONOR\_VERSION error code, 98  
 ER\_CLONE\_ENCRYPTION error code, 98  
 ER\_CLONE\_HANDLER\_EXIST\_TRACE error code, 190  
 ER\_CLONE\_IN\_PROGRESS error code, 98  
 ER\_CLONE\_LOOPBACK error code, 98  
 ER\_CLONE\_NETWORK\_PACKET error code, 105  
 ER\_CLONE\_OS error code, 98  
 ER\_CLONE\_PLATFORM error code, 98  
 ER\_CLONE\_PLUGIN\_MATCH error code, 98  
 ER\_CLONE\_PLUGIN\_NOT\_LOADED\_TRACE error code, 190  
 ER\_CLONE\_PROTOCOL error code, 98  
 ER\_CLONE\_PROTOCOL\_TRACE error code, 334  
 ER\_CLONE\_SERVER\_TRACE error code, 334  
 ER\_CLONE\_SHUTDOWN\_TRACE error code, 347  
 ER\_CLONE\_SYS\_CONFIG error code, 98  
 ER\_CLONE\_TOO\_MANY\_CONCURRENT\_CLONES error code, 81  
 ER\_CMD\_NEED\_SUPER error code, 81  
 ER\_COALESCE\_ONLY\_ON\_HASH\_PARTITION error code, 333  
 ER\_COALESCE\_PARTITION\_NO\_PARTITION error code, 334  
 ER\_CREATE\_TEMP\_TABLES\_IN\_TRX\_IN\_SBR error code, 34  
 ER\_COLLATION\_CHARSET\_MISMATCH error code, 19

---

ER_COLUMNACCESS_DENIED_ERROR error code, 12	ER_COMPONENT_EE_DATA_DECRYPTION_ERROR error code, 385
ER_COLUMN_CHANGE_SIZE error code, 99	ER_COMPONENT_EE_DATA_ENCRYPTION_ERROR error code, 385
ER_COLUMN_CHECK_CONSTRAINT_REFERENCES_CANT_BE_DELETED error code, 94	ER_COMPONENT_EE_DATA_LENGTH_OUT_OF_RANGE error code, 385
ER_COL_COUNT_DOESNT_MATCH_CORRUPTED_V2 error code, 51	ER_COMPONENT_EE_DATA_SIGN_ERROR error code, 385
ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE error code, 36	ER_COMPONENT_EE_FUNCTION_DEREGISTRATION_FAILURE error code, 384
ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE_V2 error code, 58	ER_COMPONENT_EE_FUNCTION_INVALID_ALGORITHM error code, 384
ER_COMMAND_BACKEND_FAILED_TO_FETCH_SECURITY_CODE error code, 117	ER_COMPONENT_EE_FUNCTION_INVALID_ARGUMENTS error code, 384
ER_COMMAND_SERVICE_BACKEND_FAILED error code, 117	ER_COMPONENT_EE_FUNCTION_KEY_LENGTH_OUT_OF_RANGE error code, 384
ER_COMMENT_CONTAINS_INVALID_STRING error code, 115	ER_COMPONENT_EE_FUNCTION_PRIVATE_KEY_GENERATION_FAILURE error code, 384
ER_COMMIT_NOT_ALLOWED_IN_SF_OR_TRG error code, 28	ER_COMPONENT_EE_FUNCTION_PUBLIC_KEY_GENERATION_FAILURE error code, 384
ER_COMPONENTS_CANT_ACQUIRE_SERVICE_IMPLEMENTATION error code, 74	ER_COMPONENT_EE_FUNCTION_REGISTRATION_FAILURE error code, 384
ER_COMPONENTS_CANT_LOAD error code, 74	ER_COMPONENT_EE_INSUFFICIENT_LENGTH error code, 385
ER_COMPONENTS_CANT_RELEASE_SERVICE error code, 75	ER_COMPONENT_EE_OPENSSL_ERROR error code, 385
ER_COMPONENTS_CANT_SATISFY_DEPENDENCY error code, 74	ER_COMPONENT_EE_SYS_VAR_DEREGISTRATION_FAILURE error code, 384
ER_COMPONENTS_CANT_UNLOAD error code, 75	ER_COMPONENT_EE_SYS_VAR_REGISTRATION_FAILURE error code, 384
ER_COMPONENTS_FAILED_TO_ACQUIRE_SERVICE_IMPLEMENTATION error code, 193	ER_COMPONENT_FILTER_CONFUSED error code, 206
ER_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP error code, 133	ER_COMPONENT_FILTER_DIAGNOSTICS error code, 86
ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_DESCRIPTOR error code, 366	ER_COMPONENT_FILTER_FLABBERGASTED error code, 80
ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_INVALID error code, 366	ER_COMPONENT_FILTER_WRONG_VALUE error code, 324
ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN error code, 133	ER_COMPONENT_KEYRING_OCI_CREATE_PRIVATE_KEY_FAILURE error code, 386
ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN_START error code, 397	ER_COMPONENT_KEYRING_OCI_INVALID_CONFIG_VAR error code, 398
ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN_STOP error code, 397	ER_COMPONENT_KEYRING_OCI_OPEN_KEY_FILE_FAILURE error code, 386
ER_COMPONENTS_LOAD_CANT_INITIALIZE error code, 75	ER_COMPONENT_KEYRING_OCI_READ_KEY_FILE_FAILURE error code, 386
ER_COMPONENTS_LOAD_CANT_REGISTER_SERVICE_IMPLEMENTATION error code, 74	ER_COMPONENT_LOCK error code, 393
ER_COMPONENTS_NO_SCHEME error code, 74	ER_COMPONENT_MANIPULATE_ROW_FAILED error code, 75
ER_COMPONENTS_NO_SCHEME_SERVICE error code, 74	ER_COMPONENT_MASKING_ABI error code, 394
ER_COMPONENTS_PERSIST_LOADER_BOOTSTRAP error code, 133	ER_COMPONENT_MASKING_ABI_REASON error code, 394
ER_COMPONENTS_UNLOAD_CANT_DEINITIALIZE error code, 75	ER_COMPONENT_MASKING_CANNOT_ACCESS_TABLE error code, 394
ER_COMPONENTS_UNLOAD_CANT_UNREGISTER_SERVICE_IMPLEMENTATION error code, 75	ER_COMPONENT_MASKING_INVALID_FLUSH_INTERVAL error code, 404
ER_COMPONENTS_UNLOAD_DUPLICATE_IN_GROUP error code, 75	ER_COMPONENT_MASKING_NOTIFICATION_REGISTRATION_FAILURE error code, 404
ER_COMPONENTS_UNLOAD_NOT_LOADED error code, 75	

---

---

ER\_COMPONENT\_MASKING\_OTHER\_ERROR error code, 394  
 ER\_COMPONENT\_MASKING\_RANDOM\_CREATE error code, 394  
 ER\_COMPONENT\_MASKING\_RANDOM\_CREATE\_REPEAT error code, 394  
 ER\_COMPONENT\_MASKING\_VAR\_REGISTRATION\_FAILURE error code, 404  
 ER\_COMPONENT\_SERVICE\_CALL error code, 393  
 ER\_COMPONENT\_SERVICE\_CALL\_RESULT error code, 393  
 ER\_COMPONENT\_TABLE\_INCORRECT error code, 75  
 ER\_COMPONENT\_UNLOCK error code, 394  
 ER\_CONCURRENT\_PROCEDURE\_USAGE error code, 115  
 ER\_CONDITIONAL\_DEBUG error code, 385  
 ER\_COND\_ITEM\_TOO\_LONG error code, 41  
 ER\_CONFIG\_OPTION\_WITHOUT\_GROUP error code, 142  
 ER\_CONFIRMING\_THE\_FUTURE error code, 136  
 ER\_CONFLICTING\_DECLARATIONS error code, 21  
 ER\_CONFLICT\_FN\_PARSE\_ERROR error code, 39  
 ER\_CONNECTIONS\_SHUTDOWN\_END error code, 398  
 ER\_CONNECTIONS\_SHUTDOWN\_START error code, 397  
 ER\_CONNECTION\_ABORTED error code, 323  
 ER\_CONNECTION\_HANDLING\_OOM error code, 134  
 ER\_CONNECTION\_METADATA error code, 15  
 ER\_CONNECT\_TO\_FOREIGN\_DATA\_SOURCE error code, 29  
 ER\_CONNECT\_TO\_SOURCE error code, 17  
 ER\_CONN\_ATTR\_TRUNCATED error code, 147  
 ER\_CONN\_CONTROL\_DELAY\_ACTION\_INIT\_FAILED error code, 207  
 ER\_CONN\_CONTROL\_ERROR\_MSG error code, 205  
 ER\_CONN\_CONTROL\_EVENT\_COORDINATOR\_INIT\_FAILURE error code, 207  
 ER\_CONN\_CONTROL\_FAILED\_TO\_SET\_CONN\_DELAY error code, 207  
 ER\_CONN\_CONTROL\_FAILED\_TO\_UPDATE\_CONN\_DELAY error code, 207  
 ER\_CONN\_CONTROL\_INVALID\_CONN\_DELAY\_TYPE error code, 207  
 ER\_CONN\_CONTROL\_STAT\_CONN\_DELAY\_TRIGGERED error code, 207  
 ER\_CONN\_CONTROL\_STAT\_CONN\_DELAY\_TRIGGERED\_ON\_DATA\_FAILURE error code, 207  
 ER\_CONN\_INIT\_CONNECT\_IGNORED error code, 206  
 ER\_CONN\_INIT\_CONNECT\_IGNORED\_MFA error code, 394  
 ER\_CONN\_LIMIT error code, 377  
 ER\_CONN\_PER\_THREAD\_NO\_THREAD error code, 145  
 ER\_CONN\_PIP\_CANT\_CREATE\_EVENT error code, 145  
 ER\_CONN\_PIP\_CANT\_CREATE\_PIPE error code, 145  
 ER\_CONN\_SHM\_CANT\_CREATE\_CONNECTION error code, 144  
 ER\_CONN\_SHM\_CANT\_CREATE\_SERVICE error code, 144  
 ER\_CONN\_SHM\_LISTENER error code, 144  
 ER\_CONN\_SOCKET\_ACCEPT\_FAILED error code, 147  
 ER\_CONN\_SOCKET\_SELECT\_FAILED error code, 147  
 ER\_CONN\_TCP\_ADDRESS error code, 145  
 ER\_CONN\_TCP\_BIND\_FAIL error code, 146  
 ER\_CONN\_TCP\_BIND\_RETRY error code, 145  
 ER\_CONN\_TCP\_CANT\_RESET\_V6ONLY error code, 145  
 ER\_CONN\_TCP\_CANT\_RESOLVE\_HOSTNAME error code, 145  
 ER\_CONN\_TCP\_CREATED error code, 145  
 ER\_CONN\_TCP\_ERROR\_WITH\_STRERROR error code, 145  
 ER\_CONN\_TCP\_IPV6\_AVAILABLE error code, 145  
 ER\_CONN\_TCP\_IPV6\_UNAVAILABLE error code, 145  
 ER\_CONN\_TCP\_IP\_NOT\_LOGGED error code, 146  
 ER\_CONN\_TCP\_IS\_THERE\_ANOTHER\_USING\_PORT error code, 145  
 ER\_CONN\_TCP\_LISTEN\_FAIL error code, 146  
 ER\_CONN\_TCP\_NO\_SOCKET error code, 145  
 ER\_CONN\_TCP\_RESOLVE\_INFO error code, 146  
 ER\_CONN\_TCP\_START\_FAIL error code, 146  
 ER\_CONN\_UNIX\_IS\_THERE\_ANOTHER\_USING\_SOCKET error code, 145  
 ER\_CONN\_UNIX\_LISTEN\_FAILED error code, 146  
 ER\_CONN\_UNIX\_LOCK\_FILE\_CANT\_CLOSE error code, 147  
 ER\_CONN\_UNIX\_LOCK\_FILE\_CANT\_CREATE error code, 146  
 ER\_CONN\_UNIX\_LOCK\_FILE\_CANT\_DELETE error code, 147  
 ER\_CONN\_UNIX\_LOCK\_FILE\_CANT\_OPEN error code, 146  
 ER\_CONN\_UNIX\_LOCK\_FILE\_CANT\_READ error code, 146  
 ER\_CONN\_UNIX\_LOCK\_FILE\_CANT\_SYNC error code, 147  
 ER\_CONN\_UNIX\_LOCK\_FILE\_CANT\_WRITE error code, 147  
 ER\_CONN\_UNIX\_LOCK\_FILE\_EMPTY error code, 146  
 ER\_CONN\_UNIX\_LOCK\_FILE\_FAIL error code, 146  
 ER\_CONN\_UNIX\_LOCK\_FILE\_GIVING\_UP error code, 146  
 ER\_CONN\_UNIX\_LOCK\_FILE\_PIDLESS error code, 147  
 ER\_CONN\_UNIX\_NO\_BIND\_NO\_START error code, 146  
 ER\_CONN\_UNIX\_NO\_FD error code, 146  
 ER\_CONN\_UNIX\_PATH\_TOO\_LONG error code, 146

---



---

ER\_CONN\_UNIX\_PID\_CLAIMED\_SOCKET\_FILE error code, 145  
 ER\_CONSECUTIVE\_REORG\_PARTITIONS error code, 34  
 ER\_CONSTRAINT\_NOT\_FOUND error code, 103  
 ER\_CONVERT\_MULTI\_VALUE error code, 395  
 ER\_CON\_COUNT\_ERROR error code, 5  
 ER\_CORE\_VALUES error code, 135  
 ER\_CORRUPTED\_JSON\_DIFF error code, 82  
 ER\_CORRUPT\_HELP\_DB error code, 18  
 ER\_COULD\_NOT\_APPLY\_JSON\_DIFF error code, 82  
 ER\_COULD\_NOT\_CREATE\_WINDOWS\_REGISTRY\_KEYS error code, 332  
 ER\_COULD\_NOT\_REINITIALIZE\_AUDIT\_LOG\_FILTERS error code, 327  
 ER\_CRASHED\_ON\_REPAIR error code, 15  
 ER\_CRASHED\_ON\_USAGE error code, 15  
 ER\_CREATED\_SYSTEM\_WITH\_VERSION error code, 188  
 ER\_CREATE\_FILEGROUP\_FAILED error code, 35  
 ER\_CREATE\_SELECT\_WITH\_GIPK\_DISALLOWED\_IN\_SCHEMA error code, 117  
 ER\_CREATING\_NEW\_UUID error code, 133  
 ER\_CREATING\_NEW\_UUID\_FIRST\_START error code, 182  
 ER\_CREDENTIALLESS\_AUTO\_USER\_BAD error code, 134  
 ER\_CREDENTIALS\_CONTRADICT\_TO\_HISTORY error code, 81  
 ER\_CTE\_MAX\_RECURSION\_DEPTH error code, 81  
 ER\_CTE\_RECURSIVE\_FORBIDDEN\_JOIN\_ORDER error code, 77  
 ER\_CTE\_RECURSIVE\_FORBIDS\_AGGREGATION error code, 77  
 ER\_CTE\_RECURSIVE\_NOT\_UNION error code, 117  
 ER\_CTE\_RECURSIVE\_REQUIRES\_NONRECURSIVE\_FILTERS error code, 77  
 ER\_CTE\_RECURSIVE\_REQUIRES\_SINGLE\_REFERENCE error code, 77  
 ER\_CTE\_RECURSIVE\_REQUIRES\_UNION error code, 77  
 ER\_CURRENT\_PASSWORD\_CANNOT\_BE\_RETAINED error code, 100  
 ER\_CURRENT\_PASSWORD\_NOT\_REQUIRED error code, 100  
 ER\_CUT\_VALUE\_GROUP\_CONCAT error code, 19  
 ER\_CYCLE\_TIMER\_IS\_NOT\_AVAILABLE error code, 190  
 ER\_DATABASE\_NAME error code, 39  
 ER\_DATA\_DIRECTORY\_UNUSABLE error code, 332  
 ER\_DATA\_DIRECTORY\_UNUSABLE\_DELETABLE error code, 347  
 ER\_DATA\_OUT\_OF\_RANGE error code, 43  
 ER\_DATA\_TOO\_LONG error code, 27  
 ER\_DATETIME\_FUNCTION\_OVERFLOW error code, 29  
 ER\_DA\_AUTH\_ID\_WITH\_SYSTEM\_USER\_PRIV\_IN\_MANDATORY\_ROLES error code, 99  
 ER\_DA\_CANT\_OPEN\_ERROR\_LOG error code, 108  
 ER\_DA\_CONN\_LIMIT error code, 115  
 ER\_DA\_ERROR\_LOG\_COMPONENT\_FLUSH\_FAILED error code, 112  
 ER\_DA\_ERROR\_LOG\_MULTIPLE\_FILTERS error code, 108  
 ER\_DA\_ERROR\_LOG\_TABLE\_DISABLED error code, 108  
 ER\_DA\_GLOBAL\_CONN\_LIMIT error code, 115  
 ER\_DA\_GRP\_RPL\_RECOVERY\_ENDPOINT\_FORMAT error code, 106  
 ER\_DA\_GRP\_RPL\_RECOVERY\_ENDPOINT\_INVALID error code, 106  
 ER\_DA\_GRP\_RPL\_STARTED\_AUTO\_REJOIN error code, 101  
 ER\_DA\_INVALID\_CONDITION\_NUMBER error code, 48  
 ER\_DA\_NO\_ERROR\_LOG\_PARSER\_CONFIGURED error code, 108  
 ER\_DA\_OOM error code, 104  
 ER\_DA\_PLUGIN\_INSTALL\_ERROR error code, 99  
 ER\_DA\_RPL\_GTID\_TABLE\_CANNOT\_OPEN error code, 99  
 ER\_DA\_SSL\_FIPS\_MODE\_ERROR error code, 114  
 ER\_DA\_SSL\_LIBRARY\_ERROR error code, 99  
 ER\_DA\_UDF\_INVALID\_ARGUMENT\_TO\_SET\_CHARSET error code, 104  
 ER\_DA\_UDF\_INVALID\_CHARSET error code, 103  
 ER\_DA\_UDF\_INVALID\_CHARSET\_SPECIFIED error code, 103  
 ER\_DA\_UDF\_INVALID\_COLLATION error code, 103  
 ER\_DA\_UDF\_INVALID\_EXTENSION\_ARGUMENT\_TYPE error code, 103  
 ER\_DA\_UDF\_INVALID\_RETURN\_TYPE\_TO\_SET\_CHARSET error code, 104  
 ER\_DA\_UNKNOWN\_ERROR\_NUMBER error code, 99  
 ER\_DBACCESS\_DENIED\_ERROR error code, 5  
 ER\_DEBUG\_CHECK\_SHARES\_DROPPED error code, 160  
 ER\_DEBUG\_CHECK\_SHARES\_INFO error code, 160  
 ER\_DEBUG\_CHECK\_SHARES\_OPEN error code, 160  
 ER\_DB\_ACCESS\_DENIED error code, 99  
 ER\_DB\_CREATE\_EXISTS error code, 4  
 ER\_DB\_DROP\_EXISTS error code, 4  
 ER\_DB\_DROP\_RMDIR error code, 4  
 ER\_DB\_DROP\_RMDIR2 error code, 79  
 ER\_DB\_OPT\_NOT\_FOUND\_USING\_DEFAULT\_CHARSET error code, 172  
 ER\_DDL\_MSG\_1 error code, 372  
 ER\_DD\_ABORTING\_PARTIAL\_UPGRADE error code, 151  
 ER\_DD\_CACHE\_NOT\_EMPTY\_AT\_SHUTDOWN error code, 130  
 ER\_DD\_CANT\_CREATE\_OBJECT\_KEY error code, 130  
 ER\_DD\_CANT\_CREATE\_SP error code, 171  
 ER\_DD\_CANT\_FETCH\_TABLE\_DATA error code, 171

---

---

ER\_DD\_CANT\_FIX\_SE\_DATA error code, 171  
 ER\_DD\_CANT\_GET\_OBJECT\_KEY error code, 130  
 ER\_DD\_CANT\_RESOLVE\_VIEW error code, 142  
 ER\_DD\_CREATED\_FOR\_UPGRADE error code, 151  
 ER\_DD\_ERROR\_CREATING\_ENTRY error code, 171  
 ER\_DD\_FAILSAFE error code, 129  
 ER\_DD\_FRM\_EXISTS\_FOR\_TABLE error code, 151  
 ER\_DD\_INITIALIZE error code, 193  
 ER\_DD\_INITIALIZE\_SQL\_ERROR error code, 328  
 ER\_DD\_INIT\_FAILED error code, 130  
 ER\_DD\_INIT\_UPGRADE\_FAILED error code, 129  
 ER\_DD\_METADATA\_NOT\_FOUND error code, 130  
 ER\_DD\_MINOR\_DOWNGRADE error code, 194  
 ER\_DD\_MINOR\_DOWNGRADE\_VERSION\_NOT\_SUPPORTED error code, 194  
 ER\_DD\_NO\_VERSION\_FOUND error code, 194  
 ER\_DD\_NO\_WRITES\_NO\_REPOPULATION error code, 129  
 ER\_DD\_OBJECT\_RELEASER\_REMAINS error code, 130  
 ER\_DD\_OBJECT\_REMAINS error code, 130  
 ER\_DD\_OBJECT\_REMAINS\_IN\_RELEASER error code, 130  
 ER\_DD\_POPULATING\_TABLES\_FAILED error code, 130  
 ER\_DD\_RESTART error code, 193  
 ER\_DD\_SCHEMA\_NOT\_FOUND error code, 151  
 ER\_DD\_SE\_INIT\_FAILED error code, 151  
 ER\_DD\_TABLESPACE\_NOT\_FOUND error code, 141  
 ER\_DD\_TABLE\_NOT\_FOUND error code, 151  
 ER\_DD\_TRG\_CANT\_ADD error code, 141  
 ER\_DD\_TRG\_CONNECTION\_COLLATION\_MISSING error code, 141  
 ER\_DD\_TRG\_DB\_COLLATION\_MISSING error code, 141  
 ER\_DD\_TRG\_DEFINER\_OOM error code, 141  
 ER\_DD\_TRG\_FILE\_UNREADABLE error code, 141  
 ER\_DD\_UPDATING\_PLUGIN\_MD\_FAILED error code, 130  
 ER\_DD\_UPGRADE error code, 194  
 ER\_DD\_UPGRADE\_COMPLETED error code, 345  
 ER\_DD\_UPGRADE\_DD\_OPEN\_FAILED error code, 187  
 ER\_DD\_UPGRADE\_DD\_POPULATED error code, 187  
 ER\_DD\_UPGRADE\_FAILED\_FIND\_VALID\_DATA\_DIR error code, 188  
 ER\_DD\_UPGRADE\_FAILED\_INIT\_DD\_SE error code, 188  
 ER\_DD\_UPGRADE\_FAILED\_TO\_ACQUIRE\_TABLESPACE error code, 187  
 ER\_DD\_UPGRADE\_FAILED\_TO\_CREATE\_INDEX\_STATS error code, 188  
 ER\_DD\_UPGRADE\_FAILED\_TO\_CREATE\_TABLE\_STATS error code, 187  
 ER\_DD\_UPGRADE\_FAILED\_TO\_FETCH\_TABLES error code, 187  
 ER\_DD\_UPGRADE\_FAILED\_TO\_FETCH\_TABLESPACE error code, 187  
 ER\_DD\_UPGRADE\_FAILED\_TO\_RESOLVE\_TABLESPACE\_ENG error code, 187  
 ER\_DD\_UPGRADE\_FAILED\_TO\_UPDATE\_VER\_NO\_IN\_TABLES error code, 193  
 ER\_DD\_UPGRADE\_FOUND\_PARTIALLY\_UPGRADED\_DD\_ABO error code, 188  
 ER\_DD\_UPGRADE\_FOUND\_PARTIALLY\_UPGRADED\_DD\_CON error code, 188  
 ER\_DD\_UPGRADE\_FOUND\_PREPARED\_XA\_TRANSACTION error code, 353  
 ER\_DD\_UPGRADE\_INDEX\_STATS\_MIGRATE\_COMPLETED error code, 188  
 ER\_DD\_UPGRADE\_INFO\_FILE\_CLOSE\_FAILED error code, 187  
 ER\_DD\_UPGRADE\_INFO\_FILE\_OPEN\_FAILED error code, 187  
 ER\_DD\_UPGRADE\_OFF error code, 194  
 ER\_DD\_UPGRADE\_RENAME\_IDX\_STATS\_FILE\_FAILED error code, 187  
 ER\_DD\_UPGRADE\_SCHEMA\_UNAVAILABLE error code, 194  
 ER\_DD\_UPGRADE\_SDI\_INFO\_UPDATE\_FAILED error code, 188  
 ER\_DD\_UPGRADE\_SE\_LOGS\_FAILED error code, 188  
 ER\_DD\_UPGRADE\_START error code, 188  
 ER\_DD\_UPGRADE\_TABLESPACE\_MIGRATION\_FAILED error code, 187  
 ER\_DD\_UPGRADE\_TABLE\_INTACT\_ERROR error code, 192  
 ER\_DD\_UPGRADE\_TABLE\_STATS\_MIGRATE\_COMPLETED error code, 188  
 ER\_DD\_UPGRADE\_VERSION\_NOT\_SUPPORTED error code, 194  
 ER\_DD\_UPGRADE\_VIEW\_COLUMN\_NAME\_TOO\_LONG error code, 193  
 ER\_DD\_VERSION\_FOUND error code, 129  
 ER\_DD\_VERSION\_INSTALLED error code, 129  
 ER\_DD\_VERSION\_UNSUPPORTED error code, 129  
 ER\_DD\_VIEW\_CANT\_ALLOC\_CHARSET error code, 129  
 ER\_DD\_VIEW\_CANT\_CREATE error code, 130  
 ER\_DD\_VIEW\_WITHOUT\_DEFINER error code, 142  
 ER\_DEBUG\_SYNC\_EXECUTED error code, 131  
 ER\_DEBUG\_SYNC\_HIT error code, 131  
 ER\_DEBUG\_SYNC\_HIT\_LIMIT error code, 40  
 ER\_DEBUG\_SYNC\_OOM error code, 131  
 ER\_DEBUG\_SYNC\_THREAD\_MAX error code, 131  
 ER\_DEBUG\_SYNC\_TIMEOUT error code, 40  
 ER\_DEFAULT\_AS\_VAL\_GENERATED error code, 91  
 ER\_DEFAULT\_SE\_UNAVAILABLE error code, 141  
 ER\_DEFAULT\_VAL\_GENERATED\_FUNCTION\_IS\_NOT\_ALLOWED error code, 91  
 ER\_DEFAULT\_VAL\_GENERATED\_NAMED\_FUNCTION\_IS\_NOT\_ALLOWED error code, 91  
 ER\_DEFAULT\_VAL\_GENERATED\_NON\_PRIOR error code, 90

---

ER\_DEFAULT\_VAL\_GENERATED\_REF\_AUTO\_INC error code, 91  
 ER\_DEFAULT\_VAL\_GENERATED\_ROW\_VALUE error code, 91  
 ER\_DEFAULT\_VAL\_GENERATED\_VARIABLES error code, 91  
 ER\_DEFINITION\_CONTAINS\_INVALID\_STRING error code, 115  
 ER\_DEPART\_WITH\_GRACE error code, 133  
 ER\_DEPENDENT\_BY\_CHECK\_CONSTRAINT error code, 105  
 ER\_DEPENDENT\_BY\_DEFAULT\_GENERATED\_VALUE error code, 90  
 ER\_DEPENDENT\_BY\_FUNCTIONAL\_INDEX error code, 96  
 ER\_DEPENDENT\_BY\_GENERATED\_COLUMN error code, 65  
 ER\_DEPENDENT\_BY\_PARTITION\_FUNC error code, 97  
 ER\_DEPRECATED\_NATIONAL error code, 87  
 ER\_DEPRECATED\_PERSISTED\_VARIABLE\_WITH\_ALIAS error code, 371  
 ER\_DEPRECATED\_SYNTAX\_NO\_REPLACEMENT error code, 192  
 ER\_DEPRECATED\_SYNTAX\_WITH\_REPLACEMENT error code, 192  
 ER\_DEPRECATED\_TIMESTAMP\_IMPLICIT\_DEFAULTS error code, 134  
 ER\_DEPRECATED\_UTF8\_ALIAS error code, 87  
 ER\_DEPRECATED\_MSG\_NO\_REPLACEMENT error code, 192  
 ER\_DEPRECATED\_MSG\_WITH\_REPLACEMENT error code, 181  
 ER\_DERIVED\_MUST\_HAVE\_ALIAS error code, 18  
 ER\_DES\_FILE\_WRONG\_KEY error code, 142  
 ER\_DETACHED\_SESSIONS\_LEFT\_BY\_PLUGIN error code, 160  
 ER\_DETACHING\_SESSION\_LEFT\_BY\_PLUGIN error code, 160  
 ER\_DIMENSION\_UNSUPPORTED error code, 62  
 ER\_DISABLED\_STORAGE\_ENGINE error code, 69  
 ER\_DISABLED\_STORAGE\_ENGINE\_AS\_DEFAULT error code, 131  
 ER\_DISABLE\_AUTO\_POSITION\_REQUIRES\_ASYNC\_REPLICATION error code, 108  
 ER\_DISABLE\_GTID\_MODE\_REQUIRES\_ASYNC\_REPLICATION error code, 107  
 ER\_DISALLOWED\_OPERATION error code, 83  
 ER\_DISCARD\_FK\_CHECKS\_RUNNING error code, 51  
 ER\_DISCONNECTING\_REMAINING\_CLIENTS error code, 136  
 ER\_DISK\_FULL\_NOWAIT error code, 84  
 ER\_DIVISION\_BY\_ZERO error code, 25  
 ER\_DONT\_SUPPORT\_REPLICA\_PRESERVE\_COMMIT\_ORDER error code, 59  
 ER\_DROP\_DATABASE\_FAILED\_RMDIR\_MANUALLY error code, 193  
 ER\_DROP\_FILEGROUP\_FAILED error code, 35  
 ER\_DROP\_INDEX\_FK error code, 35  
 ER\_DROP\_LAST\_PARTITION error code, 33  
 ER\_DROP\_PARTITION\_NON\_EXISTENT error code, 33  
 ER\_DROP\_PK\_COLUMN\_TO\_DROP\_GIPK error code, 117  
 ER\_DUPLICATED\_VALUE\_IN\_TYPE error code, 21  
 ER\_DUPLICATE\_OPTION\_KEY error code, 76  
 ER\_DUPLICATE\_SYS\_VAR error code, 329  
 ER\_DUPLICATE\_TABLE\_LOCK error code, 77  
 ER\_DUP\_ARGUMENT error code, 17  
 ER\_DUP\_ENTRY error code, 7  
 ER\_DUP\_ENTRY\_AUTOINCREMENT\_CASE error code, 36  
 ER\_DUP\_ENTRY\_WITH\_KEY\_NAME error code, 37  
 ER\_DUP\_FD\_OPEN\_FAILED error code, 183  
 ER\_DUP\_FIELDNAME error code, 7  
 ER\_DUP\_INDEX error code, 53  
 ER\_DUP\_KEY error code, 4  
 ER\_DUP\_KEYNAME error code, 7  
 ER\_DUP\_LIST\_ENTRY error code, 59  
 ER\_DUP\_SIGNAL\_SET error code, 40  
 ER\_DUP\_UNIQUE error code, 14  
 ER\_DUP\_UNKNOWN\_IN\_INDEX error code, 55  
 ER\_EMPTY\_PIPELINE\_FOR\_ERROR\_LOG\_SERVICE error code, 86  
 ER\_EMPTY\_PRIVILEGE\_NAME\_IGNORED error code, 362  
 ER\_EMPTY\_QUERY error code, 7  
 ER\_ENDING\_INIT error code, 328  
 ER\_END\_INITFILE error code, 137  
 ER\_ENFORCE\_GTID\_CONSISTENCY\_WARN\_WITH\_ONGOING error code, 65  
 ER\_ENGINE\_ATTRIBUTE\_NOT\_SUPPORTED error code, 107  
 ER\_ENGINE\_CANT\_DROP\_MISSING\_TABLE error code, 79  
 ER\_ENGINE\_CANT\_DROP\_TABLE error code, 79  
 ER\_ENGINE\_COST\_FAILED\_TO\_READ error code, 157  
 ER\_ENGINE\_COST\_INVALID\_CONST\_CONSTANT\_FOR\_SELECTION error code, 157  
 ER\_ENGINE\_COST\_INVALID\_DEVICE\_TYPE\_FOR\_SELECTION error code, 157  
 ER\_ENGINE\_COST\_UNKNOWN\_COST\_CONSTANT error code, 157  
 ER\_ENGINE\_COST\_UNKNOWN\_STORAGE\_ENGINE error code, 157  
 ER\_ENGINE\_OUT\_OF\_MEMORY error code, 58  
 ER\_ERRMSG\_CANT\_FIND\_FILE error code, 151  
 ER\_ERRMSG\_CANT\_READ error code, 151  
 ER\_ERRMSG\_LOADING\_55\_STYLE error code, 151  
 ER\_ERRMSG\_MISSING\_IN\_FILE error code, 151  
 ER\_ERRMSG\_OOM error code, 151  
 ER\_ERRMSG\_REPLACEMENTS\_FAILED error code, 179

---

---

ER\_ERRMSG\_REPLACEMENT\_DODGY error code, 179  
 ER\_ERROR\_DURING\_COMMIT error code, 14  
 ER\_ERROR\_DURING\_FLUSH\_LOGS error code, 14  
 ER\_ERROR\_DURING\_FLUSH\_LOG\_COMMIT\_PHASE error code, 193  
 ER\_ERROR\_DURING\_OPTIMIZE\_TABLE error code, 171  
 ER\_ERROR\_DURING\_ROLLBACK error code, 14  
 ER\_ERROR\_ENABLING\_KEYS error code, 171  
 ER\_ERROR\_INFO\_FROM\_DA error code, 325  
 ER\_ERROR\_IN\_TRIGGER\_BODY error code, 45  
 ER\_ERROR\_IN\_UNKNOWN\_TRIGGER\_BODY error code, 45  
 ER\_ERROR\_LOG\_DESTINATION\_NOT\_A\_FILE error code, 362  
 ER\_ERROR\_ON\_MODIFYING\_GTID\_EXECUTED\_TABLE error code, 70  
 ER\_ERROR\_ON\_READ error code, 4  
 ER\_ERROR\_ON\_RENAME error code, 4  
 ER\_ERROR\_ON\_SOURCE error code, 57  
 ER\_ERROR\_ON\_WRITE error code, 4  
 ER\_ERROR\_WHEN\_EXECUTING\_COMMAND error code, 17  
 ER\_EVENT\_ALREADY\_EXISTS error code, 35  
 ER\_EVENT\_CANNOT\_ALTER\_IN\_THE\_PAST error code, 37  
 ER\_EVENT\_CANNOT\_CREATE\_IN\_THE\_PAST error code, 37  
 ER\_EVENT\_CANT\_FIND\_TIMEZONE error code, 172  
 ER\_EVENT\_CANT\_GET\_CHARSET error code, 172  
 ER\_EVENT\_CANT\_GET\_COLLATION error code, 172  
 ER\_EVENT\_CANT\_GET\_LOCK\_FOR\_DROPPING\_EVENT error code, 173  
 ER\_EVENT\_CANT\_GET\_TIMEZONE\_FROM\_FIELD error code, 172  
 ER\_EVENT\_CANT\_INIT\_QUEUE error code, 131  
 ER\_EVENT\_CANT\_OPEN\_TABLE\_MYSQL\_EVENT error code, 172  
 ER\_EVENT\_DOES\_NOT\_EXIST error code, 35  
 ER\_EVENT\_DROPPING error code, 158  
 ER\_EVENT\_ENDS\_BEFORE\_STARTS error code, 35  
 ER\_EVENT\_ERROR\_CREATING\_QUERY\_TO\_WRITE\_TO\_BINLOG error code, 173  
 ER\_EVENT\_ERROR\_DURING\_COMPILATION error code, 158  
 ER\_EVENT\_EXECUTION\_FAILED error code, 131  
 ER\_EVENT\_EXECUTION\_FAILED\_CANT\_AUTHENTICATE error code, 158  
 ER\_EVENT\_EXECUTION\_FAILED\_USER\_LOST\_EVENTS error code, 158  
 ER\_EVENT\_EXEC\_TIME\_IN\_THE\_PAST error code, 35  
 ER\_EVENT\_INTERVAL\_NOT\_POSITIVE\_OR\_TOO\_BIG error code, 35  
 ER\_EVENT\_INVALID\_CREATION\_CTX error code, 38  
 ER\_EVENT\_LAST\_EXECUTION error code, 131  
 ER\_EVENT\_MESSAGE\_STACK error code, 131  
 ER\_EVENT\_PURGING\_QUEUE error code, 131  
 ER\_EVENT\_RECURSION\_FORBIDDEN error code, 37  
 ER\_EVENT\_SAME\_NAME error code, 35  
 ER\_EVENT\_SCHEDULER\_ERROR\_GETTING\_EVENT\_OBJECT error code, 173  
 ER\_EVENT\_SCHEDULER\_ERROR\_LOADING\_FROM\_DB error code, 173  
 ER\_EVENT\_SCHEDULER\_GOT\_BAD\_DATA\_FROM\_TABLE error code, 173  
 ER\_EVENT\_SET\_VAR\_ERROR error code, 36  
 ER\_EVENT\_UNABLE\_TO\_DROP\_EVENT error code, 174  
 ER\_EXCEEDED\_MV\_KEYS\_NUM error code, 101  
 ER\_EXCEEDED\_MV\_KEYS\_SPACE error code, 101  
 ER\_EXCEPTIONS\_WRITE\_ERROR error code, 39  
 ER\_EXCESS\_ARGUMENTS error code, 138  
 ER\_EXPLAIN\_INTO\_ANALYZE\_NOT\_SUPPORTED error code, 122  
 ER\_EXPLAIN\_INTO\_FORMAT\_NOT\_SUPPORTED error code, 122  
 ER\_EXPLAIN\_INTO\_FOR\_CONNECTION\_NOT\_SUPPORTED error code, 122  
 ER\_EXPLAIN\_INTO\_IMPLICIT\_FORMAT\_NOT\_SUPPORTED error code, 122  
 ER\_EXPLAIN\_NOT\_SUPPORTED error code, 58  
 ER\_FAILED\_DEFAULT\_ROLES error code, 74  
 ER\_FAILED\_GET\_DD\_PROPERTY error code, 395  
 ER\_FAILED\_READ\_FROM\_PAR\_FILE error code, 44  
 ER\_FAILED\_REVOKE\_ROLE error code, 74  
 ER\_FAILED\_ROLE\_GRANT error code, 74  
 ER\_FAILED\_SET\_DD\_PROPERTY error code, 395  
 ER\_FAILED\_START\_MYSQLD\_DAEMON error code, 183  
 ER\_FAILED\_TO\_ACQUIRE\_LOCK\_ON\_RESOURCE\_GROUP error code, 185  
 ER\_FAILED\_TO\_ADD\_RESOURCE\_GROUP\_TO\_MAP error code, 185  
 ER\_FAILED\_TO\_ADD\_RPL\_FILTER error code, 189  
 ER\_FAILED\_TO\_ALLOCATE\_MEMORY\_FOR\_RESOURCE\_GROUP error code, 185  
 ER\_FAILED\_TO\_ALLOCATE\_MEMORY\_FOR\_RESOURCE\_GROUP error code, 185  
 ER\_FAILED\_TO\_ALLOCATE\_SSL\_BIO error code, 328  
 ER\_FAILED\_TO\_APPLY\_RESOURCE\_GROUP\_CONTROLLER error code, 185  
 ER\_FAILED\_TO\_BINLOG\_DROP\_EVENT error code, 189  
 ER\_FAILED\_TO\_BUILD\_DO\_AND\_IGNORE\_TABLE\_HASHES error code, 189  
 ER\_FAILED\_TO\_COMPRESS\_GTID\_EXECUTED\_TABLE error code, 154  
 ER\_FAILED\_TO\_COMPRESS\_GTID\_EXECUTED\_TABLE\_OOM error code, 155  
 ER\_FAILED\_TO\_CONSTRUCT\_DROP\_EVENT\_QUERY error code, 189

---

ER\_FAILED\_TO\_CREATE\_GTID\_TABLE\_COMPRESSION\_THREAD error code, 155  
 ER\_FAILED\_TO\_CREATE\_SDI\_FOR\_TABLESPACE error code, 187  
 ER\_FAILED\_TO\_DECREMENT\_NUMBER\_OF\_THREADS error code, 160  
 ER\_FAILED\_TO\_DELETE\_FROM\_GTID\_EXECUTED\_TABLE error code, 154  
 ER\_FAILED\_TO\_DESERIALIZE\_RESOURCE\_GROUP error code, 185  
 ER\_FAILED\_TO\_DETERMINE\_IF\_ROLE\_IS\_MANDATORY error code, 104  
 ER\_FAILED\_TO\_FETCH\_MANDATORY\_ROLE\_LIST error code, 104  
 ER\_FAILED\_TO\_FIND\_COLLATION\_NAME error code, 182  
 ER\_FAILED\_TO\_FIND\_DL\_ENTRY error code, 180  
 ER\_FAILED\_TO\_FIND\_LOCALE\_NAME error code, 182  
 ER\_FAILED\_TO\_FIND\_MYSQLD\_STATUS error code, 192  
 ER\_FAILED\_TO\_GENERATE\_UNIQUE\_LOGFILE error code, 180  
 ER\_FAILED\_TO\_GET\_ABSOLUTE\_PATH error code, 183  
 ER\_FAILED\_TO\_HANDLE\_DEFAULTS\_FILE error code, 329  
 ER\_FAILED\_TO\_INIT\_SYS\_VAR error code, 329  
 ER\_FAILED\_TO\_INIT\_THREAD\_ATTR\_FOR\_GTID\_TABLE\_COMPRESSION error code, 155  
 ER\_FAILED\_TO\_JOIN\_GTID\_TABLE\_COMPRESSION\_THREAD error code, 155  
 ER\_FAILED\_TO\_LOCK\_MEM error code, 137  
 ER\_FAILED\_TO\_OPEN\_COST\_CONSTANT\_TABLES error code, 158  
 ER\_FAILED\_TO\_OPEN\_SHARED\_LIBRARY error code, 180  
 ER\_FAILED\_TO\_PERSIST\_RESOURCE\_GROUP\_METADATA error code, 185  
 ER\_FAILED\_TO\_READ\_FILE error code, 180  
 ER\_FAILED\_TO\_REMOVE\_TEMP\_TABLE error code, 168  
 ER\_FAILED\_TO\_REPAIR\_TABLE error code, 168  
 ER\_FAILED\_TO\_SET\_PERSISTED\_OPTIONS error code, 192  
 ER\_FAILED\_TO\_START\_REPLICA\_THREAD error code, 189  
 ER\_FAILED\_TO\_STORE\_SDI\_FOR\_TABLESPACE error code, 187  
 ER\_FAILED\_TO\_UPDATE\_RESOURCE\_GROUP error code, 185  
 ER\_FAILED\_TO\_VALIDATE\_CERTIFICATES\_SERVER\_ERROR error code, 396  
 ER\_FAILED\_TO\_WRITE\_TO\_FILE error code, 180  
 ER\_FAIL\_CHROOT error code, 137  
 ER\_FAIL\_SETGID error code, 137  
 ER\_FAIL\_SETREGID error code, 137  
 ER\_FAIL\_SETREUID error code, 137  
 ER\_FEATURE\_DISABLED error code, 21  
 ER\_FEATURE\_DISABLED\_SEE\_DOC error code, 69  
 ER\_FEATURE\_NOT\_AVAILABLE error code, 65  
 ER\_FEATURE\_UNSUPPORTED error code, 83  
 ER\_FIELD\_IN\_GROUPING\_NOT\_GROUP\_BY error code, 79  
 ER\_FIELD\_IN\_ORDER\_NOT\_SELECT error code, 61  
 ER\_FIELD\_NOT\_FOUND\_PART\_ERROR error code, 32  
 ER\_FIELD\_SPECIFIED\_TWICE error code, 10  
 ER\_FIELD\_TYPE\_NOT\_ALLOWED\_AS\_PARTITION\_FIELD error code, 41  
 ER\_FILEGROUP\_OPTION\_ONLY\_ONCE error code, 34  
 ER\_FILE\_CORRUPT error code, 57  
 ER\_FILE\_EXISTS\_DURING\_UPGRADE error code, 173  
 ER\_FILE\_EXISTS\_ERROR error code, 8  
 ER\_FILE\_HAS\_OLD\_FORMAT error code, 181  
 ER\_FILE\_NOT\_FOUND error code, 4  
 ER\_FILE\_TYPE\_UNKNOWN error code, 152  
 ER\_FILE\_USED error code, 5  
 ER\_FIREWALL\_ACCESS\_DENIED error code, 201  
 ER\_FIREWALL\_DEPRECATED\_USER\_PROFILE error code, 369  
 ER\_FIREWALL\_FAILED\_TO\_READ\_FIREWALL\_TABLES error code, 201  
 ER\_FIREWALL\_FAILED\_TO\_REGISTER\_DYNAMIC\_PRIVILEGES error code, 201  
 ER\_FIREWALL\_INVALID\_RELOAD\_INTERVAL\_VALUE error code, 398  
 ER\_FIREWALL\_PFS\_TABLE\_REGISTER\_FAILED error code, 366  
 ER\_FIREWALL\_RECORDING\_STMT\_WAS\_TRUNCATED error code, 201  
 ER\_FIREWALL\_RECORDING\_STMT\_WITHOUT\_TEXT error code, 201  
 ER\_FIREWALL\_RELOADING\_CACHE error code, 201  
 ER\_FIREWALL\_RESET\_FOR\_USER error code, 201  
 ER\_FIREWALL\_SCHEDULER\_REGISTER\_FAILED error code, 398  
 ER\_FIREWALL\_SERVICES\_NOT\_ACQUIRED error code, 366  
 ER\_FIREWALL\_SKIPPED\_UNKNOWN\_USER\_MODE error code, 201  
 ER\_FIREWALL\_STATUS\_FLUSHED error code, 201  
 ER\_FIREWALL\_SUSPICIOUS\_STMT error code, 201  
 ER\_FIREWALL\_UDF\_REGISTER\_FAILED error code, 366  
 ER\_FIXING\_CLIENT\_CHARSET error code, 137  
 ER\_FTFS\_CANNOT\_CHANGE\_ENGINE error code, 91  
 ER\_FK\_CANNOT\_DROP\_PARENT error code, 88  
 ER\_FK\_CANNOT\_OPEN\_PARENT error code, 53  
 ER\_FK\_CANNOT\_USE\_VIRTUAL\_COLUMN error code, 88  
 ER\_FK\_COLUMN\_CANNOT\_CHANGE error code, 53

---

---

ER\_FK\_COLUMN\_CANNOT\_CHANGE\_CHILD error code, 53  
 ER\_FK\_COLUMN\_CANNOT\_DROP error code, 53  
 ER\_FK\_COLUMN\_CANNOT\_DROP\_CHILD error code, 53  
 ER\_FK\_COLUMN\_NOT\_NULL error code, 53  
 ER\_FK\_DEPTH\_EXCEEDED error code, 57  
 ER\_FK\_DUP\_NAME error code, 53  
 ER\_FK\_FAIL\_ADD\_SYSTEM error code, 52  
 ER\_FK\_INCOMPATIBLE\_COLUMNS error code, 91  
 ER\_FK\_INCORRECT\_OPTION error code, 53  
 ER\_FK\_NO\_COLUMN\_PARENT error code, 88  
 ER\_FK\_NO\_INDEX\_CHILD error code, 52  
 ER\_FK\_NO\_INDEX\_PARENT error code, 52  
 ER\_FORBID\_SCHEMA\_CHANGE error code, 30  
 ER\_FORCE\_CLOSE\_THREAD error code, 181  
 ER\_FORCING\_CLOSE error code, 8  
 ER\_FOREIGN\_DATA\_SOURCE\_DOESNT\_EXIST error code, 29  
 ER\_FOREIGN\_DATA\_STRING\_INVALID error code, 29  
 ER\_FOREIGN\_DATA\_STRING\_INVALID\_CANT\_CREATE error code, 29  
 ER\_FOREIGN\_DUPLICATE\_KEY\_OLD\_UNUSED error code, 36  
 ER\_FOREIGN\_DUPLICATE\_KEY\_WITHOUT\_CHILD\_INFO error code, 48  
 ER\_FOREIGN\_DUPLICATE\_KEY\_WITH\_CHILD\_INFO error code, 48  
 ER\_FOREIGN\_KEY\_ON\_PARTITIONED error code, 33  
 ER\_FOREIGN\_KEY\_WITH\_ATOMIC\_CREATE\_SELECT error code, 106  
 ER\_FOREIGN\_SERVER\_DOESNT\_EXIST error code, 32  
 ER\_FOREIGN\_SERVER\_EXISTS error code, 32  
 ER\_FOUND\_MISSING\_GTIDS error code, 246  
 ER\_FOUND\_ROWS\_WHILE\_REPAIRING error code, 170  
 ER\_FPARSER\_BAD\_HEADER error code, 24  
 ER\_FPARSER\_EOF\_IN\_COMMENT error code, 24  
 ER\_FPARSER\_EOF\_IN\_UNKNOWN\_PARAMETER error code, 24  
 ER\_FPARSER\_ERROR\_IN\_PARAMETER error code, 24  
 ER\_FPARSER\_TOO\_BIG\_FILE error code, 24  
 ER\_FSEEK\_FAIL error code, 26  
 ER\_FT\_BOOL\_SYNTAX\_INVALID error code, 134  
 ER\_FT\_MATCHING\_KEY\_NOT\_FOUND error code, 15  
 ER\_FULLTEXT\_FUNCTIONAL\_INDEX error code, 90  
 ER\_FULLTEXT\_NOT\_SUPPORTED\_WITH\_PARTITIONING error code, 48  
 ER\_FULLTEXT\_WITH\_ROLLUP error code, 114  
 ER\_FUNCTIONAL\_INDEX\_DATA\_IS\_TOO\_LONG error code, 101  
 ER\_FUNCTIONAL\_INDEX\_FUNCTION\_IS\_NOT\_ALLOWED error code, 90  
 ER\_FUNCTIONAL\_INDEX\_ON\_FIELD error code, 90  
 ER\_FUNCTIONAL\_INDEX\_ON\_JSON\_OR\_GEOMETRY\_FUNCTIONS error code, 89  
 ER\_FUNCTIONAL\_INDEX\_ON\_LOB error code, 90  
 ER\_FUNCTIONAL\_INDEX\_PRIMARY\_KEY error code, 90  
 ER\_FUNCTIONAL\_INDEX\_REF\_AUTO\_INCREMENT error code, 90  
 ER\_FUNCTIONAL\_INDEX\_ROW\_VALUE\_IS\_NOT\_ALLOWED error code, 93  
 ER\_FUNCTION\_DOES\_NOT\_SUPPORT\_CHARACTER\_SET error code, 107  
 ER\_FUNCTION\_NOT\_DEFINED error code, 11  
 ER\_FUNC\_INEXISTENT\_NAME\_COLLISION error code, 39  
 ER\_FUTURE\_DATE error code, 136  
 ER\_GENERATED\_COLUMN\_FUNCTION\_IS\_NOT\_ALLOWED error code, 64  
 ER\_GENERATED\_COLUMN\_NAMED\_FUNCTION\_IS\_NOT\_ALLOWED error code, 90  
 ER\_GENERATED\_COLUMN\_NON\_PRIOR error code, 65  
 ER\_GENERATED\_COLUMN\_REF\_AUTO\_INCREMENT error code, 65  
 ER\_GENERATED\_COLUMN\_ROW\_VALUE error code, 90  
 ER\_GENERATED\_COLUMN\_VARIABLES error code, 90  
 ER\_GEOMETRY\_IN\_UNKNOWN\_LENGTH\_UNIT error code, 99  
 ER\_GEOMETRY\_PARAM\_LATITUDE\_OUT\_OF\_RANGE error code, 88  
 ER\_GEOMETRY\_PARAM\_LONGITUDE\_OUT\_OF\_RANGE error code, 88  
 ER\_GET\_ERRMSG error code, 21  
 ER\_GET\_ERRNO error code, 5  
 ER\_GET\_ERRNO\_FROM\_STORAGE\_ENGINE error code, 182  
 ER\_GET\_STACKED\_DATA\_WITHOUT\_ACTIVE\_HANDLER error code, 57  
 ER\_GET\_TEMPORARY\_ERRMSG error code, 21  
 ER\_GIPK\_COLUMN ALTER NOT ALLOWED error code, 117  
 ER\_GIPK\_COLUMN\_EXISTS error code, 117  
 ER\_GIPK\_FAILED\_AUTOINC\_COLUMN\_EXISTS error code, 117  
 ER\_GIS\_DATA\_WRONG\_ENDIANESS error code, 61  
 ER\_GIS\_DIFFERENT\_SRIDS error code, 59  
 ER\_GIS\_DIFFERENT\_SRIDS\_AGGREGATION error code, 111  
 ER\_GIS\_INVALID\_DATA error code, 60  
 ER\_GIS\_MAX\_POINTS\_IN\_GEOMETRY\_OVERFLOWED error code, 67  
 ER\_GIS\_UNKNOWN\_ERROR error code, 59  
 ER\_GIS\_UNKNOWN\_EXCEPTION error code, 60  
 ER\_GIS\_UNSUPPORTED\_ARGUMENT error code, 59  
 ER\_GLOBAL\_CONN\_LIMIT error code, 377

---

ER\_GLOBAL\_VARIABLE error code, 17  
 ER\_GLOBSTAT\_CHANGE\_DURING\_QUERY error code, 101  
 ER\_GNO\_EXHAUSTED error code, 49  
 ER\_GRANT\_WRONG\_HOST\_OR\_USER error code, 12  
 ER\_GROUPING\_ON\_TIMESTAMP\_IN\_DST error code, 101  
 ER\_GROUP\_REPLICATION\_APPLIER\_INIT\_ERROR error code, 64  
 ER\_GROUP\_REPLICATION\_CERTIFICATION\_MODULE\_FAILURE error code, 402  
 ER\_GROUP\_REPLICATION\_CERTIFIER\_MESSAGE\_LARGE error code, 399  
 ER\_GROUP\_REPLICATION\_COMMAND\_FAILURE error code, 83  
 ER\_GROUP\_REPLICATION\_COMMUNICATION\_LAYER\_ERROR error code, 64  
 ER\_GROUP\_REPLICATION\_COMMUNICATION\_LAYER\_SESSION\_ERROR error code, 64  
 ER\_GROUP\_REPLICATION\_COMPRESS\_EXCEEDS\_MAX\_SIZE error code, 400  
 ER\_GROUP\_REPLICATION\_COMPRESS\_OUT\_OF\_MEMORY error code, 400  
 ER\_GROUP\_REPLICATION\_COMPRESS\_PROCESS error code, 399  
 ER\_GROUP\_REPLICATION\_CONFIGURATION error code, 63  
 ER\_GROUP\_REPLICATION\_DECOMPRESS\_CORRUPTED error code, 400  
 ER\_GROUP\_REPLICATION\_DECOMPRESS\_END error code, 400  
 ER\_GROUP\_REPLICATION\_DECOMPRESS\_EXCEEDS\_MAX\_SIZE error code, 400  
 ER\_GROUP\_REPLICATION\_DECOMPRESS\_OUT\_OF\_MEMORY error code, 400  
 ER\_GROUP\_REPLICATION\_DECOMPRESS\_PROCESSOR error code, 400  
 ER\_GROUP\_REPLICATION\_DECOMPRESS\_TRUNCATED error code, 400  
 ER\_GROUP\_REPLICATION\_ERROR\_COMPRESS\_INITIALIZATION error code, 399  
 ER\_GROUP\_REPLICATION\_ERROR\_DECOMPRESS\_INITIALIZATION error code, 400  
 ER\_GROUP\_REPLICATION\_ERROR\_RECEIVED\_WAITING\_FOR\_UPDATE error code, 401  
 ER\_GROUP\_REPLICATION\_FORCE\_MEMBERS\_COMMAND\_FAILURE error code, 117  
 ER\_GROUP\_REPLICATION\_MAX\_GROUP\_SIZE error code, 71  
 ER\_GROUP\_REPLICATION\_METADATA\_CERT\_INFO\_ENCODING\_ERROR error code, 403  
 ER\_GROUP\_REPLICATION\_METADATA\_CERT\_INFO\_ERROR error code, 402  
 ER\_GROUP\_REPLICATION\_METADATA\_CERT\_INFO\_PACKET\_COUNT error code, 403  
 ER\_GROUP\_REPLICATION\_METADATA\_CERT\_INFO\_PACKET\_EMPTY error code, 402  
 ER\_GROUP\_REPLICATION\_METADATA\_ERROR\_ON\_SEND error code, 402  
 ER\_GROUP\_REPLICATION\_METADATA\_INITIALIZATION\_FAILURE error code, 402  
 ER\_GROUP\_REPLICATION\_METADATA\_MEMORY\_ALLOC error code, 402  
 ER\_GROUP\_REPLICATION\_METADATA\_MESSAGE\_PAYLOAD\_ERROR error code, 401  
 ER\_GROUP\_REPLICATION\_METADATA\_NO\_VALID\_DONOR error code, 403  
 ER\_GROUP\_REPLICATION\_METADATA\_PAYLOAD\_DECODING\_ERROR error code, 401  
 ER\_GROUP\_REPLICATION\_METADATA\_PAYLOAD\_EMPTY error code, 401  
 ER\_GROUP\_REPLICATION\_METADATA\_PROTOBUF\_PARSING\_ERROR error code, 401  
 ER\_GROUP\_REPLICATION\_METADATA\_READ\_GTID\_EXECUTOR\_ERROR error code, 401  
 ER\_GROUP\_REPLICATION\_METADATA\_SAVE\_RECOVERY\_SESSION\_ERROR error code, 401  
 ER\_GROUP\_REPLICATION\_METADATA\_SENDER\_MAX\_SIZE error code, 399  
 ER\_GROUP\_REPLICATION\_METADATA\_SENDER\_IS\_REMOVED error code, 399  
 ER\_GROUP\_REPLICATION\_METADATA\_SEND\_ERROR error code, 401  
 ER\_GROUP\_REPLICATION\_METADATA\_SET\_IN\_RECOVERY error code, 402  
 ER\_GROUP\_REPLICATION\_NO\_CERTIFICATION\_DONOR\_AVAILABLE error code, 403  
 ER\_GROUP\_REPLICATION\_PASSWORD\_LENGTH error code, 106  
 ER\_GROUP\_REPLICATION\_PLUGIN\_NOT\_INSTALLED error code, 154  
 ER\_GROUP\_REPLICATION\_PROTOBUF\_SERIALIZING\_ERROR error code, 401  
 ER\_GROUP\_REPLICATION\_RECOVERY\_ERROR\_ADD\_GTID error code, 402  
 ER\_GROUP\_REPLICATION\_RECOVERY\_FETCHING\_GTID\_ERROR error code, 402  
 ER\_GROUP\_REPLICATION\_RECOVERY\_METADATA\_SENDING\_ERROR error code, 402  
 ER\_GROUP\_REPLICATION\_RECOVERY\_SKIPPED\_GTID\_PACKET error code, 402  
 ER\_GROUP\_REPLICATION\_RECOVERY\_STOPPED\_GTID\_FETCHING error code, 403  
 ER\_GROUP\_REPLICATION\_RUNNING error code, 63  
 ER\_GROUP\_REPLICATION\_STOP\_APPLIER\_THREAD\_TIMEOUT error code, 64  
 ER\_GROUP\_REPLICATION\_TIMEOUT\_ERROR\_FETCHING\_GTID error code, 402  
 ER\_GROUP\_REPLICATION\_UNKOWN\_COMPRESSION\_TYPE error code, 400  
 ER\_GROUP\_REPLICATION\_USER\_EMPTY\_MSG\_PACKET\_COUNT error code, 400  
 ER\_GROUP\_REPLICATION\_USER\_MANDATORY\_MSG\_PACKET\_EMPTY error code, 400

---

---

ER_GRP_OPERATION_NOT_ALLOWED_GR_MUST_STOP error code, 105	ER_GRP_RPL_AUTO_INC_OFFSET_RESET error code, 226
ER_GRP_RPL_ABORTS_AS_SSL_NOT_SUPPORTED error code, 236	ER_GRP_RPL_AUTO_INC_OFFSET_SET error code, 226
ER_GRP_RPL_ADD_GRPSID_TO_GRPGTIDSID_MAP error code, 219	ER_GRP_RPL_AUTO_INC_RESET error code, 226
ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_LOCAL_GTID error code, 227	ER_GRP_RPL_AUTO_INC_SET error code, 226
ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_REMOTE_GTID error code, 227	ER_GRP_RPL_BINLOG_DISABLED error code, 236
ER_GRP_RPL_ADD_GTID_INFO_WITH_LOCAL_GTID error code, 227	ER_GRP_RPL_BLOCK_SIZE_DIFF_FROM_GRP error code, 225
ER_GRP_RPL_ADD_GTID_INFO_WITH_REMOTE_GTID error code, 227	ER_GRP_RPL_BROADCASTING_TRANS_TO_GRP_FAILED error code, 231
ER_GRP_RPL_ADD_GTID_TO_GRPGTID_EXECUTED error code, 220	ER_GRP_RPL_BROADCAST_COMMIT_MSSG_TOO_BIG error code, 240
ER_GRP_RPL_ADD_RETRIEVED_SET_TO_GRP_GTID error code, 220	ER_GRP_RPL_BROADCAST_COMMIT_TRANS_MSSG_FAILED error code, 219
ER_GRP_RPL_ADD_VIEW_CHANGE_UUID_TO_GRP error code, 370	ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_ERROR_STATE error code, 230
ER_GRP_RPL_ALL_DONORS_LEFT_ABORT_RECOVERY error code, 228	ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_OFFLINE_MODE error code, 230
ER_GRP_RPL_ALL_OBSERVERS_UNREGISTERED error code, 235	ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_RECOVERING error code, 230
ER_GRP_RPL_APPLIER_CHANNEL_STILL_RUNNING error code, 365	ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_STOPPING error code, 230
ER_GRP_RPL_APPLIER_ERROR_PACKET_RECEIVED error code, 404	ER_GRP_RPL_CANT_GENERATE_GTID error code, 220
ER_GRP_RPL_APPLIER_EXECUTION_FATAL_ERROR error code, 219	ER_GRP_RPL_CANT_KILL_THREAD error code, 348
ER_GRP_RPL_APPLIER_HANDLER_IS_IN_USE error code, 238	ER_GRP_RPL_CANT_READ_GRP_GTID_EXTRACTED error code, 221
ER_GRP_RPL_APPLIER_HANDLER_NOT_INITIALIZED error code, 238	ER_GRP_RPL_CANT_READ_GTID error code, 221
ER_GRP_RPL_APPLIER_HANDLER_ROLE_IS_IN_USE error code, 238	ER_GRP_RPL_CANT_READ_WRITE_SET_ITEM error code, 221
ER_GRP_RPL_APPLIER_INITIALIZED error code, 235	ER_GRP_RPL_CERTIFICATE_SIZE_ERROR error code, 218
ER_GRP_RPL_APPLIER_METADATA_REPO_MUST_BE_AVAILABLE error code, 236	ER_GRP_RPL_CERTIFICATION_INITIALIZATION_FAILURE error code, 220
ER_GRP_RPL_APPLIER_NOT_STARTED_DUE_TO_RUNNING error code, 235	ER_GRP_RPL_CERTIFICATION_REC_PROCESS error code, 232
ER_GRP_RPL_APPLIER_PIPELINE_NOT_DISPOSED error code, 219	ER_GRP_RPL_CERTIFIER_MSSG_PROCESS_ERROR error code, 221
ER_GRP_RPL_APPLIER_TERMINATION_TIMED_OUT error code, 234	ER_GRP_RPL_CHANGE_GRP_MEM_NOT_PROCESSED error code, 222
ER_GRP_RPL_APPLIER_THD_EXECUTION_ABORTED error code, 219	ER_GRP_RPL_CHANNEL_THREAD_WHEN_GROUP_ACTION_RUNNING error code, 330
ER_GRP_RPL_APPLIER_THD_KILLED error code, 218	ER_GRP_RPL_CHECK_STATUS_TABLE error code, 220
ER_GRP_RPL_APPLIER_THD_SETUP_ERROR error code, 225	ER_GRP_RPL_CLONE_PROCESS_EXEC_ERROR error code, 348
ER_GRP_RPL_APPLIER_THD_START_ERROR error code, 225	ER_GRP_RPL_CLONE_PROCESS_PREPARE_ERROR error code, 347
ER_GRP_RPL_APPLIER_THD_STOP_ERROR error code, 225	ER_GRP_RPL_COMMUNICATION_SSL_CONF_INFO error code, 236
ER_GRP_RPL_APPOINTED_PRIMARY_NOT_PRESENT error code, 330	ER_GRP_RPL_CONFIGURATION_ACTION_END error code, 331
	ER_GRP_RPL_CONFIGURATION_ACTION_ERROR error code, 331
	ER_GRP_RPL_CONFIGURATION_ACTION_KILLED_ERROR error code, 331

---



---

ER_GRP_RPL_CONFIGURATION_ACTION_LOCAL_TERMINATION error code, 331	ER_GRP_RPL_ERROR_STOPPING_CHANNELS error code, 219
ER_GRP_RPL_CONFIGURATION_ACTION_START error code, 331	ER_GRP_RPL_ERROR_WHILE_WAITING_FOR_CONFLICT error code, 232
ER_GRP_RPL_CONFIG_RECOVERY error code, 229	ER_GRP_RPL_ESTABLISHING_CONN_GRP_REC_DONOR error code, 229
ER_GRP_RPL_CONFLICT_DETECTION_DISABLED error code, 221	ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_ANOTHER error code, 229
ER_GRP_RPL_CONNECTION_METADATA_REPO_MUST_BE_TABLE error code, 236	ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_DONOR error code, 229
ER_GRP_RPL_CONN_INTERNAL_PLUGIN_FAIL error code, 228	ER_GRP_RPL_EVENT_HANDLING_ERROR error code, 218
ER_GRP_RPL_CONN_KILLED error code, 396	ER_GRP_RPL_EXCEEDS_AUTO_INC_VALUE error code, 223
ER_GRP_RPL_COPY_FROM_EMPTY_STRING error code, 228	ER_GRP_RPL_EXIT_GRP_GCS_ERROR error code, 239
ER_GRP_RPL_CREATE_APPLIER_CACHE_ERROR error code, 219	ER_GRP_RPL_FAILED_TO_BOOTSTRAP_EVENT_HANDLING error code, 238
ER_GRP_RPL_CREATE_GRP_RPL_REC_CHANNEL error code, 229	ER_GRP_RPL_FAILED_TO_BROADCAST_GRP_MEMBERSHIP error code, 230
ER_GRP_RPL_CREATE_SESSION_UNABLE error code, 228	ER_GRP_RPL_FAILED_TO_BROADCAST_MEMBER_STATUS error code, 230
ER_GRP_RPL_DATA_NOT_PROVIDED_BY_MEMBER error code, 224	ER_GRP_RPL_FAILED_TO_CALL_GRP_COMMUNICATION_PLUGIN error code, 233
ER_GRP_RPL_DEBUG_OPTIONS error code, 239	ER_GRP_RPL_FAILED_TO_CONFIRM_IF_SERVER_LEFT_GROUP error code, 233
ER_GRP_RPL_DEFAULT_TABLE_ENCRYPTION_DIFFERENTIAL error code, 342	ER_GRP_RPL_FAILED_TO_CREATE_TRANS_CONTEXT error code, 231
ER_GRP_RPL_DISABLE_READ_ONLY_FAILED error code, 223	ER_GRP_RPL_FAILED_TO_ENABLE_READ_ONLY_MODE error code, 234
ER_GRP_RPL_DISABLE_SRV_READ_MODE_RESTRICTIONS error code, 222	ER_GRP_RPL_FAILED_TO_ENABLE_SUPER_READ_ONLY error code, 233
ER_GRP_RPL_DONOR_CONN_TERMINATION error code, 229	ER_GRP_RPL_FAILED_TO_EXTRACT_TRANS_WRITE_SET error code, 231
ER_GRP_RPL_DONOR_SERVER_CONN error code, 229	ER_GRP_RPL_FAILED_TO_GATHER_TRANS_WRITE_SET error code, 235
ER_GRP_RPL_DONOR_TRANS_INFO_ERROR error code, 220	ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_GRP error code, 235
ER_GRP_RPL_DONOR_VIEW_CHANGE_UUID_TRANS_INFO_ERROR error code, 371	ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_VIEW error code, 370
ER_GRP_RPL_ENABLE_READ_ONLY_FAILED error code, 223	ER_GRP_RPL_FAILED_TO_INIT_APPLIER_HANDLER error code, 238
ER_GRP_RPL_ERROR_FETCHING_GTID_EXECUTED_SET error code, 220	ER_GRP_RPL_FAILED_TO_INIT_APPLIER_MODULE error code, 235
ER_GRP_RPL_ERROR_FETCHING_GTID_SET error code, 220	ER_GRP_RPL_FAILED_TO_INIT_COMMUNICATION_ENGINE error code, 233
ER_GRP_RPL_ERROR_GTID_EXECUTION_INFO error code, 218	ER_GRP_RPL_FAILED_TO_INIT_HANDLER error code, 234
ER_GRP_RPL_ERROR_GTID_SET_EXTRACTION error code, 330	ER_GRP_RPL_FAILED_TO_INSERT_TRX_ON_TCM_ON_AFFECT error code, 337
ER_GRP_RPL_ERROR_MSG error code, 205	ER_GRP_RPL_FAILED_TO_LOG_VIEW_CHANGE error code, 383
ER_GRP_RPL_ERROR_ON_CERT_DB_INSTALL error code, 339	ER_GRP_RPL_FAILED_TO_NOTIFY_GRP_MEMBERSHIP_EVENT error code, 230
ER_GRP_RPL_ERROR_ON_MESSAGE_SENDING error code, 330	ER_GRP_RPL_FAILED_TO_PARSE_THE_GRP_NAME error code, 235
ER_GRP_RPL_ERROR_SENDING_SINGLE_PRIMARY_MSG error code, 219	ER_GRP_RPL_FAILED_TO_PARSE_THE_VIEW_CHANGE_UUID error code, 370
ER_GRP_RPL_ERROR_SET_MULTI_CONSENSUS_LEADER error code, 376	
ER_GRP_RPL_ERROR_SET_SINGLE_CONSENSUS_LEADER error code, 376	

---

---

ER_GRP_RPL_FAILED_TO_REGISTER_BINLOG_STATE_OBSERVER error code, 235	ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_FAILED error code, 227
ER_GRP_RPL_FAILED_TO_REGISTER_SERVER_STATE_OBSERVER error code, 234	ER_GRP_RPL_FETCH_TRANS_DATA_FAILED error code, 225
ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_OUTCOME_NOTIFICATION_VIEW_CHANGE_LOG_EVENT_FAILED error code, 231	ER_GRP_RPL_FETCH_VIEW_CHANGE_LOG_EVENT_FAILED error code, 227
ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_STATE_OBSERVER error code, 234	ER_GRP_RPL_FINISHED_AUTO_REJOIN error code, 342
ER_GRP_RPL_FAILED_TO_REINIT_BINLOG_CACHE_FOR_GRP error code, 231	ER_GRP_RPL_FK_WITH_CASCADE_UNSUPPORTED error code, 226
ER_GRP_RPL_FAILED_TO_SHUTDOWN_REGISTRY_MODULE error code, 234	ER_GRP_RPL_FLOW_CONTROL_STATS error code, 240
ER_GRP_RPL_FAILED_TO_START_COMMUNICATION_ENGINE error code, 233	ER_GRP_RPL_FLOW_CTRL_MAX_QUOTA_SMALLER_THAN_MAX error code, 237
ER_GRP_RPL_FAILED_TO_START_ON_BOOT error code, 235	ER_GRP_RPL_FLOW_CTRL_MIN_QUOTA_GREATER_THAN_MAX error code, 237
ER_GRP_RPL_FAILED_TO_START_ON_SECONDARY_ARTISAN_CHANNEL error code, 233	ER_GRP_RPL_MIN_RECOVERY_QUOTA_GREATER_THAN_MAX error code, 237
ER_GRP_RPL_FAILED_TO_START_WITH_INVALID_SERVER error code, 232	ER_GRP_RPL_FORCE_MEMBERS_MUST_BE_EMPTY error code, 233
ER_GRP_RPL_FAILED_TO_STOP_ON_PLUGIN_UNINSTALL error code, 235	ER_GRP_RPL_FORCE_MEMBERS_WHEN_LEAVING error code, 339
ER_GRP_RPL_FAILED_TO_UNREGISTER_BINLOG_STATE_OBSERVER error code, 235	ER_GRP_RPL_FORCE_MEMBER_VALUE_SET error code, 240
ER_GRP_RPL_FAILED_TO_UNREGISTER_SERVER_STATE_OBSERVER error code, 235	ER_GRP_RPL_FORCE_MEMBER_VALUE_SET_ERROR error code, 240
ER_GRP_RPL_FAILED_TO_UNREGISTER_TRANS_STATE_OBSERVER error code, 235	ER_GRP_RPL_FORCE_MEMBER_VALUE_TIME_OUT error code, 240
ER_GRP_RPL_FAILOVER_CHANNEL_STATUS_PROPAGATION error code, 112	ER_GRP_RPL_GCS_GR_ERROR_MSG error code, 241
ER_GRP_RPL_FAILOVER_CONF_CHANNEL_DOES_NOT_EXIST error code, 373	ER_GRP_RPL_GCS_INTERFACE_ERROR error code, 240
ER_GRP_RPL_FAILOVER_CONF_DEFAULT_CONFIGURATION_ERROR error code, 373	ER_GRP_RPL_GMS_LISTENER_FAILED_TO_LOG_NOTIFICATION error code, 239
ER_GRP_RPL_FAILOVER_CONF_GET_EXCHANGEABLE_DATA error code, 373	ER_GRP_RPL_GROUP_NAME_PARSE_ERROR error code, 219
ER_GRP_RPL_FAILOVER_CONF_PARSE_ON_MEMBER_ERROR error code, 373	ER_GRP_RPL_GROUP_NAME_SAME_AS_VIEW_CHANGE_UUID error code, 370
ER_GRP_RPL_FAILOVER_CONF_UNABLE_TO_SET_DEFAULT_CONFIGURATION error code, 373	ER_GRP_RPL_GRP_COMMUNICATION_ENG_INIT_FAILED error code, 239
ER_GRP_RPL_FAILOVER_PRIMARY_BACK_TO_MAJORITY error code, 373	ER_GRP_RPL_GRP_COMMUNICATION_INIT_WITH_CONF error code, 237
ER_GRP_RPL_FAILOVER_PRIMARY_WITHOUT_MAJORITY error code, 373	ER_GRP_RPL_GRP_MEMBER_OFFLINE error code, 239
ER_GRP_RPL_FAILOVER_REGISTER_MESSAGE_LISTENER_ERROR error code, 373	ER_GRP_RPL_GRP_NAME_IS_NOT_VALID_UUID error code, 237
ER_GRP_RPL_FATAL_REC_PROCESS error code, 232	ER_GRP_RPL_GRP_NAME_IS_SAME_AS_ANONYMOUS_TO_GROUP error code, 365
ER_GRP_RPL_FETCH_FORMAT_DESC_LOG_EVENT_FAILED error code, 226	ER_GRP_RPL_GRP_NAME_IS_TOO_LONG error code, 237
ER_GRP_RPL_FETCH_GTID_LOG_EVENT_FAILED error code, 227	ER_GRP_RPL_GRP_NAME_OPTION_MANDATORY error code, 237
ER_GRP_RPL_FETCH_LOG_EVENT_FAILED error code, 227	ER_GRP_RPL_GRP_VIEW_CHANGE_UUID_IS_INCOMPATIBLE error code, 370
ER_GRP_RPL_FETCH_SNAPSHOT_VERSION_FAILED error code, 227	ER_GRP_RPL_GTID_ALREADY_USED error code, 218
ER_GRP_RPL_FETCH_TRANS_CONTEXT_FAILED error code, 226	ER_GRP_RPL_GTID_EXECUTED_EXTRACT_ERROR error code, 224

---

---

ER\_GRP\_RPL\_GTID\_MODE\_OFF error code, 236  
 ER\_GRP\_RPL\_GTID\_PURGED\_EXTRACT\_ERROR error code, 347  
 ER\_GRP\_RPL\_GTID\_SET\_EXTRACT\_ERROR error code, 224  
 ER\_GRP\_RPL\_GTID\_SET\_EXTRACT\_ERROR\_DURING\_RECOVERY error code, 338  
 ER\_GRP\_RPL\_HAS\_STARTED error code, 391  
 ER\_GRP\_RPL\_INCORRECT\_TYPE\_SET\_FOR\_PARALLEL\_REPLICATION error code, 236  
 ER\_GRP\_RPL\_INIT\_CERTIFICATION\_INFO\_FAILURE error code, 221  
 ER\_GRP\_RPL\_INTERNAL\_QUERY error code, 228  
 ER\_GRP\_RPL\_INVALID\_BINLOG\_FORMAT error code, 230  
 ER\_GRP\_RPL\_INVALID\_COMMUNICATION\_PROTOCOL error code, 342  
 ER\_GRP\_RPL\_INVALID\_DEBUG\_OPTIONS error code, 239  
 ER\_GRP\_RPL\_INVALID\_GTID\_SET error code, 220  
 ER\_GRP\_RPL\_INVALID\_SSL\_RECOVERY\_STRING error code, 237  
 ER\_GRP\_RPL\_IS\_STARTING error code, 357  
 ER\_GRP\_RPL\_IS\_STOPPED error code, 234  
 ER\_GRP\_RPL\_IS\_STOPPING error code, 234  
 ER\_GRP\_RPL\_JOINER\_EXIT\_WHEN\_GROUP\_ACTION\_RUNNING error code, 330  
 ER\_GRP\_RPL\_JOIN\_WHEN\_GROUP\_ACTION\_RUNNING error code, 330  
 ER\_GRP\_RPL\_KILLED\_FAILED\_ID error code, 228  
 ER\_GRP\_RPL\_KILLED\_SESSION\_ID error code, 228  
 ER\_GRP\_RPL\_LOCAL\_GTID\_SETS\_PROCESS\_ERROR error code, 224  
 ER\_GRP\_RPL\_LOG\_REPLICA\_UPDATES\_NOT\_SET error code, 236  
 ER\_GRP\_RPL\_LOWER\_CASE\_TABLE\_NAMES\_DIFF\_FROM\_GRP error code, 323  
 ER\_GRP\_RPL\_MAXIMUM\_CONNECTION\_RETRIES\_REACHED error code, 228  
 ER\_GRP\_RPL\_MEMBER\_ACTIONS\_RESET error code, 369  
 ER\_GRP\_RPL\_MEMBER\_ACTION\_DEFAULT\_CONFIGURATION error code, 368  
 ER\_GRP\_RPL\_MEMBER\_ACTION\_DISABLED error code, 369  
 ER\_GRP\_RPL\_MEMBER\_ACTION\_ENABLED error code, 369  
 ER\_GRP\_RPL\_MEMBER\_ACTION\_FAILURE error code, 368  
 ER\_GRP\_RPL\_MEMBER\_ACTION\_FAILURE\_IGNORE error code, 368  
 ER\_GRP\_RPL\_MEMBER\_ACTION\_GET\_EXCHANGEABLE\_DATA error code, 368  
 ER\_GRP\_RPL\_MEMBER\_ACTION\_INVALID\_ACTIONS\_ON\_MEMBER error code, 369  
 ER\_GRP\_RPL\_MEMBER\_ACTION\_PARSE\_ON\_MEMBER error code, 369  
 ER\_GRP\_RPL\_MEMBER\_ACTION\_PARSE\_ON\_RECEIVE error code, 368  
 ER\_GRP\_RPL\_MEMBER\_ACTION\_TRIGGERED error code, 368  
 ER\_GRP\_RPL\_MEMBER\_ACTION\_UNABLE\_TO\_SET\_DEFAULT error code, 369  
 ER\_GRP\_RPL\_MEMBER\_ACTION\_UPDATE\_ACTIONS error code, 368  
 ER\_GRP\_RPL\_MEMBER\_ACTION\_UPDATE\_ACTIONS\_ON\_MEMBER error code, 369  
 ER\_GRP\_RPL\_MEMBER\_ADDED error code, 222  
 ER\_GRP\_RPL\_MEMBER\_ALREADY\_EXISTS error code, 224  
 ER\_GRP\_RPL\_MEMBER\_CFG\_INCOMPATIBLE\_WITH\_GRP error code, 225  
 ER\_GRP\_RPL\_MEMBER\_CHANGE error code, 223  
 ER\_GRP\_RPL\_MEMBER\_CONF\_INFO error code, 233  
 ER\_GRP\_RPL\_MEMBER\_CONTACT\_RESTORED error code, 222  
 ER\_GRP\_RPL\_MEMBER\_EXIT\_PLUGIN\_ERROR error code, 223  
 ER\_GRP\_RPL\_MEMBER\_EXPELLED error code, 223  
 ER\_GRP\_RPL\_MEMBER\_INFO\_DOES\_NOT\_EXIST error code, 396  
 ER\_GRP\_RPL\_MEMBER\_LEFT\_GRP error code, 223  
 ER\_GRP\_RPL\_MEMBER\_NOT\_FOUND error code, 228  
 ER\_GRP\_RPL\_MEMBER\_REMOVED error code, 222  
 ER\_GRP\_RPL\_MEMBER\_SERVER\_UUID\_IS\_INCOMPATIBLE error code, 233  
 ER\_GRP\_RPL\_MEMBER\_STATS\_INFO error code, 240  
 ER\_GRP\_RPL\_MEMBER\_STOP\_RPL\_CHANNELS\_ERROR error code, 225  
 ER\_GRP\_RPL\_MEMBER\_TRANS\_GREATER\_THAN\_GRP error code, 224  
 ER\_GRP\_RPL\_MEMBER\_VERSION\_LOWER\_THAN\_GRP error code, 224  
 ER\_GRP\_RPL\_MEMBER\_VER\_INCOMPATIBLE error code, 224  
 ER\_GRP\_RPL\_MEMBER\_VER\_READ\_COMPATIBLE error code, 345  
 ER\_GRP\_RPL\_MEM\_ONLINE error code, 222  
 ER\_GRP\_RPL\_MEM\_REACHABLE error code, 222  
 ER\_GRP\_RPL\_MEM\_UNREACHABLE error code, 222  
 ER\_GRP\_RPL\_MESSAGE\_SERVICE\_FATAL\_ERROR error code, 349  
 ER\_GRP\_RPL\_MESSAGE\_SERVICE\_INIT\_FAILURE error code, 101  
 ER\_GRP\_RPL\_MISSING\_GRP\_RPL\_ACTION\_COORDINATOR error code, 330  
 ER\_GRP\_RPL\_MISSING\_GRP\_RPL\_APPLIER error code, 221  
 ER\_GRP\_RPL\_MEMBER\_JOIN error code, 227  
 ER\_GRP\_RPL\_MODULE\_TERMINATE\_ERROR error code, 227  
 ER\_GRP\_RPL\_MSG\_DECODING\_FAILED error code, 404

---

---

ER\_GRP\_RPL\_MSG\_DISCARDED error code, 221  
 ER\_GRP\_RPL\_MSG\_TOO\_LONG\_BROADCASTING\_TRANSACTION error code, 231  
 ER\_GRP\_RPL\_MULTIPLE\_CACHE\_TYPE\_NOT\_SUPPORTED error code, 231  
 ER\_GRP\_RPL\_MYSQL\_NETWORK\_PROVIDER\_CLIENT\_ERROR error code, 372  
 ER\_GRP\_RPL\_MYSQL\_NETWORK\_PROVIDER\_CLIENT\_ERROR error code, 372  
 ER\_GRP\_RPL\_MYSQL\_NETWORK\_PROVIDER\_SERVER\_ERROR error code, 398  
 ER\_GRP\_RPL\_NEEDS\_INNOODB\_TABLE error code, 226  
 ER\_GRP\_RPL\_NEW\_PRIMARY\_ELECTED error code, 223  
 ER\_GRP\_RPL\_NOTIFY\_CERTIFICATION\_OUTCOME\_FAILED error code, 227  
 ER\_GRP\_RPL\_NO\_POSSIBLE\_RECOVERY error code, 348  
 ER\_GRP\_RPL\_NO\_STAGE\_SERVICE error code, 331  
 ER\_GRP\_RPL\_NO\_SUITABLE\_PRIMARY\_MEM error code, 223  
 ER\_GRP\_RPL\_NO\_VALID\_DONOR error code, 229  
 ER\_GRP\_RPL\_NULL\_PACKET error code, 221  
 ER\_GRP\_RPL\_ONLY\_ONE\_SERVER\_ALIVE error code, 232  
 ER\_GRP\_RPL\_OOM\_FAILED\_TO\_GENERATE\_IDENTIFICATION error code, 230  
 ER\_GRP\_RPL\_PAXOS\_SINGLE\_LEADER\_DIFF\_FROM\_GROUP error code, 376  
 ER\_GRP\_RPL\_PAXOS\_SINGLE\_LEADER\_DIFF\_FROM\_GROUP error code, 390  
 ER\_GRP\_RPL\_PIPELINE\_CREATE\_FAILED error code, 240  
 ER\_GRP\_RPL\_PIPELINE\_FLUSH\_FAIL error code, 240  
 ER\_GRP\_RPL\_PIPELINE\_REINIT\_FAILED\_READ error code, 241  
 ER\_GRP\_RPL\_PIPELINE\_REINIT\_FAILED\_WRITE error code, 240  
 ER\_GRP\_RPL\_PLUGIN\_ABORT error code, 328  
 ER\_GRP\_RPL\_PLUGIN\_STRUCT\_INIT\_NOT\_POSSIBLE error code, 233  
 ER\_GRP\_RPL\_PRIMARY\_ELECTION\_PROCESS\_ERROR error code, 331  
 ER\_GRP\_RPL\_PRIMARY\_ELECTION\_STOP\_ERROR error code, 331  
 ER\_GRP\_RPL\_PRIMARY\_KEY\_NOT\_DEFINED error code, 226  
 ER\_GRP\_RPL\_PRIMARY\_MEMBER\_LEFT\_GRP error code, 222  
 ER\_GRP\_RPL\_PROCESS\_GTID\_SET\_ERROR error code, 221  
 ER\_GRP\_RPL\_PROCESS\_INTERSECTION\_GTID\_SET\_ERROR error code, 221  
 ER\_GRP\_RPL\_PURGE\_APPLIER\_LOGS error code, 225  
 ER\_GRP\_RPL\_PURGE\_REC error code, 229  
 ER\_GRP\_RPL\_QUERY\_FAIL error code, 228  
 ER\_GRP\_RPL\_READ\_UNABLE\_FOR\_READ\_ONLY\_SUPER\_READ error code, 232  
 ER\_GRP\_RPL\_SESSION\_SET\_MISSING\_GTIDS error code, 221  
 ER\_GRP\_RPL\_READ\_ERROR\_CHANNEL\_STILL\_RUNNING error code, 110  
 ER\_GRP\_RPL\_RECOVERY\_ENDPOINT\_FORMAT error code, 357  
 ER\_GRP\_RPL\_RECOVERY\_ENDPOINT\_FORMAT error code, 357  
 ER\_GRP\_RPL\_RECOVERY\_ENDPOINT\_INVALID error code, 357  
 ER\_GRP\_RPL\_RECOVERY\_ENDPOINT\_INVALID\_DONOR\_ENDPOINT error code, 357  
 ER\_GRP\_RPL\_RECOVERY\_EVAL\_ERROR error code, 348  
 ER\_GRP\_RPL\_RECOVERY\_MODULE\_TERMINATION\_TIMED\_OUT error code, 234  
 ER\_GRP\_RPL\_RECOVERY\_STRAT\_CHOICE error code, 348  
 ER\_GRP\_RPL\_RECOVERY\_STRAT\_CLONE\_PURGED error code, 348  
 ER\_GRP\_RPL\_RECOVERY\_STRAT\_CLONE\_THRESHOLD error code, 348  
 ER\_GRP\_RPL\_RECOVERY\_STRAT\_FALLBACK error code, 348  
 ER\_GRP\_RPL\_RECOVERY\_STRAT\_NO\_FALLBACK error code, 348  
 ER\_GRP\_RPL\_REGISTER\_TRX\_TO\_WAIT\_FOR\_DEPENDENCIES error code, 337  
 ER\_GRP\_RPL\_REGISTER\_TRX\_TO\_WAIT\_FOR\_GROUP\_PREPARED error code, 337  
 ER\_GRP\_RPL\_REGISTER\_TRX\_TO\_WAIT\_FOR\_SYNC\_BEFORE\_RELEASE error code, 338  
 ER\_GRP\_RPL\_RELEASE\_BEGIN\_TRX\_AFTER\_DEPENDENCIES error code, 337  
 ER\_GRP\_RPL\_RELEASE\_BEGIN\_TRX\_AFTER\_WAIT\_FOR\_SYNC error code, 338  
 ER\_GRP\_RPL\_RELEASE\_COMMIT\_AFTER\_GROUP\_PREPARED error code, 337  
 ER\_GRP\_RPL\_REPAIR\_PARTICA\_APPLIER\_THREAD\_ERROR\_OUT error code, 241  
 ER\_GRP\_RPL\_REPLICA\_APPLIER\_THREAD\_UNBLOCKED error code, 241  
 ER\_GRP\_RPL\_REPLICA\_IO\_THD\_PRIMARY\_UNKNOWN error code, 225  
 ER\_GRP\_RPL\_REPLICA\_IO\_THREAD\_ERROR\_OUT error code, 241  
 ER\_GRP\_RPL\_REPLICA\_IO\_THREAD\_UNBLOCKED error code, 241  
 ER\_GRP\_RPL\_REPLICA\_PRESERVE\_COMMIT\_ORDER\_NOT\_SUPPORTED error code, 236  
 ER\_GRP\_RPL\_REPLICA\_SQL\_THD\_ON\_SECONDARY\_MEMBER\_UNKNOWN error code, 226  
 ER\_GRP\_RPL\_REPLICA\_SQL\_THD\_PRIMARY\_UNKNOWN error code, 226

---

---

ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_CLONING error code, 348	ER_GRP_RPL_SQL_SERVICE_SERVER_SESSION_KILLED error code, 238
ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_SECONDARY error code, 374	ER_GRP_RPL_SRV_BLOCKED error code, 222
ER_GRP_RPL_REQUESTING_NON_MEMBER_SERVER error code, 234	ER_GRP_RPL_SRV_BLOCKED_FOR_SECS error code, 222
ER_GRP_RPL_RESET_APPLIER_MODULE_LOGS_ERROR error code, 225	ER_GRP_RPL_SRV_NOT_ONLINE error code, 221
ER_GRP_RPL_SALVE_IO_THD_ON_SECONDARY_MEMBER error code, 226	ER_GRP_RPL_SRV_ONLINE error code, 222
ER_GRP_RPL_SEND_STATS_ERROR error code, 240	ER_GRP_RPL_SRV_PRIMARY_MEM error code, 223
ER_GRP_RPL_SEND_TRX_PREPARED_MESSAGE_FAILED error code, 337	ER_GRP_RPL_SRV_SECONDARY_MEM error code, 223
ER_GRP_RPL_SEND_TRX_SYNC_BEFORE_EXECUTION error code, 338	ER_GRP_RPL_SSL_DISABLED error code, 236
ER_GRP_RPL_SERVER_ALREADY_LEFT error code, 234	ER_GRP_RPL_STARTED_AUTO_REJOIN error code, 229
ER_GRP_RPL_SERVER_CONN_ERROR error code, 220	ER_GRP_RPL_STARTING_GRP_REC error code, 229
ER_GRP_RPL_SERVER_IS_ALREADY_LEAVING error code, 233	ER_GRP_RPL_START_FAILED error code, 224
ER_GRP_RPL_SERVER_SET_TO_OFFLINE_MODE_DURATION error code, 349	ER_GRP_RPL_START_GRP_RPL_FAILED error code, 228
ER_GRP_RPL_SERVER_SET_TO_READ_ONLY_DURATION error code, 239	ER_GRP_RPL_STOPPING_GRP_REC error code, 229
ER_GRP_RPL_SERVER_UDF_ERROR error code, 331	ER_GRP_RPL_SUPER_READ_OFF error code, 228
ER_GRP_RPL_SESSION_OPEN_FAILED error code, 223	ER_GRP_RPL_SUPER_READ_ON error code, 228
ER_GRP_RPL_SET_GRP_COMMUNICATION_ENGINE_LOGS error code, 239	ER_GRP_RPL_SUPER_READ_ONLY_ACTIVATE_ERROR error code, 223
ER_GRP_RPL_SET_MULTI_CONSENSUS_LEADER error code, 376	ER_GRP_RPL_TIMEOUT_ON_VIEW_AFTER_JOINING_GRP error code, 233
ER_GRP_RPL_SET_SINGLE_CONSENSUS_LEADER error code, 376	ER_GRP_RPL_TIMEOUT_RECEIVED_VC_LEAVE_ON_REJOIN error code, 362
ER_GRP_RPL_SET_STABLE_TRANS_ERROR error code, 221	ER_GRP_RPL_TIMEOUT_RECEIVED_VC_ON_REJOIN error code, 342
ER_GRP_RPL_SINGLE_PRIM_MODE_NOT_ALLOWED error code, 236	ER_GRP_RPL_TIMEOUT_RECEIVED_VIEW_CHANGE_ON_REJOIN error code, 234
ER_GRP_RPL_SQL_SERVICE_COMM_SESSION_NOT_INITIALIZED error code, 238	ER_GRP_RPL_TRANS_GREATER_THAN_GRP error code, 224
ER_GRP_RPL_SQL_SERVICE_FAILED_TO_FETCH_SECONDARY error code, 238	ER_GRP_RPL_TRANS_NOT_PRESENT_IN_GRP error code, 224
ER_GRP_RPL_SQL_SERVICE_FAILED_TO_INIT_SESSION error code, 238	ER_GRP_RPL_TRANS_SIZE_EXCEEDS_LIMIT error code, 231
ER_GRP_RPL_SQL_SERVICE_FAILED_TO_RUN_SQL_QUERY error code, 238	ER_GRP_RPL_TRANS_WRITE_RESET_EXTRACT_DIFF_FROM_TRANSACTION error code, 225
ER_GRP_RPL_SQL_SERVICE_MAX_CONN_ERROR_FROM_SESSION error code, 239	ER_GRP_RPL_TRX_ALREADY_EXISTS_ON_TCM_ON_AFTER_COMMIT error code, 337
ER_GRP_RPL_SQL_SERVICE_RETRIES_EXCEEDED error code, 238	ER_GRP_RPL_TRX_DOES_NOT_EXIST_ON_TCM_ON_HANDLER error code, 337
ER_GRP_RPL_SQL_SERVICE_SERVER_ACCESS_DENIED error code, 239	ER_GRP_RPL_TRX_WAIT_FOR_GROUP_GTID_EXECUTED error code, 338
ER_GRP_RPL_SQL_SERVICE_SERVER_ERROR_ON_CONNECT error code, 239	ER_GRP_RPL_TRX_WAIT_FOR_GROUP_PREPARE_FAILED error code, 337
ER_GRP_RPL_SQL_SERVICE_SERVER_INTERNAL_FAILURE error code, 238	ER_GRP_RPL_TRX_WAIT_FOR_SYNC_BEFORE_EXECUTION error code, 338
	ER_GRP_RPL_UDF_REGISTER_ERROR error code, 101
	ER_GRP_RPL_UDF_REGISTER_SERVICE_ERROR error code, 331
	ER_GRP_RPL_UDF_UNREGISTER_ERROR error code, 331

---

---

ER_GRP_RPL_UNABLE_TO_CERTIFY_PLUGIN_TRANSACTION error code, 232	ER_GRP_RPL_WHILE_SENDING_MSG_REC error code, 232
ER_GRP_RPL_UNABLE_TO_CONVERT_EVENT_TO_PACKET error code, 240	ER_GRP_RPL_WRITE_IDENT_HASH_BASE64_ENCODING_FAILED error code, 230
ER_GRP_RPL_UNABLE_TO_CONVERT_PACKET_TO_EVENT error code, 240	ER_GRP_RPL_WRITE_TO_TRANSACTION_MESSAGE_FAILED error code, 231
ER_GRP_RPL_UNABLE_TO_ENSURE_EXECUTION_REPEAT error code, 232	ER_GRP_TRX_CONSISTENCY_AFTER_ON_TRX_BEGIN error code, 93
ER_GRP_RPL_UNABLE_TO_EVALUATE_APPLIER_STATUS error code, 232	ER_GRP_TRX_CONSISTENCY_BEFORE error code, 93
ER_GRP_RPL_UNABLE_TO_INIT_COMMUNICATION_REPEAT error code, 236	ER_GRP_TRX_CONSISTENCY_BEGIN_NOT_ALLOWED error code, 93
ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_REPEAT error code, 229	ER_GRP_TRX_CONSISTENCY_NOT_ALLOWED error code, 93
ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_REPEAT error code, 230	ER_INVALID_PRIMARY_GTID_INFORMATION error code, 352
ER_GRP_RPL_UNABLE_TO_RESET_SERVER_READ_MODE error code, 232	ER_HOLD_KILLED error code, 92
ER_GRP_RPL_UNBLOCK_CERTIFIED_TRANS error code, 232	ER_HOLD_MEMBER_STATUS_ERROR error code, 92
ER_GRP_RPL_UNBLOCK_WAITING_THD error code, 219	ER_HOLD_WAIT_TIMEOUT error code, 92
ER_GRP_RPL_UNKNOWN_GRP_RPL_APPLIER_PIPELINE_REQUESTED error code, 237	ER_GTID_ALREADY_ADDED_BY_USER error code, 154
ER_GRP_RPL_UNREACHABLE_MAJORITY_TIMEOUT error code, 239	ER_GTID_ALREADY_ADDED error code, 54
ER_GRP_RPL_UNSUPPORTED_TRANS_ISOLATION error code, 230	ER_GTID_MEMBER_EXECUTED_WAS_UPDATED error code, 181
ER_GRP_RPL_UPDATE_GRP_GTID_EXECUTED_ERROR error code, 219	ER_GTID_MODE_CAN_ONLY_CHANGE_ONE_STEP_AT_A_TIME error code, 50
ER_GRP_RPL_UPDATE_GRP_GTID_VIEW_CHANGE_UUID error code, 370	ER_GTID_MODE_OFF error code, 61
ER_GRP_RPL_UPDATE_GTID_SET_ERROR error code, 220	ER_GTID_MODE_ON_REQUIRES_ENFORCE_GTID_CONSISTENCY error code, 49
ER_GRP_RPL_UPDATE_LAST_CONFLICT_FREE_TRANSACTION error code, 220	ER_GTID_NEXT_CANT_BE_AUTOMATIC_IF_GTID_NEXT_LIST_IS_EXHAUSTED error code, 49
ER_GRP_RPL_UPDATE_SERV_CERTIFICATE_FAILED error code, 227	ER_GTID_NEXT_TAG_GTID_MODE_OFF error code, 54
ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_REFERENCE error code, 220	ER_GTID_NEXT_TYPE_UNDEFINED_GTID error code, 53
ER_GRP_RPL_VCLE_NOT_BEING_LOGGED error code, 401	ER_GTID_PURGED_WAS_CHANGED error code, 54
ER_GRP_RPL_VIEW_CHANGE_UUID_DIFF_FROM_GROUP error code, 370	ER_GTID_PURGED_WAS_UPDATED error code, 181
ER_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIABLE error code, 111	ER_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION error code, 91
ER_GRP_RPL_VIEW_CHANGE_UUID_INVALID error code, 369	ER_GTID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AND_AFFECTED error code, 57
ER_GRP_RPL_VIEW_CHANGE_UUID_IS_SAME_AS_ANOTHER error code, 370	ER_GTID_UNSAFE_CREATE_SELECT error code, 50
ER_GRP_RPL_VIEW_CHANGE_UUID_PARSE_ERROR error code, 370	ER_GTID_UNSAFE_NON_TRANSACTIONAL_TABLE error code, 50
ER_GRP_RPL_VIEW_CHANGE_UUID_SAME_AS_GROUP_NAME error code, 369	ER_HANDLERTON_OOM error code, 144
ER_GRP_RPL_WAITING_FOR_VIEW_UPDATE error code, 234	ER_HANDSHAKE_ERROR error code, 5
ER_GRP_RPL_WAIT_FOR_DEPENDENCIES_FAILED error code, 338	ER_INVALID_TRANSACTION_ID error code, 365

---

---

ER\_HEALTH\_WARNING\_MEMORY\_USAGE\_LEVEL\_1 error code, 376  
 ER\_HEALTH\_WARNING\_MEMORY\_USAGE\_LEVEL\_2 error code, 376  
 ER\_HEALTH\_WARNING\_MEMORY\_USAGE\_LEVEL\_3 error code, 376  
 ER\_HOSTNAME error code, 31  
 ER\_HOSTNAME\_DOESNT\_RESOLVE\_TO error code, 132  
 ER\_HOSTNAME\_RESEMBLES\_IPV4 error code, 132  
 ER\_HOSTNAME\_TOO\_LONG error code, 105  
 ER\_HOSTNAME\_TRUNCATED error code, 358  
 ER\_HOST\_IS\_BLOCKED error code, 11  
 ER\_HOST\_NOT\_PRIVILEGED error code, 11  
 ER\_HYPERGRAPH\_NOT\_SUPPORTED\_YET error code, 108  
 ER\_IB\_BUFFER\_POOL\_FULL error code, 387  
 ER\_IB\_BUFFER\_POOL\_OVERUSE error code, 387  
 ER\_IB\_BULK\_FLUSHER\_INFO error code, 387  
 ER\_IB\_BULK\_FLUSHER\_PUNCH\_HOLE error code, 396  
 ER\_IB\_BULK\_LOAD\_MERGE\_FAIL error code, 389  
 ER\_IB\_BULK\_LOAD\_STATS\_WARN error code, 404  
 ER\_IB\_BULK\_LOAD\_SUBTREE\_INFO error code, 387  
 ER\_IB\_BULK\_LOAD\_THREAD\_FAIL error code, 389  
 ER\_IB\_CANNOT\_UPGRADE\_WITH\_DISCARDED\_TABLESPACES error code, 358  
 ER\_IB\_CLONE\_GTID\_PERSIST error code, 256  
 ER\_IB\_CLONE\_INTERNAL error code, 256  
 ER\_IB\_CLONE\_NON\_INNOODB\_TABLE error code, 347  
 ER\_IB\_CLONE\_OPERATION error code, 347  
 ER\_IB\_CLONE\_PUNCH\_HOLE error code, 256  
 ER\_IB\_CLONE\_RESTART error code, 347  
 ER\_IB\_CLONE\_SQL error code, 256  
 ER\_IB\_CLONE\_START\_STOP error code, 347  
 ER\_IB\_CLONE\_STATUS\_FILE error code, 256  
 ER\_IB\_CLONE\_TIMEOUT error code, 256  
 ER\_IB\_CLONE\_USER\_DATA error code, 347  
 ER\_IB\_CLONE\_VALIDATE error code, 256  
 ER\_IB\_DBLWR\_BYTES\_INFO error code, 379  
 ER\_IB\_DBLWR\_DECOMPRESS\_FAILED error code, 363  
 ER\_IB\_DBLWR\_DECRYPT\_FAILED error code, 363  
 ER\_IB\_DBLWR\_KEY\_MISSING error code, 363  
 ER\_IB\_DDL\_CONVERT\_HEAP\_NOT\_FOUND error code, 395  
 ER\_IB\_DICT\_INVALID\_COLUMN\_POSITION error code, 390  
 ER\_IB\_DICT\_LOG\_TABLE\_INFO error code, 390  
 ER\_IB\_DUPLICATE\_KEY error code, 387  
 ER\_IB\_ERR\_CORRUPT\_TABLESPACE\_UNRECOVERABLE error code, 403  
 ER\_IB\_ERR\_DDL\_LOG\_INSERT\_FAILURE error code, 359  
 ER\_IB\_ERR\_FOUND\_N\_DUPLICATE\_KEYS error code, 361  
 ER\_IB\_ERR\_FOUND\_N\_RECORDS\_WRONG\_ORDER error code, 361  
 ER\_IB\_ERR\_INDEX\_DUPLICATE\_KEY error code, 361  
 ER\_IB\_ERR\_INDEX\_RECORDS\_WRONG\_ORDER error code, 361  
 ER\_IB\_ERR\_LOG\_PARSING\_BUFFER\_OVERFLOW error code, 360  
 ER\_IB\_ERR\_NOT\_ENOUGH\_MEMORY\_FOR\_PARSE\_BUFFER error code, 360  
 ER\_IB\_ERR\_PAGE\_ARCH\_DBLWR\_INIT\_FAILED error code, 372  
 ER\_IB\_ERR\_PAGE\_ARCH\_INVALID\_DOUBLE\_WRITE\_BUFFER error code, 356  
 ER\_IB\_ERR\_PAGE\_ARCH\_INVALID\_FORMAT error code, 356  
 ER\_IB\_ERR\_PAGE\_ARCH\_RECOVERY\_FAILED error code, 356  
 ER\_IB\_ERR\_PARALLEL\_READ\_OOM error code, 361  
 ER\_IB\_ERR\_RECOVERY\_REDO\_DISABLED error code, 358  
 ER\_IB\_ERR\_SCHED\_SETAFFINITY\_FAILED error code, 360  
 ER\_IB\_ERR\_TEMP\_TABLESPACE\_DIR\_CONTAINS\_SEMICOLON error code, 360  
 ER\_IB\_ERR\_TEMP\_TABLESPACE\_DIR\_DOESNT\_EXIST error code, 360  
 ER\_IB\_ERR\_TEMP\_TABLESPACE\_DIR\_EMPTY error code, 360  
 ER\_IB\_ERR\_TEMP\_TABLESPACE\_DIR\_SUBDIR\_OF\_DATAFILE error code, 360  
 ER\_IB\_ERR\_UNKNOWN\_PAGE\_FETCH\_MODE error code, 360  
 ER\_IB\_ERR\_ZLIB\_BUF\_ERROR error code, 361  
 ER\_IB\_ERR\_ZLIB\_DATA\_ERROR error code, 361  
 ER\_IB\_ERR\_ZLIB\_MEM\_ERROR error code, 361  
 ER\_IB\_ERR\_ZLIB\_UNCOMPRESS\_FAILED error code, 360  
 ER\_IB\_ERR\_ZLIB\_UNKNOWN\_ERROR error code, 361  
 ER\_IB\_FAILED\_TO\_DELETE\_TABLESPACE\_FILE error code, 359  
 ER\_IB\_FIXED\_PAGE\_ID error code, 399  
 ER\_IB\_HIDDEN\_NAME\_CONFLICT error code, 390  
 ER\_IB\_IMPORT\_INDEX\_METADATA\_READ\_FAILED error code, 302  
 ER\_IB\_IMPORT\_START\_CFG\_NAME error code, 307  
 ER\_IB\_INDEX\_BUILDER\_DONE error code, 391  
 ER\_IB\_INDEX\_BUILDER\_INIT error code, 391  
 ER\_IB\_INDEX\_LOADER\_DONE error code, 391  
 ER\_IB\_INDEX\_LOG\_VERSION\_MISMATCH error code, 391  
 ER\_IB\_INNOODB\_TBSP\_OUT\_OF\_SPACE error code, 365  
 ER\_IB\_LOAD\_BULK\_CONCURRENCY\_REDUCED error code, 389  
 ER\_IB\_LOB\_ROLLBACK\_INDEX\_LEN error code, 351

---

---

ER\_IB\_LOCK\_VALIDATE\_LATCH\_ORDER\_VIOLATION error code, 359  
ER\_IB\_LONG\_AHI\_DISABLE\_WAIT error code, 258  
ER\_IB\_MSG\_0 error code, 247  
ER\_IB\_MSG\_1 error code, 247  
ER\_IB\_MSG\_10 error code, 248  
ER\_IB\_MSG\_100 error code, 253  
ER\_IB\_MSG\_1000 error code, 306  
ER\_IB\_MSG\_1001 error code, 306  
ER\_IB\_MSG\_1002 error code, 306  
ER\_IB\_MSG\_1003 error code, 306  
ER\_IB\_MSG\_1004 error code, 306  
ER\_IB\_MSG\_1005 error code, 306  
ER\_IB\_MSG\_1006 error code, 306  
ER\_IB\_MSG\_1007 error code, 306  
ER\_IB\_MSG\_1008 error code, 306  
ER\_IB\_MSG\_1009 error code, 306  
ER\_IB\_MSG\_101 error code, 253  
ER\_IB\_MSG\_1010 error code, 306  
ER\_IB\_MSG\_1011 error code, 306  
ER\_IB\_MSG\_1012 error code, 306  
ER\_IB\_MSG\_1013 error code, 306  
ER\_IB\_MSG\_1015 error code, 307  
ER\_IB\_MSG\_1016 error code, 307  
ER\_IB\_MSG\_1017 error code, 307  
ER\_IB\_MSG\_1018 error code, 307  
ER\_IB\_MSG\_1019 error code, 307  
ER\_IB\_MSG\_102 error code, 253  
ER\_IB\_MSG\_1020 error code, 307  
ER\_IB\_MSG\_1021 error code, 307  
ER\_IB\_MSG\_1022 error code, 307  
ER\_IB\_MSG\_1023 error code, 307  
ER\_IB\_MSG\_1024 error code, 307  
ER\_IB\_MSG\_1025 error code, 307  
ER\_IB\_MSG\_1026 error code, 307  
ER\_IB\_MSG\_1027 error code, 307  
ER\_IB\_MSG\_1028 error code, 307  
ER\_IB\_MSG\_1029 error code, 307  
ER\_IB\_MSG\_103 error code, 253  
ER\_IB\_MSG\_1030 error code, 308  
ER\_IB\_MSG\_1031 error code, 308  
ER\_IB\_MSG\_1032 error code, 308  
ER\_IB\_MSG\_1033 error code, 308  
ER\_IB\_MSG\_1034 error code, 308  
ER\_IB\_MSG\_1035 error code, 308  
ER\_IB\_MSG\_1036 error code, 308  
ER\_IB\_MSG\_1037 error code, 308  
ER\_IB\_MSG\_1038 error code, 308  
ER\_IB\_MSG\_1039 error code, 308  
ER\_IB\_MSG\_104 error code, 253  
ER\_IB\_MSG\_1040 error code, 308  
ER\_IB\_MSG\_1041 error code, 308  
ER\_IB\_MSG\_1042 error code, 308  
ER\_IB\_MSG\_1043 error code, 308  
ER\_IB\_MSG\_1044 error code, 308  
ER\_IB\_MSG\_1045 error code, 308  
ER\_IB\_MSG\_1046 error code, 309  
ER\_IB\_MSG\_1047 error code, 309  
ER\_IB\_MSG\_1048 error code, 309  
ER\_IB\_MSG\_1049 error code, 309  
ER\_IB\_MSG\_105 error code, 253  
ER\_IB\_MSG\_1051 error code, 309  
ER\_IB\_MSG\_1052 error code, 309  
ER\_IB\_MSG\_1053 error code, 309  
ER\_IB\_MSG\_1054 error code, 309  
ER\_IB\_MSG\_1055 error code, 309  
ER\_IB\_MSG\_1056 error code, 309  
ER\_IB\_MSG\_1057 error code, 309  
ER\_IB\_MSG\_1058 error code, 309  
ER\_IB\_MSG\_1059 error code, 309  
ER\_IB\_MSG\_106 error code, 254  
ER\_IB\_MSG\_1060 error code, 309  
ER\_IB\_MSG\_1065 error code, 310  
ER\_IB\_MSG\_107 error code, 254  
ER\_IB\_MSG\_1070 error code, 310  
ER\_IB\_MSG\_1071 error code, 310  
ER\_IB\_MSG\_1072 error code, 310  
ER\_IB\_MSG\_1073 error code, 310  
ER\_IB\_MSG\_1074 error code, 310  
ER\_IB\_MSG\_1075 error code, 310  
ER\_IB\_MSG\_1076 error code, 310  
ER\_IB\_MSG\_1077 error code, 310  
ER\_IB\_MSG\_1078 error code, 310  
ER\_IB\_MSG\_1079 error code, 311  
ER\_IB\_MSG\_108 error code, 254  
ER\_IB\_MSG\_1080 error code, 311  
ER\_IB\_MSG\_1081 error code, 311  
ER\_IB\_MSG\_1082 error code, 311  
ER\_IB\_MSG\_1083 error code, 311  
ER\_IB\_MSG\_1085 error code, 311  
ER\_IB\_MSG\_1086 error code, 311  
ER\_IB\_MSG\_1087 error code, 311  
ER\_IB\_MSG\_1088 error code, 311  
ER\_IB\_MSG\_1089 error code, 311  
ER\_IB\_MSG\_109 error code, 254  
ER\_IB\_MSG\_1090 error code, 311  
ER\_IB\_MSG\_1091 error code, 311  
ER\_IB\_MSG\_1092 error code, 311  
ER\_IB\_MSG\_1093 error code, 311  
ER\_IB\_MSG\_1094 error code, 312  
ER\_IB\_MSG\_1095 error code, 312  
ER\_IB\_MSG\_1096 error code, 312  
ER\_IB\_MSG\_1097 error code, 312  
ER\_IB\_MSG\_1098 error code, 312  
ER\_IB\_MSG\_1099 error code, 312  
ER\_IB\_MSG\_11 error code, 248  
ER\_IB\_MSG\_110 error code, 254  
ER\_IB\_MSG\_1100 error code, 312  
ER\_IB\_MSG\_1101 error code, 312  
ER\_IB\_MSG\_1102 error code, 312  
ER\_IB\_MSG\_1103 error code, 312  
ER\_IB\_MSG\_1104 error code, 312  
ER\_IB\_MSG\_1105 error code, 312  
ER\_IB\_MSG\_1107 error code, 312  
ER\_IB\_MSG\_1108 error code, 312  
ER\_IB\_MSG\_1109 error code, 313





---

ER\_IB\_MSG\_1248 error code, 321  
ER\_IB\_MSG\_1249 error code, 321  
ER\_IB\_MSG\_125 error code, 254  
ER\_IB\_MSG\_1250 error code, 321  
ER\_IB\_MSG\_1251 error code, 321  
ER\_IB\_MSG\_1253 error code, 321  
ER\_IB\_MSG\_1255 error code, 321  
ER\_IB\_MSG\_1256 error code, 321  
ER\_IB\_MSG\_1257 error code, 321  
ER\_IB\_MSG\_1258 error code, 322  
ER\_IB\_MSG\_1259 error code, 322  
ER\_IB\_MSG\_126 error code, 254  
ER\_IB\_MSG\_1260 error code, 322  
ER\_IB\_MSG\_1261 error code, 322  
ER\_IB\_MSG\_1262 error code, 322  
ER\_IB\_MSG\_1263 error code, 322  
ER\_IB\_MSG\_1266 error code, 322  
ER\_IB\_MSG\_1268 error code, 322  
ER\_IB\_MSG\_1269 error code, 322  
ER\_IB\_MSG\_127 error code, 254  
ER\_IB\_MSG\_1271 error code, 328  
ER\_IB\_MSG\_1272 error code, 328  
ER\_IB\_MSG\_1273 error code, 328  
ER\_IB\_MSG\_1274 error code, 329  
ER\_IB\_MSG\_1275 error code, 329  
ER\_IB\_MSG\_1277 error code, 329  
ER\_IB\_MSG\_128 error code, 255  
ER\_IB\_MSG\_1280 error code, 329  
ER\_IB\_MSG\_1281 error code, 329  
ER\_IB\_MSG\_1282 error code, 329  
ER\_IB\_MSG\_1283 error code, 330  
ER\_IB\_MSG\_1284 error code, 330  
ER\_IB\_MSG\_1285 error code, 345  
ER\_IB\_MSG\_129 error code, 255  
ER\_IB\_MSG\_13 error code, 248  
ER\_IB\_MSG\_130 error code, 255  
ER\_IB\_MSG\_131 error code, 255  
ER\_IB\_MSG\_132 error code, 255  
ER\_IB\_MSG\_133 error code, 255  
ER\_IB\_MSG\_134 error code, 255  
ER\_IB\_MSG\_135 error code, 255  
ER\_IB\_MSG\_1357 error code, 359  
ER\_IB\_MSG\_1358 error code, 359  
ER\_IB\_MSG\_1359 error code, 359  
ER\_IB\_MSG\_136 error code, 255  
ER\_IB\_MSG\_137 error code, 255  
ER\_IB\_MSG\_1372 error code, 360  
ER\_IB\_MSG\_1373 error code, 360  
ER\_IB\_MSG\_1374 error code, 360  
ER\_IB\_MSG\_1375 error code, 360  
ER\_IB\_MSG\_138 error code, 255  
ER\_IB\_MSG\_1381 error code, 361  
ER\_IB\_MSG\_139 error code, 255  
ER\_IB\_MSG\_14 error code, 248  
ER\_IB\_MSG\_140 error code, 255  
ER\_IB\_MSG\_141 error code, 255  
ER\_IB\_MSG\_142 error code, 255  
ER\_IB\_MSG\_143 error code, 255

ER\_IB\_MSG\_144 error code, 256  
ER\_IB\_MSG\_145 error code, 256  
ER\_IB\_MSG\_146 error code, 256  
ER\_IB\_MSG\_147 error code, 256  
ER\_IB\_MSG\_148 error code, 256  
ER\_IB\_MSG\_15 error code, 248  
ER\_IB\_MSG\_156 error code, 256  
ER\_IB\_MSG\_157 error code, 256  
ER\_IB\_MSG\_158 error code, 256  
ER\_IB\_MSG\_159 error code, 256  
ER\_IB\_MSG\_16 error code, 248  
ER\_IB\_MSG\_160 error code, 257  
ER\_IB\_MSG\_161 error code, 257  
ER\_IB\_MSG\_162 error code, 257  
ER\_IB\_MSG\_163 error code, 257  
ER\_IB\_MSG\_164 error code, 257  
ER\_IB\_MSG\_165 error code, 257  
ER\_IB\_MSG\_166 error code, 257  
ER\_IB\_MSG\_167 error code, 257  
ER\_IB\_MSG\_168 error code, 257  
ER\_IB\_MSG\_169 error code, 257  
ER\_IB\_MSG\_17 error code, 248  
ER\_IB\_MSG\_170 error code, 257  
ER\_IB\_MSG\_171 error code, 257  
ER\_IB\_MSG\_172 error code, 257  
ER\_IB\_MSG\_173 error code, 257  
ER\_IB\_MSG\_174 error code, 257  
ER\_IB\_MSG\_175 error code, 257  
ER\_IB\_MSG\_176 error code, 258  
ER\_IB\_MSG\_177 error code, 258  
ER\_IB\_MSG\_178 error code, 258  
ER\_IB\_MSG\_179 error code, 258  
ER\_IB\_MSG\_18 error code, 249  
ER\_IB\_MSG\_180 error code, 258  
ER\_IB\_MSG\_182 error code, 258  
ER\_IB\_MSG\_183 error code, 258  
ER\_IB\_MSG\_184 error code, 258  
ER\_IB\_MSG\_185 error code, 258  
ER\_IB\_MSG\_186 error code, 258  
ER\_IB\_MSG\_187 error code, 258  
ER\_IB\_MSG\_188 error code, 258  
ER\_IB\_MSG\_189 error code, 258  
ER\_IB\_MSG\_19 error code, 249  
ER\_IB\_MSG\_190 error code, 258  
ER\_IB\_MSG\_191 error code, 258  
ER\_IB\_MSG\_192 error code, 259  
ER\_IB\_MSG\_193 error code, 259  
ER\_IB\_MSG\_194 error code, 259  
ER\_IB\_MSG\_195 error code, 259  
ER\_IB\_MSG\_196 error code, 259  
ER\_IB\_MSG\_197 error code, 259  
ER\_IB\_MSG\_198 error code, 259  
ER\_IB\_MSG\_199 error code, 259  
ER\_IB\_MSG\_2 error code, 248  
ER\_IB\_MSG\_20 error code, 249  
ER\_IB\_MSG\_200 error code, 259  
ER\_IB\_MSG\_201 error code, 259  
ER\_IB\_MSG\_202 error code, 259







---

ER\_IB\_MSG\_534 error code, 279  
ER\_IB\_MSG\_537 error code, 279  
ER\_IB\_MSG\_538 error code, 279  
ER\_IB\_MSG\_539 error code, 279  
ER\_IB\_MSG\_54 error code, 251  
ER\_IB\_MSG\_540 error code, 279  
ER\_IB\_MSG\_541 error code, 279  
ER\_IB\_MSG\_542 error code, 279  
ER\_IB\_MSG\_543 error code, 280  
ER\_IB\_MSG\_544 error code, 280  
ER\_IB\_MSG\_545 error code, 280  
ER\_IB\_MSG\_546 error code, 280  
ER\_IB\_MSG\_547 error code, 280  
ER\_IB\_MSG\_548 error code, 280  
ER\_IB\_MSG\_549 error code, 280  
ER\_IB\_MSG\_55 error code, 251  
ER\_IB\_MSG\_550 error code, 280  
ER\_IB\_MSG\_551 error code, 280  
ER\_IB\_MSG\_552 error code, 280  
ER\_IB\_MSG\_553 error code, 280  
ER\_IB\_MSG\_554 error code, 280  
ER\_IB\_MSG\_555 error code, 280  
ER\_IB\_MSG\_556 error code, 280  
ER\_IB\_MSG\_557 error code, 280  
ER\_IB\_MSG\_558 error code, 280  
ER\_IB\_MSG\_559 error code, 280  
ER\_IB\_MSG\_56 error code, 251  
ER\_IB\_MSG\_560 error code, 281  
ER\_IB\_MSG\_561 error code, 281  
ER\_IB\_MSG\_562 error code, 281  
ER\_IB\_MSG\_563 error code, 281  
ER\_IB\_MSG\_564 error code, 281  
ER\_IB\_MSG\_566 error code, 281  
ER\_IB\_MSG\_567 error code, 281  
ER\_IB\_MSG\_568 error code, 281  
ER\_IB\_MSG\_569 error code, 281  
ER\_IB\_MSG\_57 error code, 251  
ER\_IB\_MSG\_570 error code, 281  
ER\_IB\_MSG\_571 error code, 281  
ER\_IB\_MSG\_573 error code, 281  
ER\_IB\_MSG\_574 error code, 281  
ER\_IB\_MSG\_578 error code, 281  
ER\_IB\_MSG\_579 error code, 281  
ER\_IB\_MSG\_57\_STAT\_SPACE\_DELETE\_FAIL error code, 356  
ER\_IB\_MSG\_57\_UNDO\_SPACE\_DELETE\_FAIL error code, 353  
ER\_IB\_MSG\_58 error code, 251  
ER\_IB\_MSG\_580 error code, 282  
ER\_IB\_MSG\_581 error code, 282  
ER\_IB\_MSG\_582 error code, 282  
ER\_IB\_MSG\_583 error code, 282  
ER\_IB\_MSG\_584 error code, 282  
ER\_IB\_MSG\_585 error code, 282  
ER\_IB\_MSG\_586 error code, 282  
ER\_IB\_MSG\_587 error code, 282  
ER\_IB\_MSG\_588 error code, 282  
ER\_IB\_MSG\_589 error code, 282  
ER\_IB\_MSG\_59 error code, 251  
ER\_IB\_MSG\_590 error code, 282  
ER\_IB\_MSG\_591 error code, 282  
ER\_IB\_MSG\_592 error code, 282  
ER\_IB\_MSG\_593 error code, 282  
ER\_IB\_MSG\_594 error code, 282  
ER\_IB\_MSG\_595 error code, 282  
ER\_IB\_MSG\_596 error code, 283  
ER\_IB\_MSG\_597 error code, 283  
ER\_IB\_MSG\_598 error code, 283  
ER\_IB\_MSG\_599 error code, 283  
ER\_IB\_MSG\_6 error code, 248  
ER\_IB\_MSG\_60 error code, 251  
ER\_IB\_MSG\_600 error code, 283  
ER\_IB\_MSG\_601 error code, 283  
ER\_IB\_MSG\_602 error code, 283  
ER\_IB\_MSG\_603 error code, 283  
ER\_IB\_MSG\_604 error code, 283  
ER\_IB\_MSG\_605 error code, 283  
ER\_IB\_MSG\_606 error code, 283  
ER\_IB\_MSG\_607 error code, 283  
ER\_IB\_MSG\_608 error code, 283  
ER\_IB\_MSG\_609 error code, 283  
ER\_IB\_MSG\_61 error code, 251  
ER\_IB\_MSG\_610 error code, 283  
ER\_IB\_MSG\_611 error code, 283  
ER\_IB\_MSG\_612 error code, 283  
ER\_IB\_MSG\_613 error code, 284  
ER\_IB\_MSG\_614 error code, 284  
ER\_IB\_MSG\_615 error code, 284  
ER\_IB\_MSG\_616 error code, 284  
ER\_IB\_MSG\_617 error code, 284  
ER\_IB\_MSG\_618 error code, 284  
ER\_IB\_MSG\_619 error code, 284  
ER\_IB\_MSG\_62 error code, 251  
ER\_IB\_MSG\_620 error code, 284  
ER\_IB\_MSG\_621 error code, 284  
ER\_IB\_MSG\_622 error code, 284  
ER\_IB\_MSG\_623 error code, 284  
ER\_IB\_MSG\_624 error code, 284  
ER\_IB\_MSG\_625 error code, 284  
ER\_IB\_MSG\_626 error code, 284  
ER\_IB\_MSG\_627 error code, 284  
ER\_IB\_MSG\_628 error code, 284  
ER\_IB\_MSG\_629 error code, 285  
ER\_IB\_MSG\_63 error code, 251  
ER\_IB\_MSG\_630 error code, 285  
ER\_IB\_MSG\_631 error code, 285  
ER\_IB\_MSG\_632 error code, 285  
ER\_IB\_MSG\_633 error code, 285  
ER\_IB\_MSG\_634 error code, 285  
ER\_IB\_MSG\_635 error code, 285  
ER\_IB\_MSG\_636 error code, 285  
ER\_IB\_MSG\_637 error code, 285  
ER\_IB\_MSG\_638 error code, 285  
ER\_IB\_MSG\_639 error code, 285  
ER\_IB\_MSG\_64 error code, 251  
ER\_IB\_MSG\_642 error code, 285







---

ER\_IB\_MSG\_900 error code, 300  
ER\_IB\_MSG\_901 error code, 300  
ER\_IB\_MSG\_902 error code, 300  
ER\_IB\_MSG\_903 error code, 300  
ER\_IB\_MSG\_904 error code, 300  
ER\_IB\_MSG\_905 error code, 300  
ER\_IB\_MSG\_906 error code, 300  
ER\_IB\_MSG\_907 error code, 300  
ER\_IB\_MSG\_908 error code, 300  
ER\_IB\_MSG\_909 error code, 300  
ER\_IB\_MSG\_910 error code, 300  
ER\_IB\_MSG\_911 error code, 300  
ER\_IB\_MSG\_912 error code, 300  
ER\_IB\_MSG\_913 error code, 300  
ER\_IB\_MSG\_914 error code, 300  
ER\_IB\_MSG\_915 error code, 300  
ER\_IB\_MSG\_916 error code, 301  
ER\_IB\_MSG\_917 error code, 301  
ER\_IB\_MSG\_918 error code, 301  
ER\_IB\_MSG\_919 error code, 301  
ER\_IB\_MSG\_920 error code, 301  
ER\_IB\_MSG\_921 error code, 301  
ER\_IB\_MSG\_922 error code, 301  
ER\_IB\_MSG\_923 error code, 301  
ER\_IB\_MSG\_924 error code, 301  
ER\_IB\_MSG\_925 error code, 301  
ER\_IB\_MSG\_926 error code, 301  
ER\_IB\_MSG\_927 error code, 301  
ER\_IB\_MSG\_928 error code, 301  
ER\_IB\_MSG\_929 error code, 301  
ER\_IB\_MSG\_930 error code, 301  
ER\_IB\_MSG\_931 error code, 301  
ER\_IB\_MSG\_932 error code, 301  
ER\_IB\_MSG\_933 error code, 302  
ER\_IB\_MSG\_934 error code, 302  
ER\_IB\_MSG\_935 error code, 302  
ER\_IB\_MSG\_936 error code, 302  
ER\_IB\_MSG\_937 error code, 302  
ER\_IB\_MSG\_938 error code, 302  
ER\_IB\_MSG\_939 error code, 302  
ER\_IB\_MSG\_940 error code, 302  
ER\_IB\_MSG\_941 error code, 302  
ER\_IB\_MSG\_942 error code, 302  
ER\_IB\_MSG\_943 error code, 302  
ER\_IB\_MSG\_944 error code, 302  
ER\_IB\_MSG\_945 error code, 302  
ER\_IB\_MSG\_946 error code, 302  
ER\_IB\_MSG\_948 error code, 302  
ER\_IB\_MSG\_949 error code, 303  
ER\_IB\_MSG\_95 error code, 253  
ER\_IB\_MSG\_950 error code, 303  
ER\_IB\_MSG\_951 error code, 303  
ER\_IB\_MSG\_952 error code, 303  
ER\_IB\_MSG\_953 error code, 303  
ER\_IB\_MSG\_954 error code, 303  
ER\_IB\_MSG\_955 error code, 303  
ER\_IB\_MSG\_956 error code, 303  
ER\_IB\_MSG\_957 error code, 303  
ER\_IB\_MSG\_958 error code, 303  
ER\_IB\_MSG\_959 error code, 303  
ER\_IB\_MSG\_96 error code, 253  
ER\_IB\_MSG\_960 error code, 303  
ER\_IB\_MSG\_961 error code, 303  
ER\_IB\_MSG\_962 error code, 303  
ER\_IB\_MSG\_963 error code, 303  
ER\_IB\_MSG\_964 error code, 303  
ER\_IB\_MSG\_965 error code, 304  
ER\_IB\_MSG\_966 error code, 304  
ER\_IB\_MSG\_967 error code, 304  
ER\_IB\_MSG\_968 error code, 304  
ER\_IB\_MSG\_969 error code, 304  
ER\_IB\_MSG\_97 error code, 253  
ER\_IB\_MSG\_970 error code, 304  
ER\_IB\_MSG\_971 error code, 304  
ER\_IB\_MSG\_972 error code, 304  
ER\_IB\_MSG\_973 error code, 304  
ER\_IB\_MSG\_974 error code, 304  
ER\_IB\_MSG\_975 error code, 304  
ER\_IB\_MSG\_976 error code, 304  
ER\_IB\_MSG\_977 error code, 304  
ER\_IB\_MSG\_978 error code, 304  
ER\_IB\_MSG\_979 error code, 304  
ER\_IB\_MSG\_98 error code, 253  
ER\_IB\_MSG\_980 error code, 304  
ER\_IB\_MSG\_981 error code, 305  
ER\_IB\_MSG\_982 error code, 305  
ER\_IB\_MSG\_983 error code, 305  
ER\_IB\_MSG\_984 error code, 305  
ER\_IB\_MSG\_985 error code, 305  
ER\_IB\_MSG\_986 error code, 305  
ER\_IB\_MSG\_987 error code, 305  
ER\_IB\_MSG\_988 error code, 305  
ER\_IB\_MSG\_989 error code, 305  
ER\_IB\_MSG\_99 error code, 253  
ER\_IB\_MSG\_990 error code, 305  
ER\_IB\_MSG\_991 error code, 305  
ER\_IB\_MSG\_992 error code, 305  
ER\_IB\_MSG\_993 error code, 305  
ER\_IB\_MSG\_994 error code, 305  
ER\_IB\_MSG\_995 error code, 305  
ER\_IB\_MSG\_996 error code, 305  
ER\_IB\_MSG\_997 error code, 306  
ER\_IB\_MSG\_998 error code, 306  
ER\_IB\_MSG\_999 error code, 306  
ER\_IB\_MSG\_BAD\_DBLWR\_FILE\_NAME error code,  
353  
ER\_IB\_MSG\_BTREE\_LEVEL\_LIMIT\_EXCEEDED  
error code, 347  
ER\_IB\_MSG\_BUF\_PENDING\_IO error code, 312  
ER\_IB\_MSG\_BUF\_PENDING\_IO\_ON\_SHUTDOWN  
error code, 321  
ER\_IB\_MSG\_BUF\_POOL\_RESIZE\_CODE\_STATUS  
error code, 386  
ER\_IB\_MSG\_BUF\_POOL\_RESIZE\_COMPLETE\_CUR\_CODE  
error code, 386

---

---

ER\_IB\_MSG\_BUF\_POOL\_RESIZE\_PROGRESS\_UPDATE error code, 386  
 ER\_IB\_MSG\_CANNOT\_FIND\_DD\_UNDO\_SPACE error code, 357  
 ER\_IB\_MSG\_CANNOT\_OPEN\_57\_UNDO error code, 311  
 ER\_IB\_MSG\_CANT\_ENCRYPT\_REDO\_LOG\_DATA error code, 296  
 ER\_IB\_MSG\_CLEAR\_INSTANT\_DROP\_COLUMN\_METADATA error code, 386  
 ER\_IB\_MSG\_CLOCK\_GETTIME\_FAILED error code, 345  
 ER\_IB\_MSG\_CLOCK\_MONOTONIC\_UNSUPPORTED error code, 345  
 ER\_IB\_MSG\_CLONE\_DDL\_APPLY error code, 374  
 ER\_IB\_MSG\_CLONE\_DDL\_INVALIDATE error code, 374  
 ER\_IB\_MSG\_CLONE\_DDL\_NTFN error code, 374  
 ER\_IB\_MSG\_CREATED\_UNDO\_SPACE error code, 363  
 ER\_IB\_MSG\_DATA\_DIRECTORY\_NOT\_INITIALIZED\_OR\_CORRUPTED error code, 314  
 ER\_IB\_MSG\_DBLWR\_1285 error code, 353  
 ER\_IB\_MSG\_DBLWR\_1286 error code, 353  
 ER\_IB\_MSG\_DBLWR\_1287 error code, 353  
 ER\_IB\_MSG\_DBLWR\_1288 error code, 353  
 ER\_IB\_MSG\_DBLWR\_1290 error code, 353  
 ER\_IB\_MSG\_DBLWR\_1293 error code, 353  
 ER\_IB\_MSG\_DBLWR\_1294 error code, 353  
 ER\_IB\_MSG\_DBLWR\_1295 error code, 354  
 ER\_IB\_MSG\_DBLWR\_1296 error code, 354  
 ER\_IB\_MSG\_DBLWR\_1297 error code, 354  
 ER\_IB\_MSG\_DBLWR\_1298 error code, 354  
 ER\_IB\_MSG\_DBLWR\_1300 error code, 354  
 ER\_IB\_MSG\_DBLWR\_1301 error code, 354  
 ER\_IB\_MSG\_DBLWR\_1304 error code, 354  
 ER\_IB\_MSG\_DBLWR\_1305 error code, 354  
 ER\_IB\_MSG\_DBLWR\_1306 error code, 354  
 ER\_IB\_MSG\_DBLWR\_1307 error code, 354  
 ER\_IB\_MSG\_DBLWR\_1308 error code, 354  
 ER\_IB\_MSG\_DBLWR\_1309 error code, 354  
 ER\_IB\_MSG\_DBLWR\_1310 error code, 354  
 ER\_IB\_MSG\_DBLWR\_1311 error code, 354  
 ER\_IB\_MSG\_DBLWR\_1312 error code, 354  
 ER\_IB\_MSG\_DBLWR\_1313 error code, 354  
 ER\_IB\_MSG\_DBLWR\_1314 error code, 355  
 ER\_IB\_MSG\_DBLWR\_1315 error code, 355  
 ER\_IB\_MSG\_DBLWR\_1316 error code, 355  
 ER\_IB\_MSG\_DBLWR\_1317 error code, 355  
 ER\_IB\_MSG\_DBLWR\_1318 error code, 355  
 ER\_IB\_MSG\_DBLWR\_1320 error code, 355  
 ER\_IB\_MSG\_DBLWR\_1321 error code, 355  
 ER\_IB\_MSG\_DBLWR\_1323 error code, 355  
 ER\_IB\_MSG\_DBLWR\_1324 error code, 355  
 ER\_IB\_MSG\_DBLWR\_1325 error code, 355  
 ER\_IB\_MSG\_DBLWR\_1326 error code, 355  
 ER\_IB\_MSG\_DBLWR\_1327 error code, 355  
 ER\_IB\_MSG\_DBLWR\_LOAD\_WRONG\_SIZE error code, 355  
 ER\_IB\_MSG\_DBLWR\_OPEN\_OR\_CREATE\_WRONG\_SIZE error code, 355  
 ER\_IB\_MSG\_DDL\_FAIL\_NO\_BUILDER error code, 396  
 ER\_IB\_MSG\_DDL\_LOG\_DELETE\_BY\_ID\_OK error code, 286  
 ER\_IB\_MSG\_DDL\_LOG\_DELETE\_BY\_ID\_TMCT error code, 343  
 ER\_IB\_MSG\_DDL\_LOG\_FAIL\_POST\_DDL error code, 344  
 ER\_IB\_MSG\_DEPRECATED\_INNOODB\_UNDO\_TABLESPACES error code, 334  
 ER\_IB\_MSG\_DICT\_PARTITION\_NOT\_FOUND error code, 352  
 ER\_IB\_MSG\_DOWNGRADE\_PARTITION\_FILE error code, 351  
 ER\_IB\_MSG\_DROPPED\_UNDO\_SPACE error code, 363  
 ER\_IB\_MSG\_ERROR\_OPENING\_NEW\_UNDO\_SPACE error code, 333  
 ER\_IB\_MSG\_FAILED\_SDI\_Z\_BUF\_ERROR error code, 333  
 ER\_IB\_MSG\_FAILED\_SDI\_Z\_MEM\_ERROR error code, 334  
 ER\_IB\_MSG\_FAILED\_TO\_ALLOCATE\_WAIT error code, 333  
 ER\_IB\_MSG\_FAILED\_TO\_FINISH\_TRUNCATE error code, 334  
 ER\_IB\_MSG\_FAIL\_TO\_SAVE\_SPACE\_STATE error code, 333  
 ER\_IB\_MSG\_FILE\_RESIZE error code, 310  
 ER\_IB\_MSG\_FIL\_STATE\_MOVED\_CHANGED\_NAME error code, 352  
 ER\_IB\_MSG\_FIL\_STATE\_MOVED\_CHANGED\_PATH error code, 352  
 ER\_IB\_MSG\_FIL\_STATE\_MOVED\_CORRECTED error code, 352  
 ER\_IB\_MSG\_FIL\_STATE\_MOVED\_TOO\_MANY error code, 352  
 ER\_IB\_MSG\_FOUND\_WRONG\_UNDO\_SPACE error code, 334  
 ER\_IB\_MSG\_GENERAL\_TABLESPACE\_UNDER\_DATADIR error code, 270  
 ER\_IB\_MSG\_GTID\_FLUSH\_AT\_SHUTDOWN error code, 355  
 ER\_IB\_MSG\_IGNORE\_SCAN\_PATH error code, 269  
 ER\_IB\_MSG\_IMPLICIT\_TABLESPACE\_IN\_DATADIR error code, 270  
 ER\_IB\_MSG\_INCORRECT\_SIZE error code, 362  
 ER\_IB\_MSG\_INJECT\_CRASH error code, 362  
 ER\_IB\_MSG\_INJECT\_FAILURE error code, 362  
 ER\_IB\_MSG\_INNOODB\_END\_INITIALIZE error code, 356  
 ER\_IB\_MSG\_INNOODB\_START\_INITIALIZE error code, 356

---

ER_IB_MSG_INVALID_LOCATION_FOR_TABLE error code, 281	ER_IB_MSG_LOG_FILE_FORMAT_UNKNOWN error code, 287
ER_IB_MSG_INVALID_LOCATION_FOR_TABLESPACE error code, 357	ER_IB_MSG_LOG_FILE_HEADER_INVALID_CHECKSUM error code, 322
ER_IB_MSG_INVALID_LOCATION_WRONG_DB error code, 357	ER_IB_MSG_LOG_FILE_HEADER_READ_FAILED error code, 379
ER_IB_MSG_INVALID_PAGE_TYPE error code, 387	ER_IB_MSG_LOG_FILE_INVALID_LSN_RANGES error code, 381
ER_IB_MSG_LOCK_FREE_HASH_USAGE_STATS error code, 334	ER_IB_MSG_LOG_FILE_INVALID_START_LSN error code, 381
ER_IB_MSG_LOG_CHECKPOINT_FOUND error code, 381	ER_IB_MSG_LOG_FILE_IS_EMPTY error code, 379
ER_IB_MSG_LOG_CORRUPT error code, 287	ER_IB_MSG_LOG_FILE_MARK_AS_UNUSED_FAILED error code, 383
ER_IB_MSG_LOG_FILES_CANNOT_ENCRYPT_IN_READ_ONLY error code, 321	ER_IB_MSG_LOG_FILE_MARK_CURRENT_AS_INCOMPLETE error code, 381
ER_IB_MSG_LOG_FILES_CAPACITY_CHANGED error code, 381	ER_IB_MSG_LOG_FILE_MISSING_FOR_ID error code, 381
ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE error code, 289	ER_IB_MSG_LOG_FILE_OPEN_FAILED error code, 381
ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE_AND_READ_ONLY error code, 379	ER_IB_MSG_LOG_FILE_OS_CREATE_FAILED error code, 309
ER_IB_MSG_LOG_FILES_CREATED_BY_MEB error code, 289	ER_IB_MSG_LOG_FILE_PREPARE_ON_CREATE_FAILED error code, 310
ER_IB_MSG_LOG_FILES_CREATED_BY_MEB_AND_READ_ONLY error code, 289	ER_IB_MSG_LOG_FILE_REMOVE_FAILED error code, 310
ER_IB_MSG_LOG_FILES_CREATED_BY_UNKNOWN_CREATOR error code, 382	ER_IB_MSG_LOG_FILE_RENAME_ON_CREATE_FAILED error code, 382
ER_IB_MSG_LOG_FILES_CREATE_AND_READ_ONLY error code, 310	ER_IB_MSG_LOG_FILE_RESIZE_FAILED error code, 310
ER_IB_MSG_LOG_FILES_DIFFERENT_SIZES error code, 314	ER_IB_MSG_LOG_FILE_SIZE_INVALID error code, 314
ER_IB_MSG_LOG_FILES_ENCRYPTION_INIT_FAILED error code, 321	ER_IB_MSG_LOG_FILE_TOO_BIG error code, 379
ER_IB_MSG_LOG_FILES_FOUND_MISSING error code, 382	ER_IB_MSG_LOG_FILE_TOO_SMALL error code, 379
ER_IB_MSG_LOG_FILES_INITIALIZED error code, 310	ER_IB_MSG_LOG_FILE_TRUNCATE error code, 382
ER_IB_MSG_LOG_FILES_INVALID_SET error code, 314	ER_IB_MSG_LOG_FILE_UNUSED_MARK_AS_IN_USE_FAILED error code, 383
ER_IB_MSG_LOG_FILES_RESIZE_CANCELLED error code, 381	ER_IB_MSG_LOG_FILE_UNUSED_REMOVE_FAILED error code, 382
ER_IB_MSG_LOG_FILES_RESIZE_FINISHED error code, 381	ER_IB_MSG_LOG_FILE_UNUSED_RENAME_FAILED error code, 382
ER_IB_MSG_LOG_FILES_RESIZE_ON_START error code, 319	ER_IB_MSG_LOG_FILE_UNUSED_RESIZE_FAILED error code, 382
ER_IB_MSG_LOG_FILES_RESIZE_REQUESTED error code, 381	ER_IB_MSG_LOG_FORMAT_BEFORE_5_7_9 error code, 322
ER_IB_MSG_LOG_FILES_REWRITING error code, 315	ER_IB_MSG_LOG_FORMAT_BEFORE_8_0_30 error code, 287
ER_IB_MSG_LOG_FILES_UPGRADE error code, 381	ER_IB_MSG_LOG_FORMAT_OLD error code, 289
ER_IB_MSG_LOG_FILE_DIFFERENT_FORMATS error code, 382	ER_IB_MSG_LOG_FORMAT_OLD_AND_LOG_CORRUPTED error code, 287
ER_IB_MSG_LOG_FILE_FOREIGN_UUID error code, 381	ER_IB_MSG_LOG_FORMAT_OLD_AND_NO_CLEAN_SHUTDOWN error code, 287
ER_IB_MSG_LOG_FILE_FORMAT_TOO_NEW error code, 382	ER_IB_MSG_LOG_INIT_DIR_LIST_FAILED error code, 379
ER_IB_MSG_LOG_FILE_FORMAT_TOO_OLD error code, 382	ER_IB_MSG_LOG_INIT_DIR_MISSING_SUBDIR error code, 379
	ER_IB_MSG_LOG_INIT_DIR_NOT_EMPTY_WONT_INITIALIZE error code, 379

---

---

ER_IB_MSG_LOG_PARAMS_CONCURRENCY_MARGIN	ER_IB_MSG_PAR_RSEG_INIT_TIME_MSG error
error code, 322	code, 372
ER_IB_MSG_LOG_PARAMS_DEDICATED_SERVER_IG	ER_IB_MSG_POST_RECOVER_DDL_LOG_RECOVER
error code, 383	error code, 343
ER_IB_MSG_LOG_PARAMS_FILE_SIZE_UNUSED	ER_IB_MSG_POST_RECOVER_POST_TS_ENCRYPT
error code, 380	error code, 344
ER_IB_MSG_LOG_PARAMS_LEGACY_USAGE error	ER_IB_MSG_RECOVERY_CHECKPOINT_FROM_BEFORE_CLEA
code, 383	error code, 289
ER_IB_MSG_LOG_PARAMS_N_FILES_UNUSED	ER_IB_MSG_RECOVERY_CHECKPOINT_NOT_FOUND
error code, 380	error code, 287
ER_IB_MSG_LOG_PFS_ACQUIRE_SERVICES_FAILED	ER_IB_MSG_RECOVERY_CHECKPOINT_OUTSIDE_LOG_FILE
error code, 382	error code, 380
ER_IB_MSG_LOG_PFS_CREATE_TABLES_FAILED	ER_IB_MSG_RECOVERY_CORRUPT error code, 315
error code, 382	ER_IB_MSG_RECOVERY_IN_READ_ONLY error
ER_IB_MSG_LOG_PRE_8_0_30_MISSING_FILE0	code, 289
error code, 382	ER_IB_MSG_RECOVERY_IS_NEEDED error code,
ER_IB_MSG_LOG_UPGRADE_CLONED_DB error	289
code, 380	ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG__SKIP_IB
ER_IB_MSG_LOG_UPGRADE_CORRUPTION__UNEXP	CODE error code, 372
error code, 381	ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG__UNEXP
ER_IB_MSG_LOG_UPGRADE_FORCED_RECV error	error code, 372
code, 380	ER_IB_MSG_RECOVERY_SKIPPED_IN_READ_ONLY_MODE
ER_IB_MSG_LOG_UPGRADE_IN_READ_ONLY_MODE	error code, 288
error code, 380	ER_IB_MSG_REENCRYPTED_GENERAL_TABLESPACE_KEY
ER_IB_MSG_LOG_UPGRADE_UNINITIALIZED_FILES	error code, 371
error code, 380	ER_IB_MSG_REENCRYPTED_TABLESPACE_KEY
ER_IB_MSG_LOG_WRITER_ABORTS_LOG_ARCHIVER	error code, 371
error code, 320	ER_IB_MSG_RESUME_OP_FOR_SPACE error code,
ER_IB_MSG_LOG_WRITER_ENTERED_EXTRA_MARGIN	329
error code, 380	ER_IB_MSG_SCANNING_TEMP_TABLESPACE_DIR
ER_IB_MSG_LOG_WRITER_EXITED_EXTRA_MARGIN	error code, 360
error code, 380	ER_IB_MSG_SDI_Z_STREAM_ERROR error code,
ER_IB_MSG_LOG_WRITER_OUT_OF_SPACE error	334
code, 320	ER_IB_MSG_SDI_Z_UNKNOWN_ERROR error code,
ER_IB_MSG_LOG_WRITER_WAITING_FOR_ARCHIVER	334
error code, 320	ER_IB_MSG_SKIP_HIDDEN_DIR error code, 351
ER_IB_MSG_LOG_WRITER_WAIT_ON_CONSUMER	ER_IB_MSG_STATS_SAMPLING_TOO_LARGE error
error code, 385	code, 366
ER_IB_MSG_LOG_WRITER_WAIT_ON_NEW_LOG_FILE	ER_IB_MSG_THREAD_CONCURRENCY_CHANGED
error code, 380	error code, 322
ER_IB_MSG_LOG_WRITER_WRITE_FAILED error	ER_IB_MSG_TOO_LONG_PATH error code, 344
code, 380	ER_IB_MSG_TRX_RECOVERY_ROLLBACK_COMPLETED
ER_IB_MSG_MADVISE_FAILED error code, 333	error code, 317
ER_IB_MSG_MADV_DONTDUMP_UNSUPPORTED	ER_IB_MSG_TRX_RECOVERY_ROLLBACK_NOT_COMPLETED
error code, 333	error code, 358
ER_IB_MSG_MASTER_KEY_ROTATED error code,	ER_IB_MSG_TRYING_TO_OPEN_FILE_FOR_LONG_TIME
363	error code, 377
ER_IB_MSG_MAX_UNDO_SPACES_REACHED error	ER_IB_MSG_UNDO_ALTERED_ACTIVE error code,
code, 333	361
ER_IB_MSG_NOT_END_WITH_IBU error code, 334	ER_IB_MSG_UNDO_ALTERED_INACTIVE error
ER_IB_MSG_NO_ENCRYPT_PROGRESS_FOUND	code, 361
error code, 329	ER_IB_MSG_UNDO_ENCRYPTION_INFO_LOADED
ER_IB_MSG_PAGE_ARCH_NO_RESET_POINTS	error code, 374
error code, 356	ER_IB_MSG_UNDO_MARKED_ACTIVE error code,
ER_IB_MSG_PARSE_OLD_REDO_INDEX_VERSION	361
error code, 385	ER_IB_MSG_UNDO_MARKED_EMPTY error code,
ER_IB_MSG_PAR_RSEG_INIT_COMPLETE_MSG	361
error code, 372	

---

---

ER_IB_MSG_UNDO_MARKED_FOR_TRUNCATE error code, 316	ER_IB_TMP_TABLESPACE_CANNOT_CREATE_DIRECTORY error code, 359
ER_IB_MSG_UNDO_TRUNCATE_COMPLETE error code, 317	ER_IB_UNABLE_TO_EXPAND_TEMPORARY_TABLESPACE error code, 359
ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_CLONE error code, 361	ER_IB_WARN_ACCESSING_NONEXISTING_SPACE error code, 264
ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_FAILURE error code, 316	ER_IB_WARN_MANY_NON_LRU_FILES_OPENED error code, 377
ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_LOG_CREATE error code, 316	ER_IB_WARN_OPEN_PARTITION_FILE error code, 352
ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_MDL error code, 362	ER_IB_WRN_ENCRYPTION_INFO_SIZE_MISMATCH error code, 374
ER_IB_MSG_UNDO_TRUNCATE_FAIL_TO_READ_LOG error code, 316	ER_IB_WRN_FAILED_TO_ACQUIRE_SERVICE error code, 368
ER_IB_MSG_UNDO_TRUNCATE_START error code, 316	ER_IB_WRN_FAST_SHUTDOWN_REDO_DISABLED error code, 358
ER_IB_MSG_UNDO_TRUNCATE_TOO_OFTEN error code, 357	ER_IB_WRN_IGNORE_REDO_LOG_CAPACITY error code, 390
ER_IB_MSG_UNEXPECTED_FILE_EXISTS error code, 265	ER_IB_WRN_OLD_GEOMETRY_TYPE error code, 368
ER_IB_MSG_UNPROTECTED_LOCATION_ALLOWED error code, 268	ER_IB_WRN_PAGE_ARCH_FLUSH_DATA error code, 356
ER_IB_MSG_UPGRADE_PARTITION_FILE error code, 351	ER_IB_WRN_REDO_DISABLED error code, 358
ER_IB_MSG_UPGRADE_PARTITION_FILE_IMPORT error code, 352	ER_IB_WRN_REDO_ENABLED error code, 358
ER_IB_MSG_USING_UNDO_SPACE error code, 333	ER_IB_WRONG_PAGEID_AFTER_SYNC_READ error code, 399
ER_IB_MSG_WAIT_FOR_ENCRYPT_THREAD error code, 329	ER_IB_WRONG_PAGE_ID error code, 399
ER_IB_MSG_WRONG_TABLESPACE_DIR error code, 334	ER_IDENTIFIED_BY_UNSUPPORTED error code, 112
ER_IB_PARALLEL_READER_WORKER_INFO error code, 387	ER_IDENT_CAUSES_TOO_LONG_PATH error code, 55
ER_IB_PRIMARY_KEY_IS_INSTANT error code, 390	ER_IDENT_CAUSES_TOO_LONG_PATH_IN_UPGRADE error code, 348
ER_IB_RDBLWR_BYTES_INFO error code, 379	ER_IF_NOT_EXISTS_UNSUPPORTED_TRG_EXISTS_ON_DI error code, 116
ER_IB_RECV_FIRST_REC_GROUP_INVALID error code, 344	ER_IF_NOT_EXISTS_UNSUPPORTED_UDF_NATIVE_FCT_N error code, 116
ER_IB_RELOCK_LATCH_ORDER_VIOLATION error code, 359	ER_ILLEGAL_GRANT_FOR_TABLE error code, 12
ER_IB_RESURRECT_ACQUIRE_TABLE_LOCK error code, 392	ER_ILLEGAL_HA error code, 5
ER_IB_RESURRECT_IDENTIFY_TABLE_TO_LOCK error code, 392	ER_ILLEGAL_HA_CREATE_OPTION error code, 32
ER_IB_RESURRECT_RECORD_COMPLETE error code, 392	ER_ILLEGAL_PRIVILEGE_LEVEL error code, 80
ER_IB_RESURRECT_RECORD_PROGRESS error code, 392	ER_ILLEGAL_REFERENCE error code, 18
ER_IB_RESURRECT_TRX_INSERT error code, 392	ER_ILLEGAL_USER_VAR error code, 61
ER_IB_RESURRECT_TRX_INSERT_COMPLETE error code, 392	ER_ILLEGAL_VALUE_FOR_TYPE error code, 25
ER_IB_RESURRECT_TRX_UPDATE error code, 392	ER_IMPLICIT_COMPARISON_FOR_JSON error code, 107
ER_IB_RESURRECT_TRX_UPDATE_COMPLETE error code, 392	ER_IMPOSSIBLE_STRING_CONVERSION error code, 107
ER_IB_SELECT_COUNT_STAR error code, 391	ER_IMP_INCOMPATIBLE_CFG_VERSION error code, 104
ER_IB_SYNC_READ_FAILED error code, 399	ER_IMP_INCOMPATIBLE_DD_VERSION error code, 80
ER_IB_TABLESPACE_PATH_VALIDATION_SKIPPED error code, 358	ER_IMP_INCOMPATIBLE_MYSQLD_VERSION error code, 80
	ER_IMP_INCOMPATIBLE_SDI_VERSION error code, 80
	ER_IMP_NO_FILES_MATCHED error code, 80
	ER_IMP_SCHEMA_DOES_NOT_EXIST error code, 80

---

---

ER\_IMP\_TABLE\_ALREADY\_EXISTS error code, 80  
 ER\_INCONSISTENT\_ERROR error code, 324  
 ER\_INCONSISTENT\_PARTITION\_INFO\_ERROR error code, 32  
 ER\_INCONSISTENT\_TYPE\_OF\_FUNCTIONS\_ERROR error code, 32  
 ER\_INCORRECT\_CURRENT\_PASSWORD error code, 100  
 ER\_INCORRECT\_GLOBAL\_LOCAL\_VAR error code, 18  
 ER\_INCORRECT\_TYPE error code, 61  
 ER\_INDEX\_COLUMN\_TOO\_LONG error code, 45  
 ER\_INDEX\_CORRUPT error code, 45  
 ER\_INDEX\_OTHER\_THAN\_PK error code, 118  
 ER\_INDEX\_TYPE\_NOT\_SUPPORTED\_FOR\_SPATIAL\_INDEX error code, 88  
 ER\_INFORMATION\_SCHEMA\_VERSION\_CHANGE error code, 395  
 ER\_INIT\_BOOTSTRAP\_COMPLETE error code, 159  
 ER\_INIT\_CANT\_OPEN\_BOOTSTRAP\_FILE error code, 159  
 ER\_INIT\_CREATING\_DD error code, 159  
 ER\_INIT\_DATADIR\_EXISTS\_AND\_NOT\_WRITABLE\_WONT\_INITIALIZE error code, 159  
 ER\_INIT\_DATADIR\_EXISTS\_AND\_PATH\_TOO\_LONG\_WONT\_INITIALIZE error code, 159  
 ER\_INIT\_DATADIR\_EXISTS\_WONT\_INITIALIZE error code, 159  
 ER\_INIT\_DATADIR\_NOT\_EMPTY\_WONT\_INITIALIZE error code, 159  
 ER\_INIT\_FAILED\_TO\_GENERATE\_ROOT\_PASSWORD error code, 350  
 ER\_INIT\_GENERATING\_TEMP\_PASSWORD\_FOR\_ROOT error code, 159  
 ER\_INIT\_ROOT\_WITHOUT\_PASSWORD error code, 158  
 ER\_INNOBDB\_ACTIVE\_INDEX\_CHANGE\_FAILED error code, 190  
 ER\_INNOBDB\_AUTOEXTEND\_SIZE\_OUT\_OF\_RANGE error code, 110  
 ER\_INNOBDB\_CANNOT\_CREATE\_TABLE error code, 191  
 ER\_INNOBDB\_CANT\_BUILD\_INDEX\_XLATION\_TABLE\_FOR error code, 179  
 ER\_INNOBDB\_CANT\_FIND\_INDEX\_IN\_INNOBDB\_DD error code, 179  
 ER\_INNOBDB\_CLOSING\_CONNECTION\_ROLLS\_BACK error code, 179  
 ER\_INNOBDB\_CLUSTERED\_INDEX\_PRIVATE error code, 179  
 ER\_INNOBDB\_COMPRESSION\_FAILURE error code, 111  
 ER\_INNOBDB\_DIFF\_IN\_REF\_LEN error code, 190  
 ER\_INNOBDB\_DIRTY\_WATER\_MARK\_NOT\_LOW error code, 178  
 ER\_INNOBDB\_ERROR\_LOGGER\_FATAL\_MSG error code, 192  
 ER\_INNOBDB\_ERROR\_LOGGER\_MSG error code, 192  
 ER\_INNOBDB\_FAILED\_TO\_FIND\_IDX error code, 190  
 ER\_INNOBDB\_FAILED\_TO\_FIND\_IDX\_FROM\_DICT\_CACHE error code, 190  
 ER\_INNOBDB\_FAILED\_TO\_FIND\_IDX\_WITH\_KEY\_NO error code, 190  
 ER\_INNOBDB\_FILES\_SAME error code, 178  
 ER\_INNOBDB\_FORCED\_RECOVERY error code, 56  
 ER\_INNOBDB\_FT\_AUX\_NOT\_HEX\_ID error code, 56  
 ER\_INNOBDB\_FT\_LIMIT error code, 51  
 ER\_INNOBDB\_FT\_WRONG\_DOCID\_COLUMN error code, 51  
 ER\_INNOBDB\_FT\_WRONG\_DOCID\_INDEX error code, 51  
 ER\_INNOBDB\_IDX\_CNT\_FEWER\_THAN\_DEFINED\_IN\_MYSQL error code, 191  
 ER\_INNOBDB\_IDX\_CNT\_MORE\_THAN\_DEFINED\_IN\_MYSQL error code, 191  
 ER\_INNOBDB\_IDX\_COLUMN\_CNT\_DIFF error code, 191  
 ER\_INNOBDB\_ILLEGAL\_COLON\_IN\_POOL error code, 178  
 ER\_INNOBDB\_IMPORT\_DROP\_COL\_METADATA\_MISMATCH error code, 122  
 ER\_INNOBDB\_IMPORT\_ENUM\_NULL\_TERMINATOR\_MISSING error code, 122  
 ER\_INNOBDB\_IMPORT\_ERROR error code, 52  
 ER\_INNOBDB\_IMPORT\_WRONG\_DROPPED\_ENUM\_LENGTH error code, 122  
 ER\_INNOBDB\_IMPORT\_WRONG\_NUMBER\_OF\_INDEXES\_TOO\_FEW error code, 122  
 ER\_INNOBDB\_IMPORT\_WRONG\_NUMBER\_OF\_INDEXES\_ZERO error code, 122  
 ER\_INNOBDB\_INCOMPATIBLE\_WITH\_TABLESPACE error code, 110  
 ER\_INNOBDB\_INDEX\_COLUMN\_INFO\_UNLIKE\_MYSQLS error code, 179  
 ER\_INNOBDB\_INDEX\_CORRUPT error code, 52  
 ER\_INNOBDB\_INSTANT\_ADD\_DROP\_NOT\_SUPPORTED\_MAX\_SIZE error code, 120  
 ER\_INNOBDB\_INSTANT\_ADD\_NOT\_SUPPORTED\_MAX\_FIELDS error code, 121  
 ER\_INNOBDB\_INTERNAL\_INDEX error code, 191  
 ER\_INNOBDB\_INVALID\_AUTOEXTEND\_SIZE\_VALUE error code, 110  
 ER\_INNOBDB\_INVALID\_INNOBDB\_UNDO\_DIRECTORY error code, 178  
 ER\_INNOBDB\_INVALID\_INNOBDB\_UNDO\_DIRECTORY\_LOCATION error code, 335  
 ER\_INNOBDB\_INVALID\_LOG\_GROUP\_HOME\_DIR error code, 178  
 ER\_INNOBDB\_INVALID\_MONITOR\_COUNTER\_NAME error code, 191  
 ER\_INNOBDB\_INVALID\_PAGE\_SIZE error code, 178  
 ER\_INNOBDB\_IO\_CAPACITY\_EXCEEDS\_MAX error code, 178

---

ER\_INNODB\_IO\_WRITE\_ERROR\_RETRYING error code, 363  
 ER\_INNODB\_IO\_WRITE\_FAILED error code, 363  
 ER\_INNODB\_MANDATORY error code, 134  
 ER\_INNODB\_MAX\_ROW\_VERSION error code, 116  
 ER\_INNODB\_MONITOR\_DEFAULT\_VALUE\_NOT\_DEFINED error code, 191  
 ER\_INNODB\_MONITOR\_IS\_ENABLED error code, 191  
 ER\_INNODB\_NO\_FT\_TEMP\_TABLE error code, 51  
 ER\_INNODB\_ONLINE\_LOG\_TOO\_BIG error code, 51  
 ER\_INNODB\_OUT\_OF\_RESOURCES error code, 353  
 ER\_INNODB\_PK\_NOT\_IN\_MYSQL error code, 179  
 ER\_INNODB\_PK\_ONLY\_IN\_MYSQL error code, 179  
 ER\_INNODB\_READ\_ONLY error code, 56  
 ER\_INNODB\_REDO\_ARCHIVING\_ENABLED error code, 107  
 ER\_INNODB\_REDO\_DISABLED error code, 107  
 ER\_INNODB\_REDO\_LOG\_ARCHIVE\_ACTIVE error code, 97  
 ER\_INNODB\_REDO\_LOG\_ARCHIVE\_DIRS\_INVALID error code, 96  
 ER\_INNODB\_REDO\_LOG\_ARCHIVE\_DIR\_CLASH error code, 97  
 ER\_INNODB\_REDO\_LOG\_ARCHIVE\_DIR\_EMPTY error code, 96  
 ER\_INNODB\_REDO\_LOG\_ARCHIVE\_DIR\_PERMISSIONS error code, 97  
 ER\_INNODB\_REDO\_LOG\_ARCHIVE\_FAILED error code, 97  
 ER\_INNODB\_REDO\_LOG\_ARCHIVE\_FILE\_CREATE error code, 97  
 ER\_INNODB\_REDO\_LOG\_ARCHIVE\_INACTIVE error code, 97  
 ER\_INNODB\_REDO\_LOG\_ARCHIVE\_LABEL\_NOT\_FOUND error code, 96  
 ER\_INNODB\_REDO\_LOG\_ARCHIVE\_NO\_SUCH\_DIR error code, 96  
 ER\_INNODB\_REDO\_LOG\_ARCHIVE\_SESSION error code, 97  
 ER\_INNODB\_REDO\_LOG\_ARCHIVE\_START\_SUBDIR\_ERROR error code, 96  
 ER\_INNODB\_REDO\_LOG\_ARCHIVE\_START\_TIMEOUT error code, 96  
 ER\_INNODB\_TRX\_XLATION\_TABLE\_OOM error code, 179  
 ER\_INNODB\_UNABLE\_TO\_ACQUIRE\_DD\_OBJECT error code, 356  
 ER\_INNODB\_UNDO\_LOG\_FULL error code, 58  
 ER\_INNODB\_UNKNOWN\_COLLATION error code, 178  
 ER\_INNODB\_UNREGISTERED\_TRX\_ACTIVE error code, 178  
 ER\_INNODB\_USE\_MONITOR\_GROUP\_NAME error code, 191  
 ER\_INSECURE\_CHANGE\_SOURCE error code, 48  
 ER\_INSECURE\_PLAIN\_TEXT error code, 48  
 ER\_INSERT\_INFO error code, 9  
 ER\_INSIDE\_TRANSACTION\_PREVENTS\_SWITCH\_BINLOG error code, 43  
 ER\_INSIDE\_TRANSACTION\_PREVENTS\_SWITCH\_BINLOG error code, 43  
 ER\_INSIDE\_TRANSACTION\_PREVENTS\_SWITCH\_SQL\_LOG error code, 44  
 ER\_INSTALL\_COMPONENT\_SET\_NULL\_VALUE error code, 121  
 ER\_INSTALL\_COMPONENT\_SET\_UNUSED\_VALUE error code, 121  
 ER\_INSTALL\_PLUGIN\_CONFLICT\_CLIENT error code, 112  
 ER\_INSTALL\_PLUGIN\_CONFLICT\_LOG error code, 371  
 ER\_INTERNAL\_ERROR error code, 52  
 ER\_INTERSECT\_ALL\_MAX\_DUPLICATES\_EXCEEDED error code, 118  
 ER\_INVALID\_ADMIN\_ADDRESS error code, 336  
 ER\_INVALID\_ARGUMENT\_FOR\_LOGARITHM error code, 58  
 ER\_INVALID\_ASSIGNMENT\_TARGET error code, 112  
 ER\_INVALID\_AUTHENTICATION\_POLICY error code, 374  
 ER\_INVALID\_BITWISE\_AGGREGATE\_OPERANDS\_SIZE error code, 73  
 ER\_INVALID\_BITWISE\_OPERANDS\_SIZE error code, 73  
 ER\_INVALID\_CAST error code, 108  
 ER\_INVALID\_CAST\_POLYGON\_RING\_DIRECTION error code, 111  
 ER\_INVALID\_CAST\_TO\_GEOMETRY error code, 111  
 ER\_INVALID\_CAST\_TO\_JSON error code, 68  
 ER\_INVALID\_CHARACTER\_STRING error code, 21  
 ER\_INVALID\_CHARSET\_AND\_DEFAULT\_IS\_MB error code, 151  
 ER\_INVALID\_COLLATION\_FOR\_CHARSET error code, 182  
 ER\_INVALID\_DD\_OBJECT error code, 73  
 ER\_INVALID\_DD\_OBJECT\_ID error code, 73  
 ER\_INVALID\_DD\_OBJECT\_NAME error code, 73  
 ER\_INVALID\_DEFAULT error code, 7  
 ER\_INVALID\_DEFAULT\_UTF8MB4\_COLLATION error code, 87  
 ER\_INVALID\_ENCRYPTION\_OPTION error code, 70  
 ER\_INVALID\_ENCRYPTION\_REQUEST error code, 95  
 ER\_INVALID\_ERROR\_LOG\_NAME error code, 141  
 ER\_INVALID\_FIELD\_SIZE error code, 58  
 ER\_INVALID\_GEOJSON\_CRS\_NOT\_TOP\_LEVEL error code, 84  
 ER\_INVALID\_GEOJSON\_MISSING\_MEMBER error code, 62  
 ER\_INVALID\_GEOJSON\_UNSPECIFIED error code, 62  
 ER\_INVALID\_GEOJSON\_WRONG\_TYPE error code, 62  
 ER\_INVALID\_GROUP\_FUNC\_USE error code, 10

---

---

ER\_INVALID\_INFO\_IN\_FRM error code, 152  
 ER\_INVALID\_INSTRUMENT error code, 134  
 ER\_INVALID\_JSON\_ATTRIBUTE error code, 107  
 ER\_INVALID\_JSON\_BINARY\_DATA error code, 67  
 ER\_INVALID\_JSON\_CHARSET error code, 68  
 ER\_INVALID\_JSON\_CHARSET\_IN\_FUNCTION error code, 68  
 ER\_INVALID\_JSON\_DATA error code, 62  
 ER\_INVALID\_JSON\_PATH error code, 68  
 ER\_INVALID\_JSON\_PATH\_ARRAY\_CELL error code, 69  
 ER\_INVALID\_JSON\_PATH\_CHARSET error code, 68  
 ER\_INVALID\_JSON\_PATH\_WILDCARD error code, 68  
 ER\_INVALID\_JSON\_TEXT error code, 67  
 ER\_INVALID\_JSON\_TEXT\_IN\_PARAM error code, 67  
 ER\_INVALID\_JSON\_TYPE error code, 97  
 ER\_INVALID\_JSON\_VALUE\_FOR\_CAST error code, 68  
 ER\_INVALID\_JSON\_VALUE\_FOR\_FUNC\_INDEX error code, 100  
 ER\_INVALID\_MFA\_OPERATIONS\_FOR\_PASSWORDLESS\_USER error code, 113  
 ER\_INVALID\_MFA\_PLUGIN\_SPECIFIED error code, 112  
 ER\_INVALID\_MULTIPLE\_CLAUSES error code, 96  
 ER\_INVALID\_NAMED\_PIPE\_FULL\_ACCESS\_GROUP error code, 341  
 ER\_INVALID\_NO\_OF\_ARGS error code, 79  
 ER\_INVALID\_ON\_UPDATE error code, 21  
 ER\_INVALID\_OPTION\_CHARACTERS error code, 76  
 ER\_INVALID\_OPTION\_END\_CHARACTER error code, 76  
 ER\_INVALID\_OPTION\_KEY error code, 76  
 ER\_INVALID\_OPTION\_KEY\_VALUE\_PAIR error code, 76  
 ER\_INVALID\_OPTION\_START\_CHARACTER error code, 76  
 ER\_INVALID\_OPTION\_VALUE error code, 76  
 ER\_INVALID\_OR\_OLD\_TABLE\_OR\_DB\_NAME error code, 160  
 ER\_INVALID\_PARAMETER\_USE error code, 108  
 ER\_INVALID\_PLUGIN\_FOR\_REGISTRATION error code, 113  
 ER\_INVALID\_PROPERTY\_KEY error code, 338  
 ER\_INVALID\_RPL\_WILD\_TABLE\_FILTER\_PATTERN error code, 62  
 ER\_INVALID\_SERVER\_DOWNGRADE\_NOT\_PATCH error code, 395  
 ER\_INVALID\_SERVER\_UPGRADE\_NOT\_LTS error code, 395  
 ER\_INVALID\_THREAD\_ID error code, 83  
 ER\_INVALID\_THREAD\_PRIORITY error code, 83  
 ER\_INVALID\_TIME\_ZONE\_INTERVAL error code, 108  
 ER\_INVALID\_TLS\_VERSION error code, 377  
 ER\_INVALID\_TYPE\_FOR\_JSON error code, 68  
 ER\_INVALID\_USER\_ATTRIBUTE\_JSON error code, 107  
 ER\_INVALID\_USER\_FOR\_REGISTRATION error code, 113  
 ER\_INVALID\_USE\_OF\_FORCE\_OPTION error code, 83  
 ER\_INVALID\_USE\_OF\_NULL error code, 12  
 ER\_INVALID\_VALUE\_FOR\_ENFORCE\_GTID\_CONSISTENCY error code, 130  
 ER\_INVALID\_VALUE\_OF\_BIND\_ADDRESSES error code, 330  
 ER\_INVALID\_VCPU\_ID error code, 82  
 ER\_INVALID\_VCPU\_RANGE error code, 83  
 ER\_INVALID\_XPLUGIN\_SOCKET\_SAME\_AS\_SERVER error code, 356  
 ER\_INVALID\_YEAR\_COLUMN\_LENGTH error code, 52  
 ER\_IO\_ERR\_LOG\_INDEX\_READ error code, 26  
 ER\_IO\_READ\_ERROR error code, 52  
 ER\_IO\_WRITE\_ERROR error code, 52  
 ER\_IPSOCK\_ERROR error code, 8  
 ER\_IS\_QUERY\_INVALID\_CLAUSE error code, 76  
 ER\_I\_S\_SKIPPED\_TABLESPACE error code, 82  
 ER\_JSON\_BAD\_ONE\_OR\_ALL\_ARG error code, 68  
 ER\_JSON\_DOCUMENT\_NULL\_KEY error code, 69  
 ER\_JSON\_DOCUMENT\_TOO\_DEEP error code, 68  
 ER\_JSON\_KEY\_TOO\_BIG error code, 68  
 ER\_JSON\_PARSE\_ERROR error code, 142  
 ER\_JSON\_SCHEMA\_VALIDATION\_ERROR\_WITH\_DETAILED\_REASON error code, 103  
 ER\_JSON\_USED\_AS\_KEY error code, 68  
 ER\_JSON\_VACUOUS\_PATH error code, 68  
 ER\_JSON\_VALUE\_OUT\_OF\_RANGE\_FOR\_FUNC\_INDEX error code, 101  
 ER\_JSON\_VALUE\_TOO\_BIG error code, 68  
 ER\_JT\_MAX\_NESTED\_PATH error code, 84  
 ER\_JT\_VALUE\_OUT\_OF\_RANGE error code, 84  
 ER\_KERBEROS\_CREATE\_USER error code, 112  
 ER\_KEYCACHE\_OOM error code, 136  
 ER\_KEYRING\_ACCESS\_DENIED\_ERROR error code, 72  
 ER\_KEYRING\_AWS\_CMK\_ID\_NOT\_SET error code, 217  
 ER\_KEYRING\_AWS\_FAILED\_TO\_ACCESS\_DATA\_FILE error code, 217  
 ER\_KEYRING\_AWS\_FAILED\_TO\_ACCESS\_KEY\_FROM\_CONFIGURATION error code, 216  
 ER\_KEYRING\_AWS\_FAILED\_TO\_ACCESS\_KEY\_ID\_FROM\_CONFIGURATION error code, 216  
 ER\_KEYRING\_AWS\_FAILED\_TO\_ACCESS\_OR\_CREATE\_KEYRING error code, 217  
 ER\_KEYRING\_AWS\_FAILED\_TO\_ACCESS\_OR\_CREATE\_KEYRING error code, 216  
 ER\_KEYRING\_AWS\_FAILED\_TO\_CONNECT\_KMS error code, 218  
 ER\_KEYRING\_AWS\_FAILED\_TO\_DECRYPT\_KEY error code, 218  
 ER\_KEYRING\_AWS\_FAILED\_TO\_ENCRYPT\_KEY error code, 218



---

ER_KEYRING_AWS_FAILED_TO_FLUSH_KEYRING_TO_FILE error code, 218	ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_FLUSH_KEYRING error code, 215
ER_KEYRING_AWS_FAILED_TO_GENERATE_KEY_DUETO_CREDENTIAL_ERROR error code, 217	ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_RESTORE_KEYRING error code, 215
ER_KEYRING_AWS_FAILED_TO_GENERATE_NEW_KEY error code, 218	ER_KEYRING_ENCRYPTED_FILE_FOUND_MALFORMED_BACKUP_FILE error code, 215
ER_KEYRING_AWS_FAILED_TO_GET_KMS_CREDENTIALS error code, 217	ER_KEYRING_ENCRYPTED_FILE_GEN_KEY_FAILED_DUE_TO_INVALID_KEY error code, 216
ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_INTERNAL_ERROR error code, 217	ER_KEYRING_ENCRYPTED_FILE_INCORRECT_KEYRING_PATH error code, 215
ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_PLUGIN_ERROR error code, 217	ER_KEYRING_ENCRYPTED_FILE_INIT_FAILED_DUE_TO_INVALID_KEYRING error code, 216
ER_KEYRING_AWS_FAILED_TO_OPEN_CONF_FILE error code, 216	ER_KEYRING_ENCRYPTED_FILE_INIT_FAILURE error code, 216
ER_KEYRING_AWS_FAILED_TO_RESTORE_FROM_BACKUP_FILE error code, 217	ER_KEYRING_ENCRYPTED_FILE_INVALID_KEYRING_DIRECTORY error code, 215
ER_KEYRING_AWS_FAILED_TO_RE_ENCRYPT_KEY error code, 218	ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_INVALID error code, 215
ER_KEYRING_AWS_FAILED_TO_ROTATE_CMK error code, 218	ER_KEYRING_ENCRYPTED_FILE_PASSWORD_IS_TOO_LONG error code, 215
ER_KEYRING_AWS_FAILED_TO_SET_CMK_ID error code, 216	ER_KEYRING_FAILED_TO_CREATE_KEYRING_DIRECTORY error code, 211
ER_KEYRING_AWS_FAILED_TO_SET_REGION error code, 216	ER_KEYRING_FAILED_TO_FLUSH_KEYRING_TO_FILE error code, 212
ER_KEYRING_AWS_FOUND_MALFORMED_BACKUP_FILE error code, 217	ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING_DIRECTORY error code, 212
ER_KEYRING_AWS_INCORRECT_FILE error code, 217	ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING_DIRECTORY error code, 212
ER_KEYRING_AWS_INCORRECT_PROXY error code, 349	ER_KEYRING_FAILED_TO_GENERATE_KEY error code, 211
ER_KEYRING_AWS_INCORRECT_REGION error code, 218	ER_KEYRING_FAILED_TO_GET_FILE_STAT error code, 212
ER_KEYRING_AWS_INIT_FAILURE error code, 217	ER_KEYRING_FAILED_TO_LOAD_KEYRING_CONTENT error code, 212
ER_KEYRING_AWS_INVALID_CONF_FILE_PATH error code, 216	ER_KEYRING_FAILED_TO_REMOVE_FILE error code, 212
ER_KEYRING_AWS_INVALID_DATA_FILE_PATH error code, 216	ER_KEYRING_FAILED_TO_REMOVE_KEY_DUE_TO_EMPTY_KEYRING error code, 212
ER_KEYRING_AWS_INVALID_KEY_LENGTH_FOR_CIPHER error code, 217	ER_KEYRING_FAILED_TO_RESTORE_FROM_BACKUP_FILE error code, 212
ER_KEYRING_AWS_UDF_AWS_KMS_ERROR error code, 71	ER_KEYRING_FAILED_TO_SET_KEYRING_FILE_DATA error code, 212
ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_EMPTY_KEYRING error code, 211	ER_KEYRING_FAILED_TO_TRUNCATE_FILE error code, 212
ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_INVALID_KEY error code, 211	ER_KEYRING_FILE_INIT_FAILED error code, 211
ER_KEYRING_COMPONENT_EXCEPTION error code, 366	ER_KEYRING_FILE_IO_ERROR error code, 212
ER_KEYRING_COMPONENT_MEMORY_ALLOCATION_ERROR error code, 367	ER_KEYRING_FOUND_MALFORMED_BACKUP_FILE error code, 211
ER_KEYRING_COMPONENT_NOT_INITIALIZED error code, 366	ER_KEYRING_INCORRECT_FILE error code, 211
ER_KEYRING_ENCRYPTED_FILE_DECRYPTION_FAILURE error code, 215	ER_KEYRING_INTERNAL_EXCEPTION_FAILED_FILE_INIT error code, 211
ER_KEYRING_ENCRYPTED_FILE_ENCRYPTION_FAILURE error code, 215	ER_KEYRING_INVALID_KEY_LENGTH error code, 211
ER_KEYRING_ENCRYPTED_FILE_FAILED_TO_CREATE_KEYRING_DIRECTORY error code, 215	ER_KEYRING_INVALID_KEY_TYPE error code, 211
	ER_KEYRING_KEY_FETCH_FAILED_DUE_TO_EMPTY_KEYRING error code, 211
	ER_KEYRING_LOGGER_ERROR_MSG error code, 201

---

---

ER\_KEYRING\_MIGRATE\_FAILED error code, 323  
 ER\_KEYRING\_MIGRATION\_EXTRA\_OPTIONS error code, 247  
 ER\_KEYRING\_MIGRATION\_FAILED error code, 193  
 ER\_KEYRING\_MIGRATION\_FAILURE error code, 71  
 ER\_KEYRING\_MIGRATION\_STATUS error code, 72  
 ER\_KEYRING\_MIGRATION\_SUCCESSFUL error code, 193  
 ER\_KEYRING\_OCI\_HTTP\_REQUEST error code, 386  
 ER\_KEYRING\_OCI\_INVALID\_JSON error code, 386  
 ER\_KEYRING\_OCI\_PARSE\_JSON error code, 386  
 ER\_KEYRING\_OKV\_CONNECTION\_TO\_SERVER\_FAILED error code, 214  
 ER\_KEYRING\_OKV\_FAILED\_TO\_ACTIVATE\_KEYS error code, 214  
 ER\_KEYRING\_OKV\_FAILED\_TO\_ADD\_ATTRIBUTE error code, 214  
 ER\_KEYRING\_OKV\_FAILED\_TO\_FETCH\_KEY error code, 214  
 ER\_KEYRING\_OKV\_FAILED\_TO\_FIND\_SERVER\_ENTRY error code, 213  
 ER\_KEYRING\_OKV\_FAILED\_TO\_FIND\_STANDBY\_SERVER error code, 213  
 ER\_KEYRING\_OKV\_FAILED\_TO\_GENERATE\_KEY error code, 214  
 ER\_KEYRING\_OKV\_FAILED\_TO\_GENERATE\_KEY\_DUPLICATE error code, 213  
 ER\_KEYRING\_OKV\_FAILED\_TO\_INIT\_CLIENT error code, 213  
 ER\_KEYRING\_OKV\_FAILED\_TO\_INIT\_SSL\_LAYER error code, 213  
 ER\_KEYRING\_OKV\_FAILED\_TO\_LOAD\_KEY\_UID error code, 213  
 ER\_KEYRING\_OKV\_FAILED\_TO\_LOAD\_SSL\_TRUST\_STORE error code, 214  
 ER\_KEYRING\_OKV\_FAILED\_TO\_PARSE\_CONF\_FILE error code, 213  
 ER\_KEYRING\_OKV\_FAILED\_TO\_REMOVE\_KEY error code, 214  
 ER\_KEYRING\_OKV\_FAILED\_TO\_RETRIEVE\_KEY error code, 214  
 ER\_KEYRING\_OKV\_FAILED\_TO\_RETRIEVE\_KEY\_SIGNATURE error code, 214  
 ER\_KEYRING\_OKV\_FAILED\_TO\_SET\_CERTIFICATE\_FILE error code, 214  
 ER\_KEYRING\_OKV\_FAILED\_TO\_SET\_KEY\_FILE error code, 214  
 ER\_KEYRING\_OKV\_FAILED\_TO\_STORE\_KEY error code, 214  
 ER\_KEYRING\_OKV\_FAILED\_TO\_STORE\_OR\_GENERATE\_KEY error code, 214  
 ER\_KEYRING\_OKV\_INCORRECT\_KEY\_VAULT\_CONFIGURATION error code, 213  
 ER\_KEYRING\_OKV\_INIT\_FAILED\_DUE\_TO\_INCORRECT\_CONFIG error code, 213  
 ER\_KEYRING\_OKV\_INIT\_FAILED\_DUE\_TO\_INTERNAL\_ERROR error code, 213  
 ER\_KEYRING\_OKV\_INVALID\_KEY\_LENGTH\_FOR\_CIPHER error code, 213  
 ER\_KEYRING\_OKV\_INVALID\_KEY\_TYPE error code, 213  
 ER\_KEYRING\_OKV\_KEY\_MISMATCH error code, 215  
 ER\_KEYRING\_OKV\_STANDBY\_SERVER\_COUNT\_EXCEEDED error code, 377  
 ER\_KEYRING\_OPERATION\_FAILED\_DUE\_TO\_INTERNAL\_ERROR error code, 211  
 ER\_KEYRING\_UDF\_KEYRING\_SERVICE\_ERROR error code, 71  
 ER\_KEYRING\_UNKNOWN\_ERROR error code, 212  
 ER\_KEY\_COLUMN\_DOES\_NOT\_EXISTS error code, 8  
 ER\_KEY\_DOES\_NOT\_EXISTS error code, 14  
 ER\_KEY\_NOT\_FOUND error code, 5  
 ER\_KEY\_PART\_0 error code, 26  
 ER\_KEY\_REF\_DO\_NOT\_MATCH\_TABLE\_REF error code, 18  
 ER\_KILLED\_THREADS\_OF\_PLUGIN error code, 160  
 ER\_KILLING\_THREAD error code, 159  
 ER\_KILL\_DENIED\_ERROR error code, 9  
 ER\_LANGUAGE\_COMPONENT error code, 121  
 ER\_LANGUAGE\_COMPONENT\_CANNOT\_UNINSTALL error code, 121  
 ER\_LANGUAGE\_COMPONENT\_ERROR error code, 121  
 ER\_LANGUAGE\_COMPONENT\_ERROR\_DUE\_TO\_INTERNAL\_ERROR error code, 396  
 ER\_LANGUAGE\_COMPONENT\_INFO error code, 396  
 ER\_LANGUAGE\_COMPONENT\_NOT\_AVAILABLE error code, 121  
 ER\_LANGUAGE\_COMPONENT\_UNSUPPORTED\_LANGUAGE error code, 121  
 ER\_LANGUAGE\_COMPONENT\_WARNING error code, 396  
 ER\_LATITUDE\_OUT\_OF\_RANGE error code, 80  
 ER\_LCTN\_CHANGED error code, 193  
 ER\_LCTN\_NOT\_FOUND error code, 323  
 ER\_LDAP\_AUTH\_CERTIFICATE\_NAME error code, 243  
 ER\_LDAP\_AUTH\_COMMUNICATION\_HOST\_INFO error code, 245  
 ER\_LDAP\_AUTH\_CONNECTION\_CREATOR\_ENTERED error code, 244  
 ER\_LDAP\_AUTH\_CONNECTION\_GET\_LDAP\_INFO\_NULL error code, 245  
 ER\_LDAP\_AUTH\_CONNECTION\_POOL\_INIT\_FAILED error code, 244  
 ER\_LDAP\_AUTH\_CONNECTION\_POOL\_REINIT\_ENTERED error code, 246  
 ER\_LDAP\_AUTH\_CONNECTION\_PUSHED\_TO\_POOL error code, 244  
 ER\_LDAP\_AUTH\_CONN\_POOL\_DEINITIALIZING error code, 242  
 ER\_LDAP\_AUTH\_CONN\_POOL\_INITIALIZING error code, 242  
 ER\_LDAP\_AUTH\_CONN\_POOL\_NOT\_CREATED error code, 242  
 ER\_LDAP\_AUTH\_CREATE\_CONNECTION\_KEY error code, 245

---

ER_LDAP_AUTH_CREATING_LDAP_CONNECTION error code, 244	ER_LDAP_AUTH_LDAPS error code, 339
ER_LDAP_AUTH_DEINIT_FAILED error code, 241	ER_LDAP_AUTH_LDAP_INFO_NULL error code, 244
ER_LDAP_AUTH_DELETING_CONNECTION_KEY error code, 245	ER_LDAP_AUTH_MAX_ALLOWED_CONNECTION_LIMIT_HIT error code, 244
ER_LDAP_AUTH_DISTINGUISHED_NAME error code, 245	ER_LDAP_AUTH_MAX_POOL_SIZE_SET_FAILED error code, 244
ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_CONNECTION error code, 246	ER_LDAP_AUTH_METHOD_TO_CLIENT error code, 245
ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT error code, 241	ER_LDAP_AUTH_OBJECT_CREATE_TIMESTAMP error code, 243
ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT error code, 241	ER_LDAP_AUTH_OR_GROUP_RETRIEVAL_FAILED error code, 245
ER_LDAP_AUTH_FAILED_TO_CREATE_OR_GET_CONNECTION error code, 241	ER_LDAP_AUTH_PLUGIN_FAILED_TO_READ_PACKET error code, 244
ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_NOT_READY error code, 243	ER_LDAP_AUTH_POOLED_CONNECTION_KEY error code, 245
ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_POOL_IN_ERROR_CODE, 243	ER_LDAP_AUTH_POOL_DISABLE_MAX_SIZE_ZERO error code, 241
ER_LDAP_AUTH_FAILED_TO_ESTABLISH_TLS_CONNECTION error code, 246	ER_LDAP_AUTH_POOL_GET_FAILED_TO_CREATE_CONNECTION error code, 246
ER_LDAP_AUTH_FAILED_TO_GET_CONNECTION_AS_PLUGIN_NOT_READY error code, 243	ER_LDAP_AUTH_POOL_REINITIALIZING error code, 242
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_DENIED_STATE error code, 243	ER_LDAP_AUTH_RETURNING_CONNECTION_TO_POOL error code, 244
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_INIT_CODE, 243	ER_LDAP_AUTH_SASL_BIND_SUCCESS_INFO error code, 245
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_READY_CODE, 243	ER_LDAP_AUTH_SASL_PROCESS_SASL error code, 246
ER_LDAP_AUTH_FAILED_TO_POOL_DEINIT error code, 243	ER_LDAP_AUTH_SASL_REQUEST_FROM_CLIENT error code, 245
ER_LDAP_AUTH_FAILED_TO_SEARCH_DN error code, 246	ER_LDAP_AUTH_SEARCHED_USER_GRP_NAME error code, 243
ER_LDAP_AUTH_FAILED_TO_WRITE_PACKET error code, 242	ER_LDAP_AUTH_SEARCH_USER_GROUP_ATTR_NOT_FOUND error code, 244
ER_LDAP_AUTH_FREEING_CONNECTION error code, 244	ER_LDAP_AUTH_SETTING_USERNAME error code, 242
ER_LDAP_AUTH_GETTING_CONNECTION_FROM_POOL error code, 244	ER_LDAP_AUTH_SKIPPING_USER_GROUP_SEARCH error code, 241
ER_LDAP_AUTH_GRP_DN_PARSING_FAILED error code, 339	ER_LDAP_AUTH_STARTED_FOR_USER error code, 245
ER_LDAP_AUTH_GRP_INCORRECT_ATTRIBUTE error code, 339	ER_LDAP_AUTH_STARTING_TLS error code, 244
ER_LDAP_AUTH_GRP_INFO_FOUND_IN_MANY_OBJECTS error code, 339	ER_LDAP_AUTH_TLS_CONF error code, 241
ER_LDAP_AUTH_GRP_IS_FULL_DN error code, 242	ER_LDAP_AUTH_TLS_CONNECTION error code, 242
ER_LDAP_AUTH_GRP_NULL_ATTRIBUTE_VALUE error code, 339	ER_LDAP_AUTH_USER_AUTH_DATA error code, 242
ER_LDAP_AUTH_GRP_OBJECT_HAS_USER_INFO error code, 339	ER_LDAP_AUTH_USER_BIND_FAILED error code, 246
ER_LDAP_AUTH_GRP_SEARCH_NOT_SPECIAL_HDL error code, 339	ER_LDAP_AUTH_USER_FOUND_IN_MANY_GRPS error code, 243
ER_LDAP_AUTH_GRP_SEARCH_SPECIAL_HDL error code, 242	ER_LDAP_AUTH_USER_GROUP_SEARCH_FAILED error code, 245
ER_LDAP_AUTH_GRP_USER_OBJECT_HAS_GROUP_INFO error code, 339	ER_LDAP_AUTH_USER_GROUP_SEARCH_INFO error code, 242
ER_LDAP_AUTH_INFO_FOR_USER error code, 242	ER_LDAP_AUTH_USER_GROUP_SEARCH_ROOT_BIND error code, 332
ER_LDAP_AUTH_INIT_FAILED error code, 245	ER_LDAP_AUTH_USER_HAS_MULTIPLE_GRP_NAMES error code, 243

---

---

ER\_LDAP\_AUTH\_USER\_NOT\_FOUND\_IN\_ANY\_GRP error code, 242  
 ER\_LDAP\_AUTH\_ZERO\_MAX\_POOL\_SIZE\_UNCHANGED error code, 242  
 ER\_LDAP\_EMPTY\_USERDN\_PASSWORD error code, 346  
 ER\_LDAP\_MAPPING\_CHECK\_DELIMI\_QUOTE error code, 340  
 ER\_LDAP\_MAPPING\_EMPTY\_MAPPING error code, 340  
 ER\_LDAP\_MAPPING\_GETTING\_NEXT\_MAPPING error code, 340  
 ER\_LDAP\_MAPPING\_GET\_USER\_PROXY error code, 340  
 ER\_LDAP\_MAPPING\_INFO error code, 340  
 ER\_LDAP\_MAPPING\_IS\_QUOTE error code, 341  
 ER\_LDAP\_MAPPING\_NON\_DESIRED\_STATE error code, 341  
 ER\_LDAP\_MAPPING\_NO\_SEPEARATOR\_END\_OF\_GROUP error code, 340  
 ER\_LDAP\_MAPPING\_PARSING\_CURRENT\_STATE error code, 340  
 ER\_LDAP\_MAPPING\_PARSING\_ERROR error code, 341  
 ER\_LDAP\_MAPPING\_PARSING\_MAPPING\_INFO error code, 341  
 ER\_LDAP\_MAPPING\_PROCESS\_DELIMITER error code, 340  
 ER\_LDAP\_MAPPING\_PROCESS\_DELIMITER\_COMMA\_NOT\_FOUND error code, 340  
 ER\_LDAP\_MAPPING\_PROCESS\_DELIMITER\_EQUAL\_NOT\_FOUND error code, 340  
 ER\_LDAP\_MAPPING\_PROCESS\_DELIMITER\_TRY\_COMMA error code, 340  
 ER\_LDAP\_MAPPING\_PROCESS\_MAPPING error code, 340  
 ER\_LDAP\_MAPPING\_TRIMMING\_SPACES error code, 341  
 ER\_LDAP\_MAPPING\_USER\_DONT\_BELONG\_GROUP error code, 340  
 ER\_LH\_AVRO\_CANNOT\_PARSE\_HEADER error code, 128  
 ER\_LH\_AVRO\_DECODING\_ERR error code, 127  
 ER\_LH\_AVRO\_ENUM\_CANNOT\_CONVERT\_CHARSET error code, 126  
 ER\_LH\_AVRO\_ENUM\_MISMATCH error code, 126  
 ER\_LH\_AVRO\_FILE\_DATA\_CORRUPT error code, 126  
 ER\_LH\_AVRO\_FILE\_ENDS\_UNEXPECTEDLY error code, 126  
 ER\_LH\_AVRO\_HEADER\_METADATA\_ERR error code, 127  
 ER\_LH\_AVRO\_HEADER\_MISMATCH error code, 126  
 ER\_LH\_AVRO\_HEADER\_NO\_SCHEMA error code, 127  
 ER\_LH\_AVRO\_INVALID\_BLOCK\_RECORD\_COUNT error code, 127  
 ER\_LH\_AVRO\_INVALID\_BLOCK\_SIZE error code, 127  
 ER\_LH\_AVRO\_INVALID\_NAME\_IN\_SCHEMA error code, 127  
 ER\_LH\_AVRO\_INVALID\_UNION error code, 127  
 ER\_LH\_AVRO\_NO\_CODEEC\_IN\_HEADER error code, 127  
 ER\_LH\_AVRO\_SCHEMA\_DEPTH\_EXCEEDS\_MAX error code, 126  
 ER\_LH\_AVRO\_TYPE\_CANNOT\_CONVERT error code, 126  
 ER\_LH\_AWS\_AUTH\_ERR error code, 125  
 ER\_LH\_BAD\_VALUE error code, 124  
 ER\_LH\_CANNOT\_CONVERT\_STRING error code, 125  
 ER\_LH\_CHARSET\_UNSUPPORTED error code, 126  
 ER\_LH\_COLUMN\_MAX\_ERR error code, 126  
 ER\_LH\_COLUMN\_MISMATCH\_ERR error code, 126  
 ER\_LH\_COL\_IS\_EMPTY error code, 124  
 ER\_LH\_COL\_IS\_EMPTY\_WARN error code, 124  
 ER\_LH\_COL\_NOT\_NULLABLE error code, 124  
 ER\_LH\_CSV\_PARSING\_ERR error code, 125  
 ER\_LH\_DATETIME\_FORMAT error code, 125  
 ER\_LH\_DECIMAL\_OOM\_ERR error code, 125  
 ER\_LH\_DECIMAL\_PRECISION\_EXCEEDS\_SCHEMA error code, 125  
 ER\_LH\_DECIMAL\_UNKNOWN\_ERR error code, 125  
 ER\_LH\_DUPLICATE\_FILE error code, 126  
 ER\_LH\_EMPTY\_FILE error code, 126  
 ER\_LH\_EXCEEDS\_MAX error code, 125  
 ER\_LH\_EXCEEDS\_MIN error code, 125  
 ER\_LH\_FORMAT\_HEADER\_NO\_MAGIC\_BYTES error code, 127  
 ER\_LH\_INFER\_FILE\_HAS\_NO\_DATA error code, 128  
 ER\_LH\_INFER\_NO\_DATA error code, 128  
 ER\_LH\_INFER\_NO\_FILES error code, 128  
 ER\_LH\_INFER\_SCHEMA\_MISMATCH error code, 128  
 ER\_LH\_INFER\_WARN\_GOT\_EXCEPTION error code, 128  
 ER\_LH\_NO\_FILES\_FOUND error code, 126  
 ER\_LH\_OOM error code, 128  
 ER\_LH\_OUT\_OF\_RANGE error code, 125  
 ER\_LH\_PARQUET\_CANNOT\_LOCATE\_OFFSET error code, 127  
 ER\_LH\_PARQUET\_CANNOT\_LOCATE\_SCHEMA error code, 127  
 ER\_LH\_PARQUET\_CANNOT\_READ\_HEADER error code, 128  
 ER\_LH\_PARQUET\_CANT\_OPEN\_FILE error code, 128  
 ER\_LH\_PARQUET\_DECIMAL\_CONVERSION\_ERR error code, 126  
 ER\_LH\_PARQUET\_NON\_UTF8\_FILE\_ENC error code, 127  
 ER\_LH\_PARQUET\_ROW\_GROUP\_SIZE\_EXCEEDS\_MAX error code, 127  
 ER\_LH\_PARQUET\_SCHEMA\_MISMATCH error code, 127

---

ER\_LH\_PARQUET\_TYPE\_CANNOT\_CONVERT error code, 127  
 ER\_LH\_REAL\_IS\_NAN error code, 125  
 ER\_LH\_RESORCE\_PRINCIPAL\_BUCKET\_ERR error code, 126  
 ER\_LH\_RESORCE\_PRINCIPAL\_ERR error code, 125  
 ER\_LH\_STRING\_TOO\_LONG error code, 126  
 ER\_LH\_WARN\_COL\_MISSING\_NOT\_NULLABLE error code, 124  
 ER\_LH\_WARN\_DECIMAL\_ROUNDING error code, 125  
 ER\_LH\_WARN\_EXCEEDS\_MAX\_TRUNCATING error code, 125  
 ER\_LH\_WARN\_EXCEEDS\_MIN\_TRUNCATING error code, 125  
 ER\_LH\_WARN\_INFER\_SKIPPED\_FILES error code, 128  
 ER\_LH\_WARN\_INFER\_SKIPPED\_LINES error code, 128  
 ER\_LH\_WARN\_INFER\_USE\_DEFAULT\_COL\_NAMES error code, 128  
 ER\_LH\_WARN\_TRUNCATED error code, 125  
 ER\_LIMITED\_PART\_RANGE error code, 34  
 ER\_LOAD\_BULK\_DATA\_FAILED error code, 120  
 ER\_LOAD\_BULK\_DATA\_UNSORTED error code, 119  
 ER\_LOAD\_BULK\_DATA\_WARN\_NULL\_TO\_NOTNULL error code, 120  
 ER\_LOAD\_BULK\_DATA\_WARN\_NULL\_TO\_NOTNULL\_LOG error code, 389  
 ER\_LOAD\_BULK\_DATA\_WRONG\_VALUE\_FOR\_FIELD error code, 120  
 ER\_LOAD\_BULK\_DATA\_WRONG\_VALUE\_FOR\_FIELD\_LOG error code, 389  
 ER\_LOAD\_DATA\_INFILE\_FAILED\_IN\_UNEXPECTED\_WARN error code, 143  
 ER\_LOAD\_FROM\_FIXED\_SIZE\_ROWS\_TO\_VAR error code, 27  
 ER\_LOAD\_INFO error code, 8  
 ER\_LOCAL\_VARIABLE error code, 17  
 ER\_LOCKING\_SERVICE\_DEADLOCK error code, 67  
 ER\_LOCKING\_SERVICE\_TIMEOUT error code, 67  
 ER\_LOCKING\_SERVICE\_WRONG\_NAME error code, 67  
 ER\_LOCK\_ABORTED error code, 43  
 ER\_LOCK\_DEADLOCK error code, 16  
 ER\_LOCK\_NOWAIT error code, 77  
 ER\_LOCK\_ORDER\_DEPENDENCIES\_SYNTAX error code, 347  
 ER\_LOCK\_ORDER\_FAILED\_READ\_FILE error code, 347  
 ER\_LOCK\_ORDER\_FAILED\_WRITE\_FILE error code, 346  
 ER\_LOCK\_ORDER\_INIT\_FAILED error code, 345  
 ER\_LOCK\_ORDER\_MESSAGE error code, 347  
 ER\_LOCK\_ORDER\_SCANNER\_SYNTAX error code, 347  
 ER\_LOCK\_OR\_ACTIVE\_TRANSACTION error code, 15  
 ER\_LOCK\_REFUSED\_BY\_ENGINE error code, 70  
 ER\_LOCK\_TABLE\_FULL error code, 16  
 ER\_LOCK\_WAIT\_TIMEOUT error code, 16  
 ER\_LOG\_BIN\_BETTER\_WITH\_NAME error code, 139  
 ER\_LOG\_CANNOT\_PURGE\_BINLOG\_WITH\_BACKUP\_LOCK error code, 395  
 ER\_LOG\_CANNOT\_WRITE error code, 129  
 ER\_LOG\_CANNOT\_WRITE\_EXTENDED error code, 349  
 ER\_LOG\_COMPONENT\_CANNOT\_INIT error code, 363  
 ER\_LOG\_COMPONENT\_FLUSH\_FAILED error code, 371  
 ER\_LOG\_FILES\_GIVEN\_LOG\_OUTPUT\_IS\_TABLE error code, 139  
 ER\_LOG\_FILE\_CANNOT\_OPEN error code, 206  
 ER\_LOG\_FILE\_INVALID error code, 139  
 ER\_LOG\_GENERAL\_CANNOT\_OPEN error code, 129  
 ER\_LOG\_IN\_USE error code, 26  
 ER\_LOG\_OUTPUT\_CONTRADICTION error code, 138  
 ER\_LOG\_PRINTF\_MSG error code, 192  
 ER\_LOG\_PRIV\_CHECKS\_REQUIRE\_ROW\_FORMAT\_NOT\_S error code, 351  
 ER\_LOG\_PURGE\_NO\_FILE error code, 38  
 ER\_LOG\_PURGE\_UNKNOWN\_ERR error code, 26  
 ER\_LOG\_SLOW\_CANNOT\_OPEN error code, 129  
 ER\_LOG\_SYSLOG\_CANNOT\_OPEN error code, 129  
 ER\_LONGITUDE\_OUT\_OF\_RANGE error code, 80  
 ER\_LOWER\_CASE\_TABLE\_NAMES\_CS\_DD\_ON\_CI\_FS\_UN error code, 139  
 ER\_LOWER\_CASE\_TABLE\_NAMES\_USING\_0 error code, 139  
 ER\_LOWER\_CASE\_TABLE\_NAMES\_USING\_2 error code, 139  
 ER\_MALFORMED\_GTID\_SET\_ENCODING error code, 49  
 ER\_MALFORMED\_GTID\_SET\_SPECIFICATION error code, 49  
 ER\_MALFORMED\_GTID\_SPECIFICATION error code, 49  
 ER\_MALFORMED\_PACKET error code, 53  
 ER\_MANDATORY\_ROLE error code, 81  
 ER\_MASTER\_KEY\_ROTATION\_BINLOG\_FAILED error code, 70  
 ER\_MASTER\_KEY\_ROTATION\_NOT\_SUPPORTED\_BY\_SE error code, 70  
 ER\_MASTER\_KEY\_ROTATION\_SE\_UNAVAILABLE error code, 70  
 ER\_MAXVALUE\_IN\_VALUES\_IN error code, 41  
 ER\_MAX\_PREPARED\_STMT\_COUNT\_REACHED error code, 31  
 ER\_MDL\_OUT\_OF\_RESOURCES error code, 107  
 ER\_MECAB\_CHARSET\_LOADED error code, 196  
 ER\_MECAB\_CREATE\_LATTICE\_FAILED error code, 196  
 ER\_MECAB\_CREATING\_MODEL error code, 196

---

---

ER\_MECAB\_FAILED\_TO\_CREATE\_MODEL error code, 196  
 ER\_MECAB\_FAILED\_TO\_CREATE\_TRIGGER error code, 196  
 ER\_MECAB\_NOT\_SUPPORTED error code, 195  
 ER\_MECAB\_NOT\_VERIFIED error code, 196  
 ER\_MECAB\_OOM\_WHILE\_PARSING\_TEXT error code, 196  
 ER\_MECAB\_PARSE\_FAILED error code, 196  
 ER\_MECAB\_UNSUPPORTED\_CHARSET error code, 196  
 ER\_MESSAGE\_AND\_STATEMENT error code, 42  
 ER\_MFA\_METHODS\_IDENTICAL error code, 113  
 ER\_MFA\_METHODS\_INVALID\_ORDER error code, 113  
 ER\_MFA\_METHOD\_EXISTS error code, 113  
 ER\_MFA\_METHOD\_NOT\_EXISTS error code, 113  
 ER\_MFA\_PLUGIN\_NOT\_LOADED error code, 376  
 ER\_MFA\_USER\_ATTRIBUTES\_CORRUPT error code, 376  
 ER\_MICROSECOND\_TIMER\_IS\_NOT\_AVAILABLE error code, 190  
 ER\_MIGRATE\_TABLE\_TO\_DD\_OOM error code, 353  
 ER\_MISPLACED\_INTO error code, 104  
 ER\_MISSING\_ACL\_SYSTEM\_TABLE error code, 184  
 ER\_MISSING\_CURRENT\_PASSWORD error code, 100  
 ER\_MISSING\_GRANT\_SYSTEM\_TABLE error code, 184  
 ER\_MISSING\_HA\_CREATE\_OPTION error code, 58  
 ER\_MISSING\_JSON\_TABLE\_VALUE error code, 83  
 ER\_MISSING\_JSON\_VALUE error code, 105  
 ER\_MISSING\_KEY error code, 57  
 ER\_MISSING\_SKIP\_REPLICA error code, 20  
 ER\_MISSING\_TABLESPACE\_FILE error code, 81  
 ER\_MIXING\_NOT\_ALLOWED error code, 17  
 ER\_MIX\_HANDLER\_ERROR error code, 33  
 ER\_MIX\_OF\_GROUP\_FUNC\_AND\_FIELDS error code, 12  
 ER\_MIX\_OF\_GROUP\_FUNC\_AND\_FIELDS\_V2 error code, 63  
 ER\_MTA\_CANT\_PARALLEL error code, 48  
 ER\_MTA\_CHANGE\_SOURCE\_CANT\_RUN\_WITH\_GAPS error code, 51  
 ER\_MTA\_EVENT\_BIGGER\_PENDING\_JOBS\_SIZE\_MAX error code, 55  
 ER\_MTA\_FEATURE\_IS\_NOT\_SUPPORTED error code, 48  
 ER\_MTA\_INCONSISTENT\_DATA error code, 48  
 ER\_MTA\_RECOVERY\_FAILURE error code, 51  
 ER\_MTA\_RESET\_WORKERS error code, 51  
 ER\_MTA\_UPDATED\_DBS\_GREATER\_MAX error code, 48  
 ER\_MTR\_MSG\_1 error code, 372  
 ER\_MULTIPLE\_CONSTRAINTS\_WITH\_SAME\_NAME error code, 103  
 ER\_MULTIPLE\_DEF\_CONST\_IN\_LIST\_PART\_ERROR error code, 33  
 ER\_MULTIPLE\_INTO\_CLAUSES error code, 104  
 ER\_MULTIPLE\_JSON\_VALUES error code, 105  
 ER\_MULTIPLE\_PRI\_KEY error code, 7  
 ER\_MULTI\_UPDATE\_KEY\_CONFLICT error code, 44  
 ER\_MUST\_CHANGE\_PASSWORD error code, 52  
 ER\_MUST\_CHANGE\_PASSWORD\_LOGIN error code, 55  
 ER\_MYINIT\_FAILED error code, 137  
 ER\_MYISAM\_CHECK\_METHOD\_ERROR error code, 192  
 ER\_MYISAM\_CRASHED\_ERROR error code, 192  
 ER\_MYISAM\_CRASHED\_ERROR\_IN error code, 144  
 ER\_MYISAM\_CRASHED\_ERROR\_IN\_THREAD error code, 144  
 ER\_MYSQLBACKUP\_CLIENT\_MSG error code, 115  
 ER\_MYSQLBACKUP\_MSG error code, 350  
 ER\_MYSQL\_NATIVE\_PASSWORD\_SECOND\_PASSWORD\_USED error code, 336  
 ER\_MY\_MALLOC\_GETPROCADDRESS\_FAILED error code, 378  
 ER\_MY\_MALLOC\_LOADLIBRARY\_FAILED error code, 378  
 ER\_MY\_MALLOC\_USING\_JEMALLOC error code, 378  
 ER\_MY\_MALLOC\_USING\_STD\_MALLOC error code, 378  
 ER\_MY\_NET\_WRITE\_FAILED\_FALLING\_BACK\_ON\_STDERR error code, 170  
 ER\_M\_BIGGER\_THAN\_D error code, 28  
 ER\_NAME\_BECOMES\_EMPTY error code, 31  
 ER\_NANOSECOND\_TIMER\_IS\_NOT\_AVAILABLE error code, 190  
 ER\_NATIVE\_FCT\_NAME\_COLLISION error code, 37  
 ER\_NDBINFO\_NOT\_UPGRADING\_SCHEMA error code, 356  
 ER\_NDBINFO\_UPGRADING\_SCHEMA error code, 356  
 ER\_NDBINFO\_UPGRADING\_SCHEMA\_FAIL error code, 356  
 ER\_NDB\_LOG\_ENTRY error code, 178  
 ER\_NDB\_LOG\_ENTRY\_WITH\_PREFIX error code, 178  
 ER\_NDB\_REPLICATION\_SCHEMA\_ERROR error code, 39  
 ER\_NEED\_FILE\_INSTEAD\_OF\_DIR error code, 139  
 ER\_NEED\_LOG\_BIN error code, 139  
 ER\_NEED\_REPREPARE error code, 39  
 ER\_NETWORK\_NAMESPACES\_NOT\_SUPPORTED error code, 344  
 ER\_NETWORK\_NAMESPACE\_FILE\_PATH\_TOO\_LONG error code, 344  
 ER\_NETWORK\_NAMESPACE\_NOT\_ALLOWED\_FOR\_WILDCARD error code, 344  
 ER\_NETWORK\_READ\_EVENT\_CHECKSUM\_FAILURE error code, 324  
 ER\_NET\_ERROR\_ON\_WRITE error code, 13  
 ER\_NET\_FCNTL\_ERROR error code, 13  
 ER\_NET\_OK\_PACKET\_TOO\_LARGE error code, 62

ER\_NET\_PACKETS\_OUT\_OF\_ORDER error code, 13  
 ER\_NET\_PACKET\_TOO\_LARGE error code, 13  
 ER\_NET\_READ\_ERROR error code, 13  
 ER\_NET\_READ\_ERROR\_FROM\_PIPE error code, 13  
 ER\_NET\_READ\_INTERRUPTED error code, 13  
 ER\_NET\_UNCOMPRESS\_ERROR error code, 13  
 ER\_NET\_WAIT\_ERROR error code, 345  
 ER\_NET\_WAIT\_ERROR2 error code, 368  
 ER\_NET\_WRITE\_INTERRUPTED error code, 13  
 ER\_NEW\_ABORTING\_CONNECTION error code, 14  
 ER\_NO error code, 3  
 ER\_NONEXISTING\_GRANT error code, 12  
 ER\_NONEXISTING\_PROC\_GRANT error code, 27  
 ER\_NONEXISTING\_TABLE\_GRANT error code, 12  
 ER\_NONPOSITIVE\_RADIUS error code, 86  
 ER\_NONUNIQU\_TABLE error code, 7  
 ER\_NONUPDATEABLE\_COLUMN error code, 24  
 ER\_NON\_BOOLEAN\_EXPR\_FOR\_CHECK\_CONSTRAINT error code, 94  
 ER\_NON\_DEFAULT\_VALUE\_FOR\_GENERATED\_COLUMN error code, 65  
 ER\_NON\_GROUPING\_FIELD\_USED error code, 31  
 ER\_NON\_INSERTABLE\_TABLE error code, 31  
 ER\_NON\_RO\_SELECT\_DISABLE\_TIMER error code, 59  
 ER\_NON\_UNIQ\_ERROR error code, 6  
 ER\_NON\_UPDATABLE\_TABLE error code, 21  
 ER\_NORMAL\_SERVER\_SHUTDOWN error code, 323  
 ER\_NOTE\_COMPONENT\_KEYRING\_OCI\_MISSING\_NAME error code, 386  
 ER\_NOTE\_COMPONENT\_SLOT\_DEREGISTRATION\_SUCCESS error code, 392  
 ER\_NOTE\_COMPONENT\_SLOT\_REGISTRATION\_SUCCESS error code, 392  
 ER\_NOTE\_KEYRING\_COMPONENT\_AES\_DATA\_IDENTIFIER error code, 367  
 ER\_NOTE\_KEYRING\_COMPONENT\_AES\_INVALID\_KEY error code, 367  
 ER\_NOTE\_KEYRING\_COMPONENT\_AES\_INVALID\_MODE error code, 367  
 ER\_NOTE\_KEYRING\_COMPONENT\_AES\_OPERATION\_ERROR error code, 367  
 ER\_NOTE\_KEYRING\_COMPONENT\_GENERATE\_FAILED error code, 367  
 ER\_NOTE\_KEYRING\_COMPONENT\_INITIALIZED error code, 366  
 ER\_NOTE\_KEYRING\_COMPONENT\_KEYS\_METADATA\_ERROR error code, 367  
 ER\_NOTE\_KEYRING\_COMPONENT\_METADATA\_ITERATION\_ERROR error code, 368  
 ER\_NOTE\_KEYRING\_COMPONENT\_READ\_DATA\_NOT\_FOUND error code, 367  
 ER\_NOTE\_KEYRING\_COMPONENT\_REMOVE\_FAILED error code, 367  
 ER\_NOTE\_KEYRING\_COMPONENT\_STORE\_FAILED error code, 367  
 ER\_NOTE\_KEYRING\_COMPONENT\_WRITE\_MAXIMUM\_LENGTH error code, 367  
 ER\_NOT\_ALLOWED\_COMMAND error code, 12  
 ER\_NOT\_ALLOWED\_WITH\_START\_TRANSACTION error code, 106  
 ER\_NOT\_FORM\_FILE error code, 5  
 ER\_NOT\_HINT\_UPDATABLE\_VARIABLE error code, 81  
 ER\_NOT\_IMPLEMENTED\_FOR\_CARTESIAN\_SRS error code, 86  
 ER\_NOT\_IMPLEMENTED\_FOR\_GEOGRAPHIC\_SRS error code, 80  
 ER\_NOT\_IMPLEMENTED\_FOR\_PROJECTED\_SRS error code, 86  
 ER\_NOT\_IMPLEMENTED\_GET\_TABLESPACE\_STATISTICS error code, 206  
 ER\_NOT\_KEYFILE error code, 5  
 ER\_NOT\_RIGHT\_NOW error code, 137  
 ER\_NOT\_SUPPORTED\_AUTH\_MODE error code, 19  
 ER\_NOT\_SUPPORTED\_YET error code, 18  
 ER\_NOT\_VALID\_PASSWORD error code, 52  
 ER\_NO\_ACCESS\_TO\_NATIVE\_FCT error code, 77  
 ER\_NO\_BINARY\_LOGGING error code, 26  
 ER\_NO\_BINLOG\_ERROR error code, 34  
 ER\_NO\_CSV\_NO\_LOG\_TABLES error code, 138  
 ER\_NO\_DB\_ERROR error code, 6  
 ER\_NO\_DEFAULT error code, 17  
 ER\_NO\_DEFAULT\_FOR\_FIELD error code, 25  
 ER\_NO\_DEFAULT\_FOR\_VIEW\_FIELD error code, 28  
 ER\_NO\_ERROR\_LOG\_PARSER\_CONFIGURED error code, 362  
 ER\_NO\_FORMAT\_DESCRIPTION\_EVENT\_BEFORE\_BINLOG\_STATE error code, 38  
 ER\_NO\_FT\_MATERIALIZED\_SUBQUERY error code, 38  
 ER\_NO\_PARTITION\_FOR\_GIVEN\_VALUE error code, 37  
 ER\_NO\_PARTITION\_FOR\_GIVEN\_VALUE\_SILENT error code, 37  
 ER\_NO\_PARTS\_ERROR error code, 33  
 ER\_NO\_PACKETS\_FOR\_SHARED\_LIBRARY error code, 328  
 ER\_NO\_PERMISSION\_TO\_CREATE\_USER error code, 16  
 ER\_NO\_REFERENCED\_ROW error code, 16  
 ER\_NO\_REFERENCED\_ROW\_2 error code, 30  
 ER\_NO\_SECURE\_TRANSPORTS\_CONFIGURED error code, 69  
 ER\_NO\_SESSION\_NAME error code, 99  
 ER\_NO\_SUCH\_DB error code, 72  
 ER\_NO\_SUCH\_INDEX error code, 8  
 ER\_NO\_SUCH\_TABLE error code, 12  
 ER\_NO\_SUCH\_THREAD error code, 9  
 ER\_NO\_SUCH\_USER error code, 30  
 ER\_NO\_SUPER\_WITHOUT\_USER\_PLUGIN error code, 150  
 ER\_NO\_SYSTEM\_SCHEMA\_ACCESS error code, 76  
 ER\_NO\_SYSTEM\_TABLESPACE\_ACCESS error code, 76  
 ER\_NO\_SYSTEM\_TABLE\_ACCESS error code, 76

---

ER_NO_SYSTEM_TABLE_ACCESS_FOR_DICTIONARY	ER_PAGE_TRACKING_RANGE_NOT_TRACKED
error code, 76	error code, 93
ER_NO_SYSTEM_TABLE_ACCESS_FOR_SYSTEM_TABLE	ER_PARSER_TRACE error code, 128
error code, 76	ER_PARSE_ERROR error code, 7
ER_NO_SYSTEM_TABLE_ACCESS_FOR_TABLE	ER_PARSE_ERROR_IN_DIGEST_FN error code, 84
error code, 76	ER_PARSING_VIEW error code, 132
ER_NO_SYSTEM_VIEW_ACCESS error code, 80	ER_PARTIAL_REVOKE_EXISTS error code, 100
ER_NO_TABLES_USED error code, 9	ER_PARTIAL_REVOKE_AND_DB_GRANT_BOTH_EXISTS
ER_NO_THD_NO_UUID error code, 133	error code, 100
ER_NO_TRIGGERS_ON_SYSTEM_SCHEMA error	ER_PARTITIONS_MUST_BE_DEFINED_ERROR
code, 31	error code, 32
ER_NO_UNIQUE_LOGFILE error code, 9	ER_PARTITION_CLAUSE_ON_NONPARTITIONED
ER_NPIPE_CANT_CREATE error code, 179	error code, 47
ER_NPIPE_FAILED_TO_INIT_SECURITY_DESCRIPTOR	ER_PARTITION_COLUMN_LIST_ERROR error code,
error code, 155	41
ER_NPIPE_FAILED_TO_SET_SECURITY_DESCRIPTOR	ER_PARTITION_CONST_DOMAIN_ERROR error
error code, 155	code, 36
ER_NPIPE_PIPE_ALREADY_IN_USE error code, 155	ER_PARTITION_ENTRY_ERROR error code, 33
ER_NULL_CANT_BE_PERSISTED_FOR_READONLY	ER_PARTITION_EXCHANGE_DIFFERENT_OPTION
error code, 122	error code, 46
ER_NULL_COLUMN_IN_INDEX error code, 11	ER_PARTITION_EXCHANGE_FOREIGN_KEY error
ER_NULL_IN_VALUES_LESS_THAN error code, 36	code, 47
ER_NUMERIC_JSON_VALUE_OUT_OF_RANGE	ER_PARTITION_EXCHANGE_PART_TABLE error
error code, 68	code, 46
ER_NUM_THREADS_STILL_ALIVE error code, 398	ER_PARTITION_EXCHANGE_TEMP_TABLE error
ER_OBSOLETE_FILE_PRIVILEGE_FOR_REPLICATION	code, 46
error code, 350	ER_PARTITION_FIELDS_TOO_LONG error code, 41
ER_OBSOLETE_REQUIRE_ROW_FORMAT_VIOLATION	ER_PARTITION_FUNCTION_FAILURE error code, 34
error code, 351	ER_PARTITION_FUNCTION_IS_NOT_ALLOWED
ER_OLD_FILE_FORMAT error code, 30	error code, 36
ER_OLD_KEYFILE error code, 5	ER_PARTITION_FUNC_NOT_ALLOWED_ERROR
ER_OLD_TEMPORALS_UPGRADED error code, 56	error code, 32
ER_ONLY_FD_AND_RBR_EVENTS_ALLOWED_IN_BINLOG	ER_PARTITION_HANDLER_ADMIN_MSG error code,
error code, 46	191
ER_ONLY_IMPLEMENTED_FOR_SRID_0_AND_4326	ER_PARTITION_INSTEAD_OF_SUBPARTITION error
error code, 84	code, 47
ER_ONLY_INTEGERS_ALLOWED error code, 37	ER_PARTITION_MAXVALUE_ERROR error code, 32
ER_ONLY_ON_RANGE_LIST_PARTITION error code,	ER_PARTITION_MERGE_ERROR error code, 36
34	ER_PARTITION_MGMT_ON_NONPARTITIONED
ER_OOM error code, 137	error code, 33
ER_OOM_SAVE_GTIDS error code, 323	ER_PARTITION_MOVE_CREATED_DUPLICATE_ROW_PLEASE
ER_OPEN_AS_READONLY error code, 5	error code, 179
ER_OPEN_ROLE_TABLES error code, 74	ER_PARTITION_NAME error code, 40
ER_OPERAND_COLUMNS error code, 18	ER_PARTITION_NOT_DEFINED_ERROR error code,
ER_OPERATION_NOT_ALLOWED_ON_GR_SECONDARY	error code, 33
error code, 112	ER_PARTITION_NO_TEMPORARY error code, 36
ER_OPERATION_NOT_ALLOWED_WHILE_PRIMARY_COPYING	ER_PARTITION_NO_TEMPORARY error code, 36
error code, 116	ER_PARTITION_NO_TEMPORARY error code, 36
ER_OPTION_PREVENTS_STATEMENT error code,	ER_PARTITION_REQUIRES_VALUES_ERROR error
21	code, 32
ER_OPT_WRONG_TREE error code, 128	ER_PARTITION_WRONG_NO_PART_ERROR error
ER_OUTOFMEMORY error code, 5	code, 32
ER_OUT_OF_RESOURCES error code, 5	ER_PARTITION_WRONG_NO_SUBPART_ERROR
ER_OUT_OF_SORTMEMORY error code, 5	error code, 32
ER_PAGE_TRACKING_CANNOT_PURGE error code,	ER_PARTITION_WRONG_VALUES_ERROR error
93	code, 32
ER_PAGE_TRACKING_NOT_STARTED error code,	ER_PART_EXPR_TOO_LONG error code, 80
93	ER_PASSWORD_ANONYMOUS_USER error code,
	11

---



---

ER\_PASSWORD\_CANNOT\_BE\_RETAINED\_ON\_PLUGIN\_CHANGE error code, 100  
 ER\_PASSWORD\_EXPIRATION\_NOT\_SUPPORTED\_BY\_PLUGIN error code, 84  
 ER\_PASSWORD\_EXPIRE\_ANONYMOUS\_USER error code, 58  
 ER\_PASSWORD\_FORMAT error code, 53  
 ER\_PASSWORD\_NOT\_ALLOWED error code, 11  
 ER\_PASSWORD\_NO\_MATCH error code, 11  
 ER\_PATH\_IN\_DATADIR error code, 81  
 ER\_PATH\_LENGTH error code, 43  
 ER\_PERFORMANCE\_SCHEMA\_VERSION\_CHANGE error code, 396  
 ER\_PERFSCHEMA\_COMPONENTS\_INFRASTRUCTURE\_ERROR error code, 183  
 ER\_PERFSCHEMA\_COMPONENTS\_INFRASTRUCTURE\_ERROR error code, 183  
 ER\_PERFSCHEMA\_INIT\_FAILED error code, 140  
 ER\_PERFSCHEMA\_TABLES\_INIT\_FAILED error code, 184  
 ER\_PERSISTED\_VARIABLES\_DECRYPTION\_FAILED error code, 378  
 ER\_PERSISTED\_VARIABLES\_ENCRYPTION\_FAILED error code, 378  
 ER\_PERSISTED\_VARIABLES\_KEYRING\_SUPPORT\_REQUIRED error code, 378  
 ER\_PERSISTED\_VARIABLES\_LACK\_KEYRING\_SUPPORT error code, 378  
 ER\_PERSISTED\_VARIABLES\_MASTER\_KEY\_CANNOT\_BE\_GENERATED error code, 378  
 ER\_PERSISTED\_VARIABLES\_MASTER\_KEY\_NOT\_FOUND error code, 378  
 ER\_PERSISTENT\_PRIVILEGES\_BOOTSTRAP error code, 183  
 ER\_PERSIST\_ONLY\_ACCESS\_DENIED\_ERROR error code, 81  
 ER\_PERSIST\_OPTION\_HOST\_TRUNCATED error code, 345  
 ER\_PERSIST\_OPTION\_STATUS error code, 206  
 ER\_PERSIST\_OPTION\_USER\_TRUNCATED error code, 345  
 ER\_PER\_CHANNEL\_RPL\_FILTER\_CONF\_FOR\_GRP\_RPL error code, 189  
 ER\_PFS\_MALLOC\_ARRAY\_OOM error code, 190  
 ER\_PFS\_MALLOC\_ARRAY\_OVERFLOW error code, 190  
 ER\_PFS\_NOTIFICATION\_FUNCTION\_REGISTER\_FAILED error code, 185  
 ER\_PID\_FILEPATH\_LOCATIONS\_INACCESSIBLE error code, 329  
 ER\_PID\_FILE\_PRIV\_DIRECTORY\_INSECURE error code, 246  
 ER\_PK\_INDEX\_CANT\_BE\_INVISIBLE error code, 74  
 ER\_PLUGGABLE\_PROTOCOL\_COMMAND\_NOT\_SUPPORTED error code, 66  
 ER\_PLUGINS\_SHUTDOWN\_END error code, 397  
 ER\_PLUGINS\_SHUTDOWN\_START error code, 397  
 ER\_PLUGIN\_BAD\_OPTIONS error code, 170  
 ER\_PLUGIN\_CANNOT\_BE\_UNINSTALLED error code, 56  
 ER\_PLUGIN\_CANT\_LOAD error code, 169  
 ER\_PLUGIN\_CANT\_OPEN\_PLUGIN\_TABLE error code, 169  
 ER\_PLUGIN\_CANT\_SET\_PERSISTENT\_OPTIONS error code, 170  
 ER\_PLUGIN\_COMMON\_FAILED\_TO\_OPEN\_FILTER\_TABLES error code, 205  
 ER\_PLUGIN\_COMMON\_FAILED\_TO\_OPEN\_TABLE error code, 205  
 ER\_PLUGIN\_DELETE\_BUILTIN error code, 39  
 ER\_PLUGIN\_DID\_NOT\_DEINITIALIZE\_THREADS error code, 169  
 ER\_PLUGIN\_DISABLED error code, 170  
 ER\_PLUGIN\_EXCEPTION\_OPERATION\_FAILED error code, 389  
 ER\_PLUGIN\_FAILED\_DEINITIALIZATION error code, 169  
 ER\_PLUGIN\_FAILED\_TO\_OPEN\_TABLE error code, 327  
 ER\_PLUGIN\_FAILED\_TO\_OPEN\_TABLES error code, 327  
 ER\_PLUGIN\_FORCING\_SHUTDOWN error code, 169  
 ER\_PLUGIN\_HAS\_CONFLICTING\_SYSTEM\_VARIABLES error code, 170  
 ER\_PLUGIN\_HAS\_NONZERO\_REFCOUNT\_AFTER\_DEINITIALIZATION error code, 169  
 ER\_PLUGIN\_HAS\_NONZERO\_REFCOUNT\_AFTER\_SHUTDOWN error code, 169  
 ER\_PLUGIN\_INIT\_FAILED error code, 142  
 ER\_PLUGIN\_INSTALL\_ERROR error code, 332  
 ER\_PLUGIN\_INVALID\_TABLE\_DEFINITION error code, 371  
 ER\_PLUGIN\_IS\_NOT\_LOADED error code, 34  
 ER\_PLUGIN\_IS\_PERMANENT error code, 44  
 ER\_PLUGIN\_LOAD\_OPTIONS\_IGNORED error code, 350  
 ER\_PLUGIN\_LOAD\_PARAMETER\_TOO\_LONG error code, 169  
 ER\_PLUGIN\_NOT\_EARLY error code, 96  
 ER\_PLUGIN\_NOT\_EARLY\_DUP error code, 345  
 ER\_PLUGIN\_NO\_INSTALL error code, 46  
 ER\_PLUGIN\_NO\_INSTALL\_DUP error code, 345  
 ER\_PLUGIN\_NO\_UNINSTALL error code, 45  
 ER\_PLUGIN\_OOM error code, 170  
 ER\_PLUGIN\_PARSING\_OPTIONS\_FAILED error code, 170  
 ER\_PLUGIN\_REGISTRATION\_DONE error code, 113  
 ER\_PLUGIN\_REGISTRATION\_FAILED error code, 169  
 ER\_PLUGIN\_REQUIRES\_REGISTRATION error code, 113  
 ER\_PLUGIN\_SHUTTING\_DOWN\_PLUGIN error code, 169  
 ER\_PLUGIN\_UNINSTALL\_ERROR error code, 332  
 ER\_PLUGIN\_UNKNOWN\_VARIABLE\_TYPE error code, 170

---

---

ER\_PLUGIN\_VARIABLE\_MISSING\_NAME error code, 170  
 ER\_PLUGIN\_VARIABLE\_NOT\_ALLOCATED\_THREAD\_LOCAL error code, 170  
 ER\_PLUGIN\_VARIABLE\_SET\_READ\_ONLY error code, 170  
 ER\_POINTLESS\_WITHOUT\_SLOWLOG error code, 134  
 ER\_POLYGON\_TOO\_LARGE error code, 87  
 ER\_PREPARE\_FOR\_PRIMARY\_ENGINE error code, 372  
 ER\_PREPARE\_FOR\_SECONDARY\_ENGINE error code, 341  
 ER\_PREVENTS\_VARIABLE\_WITHOUT\_RBR error code, 64  
 ER\_PRIMARY\_CANT\_HAVE\_NULL error code, 14  
 ER\_PRIVILEGE\_DEREGISTRATION error code, 393  
 ER\_PRIVILEGE\_REGISTRATION error code, 393  
 ER\_PRIVILEGE\_SYSTEM\_INIT\_FAILED error code, 183  
 ER\_PROCACCESS\_DENIED\_ERROR error code, 26  
 ER\_PROC\_AUTO\_GRANT\_FAIL error code, 27  
 ER\_PROC\_AUTO\_REVOKE\_FAIL error code, 27  
 ER\_PROTOCOL\_COMPRESSION\_RESET\_LOG error code, 350  
 ER\_PS\_MANY\_PARAM error code, 26  
 ER\_PS\_NO\_RECURSION error code, 30  
 ER\_QUALIFY\_WITHOUT\_WINDOW\_FUNCTION error code, 124  
 ER\_QUERY\_INTERRUPTED error code, 22  
 ER\_QUERY\_ON\_FOREIGN\_DATA\_SOURCE error code, 29  
 ER\_QUERY\_TIMEOUT error code, 59  
 ER\_RANGE\_NOT\_INCREASING\_ERROR error code, 32  
 ER\_READING\_TABLE\_FAILED error code, 142  
 ER\_READY error code, 8  
 ER\_READ\_LOG\_EVENT\_FAILED error code, 188  
 ER\_READ\_ONLY\_MODE error code, 53  
 ER\_READ\_ONLY\_TRANSACTION error code, 16  
 ER\_REALLY\_RUN\_AS\_ROOT error code, 136  
 ER\_RECORD\_FILE\_FULL error code, 10  
 ER\_RECOVERING\_TABLE error code, 171  
 ER\_REDUCED\_DBLWR\_FILE\_CORRUPTED error code, 394  
 ER\_REDUCED\_DBLWR\_PAGE\_FOUND error code, 394  
 ER\_REFERENCED\_TRG\_DOES\_NOT\_EXIST error code, 58  
 ER\_REGEXP\_BAD\_ESCAPE\_SEQUENCE error code, 85  
 ER\_REGEXP\_BAD\_INTERVAL error code, 85  
 ER\_REGEXP\_BUFFER\_OVERFLOW error code, 85  
 ER\_REGEXP\_ERROR error code, 12  
 ER\_REGEXP\_ILLEGAL\_ARGUMENT error code, 85  
 ER\_REGEXP\_INDEX\_OUTOFBOUNDS\_ERROR error code, 85  
 ER\_REGEXP\_INTERNAL\_ERROR error code, 85  
 ER\_REGEXP\_INVALID\_BACK\_REF error code, 85  
 ER\_REGEXP\_INVALID\_CAPTURE\_GROUP\_NAME error code, 99  
 ER\_REGEXP\_INVALID\_FLAG error code, 100  
 ER\_REGEXP\_INVALID\_RANGE error code, 85  
 ER\_REGEXP\_LOOK\_BEHIND\_LIMIT error code, 85  
 ER\_REGEXP\_MAX\_LT\_MIN error code, 85  
 ER\_REGEXP\_MISMATCHED\_PAREN error code, 85  
 ER\_REGEXP\_MISSING\_CLOSE\_BRACKET error code, 85  
 ER\_REGEXP\_MISSING\_FILE error code, 115  
 ER\_REGEXP\_MISSING\_ICU\_DATADIR error code, 377  
 ER\_REGEXP\_MISSING\_RESOURCE error code, 114  
 ER\_REGEXP\_PATTERN\_TOO\_BIG error code, 85  
 ER\_REGEXP\_RULE\_SYNTAX error code, 85  
 ER\_REGEXP\_STACK\_OVERFLOW error code, 85  
 ER\_REGEXP\_TIME\_OUT error code, 85  
 ER\_REGEXP\_UNIMPLEMENTED error code, 85  
 ER\_REGEX\_NUMBER\_TOO\_BIG error code, 109  
 ER\_RELAY\_LOG\_FAIL error code, 26  
 ER\_RELAY\_LOG\_INIT error code, 26  
 ER\_RELAY\_LOG\_SPACE\_LIMIT\_DISABLED error code, 330  
 ER\_RELOAD\_KEYRING\_FAILURE error code, 111  
 ER\_REMOVED\_SPACES error code, 31  
 ER\_RENAMED\_NAME error code, 40  
 ER\_RENAME\_ROLE error code, 74  
 ER\_REORG\_HASH\_ONLY\_ON\_SAME\_NO error code, 33  
 ER\_REORG\_NO\_PARAM\_ERROR error code, 34  
 ER\_REORG\_OUTSIDE\_RANGE error code, 34  
 ER\_REORG\_PARTITION\_NOT\_EXIST error code, 34  
 ER\_REPLACE\_INACCESSIBLE\_ROWS error code, 61  
 ER\_REPLICATION\_INCOMPATIBLE\_TABLE\_WITH\_GIPK error code, 387  
 ER\_REPLICA\_AM\_INIT\_REPOSITORY error code, 56  
 ER\_REPLICA\_ANONYMOUS\_TO\_GTID\_UUID\_SAME\_AS\_GROUP error code, 364  
 ER\_REPLICA\_ANON\_TO\_GTID\_IS\_LOCAL\_OR\_UUID\_AND\_GTID error code, 364  
 ER\_REPLICA\_CANT\_CREATE\_CONVERSION error code, 43  
 ER\_REPLICA\_CANT\_USE\_TEMPDIR error code, 167  
 ER\_REPLICA\_CHANGE\_SOURCE\_TO\_EXECUTED error code, 166  
 ER\_REPLICA\_CHANNEL\_DOES\_NOT\_EXIST error code, 62  
 ER\_REPLICA\_CHANNEL\_IO\_THREAD\_MUST\_STOP error code, 58  
 ER\_REPLICA\_CHANNEL\_MUST\_STOP error code, 62  
 ER\_REPLICA\_CHANNEL\_NAME\_INVALID\_OR\_TOO\_LONG error code, 62  
 ER\_REPLICA\_CHANNEL\_NOT\_RUNNING error code, 63  
 ER\_REPLICA\_CHANNEL\_OPERATION\_NOT\_ALLOWED error code, 67

---

ER\_REPLICA\_CHANNEL\_SQL\_SKIP\_COUNTER error code, 63  
 ER\_REPLICA\_CHANNEL\_SQL\_THREAD\_MUST\_STOP error code, 63  
 ER\_REPLICA\_CHANNEL\_WAS\_NOT\_RUNNING error code, 63  
 ER\_REPLICA\_CHANNEL\_WAS\_RUNNING error code, 63  
 ER\_REPLICA\_CM\_INIT\_REPOSITORY error code, 56  
 ER\_REPLICA\_CONFIGURATION error code, 51  
 ER\_REPLICA\_CORRUPT\_EVENT error code, 38  
 ER\_REPLICA\_CREATE\_EVENT\_FAILURE error code, 324  
 ER\_REPLICA\_FATAL\_ERROR error code, 324  
 ER\_REPLICA\_HAS\_MORE\_GTIDS\_THAN\_SOURCE error code, 57  
 ER\_REPLICA\_HEARTBEAT\_FAILURE error code, 324  
 ER\_REPLICA\_HEARTBEAT\_VALUE\_OUT\_OF\_RANGE error code, 39  
 ER\_REPLICA\_HEARTBEAT\_VALUE\_OUT\_OF\_RANGE\_MAX error code, 44  
 ER\_REPLICA\_HEARTBEAT\_VALUE\_OUT\_OF\_RANGE\_MIN error code, 44  
 ER\_REPLICA\_IGNORED\_SSL\_PARAMS error code, 20  
 ER\_REPLICA\_IGNORED\_TABLE error code, 18  
 ER\_REPLICA\_IGNORE\_SERVER\_IDS error code, 41  
 ER\_REPLICA\_INCIDENT error code, 324  
 ER\_REPLICA\_KILLED\_AFTER\_RECONNECT error code, 189  
 ER\_REPLICA\_MAX\_CHANNELS\_EXCEEDED error code, 62  
 ER\_REPLICA\_MULTIPLE\_CHANNELS\_CMD error code, 62  
 ER\_REPLICA\_NEW\_CHANNEL\_WRONG\_REPOSITORY error code, 62  
 ER\_REPLICA\_NOT\_RUNNING error code, 15  
 ER\_REPLICA\_NOT\_STARTED\_ON\_SOME\_CHANNELS error code, 189  
 ER\_REPLICA\_POSSIBLY\_DIVERGED\_AFTER\_DDL error code, 87  
 ER\_REPLICA\_RECONNECT\_FAILED error code, 189  
 ER\_REPLICA\_RELAY\_LOG\_PURGE\_FAILED error code, 184  
 ER\_REPLICA\_RELAY\_LOG\_READ\_FAILURE error code, 324  
 ER\_REPLICA\_RELAY\_LOG\_TRUNCATE\_INFO error code, 184  
 ER\_REPLICA\_RELAY\_LOG\_WRITE\_FAILURE error code, 324  
 ER\_REPLICA\_SILENT\_RETRY\_TRANSACTION error code, 51  
 ER\_REPLICA\_SOURCE\_COM\_FAILURE error code, 324  
 ER\_REPLICA\_SQL\_THREAD\_MUST\_STOP error code, 58  
 ER\_REPLICA\_SQL\_THREAD\_STOPPED\_AFTER\_GTIDS error code, 154  
 ER\_REPLICA\_SQL\_THREAD\_STOPPED\_BEFORE\_GTIDS error code, 154  
 ER\_REPLICA\_SQL\_THREAD\_STOPPED\_BEFORE\_GTIDS\_READ error code, 154  
 ER\_REPLICA\_SQL\_THREAD\_STOPPED\_GAP\_TRX\_PROCESSING error code, 154  
 ER\_REPLICA\_SQL\_THREAD\_STOPPED\_UNTIL\_CONDITION error code, 154  
 ER\_REPLICA\_SQL\_THREAD\_STOPPED\_UNTIL\_POSITION error code, 154  
 ER\_REPLICA\_THREAD error code, 15  
 ER\_REPLICA\_WORKER\_STOPPED\_PREVIOUS\_THD\_ERROR error code, 59  
 ER\_REQUIRES\_PRIMARY\_KEY error code, 14  
 ER\_REQUIRE\_ROW\_FORMAT\_INVALID\_VALUE error code, 104  
 ER\_REQUIRE\_TABLE\_PRIMARY\_KEY\_CHECK\_GENERATE\_MAX error code, 120  
 ER\_REQUIRE\_TABLE\_PRIMARY\_KEY\_CHECK\_GENERATE\_MIN error code, 389  
 ER\_RESERVED\_SYNTAX error code, 26  
 ER\_RESERVED\_TABLESPACE\_NAME error code, 87  
 ER\_RESET\_SOURCE\_TO\_VALUE\_OUT\_OF\_RANGE error code, 77  
 ER\_RESIGNAL\_WITHOUT\_ACTIVE\_HANDLER error code, 40  
 ER\_RESOURCE\_GROUP\_BIND\_FAILED error code, 83  
 ER\_RESOURCE\_GROUP\_BUSY error code, 83  
 ER\_RESOURCE\_GROUP\_DISABLED error code, 83  
 ER\_RESOURCE\_GROUP\_EXISTS error code, 82  
 ER\_RESOURCE\_GROUP\_IS\_DISABLED error code, 185  
 ER\_RESOURCE\_GROUP\_METADATA\_UPDATE\_SKIPPED error code, 185  
 ER\_RESOURCE\_GROUP\_NOT\_EXISTS error code, 82  
 ER\_RESOURCE\_GROUP\_POST\_INIT\_FAILED error code, 183  
 ER\_RESOURCE\_GROUP\_SUBSYSTEM\_INIT\_FAILED error code, 183  
 ER\_RESOURCE\_GROUP\_VALIDATION\_FAILED error code, 185  
 ER\_RESTART\_RECEIVED\_INFO error code, 193  
 ER\_RESTART\_SERVER\_FAILED error code, 86  
 ER\_RES\_GRP\_FAILED\_DETERMINE\_CPU\_COUNT error code, 186  
 ER\_RES\_GRP\_FAILED\_TO\_DETERMINE\_NICE\_CAPABILITY error code, 186  
 ER\_RES\_GRP\_FAILED\_TO\_GET\_THREAD\_HANDLE error code, 186  
 ER\_RES\_GRP\_FEATURE\_NOT\_AVAILABLE error code, 186  
 ER\_RES\_GRP\_GET\_THREAD\_PRIO\_NOT\_SUPPORTED error code, 186  
 ER\_RES\_GRP\_INVALID\_THREAD\_PRIORITY error code, 186  
 ER\_RES\_GRP\_INVALID\_VCPU\_ID error code, 193

---

---

ER\_RES\_GRP\_INVALID\_VCPU\_RANGE error code, 193  
 ER\_RES\_GRP\_SET\_THREAD\_PRIORITY\_FAILED error code, 186  
 ER\_RES\_GRP\_SET\_THR\_AFFINITY\_FAILED error code, 186  
 ER\_RES\_GRP\_SET\_THR\_AFFINITY\_TO\_CPUS\_FAILED error code, 186  
 ER\_RES\_GRP\_SOLARIS\_PROCESSOR\_AFFINITY\_FAILED error code, 186  
 ER\_RES\_GRP\_SOLARIS\_PROCESSOR\_BIND\_TO\_CPU error code, 186  
 ER\_RES\_GRP\_SOLARIS\_PROCESSOR\_BIND\_TO\_THREADS error code, 186  
 ER\_RES\_GRP\_THD\_UNBIND\_FROM\_CPU\_FAILED error code, 186  
 ER\_RETRYING\_REPAIR\_WITHOUT\_QUICK error code, 170  
 ER\_RETRYING\_REPAIR\_WITH\_KEYCACHE error code, 170  
 ER\_REVOKE\_GRANTS error code, 20  
 ER\_REWRITER\_LOAD\_FAILED error code, 207  
 ER\_REWRITER\_OOM error code, 206  
 ER\_REWRITER\_QUERY\_ERROR\_MSG error code, 204  
 ER\_REWRITER\_QUERY\_FAILED error code, 204  
 ER\_REWRITER\_READ\_FAILED error code, 207  
 ER\_REWRITER\_TABLE\_MALFORMED\_ERROR error code, 207  
 ER\_ROLE\_GRANTED\_TO\_ITSELF error code, 110  
 ER\_ROLE\_NOT\_GRANTED error code, 74  
 ER\_ROW\_DATA\_TOO\_BIG\_TO\_WRITE\_IN\_BINLOG error code, 189  
 ER\_ROW\_DOES\_NOT\_MATCH\_GIVEN\_PARTITION\_SIZE error code, 47  
 ER\_ROW\_DOES\_NOT\_MATCH\_PARTITION error code, 47  
 ER\_ROW\_IN\_WRONG\_PARTITION error code, 55  
 ER\_ROW\_IN\_WRONG\_PARTITION\_PLEASE\_REPAIR error code, 144  
 ER\_ROW\_IS\_REFERENCED error code, 17  
 ER\_ROW\_IS\_REFERENCED\_2 error code, 30  
 ER\_ROW\_SINGLE\_PARTITION\_FIELD\_ERROR error code, 41  
 ER\_RPL\_AM\_INIT\_INFO\_MSG error code, 191  
 ER\_RPL\_ASYNC\_CHANNEL\_CANT\_CONNECT error code, 363  
 ER\_RPL\_ASYNC\_CHANNEL\_CANT\_CONNECT\_NO\_QUORUM error code, 364  
 ER\_RPL\_ASYNC\_CHANNEL\_STOPPED\_QUORUM\_LOST error code, 364  
 ER\_RPL\_ASYNC\_CHECK\_CONNECTION\_ERROR error code, 403  
 ER\_RPL\_ASYNC\_GET\_GROUP\_MEMBERSHIP\_DETAILS error code, 403  
 ER\_RPL\_ASYNC\_MANAGED\_NAME\_ADDED error code, 364  
 ER\_RPL\_ASYNC\_MANAGED\_NAME\_REMOVED error code, 364  
 ER\_RPL\_ASYNC\_MONITOR\_IO\_THD\_FETCH\_GROUP\_MAJORITY error code, 403  
 ER\_RPL\_ASYNC\_NEXT\_FAILOVER\_CHANNEL\_SELECTED error code, 390  
 ER\_RPL\_ASYNC\_READ\_FAILOVER\_TABLE error code, 364  
 ER\_RPL\_ASYNC\_RECONNECT\_AUTO\_POSITION\_OFF error code, 107  
 ER\_RPL\_ASYNC\_RECONNECT\_FAIL\_NO\_SOURCE error code, 362  
 ER\_RPL\_ASYNC\_RECONNECT\_GTID\_MODE\_OFF error code, 107  
 ER\_RPL\_ASYNC\_RECONNECT\_GTID\_MODE\_OFF\_CHANNEL error code, 365  
 ER\_RPL\_ASYNC\_REPLICA\_IO\_THD\_FETCH\_GROUP\_MAJORITY error code, 403  
 ER\_RPL\_ASYNC\_SENDER\_ADDED error code, 363  
 ER\_RPL\_ASYNC\_SENDER\_REMOVED error code, 363  
 ER\_RPL\_BINLOG\_FILTERS\_OOM error code, 136  
 ER\_RPL\_BINLOG\_RELAY\_DELEGATES\_INIT\_FAILED error code, 142  
 ER\_RPL\_BINLOG\_SKIPPING\_REMAINING\_HEARTBEAT\_INFO error code, 159  
 ER\_RPL\_BINLOG\_SOURCE\_SENDS\_HEARTBEAT error code, 159  
 ER\_RPL\_BINLOG\_SOURCE\_USES\_CHECKSUM\_AND\_REPLICATION error code, 159  
 ER\_RPL\_BINLOG\_STARTING\_DUMP error code, 159  
 ER\_RPL\_BINLOG\_STORAGE\_DELEGATES\_INIT\_FAILED error code, 142  
 ER\_RPL\_BINLOG\_TRANSMIT\_DELEGATES\_INIT\_FAILED error code, 142  
 ER\_RPL\_CANNOT\_OPEN\_RELAY\_LOG error code, 375  
 ER\_RPL\_CANT\_ADD\_DO\_TABLE error code, 138  
 ER\_RPL\_CANT\_ADD\_IGNORE\_TABLE error code, 138  
 ER\_RPL\_CANT\_CREATE\_REPLICA\_THREAD error code, 162  
 ER\_RPL\_CANT\_FIND\_FOLLOWUP\_FILE error code, 165  
 ER\_RPL\_CANT\_HAVE\_SAME\_BASENAME error code, 181  
 ER\_RPL\_CANT\_INITIALIZE\_GTID\_SETS\_IN\_AM\_INIT\_INFO error code, 167  
 ER\_RPL\_CANT\_MAKE\_PATHS error code, 139  
 ER\_RPL\_CANT\_OPEN\_INFO\_TABLE error code, 155  
 ER\_RPL\_CANT\_OPEN\_LOG\_IN\_AM\_INIT\_INFO error code, 167  
 ER\_RPL\_CANT\_SCAN\_INFO\_TABLE error code, 155  
 ER\_RPL\_CANT\_STOP\_REPLICA\_WHILE\_LOCKED\_BACKUP error code, 97  
 ER\_RPL\_CHANNELS\_REQUIRE\_NON\_ZERO\_SERVER\_ID error code, 156  
 ER\_RPL\_CORRUPTED\_INFO\_TABLE error code, 155

---

---

ER_RPL_CORRUPTED_KEYS_IN_INFO_TABLE error code, 155	ER_RPL_FILTER_ADD_WILD_DO_TABLE_FAILED error code, 183
ER_RPL_ENCRYPTION_CANNOT_ROTATE_BINLOG error code, 93	ER_RPL_FILTER_ADD_WILD_IGNORE_TABLE_FAILED error code, 183
ER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT error code, 93	ER_RPL_GTID_LOG_EVENT_IN_STREAM error code, 158
ER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY error code, 92	ER_RPL_GTID_MEMORY_FINALLY_AVAILABLE error code, 157
ER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY error code, 92	ER_RPL_GTID_MODE_REQUIRES_ENFORCE_GTID_CONSISTENCY error code, 181
ER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY error code, 92	ER_RPL_GTID_TABLE_CANNOT_OPEN error code, 129
ER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS error code, 92	ER_RPL_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT error code, 332
ER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY error code, 92	ER_RPL_GTID_UNSAFE_STMT_CREATE_SELECT error code, 323
ER_RPL_ENCRYPTION_HEADER_ERROR error code, 92	ER_RPL_GTID_UNSAFE_STMT_ON_NON_TRANS_TABLE error code, 323
ER_RPL_ENCRYPTION_KEYRING_INVALID_KEY error code, 92	ER_RPL_INCOMPATIBLE_DECIMAL_IN_RBR error code, 158
ER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED error code, 92	ER_RPL_INCONSISTENT_SEQUENCE_NO_IN_TRX error code, 156
ER_RPL_ENCRYPTION_KEY_NOT_FOUND error code, 92	ER_RPL_INCONSISTENT_TIMESTAMPS_IN_TRX error code, 155
ER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED error code, 93	ER_RPL_INCREMENTING_MEMBER_ACTION_VERSION error code, 373
ER_RPL_ENCRYPTION_UNABLE_TO_CHANGE_OPTIONS error code, 92	ER_RPL_INFINITY_DENIED error code, 141
ER_RPL_ERROR_CREATING_APPLIER_METADATA error code, 156	ER_RPL_INFINITY_IGNORED error code, 141
ER_RPL_ERROR_CREATING_CONNECTION_METADATA error code, 156	ER_RPL_INFO_DATA_TOO_LONG error code, 47
ER_RPL_ERROR_LOOKING_FOR_LOG error code, 164	ER_RPL_IO_THREAD_KILLED error code, 189
ER_RPL_ERROR_READING_REPLICA_WORKER_CONFIGURATION error code, 168	ER_RPL_LOG_ENTRY_EXCEEDS_REPLICA_MAX_ALLOWED_SIZE error code, 164
ER_RPL_ERROR_READING_SOURCE_CONFIGURATION error code, 169	ER_RPL_LOG_NOT_FOUND_WHILE_COUNTING_RELAY_LOG_ENTRIES error code, 167
ER_RPL_ERROR_WRITING_RELAY_LOG_CONFIGURATION error code, 167	ER_RPL_MTA_AUTOMATIC_RECOVERY_FAILED error code, 162
ER_RPL_ERROR_WRITING_SOURCE_CONFIGURATION error code, 169	ER_RPL_MTA_CHECKPOINT_PERIOD_DIFFERS_FROM_CONFIG error code, 165
ER_RPL_FAILED_TO_CREATE_CACHE_FOR_INFO_FILE error code, 157	ER_RPL_MTA_GROUP_RECOVERY_APPLIER_METADATA_MISSING error code, 164
ER_RPL_FAILED_TO_CREATE_NEW_INFO_FILE error code, 157	ER_RPL_MTA_GROUP_RECOVERY_APPLIER_METADATA_MISSING error code, 164
ER_RPL_FAILED_TO_DELETE_FROM_REPLICA_WORKER_CONFIGURATION error code, 156	ER_RPL_MTA_RECOVERY_CANT_OPEN_RELAY_LOG error code, 162
ER_RPL_FAILED_TO_OPEN_INFO_FILE error code, 157	ER_RPL_MTA_RECOVERY_COMPLETE error code, 163
ER_RPL_FAILED_TO_OPEN_RELAY_LOG error code, 168	ER_RPL_MTA_RECOVERY_FAILED_TO_START_COORDINATOR error code, 162
ER_RPL_FAILED_TO_RESET_STATE_IN_REPLICA_INFO_FILE error code, 156	ER_RPL_MTA_RECOVERY_STARTING_COORDINATOR error code, 162
ER_RPL_FAILED_TO_STAT_LOG_IN_INDEX error code, 167	ER_RPL_MTA_RECOVERY_SUCCESSFUL error code, 162
ER_RPL_FILTERS_NOT_ATTACHED_TO_CHANNEL error code, 189	ER_RPL_MTA_RECOVERY_WAITING_COORDINATOR error code, 168
	ER_RPL_MTA_STATISTICS error code, 163
	ER_RPL_MULTISOURCE_REQUIRES_TABLE_TYPE_REPOSITORY error code, 156

---

---

ER\_RPL\_OPEN\_INDEX\_FILE\_FAILED error code, 167  
 ER\_RPL\_PLEASE\_USE\_OPTION\_RELAY\_LOG error code, 167  
 ER\_RPL\_PLUGIN\_FUNCTION\_FAILED error code, 142  
 ER\_RPL\_RECOVERY\_ERROR error code, 161  
 ER\_RPL\_RECOVERY\_ERROR\_READ\_RELAY\_LOG error code, 161  
 ER\_RPL\_RECOVERY\_FILE\_SOURCE\_POS\_INFO error code, 162  
 ER\_RPL\_RECOVERY\_IO\_ERROR\_READING\_RELAY\_LOG error code, 162  
 ER\_RPL\_RECOVERY\_NO\_ROTATE\_EVENT\_FROM\_SOURCE error code, 161  
 ER\_RPL\_RECOVERY\_REPLICATE\_SAME\_SERVER\_ID error code, 162  
 ER\_RPL\_RECOVERY\_SKIPPED\_GROUP\_REPLICATION\_CHANNEL error code, 161  
 ER\_RPL\_RELAY\_LOG\_INDEX\_NEEDS\_FILE\_NOT\_DIRECTORY error code, 167  
 ER\_RPL\_RELAY\_LOG\_NEEDS\_FILE\_NOT\_DIRECTORY error code, 167  
 ER\_RPL\_RELAY\_LOG\_RECOVERY\_GTID\_ONLY error code, 377  
 ER\_RPL\_RELAY\_LOG\_RECOVERY\_INFO\_AFTER\_CLONE error code, 353  
 ER\_RPL\_REPLICA\_ADDITIONAL\_ERROR\_INFO\_FROM\_SOURCE error code, 165  
 ER\_RPL\_REPLICA\_AUTO\_POSITION\_IS\_1\_AND\_GTID\_MODE\_IS\_OFF error code, 161  
 ER\_RPL\_REPLICA\_CANT\_FLUSH\_CONNECTION\_METADATA error code, 163  
 ER\_RPL\_REPLICA\_CANT\_INITIALIZE\_REPLICA\_WORKER error code, 164  
 ER\_RPL\_REPLICA\_CANT\_INIT\_RELAY\_LOG\_POSITION error code, 163  
 ER\_RPL\_REPLICA\_CANT\_START\_REPLICA\_FOR\_CHANNEL error code, 161  
 ER\_RPL\_REPLICA\_CANT\_STOP\_REPLICA\_FOR\_CHANNEL error code, 161  
 ER\_RPL\_REPLICA\_CANT\_USE\_CHARSET error code, 166  
 ER\_RPL\_REPLICA\_CONNECTED\_TO\_SOURCE\_REPLICATION error code, 166  
 ER\_RPL\_REPLICA\_CONNECTED\_TO\_SOURCE\_RPL\_STATUS\_FILE\_BASED error code, 391  
 ER\_RPL\_REPLICA\_CONNECTED\_TO\_SOURCE\_RPL\_STATUS\_FILE\_BASED error code, 391  
 ER\_RPL\_REPLICA\_COULD\_NOT\_CREATE\_CHANNEL error code, 156  
 ER\_RPL\_REPLICA\_DUMP\_THREAD\_KILLED\_BY\_SOURCE error code, 163  
 ER\_RPL\_REPLICA\_ERROR\_INFO\_FROM\_DA error code, 165  
 ER\_RPL\_REPLICA\_ERROR\_LOADING\_USER\_DEFINED\_TABLE error code, 165  
 ER\_RPL\_REPLICA\_ERROR\_READING\_FROM\_SERVER error code, 163  
 ER\_RPL\_REPLICA\_ERROR\_READING\_RELAY\_LOG\_EVENTS error code, 166  
 ER\_RPL\_REPLICA\_ERROR\_REQUESTING\_BINLOG\_DUMP error code, 164  
 ER\_RPL\_REPLICA\_ERROR\_RETRYING error code, 163  
 ER\_RPL\_REPLICA\_ERROR\_RUNNING\_QUERY error code, 165  
 ER\_RPL\_REPLICA\_FAILED\_TO\_CREATE\_CHANNEL\_FROM\_CONNECTION error code, 157  
 ER\_RPL\_REPLICA\_FAILED\_TO\_CREATE\_OR\_RECOVER\_INFORMATION\_SCHEMA error code, 161  
 ER\_RPL\_REPLICA\_FAILED\_TO\_INIT\_A\_CONNECTION\_METADATA\_REPOSITORY error code, 156  
 ER\_RPL\_REPLICA\_FAILED\_TO\_INIT\_CONNECTION\_METADATA error code, 165  
 ER\_RPL\_REPLICA\_FAILED\_TO\_INIT\_PARTITIONS\_HASH error code, 184  
 ER\_RPL\_REPLICA\_FILTER\_CREATE\_FAILED error code, 184  
 ER\_RPL\_REPLICA\_FORCING\_TO\_RECONNECT\_IO\_THREAD error code, 164  
 ER\_RPL\_REPLICA\_GENERIC\_MESSAGE error code, 166  
 ER\_RPL\_REPLICA\_GLOBAL\_FILTERS\_COPY\_FAILED error code, 184  
 ER\_RPL\_REPLICA\_INCORRECT\_CHANNEL error code, 180  
 ER\_RPL\_REPLICA\_INSECURE\_CHANGE\_SOURCE error code, 163  
 ER\_RPL\_REPLICA\_IO\_THREAD\_ABORTED\_WAITING\_FOR\_REPLY error code, 164  
 ER\_RPL\_REPLICA\_IO\_THREAD\_CANT\_REGISTER\_ON\_SOURCE error code, 164  
 ER\_RPL\_REPLICA\_IO\_THREAD\_DETECTED\_UNEXPECTED\_EVENT error code, 166  
 ER\_RPL\_REPLICA\_IO\_THREAD\_EXITING error code, 164  
 ER\_RPL\_REPLICA\_IO\_THREAD\_KILLED error code, 164  
 ER\_RPL\_REPLICA\_IO\_THREAD\_STOP\_CMD\_EXEC\_TIMEOUT error code, 321  
 ER\_RPL\_REPLICA\_IO\_THREAD\_WAS\_KILLED error code, 162  
 ER\_RPL\_REPLICA\_MONITOR\_IO\_THREAD\_EXITING error code, 364  
 ER\_RPL\_REPLICA\_MONITOR\_IO\_THREAD\_RECONNECT\_CHANNEL error code, 364  
 ER\_RPL\_REPLICA\_NEW\_C\_M\_NEEDS\_REPOS\_TYPE\_OTHER error code, 166  
 ER\_RPL\_REPLICA\_NEXT\_LOG\_IS\_ACTIVE error code, 166  
 ER\_RPL\_REPLICA\_NEXT\_LOG\_IS\_INACTIVE error code, 166  
 ER\_RPL\_REPLICA\_QUEUE\_EVENT\_FAILED\_INVALID\_CONFIGURATION error code, 166

---

ER_RPL_REPLICA_QUEUE_EVENT_FAILED_INVALID_HOSTNAME error code, 351	ER_RPL_REPLICA_UNSUPPORTED_XA_ROLLBACK_IN_STREAM error code, 158
ER_RPL_REPLICA_READ_INVALID_EVENT_FROM_SOURCE error code, 166	ER_RPL_UNSUPPORTED_UNIGNORABLE_EVENT_IN_STREAM error code, 158
ER_RPL_REPLICA_REPORT_HOST_TOO_LONG error code, 163	ER_RPL_WORKER_CANT_FIND_NEXT_RELAY_LOG error code, 168
ER_RPL_REPLICA_REPORT_PASSWORD_TOO_LONG error code, 163	ER_RPL_WORKER_CANT_READ_RELAY_LOG error code, 168
ER_RPL_REPLICA_REPORT_USER_TOO_LONG error code, 163	ER_RPL_WORKER_ID_IS error code, 155
ER_RPL_REPLICA_RESET_FILTER_OPTIONS error code, 184	ER_RPL_ZOMBIE_ENCOUNTERED error code, 129
ER_RPL_REPLICA_SECONDS_BEHIND_SOURCE_DUBIOUS error code, 163	ER_RUNNING_APPLIER_PREVENTS_SWITCH_GLOBAL_BIN error code, 89
ER_RPL_REPLICA_SKIP_COUNTER_EXECUTED error code, 165	ER_RUN_HOOK_ERROR error code, 64
ER_RPL_REPLICA_SOURCE_UUID_HAS_CHANGED_HOST error code, 390	ER_SAME_NAME_PARTITION error code, 34
ER_RPL_REPLICA_SOURCE_UUID_HAS_NOT_CHANGED error code, 390	ER_SAME_NAME_PARTITION_FIELD error code, 41
ER_RPL_REPLICA_SOURCE_UUID_HOST_PORT_CHANGED error code, 391	ER_SCHEDULER_KILLING error code, 132
ER_RPL_REPLICA_SQL_THREAD_DETECTED_UNEXPECTED_EVENT error code, 351	ER_SCHEDULER_KILLING_FAILED error code, 132
ER_RPL_REPLICA_SQL_THREAD_EXITING error code, 165	ER_SCHEDULER_STOPPED error code, 131
ER_RPL_REPLICA_SQL_THREAD_IO_ERROR_READING_EVENT error code, 166	ER_SCHEDULER_STOPPING_FAILED_TO_CREATE_WORKER error code, 132
ER_RPL_REPLICA_SQL_THREAD_STARTING error code, 165	ER_SCHEDULER_STOPPING_FAILED_TO_GET_EVENT error code, 132
ER_RPL_REPLICA_SQL_THREAD_STARTING_WITH_PROTOCOL error code, 350	ER_SCHEDULER_STOPPING_FAILED_TO_GET_EVENT_SEQUENCE error code, 132
ER_RPL_REPLICA_SQL_THREAD_STOP_CMD_EXECUTION error code, 322	ER_SCHEMA_DIR_CREATE_FAILED error code, 84
ER_RPL_REPLICA_STOPPING_AS_SOURCE_OOM error code, 164	ER_SCHEMA_DIR_EXISTS error code, 84
ER_RPL_REPLICA_USES_CHECKSUM_AND_SOURCE_PLUGIN error code, 162	ER_SCHEMA_DIR_MISSING error code, 84
ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAILED error code, 165	ER_SCHEMA_DIR_UNKNOWN error code, 84
ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAILED error code, 165	ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED error code, 352
ER_RPL_REPO_HAS_GAPS error code, 130	ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR_PLUGIN error code, 352
ER_RPL_REWRITEDB_EMPTY_FROM error code, 138	ER_SCHEMA_READ_ONLY error code, 107
ER_RPL_REWRITEDB_EMPTY_TO error code, 138	ER_SCHEMA_SIZE_OUTGET_KEYS_INVALID_TABLESPACE error code, 111
ER_RPL_REWRITEDB_MISSING_ARROW error code, 138	ER_SDI_OPERATION_FAILED error code, 83
ER_RPL_SERVER_ID_MISSING error code, 162	ER_SDI_OPERATION_FAILED_MISSING_RECORD error code, 105
ER_RPL_SSL_INFO_IN_CONNECTION_METADATA_IGNORED error code, 169	ER_SECONDARY_ENGINE error code, 99
ER_RPL_TRX_DELEGATES_INIT_FAILED error code, 142	ER_SECONDARY_ENGINE_DDL error code, 100
ER_RPL_UNEXPECTED_BEGIN_IN_STREAM error code, 158	ER_SECONDARY_ENGINE_DDL_FAILED error code, 100
ER_RPL_UNEXPECTED_COMMIT_ROLLBACK_OR_XID_ERROR error code, 158	ER_SECONDARY_ENGINE_DDL_FAILED_WITH_ERRNO error code, 100
	ER_SECONDARY_ENGINE_PLUGIN error code, 99
	ER_SECOND_PASSWORD_CANNOT_BE_EMPTY error code, 99
	ER_SECURE_AUTH_VALUE_UNSUPPORTED error code, 134
	ER_SECURE_TRANSPORT_REQUIRED error code, 69
	ER_SEC_FILE_PRIV_ARGUMENT_TOO_LONG error code, 135
	ER_SEC_FILE_PRIV_CANT_ACCESS_DIR error code, 135
	ER_SEC_FILE_PRIV_CANT_STAT error code, 135
	ER_SEC_FILE_PRIV_DIRECTORY_INSECURE error code, 135
	ER_SECONDARY_ENGINE_PLUGIN error code, 99
	ER_SEC_FILE_PRIV_DIRECTORY_PERMISSIONS error code, 135
	ER_SEC_FILE_PRIV_EMPTY error code, 135

---

---

ER\_SEC\_FILE\_PRIV\_IGNORED error code, 135  
 ER\_SEC\_FILE\_PRIV\_NULL error code, 135  
 ER\_SELECT\_REDUCED error code, 18  
 ER\_SEMISYNC\_ADD\_ACK\_TO\_SLOT error code, 199  
 ER\_SEMISYNC\_BINLOG\_REPLY\_IS\_AHEAD error code, 198  
 ER\_SEMISYNC\_BINLOG\_WRITE\_OUT\_OF\_ORDER error code, 197  
 ER\_SEMISYNC\_CLEARED\_ACTIVE\_TRANSACTION\_TIMEOUT error code, 197  
 ER\_SEMISYNC\_CLEARED\_ALL\_ACTIVE\_TRANSACTION\_IDS error code, 197  
 ER\_SEMISYNC\_DISABLED\_ON\_SOURCE error code, 197  
 ER\_SEMISYNC\_EXECUTION\_FAILED\_ON\_SOURCE error code, 200  
 ER\_SEMISYNC\_FAILED\_REGISTER\_REPLICA\_TO\_REPLICAS error code, 199  
 ER\_SEMISYNC\_FAILED\_TO\_ALLOCATE\_TRX\_NODE error code, 196  
 ER\_SEMISYNC\_FAILED\_TO\_INSERT\_TRX\_NODE error code, 198  
 ER\_SEMISYNC\_FAILED\_TO\_START\_ACK\_RECEIVER\_THREAD error code, 199  
 ER\_SEMISYNC\_FAILED\_TO\_STOP\_ACK\_RECEIVER\_THREAD error code, 201  
 ER\_SEMISYNC\_FAILED\_TO\_WAIT\_ON\_DUMP\_SOCKET error code, 199  
 ER\_SEMISYNC\_FORCED\_SHUTDOWN error code, 197  
 ER\_SEMISYNC\_FUNCTION\_CALLED\_TWICE error code, 197  
 ER\_SEMISYNC\_INIT\_WAIT\_POS error code, 198  
 ER\_SEMISYNC\_INSERT\_LOG\_INFO\_IN\_ENTRY error code, 197  
 ER\_SEMISYNC\_MISSING\_MAGIC\_NO\_FOR\_SEMISYNC\_PACKET error code, 200  
 ER\_SEMISYNC\_MOVE\_BACK\_WAIT\_POS error code, 198  
 ER\_SEMISYNC\_NOT\_SUPPORTED\_BY\_SOURCE error code, 200  
 ER\_SEMISYNC\_NO\_SPACE\_IN\_THE\_PKT error code, 198  
 ER\_SEMISYNC\_PROBE\_LOG\_INFO\_IN\_ENTRY error code, 197  
 ER\_SEMISYNC\_RECEIVED\_ACK\_IS\_SMALLER error code, 199  
 ER\_SEMISYNC\_REPLICA\_NET\_FLUSH\_REPLY\_FAILED error code, 200  
 ER\_SEMISYNC\_REPLICA\_REPLY error code, 200  
 ER\_SEMISYNC\_REPLICA\_REPLY\_WITH\_BINLOG\_INFO error code, 200  
 ER\_SEMISYNC\_REPLICA\_SEND\_REPLY\_FAILED error code, 200  
 ER\_SEMISYNC\_REPLICA\_SET\_FAILED error code, 200  
 ER\_SEMISYNC\_REPLICA\_START error code, 200  
 ER\_SEMISYNC\_REPLY\_BINLOG\_FILE\_TOO\_LARGE error code, 197  
 ER\_SEMISYNC\_REPLY\_MAGIC\_NO\_ERROR error code, 197  
 ER\_SEMISYNC\_REPLY\_PKT\_LENGTH\_TOO\_SMALL error code, 197  
 ER\_SEMISYNC\_RPL\_ENABLED\_ON\_SOURCE error code, 197  
 ER\_SEMISYNC\_RPL\_INIT\_FOR\_TRX error code, 196  
 ER\_SEMISYNC\_RPL\_SWITCHED\_OFF error code, 198  
 ER\_SEMISYNC\_RPL\_SWITCHED\_ON error code, 198  
 ER\_SEMISYNC\_SERVER\_REPLY error code, 197  
 ER\_SEMISYNC\_SOCKET\_FD\_TOO\_LARGE error code, 200  
 ER\_SEMISYNC\_SOURCE\_FAILED\_ON\_NET\_FLUSH error code, 199  
 ER\_SEMISYNC\_SOURCE\_GOT\_REPLY\_AT\_POS error code, 198  
 ER\_SEMISYNC\_SOURCE\_OOM error code, 197  
 ER\_SEMISYNC\_SOURCE\_SIGNAL\_ALL\_WAITING\_THREADS error code, 198  
 ER\_SEMISYNC\_SOURCE\_TRX\_WAIT\_POS error code, 198  
 ER\_SEMISYNC\_STARTING\_ACK\_RECEIVER\_THD error code, 199  
 ER\_SEMISYNC\_START\_BINLOG\_DUMP\_TO\_REPLICA error code, 199  
 ER\_SEMISYNC\_STOPPING\_ACK\_RECEIVER\_THREAD error code, 199  
 ER\_SEMISYNC\_STOP\_BINLOG\_DUMP\_TO\_REPLICA error code, 199  
 ER\_SEMISYNC\_SYNC\_HEADER\_UPDATE\_INFO error code, 198  
 ER\_SEMISYNC\_TRACE\_ENTER\_FUNC error code, 196  
 ER\_SEMISYNC\_TRACE\_EXIT error code, 196  
 ER\_SEMISYNC\_TRACE\_EXIT\_WITH\_BOOL\_EXIT\_CODE error code, 196  
 ER\_SEMISYNC\_TRACE\_EXIT\_WITH\_INT\_EXIT\_CODE error code, 196  
 ER\_SEMISYNC\_TRX\_SKIPPED\_AT\_POS error code, 199  
 ER\_SEMISYNC\_UNREGISTERED\_REPLICATOR error code, 200  
 ER\_SEMISYNC\_UNREGISTER\_BINLOG\_STORAGE\_OBSERVER error code, 200  
 ER\_SEMISYNC\_UNREGISTER\_BINLOG\_TRANSMIT\_OBSERVER error code, 200  
 ER\_SEMISYNC\_UNREGISTER\_TRX\_OBSERVER\_FAILED error code, 199  
 ER\_SEMISYNC\_UPDATE\_EXISTING\_REPLICA\_ACK error code, 199  
 ER\_SEMISYNC\_WAIT\_FOR\_BINLOG\_TIMEDOUT error code, 198  
 ER\_SEMISYNC\_WAIT\_TIME\_ASSESSMENT\_FOR\_COMMIT\_TRX error code, 198



---

ER\_SEMISYNC\_WAIT\_TIME\_FOR\_BINLOG\_SENT error code, 198  
 ER\_SERVERID\_TOO\_LARGE error code, 141  
 ER\_SERVER\_ACL\_TABLE\_ERROR error code, 326  
 ER\_SERVER\_BINLOG\_MASTER\_KEY\_RECOVERY\_OUT\_OF\_SYNC error code, 341  
 ER\_SERVER\_BINLOG\_MASTER\_KEY\_ROTATION\_FAILED error code, 341  
 ER\_SERVER\_BINLOG\_UNSAFE\_SYSTEM\_FUNCTION error code, 344  
 ER\_SERVER\_CANNOT\_LOAD\_FROM\_TABLE\_V2 error code, 325  
 ER\_SERVER\_CANT\_OPEN\_FILE error code, 325  
 ER\_SERVER\_CERT\_VERIFY\_FAILED error code, 397  
 ER\_SERVER\_COL\_COUNT\_DOESNT\_MATCH\_CORRUPTED error code, 326  
 ER\_SERVER\_COL\_COUNT\_DOESNT\_MATCH\_PLEASE\_CREATE\_THE\_INDEX error code, 326  
 ER\_SERVER\_COST\_FAILED\_TO\_READ error code, 157  
 ER\_SERVER\_COST\_INVALID\_COST\_CONSTANT error code, 157  
 ER\_SERVER\_COST\_UNKNOWN\_COST\_CONSTANT error code, 157  
 ER\_SERVER\_DISK\_FULL\_NOWAIT error code, 325  
 ER\_SERVER\_DOWNGRADE\_FROM\_VERSION error code, 395  
 ER\_SERVER\_DOWNGRADE\_STATUS error code, 395  
 ER\_SERVER\_FILE\_NOT\_FOUND error code, 325  
 ER\_SERVER\_FILE\_USED error code, 325  
 ER\_SERVER\_GTID\_UNSAFE\_CREATE\_DROP\_TEMP\_TABLE\_IN\_SBR error code, 332  
 ER\_SERVER\_HANDLER\_ERROR error code, 325  
 ER\_SERVER\_INIT\_COMPILED\_IN\_COMMANDS error code, 192  
 ER\_SERVER\_ISNT\_AVAILABLE error code, 69  
 ER\_SERVER\_NET\_PACKET\_TOO\_LARGE error code, 325  
 ER\_SERVER\_NEW\_ABORTING\_CONNECTION error code, 325  
 ER\_SERVER\_NOT\_FORM\_FILE error code, 325  
 ER\_SERVER\_NO\_SESSION\_TO\_SEND\_TO error code, 325  
 ER\_SERVER\_NO\_SYSTEM\_TABLE\_ACCESS error code, 325  
 ER\_SERVER\_OFFLINE\_MODE error code, 59  
 ER\_SERVER\_OUTOFMEMORY error code, 182  
 ER\_SERVER\_OUT\_OF\_RESOURCES error code, 182  
 ER\_SERVER\_OUT\_OF\_SORTMEMORY error code, 325  
 ER\_SERVER\_RECORD\_FILE\_FULL error code, 325  
 ER\_SERVER\_REPLICA\_AM\_INIT\_REPOSITORY error code, 324  
 ER\_SERVER\_REPLICA\_CM\_INIT\_REPOSITORY error code, 324  
 ER\_SERVER\_REPLICA\_CONVERSION\_FAILED error code, 326  
 ER\_SERVER\_REPLICA\_IGNORED\_TABLE error code, 326  
 ER\_SERVER\_REPLICA\_INIT\_QUERY\_FAILED error code, 326  
 ER\_SERVER\_REPLICATION\_ENCRYPTION\_FAILED\_TO\_ENCRYPT error code, 338  
 ER\_SERVER\_REPLICATION\_ENCRYPTION\_FAILED\_TO\_FETCH\_KEY error code, 335  
 ER\_SERVER\_RPL\_ENCRYPTION\_FAILED\_TO\_GENERATE error code, 335  
 ER\_SERVER\_RPL\_ENCRYPTION\_FAILED\_TO\_REMOVE\_KEY error code, 335  
 ER\_SERVER\_RPL\_ENCRYPTION\_FAILED\_TO\_ROTATE\_LOG error code, 335  
 ER\_SERVER\_RPL\_ENCRYPTION\_FAILED\_TO\_STORE\_KEY error code, 335  
 ER\_SERVER\_RPL\_ENCRYPTION\_HEADER\_ERROR error code, 335  
 ER\_SERVER\_RPL\_ENCRYPTION\_IGNORE\_ROTATE\_MASTER error code, 336  
 ER\_SERVER\_RPL\_ENCRYPTION\_KEYRING\_INVALID\_KEY error code, 335  
 ER\_SERVER\_RPL\_ENCRYPTION\_KEY\_EXISTS\_UNEXPECTED error code, 335  
 ER\_SERVER\_RPL\_ENCRYPTION\_KEY\_NOT\_FOUND error code, 335  
 ER\_SERVER\_RPL\_ENCRYPTION\_MASTER\_KEY\_RECOVERY\_FAILED error code, 336  
 ER\_SERVER\_RPL\_ENCRYPTION\_UNABLE\_TO\_INITIALIZE error code, 336  
 ER\_SERVER\_RPL\_ENCRYPTION\_UNABLE\_TO\_ROTATE\_MASTER error code, 336  
 ER\_SERVER\_SHUTDOWN error code, 6  
 ER\_SERVER\_SHUTDOWN\_COMPLETE error code, 181  
 ER\_SERVER\_SHUTDOWN\_INFO error code, 328  
 ER\_SERVER\_SOURCE\_FATAL\_ERROR\_READING\_BINLOG error code, 324  
 ER\_SERVER\_STARTUP\_ADMIN\_INTERFACE error code, 336  
 ER\_SERVER\_STARTUP\_MSG error code, 182  
 ER\_SERVER\_TABLE\_CHECK\_FAILED error code, 326  
 ER\_SERVER\_TEST\_MESSAGE error code, 326  
 ER\_SERVER\_UNKNOWN\_SYSTEM\_VARIABLE error code, 325  
 ER\_SERVER\_UPGRADE\_CHECKING\_DB error code, 343  
 ER\_SERVER\_UPGRADE\_EMPTY\_SYS error code, 343  
 ER\_SERVER\_UPGRADE\_FAILED error code, 342  
 ER\_SERVER\_UPGRADE\_FROM\_VERSION error code, 339  
 ER\_SERVER\_UPGRADE\_HELP\_TABLE\_STATUS error code, 344  
 ER\_SERVER\_UPGRADE\_INFO\_FILE error code, 343  
 ER\_SERVER\_UPGRADE\_MYSQL\_TABLES error code, 343

---

---

ER\_SERVER\_UPGRADE\_NO\_SYS\_VERSION error code, 343  
 ER\_SERVER\_UPGRADE\_OFF error code, 342  
 ER\_SERVER\_UPGRADE\_PENDING error code, 342  
 ER\_SERVER\_UPGRADE\_REPAIR\_REQUIRED error code, 342  
 ER\_SERVER\_UPGRADE\_REPAIR\_STATUS error code, 343  
 ER\_SERVER\_UPGRADE\_SKIP error code, 342  
 ER\_SERVER\_UPGRADE\_STATUS error code, 342  
 ER\_SERVER\_UPGRADE\_SYSTEM\_TABLES error code, 343  
 ER\_SERVER\_UPGRADE\_SYS\_SCHEMA error code, 343  
 ER\_SERVER\_UPGRADE\_SYS\_SCHEMA\_OBJECT\_COUNT error code, 343  
 ER\_SERVER\_UPGRADE\_SYS\_SCHEMA\_OUTDATED error code, 343  
 ER\_SERVER\_UPGRADE\_SYS\_SCHEMA\_UP\_TO\_DATE error code, 343  
 ER\_SERVER\_UPGRADE\_SYS\_VERSION\_EMPTY error code, 343  
 ER\_SERVER\_UPGRADE\_VERSION\_NOT\_SUPPORTED error code, 339  
 ER\_SERVER\_WARN\_DEPRECATED error code, 341  
 ER\_SERVER\_WRONG\_VALUE\_FOR\_VAR error code, 332  
 ER\_SESSION\_WAS\_KILLED error code, 69  
 ER\_SETNS\_FAILED error code, 344  
 ER\_SET\_CONSTANTS\_ONLY error code, 16  
 ER\_SET\_EVENT\_FAILED error code, 328  
 ER\_SET\_PASSWORD\_AUTH\_PLUGIN\_ERROR error code, 116  
 ER\_SET\_STATEMENT\_CANNOT\_INVOKE\_FUNCTION error code, 49  
 ER\_SE\_TYPECODE\_CONFLICT error code, 144  
 ER\_SHA256\_PASSWORD\_SECOND\_PASSWORD\_USED error code, 336  
 ER\_SHAPE\_PREDICTION\_UDF error code, 118  
 ER\_SHARED\_TABLESPACE\_USED\_BY\_PARTITIONED\_TABLE error code, 332  
 ER\_SHA\_PWD\_AUTH\_REQUIRES\_RSA\_OR\_SSL error code, 205  
 ER\_SHA\_PWD\_FAILED\_TO\_GENERATE\_MULTI\_ROUND\_HASH error code, 205  
 ER\_SHA\_PWD\_FAILED\_TO\_PARSE\_AUTH\_STRING error code, 205  
 ER\_SHA\_PWD\_RSA\_KEY\_TOO\_LONG error code, 205  
 ER\_SHA\_PWD\_SALT\_FOR\_USER\_CORRUPT error code, 206  
 ER\_SHUTDOWN\_COMPLETE error code, 8  
 ER\_SHUTTING\_DOWN\_REPLICA\_THREADS error code, 136  
 ER\_SIGNAL\_BAD\_CONDITION\_TYPE error code, 40  
 ER\_SIGNAL\_EXCEPTION error code, 40  
 ER\_SIGNAL\_NOT\_FOUND error code, 40  
 ER\_SIGNAL\_WARN error code, 40  
 ER\_SIMULATED\_INJECTION\_ERROR error code, 122  
 ER\_SIZE\_OVERFLOW\_ERROR error code, 35  
 ER\_SKIP\_UPDATING\_METADATA\_IN\_SE\_RO\_MODE error code, 188  
 ER\_SLOW\_LOG\_MODE\_IGNORED\_WHEN\_NOT\_LOGGING\_TO error code, 93  
 ER\_SOURCE error code, 15  
 ER\_SOURCE\_DELAY\_VALUE\_OUT\_OF\_RANGE error code, 46  
 ER\_SOURCE\_FATAL\_ERROR\_READING\_BINLOG error code, 18  
 ER\_SOURCE\_HAS\_PURGED\_REQUIRED\_GTIDS error code, 50  
 ER\_SOURCE\_NET\_READ error code, 15  
 ER\_SOURCE\_NET\_WRITE error code, 15  
 ER\_SPATIAL\_CANT\_HAVE\_NULL error code, 19  
 ER\_SPATIAL\_FUNCTIONAL\_INDEX error code, 90  
 ER\_SPATIAL\_MUST\_HAVE\_GEOM\_COL error code, 43  
 ER\_SPATIAL\_UNIQUE\_INDEX error code, 87  
 ER\_SPECIFIC\_ACCESS\_DENIED error code, 124  
 ER\_SPECIFIC\_ACCESS\_DENIED\_ERROR error code, 17  
 ER\_SPVAR\_NONINTEGER\_TYPE error code, 109  
 ER\_SP\_ALREADY\_EXISTS error code, 22  
 ER\_SP\_BADRETURN error code, 22  
 ER\_SP\_BADSELECT error code, 22  
 ER\_SP\_BADSTATEMENT error code, 22  
 ER\_SP\_BAD\_CURSOR\_QUERY error code, 23  
 ER\_SP\_BAD\_CURSOR\_SELECT error code, 23  
 ER\_SP\_BAD\_SQLSTATE error code, 27  
 ER\_SP\_BAD\_VAR\_SHADOW error code, 30  
 ER\_SP\_CANT ALTER error code, 23  
 ER\_SP\_CANT\_SET\_AUTOCOMMIT error code, 30  
 ER\_SP\_CASE\_NOT\_FOUND error code, 24  
 ER\_SP\_CURSOR\_MISMATCH error code, 22  
 ER\_SP\_CURSOR\_AFTER\_HANDLER error code, 24  
 ER\_SP\_CURSOR\_ALREADY\_OPEN error code, 23  
 ER\_SP\_CURSOR\_MISMATCH error code, 23  
 ER\_SP\_CURSOR\_NOT\_OPEN error code, 23  
 ER\_SP\_DOES\_NOT\_EXIST error code, 22  
 ER\_SP\_DROP\_FAILED error code, 22  
 ER\_SP\_DUP\_COND error code, 23  
 ER\_SP\_DUP\_CURS error code, 23  
 ER\_SP\_DUP\_HANDLER error code, 28  
 ER\_SP\_DUP\_PARAM error code, 23  
 ER\_SP\_DUP\_VAR error code, 23  
 ER\_SP\_FETCH\_NO\_DATA error code, 23  
 ER\_SP\_LABEL\_MISMATCH error code, 22  
 ER\_SP\_LABEL\_REDEFINE error code, 22  
 ER\_SP\_LILABEL\_MISMATCH error code, 22  
 ER\_SP\_LOAD\_FAILED error code, 73  
 ER\_SP\_NORETURN error code, 23  
 ER\_SP\_NORETURNEND error code, 23  
 ER\_SP\_NOT\_VAR\_ARG error code, 28  
 ER\_SP\_NO\_AGGREGATE error code, 31  
 ER\_SP\_NO ALTER LANGUAGE error code, 122

---

ER\_SP\_NO\_DROP\_SP error code, 25  
 ER\_SP\_NO\_RECURSION error code, 28  
 ER\_SP\_NO\_RECURSIVE\_CREATE error code, 21  
 ER\_SP\_NO\_RESET error code, 28  
 ER\_SP\_RECURSION\_LIMIT error code, 30  
 ER\_SP\_STORE\_FAILED error code, 22  
 ER\_SP\_SUBSELECT\_NYI error code, 23  
 ER\_SP\_UNDECLARED\_VAR error code, 23  
 ER\_SP\_UNINIT\_VAR error code, 22  
 ER\_SP\_VARCOND\_AFTER\_CURSHNDLR error code, 24  
 ER\_SP\_WRONG\_NAME error code, 30  
 ER\_SP\_WRONG\_NO\_OF\_ARGS error code, 22  
 ER\_SP\_WRONG\_NO\_OF\_FETCH\_ARGS error code, 23  
 ER\_SQLTHREAD\_WITH\_SECURE\_REPLICA error code, 48  
 ER\_SQL\_AUTHOR\_DEFAULT\_ROLES\_FAIL error code, 144  
 ER\_SQL\_HA\_READ\_FAILED error code, 142  
 ER\_SQL\_MODE\_MERGED error code, 67  
 ER\_SQL\_MODE\_MERGED\_WITH\_STRICT\_MODE error code, 181  
 ER\_SQL\_REPLICA\_SKIP\_COUNTER\_USED\_WITH\_GTID error code, 109  
 ER\_SQL\_USER\_TABLE\_ALTER\_WARNING error code, 144  
 ER\_SQL\_USER\_TABLE\_CREATE\_WARNING error code, 144  
 ER\_SRS\_ATTRIBUTE\_STRING\_TOO\_LONG error code, 87  
 ER\_SRS\_GEOGCS\_INVALID\_AXES error code, 88  
 ER\_SRS\_ID\_ALREADY\_EXISTS error code, 86  
 ER\_SRS\_INVALID\_ANGULAR\_UNIT error code, 88  
 ER\_SRS\_INVALID\_CHARACTER\_IN\_ATTRIBUTE error code, 87  
 ER\_SRS\_INVALID\_HEIGHT error code, 118  
 ER\_SRS\_INVALID\_INVERSE\_FLATTENING error code, 88  
 ER\_SRS\_INVALID\_LATITUDE\_OF\_ORIGIN error code, 117  
 ER\_SRS\_INVALID\_LATITUDE\_POLAR\_STERE\_VAR\_A error code, 118  
 ER\_SRS\_INVALID\_LONGITUDE\_OF\_ORIGIN error code, 117  
 ER\_SRS\_INVALID\_PRIME\_MERIDIAN error code, 88  
 ER\_SRS\_INVALID\_SCALING error code, 118  
 ER\_SRS\_INVALID\_SEMI\_MAJOR\_AXIS error code, 88  
 ER\_SRS\_INVALID\_ZONE\_WIDTH error code, 118  
 ER\_SRS\_MISSING\_MANDATORY\_ATTRIBUTE error code, 86  
 ER\_SRS\_MULTIPLE\_ATTRIBUTE\_DEFINITIONS error code, 86  
 ER\_SRS\_NAME\_CANT\_BE\_EMPTY\_OR\_WHITESPACE error code, 86  
 ER\_SRS\_NOT\_CARTESIAN error code, 73  
 ER\_SRS\_NOT\_CARTESIAN\_UNDEFINED error code, 74  
 ER\_SRS\_NOT\_FOUND error code, 75  
 ER\_SRS\_NOT\_GEOGRAPHIC error code, 87  
 ER\_SRS\_ORGANIZATION\_CANT\_BE\_EMPTY\_OR\_WHITESPACE error code, 86  
 ER\_SRS\_PARSE\_ERROR error code, 73  
 ER\_SRS\_PROJ\_PARAMETER\_MISSING error code, 73  
 ER\_SRS\_UNUSED\_PROJ\_PARAMETER\_PRESENT error code, 117  
 ER\_SRV\_END error code, 397  
 ER\_SRV\_INIT\_END error code, 397  
 ER\_SRV\_INIT\_START error code, 397  
 ER\_SRV\_START error code, 397  
 ER\_SR\_BOGUS\_VALUE error code, 142  
 ER\_SR\_INVALID\_CONTEXT error code, 142  
 ER\_SSL\_FIPS\_MODE\_ERROR error code, 206  
 ER\_SSL\_LIBRARY\_ERROR error code, 133  
 ER\_SSL\_MEMORY\_INSTRUMENTATION\_INIT\_FAILED error code, 333  
 ER\_SSL\_TRYING\_DATADIR\_DEFAULTS error code, 140  
 ER\_STACK\_OVERFLOW error code, 140  
 ER\_STACK\_BACKTRACE error code, 386  
 ER\_STACK\_OVERRUN error code, 11  
 ER\_STACK\_OVERRUN\_NEED\_MORE error code, 29  
 ER\_STARTING\_AS error code, 136  
 ER\_STARTING\_INIT error code, 328  
 ER\_STARTING\_REPLICA\_MONITOR\_IO\_THREAD error code, 109  
 ER\_STARTUP error code, 27  
 ER\_START\_REPLICA\_CHANNEL\_INVALID\_CONFIGURATION error code, 124  
 ER\_START\_REPLICA\_CHANNEL\_INVALID\_CONFIGURATION error code, 399  
 ER\_STATEMENT\_NOT\_ALLOWED\_AFTER\_START\_TRANSACTION error code, 106  
 ER\_STD\_BAD\_ALLOC\_ERROR error code, 60  
 ER\_STD\_DOMAIN\_ERROR error code, 60  
 ER\_STD\_INVALID\_ARGUMENT error code, 60  
 ER\_STD\_LENGTH\_ERROR error code, 60  
 ER\_STD\_LOGIC\_ERROR error code, 61  
 ER\_STD\_OUT\_OF\_RANGE\_ERROR error code, 60  
 ER\_STD\_OVERFLOW\_ERROR error code, 60  
 ER\_STD\_RANGE\_ERROR error code, 60  
 ER\_STD\_REGEX\_ERROR error code, 97  
 ER\_STD\_RUNTIME\_ERROR error code, 61  
 ER\_STD\_UNDERFLOW\_ERROR error code, 61  
 ER\_STD\_UNKNOWN\_EXCEPTION error code, 61  
 ER\_STMT\_CACHE\_FULL error code, 44  
 ER\_STMT\_HAS\_NO\_OPEN\_CURSOR error code, 28  
 ER\_STMT\_NOT\_ALLOWED\_IN\_SF\_OR\_TRG error code, 24  
 ER\_STOP\_REPLICA\_IO\_THREAD\_DISK\_SPACE error code, 206  
 ER\_STOP\_REPLICA\_IO\_THREAD\_TIMEOUT error code, 56

---

---

ER\_STOP\_REPLICA\_MONITOR\_IO\_THREAD\_TIMEOUT error code, 109  
 ER\_STOP\_REPLICA\_SQL\_THREAD\_TIMEOUT error code, 56  
 ER\_STORAGE\_ENGINE\_NOT\_LOADED error code, 57  
 ER\_STORED\_FUNCTION\_PREVENTS\_SWITCH\_BINLOG\_FORMAT error code, 43  
 ER\_STORED\_FUNCTION\_PREVENTS\_SWITCH\_BINLOG\_FORMAT error code, 36  
 ER\_STORED\_FUNCTION\_PREVENTS\_SWITCH\_SQL\_LOG\_BIN error code, 44  
 ER\_SUBPARTITION\_ERROR error code, 33  
 ER\_SUBPARTITION\_NAME error code, 40  
 ER\_SUBQUERY\_NO\_1\_ROW error code, 18  
 ER\_SUBQUERY\_TRANSFORM\_REJECTED error code, 106  
 ER\_SUPPORTED\_ONLY\_WITH\_HYPERGRAPH error code, 124  
 ER\_SWITCH\_TMP\_ENGINE error code, 77  
 ER\_SYNTAX\_ERROR error code, 13  
 ER\_SYSTEMD\_NOTIFY\_CONNECT\_FAILED error code, 246  
 ER\_SYSTEMD\_NOTIFY\_DEBUG error code, 385  
 ER\_SYSTEMD\_NOTIFY\_PATH\_TOO\_LONG error code, 246  
 ER\_SYSTEMD\_NOTIFY\_WRITE\_FAILED error code, 246  
 ER\_SYSTEM\_SCHEMA\_NOT\_FOUND error code, 129  
 ER\_SYSTEM\_TABLES\_NOT\_SUPPORTED\_BY\_STORAGE\_ENGINE error code, 182  
 ER\_SYSTEM\_TABLE\_NOT\_TRANSACTIONAL error code, 169  
 ER\_SYSTEM\_VIEW\_INIT\_FAILED error code, 183  
 ER\_SYSVAR\_CHANGE\_DURING\_QUERY error code, 101  
 ER\_SYS\_VAR\_COMPONENT\_FAILED\_TO\_MAKE\_VARIABLE\_DYNAMIC error code, 206  
 ER\_SYS\_VAR\_COMPONENT\_FAILED\_TO\_PARSE\_VARIABLE\_OPTIONS error code, 206  
 ER\_SYS\_VAR\_COMPONENT\_OOM error code, 206  
 ER\_SYS\_VAR\_COMPONENT\_UNKNOWN\_VARIABLE\_TYPE error code, 206  
 ER\_SYS\_VAR\_COMPONENT\_VARIABLE\_SET\_READ\_ONLY error code, 206  
 ER\_SYS\_VAR\_DEREGISTRATION error code, 393  
 ER\_SYS\_VAR\_NOT\_FOUND error code, 329  
 ER\_SYS\_VAR\_REGISTRATION error code, 393  
 ER\_TABLEACCESS\_DENIED\_ERROR error code, 12  
 ER\_TABLENAME\_NOT\_ALLOWED\_HERE error code, 18  
 ER\_TABLESPACE\_AUTO\_EXTEND\_ERROR error code, 35  
 ER\_TABLESPACE\_CANNOT\_BE\_DECRYPTED error code, 95  
 ER\_TABLESPACE\_CANNOT\_BE\_ENCRYPTED error code, 95  
 ER\_TABLESPACE\_CANNOT\_ENCRYPT error code, 70  
 ER\_TABLESPACE\_DISCARDED error code, 52  
 ER\_TABLESPACE\_DUP\_FILENAME error code, 79  
 ER\_TABLESPACE\_ENGINE\_MISMATCH error code, 82  
 ER\_TABLESPACE\_EXISTS error code, 52  
 ER\_TABLESPACE\_IS\_NOT\_EMPTY error code, 66  
 ER\_TABLESPACE\_MISSING error code, 52  
 ER\_TABLESPACE\_MISSING\_WITH\_NAME error code, 52  
 ER\_TABLESPACE\_TYPE\_UNKNOWN error code, 96  
 ER\_TABLES\_DIFFERENT\_METADATA error code, 47  
 ER\_TABLE\_CANT\_HANDLE\_AUTO\_INCREMENT error code, 13  
 ER\_TABLE\_CANT\_HANDLE\_BLOB error code, 13  
 ER\_TABLE\_CANT\_HANDLE\_FT error code, 16  
 ER\_TABLE\_CANT\_HANDLE\_SPKEYS error code, 31  
 ER\_TABLE\_CHECK\_INTACT error code, 141  
 ER\_TABLE\_CORRUPT error code, 56  
 ER\_TABLE\_CREATED\_WITH\_DIFFERENT\_VERSION error code, 152  
 ER\_TABLE\_DEF\_CHANGED error code, 28  
 ER\_TABLE\_EXISTS\_ERROR error code, 6  
 ER\_TABLE\_HAS\_NO\_FT error code, 48  
 ER\_TABLE\_INCOMPATIBLE\_DECIMAL\_FIELD error code, 151  
 ER\_TABLE\_INCOMPATIBLE\_YEAR\_FIELD error code, 151  
 ER\_TABLE\_IN\_FK\_CHECK error code, 46  
 ER\_TABLE\_IN\_SHARED\_TABLESPACE error code, 118  
 ER\_TABLE\_IN\_SYSTEM\_TABLESPACE error code, 52  
 ER\_TABLE\_MUST\_HAVE\_A\_VISIBLE\_COLUMN error code, 110  
 ER\_TABLE\_MUST\_HAVE\_COLUMNS error code, 10  
 ER\_TABLE\_NOT\_FOUND error code, 40  
 ER\_TABLE\_NAME\_CAUSES\_TOO\_LONG\_PATH error code, 110  
 ER\_TABLE\_OPTIONS error code, 110  
 ER\_TABLE\_NAME\_IN\_UPPER\_CASE\_NOT\_ALLOWED error code, 352  
 ER\_TABLE\_NAME\_IN\_UPPER\_CASE\_NOT\_ALLOWED\_FOR\_FK error code, 352  
 ER\_TABLE\_NEEDS\_DUMP\_UPGRADE error code, 193  
 ER\_TABLE\_NEEDS\_REBUILD error code, 44  
 ER\_TABLE\_NEEDS\_UPGRADE error code, 30  
 ER\_TABLE\_NOT\_EMPTY error code, 118  
 ER\_TABLE\_NOT\_LOCKED error code, 9  
 ER\_TABLE\_NOT\_LOCKED\_FOR\_WRITE error code, 9  
 ER\_TABLE\_NO\_PRIMARY\_KEY error code, 118  
 ER\_TABLE\_REFERENCED error code, 71  
 ER\_TABLE\_SCHEMA\_MISMATCH error code, 52  
 ER\_TABLE\_UPGRADE\_REQUIRED error code, 182  
 ER\_TABLE\_VALUE\_CONSTRUCTOR\_CANNOT\_HAVE\_DEFAULT error code, 103

---

ER\_TABLE\_VALUE\_CONSTRUCTOR\_MUST\_HAVE\_COLUMNS error code, 103  
 ER\_TABLE\_WITHOUT\_PK error code, 89  
 ER\_TABLE\_WRONG\_KEY\_DEFINITION error code, 152  
 ER\_TARGET\_TABLESPACE\_UNENCRYPTED error code, 96  
 ER\_TC\_BAD\_MAGIC\_IN\_TC\_LOG error code, 160  
 ER\_TC\_CANT\_AUTO\_RECOVER\_WITH\_TC\_HEURISTIC error code, 160  
 ER\_TC\_HEURISTIC\_RECOVERY\_FAILED error code, 161  
 ER\_TC\_HEURISTIC\_RECOVERY\_MODE error code, 161  
 ER\_TC\_NEED\_N\_SE\_SUPPORTING\_2PC\_FOR\_RECOVERY error code, 160  
 ER\_TC\_RECOVERING\_AFTER\_CRASH\_USING error code, 160  
 ER\_TC\_RECOVERY\_FAILED\_THESE\_ARE\_YOUR\_OPTIONS error code, 161  
 ER\_TC\_RESTART\_WITHOUT\_TC\_HEURISTIC\_RECOVERY error code, 161  
 ER\_TELEMETRY\_ERROR error code, 397  
 ER\_TELEMETRY\_INFO error code, 397  
 ER\_TELEMETRY\_WARNING error code, 397  
 ER\_TEMPORARY\_NAME error code, 40  
 ER\_TEMP\_FILE\_WRITE\_FAILURE error code, 56  
 ER\_TEMP\_TABLE\_PREVENTS\_SWITCH\_GLOBAL\_BINDEX error code, 89  
 ER\_TEMP\_TABLE\_PREVENTS\_SWITCH\_SESSION\_BINLOG error code, 89  
 ER\_TEXTFILE\_NOT\_READABLE error code, 8  
 ER\_TF\_FORBIDDEN\_JOIN\_TYPE error code, 83  
 ER\_TF\_MUST\_HAVE\_ALIAS error code, 83  
 ER\_THE\_USER\_ABIDES error code, 138  
 ER\_THREAD\_HANDLING\_OOM error code, 134  
 ER\_THREAD\_POOL\_ALGORITHM\_INVALID error code, 194  
 ER\_THREAD\_POOL\_BUFFER\_TOO\_SMALL error code, 195  
 ER\_THREAD\_POOL\_CANNOT\_REGISTER\_DYNAMIC\_FUNCTION error code, 385  
 ER\_THREAD\_POOL\_CANNOT\_SET\_THREAD\_SPECIFIC\_ERROR error code, 195  
 ER\_THREAD\_POOL\_CONNECTION\_REPORT error code, 394  
 ER\_THREAD\_POOL\_CON\_HANDLER\_INIT\_FAILED error code, 195  
 ER\_THREAD\_POOL\_DEDICATED\_LISTENERS\_INVALID error code, 379  
 ER\_THREAD\_POOL\_FAILED\_PROCESS\_CONNECT\_EVENT error code, 195  
 ER\_THREAD\_POOL\_FAILED\_TO\_CREATE\_CONNECT\_HANDLER error code, 195  
 ER\_THREAD\_POOL\_FAILED\_TO\_CREATE\_POOL error code, 195  
 ER\_THREAD\_POOL\_FAILED\_TO\_CREATE\_THD\_AND\_ABORT error code, 195  
 ER\_THREAD\_POOL\_IDLE\_CONNECTION\_CLOSED error code, 390  
 ER\_THREAD\_POOL\_INIT\_FAILED error code, 195  
 ER\_THREAD\_POOL\_INVALID\_PRIO\_KICKUP\_TIMER error code, 194  
 ER\_THREAD\_POOL\_INVALID\_STALL\_LIMIT error code, 194  
 ER\_THREAD\_POOL\_LOW\_LEVEL\_REARM\_FAILED error code, 195  
 ER\_THREAD\_POOL\_MAX\_UNUSED\_THREADS\_INVALID error code, 195  
 ER\_THREAD\_POOL\_NOT\_SUPPORTED\_ON\_PLATFORM error code, 194  
 ER\_THREAD\_POOL\_PFS\_TABLES\_ADD\_FAILED error code, 335  
 ER\_THREAD\_POOL\_PFS\_TABLES\_INIT\_FAILED error code, 334  
 ER\_THREAD\_POOL\_PLUGIN\_STARTED error code, 335  
 ER\_THREAD\_POOL\_QUERY\_THREADS\_PER\_GROUP\_INVALID error code, 387  
 ER\_THREAD\_POOL\_QUERY\_THRS\_PER\_GRP\_EXCEEDS\_THREADS error code, 387  
 ER\_THREAD\_POOL\_RATE\_LIMITED\_ERROR\_MSGS error code, 195  
 ER\_THREAD\_POOL\_SIZE\_TOO\_HIGH error code, 194  
 ER\_THREAD\_POOL\_SIZE\_TOO\_LOW error code, 194  
 ER\_THREAD\_POOL\_SYSVAR\_CHANGE error code, 386  
 ER\_THREAD\_PRIORITY\_IGNORED error code, 180  
 ER\_THREAD\_STILL\_ALIVE error code, 398  
 ER\_TLS\_CONFIGURATION\_REUSED error code, 358  
 ER\_TLS\_CONFIGURED\_FOR\_CHANNEL error code, 358  
 ER\_TLS\_LIBRARY\_ERROR\_INTERNAL error code, 397  
 ER\_TMPDIR\_PATH\_TOO\_LONG error code, 362  
 ER\_TMP\_SESSION\_FOR\_VAR error code, 385  
 ER\_TOO\_BIG\_BIG\_DISPLAYWIDTH error code, 29  
 ER\_TOO\_BIG\_ENUM error code, 72  
 ER\_TOO\_BIG\_FIELDLENGTH error code, 8  
 ER\_TOO\_BIG\_FOR\_UNCOMPRESS error code, 19  
 ER\_TOO\_BIG\_PRECISION error code, 28  
 ER\_TOO\_BIG\_ROW\_SIZE error code, 10  
 ER\_TOO\_BIG\_SCALE error code, 28  
 ER\_TOO\_BIG\_SELECT error code, 10  
 ER\_TOO\_BIG\_SET error code, 9  
 ER\_TOO\_HIGH\_LEVEL\_OF\_NESTING\_FOR\_SELECT error code, 31  
 ER\_TOO\_LONG\_BODY error code, 29  
 ER\_TOO\_LONG\_FIELD\_COMMENT error code, 39  
 ER\_TOO\_LONG\_IDENT error code, 7  
 ER\_TOO\_LONG\_INDEX\_COMMENT error code, 43  
 ER\_TOO\_LONG\_KEY error code, 7  
 ER\_TOO\_LONG\_ROUTINE\_COMMENT error code, 73

---

---

ER\_TOO\_LONG\_SET\_ENUM\_VALUE error code, 72  
 ER\_TOO\_LONG\_STRING error code, 13  
 ER\_TOO\_LONG\_TABLESPACE\_COMMENT error code, 79  
 ER\_TOO\_LONG\_TABLE\_COMMENT error code, 39  
 ER\_TOO\_LONG\_TABLE\_PARTITION\_COMMENT error code, 50  
 ER\_TOO\_MANY\_CONCURRENT\_TRXS error code, 40  
 ER\_TOO\_MANY\_FIELDS error code, 10  
 ER\_TOO\_MANY\_GROUP\_BY\_MODIFIER\_BRANCHES error code, 124  
 ER\_TOO\_MANY\_KEYS error code, 7  
 ER\_TOO\_MANY\_KEY\_PARTS error code, 7  
 ER\_TOO\_MANY\_PARTITIONS\_ERROR error code, 33  
 ER\_TOO\_MANY\_PARTITION\_FUNC\_FIELDS\_ERROR error code, 41  
 ER\_TOO\_MANY\_ROWS error code, 14  
 ER\_TOO\_MANY\_STORAGE\_ENGINES error code, 144  
 ER\_TOO\_MANY\_TABLES error code, 10  
 ER\_TOO\_MANY\_USER\_CONNECTIONS error code, 15  
 ER\_TOO\_MANY\_VALUES\_ERROR error code, 41  
 ER\_TOO\_MANY\_WINDOWS error code, 115  
 ER\_TP\_QUERY\_THRS\_PER\_GRP\_EXCEEDS\_TXN\_THRESHOLD error code, 118  
 ER\_TRACK\_VARIABLES\_BOGUS error code, 138  
 ER\_TRANSACTION\_ROLLBACK\_DURING\_COMMIT error code, 64  
 ER\_TRANSFORM\_SOURCE\_SRS\_MISSING\_TOWGS84 error code, 89  
 ER\_TRANSFORM\_SOURCE\_SRS\_NOT\_SUPPORTED error code, 88  
 ER\_TRANSFORM\_TARGET\_SRS\_MISSING\_TOWGS84 error code, 89  
 ER\_TRANSFORM\_TARGET\_SRS\_NOT\_SUPPORTED error code, 89  
 ER\_TRANSPORTS\_WHAT\_TRANSPORTS error code, 137  
 ER\_TRANS\_CACHE\_FULL error code, 15  
 ER\_TREE\_CORRUPT\_2\_CONSECUTIVE\_REDS error code, 167  
 ER\_TREE\_CORRUPT\_INCORRECT\_BLACK\_COUNT error code, 168  
 ER\_TREE\_CORRUPT\_PARENT\_SHOULD\_POINT\_AT\_PARENT error code, 167  
 ER\_TREE\_CORRUPT\_RIGHT\_IS\_LEFT error code, 168  
 ER\_TREE\_CORRUPT\_ROOT\_SHOULD\_BE\_BLACK error code, 167  
 ER\_TRG\_ALREADY\_EXISTS error code, 25  
 ER\_TRG\_CANT\_CHANGE\_ROW error code, 25  
 ER\_TRG\_CANT\_OPEN\_TABLE error code, 38  
 ER\_TRG\_CANT\_PARSE error code, 141  
 ER\_TRG\_CORRUPTED\_FILE error code, 38  
 ER\_TRG\_CREATION\_CTX\_NOT\_SET error code, 181  
 ER\_TRG\_DOES\_NOT\_EXIST error code, 25  
 ER\_TRG\_INVALID\_CREATION\_CTX error code, 38  
 ER\_TRG\_IN\_WRONG\_SCHEMA error code, 29  
 ER\_TRG\_NO\_CLIENT\_CHARSET error code, 132  
 ER\_TRG\_NO\_CREATION\_CTX error code, 38  
 ER\_TRG\_NO\_DEFINER error code, 30  
 ER\_TRG\_NO\_SUCH\_ROW\_IN\_TRG error code, 25  
 ER\_TRG\_ON\_VIEW\_OR\_TEMP\_TABLE error code, 25  
 ER\_TRG\_WITHOUT\_DEFINER error code, 132  
 ER\_TRG\_WRONG\_ORDER error code, 339  
 ER\_TRHEAD\_POOL\_LOW\_LEVEL\_INIT\_FAILED error code, 195  
 ER\_TRIGGER\_INVALID\_VALUE error code, 128  
 ER\_TRUNCATED\_WRONG\_VALUE error code, 21  
 ER\_TRUNCATED\_WRONG\_VALUE\_FOR\_FIELD error code, 25  
 ER\_TRUNCATE\_ILLEGAL\_FK error code, 44  
 ER\_TRX\_GTID\_COLLECT\_REJECT error code, 144  
 ER\_TRX\_WRITE\_SET\_OOM error code, 144  
 ER\_TURNING\_LOGGING\_OFF\_FOR\_THE\_DURATION error code, 178  
 ER\_TURNING\_ON\_PARTIAL\_REVOKES error code, 341  
 ER\_TZ\_CANT\_BUILD\_MKTIME\_MAP error code, 154  
 ER\_TZ\_CANT\_FIND\_DESCRIPTION\_FOR\_TIME\_ZONE error code, 153  
 ER\_TZ\_CANT\_FIND\_DESCRIPTION\_FOR\_TIME\_ZONE\_ID error code, 153  
 ER\_TZ\_CANT\_OPEN\_AND\_LOCK\_TIME\_ZONE\_TABLE error code, 152  
 ER\_TZ\_ERROR\_LOADING\_LEAP\_SECOND\_TABLE error code, 153  
 ER\_TZ\_NO\_TRANSITION\_TYPES\_IN\_TIME\_ZONE error code, 153  
 ER\_TZ\_OOM\_INITIALIZING\_TIME\_ZONES error code, 152  
 ER\_TZ\_OOM\_LOADING\_LEAP\_SECOND\_TABLE error code, 152  
 ER\_TZ\_OOM\_LOADING\_TIME\_ZONE\_DESCRIPTION error code, 153  
 ER\_TZ\_OOM\_WHILE\_LOADING\_TIME\_ZONE error code, 154  
 ER\_TZ\_OOM\_WHILE\_SETTING\_TIME\_ZONE error code, 154  
 ER\_TZ\_TOO\_MANY\_LEAPS\_IN\_LEAP\_SECOND\_TABLE error code, 152  
 ER\_TZ\_TRANSITION\_TABLE\_BAD\_TRANSITION\_TYPE error code, 153  
 ER\_TZ\_TRANSITION\_TABLE\_LOAD\_ERROR error code, 153  
 ER\_TZ\_TRANSITION\_TABLE\_TOO\_MANY\_TRANSITIONS error code, 153  
 ER\_TZ\_TRANSITION\_TYPE\_TABLE\_ABBREVIATIONS\_EXCEED error code, 153  
 ER\_TZ\_TRANSITION\_TYPE\_TABLE\_LOAD\_ERROR error code, 153

---

---

ER\_TZ\_TRANSITION\_TYPE\_TABLE\_TYPE\_TOO\_LARGE error code, 153  
 ER\_TZ\_UNKNOWN\_OR\_ILLEGAL\_DEFAULT\_TIME\_ZONE error code, 153  
 ER\_UDF\_ALREADY\_EXISTS error code, 328  
 ER\_UDF\_CANT\_ALLOC\_FOR\_FUNCTION error code, 143  
 ER\_UDF\_CANT\_ALLOC\_FOR\_STRUCTURES error code, 143  
 ER\_UDF\_CANT\_OPEN\_FUNCTION\_TABLE error code, 143  
 ER\_UDF\_DEREGISTRATION error code, 393  
 ER\_UDF\_DROP\_DYNAMICALLY\_REGISTERED error code, 80  
 ER\_UDF\_ERROR error code, 71  
 ER\_UDF\_EXEC\_FAILURE error code, 393  
 ER\_UDF\_EXEC\_FAILURE\_REASON error code, 393  
 ER\_UDF\_EXISTS error code, 11  
 ER\_UDF\_INVALID\_ROW\_IN\_FUNCTION\_TABLE error code, 143  
 ER\_UDF\_NO\_PATHS error code, 11  
 ER\_UDF\_REGISTER\_ERROR error code, 362  
 ER\_UDF\_REGISTER\_SERVICE\_ERROR error code, 362  
 ER\_UDF\_REGISTRATION error code, 393  
 ER\_UDF\_UNREGISTER\_ERROR error code, 362  
 ER\_UNKNOWN\_AUTH\_ID\_OR\_ACCESS\_DENIED\_FOR\_GRANT error code, 96  
 ER\_UNABLE\_TO\_BUILD\_HISTOGRAM error code, 81  
 ER\_UNABLE\_TO\_COLLECT\_LOG\_STATUS error code, 87  
 ER\_UNABLE\_TO\_DROP\_COLUMN\_STATISTICS error code, 81  
 ER\_UNABLE\_TO\_RESOLVE\_HOSTNAME error code, 132  
 ER\_UNABLE\_TO\_RESOLVE\_IP error code, 132  
 ER\_UNABLE\_TO\_SET\_OPTION error code, 87  
 ER\_UNABLE\_TO\_STORE\_COLUMN\_STATISTICS error code, 81  
 ER\_UNABLE\_TO\_STORE\_STATISTICS error code, 76  
 ER\_UNABLE\_TO\_UPDATE\_COLUMN\_STATISTICS error code, 81  
 ER\_UNDISCLOSED\_PARSE\_ERROR\_IN\_DIGEST\_FN error code, 84  
 ER\_UNDO\_RECORD\_TOO\_BIG error code, 45  
 ER\_UNEXPECTED\_GEOMETRY\_TYPE error code, 73  
 ER\_UNIQUE\_KEY\_NEED\_ALL\_FIELDS\_IN\_PF error code, 33  
 ER\_UNIT\_NOT\_FOUND error code, 100  
 ER\_UNKNOWN\_ALTER\_ALGORITHM error code, 51  
 ER\_UNKNOWN\_ALTER\_LOCK error code, 51  
 ER\_UNKNOWN\_AUTHID error code, 74  
 ER\_UNKNOWN\_AUTH\_ID\_IN\_MANDATORY\_ROLE error code, 184  
 ER\_UNKNOWN\_CHARACTER\_SET error code, 10  
 ER\_UNKNOWN\_COLLATION error code, 20  
 ER\_UNKNOWN\_COM\_ERROR error code, 6  
 ER\_UNKNOWN\_ERROR error code, 10  
 ER\_UNKNOWN\_ERROR\_DETECTED\_IN\_SESSION error code, 188  
 ER\_UNKNOWN\_ERROR\_NUMBER error code, 143  
 ER\_UNKNOWN\_EXPLAIN\_FORMAT error code, 50  
 ER\_UNKNOWN\_KEY\_CACHE error code, 20  
 ER\_UNKNOWN\_LOCALE error code, 41  
 ER\_UNKNOWN\_NETWORK\_NAMESPACE error code, 344  
 ER\_UNKNOWN\_PARTITION error code, 47  
 ER\_UNKNOWN\_PROCEDURE error code, 10  
 ER\_UNKNOWN\_STMT\_HANDLER error code, 18  
 ER\_UNKNOWN\_STORAGE\_ENGINE error code, 21  
 ER\_UNKNOWN\_SYSTEM\_VARIABLE error code, 15  
 ER\_UNKNOWN\_TABLE error code, 10  
 ER\_UNKNOWN\_TABLESPACE\_TYPE error code, 332  
 ER\_UNKNOWN\_TABLE\_IN\_UPGRADE error code, 348  
 ER\_UNKNOWN\_TARGET\_BINLOG error code, 26  
 ER\_UNKNOWN\_TIME\_ZONE error code, 21  
 ER\_UNKNOWN\_UNSUPPORTED\_STORAGE\_ENGINE error code, 133  
 ER\_UNKNOWN\_VARIABLE\_IN\_PERSISTED\_CONFIG\_FILE error code, 329  
 ER\_UNRESOLVED\_HINT\_NAME error code, 66  
 ER\_UNRESOLVED\_TABLE\_LOCK error code, 77  
 ER\_UNSUPPORTED\_LOG\_ENGINE error code, 37  
 ER\_UNSUPPORTED\_ACTION\_ON\_DEFAULT\_VALUE\_GENERATION error code, 91  
 ER\_UNSUPPORTED\_ACTION\_ON\_GENERATED\_COLUMN error code, 65  
 ER\_UNSUPPORTED\_ALTER\_ENCRYPTION\_INPLACE error code, 71  
 ER\_UNSUPPORTED\_ALTER\_INPLACE\_ON\_VIRTUAL\_COLUMN error code, 64  
 ER\_UNSUPPORTED\_ALTER\_ONLINE\_ON\_VIRTUAL\_COLUMN error code, 70  
 ER\_UNSUPPORTED\_DATE error code, 136  
 ER\_UNSUPPORTED\_ENGINE error code, 46  
 ER\_UNSUPPORTED\_EXTENSION error code, 10  
 ER\_UNSUPPORTED\_INDEX\_ALGORITHM error code, 72  
 ER\_UNSUPPORTED\_PS error code, 21  
 ER\_UNSUPPORTED\_SQL\_MODE error code, 100  
 ER\_UNSUPPORTED\_USE\_OF\_GRANT\_AS error code, 96  
 ER\_UNSUPPORTED\_COMPRESSED\_TEMPORARY\_TABLE error code, 72  
 ER\_UNTIL\_COND\_IGNORED error code, 20  
 ER\_UPDATE\_GTID\_PURGED\_WITH\_GRANT error code, 101  
 ER\_UPDATE\_INFO error code, 12  
 ER\_UPDATE\_LOG\_DEPRECATED\_IGNORED error code, 22  
 ER\_UPDATE\_LOG\_DEPRECATED\_TRANSLATED error code, 22  
 ER\_UPDATE\_TABLE\_USED error code, 9

---

---

ER\_UPDATE\_WITHOUT\_KEY\_IN\_SAFE\_MODE error code, 14  
 ER\_UPDATING\_DD\_TABLE error code, 73  
 ER\_UPGRADE\_NONEXISTENT\_SCHEMA error code, 363  
 ER\_UPGRADE\_PARSE\_ERROR error code, 332  
 ER\_USAGE\_DEPRECATION\_COUNTER error code, 396  
 ER\_USERNAME error code, 31  
 ER\_USERNAME\_TRUNCATED error code, 358  
 ER\_USER\_ACCESS\_DENIED\_FOR\_USER\_ACCOUNT error code, 104  
 ER\_USER\_ALREADY\_EXISTS error code, 69  
 ER\_USER\_COLUMN\_OLD\_LENGTH error code, 71  
 ER\_USER\_DOES\_NOT\_EXIST error code, 69  
 ER\_USER\_LIMIT\_REACHED error code, 17  
 ER\_USER\_LOCK\_DEADLOCK error code, 61  
 ER\_USER\_LOCK\_OVERLONG\_NAME error code, 121  
 ER\_USER\_LOCK\_WRONG\_NAME error code, 61  
 ER\_USER\_NOT\_IN\_EXTRA\_USERS\_BINLOG\_POSSIBLE error code, 150  
 ER\_USER\_REFERENCED\_AS\_DEFINER error code, 108  
 ER\_USER\_REGISTRATION\_FAILED error code, 113  
 ER\_USER\_REQUIRES\_ROOT error code, 136  
 ER\_USER\_WHAT\_USER error code, 137  
 ER\_USING\_ASSIGN\_GTIDS\_TO\_ANONYMOUS\_TRANSACTIONS error code, 110  
 ER\_UUID\_INVALID error code, 133  
 ER\_UUID\_IS error code, 133  
 ER\_UUID\_SALT error code, 133  
 ER\_UUID\_SCRUB error code, 133  
 ER\_VALGRIND\_COUNT\_LEAKS error code, 143  
 ER\_VALGRIND\_DO\_QUICK\_LEAK\_CHECK error code, 143  
 ER\_VALIDATE\_PASSWORD\_INSUFFICIENT\_CHANGED error code, 121  
 ER\_VALIDATE\_PWD\_CONVERT\_TO\_BUFFER\_FAILED error code, 247  
 ER\_VALIDATE\_PWD\_COULD\_BE\_NULL error code, 247  
 ER\_VALIDATE\_PWD\_DICT\_FILE\_NOT\_LOADED error code, 204  
 ER\_VALIDATE\_PWD\_DICT\_FILE\_NOT\_SPECIFIED error code, 204  
 ER\_VALIDATE\_PWD\_DICT\_FILE\_OPEN\_FAILED error code, 247  
 ER\_VALIDATE\_PWD\_DICT\_FILE\_TOO\_BIG error code, 204  
 ER\_VALIDATE\_PWD\_FAILED\_TO\_GET\_FLD\_FROM\_SECURITY\_CTX error code, 204  
 ER\_VALIDATE\_PWD\_FAILED\_TO\_GET\_SECURITY\_CTX error code, 204  
 ER\_VALIDATE\_PWD\_FAILED\_TO\_READ\_DICT\_FILE error code, 204  
 ER\_VALIDATE\_PWD\_LENGTH\_CHANGED error code, 204  
 ER\_VALIDATE\_PWD\_STATUS\_VAR\_REGISTRATION\_FAILED error code, 246  
 ER\_VALIDATE\_PWD\_STATUS\_VAR\_UNREGISTRATION\_FAILED error code, 247  
 ER\_VALIDATE\_PWD\_STRING\_CONV\_TO\_BUFFER\_FAILED error code, 247  
 ER\_VALIDATE\_PWD\_STRING\_CONV\_TO\_LOWERCASE\_FAILED error code, 247  
 ER\_VALIDATE\_PWD\_STRING\_HANDLER\_MEM\_ALLOCATION\_FAILED error code, 247  
 ER\_VALIDATE\_PWD\_WRONG\_POLICY\_DICT\_FILE\_UNSPECIFIED error code, 247  
 ER\_VALIDATE\_PWD\_VARIABLE\_REGISTRATION\_FAILED error code, 247  
 ER\_VALIDATE\_PWD\_VARIABLE\_UNREGISTRATION\_FAILED error code, 247  
 ER\_VALUES\_IS\_NOT\_INT\_TYPE\_ERROR error code, 44  
 ER\_VALUE\_OUT\_OF\_RANGE error code, 114  
 ER\_VARIABLE\_IS\_NOT\_STRUCT error code, 20  
 ER\_VARIABLE\_NOT\_PERSISTED error code, 75  
 ER\_VARIABLE\_NOT\_SETTABLE\_IN\_SF\_OR\_TRIGGER error code, 49  
 ER\_VARIABLE\_NOT\_SETTABLE\_IN\_SP error code, 53  
 ER\_VARIABLE\_NOT\_SETTABLE\_IN\_TRANSACTION error code, 49  
 ER\_VARIABLES\_AS\_LOCAL\_OR\_UUID error code, 49  
 ER\_VAR\_CANT\_BE\_READ error code, 18  
 ER\_VAR\_DOES\_NOT\_EXIST error code, 80  
 ER\_VERBOSE\_HINT error code, 138  
 ER\_VERBOSE\_REQUIRES\_HELP error code, 134  
 ER\_VIEW\_CHECKSUM error code, 26  
 ER\_VIEW\_CHECK\_FAILED error code, 25  
 ER\_VIEW\_CREATION\_CTX\_NOT\_SET error code, 181  
 ER\_VIEW\_CREATE\_MERGE\_VIEW error code, 27  
 ER\_VIEW\_FRM\_NO\_USER error code, 30  
 ER\_VIEW\_INVALID error code, 25  
 ER\_VIEW\_INVALID\_CREATION\_CTX error code, 38  
 ER\_VIEW\_MULTIUPDATE error code, 26  
 ER\_VIEW\_NONUPD\_CHECK error code, 25  
 ER\_VIEW\_NO\_CREATION\_CTX error code, 38  
 ER\_VIEW\_NO\_EXPLAIN error code, 24  
 ER\_VIEW\_NO\_INSERT\_FIELD\_LIST error code, 26  
 ER\_VIEW\_OTHER\_USER error code, 30  
 ER\_VIEW\_PREVENT\_UPDATE error code, 29  
 ER\_VIEW\_RECURSIVE error code, 31  
 ER\_VIEW\_SELECT\_CLAUSE error code, 24  
 ER\_VIEW\_SELECT\_TMPTABLE error code, 24  
 ER\_VIEW\_SELECT\_VARIABLE error code, 24  
 ER\_VIEW\_UNKNOWN\_CHARSET\_OR\_COLLATION error code, 129  
 ER\_VIEW\_UNPARSABLE error code, 152  
 ER\_VIEW\_WRONG\_LIST error code, 25  
 ER\_VTOKEN\_PLUGIN\_TOKEN\_MISMATCH error code, 67



ER_VTOKEN_PLUGIN_TOKEN_NOT_FOUND error code, 67	ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFEST error code, 391
ER_WAITPID_FAILED error code, 192	ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFEST error code, 366
ER_WARNING_AUTHCACHE_INVALID_USER_ATTRIBUTES error code, 336	ER_WARN_COMPONENT_KEYRING_OCI_DUPLICATE_KEY error code, 386
ER_WARNING_DISCARD_OLD_PASSWORD_CLAUSE error code, 336	ER_WARN_CONFLICTING_HINT error code, 66
ER_WARNING_NOT_COMPLETE_ROLLBACK error code, 15	ER_WARN_C_DISABLE_GTID_ONLY_WITH_SOURCE_AUTO error code, 114
ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_CREATE_TEMP_TABLE error code, 19	ER_WARN_DATA_OUT_OF_RANGE_FUNCTIONAL_INDEX error code, 189
ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_DROP_TEMP_TABLE error code, 48	ER_WARN_DATA_TRUNCATED_FUNCTIONAL_INDEX error code, 89
ER_WARNING_PASSWORD_HISTORY_CLAUSES_VIOLATED error code, 82	ER_WARN_DA_PRIVILEGE_NOT_REGISTERED error code, 102
ER_WARNING_RETAIN_CURRENT_PASSWORD_CLAUSE error code, 336	ER_WARN_DEPRECATED_CHARSET_OPTION error code, 377
ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS error code, 112	ER_WARN_DEPRECATED_CLIENT_NO_SCHEMA_OPTION error code, 618
ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS error code, 371	ER_WARN_DEPRECATED_COLLATION error code, 115
ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE error code, 112	ER_WARN_DEPRECATED_COLLATION_OPTION error code, 377
ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE error code, 371	ER_WARN_DEPRECATED_DATETIME_DELIMITER error code, 116
ER_WARN_ALLOWED_PACKET_OVERFLOWED error code, 21	ER_WARN_DEPRECATED_DYNAMIC_PRIV_FOR_USER error code, 398
ER_WARN_ASYNC_CONN_FAILOVER_NETWORK_NAME error code, 111	ER_WARN_DEPRECATED_DYNAMIC_PRIV_IN_GRANT error code, 122
ER_WARN_AUDIT_LOG_DISABLED error code, 377	ER_WARN_DEPRECATED_ENGINE_SYNTAX_NO_REPLACE error code, 124
ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP ONLY error code, 112	ER_WARN_DEPRECATED_FLOAT_AUTO_INCREMENT error code, 97
ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP ONLY error code, 372	ER_WARN_DEPRECATED_FLOAT_DIGITS error code, 97
ER_WARN_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_PRIVS error code, 351	ER_WARN_DEPRECATED_FLOAT_UNSIGNED error code, 98
ER_WARN_BAD_MAX_EXECUTION_TIME error code, 66	ER_WARN_DEPRECATED_FOUND_ROWS error code, 105
ER_WARN_BINLOG_PARTIAL_UPDATES_DISABLED error code, 82	ER_WARN_DEPRECATED_IDENT error code, 118
ER_WARN_BINLOG_PARTIAL_UPDATES_SUGGESTS_PARTITIONING error code, 82	ER_WARN_DEPRECATED_INNER_INTO error code, 100
ER_WARN_CANNOT_FREE_COMPONENT_DATA_DEADLOCK error code, 392	ER_WARN_DEPRECATED_INTEGER_DISPLAY_WIDTH error code, 98
ER_WARN_CANNOT_PERSIST_SENSITIVE_VARIABLE error code, 378	ER_WARN_DEPRECATED_JSON_TABLE_ON_ERROR_ON_FAILURE error code, 115
ER_WARN_CANNOT_SECURELY_PERSIST_SENSITIVE_VARIABLE error code, 116	ER_WARN_DEPRECATED_NESTED_COMMENT_SYNTAX error code, 91
ER_WARN_CANT_DROP_DEFAULT_KEYCACHE error code, 29	ER_WARN_DEPRECATED_OR_BLOCKED_CIPHER error code, 396
ER_WARN_CANT_OPEN_CERTIFICATE error code, 396	ER_WARN_DEPRECATED_SQLMODE error code, 63
ER_WARN_CA_CERT_VERIFY_FAILED error code, 396	ER_WARN_DEPRECATED_SQL_CALC_FOUND_ROWS error code, 105
ER_WARN_CERTIFICATE_ERROR_STRING error code, 397	ER_WARN_DEPRECATED_SUPERFLUOUS_DELIMITER error code, 116
ER_WARN_CLIENT_DEPRECATED_PARTITION_PREFIX_ERROR error code, 106	ER_WARN_DEPRECATED_SYNTAX error code, 21

---

ER\_WARN\_DEPRECATED\_SYNTAX\_NO\_REPLACEMENT error code, 43  
 ER\_WARN\_DEPRECATED\_SYNTAX\_WITH\_VER error code, 36  
 ER\_WARN\_DEPRECATED\_SYSVAR\_UPDATE error code, 63  
 ER\_WARN\_DEPRECATED\_USER\_DEFINED\_COLLATION error code, 121  
 ER\_WARN\_DEPRECATED\_USER\_DEFINED\_COLLATION\_OPTIONS error code, 391  
 ER\_WARN\_DEPRECATED\_USER\_SET\_EXPR error code, 91  
 ER\_WARN\_DEPRECATED\_UTF8MB3\_CHARSET\_OPTION error code, 333  
 ER\_WARN\_DEPRECATED\_UTF8MB3\_COLLATION error code, 91  
 ER\_WARN\_DEPRECATED\_UTF8MB3\_COLLATION\_OPTIONS error code, 333  
 ER\_WARN\_DEPRECATED\_UTF8\_ALIAS\_OPTION error code, 332  
 ER\_WARN\_DEPRECATED\_VALUES\_FUNCTION\_ALLOWED error code, 105  
 ER\_WARN\_DEPRECATED\_WITH\_NOTE error code, 121  
 ER\_WARN\_DEPRECATED\_YEAR\_UNSIGNED error code, 104  
 ER\_WARN\_DEPRECATED\_ZEROFILL error code, 98  
 ER\_WARN\_ENGINE\_TRANSACTION\_ROLLBACK error code, 39  
 ER\_WARN\_FAILED\_TO\_SETUP\_TLS error code, 396  
 ER\_WARN\_FIELD\_RESOLVED error code, 20  
 ER\_WARN\_FUNC\_INDEX\_NOT\_APPLICABLE error code, 101  
 ER\_WARN\_GRP\_RPL\_VIEW\_CHANGE\_UUID\_FAIL\_GENERATED error code, 371  
 ER\_WARN\_GTID\_THRESHOLD\_BREACH error code, 365  
 ER\_WARN\_HOSTNAME\_WONT\_WORK error code, 20  
 ER\_WARN\_HYPERGRAPH\_EXPERIMENTAL error code, 108  
 ER\_WARN\_INCORRECT\_PRIVILEGE\_FOR\_DB\_RESTRICTIONS error code, 342  
 ER\_WARN\_INDEX\_NOT\_APPLICABLE error code, 47  
 ER\_WARN\_INVALID\_DB\_RESTRICTIONS error code, 342  
 ER\_WARN\_INVALID\_HINT error code, 80  
 ER\_WARN\_INVALID\_TIMESTAMP error code, 21  
 ER\_WARN\_I\_S\_SKIPPED\_TABLE error code, 43  
 ER\_WARN\_LEGACY\_SYNTAX\_CONVERTED error code, 57  
 ER\_WARN\_LOG\_DEPRECATED\_PARTITION\_PREFIX\_LENGTH error code, 357  
 ER\_WARN\_LOG\_PRIVILEGE\_CHECKS\_USER\_CORRUPT error code, 350  
 ER\_WARN\_LOG\_PRIVILEGE\_CHECKS\_USER\_DOESNT\_EXIST error code, 350  
 ER\_WARN\_LOG\_PRIVILEGE\_CHECKS\_USER\_NEEDS\_RPL\_APPLICABLE error code, 350  
 ER\_WARN\_L\_DISABLE\_GTID\_ONLY\_WITH\_SOURCE\_AUTO\_POSITION error code, 375  
 ER\_WARN\_MIGRATION\_EMPTY\_SOURCE\_KEYRING error code, 377  
 ER\_WARN\_NO\_KEYRING\_COMPONENT\_SERVICE\_FOUND error code, 366  
 ER\_WARN\_NO\_SERVERID\_SPECIFIED error code, 181  
 ER\_WARN\_NO\_SPACE\_VERSION\_COMMENT error code, 121  
 ER\_WARN\_NULL\_TO\_NOTNULL error code, 19  
 ER\_WARN\_ONLY\_SOURCE\_LOG\_FILE\_NO\_POSITION error code, 59  
 ER\_WARN\_ON\_MODIFYING\_GTID\_EXECUTED\_TABLE error code, 66  
 ER\_WARN\_OPEN\_TEMP\_TABLES\_MUST\_BE\_ZERO error code, 58  
 ER\_WARN\_OPTIMIZER\_HINT\_SYNTAX\_ERROR error code, 66  
 ER\_WARN\_OPTION\_RESET\_AND\_IGNORED\_DURING\_INITIALIZATION error code, 398  
 ER\_WARN\_PARTIAL\_REVOKE\_AND\_DB\_GRANT error code, 341  
 ER\_WARN\_PROPERTY\_STRING\_PARSE\_FAILED error code, 338  
 ER\_WARN\_PURGE\_LOG\_IN\_USE error code, 55  
 ER\_WARN\_PURGE\_LOG\_IS\_ACTIVE error code, 55  
 ER\_WARN\_REGEXP\_USING\_DEFAULT error code, 114  
 ER\_WARN\_REMOVED\_SQL\_MODE error code, 333  
 ER\_WARN\_REPLICA\_ANONYMOUS\_TO\_GTID\_UUID\_SAME\_AS\_SOURCE error code, 370  
 ER\_WARN\_REPLICA\_GTID\_ONLY\_AND\_GTID\_MODE\_NOT\_ON error code, 375  
 ER\_WARN\_RESERVED\_SRID\_RANGE error code, 87  
 ER\_WARN\_RPL\_RECOVERY\_NO\_ROTATE\_EVENT\_FROM\_SOURCE error code, 351  
 ER\_WARN\_SCHEDULED\_TASK\_RUN\_FAILED error code, 394  
 ER\_WARN\_SCHEMA\_SN\_SF\_UDF\_NAME\_COLLISION error code, 115  
 ER\_WARN\_SQL\_AFTER\_MTS\_GAPS\_GAP\_NOT\_CALCULATED error code, 112  
 ER\_WARN\_SRS\_ID\_ALREADY\_EXISTS error code, 86  
 ER\_WARN\_SRS\_NOT\_FOUND error code, 73  
 ER\_WARN\_SRS\_NOT\_FOUND\_AXIS\_ORDER error code, 76  
 ER\_WARN\_TLS\_CHANNEL\_INITIALIZATION\_ERROR error code, 357  
 ER\_WARN\_TOO\_FEW\_RECORDS error code, 19  
 ER\_WARN\_TOO\_MANY\_RECORDS error code, 19  
 ER\_WARN\_TRG\_ALREADY\_EXISTS error code, 116  
 ER\_WARN\_TRIGGER\_DOESNT\_HAVE\_CREATED error code, 58

---

ER\_WARN\_UNKNOWN\_KEYRING\_AWS\_REGION error code, 350  
 ER\_WARN\_UNKNOWN\_QB\_NAME error code, 66  
 ER\_WARN\_UNLOAD\_THE\_NOT\_PERSISTED error code, 75  
 ER\_WARN\_UNSUPPORTED\_HINT error code, 73  
 ER\_WARN\_UNSUPPORTED\_MAX\_EXECUTION\_TIME error code, 66  
 ER\_WARN\_USING\_OTHER\_HANDLER error code, 19  
 ER\_WARN\_VAR\_VALUE\_CHANGE\_NOT\_SUPPORTED error code, 108  
 ER\_WARN\_VIEW\_MERGE error code, 25  
 ER\_WARN\_VIEW\_WITHOUT\_KEY error code, 25  
 ER\_WARN\_WRONG\_COMPRESSION\_ALGORITHM\_LOG error code, 349  
 ER\_WARN\_WRONG\_COMPRESSION\_LEVEL\_LOG error code, 349  
 ER\_WASTEFUL\_NET\_BUFFER\_SIZE error code, 134  
 ER\_WILDCARD\_NOT\_ALLOWED\_FOR\_MULTIADDRESS error code, 344  
 ER\_WINDOW\_CIRCULARITY\_IN\_WINDOW\_GRAPH error code, 78  
 ER\_WINDOW\_DUPLICATE\_NAME error code, 78  
 ER\_WINDOW\_EXPLAIN\_JSON error code, 79  
 ER\_WINDOW\_FRAME\_END\_ILLEGAL error code, 78  
 ER\_WINDOW\_FRAME\_ILLEGAL error code, 78  
 ER\_WINDOW\_FRAME\_START\_ILLEGAL error code, 78  
 ER\_WINDOW\_FUNCTION\_IGNORES\_FRAME error code, 79  
 ER\_WINDOW\_ILLEGAL\_ORDER\_BY error code, 78  
 ER\_WINDOW\_INVALID\_WINDOW\_FUNC\_ALIAS\_USE error code, 79  
 ER\_WINDOW\_INVALID\_WINDOW\_FUNC\_USE error code, 78  
 ER\_WINDOW\_NESTED\_WINDOW\_FUNC\_USE\_IN\_WINDOW error code, 79  
 ER\_WINDOW\_NO\_CHILD\_PARTITIONING error code, 78  
 ER\_WINDOW\_NO\_GROUP\_ORDER\_UNUSED error code, 79  
 ER\_WINDOW\_NO\_INHERIT\_FRAME error code, 78  
 ER\_WINDOW\_NO\_REDEFINE\_ORDER\_BY error code, 78  
 ER\_WINDOW\_NO\_SUCH\_WINDOW error code, 78  
 ER\_WINDOW\_RANGE\_BOUND\_NOT\_CONSTANT error code, 78  
 ER\_WINDOW\_RANGE\_FRAME\_NUMERIC\_TYPE error code, 78  
 ER\_WINDOW\_RANGE\_FRAME\_ORDER\_TYPE error code, 78  
 ER\_WINDOW\_RANGE\_FRAME\_TEMPORAL\_TYPE error code, 78  
 ER\_WINDOW\_ROWS\_INTERVAL\_USE error code, 79  
 ER\_WIN\_LISTEN\_BUT\_HOW error code, 137  
 ER\_WIN\_LOAD\_LIBRARY\_FAILED error code, 191  
 ER\_WL9236\_NOW\_UNUSED error code, 79  
 ER\_WRITABLE\_CONFIG\_REMOVED error code, 135  
 ER\_WRITE\_ROW\_TO\_PARTITION\_FAILED error code, 185  
 ER\_WRITE\_SET\_EXCEEDS\_LIMIT error code, 72  
 ER\_WRONG\_ARGUMENTS error code, 16  
 ER\_WRONG\_AUTO\_KEY error code, 8  
 ER\_WRONG\_COLUMN\_NAME error code, 13  
 ER\_WRONG\_COMPRESSION\_ALGORITHM\_CLIENT error code, 102  
 ER\_WRONG\_COMPRESSION\_LEVEL\_CLIENT error code, 102  
 ER\_WRONG\_COUNT\_FOR\_KEY error code, 168  
 ER\_WRONG\_COUNT\_FOR\_ORIGIN error code, 168  
 ER\_WRONG\_COUNT\_OF\_ELEMENTS error code, 68  
 ER\_WRONG\_DATETIME\_SPEC error code, 136  
 ER\_WRONG\_DB\_NAME error code, 9  
 ER\_WRONG\_EXPR\_IN\_PARTITION\_FUNC\_ERROR error code, 32  
 ER\_WRONG\_FIELD\_SPEC error code, 7  
 ER\_WRONG\_FIELD\_TERMINATORS error code, 8  
 ER\_WRONG\_FIELD\_WITH\_GROUP error code, 6  
 ER\_WRONG\_FIELD\_WITH\_GROUP\_V2 error code, 63  
 ER\_WRONG\_FILE\_NAME error code, 66  
 ER\_WRONG\_FK\_DEF error code, 18  
 ER\_WRONG\_FK\_OPTION\_FOR\_GENERATED\_COLUMN error code, 64  
 ER\_WRONG\_GROUP\_FIELD error code, 7  
 ER\_WRONG\_JSON\_TABLE\_VALUE error code, 83  
 ER\_WRONG\_KEY\_COLUMN error code, 13  
 ER\_WRONG\_KEY\_COLUMN\_FUNCTIONAL\_INDEX error code, 90  
 ER\_WRONG\_LOCK\_OF\_SYSTEM\_TABLE error code, 29  
 ER\_WRONG\_MRG\_TABLE error code, 14  
 ER\_WRONG\_MVI\_VALUE error code, 101  
 ER\_WRONG\_NAME\_FOR\_CATALOG error code, 20  
 ER\_WRONG\_NAME\_FOR\_INDEX error code, 20  
 ER\_WRONG\_NATIVE\_TABLE\_STRUCTURE error code, 43  
 ER\_WRONG\_NUMBER\_OF\_COLUMNS\_IN\_SELECT error code, 17  
 ER\_WRONG\_OBJECT error code, 24  
 ER\_WRONG\_OUTER\_JOIN\_UNUSED error code, 11  
 ER\_WRONG\_PARAMCOUNT\_TO\_NATIVE\_FCT error code, 37  
 ER\_WRONG\_PARAMCOUNT\_TO\_PROCEDURE error code, 10  
 ER\_WRONG\_PARAMETERS\_TO\_NATIVE\_FCT error code, 37  
 ER\_WRONG\_PARAMETERS\_TO\_PROCEDURE error code, 10  
 ER\_WRONG\_PARAMETERS\_TO\_STORED\_FCT error code, 37  
 ER\_WRONG\_PARTITION\_NAME error code, 36  
 ER\_WRONG\_PERFSHEMA\_USAGE error code, 43  
 ER\_WRONG\_SIZE\_NUMBER error code, 35  
 ER\_WRONG\_SRID\_FOR\_COLUMN error code, 82

---

---

ER\_WRONG\_STRING\_LENGTH error code, 31  
 ER\_WRONG\_SUB\_KEY error code, 8  
 ER\_WRONG\_SUM\_SELECT error code, 7  
 ER\_WRONG\_TABLESPACE\_NAME error code, 66  
 ER\_WRONG\_TABLE\_NAME error code, 9  
 ER\_WRONG\_TYPE\_COLUMN\_VALUE\_ERROR error code, 41  
 ER\_WRONG\_TYPE\_FOR\_COLUMN\_PREFIX\_IDX\_FLD error code, 191  
 ER\_WRONG\_TYPE\_FOR\_VAR error code, 17  
 ER\_WRONG\_USAGE error code, 17  
 ER\_WRONG\_VALUE error code, 34  
 ER\_WRONG\_VALUE\_COUNT error code, 7  
 ER\_WRONG\_VALUE\_COUNT\_ON\_ROW error code, 12  
 ER\_WRONG\_VALUE\_FOR\_TYPE error code, 28  
 ER\_WRONG\_VALUE\_FOR\_VAR error code, 17  
 ER\_WRONG\_VALUE\_FOR\_VAR\_PLUS\_ACTIONABLE\_PART error code, 106  
 ER\_X509\_CANT\_CHMOD\_KEY error code, 148  
 ER\_X509\_CANT\_CREATE\_CERT error code, 148  
 ER\_X509\_CANT\_READ\_CA\_CERT error code, 148  
 ER\_X509\_CANT\_READ\_CA\_KEY error code, 148  
 ER\_X509\_CANT\_WRITE\_CERT error code, 148  
 ER\_X509\_CANT\_WRITE\_KEY error code, 148  
 ER\_X509\_CIPHERS\_MISMATCH error code, 147  
 ER\_X509\_ISSUER\_MISMATCH error code, 147  
 ER\_X509\_NEEDS\_RSA\_PRIVKEY error code, 148  
 ER\_X509\_SUBJECT\_MISMATCH error code, 147  
 ER\_XAER\_DUPID error code, 29  
 ER\_XAER\_INVALID error code, 27  
 ER\_XAER\_NOTA error code, 27  
 ER\_XAER\_OUTSIDE error code, 27  
 ER\_XAER\_RMERR error code, 27  
 ER\_XAER\_RMFAIL error code, 27  
 ER\_XA\_CANT\_CREATE\_MDL\_BACKUP error code, 349  
 ER\_XA\_NO\_MULTI\_2PC\_HEURISTIC\_RECOVER error code, 143  
 ER\_XA\_RBDEADLOCK error code, 38  
 ER\_XA\_RBROLLBACK error code, 27  
 ER\_XA\_RBTIMEOUT error code, 38  
 ER\_XA\_RECOVERY\_DONE error code, 143  
 ER\_XA\_RECOVER\_EXPLANATION error code, 143  
 ER\_XA\_RECOVER\_FOUND\_TRX\_IN\_SE error code, 143  
 ER\_XA\_RECOVER\_FOUND\_XA\_TRX error code, 143  
 ER\_XA\_REPLICATION\_FILTERS error code, 100  
 ER\_XA\_RETRY error code, 71  
 ER\_XA\_STARTING\_RECOVERY error code, 143  
 ER\_XA\_TEMP\_TABLE error code, 116  
 ER\_XPLUGIN\_ALL\_IO\_INTERFACES\_DISABLED error code, 209  
 ER\_XPLUGIN\_BUFFER\_PAGE\_ALLOC\_FAILED error code, 207  
 ER\_XPLUGIN\_CLIENT\_KILL\_MSG error code, 210  
 ER\_XPLUGIN\_COMPRESSION\_ERROR error code, 350  
 ER\_XPLUGIN\_DETECTED\_HANGING\_CLIENTS error code, 208  
 ER\_XPLUGIN\_EMPTY\_ADMIN\_CMD error code, 210  
 ER\_XPLUGIN\_ERROR\_MSG error code, 205  
 ER\_XPLUGIN\_ERROR\_READING\_SOCKET error code, 209  
 ER\_XPLUGIN\_EXCEPTION\_IN\_EVENT\_LOOP error code, 208  
 ER\_XPLUGIN\_EXCEPTION\_IN\_TASK\_SCHEDULER error code, 208  
 ER\_XPLUGIN\_EXISTING\_USER\_ACCOUNT\_WITH\_INCOMPLETE error code, 210  
 ER\_XPLUGIN\_FAILED\_AT\_SSL\_CONF error code, 209  
 ER\_XPLUGIN\_FAILED\_TO\_ACCEPT\_CLIENT error code, 208  
 ER\_XPLUGIN\_FAILED\_TO\_BIND\_INTERFACE\_ADDRESS error code, 358  
 ER\_XPLUGIN\_FAILED\_TO\_CLOSE\_SQL\_SESSION error code, 210  
 ER\_XPLUGIN\_FAILED\_TO\_CREATE\_SESSION\_FOR\_CONN error code, 209  
 ER\_XPLUGIN\_FAILED\_TO\_EXECUTE\_ADMIN\_CMD error code, 210  
 ER\_XPLUGIN\_FAILED\_TO\_GET\_CREATION\_STMT error code, 210  
 ER\_XPLUGIN\_FAILED\_TO\_GET\_ENGINE\_INFO error code, 210  
 ER\_XPLUGIN\_FAILED\_TO\_GET\_SECURITY\_CTX error code, 210  
 ER\_XPLUGIN\_FAILED\_TO\_GET\_SYS\_VAR error code, 210  
 ER\_XPLUGIN\_FAILED\_TO\_INITIALIZE\_SESSION error code, 209  
 ER\_XPLUGIN\_FAILED\_TO\_OPEN\_INTERNAL\_SESSION error code, 210  
 ER\_XPLUGIN\_FAILED\_TO\_PREPARE\_IO\_INTERFACES error code, 208  
 ER\_XPLUGIN\_FAILED\_TO\_RESET\_IPV6\_V6ONLY\_FLAG error code, 211  
 ER\_XPLUGIN\_FAILED\_TO\_SCHEDULE\_CLIENT error code, 208  
 ER\_XPLUGIN\_FAILED\_TO\_SET\_MIN\_NUMBER\_OF\_WORKERS error code, 209  
 ER\_XPLUGIN\_FAILED\_TO\_SET\_SO\_REUSEADDR\_FLAG error code, 210  
 ER\_XPLUGIN\_FAILED\_TO\_STOP\_SERVICES error code, 324  
 ER\_XPLUGIN\_FAILED\_TO\_SWITCH\_CONTEXT error code, 210  
 ER\_XPLUGIN\_FAILED\_TO\_SWITCH\_SECURITY\_CTX error code, 332  
 ER\_XPLUGIN\_FAILED\_TO\_UNREGISTER\_UDF error code, 211  
 ER\_XPLUGIN\_FAILED\_TO\_USE\_SSL\_CONF error code, 205  
 ER\_XPLUGIN\_FAILED\_TO\_VALIDATE\_ADDRESS error code, 357

---

ER\_XPLUGIN\_FORCE\_STOP\_CLIENT error code, 207  
ER\_XPLUGIN\_IPv6\_AVAILABLE error code, 210  
ER\_XPLUGIN\_LISTENER\_SETUP\_FAILED error code, 208  
ER\_XPLUGIN\_LISTENER\_STATUS\_MSG error code, 209  
ER\_XPLUGIN\_LISTENER\_SYS\_VARIABLE\_ERROR error code, 209  
ER\_XPLUGIN\_MAX\_AUTH\_ATTEMPTS\_REACHED error code, 207  
ER\_XPLUGIN\_MESSAGE\_TOO\_LONG error code, 209  
ER\_XPLUGIN\_PEER\_DISCONNECTED\_WHILE\_READING\_MSG\_BODY error code, 209  
ER\_XPLUGIN\_READ\_FAILED\_CLOSING\_CONNECTION error code, 209  
ER\_XPLUGIN\_REFERENCE\_TO\_SECURE\_CONN\_WITH\_XPLUGIN error code, 205  
ER\_XPLUGIN\_REFERENCE\_TO\_USER\_ACCOUNT\_DOC\_SECTION error code, 208  
ER\_XPLUGIN\_RETRYING\_BIND\_ON\_PORT error code, 210  
ER\_XPLUGIN\_SRV\_SESSION\_INIT\_THREAD\_FAILED error code, 208  
ER\_XPLUGIN\_STARTUP\_FAILED error code, 204  
ER\_XPLUGIN\_TASK\_SCHEDULING\_FAILED error code, 208  
ER\_XPLUGIN\_UNABLE\_TO\_ACCEPT\_CONNECTION error code, 209  
ER\_XPLUGIN\_UNABLE\_TO\_USE\_USER\_SESSION\_ACCOUNT error code, 208  
ER\_XPLUGIN\_UNEXPECTED\_EXCEPTION\_DISPATCHING\_CMD error code, 208  
ER\_XPLUGIN\_UNINITIALIZED\_MESSAGE error code, 209  
ER\_XPLUGIN\_USING\_SSL\_CONF\_FROM\_MYSQLX error code, 204  
ER\_XPLUGIN\_USING\_SSL\_CONF\_FROM\_SERVER error code, 204  
ER\_XPLUGIN\_USING\_SSL\_FOR\_TLS\_CONNECTION error code, 205  
ER\_XPLUING\_NET\_STARTUP\_FAILED error code, 208  
ER\_YES error code, 3  
ER\_ZLIB\_Z\_BUF\_ERROR error code, 19  
ER\_ZLIB\_Z\_DATA\_ERROR error code, 19  
ER\_ZLIB\_Z\_MEM\_ERROR error code, 19

WARN\_NO\_CONNECTION\_METADATA error code, 39  
WARN\_ON\_BLOCKHOLE\_IN\_RBR error code, 56  
WARN\_OPTION\_BELOW\_LIMIT error code, 44  
WARN\_OPTION\_IGNORED error code, 39  
WARN\_PLUGIN\_BUSY error code, 39  
WARN\_UNENCRYPTED\_TABLE\_IN\_ENCRYPTED\_DB error code, 95  
WARN\_UNSUPPORTED\_ACL\_TABLES\_READ error code, 109  
WARN\_USELESS\_SPATIAL\_INDEX error code, 84

## W

WARN\_AES\_KEY\_SIZE error code, 72  
WARN\_COND\_ITEM\_TRUNCATED error code, 40  
WARN\_DATA\_TRUNCATED error code, 19  
WARN\_NAMED\_PIPE\_ACCESS\_EVERYONE error code, 57  
WARN\_NON\_ASCII\_SEPARATOR\_NOT\_IMPLEMENTED error code, 40

